

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant: Shenzhen Simolio Electronic Co., Ltd
Address of applicant: 7B/F, 3 Block, Qiyu Industrial Park, Gongle Tiezai Road,
Xixiang, Baoan District, Shenzhen, Guangdong, China

Manufacturer: Shenzhen Simolio Electronic Co., Ltd
Address of manufacturer: 7B/F, 3 Block, Qiyu Industrial Park, Gongle Tiezai Road,
Xixiang, Baoan District, Shenzhen, Guangdong, China

General Description of EUT:

Product Name: Wireless Speaker
Trade Name: SIMOLIO
Model No.: SM-621D
Adding Model(s): SM-621, SM-622D, SM-623D, SM-624D, SM-625D, SM-626D,
SM-627D, TS1, TS1D, TS2D, TS3D, TS4D, TS5D, TS6D, TS7D
Rated Voltage: Power in:DC9V
Receiver Battery:DC7.4V
Power Adapter MODEL:JS018SPS-090150U
INPUT:AC100-240V, 50/60Hz, 0.5A
OUTPUT:DC9V,1.5A
FCC ID: 2AYV2-SM-621D
Equipment Type: portable device

Technical Characteristics of EUT:

Frequency Range: 2406-2472MHz
RF Output Power: 10.220dBm (Conducted)
Modulation: GFSK
Quantity of Channels: 31
Channel Separation: 2MHz
Type of Antenna: PIFA Antenna
Antenna Gain: -2dBi

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalent power density

1.3 MPE Calculation Method

$$S = (30 * P * G) / (377 * R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,
the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

For 2.4G

Maximum Tune-Up output power: 11(dBm)

Maximum peak output power at antenna input terminal: 12.59(mW)

Prediction distance: >20(cm)

Prediction frequency: 2406(MHz)

Antenna gain: -2 (dBi)

Directional gain (numeric gain): 0.63

The worst case is power density at prediction frequency at 20cm: 0.0016w/cm²

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Result: Pass