ACCREDITED
TESTING LABORATORY
CERTIFICATE # 4821.01

BACL
Bay Area Compliance Labs Corp.

FCC PART 15.247
TEST REPORT

For

ANTEXIN TECHNOLOGY Co.,Ltd.

Fuxingda Industrial Park Factory Building, No. 2 Lanjing North Road, Zhukeng Community, Longtian Street, Pingshan District, Shenzhen, China

FCC ID: 2AYWM-AT-1S

Report Type:	**Product Type:**
Original Report	Vinyl record player

Report Number: RSZ210119810-00

Report Date: 2021-03-22

Reviewed By: Jacob Kong, RF Engineer

Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen)
5F(B-West) ,6F,7F,the 3rd Phase of Wan Li Industrial Building D,Shihua Rd, FuTian Free Trade Zone, Shenzhen, China
Tel: +86-755-33320018
Fax: +86-755-33320008
www.baclcorp.com.cn

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION **4**
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
OBJECTIVE 4
TEST METHODOLOGY 4
MEASUREMENT UNCERTAINTY 5
TEST FACILITY 5
SYSTEM TEST CONFIGURATION **6**
DESCRIPTION OF TEST CONFIGURATION 6
EUT EXERCISE SOFTWARE 6
SPECIAL ACCESSORIES 6
EQUIPMENT MODIFICATIONS 6
SUPPORT EQUIPMENT LIST AND DETAILS 6
EXTERNAL I/O CABLE 6
BLOCK DIAGRAM OF TEST SETUP 7
SUMMARY OF TEST RESULTS **8**
TEST EQUIPMENT LIST **9**
FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE) **11**
APPLICABLE STANDARD 11
RESULT 11
FCC §15.203 – ANTENNA REQUIREMENT **12**
APPLICABLE STANDARD 12
ANTENNA CONNECTOR CONSTRUCTION 12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS **13**
APPLICABLE STANDARD 13
EUT SETUP 13
EMI TEST RECEIVER SETUP 13
TEST PROCEDURE 13
CORRECTED FACTOR & MARGIN CALCULATION 14
TEST DATA 14
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS **17**
APPLICABLE STANDARD 17
EUT SETUP 17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP 18
TEST PROCEDURE 18
CORRECTED AMPLITUDE & MARGIN CALCULATION 18
TEST DATA 18
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST **25**
APPLICABLE STANDARD 25
TEST PROCEDURE 25
TEST DATA 25

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH 29
APPLICABLE STANDARD 29
TEST PROCEDURE 29
TEST DATA 29
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST 34
APPLICABLE STANDARD 34
TEST PROCEDURE 34
TEST DATA 34
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME) 36
APPLICABLE STANDARD 36
TEST PROCEDURE 36
TEST DATA 36
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT 44
APPLICABLE STANDARD 44
TEST PROCEDURE 44
TEST DATA 44
FCC §15.247(d) - BAND EDGES TESTING 48
APPLICABLE STANDARD 48
TEST PROCEDURE 48
TEST DATA 48

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Vinyl record player
Tested Model	AT-1S
Multiple Model	RP-1
Model Differences	Refer to the DoS letter
Frequency Range	Bluetooth: 2402~2480MHz
Transmit Power	Bluetooth: 6.65dBm
Modulation Technique	Bluetooth: GFSK, π/4-DQPSK
Antenna Specification*	PCB Antenna: 1dBi(It is provided by the manufacturer)
Voltage Range	DC 5.0V from adapter
Date of Test	2021-02-24 to 2021-03-22
Sample number	RSZ210119810-RF-S1(Assigned by BACL, Shenzhen)
Received date	2021-01-19
Sample/EUT Status	Good condition
Adapter information	Model: RS-050100001 Input: 100-240Vac 50/60Hz 0.2A Output: 5Vdc 1.0A

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

For Radiated Emissions testing, please refer to DA 00-705 Released March 30, 2000, Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.73dB
RF conducted test with spectrum		±1.6dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±1℃
Humidity		±6%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) ,6F,7F,the 3rd Phase of Wan Li Industrial Building D,Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

"FCC assist 1.0.1.2"* exercise software was used, and the power level is 10*. The software and power level was provided by the manufacturer.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Xingniu	Socket	504	504

External I/O Cable

Cable Description	Length (m)	From Port	To
Unshielded un-detachable AC cable	1.0	Socket	LISN
Unshielded detachable USB cable	0.8	EUT	Adapter

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §2.1091	Maximum Permissible Exposure(MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2020/08/04	2021/08/03
Rohde & Schwarz	LISN	ENV216	101613	2020/08/04	2021/08/03
Rohde & Schwarz	Transient Limitor	ESH3Z2	DE25985	2020/11/29	2021/11/28
Unknow	CE Cable	CE Cable	UF A210B-1-0720-504504	2020/11/29	2021/11/28
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Radiated Emission Test					
R&S	EMI Test Receiver	ESR3	102455	2020/08/04	2021/08/03
Sonoma instrument	Pre-amplifier	310 N	186238	2020/08/04	2021/08/03
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2020/12/22	2023/12/21
Unknow	Cable 2	RF Cable 2	F-03-EM197	2020/11/29	2021/11/28
Unknow	Cable	Chamber Cable 1	F-03-EM236	2020/11/29	2021/11/28
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2020/08/04	2021/08/03
COM-POWER	Pre-amplifier	PA-122	181919	2020/11/29	2021/11/28
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2020/11/29	2021/11/28
Sunol Sciences	Horn Antenna	3115	9107-3694	2021/01/15	2023/12/21
Insulted Wire Inc.	RF Cable	SPS-2503-3150	02222010	2020/11/29	2021/11/28
Unknow	RF Cable	W1101-EQ1 OUT	F-19-EM005	2020/11/29	2021/11/28
SNSD	Band Reject filter	BSF2402-2480MN-0898-001	2.4G filter	2020/04/20	2021/04/20
Ducommun Technolagies	Horn antenna	ARH-4223-02	1007726-02 1304	2020/12/06	2023/12/05

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200120	2020/04/03	2021/04/02
WEINSCHEL	3dB Attenuator	Unknown	F-03-EM121	2020/11/29	2021/11/28
WEINSCHEL	10dB Attenuator	5324	AU3842	2020/11/29	2021/11/28
WEINSCHEL	3dB Attenuator	Unknown	F-03-EM121	2020/11/29	2021/11/28
Unknown	RF Cable	Unknown	2301 276	2020/11/29	2021/11/28

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	**Electric Field Strength (V/m)**	**Magnetic Field Strength (A/m)**	**Power Density (mW/cm^2)**	**Averaging Time (Minutes)**
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*($180/f^2$)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz
* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm2)
P = power input to the antenna (in appropriate units, e.g., mW).
G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.
R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency (MHz)	Antenna Gain		Max Tune Up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm^2)	MPE Limit (mW/cm^2)
	(dBi)	(numeric)	(dBm)	(mW)			
2410-2469.5	1.0	1.26	7.0	5.0	20	0.0013	1.0

Note: To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: compliance.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 1 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	65 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2021-03-11.

EUT operation mode: Transmitting & charging (the worst case is π/4-DQPSK Mode, Middle channel)

AC 120V/60 Hz, Line



Final Result 1

Frequency (MHz)	QuasiPeak (dB µ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.391790	45.2	9.000	L1	19.9	12.8	58.0
0.399910	49.6	9.000	L1	19.9	8.3	57.9
0.612790	38.5	9.000	L1	19.8	17.5	56.0
4.286190	38.8	9.000	L1	19.9	17.2	56.0
6.801230	47.2	9.000	L1	19.9	12.8	60.0
6.847850	47.9	9.000	L1	19.9	12.1	60.0

Final Result 2

Frequency (MHz)	Average (dB µ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.391790	37.0	9.000	L1	19.9	11.0	48.0
0.399910	42.1	9.000	L1	19.9	5.8	47.9
0.612790	31.6	9.000	L1	19.8	14.4	46.0
4.286190	30.4	9.000	L1	19.9	15.6	46.0
6.801230	37.1	9.000	L1	19.9	12.9	50.0
6.847850	37.8	9.000	L1	19.9	12.2	50.0

AC 120V/60 Hz, Neutral



Final Result 1

Frequency (MHz)	QuasiPeak (dB µ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.368450	41.7	9.000	N	19.9	16.8	58.5
0.411850	50.0	9.000	N	19.8	7.6	57.6
3.994330	34.5	9.000	N	19.9	21.5	56.0
4.742690	38.8	9.000	N	19.9	17.2	56.0
6.742010	46.9	9.000	N	19.9	13.1	60.0
6.807310	47.6	9.000	N	19.9	12.4	60.0

Final Result 2

Frequency (MHz)	Average (dB µ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.370000	33.7	9.000	N	19.9	14.8	48.5
0.410000	40.9	9.000	N	19.8	6.7	47.6
0.494000	32.3	9.000	N	19.8	13.8	46.1
0.554000	33.6	9.000	N	19.8	12.4	46.0
6.650000	36.5	9.000	N	19.9	13.5	50.0
6.870000	38.1	9.000	N	19.9	11.9	50.0

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard

FCC §15.205; §15.209; §15.247(d)

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, according to the DA 00-705 Released March 30, 2000, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Average

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Data

Environmental Conditions

Temperature:	23~25.8 ℃
Relative Humidity:	51~54 %
ATM Pressure:	101.2 kPa

The testing was performed by Kilroy Deng on 2021-02-26 for below 1GHz and Alen He on 2021-03-06 for above 1GHz.

EUT operation mode: Transmitting (Scan with GFSK, π/4-DQPSK ode, the worst case isπ/4-DQPSK Mode)

30 MHz~1 GHz: *(the worst case is π/4-DQPSK Mode, Middle channel)*



Final_Result

Frequency (MHz)	QuasiPeak (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
59.614750	34.99	40.00	5.01	119.0	V	352.0	-10.5
60.945375	35.43	40.00	4.57	140.0	V	337.0	-10.5
135.470625	34.25	43.50	9.25	341.0	H	262.0	-4.5
145.692125	28.91	43.50	14.59	201.0	H	280.0	-5.1
384.001500	38.60	46.00	7.40	104.0	H	217.0	-1.8
576.010750	39.70	46.00	6.30	163.0	H	255.0	2.2

1 GHz - 25 GHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2402 MHz)									
2358.91	28.73	PK	74	1.1	H	31.77	60.50	74	13.50
2358.91	13.51	Ave.	74	1.1	H	31.77	45.28	54	8.72
2494.28	28.09	PK	231	1.2	H	32.13	60.22	74	13.78
2494.28	13.79	Ave.	231	1.2	H	32.13	45.92	54	8.08
4804.00	45.16	PK	302	2.3	H	6.28	51.44	74	22.56
4804.00	32.19	Ave.	302	2.3	H	6.28	38.47	54	15.53
7206.00	48.60	PK	67	1.3	H	11.93	60.53	74	13.47
7206.00	34.25	Ave.	67	1.3	H	11.93	46.18	54	7.82
Middle Channel (2441 MHz)									
4882.00	44.67	PK	350	1.2	H	6.76	51.43	74	22.57
4882.00	31.87	Ave.	350	1.2	H	6.76	38.63	54	15.37
7323.00	50.14	PK	344	1.4	H	11.66	61.80	74	12.20
7323.00	34.96	Ave.	344	1.4	H	11.66	46.62	54	7.38
High Channel (2480 MHz)									
2341.09	28.64	PK	159	2.3	H	31.64	60.28	74	13.72
2341.09	13.52	Ave.	159	2.3	H	31.64	45.16	54	8.84
2483.50	31.87	PK	340	2.4	H	32.13	64.00	74	10.00
2483.50	18.42	Ave.	340	2.4	H	32.13	50.55	54	3.45
4960.00	44.69	PK	270	2.0	H	6.80	51.49	74	22.51
4960.00	31.30	Ave.	270	2.0	H	6.80	38.10	54	15.90
7440.00	50.06	PK	270	1.6	H	12.39	62.45	74	11.55
7440.00	35.08	Ave.	270	1.6	H	12.39	47.47	54	6.53

Note:
Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude = Corrected Factor + Reading
Margin = Limit - Corrected. Amplitude
The other spurious emission which is 20dB to the limit was not recorded.
And for the pre-scan is performed with the 2400-2483.5MHz band filter.

Pre-scan with high channel Peak
Horizontal



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	4.96 GHz	50.23 dBµV		
M2		1	7.44 GHz	60.68 dBµV		
M3		1	14.937 GHz	58.48 dBµV		

Date: 6.MAR.2021 08:33:55



Date: 6.MAR.2021 09:19:09

Vertical



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	4.96 GHz	48.44 dBµV		
M2		1	7.44 GHz	51.55 dBµV		
M3		1	15.232 GHz	58.58 dBµV		

Date: 6.MAR.2021 08:43:29



Date: 6.MAR.2021 09:28:56

Pre-scan for Average
Horizontal



Date: 6.MAR.2021 08:38:32



Date: 6.MAR.2021 09:23:30

Vertical



Date: 6.MAR.2021 08:47:57



Date: 6.MAR.2021 09:33:53

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	24.7 ℃
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Coco Liu from2021-02-24 to 2021-03-16.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.

Channel	Channel Separation (MHz)	20 dBc BW (MHz)	Two-thirds of the 20 dB bandwidth (MHz)	Channel Separation Limit	Result
BDR(GFSK)					
Low	1.000	0.890	0.593	> two-thirds of the 20 dB bandwidth	Compliance
Middle	1.000	0.883	0.589	> two-thirds of the 20 dB bandwidth	Compliance
High	1.003	0.887	0.591	> two-thirds of the 20 dB bandwidth	Compliance
EDR(π/4-DQPSK)					
Low	0.997	1.259	0.839	> two-thirds of the 20 dB bandwidth	Compliance
Middle	1.000	1.259	0.839	> two-thirds of the 20 dB bandwidth	Compliance
High	0.997	1.257	0.838	> two-thirds of the 20 dB bandwidth	Compliance

Please refer to the following plots.

BDR (GFSK): Low Channel



Date: 16.MAR.2021 13:39:34

BDR (GFSK): Middle Channel



Date: 24.FEB.2021 14:41:43

BDR (GFSK): High Channel



Date: 16.MAR.2021 13:43:57

EDR (π/4-DQPSK): Low Channel



Date: 16.MAR.2021 14:11:45

EDR (π/4-DQPSK): Middle Channel



Date: 24.FEB.2021 14:36:56

EDR (π/4-DQPSK): High Channel



Date: 16.MAR.2021 13:56:45

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	24.7 ℃
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Coco Liu on 2021-03-22.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.890
	Middle	2441	0.883
	High	2480	0.887
EDR (π/4-DQPSK)	Low	2402	1.259
	Middle	2441	1.259
	High	2480	1.257

BDR (GFSK): Low Channel



Date: 22.MAR.2021 11:24:53

BDR (GFSK): Middle Channel



Date: 22.MAR.2021 11:26:56

BDR (GFSK): High Channel



Date: 22.MAR.2021 11:28:57

EDR (π/4-DQPSK): Low Channel



Date: 22.MAR.2021 11:33:20

EDR (π/4-DQPSK): Middle Channel



Date: 22.MAR.2021 11:30:55

EDR (π/4-DQPSK): High Channel



Date: 22.MAR.2021 11:30:08

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

Test Data

Environmental Conditions

Temperature:	24.7 ℃
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Coco Liu on 2021-02-24.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	⩾15
EDR (π/4-DQPSK)	2400-2483.5	79	⩾15

BDR (GFSK): Number of Hopping Channels



Date: 24.FEB.2021 14:26:42

EDR (π/4-DQPSK): Number of Hopping Channels



Date: 24.FEB.2021 14:30:36

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW ≥ 3×RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses

Test Data

Environmental Conditions

Temperature:	24.7 ℃
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Coco Liu on 2021-02-24.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots

TestMode	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Hop	0.384	330	0.127	<=0.4	PASS
DH3	Hop	1.647	140	0.231	<=0.4	PASS
DH5	Hop	2.916	130	0.379	<=0.4	PASS
2DH1	Hop	0.392	380	0.149	<=0.4	PASS
2DH3	Hop	1.660	150	0.249	<=0.4	PASS
2DH5	Hop	2.944	90	0.265	<=0.4	PASS

Note 1：A period time=0.4*79=31.6(S), Result=BurstWidth*Totalhops
Note 2: Totalhops=Hopping Number in 3.16s*10
Note 3: Hopping Number in 3.16s=Total of highest signals in 3.16s(Second high signals were other channel)

BDR (GFSK):

Pulse time, Middle Channel, DH1



Date: 24.FEB.2021 15:01:18



Date: 24.FEB.2021 15:08:13

Pulse time, Middle Channel, DH3



Date: 24.FEB.2021 15:03:09



Date: 24.FEB.2021 15:07:17

Pulse time, Middle Channel, DH5



Date: 24.FEB.2021 15:04:38



Date: 24.FEB.2021 15:06:48

EDR (π/4-DQPSK):

Pulse time, Middle Channel, 2DH1



Date: 24.FEB.2021 15:02:07



Date: 24.FEB.2021 15:08:51

Pulse time, Middle Channel, 2DH3



Date: 24.FEB.2021 15:03:35



Date: 24.FEB.2021 15:07:47

Pulse time, Middle Channel, 2DH5



Date: 24.FEB.2021 15:05:14



Date: 24.FEB.2021 15:06:26

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Data

Environmental Conditions

Temperature:	24.7 ℃
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Coco Liu on 2021-02-24.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table.

Mode	Channel	Frequency (MHz)	Peak Output Power		Limit (mW)
			(dBm)	(mW)	
BDR (GFSK)	Low	2402	6.30	4.27	125
	Middle	2441	6.42	4.39	125
	High	2480	6.35	4.32	125
EDR (π/4-DQPSK)	Low	2402	6.56	4.53	125
	Middle	2441	6.65	4.62	125
	High	2480	6.64	4.61	125

BDR (GFSK): Low Channel



Date: 24.FEB.2021 14:08:07

BDR (GFSK): Middle Channel



Date: 24.FEB.2021 14:09:06

BDR (GFSK): High Channel



Date: 24.FEB.2021 14:10:10

EDR (π/4-DQPSK): Low Channel



Date: 24.FEB.2021 14:12:16

EDR (π/4-DQPSK): Middle Channel



Date: 24.FEB.2021 14:11:45

EDR (π/4-DQPSK): High Channel



Date: 24.FEB.2021 14:10:39

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	24.7 ℃
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Coco Liu on 2021-02-24.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following plots.

BDR (GFSK): Band Edge-Left Side

Hopping



Date: 24.FEB.2021 14:56:30

Single



Date: 24.FEB.2021 14:43:18

BDR (GFSK): Band Edge-Right Side

Hopping



Date: 24.FEB.2021 14:46:56

Single



Date: 24.FEB.2021 14:45:14

EDR (π/4-DQPSK): Band Edge-Left Side

Hopping



Date: 24.FEB.2021 14:50:41

Single



Date: 24.FEB.2021 14:43:55

EDR (π/4-DQPSK): Band Edge-Right Side

Hopping



Date: 24.FEB.2021 14:48:19

Single



Date: 24.FEB.2021 14:44:44

******* END OF REPORT *******