

RADIO TEST REPORT

Product : Wireless Headset

Model Name : HS2706

FCC ID : 2AYYS-HS2706

Test Regulation : FCC 47 CFR Part 15 Subpart C (Section 15.247)

Received Date : 2026/6/15

Test Date : 2026/6/16 ~ 2026/6/17

Issued Date : 2026/8/4

Applicant : Luxshare Precision Industry Co., Ltd.
Floor 2,Block A,Sanyo New Industrial Area, West Haoyi
Community,Shajing Subdistrict Office, Bao an District
Shenzhen, P. R. China

Issued By : Underwriters Laboratories Taiwan Co., Ltd.
Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd.,
Zhudong Township, Hsinchu County, Taiwan



The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report are responsible of the test sample(s) provided by the client only and are not to be used to indicate applicability to other similar products.


Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0



Original Test Report No.: 4792253114-US-R0-V0

Underwriters Laboratories Taiwan Co., Ltd.

Telephone :+886-2-7737-3000

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Table of Contents

1. Attestation of Test Results	4
2. Summary of Test Results	5
3. Test Methodology and Reference Procedures.....	6
4. Facilities and Accreditation	6
5. Measurement Uncertainty	7
6. Equipment under Test.....	8
6.1. Description of EUT	8
6.2. Channel List	9
6.3. Test Condition.....	10
6.4. Description of Available Antennas	11
6.5. Test Mode Applicability and Tested Channel Detail.....	12
6.6. Duty cycle	13
7. Test Equipment	14
8. Description of Test Setup	16
9. Test Results	18
9.1. Channel Bandwidth.....	18
9.2. Conducted Output Power	21
9.3. Hopping Channel Separation	23
9.4. Number of Hopping Frequency Used	26
9.5. Dwell Time on Each Channel	28
9.6. Conducted Out of Band Emission.....	31
9.7. Radiated Spurious Emission	36
9.8. AC Power Line Conducted Emission	56

1. Attestation of Test Results

APPLICANT: Luxshare Precision Industry Co., Ltd.
Floor 2,Block A,Sanyo New Industrial Area, West Haoyi
Community,Shajing Subdistrict Office, Bao an District Shenzhen, P. R.
China

MANUFACTURER: Luxshare Precision Industry Co., Ltd.
2nd floor,A building,Sanyo New Industrial Area,West of
Maoyi,Shajing Street,Ban'an District,Shenzhen City,Guangdong
Province,China

EUT DESCRIPTION: Wireless Headset

BRAND: Dell

MODEL: HS2706

SAMPLE STAGE: Engineering Verification Test Sample

DATE of TESTED: 2026/6/16 ~ 2026/6/17

APPLICABLE STANDARDS	
STANDARD	Test Results
FCC 47 CFR PART 15 Subpart C (Section 15.247)	PASS

Underwriters Laboratories Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Underwriters Laboratories Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Underwriters Laboratories Taiwan Co., Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Underwriters Laboratories Taiwan Co., Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Prepared By:



James Chan Date : 2026/8/4
Laboratory Test Engineer

Approved and Authorized By:



Eric Lee Date : 2026/8/4
Senior Laboratory Engineer

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

2. Summary of Test Results

Summary of Test Results		
FCC Clause	Test Items	Result
15.247(a)(1) (iii)	Number of Hopping Frequency Used	PASS
15.247(a)(1) (iii)	Dwell Time on Each Channel	PASS
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS
15.247(b)	Conducted Output Power	PASS
15.247(d)	Antenna Port Emission	PASS
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	PASS
15.207	AC Power Conducted Emission	PASS
15.203	Antenna Requirement	PASS

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

3. Test Methodology and Reference Procedures

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2, KDB558074 D01 Meas Guidance v05r02, KDB414788 D01 Radiated Test Site v01r01, ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024.

4. Facilities and Accreditation

Test Location	Underwriters Laboratories Taiwan Co., Ltd.
Address	Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Accreditation Certificate	Underwriters Laboratories Taiwan Co., Ltd. is accredited by TAF, Laboratory Code 3398.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

5. Measurement Uncertainty

For statement of conformity, Simple acceptance (Section 3.1.4 of IEC Guide 115) was applied as decision rule for measurement in this test report.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor $k=2$.

Determining compliance based on the results of the compliance measurement, not considering measurement instrumentation uncertainty.

Measurement	Frequency	Uncertainty
Conducted disturbance at mains terminals ports	150kHz ~ 30MHz	3.1 dB
RF Conducted	9 kHz - 40GHz	2.7 dB
Radiated disturbance below 30MHz	9 kHz - 30 MHz	1.9 dB
Radiated disturbance below 1 GHz	30MHz ~ 1GHz	5.8 dB
Radiated disturbance above 1 GHz	1GHz ~ 40GHz	4.9 dB

The EUT support table is constructed of high-density Expandable Polystyrene (EPS) with dimensions of 1 m × 1.5 m.

The Measurement Uncertainty (MU) report is prepared in accordance with CISPR 16-4-2:2011-06; the potential impact of the setup table material has been evaluated and included as a component of the overall uncertainty value.

6. Equipment under Test

6.1. Description of EUT

Product	Wireless Headset
Brand Name	Dell
Model Name	HS2706
Normal Voltage	5Vdc from Host 3.82Vdc from Battery
Operating Frequency	2402MHz ~ 2480MHz
Modulation	GFSK, $\pi/4$ -DQPSK and 8DPSK
Transfer Rate	Up to 3 Mbps
Maximum Output Power	7.51 dBm
Sample ID	Conducted Test:9847261
	Radiated Test:9847260

Note:

1. The EUT contains following accessory devices:

Product	Brand	Model	Description
USB dongle	Dell	UD2403	NCC ID: CCAQ23LP0170T3
USB C TO A Adapter	HAOYANG	USB C TO A Adapter	-
USB Cable	LianTao Electronics Co., Ltd.	2M06-00000-0030H	-

2. EUT is equipped with a built-in rechargeable battery with the following table:

Brand	Model	Description
Apower Electronics Co.,Ltd	AEC382631	3.82Vdc, 500mAh, 1.91Wh
SYNergy ScienTech Corp.	AHB362631KPCT	3.82Vdc, 500mAh, 1.91Wh

3. The above EUT information is declared by manufacturer and for more detailed features description, please refer the manufacturer's or user's manual, the laboratory shall not be held responsible.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

6.2. Channel List

79 channels are provided for BT-BR/EDR mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	-	-

6.3. Test Condition

Test Item	Test Site No.	Environmental	Input Power	Test Date	Tested by
Antenna Port Conducted Measurement	SR4	23°C/ 63%RH	5Vdc	2026/06/17	Rex Chen
Radiated Spurious Emission	966-2	22~26°C/ 62~68%RH	5Vdc	2026/06/16~ 2026/06/17	Rex Chen
AC power Line Conducted Emission	SR1	24°C/ 62%RH	120Vac/ 60Hz	2026/06/16	Rex Chen

Sample Calculation:

Antenna Port Conducted Measurement:

- Where relevant, the follow sample calculation is provided:
Result Value (dBm) = Reading Value (dBm) + Attenuator Factor (dB) + Cable Loss (dB).
Example: Result Value (10dBm) = Reading Value (-2dBm) + Attenuator Factor (10dB) + Cable Loss(2dB).
*Test plot only shown the “Result Value”.

Radiated Spurious Emission:

- Where relevant, the follow sample calculation is provided:
Result Value (dBuV/m) = Reading Value (dBuV) + Correction Factor (dB/m).
Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - Preamp Factor (dB).
Example: Result Value (34.5dBuV/m) = Reading Value (40.1dBuV) + Antenna Factor (18.7dB/m) + Cable Loss (4.2dB) - Preamp Factor (28.5dB).

AC power Line Conducted Emission:

- Where relevant, the follow sample calculation is provided:
Result Value (dBuV) = Reading Value (dBuV) + Correction Factor (dB).
Correction Factor (dB) = Insertion loss(dB) + Cable loss(dB).
Example: Result Value (53.7dBuV) = Reading Value (35.1dBuV) + Insertion loss(18.1dB) + Cable loss(0.5dB).

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

6.4. Description of Available Antennas

Ant. No.	Transmitter Circuit	Frequency Range	Brand Name	Model Name	Maximum Gain (dBi)	Ant. Type	Connector Type
1	Chain0	2400 ~ 2500MHz	TOPLINK	MD03-FPC	2.59	IFA	None

Note: The above antenna information was provided from customer and for more detailed features description, please refer the manufacturer's specification or user's manual, the laboratory shall not be held responsible.

6.5. Test Mode Applicability and Tested Channel Detail

Test Item	Modulation Type	Available Channel	Test Channel	Packet Type
Radiated Emissions (Above 1GHz)	GFSK	0 to 78	0,39,78	DH5
	8DPSK	0 to 78	0,39,78	3DH5
Radiated Emissions (Below 1GHz)	GFSK	0 to 78	0	DH5
AC Power Line Conducted Emission	GFSK	0 to 78	0	DH5
Antenna Port Conducted Measurement	GFSK	0 to 78	0,39,78	DH1*,DH3*,DH5
	8DPSK	0 to 78	0,39,78	3DH1*,3DH3*,3DH5

* Only for Dwell Time on Each Channel test

- The EUT was evaluated in two positions: lay and stand. Based on the investigation, the stand orientation represented the worst-case scenario. All final radiated emission tests were conducted with EUT positioned accordingly.
- The EUT has two Battery types: 3.82Vdc from Battery (Manufacturer: SYNergy ScienTech Corp. ; Model: AHB362631KPCT) and 3.82Vdc from Battery (Manufacturer: Apower Electronics Co.,Ltd ; Model: AEC382631), above two types was pre-tested, the worst case was found in the 3.82Vdc from Battery (Manufacturer: Apower Electronics Co.,Ltd ; Model: AEC382631). Therefore, only the test data of the 3.82Vdc from Battery (Manufacturer: Apower Electronics Co.,Ltd ; Model: AEC382631) was recorded in this report.
- In the transmit mode, GFSK DH5 channel 0 has the highest RF output power. Therefore, the AC conduction was performed using this worst-case mode.
- In the transmit mode, GFSK DH5 channel 0 has the highest RF output power. Therefore, all final tests for the spurious emission (below 1GHz) were performed using this worst-case mode.
- The Packet Type for DH1, DH3, and DH5 have all been pre-tested, the fundamental worst case of the Packet Type was found in DH5. Therefore, only DH5 Packet Type is recorded in the report. (Except Dwell Time).
- The modulation and bandwidth are similar for $\pi/4$ -DQPSK mode and 8DPSK mode, therefore investigated 8DPSK mode to representative mode in test report.
- For Antenna Port Conducted Measurement, this item includes all test value of each mode but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Since the DUT is a Bluetooth device, the AFH mode and non-AFH mode follow the Bluetooth timing protocol, and the same timing level has the same time interval, but the non-AFH mode has worse results, therefore only the test data of this type were recorded in this report.


Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

6.6. Duty cycle

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle	Duty Factor (dB)	VBW Set (above 1GHz)
GFSK(DH5)	2.875	3.750	0.7667	1.15	510Hz
8DPSK(3DH5)	2.880	3.755	0.7670	1.15	510Hz



7. Test Equipment

Test Equipment List					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Expired date
Radiated Spurious Emission					
Spectrum Analyzer	Keysight	N9010A	MY56070818	2026/2/9	2027/2/8
EMI Test Receiver	Rohde & Schwarz	ESR7	101754	2025/12/9	2026/12/8
Loop Antenna	ETS lindgren	6502	00213440	2025/11/14	2026/11/13
Trilog-Broadband Antenna with 5dB Attenuator	Schwarzbeck & EMCI	VULB 9168 & N-6-05	774 & AT-N0538	2025/12/23	2026/12/22
Horn Antenna (1-18 GHz)	Schwarzbeck	BBHA 9120 D	01690	2025/11/18	2026/11/17
Horn Antenna (18-40 GHz)	Schwarzbeck	BBHA 9170	781	2025/12/2	2026/12/1
Preamplifier (30-1000 MHz)	EMCI	EMC330E	980405	2026/4/28	2027/4/27
Preamplifier (1-18 GHz)	EMCI	EMC051835BE	980406	2025/12/26	2026/12/25
Preamplifier (18-40GHz)	EMCI	EMC184040SEE	980426	2026/3/24	2027/3/23
Cables (9k-18 GHz)	Hanyitek	K1K50-UP0264-K1K50-2500	170214-4 & 170425-2	2025/11/21	2026/11/20
Cables (18-40GHz)	Hanyitek	K1K50-UP0264-K1K50-2500	170214-1 & 170214-2	2025/11/21	2026/11/20

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Test Equipment List					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Expired date
Antenna Port Conducted Measurement					
Signal Analyzer	Rohde & Schwarz	FSVA3044	101281	2026/2/2	2027/2/1
Signal Analyzer	Rohde & Schwarz	FSV40	101490	2026/6/2	2027/6/1
Attenuator	EMCI	EMC-40ATK2W10	17002	2025/10/28	2026/10/27
USB Power Sensor	Anritsu	MA24408A	12031	2025/6/24	2026/6/23
Temperature & Humidity Test Chamber	GIANT FORCE	GTH-150- 40-CP-AR	MAA1701-010	2026/2/2	2027/2/1
AC power Line Conducted Emission					
EMI Test Receiver	Rohde & Schwarz	ESR7	101753	2025/9/18	2026/9/17
Two-Line V-Network	Rohde & Schwarz	ENV216	102136	2026/3/26	2027/3/25
Impuls-Begrenzer Pulse Limiter	Rohde & Schwarz	ESH3-Z2	102219-Qt	2025/8/27	2026/8/26
Cables	TITAN	CFD200	T0732ACFD 20020A300-2	2026/4/15	2027/4/14

UL Software		
Description	Name	Version
Radiated measurement	e3	6.191211 (V6)
Conducted measurement	RF-Conducted-FCC 15247	ver 1.0
AC power Line Conducted Emission	EZ_EMC	UL-3A1.2

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

8. Description of Test Setup

Support Equipment

ID	Equipment	Brand Name	Model Name	S/N	Remark
A	Laptop	MSI	MS-13Q2	K2402N0015485	Provided by Lab
B	Test Tool	Waveshare	FT232	N/A	Supplied by Client


I/O Cables

ID	Equipment	Brand Name	Model Name	Length (m)	Remark
1	DC Cable	Luxshare	DC cable 1	0.17	Supplied by Client
2	DC Cable	Luxshare	DC cable 2	0.21	Supplied by Client
3	USB Cable	LianTao Electronics Co., Ltd.	2M06-00000-0030H	1.57	Supplied by Client

Test Setup

Controlled using a bespoke application (AB1565/68 Lab Test Tool-5.7.0.0) on a test Notebook. The application was used to enable a continuous transmission mode and to select the test channels, data rates, modulation schemes and power setting as required.

Setup Diagram for Test



Under Table

Remote Site

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

9. Test Results

9.1. Channel Bandwidth


Requirements

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

Test procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- Repeat above procedures until all frequencies measured were complete.

Test Setup



The loss between RF output port of the EUT and the input port of the Spectrum Analyzer has been taken into consideration.

Test Data

Mode	CH	Freq (MHz)	Chain	20dB BW (MHz)	Limit (MHz)	Result
GFSK(DH5)	0	2402	Chain 0	0.968	N/A	Pass
GFSK(DH5)	39	2441	Chain 0	0.967	N/A	Pass
GFSK(DH5)	78	2480	Chain 0	0.967	N/A	Pass
8DPSK(3DH5)	0	2402	Chain 0	1.259	N/A	Pass
8DPSK(3DH5)	39	2441	Chain 0	1.269	N/A	Pass
8DPSK(3DH5)	78	2480	Chain 0	1.254	N/A	Pass


Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0



9.2. Conducted Output Power

Requirements


The Maximum Output Power Measurement is 125mW.

Test Procedure

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level for peak power.

A AVG power sensor was used on the output port of the EUT. A power meter was used to read the response of the AVG power sensor, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Record the power level for AVG power (Reference only).

Test Setup



The loss between RF output port of the EUT and the input port of the Power Meter has been taken into consideration.

Test Data

Mode	CH	Freq. (MHz)	Peak Power (dBm)	Total Power (mW)	Total Power (dBm)	AVG Power (dBm)	Total Power (mW)	Total Power (dBm)	Limit (dBm)	Result
			Chain 0			Chain 0				
BT-GFSK	0	2402	7.51	5.636	7.51	7.39	5.483	7.39	20.97	Pass
	39	2441	7.4	5.495	7.4	7.22	5.272	7.22	20.97	Pass
	78	2480	7.09	5.117	7.09	6.97	4.977	6.97	20.97	Pass
BT-8DPSK	0	2402	7.5	5.623	7.5	7.38	5.47	7.38	20.97	Pass
	39	2441	7.34	5.42	7.34	7.21	5.26	7.21	20.97	Pass
	78	2480	7.08	5.105	7.08	6.96	4.966	6.96	20.97	Pass

Note: Average Power is for reference Only.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

9.3. Hopping Channel Separation


Requirements

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

Test procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
- By using the MaxHold function record the separation of two adjacent channels.
- Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.

Test Setup



The loss between RF output port of the EUT and the input port of the Spectrum Analyzer has been taken into consideration.

Test Data

Mode	CH	Freq (MHz)	Chain	Channel Separation (MHz)	> Limit (MHz)
GFSK(DH5)	0	2402	Chain 0	1	0.645
GFSK(DH5)	39	2441	Chain 0	0.893	0.645
GFSK(DH5)	78	2480	Chain 0	1.002	0.645
8DPSK(3DH5)	0	2402	Chain 0	0.984	0.839
8DPSK(3DH5)	39	2441	Chain 0	1.003	0.846
8DPSK(3DH5)	78	2480	Chain 0	1.168	0.836


Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0



9.4. Number of Hopping Frequency Used


Requirements

At least 15 channels frequencies, and should be equally spaced.

Test procedure

- Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- Set the SA on View mode and then plot the result on SA screen.
- Repeat above procedures until all frequencies measured were complete.


Test Setup



The loss between RF output port of the EUT and the input port of the Spectrum Analyzer has been taken into consideration.

Test Data

There are 79 hopping frequencies in the hopping mode. On the plots, it shows that the hopping frequencies are equally spaced.



Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

9.5. Dwell Time on Each Channel

Requirements

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Test procedure

- Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- Repeat above procedures until all different time-slot modes have been completed.
- Measure the maximum time duration of one single pulse.

A Period Time = (channel number)*0.4

For normal mode:

DH1 Time Slot: Reading * (1600/2)*31.6/(channel number)

DH3 Time Slot: Reading * (1600/4)*31.6/(channel number)

DH5 Time Slot: Reading * (1600/6)*31.6/(channel number)


For AFH mode:

DH1 Time Slot: Reading * (800/2)*31.6/(channel number)

DH3 Time Slot: Reading * (800/4)*31.6/(channel number)

DH5 Time Slot: Reading * (800/6)*31.6/(channel number)

Test Setup



The loss between RF output port of the EUT and the input port of the Spectrum Analyzer has been taken into consideration.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Test Data

Mode	Freq (MHz)	Chain	Length of transmission time (ms)	Dwell Time (ms)	Limit (ms)	Result
GFSK(DH1)	2441	Chain 0	0.370	118.400	400	PASS
GFSK(DH3)	2441	Chain 0	1.625	260.000	400	PASS
GFSK(DH5)	2441	Chain 0	2.880	307.200	400	PASS
8DPSK(3DH1)	2441	Chain 0	0.380	121.600	400	PASS
8DPSK(3DH3)	2441	Chain 0	1.625	260.000	400	PASS
8DPSK(3DH5)	2441	Chain 0	2.885	307.733	400	PASS

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0



9.6. Conducted Out of Band Emission


Requirements

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b) (3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209 (a) is not required.

Test procedure

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.


Test Setup





The loss between RF output port of the EUT and the input port of the Spectrum Analyzer has been taken into consideration.

Figure 10 displays four spectral plots comparing GFSK(DH5) and FHSS signals. The plots are arranged in a 2x2 grid, showing frequency (MHz) on the x-axis and power (dBm) on the y-axis. The top row shows reference signals, and the bottom row shows conducted emissions.

- Top Left: GFSK(DH5), FHSS, Chain 0, Reference**
 - Frequency range: 2.441 GHz to 2.481 GHz (Span 23.4 MHz).
 - Power range: -80 dBm to 10 dBm.
 - Signal characteristics: A clear, narrowband signal is visible, centered around 2.481 GHz.
- Top Right: GFSK(DH5), CH0, Chain 0, Reference**
 - Frequency range: 2.402 GHz to 2.482 GHz (Span 3.0 MHz).
 - Power range: -50 dBm to 10 dBm.
 - Signal characteristics: A clear, narrowband signal is visible, centered around 2.481 GHz.
- Bottom Left: GFSK(DH5), FHSS, Chain 0, Conducted Emission**
 - Frequency range: 2.45 GHz to 2.49 GHz (Span 26.5 GHz).
 - Power range: -80 dBm to 10 dBm.
 - Signal characteristics: A noisy background with a peak at 2.488935 GHz (-48.35 dBm).
- Bottom Right: GFSK(DH5), CH0, Chain 0, Conducted Emission**
 - Frequency range: 2.45 GHz to 2.49 GHz (Span 26.5 GHz).
 - Power range: -80 dBm to 10 dBm.
 - Signal characteristics: A noisy background with a peak at 2.488935 GHz (-48.35 dBm).







9.7. Radiated Spurious Emission

Requirements

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Test Procedures

[For 9 kHz ~ 30 MHz]

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. For measurement below 30MHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

[For above 30 MHz]

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Note:

- a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- b. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.

Configuration	Average	
	RBW	VBW
Bluetooth	1MHz	Refer to section 6.6 for duty cycle.

- d. All modes of operation were investigated (includes all external accessories) and the worst-case emissions are reported, the other emission levels were low against the limit.
- e. Test data of Result value (dBuV/m) = Reading value (dBuV) + Correction Factor (dB/m).
- f. Test data of Margin(dB) = Result value (dBuV/m) - Limit value (dBuV/m).
- g. Test data of Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - Preamp Factor (dB).
- h. Test data of Notation "@" = Fundamental Frequency
- i. Test data of Notation "*" = The peak result under 20 dB above and complies with AVG limit, AVG result is deemed to comply with AVG limit.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948


Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Test Setup

<Frequency Range 9 kHz ~ 30 MHz>



<Frequency Range 30 MHz ~ 1 GHz >



Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

<Frequency Range above 1 GHz>




For the actual test configuration, please refer to the Setup Configurations.

Test Data

Above 1 GHz


Mode	GFSK	Channel	0
------	------	---------	---

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		2377.64	40.18	13.86	54.04	74	-19.96	PK
		2384.1	30.9	13.84	44.74	54	-9.26	AVG
	@	2402	90.5	13.8	104.3	N/A	N/A	PK
	@	2402	90.34	13.8	104.14	N/A	N/A	AVG
Vertical		2324.82	40.43	13.91	54.34	74	-19.66	PK
		2383.91	31.38	13.84	45.22	54	-8.78	AVG
	@	2402	88.17	13.8	101.97	N/A	N/A	PK
	@	2402	87.16	13.8	100.96	N/A	N/A	AVG




Mode	GFSK	Channel	39
------	------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		2336.22	39.97	13.92	53.89	74	-20.11	PK
		2383.91	30.99	13.84	44.83	54	-9.17	AVG
	@	2441	93.47	13.63	107.1	N/A	N/A	PK
	@	2441	92.97	13.63	106.6	N/A	N/A	AVG
		2492.78	39.63	13.67	53.3	74	-20.7	PK
		2496.58	28.99	13.67	42.66	54	-11.34	AVG
Vertical		2370.61	40.76	13.87	54.63	74	-19.37	PK
		2384.1	31.51	13.84	45.35	54	-8.65	AVG
	@	2441	89.66	13.63	103.29	N/A	N/A	PK
	@	2441	89.49	13.63	103.12	N/A	N/A	AVG
		2485.56	28.42	13.65	42.07	54	-11.93	AVG
		2485.94	39.5	13.65	53.15	74	-20.85	PK



Mode	GFSK	Channel	78
------	------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal	@	2480	90.59	13.64	104.23	N/A	N/A	PK
	@	2480	90.18	13.64	103.82	N/A	N/A	AVG
		2483.85	29.61	13.65	43.26	54	-10.74	AVG
		2487.65	40.56	13.66	54.22	74	-19.78	PK
Vertical	@	2480	89.08	13.64	102.72	N/A	N/A	PK
	@	2480	88.35	13.64	101.99	N/A	N/A	AVG
		2483.66	28.81	13.65	42.46	54	-11.54	AVG
		2491.45	40.35	13.66	54.01	74	-19.99	PK




Mode	GFSK - Emission	Channel	0
------	-----------------	---------	---

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal	*	4804	35.81	4.22	40.03	74	-33.97	PK
		14500	29.88	28	57.88	74	-16.12	PK
		14500	21.61	28	49.61	54	-4.39	AVG
		15340	30.42	26.45	56.87	74	-17.13	PK
	*	15340	21.59	26.45	48.04	54	-5.96	AVG
		16814	36.64	5.31	41.95	74	-32.05	PK
		19216	35.51	3.49	39	74	-35	PK
		21618	35.34	5.99	41.33	74	-32.67	PK
		24020	34.75	10.58	45.33	74	-28.67	PK
Vertical	*	4804	35.22	4.22	39.44	74	-34.56	PK
		14470	30.8	27.97	58.77	74	-15.23	PK
		14470	22.53	27.97	50.5	54	-3.5	AVG
		15340	30.34	26.45	56.79	74	-17.21	PK
	*	15340	21.51	26.45	47.96	54	-6.04	AVG
		16814	35.66	5.31	40.97	74	-33.03	PK
		19216	35.89	3.49	39.38	74	-34.62	PK
		21618	35.53	5.99	41.52	74	-32.48	PK
		24020	34.89	10.58	45.47	74	-28.53	PK


TX, GFSK - Emission (Ch 0)

Radiated Spurious Emission, Horizontal




TX, GFSK - Emission (Ch 0)

Radiated Spurious Emission, Vertical




TX, GFSK - Emission (Ch 0)

Radiated Spurious Emission, Horizontal



TX, GFSK - Emission (Ch 0)

Radiated Spurious Emission, Vertical



Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Mode	GFSK - Emission	Channel	39
------	-----------------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal	*	4882	35.3	4.48	39.78	74	-34.22	PK
		14500	31.16	28	59.16	74	-14.84	PK
		14500	22.89	28	50.89	54	-3.11	AVG
		15310	31.14	26.6	57.74	74	-16.26	PK
		15310	22.31	26.6	48.91	54	-5.09	AVG
	*	17087	34.96	5.32	40.28	74	-33.72	PK
	*	19528	35.96	3.87	39.83	74	-34.17	PK
	*	21969	34.69	6.08	40.77	74	-33.23	PK
	*	24410	35.69	11.82	47.51	74	-26.49	PK
	*	4882	35.76	4.48	40.24	74	-33.76	PK
Vertical	*	14500	30.67	28	58.67	74	-15.33	PK
		14500	22.4	28	50.4	54	-3.6	AVG
		15565	31	25.63	56.63	74	-17.37	PK
		15565	22.17	25.63	47.8	54	-6.2	AVG
		17087	35.73	5.32	41.05	74	-32.95	PK
	*	19528	35.24	3.87	39.11	74	-34.89	PK
	*	21969	35.82	6.08	41.9	74	-32.1	PK
	*	24410	34.52	11.82	46.34	74	-27.66	PK




Mode	GFSK - Emission	Channel	78
------	-----------------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal	*	4960	35.34	4.59	39.93	74	-34.07	PK
		14500	29.92	28	57.92	74	-16.08	PK
		14500	21.65	28	49.65	54	-4.35	AVG
		15340	31.49	26.45	57.94	74	-16.06	PK
	*	15340	22.66	26.45	49.11	54	-4.89	AVG
		17360	34.72	4.82	39.54	74	-34.46	PK
		19840	35.49	3.92	39.41	74	-34.59	PK
		22320	34.6	6.78	41.38	74	-32.62	PK
		24800	34.15	12.27	46.42	74	-27.58	PK
Vertical	*	4960	36.33	4.59	40.92	74	-33.08	PK
		14500	29.99	28	57.99	74	-16.01	PK
		14500	21.72	28	49.72	54	-4.28	AVG
		15325	30.44	26.53	56.97	74	-17.03	PK
	*	15325	21.61	26.53	48.14	54	-5.86	AVG
		17360	35	4.82	39.82	74	-34.18	PK
		19840	35.78	3.92	39.7	74	-34.3	PK
		22320	35.12	6.78	41.9	74	-32.1	PK
		24800	34.77	12.27	47.04	74	-26.96	PK


TX, GFSK - Emission (Ch 78)

Radiated Spurious Emission, Horizontal




TX, GFSK - Emission (Ch 78)

Radiated Spurious Emission, Vertical




TX, GFSK - Emission (Ch 78)

Radiated Spurious Emission, Horizontal







TX, GFSK - Emission (Ch 78)

Radiated Spurious Emission, Vertical




Mode	8DPSK	Channel	0
------	-------	---------	---

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		2318.74	40.22	13.92	54.14	74	-19.86	PK
		2383.91	30.84	13.84	44.68	54	-9.32	AVG
	@	2402	89.36	13.8	103.16	N/A	N/A	PK
	@	2402	85.99	13.8	99.79	N/A	N/A	AVG
Vertical		2341.92	40.56	13.92	54.48	74	-19.52	PK
		2383.91	31.77	13.84	45.61	54	-8.39	AVG
	@	2402	86.29	13.8	100.09	N/A	N/A	PK
	@	2402	84.29	13.8	98.09	N/A	N/A	AVG

TX, 8DPSK (Ch 0)
Band Edge (Average), Horizontal

TX, 8DPSK (Ch 0)
Band Edge (Average), Vertical

TX, 8DPSK (Ch 0)
Band Edge (Peak), Horizontal

TX, 8DPSK (Ch 0)
Band Edge (Peak), Vertical



Mode	8DPSK	Channel	39
------	-------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		2325.39	40.11	13.92	54.03	74	-19.97	PK
		2384.1	31.06	13.84	44.9	54	-9.1	AVG
	@	2441	91.85	13.63	105.48	N/A	N/A	PK
	@	2441	88.3	13.63	101.93	N/A	N/A	AVG
		2493.92	28.98	13.67	42.65	54	-11.35	AVG
		2494.49	40.56	13.67	54.23	74	-19.77	PK
Vertical		2379.16	40.8	13.85	54.65	74	-19.35	PK
		2384.1	31.5	13.84	45.34	54	-8.66	AVG
	@	2441	87.54	13.63	101.17	N/A	N/A	PK
	@	2441	84.8	13.63	98.43	N/A	N/A	AVG
		2495.82	40.1	13.67	53.77	74	-20.23	PK
		2499.81	28.54	13.68	42.22	54	-11.78	AVG



Mode	8DPSK	Channel	78
------	-------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal	@	2480	87.28	13.64	100.92	N/A	N/A	PK
	@	2480	85.26	13.64	98.9	N/A	N/A	AVG
		2484.23	29.42	13.65	43.07	54	-10.93	AVG
		2487.46	41.27	13.66	54.93	74	-19.07	PK
Vertical	@	2480	87.62	13.64	101.26	N/A	N/A	PK
	@	2480	84.34	13.64	97.98	N/A	N/A	AVG
		2483.66	28.9	13.65	42.55	54	-11.45	AVG
		2495.44	40.57	13.67	54.24	74	-19.76	PK




Mode	8DPSK - Emission	Channel	0
------	------------------	---------	---

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal	*	4804	34.93	4.22	39.15	74	-34.85	PK
		14485	30.88	27.98	58.86	74	-15.14	PK
		14485	22.61	27.98	50.59	54	-3.41	AVG
		15310	29.9	26.6	56.5	74	-17.5	PK
	*	15310	21.07	26.6	47.67	54	-6.33	AVG
		16814	35.48	5.31	40.79	74	-33.21	PK
		19216	35.48	3.49	38.97	74	-35.03	PK
		21618	35.12	5.99	41.11	74	-32.89	PK
		24020	34.85	10.58	45.43	74	-28.57	PK
Vertical	*	4804	35.2	4.22	39.42	74	-34.58	PK
		14500	30.76	28	58.76	74	-15.24	PK
		14500	22.49	28	50.49	54	-3.51	AVG
		15340	30.95	26.45	57.4	74	-16.6	PK
	*	15340	22.12	26.45	48.57	54	-5.43	AVG
		16814	35.87	5.31	41.18	74	-32.82	PK
		19216	35.34	3.49	38.83	74	-35.17	PK
		21618	35.62	5.99	41.61	74	-32.39	PK
		24020	35.11	10.58	45.69	74	-28.31	PK


TX, 8DPSK - Emission (Ch 0)

Radiated Spurious Emission, Horizontal




TX, 8DPSK - Emission (Ch 0)

Radiated Spurious Emission, Vertical




TX, 8DPSK - Emission (Ch 0)

Radiated Spurious Emission, Horizontal




TX, 8DPSK - Emission (Ch 0)

Radiated Spurious Emission, Vertical



Mode	8DPSK - Emission	Channel	39
------	------------------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal	*	4882	35.24	4.48	39.72	74	-34.28	PK
		14470	30.99	27.97	58.96	74	-15.04	PK
		14470	22.72	27.97	50.69	54	-3.31	AVG
		15565	32.24	25.63	57.87	74	-16.13	PK
		15565	23.41	25.63	49.04	54	-4.96	AVG
	*	17087	35.46	5.32	40.78	74	-33.22	PK
	*	19528	34.62	3.87	38.49	74	-35.51	PK
	*	21969	34.76	6.08	40.84	74	-33.16	PK
	*	24410	34.36	11.82	46.18	74	-27.82	PK
Vertical	*	4882	34.92	4.48	39.4	74	-34.6	PK
		14500	30.31	28	58.31	74	-15.69	PK
		14500	22.04	28	50.04	54	-3.96	AVG
		15445	30.96	26.05	57.01	74	-16.99	PK
		15445	22.13	26.05	48.18	54	-5.82	AVG
	*	17087	34.87	5.32	40.19	74	-33.81	PK
	*	19528	35.56	3.87	39.43	74	-34.57	PK
	*	21969	35.37	6.08	41.45	74	-32.55	PK
	*	24410	34.66	11.82	46.48	74	-27.52	PK




Mode	8DPSK - Emission	Channel	78
------	------------------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal	*	4960	34.8	4.59	39.39	74	-34.61	PK
		14485	31.23	27.98	59.21	74	-14.79	PK
		14485	22.96	27.98	50.94	54	-3.06	AVG
		15325	30.18	26.53	56.71	74	-17.29	PK
		15325	21.35	26.53	47.88	54	-6.12	AVG
	*	17360	34.28	4.82	39.1	74	-34.9	PK
	*	19840	36.19	3.92	40.11	74	-33.89	PK
	*	22320	35.1	6.78	41.88	74	-32.12	PK
	*	24800	34.26	12.27	46.53	74	-27.47	PK
Vertical	*	4960	34.8	4.59	39.39	74	-34.61	PK
		14500	30.48	28	58.48	74	-15.52	PK
		14500	22.21	28	50.21	54	-3.79	AVG
		15325	31.33	26.53	57.86	74	-16.14	PK
		15325	22.5	26.53	49.03	54	-4.97	AVG
	*	17360	34.16	4.82	38.98	74	-35.02	PK
	*	19840	35.75	3.92	39.67	74	-34.33	PK
	*	22320	34.48	6.78	41.26	74	-32.74	PK
	*	24800	33.99	12.27	46.26	74	-27.74	PK


TX, 8DPSK - Emission (Ch 78)

Radiated Spurious Emission, Horizontal




TX, 8DPSK - Emission (Ch 78)

Radiated Spurious Emission, Vertical




TX, 8DPSK - Emission (Ch 78)

Radiated Spurious Emission, Horizontal



TX, 8DPSK - Emission (Ch 78)


Radiated Spurious Emission, Vertical



Below 1 GHz

Mode	GFSK	Channel	0
------	------	---------	---

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		57.16	30.34	-11.02	19.32	40	-20.68	PK
		186.17	33.92	-12.62	21.3	43.5	-22.2	PK
		286.08	35.05	-9.77	25.28	46	-20.72	PK
		348.16	39.25	-8.04	31.21	46	-14.79	PK
		466.5	32.77	-4.77	28	46	-18	PK
		723.55	32.56	0.63	33.19	46	-12.81	PK
Vertical		45.52	30.54	-10.99	19.55	40	-20.45	PK
		168.71	30.81	-11.04	19.77	43.5	-23.73	PK
		228.85	33.98	-12.21	21.77	46	-24.23	PK
		340.4	35.43	-8.17	27.26	46	-18.74	PK
		501.42	33.27	-4.05	29.22	46	-16.78	PK
		652.74	30.39	-0.65	29.74	46	-16.26	PK




Charging Mode

Below 1 GHz


Mode	Charging Mode (Laptop)	Channel	0
------	------------------------	---------	---

Polarization	Notation @	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		60.07	30.56	-11.46	19.1	40	-20.9	PK
		191.99	34.38	-13.07	21.31	43.5	-22.19	PK
		228.85	35.12	-12.21	22.91	46	-23.09	PK
		265.71	37.33	-10.86	26.47	46	-19.53	PK
		353.01	35.78	-7.93	27.85	46	-18.15	PK
		508.21	31.2	-3.79	27.41	46	-18.59	PK
Vertical		50.37	30.87	-10.79	20.08	40	-19.92	PK
		146.4	31.69	-11.19	20.5	43.5	-23	PK
		229.82	37.4	-12.08	25.32	46	-20.68	PK
		355.92	33.85	-7.81	26.04	46	-19.96	PK
		474.26	34.83	-4.66	30.17	46	-15.83	PK
		511.12	33.97	-3.69	30.28	46	-15.72	PK

Charging Mode, Charging Mode (Laptop) (Ch 0) Radiated Spurious Emission, Horizontal



Charging Mode, Charging Mode (Laptop) (Ch 0) Radiated Spurious Emission, Vertical



Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

9 kHz ~ 30 MHz Data:

For 9 kHz to 30 MHz radiated emission have performed all modes of operation were investigated. The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

No non-compliance noted:

KDB 414788 D01 OATS and Chamber Correlation Justification

- Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

- OATs and chamber correlation testing had been performed and chamber measured test results is the worst case test result.

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

9.8. AC Power Line Conducted Emission

Requirements

Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

Test Procedures

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.
2. All modes of operation were investigated (includes all external accessories) and the worst-case emissions are reported, the other emission levels were low against the limit.
3. Test data of Result value (dB μ V) = Reading value (dB μ V) + Correction Factor (dB).
4. Test data of Margin(dB) = Result value (dB μ V) - Limit value (dB μ V).
5. Test data of Correction Factor (dB) = Insertion loss(dB) + Cable loss(dB).

Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Test Setup




Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the Setup Configurations.

Test Data

Mode	DH5_TX2402	Channel	0
------	------------	---------	---



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1685	37.24	9.95	47.19	65.03	-17.84	QP
2	0.1685	13.54	9.95	23.49	55.03	-31.54	AVG
3	0.1856	36.14	9.95	46.09	64.23	-18.14	QP
4	0.1856	17.36	9.95	27.31	54.23	-26.92	AVG
5	0.2837	27.08	9.95	37.03	60.71	-23.68	QP
6	0.2837	6.20	9.95	16.15	50.71	-34.56	AVG
7	0.3022	25.52	9.96	35.48	60.18	-24.70	QP
8	0.3022	6.09	9.96	16.05	50.18	-34.13	AVG
9	0.3221	24.44	9.96	34.40	59.65	-25.25	QP
10	0.3221	5.32	9.96	15.28	49.65	-34.37	AVG
11	29.4174	25.05	10.81	35.86	60.00	-24.14	QP
12	29.4174	19.86	10.81	30.67	50.00	-19.33	AVG

Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0


Mode	DH5_TX2402	Channel	0
------	------------	---------	---



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1517	36.11	9.94	46.05	65.91	-19.86	QP
2	0.1517	9.58	9.94	19.52	55.91	-36.39	AVG
3	0.1542	36.08	9.94	46.02	65.77	-19.75	QP
4	0.1542	10.23	9.94	20.17	55.77	-35.60	AVG
5	0.1771	34.96	9.93	44.89	64.62	-19.73	QP
6	0.1771	15.86	9.93	25.79	54.62	-28.83	AVG
7	0.2045	31.66	9.93	41.59	63.43	-21.84	QP
8	0.2045	13.07	9.93	23.00	53.43	-30.43	AVG
9	0.3087	22.74	9.93	32.67	60.01	-27.34	QP
10	0.3087	6.62	9.93	16.55	50.01	-33.46	AVG
11	0.3772	19.64	9.93	29.57	58.34	-28.77	QP
12	0.3772	6.18	9.93	16.11	48.34	-32.23	AVG

Charging Mode

Mode	Charging Mode	Channel	N/A
------	---------------	---------	-----



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1516	42.95	9.95	52.90	65.91	-13.01	QP
2	0.1516	20.21	9.95	30.16	55.91	-25.75	AVG
3	0.1655	38.17	9.95	48.12	65.18	-17.06	QP
4	0.1655	10.66	9.95	20.61	55.18	-34.57	AVG
5	0.1910	36.98	9.95	46.93	63.99	-17.06	QP
6	0.1910	20.06	9.95	30.01	53.99	-23.98	AVG
7	0.2096	34.21	9.95	44.16	63.22	-19.06	QP
8	0.2096	8.38	9.95	18.33	53.22	-34.89	AVG
9	0.2362	32.46	9.95	42.41	62.23	-19.82	QP
10	0.2362	15.73	9.95	25.68	52.23	-26.55	AVG
11	28.8288	27.83	10.80	38.63	60.00	-21.37	QP
12	28.8288	22.56	10.80	33.36	50.00	-16.64	AVG

Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Mode	Charging Mode	Channel	N/A
------	---------------	---------	-----



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1584	37.39	9.94	47.33	65.55	-18.22	QP
2	0.1584	10.02	9.94	19.96	55.55	-35.59	AVG
3	0.1773	35.84	9.93	45.77	64.61	-18.84	QP
4	0.1773	18.90	9.93	28.83	54.61	-25.78	AVG
5	0.2117	31.41	9.93	41.34	63.14	-21.80	QP
6	0.2117	13.06	9.93	22.99	53.14	-30.15	AVG
7	0.2510	27.19	9.93	37.12	61.72	-24.60	QP
8	0.2510	8.98	9.93	18.91	51.72	-32.81	AVG
9	0.2728	26.18	9.93	36.11	61.03	-24.92	QP
10	0.2728	9.56	9.93	19.49	51.03	-31.54	AVG
11	0.3324	21.98	9.93	31.91	59.39	-27.48	QP
12	0.3324	5.58	9.93	15.51	49.39	-33.88	AVG

END OF REPORT

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0