

RF Exposure

The equipment under test (EUT) is an Air Purifier with Bluetooth (BLE mode) function operating in 2402-2480MHz, 2.4G Wi-Fi function operating in 2412MHz~2462MHz. The EUT is powered by DC 24V/2A from adapter. For more detail information pls. refer to the user manual.

BLE

Antenna Type: Internal antenna.

Antenna Gain: 2.54dBi.

Modulation Type: GFSK.

The nominal conducted output power specified: 5dBm (Tolerance: +/-2dB).

The maximum conducted output power for the EUT is 5.60dBm in the frequency 2480MHz which is within the production variation.

The minimum conducted output power for the EUT is 5.05dBm in the frequency 2402MHz which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 V06 and OET 65, the simple calculation as below:

The source-based time averaged maximum radiated power = 7dBm+2.54dBi = 9.54dBm = 8.99mW

From above data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna for 2.4GHz band can be calculated according to OET 65 as follow:
= $8.99\text{mW} / 4\pi R^2$
= 0.0018 mW/cm²
<1mW/cm²

The MPE limit is 1.0 mW/cm² for general population and uncontrolled exposure in the WIFI frequency range according to FCC Part 1.1310. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

2.4GHz Wi-Fi:

Antenna Type: Internal Antenna.

Antenna Gain: 2.54dBi

Modulation Type: BPSK, QPSK, 16QAM, 64QAM, CCK, DQPSK, DBPSK.

The nominal conducted output power specified: 20dBm (Tolerance: +/-3dB).

The maximum conducted output power for the EUT is 21.8dBm in the frequency 2462MHz (IEEE 802.11N20) which is within the production variation.

The minimum conducted output power for the EUT is 18.6dBm in the frequency 2412MHz (IEEE 802.11B) which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 V06 and OET 65, the simple calculation as below:

The source-based time averaged maximum radiated power = 23dBm + 2.54dBi = 25.54dBm
= 358.09 mW

From above data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna for 2.4GHz band can be calculated according to OET 65 as follow:
= 358.09 mW/ $4\pi R^2$
= 0.0713 mW/cm²
<1mW/cm²

The MPE limit is 1.0 mW/cm² for general population and uncontrolled exposure in the WIFI frequency range according to FCC Part 1.1310. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

The following RF exposure statement or similar sentence is proposed to be included in the user manual:

“FCC RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”