RADIO TEST REPORT
FCC ID:2AZ2R-M265

Product: Robotic Vacuum Cleaner

Trade Mark: N/A

Model No.: M265

Family Model: M210 PRO OMNI, M2**, M2*, M2**PRO OMNI, M2*PRO OMNI

Report No.: N26012307916E

Issue Date: Mar. 24, 2026

Prepared for

Shenzhen USEER Robotics Co.,Ltd.
Building 2, Fashion Brand Industrial Park, E'Bu Town, Shenzhen-Shanwei Special Cooperation Zone, Shenzhen, Guangdong, China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
No. 24 Xinfa East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China
Tel. 0755-23200050 Website: http://www.ntek.org.cn

Table of Contents **Page**

1 TEST RESULT CERTIFICATION 3

2 SUMMARY OF TEST RESULTS 4

3 FACILITIES AND ACCREDITATIONS 5

3.1 FACILITIES 5
3.2 LABORATORY ACCREDITATIONS AND LISTINGS 5
3.3 MEASUREMENT UNCERTAINTY 5

4 GENERAL DESCRIPTION OF EUT 6

5 DESCRIPTION OF TEST MODES 8

6 SETUP OF EQUIPMENT UNDER TEST 10

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM 10
6.2 SUPPORT EQUIPMENT 11
6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS 12

7 TEST REQUIREMENTS 14

7.1 CONDUCTED EMISSIONS TEST 14
7.2 RADIATED SPURIOUS EMISSION 17
7.3 6DB BANDWIDTH 35
7.4 DUTY CYCLE 36
7.5 PEAK OUTPUT POWER 38
7.6 POWER SPECTRAL DENSITY 39
7.7 CONDUCTED BAND EDGE MEASUREMENT 41
7.8 SPURIOUS RF CONDUCTED EMISSIONS 42
7.9 ANTENNA APPLICATION 43

8 TEST RESULTS 44

8.1 DUTY CYCLE 44
8.2 MAXIMUM CONDUCTED OUTPUT POWER 47
8.3 -6DB BANDWIDTH 50
8.4 OCCUPIED CHANNEL BANDWIDTH 53
8.5 MAXIMUM POWER SPECTRAL DENSITY LEVEL 56
8.6 BAND EDGE 59
8.7 CONDUCTED RF SPURIOUS EMISSION 62

1 TEST RESULT CERTIFICATION

Applicant's name .....:	Shenzhen USEER Robotics Co.,Ltd.
Address .....:	Building 2, Fashion Brand Industrial Park, E'Bu Town, Shenzhen-Shanwei Special Cooperation Zone, Shenzhen, Guangdong, China
Manufacturer's Name .....:	Shenzhen USEER Robotics Co.,Ltd.
Address .....:	Building 2, Fashion Brand Industrial Park, E'Bu Town, Shenzhen-Shanwei Special Cooperation Zone, Shenzhen, Guangdong, China
Product description	
Product name .....:	Robotic Vacuum Cleaner
Trade Mark .....:	N/A
Model and/or type reference .....:	M265
Family Model .....:	M210 PRO OMNI, M2**, M2*, M2**PRO OMNI, M2*PRO OMNI
Test Sample number .....:	S2601310068-1#
Date of Test .....:	Jan. 23, 2026 ~ Mar. 24, 2026

Measurement Procedure Used:

APPLICABLE STANDARDS	
APPLICABLE STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C ANSI C63.10-2020+Cor 1-2023 KDB 558074 D01 15.247 Meas Guidance v05r02	Complied

This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.
The test results of this report relate only to the tested sample identified in this report.

Prepared By:	Reviewed By:	Approved By:
Allen Liu (Project Engineer)	Aaron Cheng (Supervisor)	Alex Li (Manager)

2 SUMMARY OF TEST RESULTS

FCC Part15 (15.247), Subpart C			
Standard Section	**Test Item**	**Verdict**	**Remark**
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.209 (a) 15.205 (a)	Radiated Spurious Emission	PASS	
15.247 (e)	Power Spectral Density	PASS	
15.247 (d)	Band Edge Emission	PASS	
15.247 (d)	Spurious RF Conducted Emission	PASS	
15.203	Antenna Requirement	PASS	

Remark:
1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.

3 FACILITIES AND ACCREDITATIONS

3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at
No. 24 Xinfa East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China.
The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab.	:	The Certificate Registration Number is L5516.
IC-Registration		The Certificate Registration Number is 9270A. CAB identifier:CN0074
FCC- Accredited		Test Firm Registration Number: 463705. Designation Number: CN1184
A2LA-Lab.		The Certificate Registration Number is 4298.01 This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).
Name of Firm	:	Shenzhen NTEK Testing Technology Co., Ltd.
Site Location	:	No. 24 Xinfa East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China.

3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	±2.80dB
2	RF power, conducted	±0.16dB
3	Spurious emissions, conducted	±0.21dB
4	All emissions, radiated(30MHz~1GHz)	±2.64dB
5	All emissions, radiated(1GHz~6GHz)	±2.40dB
6	All emissions, radiated(＞6GHz)	±2.52dB
7	Temperature	±0.5°C
8	Humidity	±2%
9	All emissions, radiated(9KHz~30MHz)	±6dB
10	Occupied bandwidth	±4.7dB

4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification	
Equipment	Robotic Vacuum Cleaner
Trade Mark	N/A
FCC ID	2AZ2R-M265
Model No.	M265
Family Model	M210 PRO OMNI, M2**, M2*, M2**PRO OMNI, M2*PRO OMNI
Model Difference	All models have the same circuit and RF module, except for the color and appearances (*=9-0 or A-Z, represent different color/accessories).
Operating Frequency	2402~2480 MHz
Modulation	GFSK
Number of Channels	Please refer channel list
Antenna Type	FPC Antenna
Antenna Gain	2.98 dBi
Adapter	Model: AD-0191900100US Input: 100-240V~50/60Hz 0.8A Output: 19.0V⎓1.0A 19.0W
Battery	Rated Capacity: DC 14.4V, 2900mAh, 41.76Wh Typical Capacity: DC 14.4V, 3200mAh, 46.08Wh
Power supply	DC 14.4V from battery or DC 19V from adapter
HW Version	N/A
FW Version	N/A
SW Version	N/A

Note 1: More details of EUT technical specification, please refer to the User's Manual.
Note 2: The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.

Revision History

Report No.	Version	Description	Issued Date
N26012307916E	Rev.01	Initial issue of report	Mar. 24, 2026

5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for GFSK modulation) were used for all test.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

Carrier Frequency and Channel list:

Channel	Frequency(MHz)
0	2402
1	2404
…	…
19	2440
20	2442
…	…
38	2478
39	2480

Note: fc=2402MHz+k×2MHz k=0 to 39

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Test Cases	
Test Item	Data Rate/ Modulation
AC Conducted Emission	Mode 1: normal link mode
Radiated Test Cases	Mode 1: normal link mode
	Mode 2: GFSK Tx Ch00_2402MHz_1Mbps
	Mode 3: GFSK Tx Ch19_2440MHz_1Mbps
	Mode 4: GFSK Tx Ch39_2480MHz_1Mbps
Conducted Test Cases	Mode 2: GFSK Tx Ch00_2402MHz_1Mbps
	Mode 3: GFSK Tx Ch19_2440MHz_1Mbps
	Mode 4: GFSK Tx Ch39_2480MHz_1Mbps

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. AC power line Conducted Emission was tested under maximum output power.
3. For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.
4. EUT built-in battery-powered, the battery is fully-charged.

6 SETUP OF EQUIPMENT UNDER TEST

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM

For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
AE-1	Robotic Vacuum Cleaner	M265	N/A	EUT
AE-2	Adapter	AD-0191900100US	N/A	Peripherals
AE-3	EV charge	N/A	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	DC Cable	NO	NO	1.2m
C-2	RF Cable	YES	NO	0.1m

Notes:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.
(3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4440A	MY41000130	2025.04.24	2026.04.23	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2025.04.17	2026.04.16	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2025.04.17	2026.04.16	1 year
4	Test Receiver	R&S	ESPI7	101318	2025.04.17	2026.04.16	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2025.04.17	2026.04.16	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2024.04.26	2027.04.25	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2024.05.12	2027.05.11	3 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2024.05.12	2027.05.11	3 year
9	Amplifier	EMC	EMC051835SE	980246	2025.04.17	2026.04.16	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519 B	055	2024.05.17	2027.05.16	3 year
11	Power Meter	DARE	RPR3006W	15I00041SNO84	2025.04.17	2026.04.16	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2023.05.06	2026.05.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2023.05.06	2026.05.05	3 year
14	High Test Cable(1G-40GHz)	N/A	R-03	N/A	2023.05.06	2026.05.05	3 year
15	Filter	TRILTHIC	2400MHz	29	2024.04.26	2027.04.25	3 year
16	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:
We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2025.04.17	2026.04.16	1 year
2	LISN	R&S	ENV216	101313	2025.04.16	2026.04.15	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2025.04.16	2026.04.15	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2024.04.26	2027.04.25	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2023.05.06	2026.05.05	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2023.05.06	2026.05.05	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2023.05.06	2026.05.05	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Aux Equipment & Test Cable which is scheduled for calibration every 2 or 3 years.

Measurement Software

Item	Manufacturer	Software Name	Software Version	Description
1	MWRFtest	MTS 8310 2.4GHz/5GHz	2.0	RF Conducted Test
2	Farad	EZ-EMC_RE	AIT-03A	RadiatedTest
3	Farad	EZ-EMC_CE	AIT-03A	AC Conducted Test

7 TEST REQUIREMENTS

7.1 CONDUCTED EMISSIONS TEST

7.1.1 Applicable Standard

According to FCC Part 15.207(a)

7.1.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
2. The lower limit shall apply at the transition frequencies
3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

7.1.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.1.4 Test Configuration



7.1.5 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

7.1.6 **Test Results**

EUT:	Robotic Vacuum Cleaner	Model Name :	M265
Temperature:	24.7 ℃	Relative Humidity:	54.4%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 19V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1780	35.71	20.32	56.03	64.58	-8.55	QP
0.1780	9.40	20.32	29.72	54.58	-24.86	AVG
0.2340	33.17	20.35	53.52	62.31	-8.79	QP
0.2340	6.09	20.35	26.44	52.31	-25.87	AVG
0.5100	28.54	20.43	48.97	56.00	-7.03	QP
0.5100	2.71	20.43	23.14	46.00	-22.86	AVG
1.5820	21.26	20.36	41.62	56.00	-14.38	QP
1.5820	0.48	20.36	20.84	46.00	-25.16	AVG
2.7180	21.47	20.42	41.89	56.00	-14.11	QP
2.7180	-4.66	20.42	15.76	46.00	-30.24	AVG
5.4660	24.34	20.61	44.95	60.00	-15.05	QP
5.4660	-4.75	20.61	15.86	50.00	-34.14	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	Robotic Vacuum Cleaner	Model Name ：	M265
Temperature：	24.7℃	Relative Humidity：	54.4%
Pressure：	1010hPa	Phase :	N
Test Voltage ：	DC 19V from Adapter AC 120V/60Hz	Test Mode：	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1913	9.13	20.32	29.45	53.98	-24.53	AVG
0.1940	34.10	20.32	54.42	63.86	-9.44	QP
0.2620	31.41	20.37	51.78	61.37	-9.59	QP
0.2620	4.72	20.37	25.09	51.37	-26.28	AVG
0.5860	2.10	20.44	22.54	46.00	-23.46	AVG
0.5940	25.40	20.44	45.84	56.00	-10.16	QP
0.6540	25.26	20.44	45.70	56.00	-10.30	QP
0.6540	1.62	20.44	22.06	46.00	-23.94	AVG
1.3540	0.70	20.35	21.05	46.00	-24.95	AVG
1.3700	22.31	20.35	42.66	56.00	-13.34	QP
1.8620	-0.74	20.37	19.63	46.00	-26.37	AVG
1.8700	20.35	20.37	40.72	56.00	-15.28	QP

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



7.2 RADIATED SPURIOUS EMISSION

7.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and ANSI C63.10

7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	24000/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. For Frequency 9kHz~30MHz: Distance extrapolation factor =40log(Specific distance/ test distance)(dB); Limit line=Specific limits(dBuV) + distance extrapolation factor.
For Frequency above 30MHz: Distance extrapolation factor =20log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

7.2.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.2.4 Test Configuration

(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10 and CAN/CSA-CEI/IEC CISPR 22.
This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.
Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1MHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
e. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
f. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
g. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	1 MHz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10*lg(100 [kHz]/narrower RBW [kHz]). , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

7.2.6 **Test Results**

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	Robotic Vacuum Cleaner	Model No.:	M265
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/ Mode4	Test By:	Allen Liu

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

■ Spurious Emission below 1GHz (30MHz to 1GHz)
All the modulation modes have been tested, and the worst result was report as below:

EUT:	Robotic Vacuum Cleaner	Model Name :	M265
Temperature:	25.3 ℃	Relative Humidity:	51%
Pressure:	1010hPa	Test Mode:	Mode 3 (1Mbps)
Test Voltage :	DC 14.4V		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	45.2165	8.40	19.71	28.11	40.00	-11.89	QP
V	123.6984	19.22	15.46	34.68	43.50	-8.82	QP
V	199.9855	19.47	17.73	37.20	43.50	-6.30	QP
V	300.3672	16.18	20.19	36.37	46.00	-9.63	QP
V	400.4318	13.93	22.78	36.71	46.00	-9.29	QP
V	511.8351	12.97	24.64	37.61	46.00	-8.39	QP

Remark:
Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
H	48.1625	6.11	20.18	26.29	40.00	-13.71	QP
H	125.0065	18.71	15.24	33.95	43.50	-9.55	QP
H	199.9855	14.08	17.73	31.81	43.50	-11.69	QP
H	250.3010	20.44	19.17	39.61	46.00	-6.39	QP
H	350.4766	16.85	21.68	38.53	46.00	-7.47	QP
H	451.1350	16.03	23.24	39.27	46.00	-6.73	QP

Remark:
Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



■ Spurious Emission Above 1GHz (1GHz to 18GHz)

EUT:	Robotic Vacuum Cleaner	Model No.:	M265
Temperature:	25.4 ℃	Relative Humidity:	52.4%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Allen Liu

2402

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	1233.325	51.25	-18.05	33.20	54.00	-20.80	AVG
V	1269.875	59.12	-17.86	41.26	74.00	-32.74	peak
V	1991.950	57.22	-13.78	43.44	74.00	-30.56	peak
V	2021.700	48.04	-13.29	34.75	54.00	-19.25	AVG
V	3018.325	54.41	-9.52	44.89	74.00	-29.11	peak
V	3018.325	46.75	-9.52	37.23	54.00	-16.77	AVG
V	5033.675	41.85	-6.01	35.84	54.00	-18.16	AVG
V	5059.175	50.05	-5.99	44.06	74.00	-29.94	peak
V	7360.550	50.78	-2.03	48.75	74.00	-25.25	peak
V	7360.550	46.84	-2.03	44.81	54.00	-9.19	AVG
V	14204.325	46.28	5.70	51.98	74.00	-22.02	peak
V	14249.375	38.20	5.75	43.95	54.00	-10.05	AVG

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was GFSK 1MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
H	1252.875	51.80	-17.88	33.92	54.00	-20.08	AVG
H	1307.275	59.00	-17.86	41.14	74.00	-32.86	peak
H	2007.675	55.88	-13.49	42.39	74.00	-31.61	peak
H	2050.175	47.97	-12.88	35.09	54.00	-18.91	AVG
H	3061.250	46.53	-9.60	36.93	54.00	-17.07	AVG
H	3098.225	54.40	-9.55	44.85	74.00	-29.15	peak
H	5480.350	51.26	-5.60	45.66	74.00	-28.34	peak
H	5512.225	42.78	-5.39	37.39	54.00	-16.61	AVG
H	9377.175	48.74	0.14	48.88	74.00	-25.12	peak
H	10094.575	39.19	2.12	41.31	54.00	-12.69	AVG
H	13520.925	38.25	5.41	43.66	54.00	-10.34	AVG
H	14253.200	45.53	5.75	51.28	74.00	-22.72	peak

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was GFSK 1MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



2440

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	1224.825	59.47	-18.14	41.33	74.00	-32.67	peak
V	1252.025	51.10	-17.87	33.23	54.00	-20.77	AVG
V	2028.075	55.73	-13.19	42.54	74.00	-31.46	peak
V	2054.850	47.20	-12.85	34.35	54.00	-19.65	AVG
V	2965.625	54.25	-9.88	44.37	74.00	-29.63	peak
V	3016.625	46.60	-9.51	37.09	54.00	-16.91	AVG
V	4247.000	50.58	-7.75	42.83	74.00	-31.17	peak
V	4271.650	43.17	-7.79	35.38	54.00	-18.62	AVG
V	7386.900	51.96	-2.66	49.30	74.00	-24.70	peak
V	7386.900	48.73	-2.66	46.07	54.00	-7.93	AVG
V	13674.350	46.09	5.14	51.23	74.00	-22.77	peak
V	14206.450	37.78	5.70	43.48	54.00	-10.52	AVG

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was GFSK 1MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
H	1620.500	49.86	-16.56	33.30	54.00	-20.70	AVG
H	1673.625	59.11	-16.63	42.48	74.00	-31.52	peak
H	2771.400	55.02	-10.65	44.37	74.00	-29.63	peak
H	2776.500	46.71	-10.61	36.10	54.00	-17.90	AVG
H	3580.175	54.61	-9.47	45.14	74.00	-28.86	peak
H	3580.175	46.10	-9.47	36.63	54.00	-17.37	AVG
H	5227.900	50.77	-6.12	44.65	74.00	-29.35	peak
H	5249.575	43.20	-5.90	37.30	54.00	-16.70	AVG
H	7573.475	51.29	-2.42	48.87	74.00	-25.13	peak
H	7573.475	45.88	-2.42	43.46	54.00	-10.54	AVG
H	12245.925	38.29	4.81	43.10	54.00	-10.90	AVG
H	12325.400	46.21	5.00	51.21	74.00	-22.79	peak

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was GFSK 1MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



2480

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	1279.650	50.49	-17.86	32.63	54.00	-21.37	AVG
V	1322.150	59.16	-17.88	41.28	74.00	-32.72	peak
V	2000.450	56.04	-13.59	42.45	74.00	-31.55	peak
V	2000.450	48.29	-13.59	34.70	54.00	-19.30	AVG
V	3004.725	54.11	-9.49	44.62	74.00	-29.38	peak
V	3077.400	46.25	-9.59	36.66	54.00	-17.34	AVG
V	5475.250	50.99	-5.69	45.30	74.00	-28.70	peak
V	5475.250	42.19	-5.69	36.50	54.00	-17.50	AVG
V	7413.675	52.12	-2.82	49.30	74.00	-24.70	peak
V	7413.675	48.92	-2.82	46.10	54.00	-7.90	AVG
V	13411.700	46.00	5.11	51.11	74.00	-22.89	peak
V	13454.200	37.91	5.32	43.23	54.00	-10.77	AVG

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was GFSK 1MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
H	1252.875	51.26	-17.88	33.38	54.00	-20.62	AVG
H	1320.025	59.12	-17.88	41.24	74.00	-32.76	peak
H	2031.050	55.78	-13.16	42.62	74.00	-31.38	peak
H	2050.600	48.38	-12.88	35.50	54.00	-18.50	AVG
H	2789.250	55.05	-10.50	44.55	74.00	-29.45	peak
H	2789.250	47.51	-10.50	37.01	54.00	-16.99	AVG
H	5496.075	43.01	-5.35	37.66	54.00	-16.34	AVG
H	5527.525	50.18	-5.51	44.67	74.00	-29.33	peak
H	9315.125	47.85	0.17	48.02	74.00	-25.98	peak
H	9354.650	39.90	0.03	39.93	54.00	-14.07	AVG
H	14308.875	37.89	5.78	43.67	54.00	-10.33	AVG
H	14350.525	45.72	5.67	51.39	74.00	-22.61	peak

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was GFSK 1MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



■ Spurious Emission Above 1GHz (18GHz to 25GHz)

EUT:	Robotic Vacuum Cleaner	Model No.:	M265
Temperature:	23.8 ℃	Relative Humidity:	49.5%
Test Mode:	Mode2/ Mode4	Test By:	Allen Liu

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	18329.350	59.15	-14.71	44.44	74.00	-29.56	peak
V	18329.350	50.97	-14.71	36.26	54.00	-17.74	AVG
V	19514.800	51.44	-13.45	37.99	54.00	-16.01	AVG
V	19530.375	59.05	-13.41	45.64	74.00	-28.36	peak
V	20355.500	59.23	-12.51	46.72	74.00	-27.28	peak
V	20431.100	50.67	-12.33	38.34	54.00	-15.66	AVG
V	21044.650	50.09	-12.29	37.80	54.00	-16.20	AVG
V	21091.550	57.92	-12.27	45.65	74.00	-28.35	peak
V	22446.925	50.29	-11.55	38.74	54.00	-15.26	AVG
V	22497.150	57.72	-11.49	46.23	74.00	-27.77	peak
V	23808.075	49.65	-11.45	38.20	54.00	-15.80	AVG
V	23880.000	57.88	-11.28	46.60	74.00	-27.40	peak

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was GFSK 1MHz 2402MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	18846.475	58.16	-14.38	43.78	74.00	-30.22	peak
H	18923.300	51.75	-14.22	37.53	54.00	-16.47	AVG
H	19529.500	51.49	-13.41	38.08	54.00	-15.92	AVG
H	19563.450	59.57	-13.33	46.24	74.00	-27.76	peak
H	20887.850	57.92	-12.22	45.70	74.00	-28.30	peak
H	20968.350	50.25	-12.28	37.97	54.00	-16.03	AVG
H	22013.625	58.27	-11.98	46.29	74.00	-27.71	peak
H	22047.575	50.76	-11.95	38.81	54.00	-15.19	AVG
H	22658.675	57.89	-11.68	46.21	74.00	-27.79	peak
H	22662.000	48.46	-11.68	36.78	54.00	-17.22	AVG
H	23806.150	57.82	-11.45	46.37	74.00	-27.63	peak
H	23898.200	49.44	-11.25	38.19	54.00	-15.81	AVG

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was GFSK 1MHz 2402MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



■ Radiated Spurious at Band Edges

EUT:	Robotic Vacuum Cleaner	Model No.:	M265
Temperature:	25.4 ℃	Relative Humidity:	52.4%
Test Mode:	Mode2/ Mode4	Test By:	Allen Liu

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	2400.000	55.02	-7.21	47.81	74.00	-26.19	peak
V	2400.000	44.30	-7.21	37.09	54.00	-16.91	AVG

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was GFSK 1MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	2400.000	57.00	-7.21	49.79	74.00	-24.21	peak
H	2400.000	46.66	-7.21	39.45	54.00	-14.55	AVG

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was GFSK 1MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	2483.500	55.02	-6.38	48.64	74.00	-25.36	peak
V	2483.500	43.96	-6.38	37.58	54.00	-16.42	AVG

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was GFSK 1MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	2483.500	55.54	-6.38	49.16	74.00	-24.84	peak
H	2483.500	43.98	-6.38	37.60	54.00	-16.40	AVG

Remark:
Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor
All the modulation modes have been tested, and the worst-case result was GFSK 1MHz. Only the worst-case mode reported.
Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
When PK value is lower than the Average value limit, average don't record.



7.3 6DB BANDWIDTH

7.3.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.2.

7.3.2 Conformance Limit

The minimum permissible 6dB bandwidth is 500 kHz.

7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

7.3.5 Test Procedure

The testing follows Subclause 11.8 of ANSI C63.10
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:
a) Set RBW=shall be in therange of 1% to 5% of the OBW but not less than100kHz.
b) Set the VBW≥[3xRBW]
c) Detector = Peak.
d) Trace mode = max-hold.
e) Sweep=No faster than coupled (auto) time
f) Allow the trace to stabilize.
g) Measure the maximum width of the emission by placing two markers,one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display.such that each marker is at or slightly below the“-6 dB down amplitude".If a marker is below this“-6 dB down amplitude" value,then it shall be as close as possible to this value.

7.3.6 Test Results

EUT:	Robotic Vacuum Cleaner	Model No.:	M265
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Allen Liu

Test data reference attachment.

7.4 DUTY CYCLE

7.4.1 Applicable Standard

According to KDB 558074 D01 15.247 Meas Guidance v05r02s Section 6.

7.4.2 Conformance Limit

No limit requirement.

7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

7.4.5 Test Procedure

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value. Set VBW ≥ RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if T ≤ 16.7 microseconds.)

The transmitter output is connected to the Spectrum Analyzer. We tested accroding to the zero-span measurement method, 6.0)b) in KDB 558074

The largest availble value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if T ≤ 6.25 microseconds. (50/6.25 = 8)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are > 50/T.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:
Span = Zero Span
RBW = 8MHz(the largest available value)
VBW = 8MHz (≥ RBW)
Number of points in Sweep >100
Detector function = peak
Trace = Clear write
Measure T_{total} and T_{on}
Calculate Duty Cycle = T_{on} / T_{total}

7.4.6 **Test Results**

EUT:	Robotic Vacuum Cleaner	Model No.:	M265
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Allen Liu

Test data reference attachment.

7.5 PEAK OUTPUT POWER

7.5.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.3.1.

7.5.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm). If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

7.5.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.5.4 Test Setup

Please refer to Section 6.1 of this test report.

7.5.5 Test Procedure

The testing follows Measurement Procedure Subclause 11.9.2.3.1 of ANSI C63.10
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:
Set the RBW ≧DTS bandwidth.
Set VBW =3*RBW.
Set the span ≧3*RBW
Set Sweep time = auto couple.
Set Detector = peak.
Set Trace mode = max hold.
Allow trace to fully stabilize.
Use peak marker function to determine the peak amplitude level.

7.5.6 Test Results

EUT:	Robotic Vacuum Cleaner	Model No.:	M265
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Allen Liu

Test data reference attachment.

7.6 POWER SPECTRAL DENSITY

7.6.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.4.

7.6.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

7.6.5 Test Procedure

The testing follows Measurement Procedure Subclause 11.10.2 of ANSI C63.10
This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
a) Set analyzer center frequency to DTS channel center frequency.
b) Set the span to 1.5*DTS bandwidth.
c) Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
d) Set the VBW ≥ 3 RBW.
e) Detector = peak.
f) Sweep time = auto couple.
g) Trace mode = max hold.
h) Allow trace to fully stabilize.
i) Use the peak marker function to determine the maximum amplitude level within the RBW.
j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.6.6 **Test Results**

EUT:	Robotic Vacuum Cleaner	Model No.:	M265
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Allen Liu

Test data reference attachment.

7.7 CONDUCTED BAND EDGE MEASUREMENT

7.7.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.7.

7.7.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

7.7.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.7.4 Test Setup

Please refer to Section 6.1 of this test report.

7.7.5 Test Procedure

The testing follows FCC KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.7.
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
Repeat above procedures until all measured frequencies were complete.

7.7.6 Test Results

EUT:	Robotic Vacuum Cleaner	Model No.:	M265
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode4	Test By:	Allen Liu

Test data reference attachment.

7.8 SPURIOUS RF CONDUCTED EMISSIONS

7.8.1 Conformance Limit

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

7.8.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.8.3 Test Setup

Please refer to Section 6.1 of this test report.

7.8.4 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength , and measure frequency range from 30MHz to 26.5GHz.

7.8.5 Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.

Test data reference attachment.

7.9 ANTENNA APPLICATION

7.9.1 Antenna Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.9.2 Result

The EUT antenna is permanent attached FPC Antenna (Gain: 2.98 dBi). It comply with the standard requirement.

8 TEST RESULTS

8.1 DUTY CYCLE

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	Ant1	65.95	1.81	2.5
NVNT	BLE 1M	2440	Ant1	66.22	1.79	2.44
NVNT	BLE 1M	2480	Ant1	65.6	1.83	2.5

Test Graphs

Duty Cycle NVNT BLE 1M 2402MHz Ant1



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	300.0 µs	3.22 dBm		
M2		1	520.0 µs	-17.67 dBm		
M3		1	920.0 µs	3.20 dBm		

Duty Cycle NVNT BLE 1M 2440MHz Ant1



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	230.0 µs	2.77 dBm		
M2		1	450.0 µs	-17.84 dBm		
M3		1	860.0 µs	-16.73 dBm		

Duty Cycle NVNT BLE 1M 2480MHz Ant1



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	240.0 µs	4.68 dBm		
M2		1	470.0 µs	3.10 dBm		
M3		1	870.0 µs	2.43 dBm		

8.2 MAXIMUM CONDUCTED OUTPUT POWER

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	5.55	30	Pass
NVNT	BLE 1M	2440	Ant1	4.99	30	Pass
NVNT	BLE 1M	2480	Ant1	4.72	30	Pass

Test Graphs

Power NVNT BLE 1M 2402MHz Ant1



Power NVNT BLE 1M 2440MHz Ant1



Power NVNT BLE 1M 2480MHz Ant1



8.3 -6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.64	0.5	Pass
NVNT	BLE 1M	2440	Ant1	0.657	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.587	0.5	Pass

Test Graphs

-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2440MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4799832 GHz	1.78 dBm		
M2		1	2.47969 GHz	-4.21 dBm		
M3		1	2.480277 GHz	-4.24 dBm		

8.4 OCCUPIED CHANNEL BANDWIDTH

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE 1M	2402	Ant1	1.079
NVNT	BLE 1M	2440	Ant1	1.074
NVNT	BLE 1M	2480	Ant1	1.081

Test Graphs

OBW NVNT BLE 1M 2402MHz Ant1



OBW NVNT BLE 1M 2440MHz Ant1



OBW NVNT BLE 1M 2480MHz Ant1



8.5 MAXIMUM POWER SPECTRAL DENSITY LEVEL

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-16.58	8	Pass
NVNT	BLE 1M	2440	Ant1	-12.5	8	Pass
NVNT	BLE 1M	2480	Ant1	-14.39	8	Pass

Test Graphs

PSD NVNT BLE 1M 2402MHz Ant1



PSD NVNT BLE 1M 2440MHz Ant1



PSD NVNT BLE 1M 2480MHz Ant1



8.6 **BAND EDGE**

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-61.31	-20	Pass
NVNT	BLE 1M	2480	Ant1	-57.76	-20	Pass

Test Graphs

Band Edge NVNT BLE 1M 2402MHz Ant1 Ref



Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40195 GHz	2.26 dBm		
M2		1	2.4 GHz	-45.65 dBm		
M3		1	2.39 GHz	-65.18 dBm		
M4		1	2.3427 GHz	-59.32 dBm		

Band Edge NVNT BLE 1M 2480MHz Ant1 Ref



Band Edge NVNT BLE 1M 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47995 GHz	2.28 dBm		
M2		1	2.4835 GHz	-55.67 dBm		
M3		1	2.5 GHz	-64.31 dBm		
M4		1	2.4835 GHz	-55.67 dBm		

8.7 CONDUCTED RF SPURIOUS EMISSION

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-42.08	-20	Pass
NVNT	BLE 1M	2440	Ant1	-43.07	-20	Pass
NVNT	BLE 1M	2480	Ant1	-41.48	-20	Pass

Test Graphs

Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40207 GHz	1.83 dBm		
M2		1	23.912999 GHz	-42.55 dBm		
M3		1	4.75666 GHz	-54.07 dBm		
M4		1	7.034844 GHz	-51.52 dBm		
M5		1	9.440085 GHz	-51.76 dBm		

Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.44001 GHz	-1.80 dBm		
M2		1	23.909469 GHz	-41.83 dBm		
M3		1	4.934009 GHz	-53.78 dBm		
M4		1	7.370131 GHz	-52.36 dBm		
M5		1	9.945662 GHz	-51.28 dBm		

Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47972 GHz	0.89 dBm		
M2		1	23.889176 GHz	-43.12 dBm		
M3		1	5.099005 GHz	-53.72 dBm		
M4		1	7.633949 GHz	-53.07 dBm		
M5		1	9.988014 GHz	-51.94 dBm		

END OF REPORT