

# FCC ID: 2AZ2R-PW7

## Maximum Permissible Exposure (MPE)

According to FCC 2.1091, FCC 1.1310 and KDB447498 D01 General RF Exposure Guidance V06: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

| Frequency range (MHz)                                          | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|----------------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| <b>(A) Limits for Occupational/Controlled Exposure</b>         |                               |                               |                                     |                          |
| 0.3-3.0                                                        | 614                           | 1.63                          | *100                                | 6                        |
| 3.0-30                                                         | 1842/f                        | 4.89/f                        | *900/f <sup>2</sup>                 | 6                        |
| 30-300                                                         | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300-1,500                                                      |                               |                               | f/300                               | 6                        |
| 1,500-100,000                                                  |                               |                               | 5                                   | 6                        |
| <b>(B) Limits for General Population/Uncontrolled Exposure</b> |                               |                               |                                     |                          |
| 0.3-1.34                                                       | 614                           | 1.63                          | *100                                | 30                       |
| 1.34-30                                                        | 824/f                         | 2.19/f                        | *180/f <sup>2</sup>                 | 30                       |
| 30-300                                                         | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1,500                                                      |                               |                               | f/1500                              | 30                       |
| 1,500-100,000                                                  |                               |                               | 1.0                                 | 30                       |

f = frequency in MHz \* = Plane-wave equivalent power density

## MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

## Measurement Result

BLE:

Antenna gain: -1.04dBi;

R=20cm

| Freq. (MHz) | modulation | (dBm) | power (dBm) | tune-up power |       | Gain  |         | (mW/cm <sup>2</sup> ) | (mW/cm <sup>2</sup> ) |
|-------------|------------|-------|-------------|---------------|-------|-------|---------|-----------------------|-----------------------|
|             |            |       |             | (dBm)         | (mW)  | (dBi) | Numeric |                       |                       |
| 2402        | BLE 1M     | -1.11 | -1±1        | 0             | 1.000 | -1.04 | 0.79    | 0.0002                | 1                     |
| 2440        |            | -1.71 | -1±1        | 0             | 1.000 | -1.04 | 0.79    | 0.0002                | 1                     |
| 2480        |            | -2.59 | -2±1        | -1            | 0.794 | -1.04 | 0.79    | 0.0001                | 1                     |

2.4GWIFI:

Antenna gain ANT1: -1.04dBi

R=20cm

| Channel Freq. (MHz) | modulation | conducted power | Tune-up power (dBm) | Max           |        | Antenna |         | Evaluation result | Power density |
|---------------------|------------|-----------------|---------------------|---------------|--------|---------|---------|-------------------|---------------|
|                     |            | (dBm)           |                     | tune-up power |        | Gain    |         |                   |               |
|                     |            |                 |                     | (dBm)         | (mW)   | (dBi)   | Numeric |                   |               |
| 2412                | 11b        | 14.57           | 14±1                | 15            | 31.623 | -1.04   | 0.79    | 0.0050            | 1             |
| 2437                |            | 13.71           | 13±1                | 14            | 25.119 | -1.04   | 0.79    | 0.0039            | 1             |
| 2462                |            | 12.85           | 12±1                | 13            | 19.953 | -1.04   | 0.79    | 0.0031            | 1             |
| 2412                | 11g        | 13.89           | 13±1                | 14            | 25.119 | -1.04   | 0.79    | 0.0039            | 1             |
| 2437                |            | 13.57           | 13±1                | 14            | 25.119 | -1.04   | 0.79    | 0.0039            | 1             |
| 2462                |            | 13.08           | 13±1                | 14            | 25.119 | -1.04   | 0.79    | 0.0039            | 1             |
| 2412                | 11n20      | 13.69           | 13±1                | 14            | 25.119 | -1.04   | 0.79    | 0.0039            | 1             |
| 2437                |            | 13.39           | 13±1                | 14            | 25.119 | -1.04   | 0.79    | 0.0039            | 1             |
| 2462                |            | 12.89           | 12±1                | 13            | 19.953 | -1.04   | 0.79    | 0.0031            | 1             |

## SIMULTANEOUS TRANSMISSIONS

When a number of sources at different frequencies, and/or broadband sources, contribute to the total exposure, it becomes necessary to weigh each contribution relative to the MPE. To comply with the MPE, the fraction of the MPE in terms of  $E^2$ ,  $H^2$  (or power density) incurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity. In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^n \frac{S_i}{MPE_i} \leq 1$$

Note: The BLE/WIFI 2.4G share the same ANT cannot transmit at same time.

**Conclusion:** pass

**Signature:** 

**Date:** 2026-06-10

**NAME AND TITLE** (Please print or type): alex li/Manager

---

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China