

RF Exposure

Applicant : Guangzhou Daxin Health Technology Co.,Ltd.
Room 810, No.1, Yichuang street, Huangpu District,
Address : Guangzhou (China-Singapore Guangzhou Knowledge City)
Product Name : Blood pressure monitor
Brand Mark : DAXIN
Model : M502D
Series model : M501A/M502A
Report Number : BLA-EMC-202510-A7103
FCC ID : 2AZ2X-M502D
Date of Receipt : Oct. 27,2025
Date of Test : Oct. 30,2025 to Nov. 06,2025
47 CFR Part 15, Part1.1307
Test Standard : 47 CFR Part 15, Part2.1093
KDB447498D04 General RF Exposure Guidance v01
Test Result : Pass

Compiled by: charlie

Review by: Xavier

Approved by: 131016 Zheng

Issued Date: Nov. 07,2025



BlueAsia of Technical Services(Shenzhen) Co.,Ltd.

Address: Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China



The test report is effective only with both signature and specialized stamp and The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full. The results described in this report do not represent the quality or characteristics of the sampled batch, nor do they represent any similar or identical products that are not explicitly stated.

Table of Contents

1 General information	4
1.1 General information	4
1.2 General description of EUT	4
2 Laboratory and accreditations	5
3 RF Exposure Compliance Requirement	6
3.1 Standard Requirement	6
3.2 Limits	6
3.3 Result	7

Revise Record

Version No.	Date	Description
01	Nov. 07,2025	Original

1 General information

1.1 General information

Applicant	Guangzhou Daxin Health Technology Co.,Ltd.
Address	Room 810, No.1, Yichuang street, Huangpu District, Guangzhou (China-Singapore Guangzhou Knowledge City)
Manufacturer	Guangzhou Daxin Health Technology Co.,Ltd.
Address	Room 810, No.1, Yichuang street, Huangpu District, Guangzhou (China-Singapore Guangzhou Knowledge City)

1.2 General description of EUT

Product name	Blood pressure monitor
Model no.	M502D
Series model	M501A/M502A
Differences of Series model	The Model of M501A/M502A/M502D.Their electrical circuit design layout, components used and internal wiring are identical, Only the model name,press button.backlight color.
Power supply or adapter information	4 Alkaline 1.5V batteries(AAA), DC 6.0V:DC:5V/1A,USB port
Hardware version	ePA-20B4 V1.0
Software version	ePA-20B4 V1.0
Engineer sample no.	BLA-EMC-202510-A71
<i>Note: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.</i>	

For BLE

Operation Frequency	2402MHz-2480MHz
Modulation Type	GFSK
Rate data	1Mbps
Channel Spacing	2MHz
Number of Channels	40
Antenna Type	PCB antenna
Antenna Gain	2.43dBi(Provided by customer)

2 Laboratory and accreditations

The test facility is recognized, certified, or accredited by the following organizations:

FCC	Company name:	BlueAsia of Technical Services(Shenzhen) Co., Ltd.
	Address:	Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
	A2LA Cert. No.:	5071.01
	FCC Designation No.:	CN1252
	Test Firm Registration Number:	923526
Telephone:		+86-755-28682673
FAX:		+86-755-28682673

3 RF Exposure Compliance Requirement

3.1 Standard Requirement

According to 447498 D04 Interim General RF Exposure Guidance v01

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

3.2 Limits

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

3.3 Result

Calculated Result and Limit (WORSE CASE IS AS BELOW)

Mode	Frequency (MHz)	Max Output power(dBm)	Max Output power(mW)	Ant gain (dBi)	Evaluation ERP(dBm)	Evaluation ERP(mW)	Limit of Pth(mW)	Result
BLE 1M	2402	1.828	1.52	2.43	2.108	1.62	2.79	Pass

$ERP = \text{Max Output power} + \text{Ant gain} - 2.15$

Comply with RF exposure exemption limit.

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, the result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.