FCC TEST REPORT

Client Name	:	Shenzhen Sanag Technology Co.,Ltd
Address	:	C310 Ganghong Synthetic building, NO.7 Xiangye Road, Xia LiLang Community, Nanwan Street, Longgang District, Shenzhen
Product Name	:	Wireless Sports Headset
Date	:	Jul. 12, 2021

Shenzhen Anbotek Compliance Laboratory Limited

Contents

1. General Information....5
1.1. Client Information....5
1.2. Description of Device (EUT)....5
1.3. Auxiliary Equipment Used During Test....5
1.4. Description of Test Modes....6
1.5. List of channels....7
1.6. Description Of Test Setup....8
1.7. Test Equipment List....9
1.8. Measurement Uncertainty....10
1.9. Description of Test Facility....10
2. Summary of Test Results....11
3. Conducted Emission Test....12
3.1. Test Standard and Limit....12
3.2. Test Setup....12
3.3. Test Procedure....12
3.4. Test Data....12
4. Radiation Spurious Emission and Band Edge....17
4.1. Test Standard and Limit....17
4.2. Test Setup....17
4.3. Test Procedure....18
4.4. Test Data....19
5. Maximum Peak Output Power Test....27
5.1. Test Standard and Limit....27
5.2. Test Setup....27
5.3. Test Procedure....27
5.4. Test Data....27
6. 20DB Occupy Bandwidth Test....28
6.1. Test Standard....28
6.2. Test Setup....28
6.3. Test Procedure....28
6.4. Test Data....28
7. Carrier Frequency Separation Test....29
7.1. Test Standard and Limit....29
7.2. Test Setup....29
7.3. Test Procedure....29
7.4. Test Data....29
8. Number of Hopping Channel Test....30
8.1. Test Standard and Limit....30

8.2. Test Setup....30
8.3. Test Procedure....30
8.4. Test Data....30
9. Dwell Time Test....31
9.1. Test Standard and Limit....31
9.2. Test Setup....31
9.3. Test Procedure....31
9.4. Test Data....31
10. 100kHz Bandwidth of Frequency Band Edge Requirement....32
10.1. Test Standard and Limit....32
10.2. Test Setup....32
10.3. Test Procedure....32
10.4. Test Data....32
11. Antenna Requirement....33
11.1. Test Standard and Requirement....33
11.2. Antenna Connected Construction....33
APPENDIX I -- TEST SETUP PHOTOGRAPH....34
APPENDIX II -- EXTERNAL PHOTOGRAPH....36
APPENDIX III -- INTERNAL PHOTOGRAPH....40
APPENDIX IV – Appendix Test Data....44

TEST REPORT

Applicant	:	Shenzhen Sanag Technology Co.,Ltd
Manufacturer	:	Shenzhen Sanag Technology Co.,Ltd
Product Name	:	Wireless Sports Headset
Model No.	:	A5S, A5, A5S Pro, A5S MAX, A8S
Trade Mark	:	N.A
Rating(s)	:	Input: DC 5V, 220mA (with DC 3.7V, 120mAh Battery inside)
Test Standard(s)	**:**	**FCC Part15 Subpart C, Section 15.247**
Test Method(s)	**:**	**ANSI C63.10: 2013**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of receipt	Jun. 04, 2021
Date of Test	Jun. 04 ~ Jul. 07, 2021
Prepared by	(Ella Liang)
Approved & Authorized Signer	(Kingkong Jin)

1. General Information

1.1. Client Information

Applicant	:	Shenzhen Sanag Technology Co.,Ltd
Address	:	C310 Ganghong Synthetic building, NO.7 Xiangye Road, Xia LiLang Community, Nanwan Street, Longgang District, Shenzhen
Manufacturer	:	Shenzhen Sanag Technology Co.,Ltd
Address	:	C310 Ganghong Synthetic building, NO.7 Xiangye Road, Xia LiLang Community, Nanwan Street, Longgang District, Shenzhen
Factory	:	Shenzhen Gude Electronic Technology Co., Ltd.
Address	:	101, Building 4, C Zone, Nanbiantou Industrial Zone, Dongfang Community, Songgang Street, Baoan District, Shenzhen

1.2. Description of Device (EUT)

Product Name	:	Wireless Sports Headset	
Model No.	:	A5S, A5, A5S Pro, A5S MAX, A8S (Note: All samples are the same except for model, appearance and workmanship, so we prepare "A5S" for testing only.)	
Trade Mark	:	N.A	
Test Power Supply	:	AC 120V, 60Hz for adapter / AC 240V, 60Hz for adapter DC 3.7V Battery inside	
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)	
Product Description	:	Operation Frequency:	2402~2480MHz
		Number of Channel:	79 Channels
		Modulation Type:	GFSK, π/4-DQPSK, 8DPSK
		Antenna Type:	Ceramic Antenna
		Antenna Gain(Peak):	0 dBi
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.			

1.3. Auxiliary Equipment Used During Test

Adapter	:	M/N: A2014 Input: AC 100-240V, 0.75A, 50-60Hz Output: 5V⎓3A,9V⎓2A,12V⎓3A, 20V⎓1.5A

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

TEST MODE:

Mode 1	GFSK	CH00	TX+ Charging Mode/TX Only
Mode 2		CH39	
Mode 3		CH78	
Mode 4	π/4-DQPSK	CH00	
Mode 5		CH39	
Mode 6		CH78	
Mode 7	8DPSK	CH00	
Mode 8		CH39	
Mode 9		CH78	

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

(2)The data rate was set in 1Mbps for radiated emission due to the highest RF output power.

1.5. List of channels

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
00	2402	17	2419	34	2436	51	2453	68	2470
01	2403	18	2420	35	2437	52	2454	69	2471
02	2404	19	2421	36	2438	53	2455	70	2472
03	2405	20	2422	37	2439	54	2456	71	2473
04	2406	21	2423	38	2440	55	2457	72	2474
05	2407	22	2424	39	2441	56	2458	73	2475
06	2408	23	2425	40	2442	57	2459	74	2476
07	2409	24	2426	41	2443	58	2460	75	2477
08	2410	25	2427	42	2444	59	2461	76	2478
09	2411	26	2428	43	2445	60	2462	77	2479
10	2412	27	2429	44	2446	61	2463	78	2480
11	2413	28	2430	45	2447	62	2464		
12	2414	29	2431	46	2448	63	2465		
13	2415	30	2432	47	2449	64	2466		
14	2416	31	2433	48	2450	65	2467		
15	2417	32	2434	49	2451	66	2468		
16	2418	33	2435	50	2452	67	2469		

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT built-in battery-powered, fully-charged battery use of the test battery.

1.6. Description Of Test Setup

CE



RE



1.7. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 26, 2020	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 26, 2020	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 26, 2020	1 Year
4.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Oct. 26, 2020	1 Year
5.	MAX Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 26, 2020	1 Year
6.	Preamplifier	SKET Electronic	BK1G18G30D	KD17503	Oct. 26, 2020	1 Year
7.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Nov. 02, 2020	2 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Nov. 02, 2020	2 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Nov. 02, 2020	2 Year
10.	Horn Antenna	A-INFO	LB-180400-KF	J211060628	Nov. 02, 2020	2 Year
11.	Pre-amplifier	SONOMA	310N	186860	Oct. 26, 2020	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	RF Test Control System	YIHENG	YH3000	2017430	Oct. 26, 2020	1 Year
14.	Power Sensor	DAER	RPR3006W	15I00041SN045	Oct. 26, 2020	1 Year
15.	Power Sensor	DAER	RPR3006W	15I00041SN046	Oct. 26, 2020	1 Year
16.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 26, 2020	1 Year
17.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 26, 2020	1 Year
18.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 26, 2020	1 Year
19.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 26, 2020	1 Year

1.8. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
		Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, September 30, 2020.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A, September 30, 2020.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.
1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518128

2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.247(b)(1)	Conducted Peak Output Power	PASS
15.247(a)(1)	20dB Occupied Bandwidth	PASS
15.247(a)(1)	Carrier Frequencies Separation	PASS
15.247(a)(1)	Hopping Channel Number	PASS
15.247(a)(1)	Dwell Time	PASS
15.247(d)	Band Edge	PASS
Remark: “N/A” is an abbreviation for Not Applicable.		

3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50
Remark: (1) *Decreasing linearly with logarithm of the frequency. (2) The lower limit shall apply at the transition frequency.			

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

During the test, pre-scan the GFSK, π/4-DQPSK, 8DPSK modulation, and found the GFSK modulation Low channel(TX+Charging Mode) which is the worst case, only the worst case is recorded in the report. Please to see the following pages.

Conducted Emission Test Data

Test Site: 1# Shielded Room

Operating Condition: Mode 1

Test Specification: AC 120V, 60Hz for adapter

Comment: Live Line

Tem.: 24.5℃ Hum.: 49%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1660	18.51	19.90	38.41	65.15	-26.74	QP	
2	0.5260	15.53	19.99	35.52	56.00	-20.48	QP	
3	0.5260	-0.21	19.99	19.78	46.00	-26.22	AVG	
4	0.9980	-2.25	20.12	17.87	46.00	-28.13	AVG	
5	1.0980	9.20	20.12	29.32	56.00	-26.68	QP	
6	1.4260	7.89	20.13	28.02	56.00	-27.98	QP	
7	1.6820	-2.09	20.13	18.04	46.00	-27.96	AVG	
8	2.3980	-2.73	20.15	17.42	46.00	-28.58	AVG	
9	3.5780	-2.74	20.17	17.43	46.00	-28.57	AVG	
10	3.6100	7.85	20.17	28.02	56.00	-27.98	QP	
11	4.8980	-3.08	20.20	17.12	46.00	-28.88	AVG	
12	4.9780	7.35	20.21	27.56	56.00	-28.44	QP	

Conducted Emission Test Data

Test Site: 1# Shielded Room

Operating Condition: Mode 1

Test Specification: AC 120V, 60Hz for adapter

Comment: Neutral Line

Tem.: 24.5℃ Hum.: 49%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	19.39	19.90	39.29	65.99	-26.70	QP	
2	0.2220	15.26	19.90	35.16	62.74	-27.58	QP	
3	0.5180	-0.50	19.99	19.49	46.00	-26.51	AVG	
4	0.5220	14.20	19.99	34.19	56.00	-21.81	QP	
5	0.9500	8.27	20.11	28.38	56.00	-27.62	QP	
6	0.9820	-2.23	20.12	17.89	46.00	-28.11	AVG	
7	1.4260	-2.66	20.13	17.47	46.00	-28.53	AVG	
8	1.5500	7.89	20.13	28.02	56.00	-27.98	QP	
9	1.7940	-2.25	20.14	17.89	46.00	-28.11	AVG	
10	2.3940	-2.88	20.15	17.27	46.00	-28.73	AVG	
11	4.9500	-2.62	20.21	17.59	46.00	-28.41	AVG	
12	4.9580	7.65	20.21	27.86	56.00	-28.14	QP	

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel:(86) 755-26066440 Fax: (86) 755-26014772 Email: service@anbotek.com
Hotline 400-003-0500
www.anbotek.com

Conducted Emission Test Data

Test Site: 1# Shielded Room

Operating Condition: Mode 1

Test Specification: AC 240V, 60Hz for adapter

Comment: Live Line

Tem.: 24.5℃ Hum.: 49%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.4380	13.06	19.95	33.01	57.10	-24.09	QP	
2	0.5500	17.22	19.99	37.21	56.00	-18.79	QP	
3	0.5580	-0.22	20.00	19.78	46.00	-26.22	AVG	
4	1.2260	-1.73	20.12	18.39	46.00	-27.61	AVG	
5	1.2500	11.75	20.12	31.87	56.00	-24.13	QP	
6	1.8660	10.86	20.14	31.00	56.00	-25.00	QP	
7	1.9620	-1.95	20.14	18.19	46.00	-27.81	AVG	
8	2.6900	-2.00	20.15	18.15	46.00	-27.85	AVG	
9	3.6460	10.47	20.17	30.64	56.00	-25.36	QP	
10	4.4660	-2.55	20.19	17.64	46.00	-28.36	AVG	
11	4.9500	9.60	20.21	29.81	56.00	-26.19	QP	
12	26.1460	-2.43	20.28	17.85	50.00	-32.15	AVG	

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel:(86) 755-26066440 Fax: (86) 755-26014772 Email: service@anbotek.com
Hotline 400-003-0500
www.anbotek.com

Conducted Emission Test Data

Test Site: 1# Shielded Room

Operating Condition: Mode 1

Test Specification: AC 240V, 60Hz for adapter

Comment: Neutral Line

Tem.: 24.5℃ Hum.: 49%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1580	16.25	19.90	36.15	65.56	-29.41	QP	
2	0.1740	0.63	19.90	20.53	54.76	-34.23	AVG	
3	0.2060	0.58	19.90	20.48	53.36	-32.88	AVG	
4	0.2819	11.88	19.89	31.77	60.76	-28.99	QP	
5	0.5580	16.05	20.00	36.05	56.00	-19.95	QP	
6	0.5580	0.75	20.00	20.75	46.00	-25.25	AVG	
7	1.0900	10.63	20.12	30.75	56.00	-25.25	QP	
8	1.8580	-1.91	20.14	18.23	46.00	-27.77	AVG	
9	1.8900	10.10	20.14	30.24	56.00	-25.76	QP	
10	3.6700	9.34	20.17	29.51	56.00	-26.49	QP	
11	5.2180	-2.35	20.21	17.86	50.00	-32.14	AVG	
12	28.4860	-2.59	20.27	17.68	50.00	-32.32	AVG	

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:
(1)The lower limit shall apply at the transition frequency.
(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:
RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:
RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:
RBW = 120kHz, VBW =300kHz,Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz,Set the spectrum analyzer as:
RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.
For average measurement: use duty cycle correction factor method (DCCF)
Average level = Peak level + DCCF

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

During the test, pre-scan the GFSK, π/4-DQPSK, 8DPSK modulation, and found the GFSK modulation Low channel(TX) which is the worst case, only the worst case is recorded in the report

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Test Results (30~1000MHz)

Test Mode: Mode 1

Power Source: DC 3.7V battery inside

Polarization: Vertical

Temp.(℃)/Hum.(%RH): 24.3℃/46%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	49.0145	28.87	-14.70	14.17	40.00	-25.83	QP	100	360	
2	67.2022	36.20	-18.23	17.97	40.00	-22.03	QP	100	0	
3	134.5592	33.01	-19.71	13.30	43.50	-30.20	QP	100	360	
4	337.2155	44.24	-12.36	31.88	46.00	-14.12	QP	100	0	
5	807.4291	30.64	-4.01	26.63	46.00	-19.37	QP	100	360	
6	1000.0000	29.97	0.32	30.29	54.00	-23.71	QP	100	0	

Test Results (30~1000MHz)

Test Mode: Mode 1

Power Source: DC 3.7V battery inside

Polarization: Horizontal

Temp.(℃)/Hum.(%RH): 24.3℃/46%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	42.7496	29.34	-14.61	14.73	40.00	-25.27	QP	100	360	
2	99.5281	33.74	-19.42	14.32	43.50	-29.18	QP	100	0	
3	265.6757	34.52	-17.41	17.11	46.00	-28.89	QP	100	360	
4	290.0172	39.15	-15.20	23.95	46.00	-22.05	QP	100	0	
5	719.1995	31.48	-5.71	25.77	46.00	-20.23	QP	100	360	
6	979.1804	31.34	-0.17	31.17	54.00	-22.83	QP	100	0	

Test Results (1GHz-25GHz)

Test Mode: CH00				Test channel: Lowest		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	27.85	15.27	43.12	74.00	-30.89	Vertical
7206.00	28.89	18.09	46.98	74.00	-27.02	Vertical
9608.00	29.95	23.76	53.71	74.00	-20.29	Vertical
12010.00	*			74.00		Vertical
14412.00	*			74.00		Vertical
4804.00	28.16	15.27	43.43	74.00	-30.57	Horizontal
7206.00	29.31	18.09	47.40	74.00	-26.60	Horizontal
9608.00	28.53	23.76	52.29	74.00	-21.72	Horizontal
12010.00	*			74.00		Horizontal
14412.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	17.23	15.27	32.50	54.00	-21.51	Vertical
7206.00	17.92	18.09	36.01	54.00	-17.99	Vertical
9608.00	18.97	23.76	42.73	54.00	-11.27	Vertical
12010.00	*			54.00		Vertical
14412.00	*			54.00		Vertical
4804.00	16.51	15.27	31.78	54.00	-22.22	Horizontal
7206.00	18.37	18.09	36.46	54.00	-17.54	Horizontal
9608.00	17.84	23.76	41.60	54.00	-12.41	Horizontal
12010.00	*			54.00		Horizontal
14412.00	*			54.00		Horizontal

Test Results (1GHz-25GHz)

Test Mode: CH39				Test channel: Middle		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	27.87	15.42	43.29	74.00	-30.72	Vertical
7323.00	28.74	18.02	46.76	74.00	-27.24	Vertical
9764.00	28.96	23.80	52.76	74.00	-21.24	Vertical
12205.00	*			74.00		Vertical
14646.00	*			74.00		Vertical
4882.00	27.86	15.42	43.28	74.00	-30.72	Horizontal
7323.00	29.30	18.02	47.32	74.00	-26.68	Horizontal
9764.00	28.23	23.80	52.03	74.00	-21.98	Horizontal
12205.00	*			74.00		Horizontal
14646.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	16.96	15.42	32.38	54.00	-21.63	Vertical
7323.00	18.02	18.02	36.04	54.00	-17.96	Vertical
9764.00	18.83	23.80	42.63	54.00	-11.37	Vertical
12205.00	*			54.00		Vertical
14646.00	*			54.00		Vertical
4882.00	16.42	15.42	31.84	54.00	-22.16	Horizontal
7323.00	17.93	18.02	35.95	54.00	-18.05	Horizontal
9764.00	18.35	23.80	42.15	54.00	-11.86	Horizontal
12205.00	*			54.00		Horizontal
14646.00	*			54.00		Horizontal

Test Results (1GHz-25GHz)

Test Mode: CH78				Test channel: Highest		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	28.14	15.58	43.72	74.00	-30.29	Vertical
7440.00	28.75	17.93	46.68	74.00	-27.32	Vertical
9920.00	29.51	23.83	53.34	74.00	-20.66	Vertical
12400.00	*			74.00		Vertical
14880.00	*			74.00		Vertical
4960.00	27.93	15.58	43.51	74.00	-30.49	Horizontal
7440.00	29.33	17.93	47.26	74.00	-26.74	Horizontal
9920.00	28.91	23.83	52.74	74.00	-21.27	Horizontal
12400.00	*			74.00		Horizontal
14880.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	18.08	15.58	33.66	54.00	-20.35	Vertical
7440.00	19.03	17.93	36.96	54.00	-17.04	Vertical
9920.00	19.38	23.83	43.21	54.00	-10.79	Vertical
12400.00				54.00		Vertical
14880.00				54.00		Vertical
4960.00	17.86	15.58	33.44	54.00	-20.56	Horizontal
7440.00	19.30	17.93	37.23	54.00	-16.77	Horizontal
9920.00	18.25	23.83	42.08	54.00	-11.93	Horizontal
12400.00	*			54.00		Horizontal
14880.00	*			54.00		Horizontal

Remark:

1. During the test, pre-scan the GFSK, π/4-DQPSK, 8DPSK modulation, and found the GFSK modulation is worse case, the report only record this mode.
2. Result=Reading + Factor
3. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Band Edge:

Test Mode: CH00	Test channel: Lowest
	
Average Value(Vertical)	Average Value(Horizontal)
	
Peak Value(Vertical)	Peak Value(Horizontal)

Test Mode: CH78	Test channel: Highest
	
Average Value(Vertical)	Average Value(Horizontal)
	
Peak Value(Vertical)	Peak Value(Horizontal)

Remark:

1. During the test, pre-scan the GFSK, π/4-DQPSK, 8DPSK modulation, and found the GFSK modulation is worse case, the report only record this mode.
2. Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

5. Maximum Peak Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(1)
Test Limit	1W for GFSK; 125mW for Pi/4DQPSK and 8DPSK

5.2. Test Setup



5.3. Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above,
2. Spectrum Setting:
   RBW > the 20 dB bandwidth of the emission being measured
   Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
   VBW ≥ RBW
   Sweep = auto
   Detector function = peak
   Trace = max hold

5.4. Test Data

Pass

Please refer to clause 2 of the Appendix Test Data.

6. 20DB Occupy Bandwidth Test

6.1. Test Standard

Test Standard	FCC Part15 C Section 15.247 (a)(1)

6.2. Test Setup



6.3. Test Procedure

Using the following spectrum analyzer settings:

1. Span= approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel.
2. Set the RBW ≥1% of the 20 dB bandwidth.
3. Set the VBW ≥RBW
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

6.4. Test Data

Pass

Please refer to clause 1 of the Appendix Test Data.

7. Carrier Frequency Separation Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	>25KHz or >two-thirds of the 20 dB bandwidth

7.2. Test Setup



7.3. Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer settings:

1. Span= Wide enough to capture the peaks of two adjacent channels
2. Set the RBW =approximately 30% of the channel spacing.
3. Set the VBW ≥ RBW.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

7.4. Test Data

Pass

Please refer to clause 3 of the Appendix Test Data.

8. Number of Hopping Channel Test

8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	>15 channels

8.2. Test Setup



8.3. Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer setting:

1. Span= the frequency band of operation
2. Set the RBW = less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
3. Set the VBW ≥ RBW.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

8.4. Test Data

Pass

Please refer to clause 4 of the Appendix Test Data.

9. Dwell Time Test

9.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	0.4 sec

9.2. Test Setup



9.3. Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span= zero span, centered on a hopping channel
2. Set the RBW = 1 MHz.
3. Set the VBW = 1 MHz.
4. Sweep time = as necessary to capture the entire dwell time per hopping channel.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

9.4. Test Data

Pass

Please refer to clause 5 of the Appendix Test Data.

10. 100kHz Bandwidth of Frequency Band Edge Requirement

10.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

10.2. Test Setup



10.3. Test Procedure

The EUT must have its hopping/Non-hopping function enabled. Using the following spectrum analyzer setting:

1. Set the RBW = 100kHz.
2. Set the VBW = 300kHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.

10.4. Test Data

Pass

Please refer to clause 6 of the Appendix Test Data.

11. Antenna Requirement

11.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

11.2. Antenna Connected Construction

The antenna is Ceramic Antenna which permanently attached, and the best case gain of the antenna is 0 dBi. It complies with the standard requirement.



APPENDIX I -- TEST SETUP PHOTOGRAPH

Photo of Conducted Emission Measurement



Photo of Radiation Emission Test



APPENDIX II -- EXTERNAL PHOTOGRAPH



sdnog

APPENDIX III -- INTERNAL PHOTOGRAPH




4
3
2
1
0
nbotek
roduct Safety
0 1 2 3 4 5 6


RN
RP


B-
RN
RP




SC 601025 3.7V
120mAh 210514

APPENDIX IV – Appendix Test Data