

TEST REPORT

Report No.: SHATBL2507008W02

Applicant : Jiangsu Niu Electric Technology Co., Ltd

Product Name : NIU Kick Scooter

Brand Name : NIU

Model Name : KQi 90P

FCC ID : 2AZ6G-K1YC3121

Test Standard : KDB 447498D01V06
47 CFR Part 2.1093


Date of Test : 2025.07.11~2025.09.15

Report Prepared by :




(Emily)

Report Approved by :



(Guozheng Li)

Authorized Signatory :



(Terry Yang)



TABLE OF CONTENTS

REVISION HISTORY	3
DECLARATION OF REPORT	4
1. GENERAL DESCRIPTION	5
1.1. Applicant	5
1.2. Manufacturer	5
1.3. Factory	5
1.4. General Information of EUT	6
1.5. Equipment Specification	6
1.6. Modification of EUT	7
1.7. Laboratory Information	7
1.8. Applicable Standards	7
2. RF EXPOSURE EVALUATION	8
2.1. Limits	8
2.2. Test Procedure	9
2.3. Test Result of RF Exposure Evaluation	9
2.4. Description	9

REVISION HISTORY

Rev.	Issue Date	Revisions	Revised by
00	2025.09.15	Initial Release	Guozheng Li

DECLARATION OF REPORT

1. The device has been tested by ATBL, and the test results show that the equipment under test (EUT) is in compliance with the requirements of 47 CFR Part 2.1093. And it is applicable only to the tested sample identified in the report.

2. This report shall not be reproduced except in full, without the written approval of ATBL, this document only be altered or revised by ATBL, personal only, and shall be noted in the revision of the document.

3. The general information of EUT in this report is provided by the customer or manufacture, ATBL is only responsible for the test data but not for the information provided by the customer or manufacture.

4. The results in this report is only apply to the sample as tested under conditions. The customer or manufacturer is responsible for ensuring that the additional production units of this model have the same electrical and mechanical components.

1. GENERAL DESCRIPTION

1.1. Applicant

Name : Jiangsu Niu Electric Technology Co., Ltd
Address : No.387 Changting Road, West Taihu Science and Technology Industrial Park,
Changzhou City,Jiangsu P.R. China

1.2. Manufacturer

Name : Jiangsu Niu Electric Technology Co., Ltd
Address : No.387 Changting Road, West Taihu Science and Technology Industrial Park,
Changzhou City,Jiangsu P.R. China

1.3. Factory

Name : Jiangsu Niu Electric Technology Co., Ltd
Address : No.387 Changting Road, West Taihu Science and Technology Industrial Park,
Changzhou City,Jiangsu P.R. China

1.4. General Information of EUT

General Information	
Equipment Name	NIU Kick Scooter
Brand Name	NIU
Model Name	KQi 90P
Series Model	KQi 90E, KQi1 Pro MIDNIGHT BLACK
Model Difference	Model KQi 90P is identical to KQi 90E, KQi1 Pro MIDNIGHT BLACK except for front fork.
Sample No.	202507110008002
Power Input	DC 36V
Adapter	Model:GaN65 Input:100-240Vac, 1.5A, 50/60Hz Output:5Vdc, 3A or 9Vdc, 3A or 12Vdc, 3A or 15Vdc, 3A or 20Vdc, 3.25A
Battery	Model:NIU-36W5A0 Brand:NIU Rated Voltage:36Vdc Charge Limit Voltage:42Vdc Capacity:5.2Ah
Hardware Version	KEE13S01
Software Version	KEE13Axx
Operating Temperature Range	-10℃ ~ +45℃
Connecting I/O Port(s)	Refer to the remark below.

Remark:

The above information of EUT was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.5. Equipment Specification

Equipment Specification		
Frequency Range	2402MHz - 2480MHz	
Number of Channels	40	
Carrier Frequency of Each Channel	2402 + n*2 MHz; n = 0 ~ 39	
Maximum Output Power To Antenna	☒ Bluetooth LE(1Mbps):	2.31dBm (0.0017W)
Type of Modulation	Bluetooth LE:	GFSK
Antenna Type	PIFA antenna	
Antenna Gain	-2.1 dBi	

1.6. Modification of EUT

No modifications are made to the EUT during all test items.

1.7. Laboratory Information

Company Name	:	Shanghai ATBL Technology Co., Ltd.
Address	:	Building 8, No. 160 Basheng Road, Waigaoqiao Free Trade Zone, Pudong New Area, Shanghai
Telephone	:	+86(0)21-51298625
FCC Test Firm registration Number	:	485917
A2LA Number	:	6184.01
CNAS Number	:	CNAS L14531
CAB Identifier	:	CN1306

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

Standard	Description
47 CFR Part 15.247	Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz.
47 CFR Part 2.1093	Radio frequency radiation exposure evaluation: mobile devices.
KDB 447498 D01 V06	Rf Exposure Procedures And Equipment Authorization Policies For Mobile And Portable Devices

Remark:

All test items were verified and recorded according to the standards and without any deviation during the test.

2. RF EXPOSURE EVALUATION

2.1. Limits

2.1.1 Limits According to KDB 447498 D01 General RF Exposure Guidance v06

4.3.1 Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following, and as illustrated in Appendix B:

a) $[\text{Power allowed at numeric threshold for 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)] \text{ mW}$, at 100 MHz to 1500 MHz.

b) $[\text{Power allowed at numeric threshold for 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot 10] \text{ mW}$ at > 1500 MHz and ≤ 6 GHz.

3) The 1-g and 10-g SAR test exclusion thresholds for below 100 MHz at test separation distances ≤ 50 mm are determined by:

a) The power threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1 + \log(100/f(\text{MHz}))]$ for test separation distances > 50 mm and < 200 mm.

b) The power threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for test separation distances ≤ 50 mm.

c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable. Note: when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

2.3. Test Result of RF Exposure Evaluation

Based on The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm and the formula below:

Band	Exposure Condition	Pmax	Pmax	Distance	F(GHz)	calculation result	Stand-alone Testexclusion threshold	SAR Test
		dBm	(mw)	mm				
BT	Body	3.31	2.14	5	2.440	0.668	3	NO

Conclusion: 2.4GHz SAR was not required.

2.4. Description



*****END OF THE REPORT*****