TEST REPORT

Applicant:	Shenzhen Ancheng Technology & Innovation Co.,Ltd
Address of Applicant:	Floor 3, Building B, Tian xin No.2 Industrial Park, Shang Wu, Shi Yan, Bao An, Shenzhen, China
Manufacturer:	Shenzhen Ancheng Technology & Innovation Co.,Ltd
Address of Manufacturer:	Floor 3, Building B, Tian xin No.2 Industrial Park, Shang Wu, Shi Yan, Bao An, Shenzhen, China

Equipment Under Test (EUT)

Product Name:	DLP Projector
Model No.:	Cylinder X2 Cylinder X2 Pro
Trade Mark:	ANXONIT
FCC ID:	2AZC3-X2
Applicable standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of sample receipt:	Jan. 13, 2021
Date of Test:	Jan. 13, 2021 to Feb. 05, 2021
Date of report issued:	Feb. 05, 2021
Test Result :	PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Luo

Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	*Feb. 05, 2021*	*Original*

Prepared By: ***Date:*** *Feb. 05, 2021*

Project Engineer

Check By: ***Date:*** *Feb. 05, 2021*

Reviewer

3 Contents

Page

1 COVER PAGE 1

2 VERSION 2

3 CONTENTS 3

4 TEST SUMMARY 4

5 GENERAL INFORMATION 5

5.1 GENERAL DESCRIPTION OF EUT 5
5.2 TEST MODE 7
5.3 DESCRIPTION OF SUPPORT UNITS 7
5.4 DEVIATION FROM STANDARDS 7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS 7
5.6 TEST FACILITY 7
5.7 TEST LOCATION 7
5.8 ADDITIONAL INSTRUCTIONS 7

6 TEST INSTRUMENTS LIST 8

7 TEST RESULTS AND MEASUREMENT DATA 10

7.1 ANTENNA REQUIREMENT 10
7.2 CONDUCTED EMISSIONS 11
7.3 CONDUCTED PEAK OUTPUT POWER 14
7.4 CHANNEL BANDWIDTH & 99% OCCUPY BANDWIDTH 15
7.5 POWER SPECTRAL DENSITY 19
7.6 BAND EDGES 22
7.6.1 Conducted Emission Method 22
7.6.2 Radiated Emission Method 25
7.7 SPURIOUS EMISSION 30
7.7.1 Conducted Emission Method 30
7.7.2 Radiated Emission Method 35

8 TEST SETUP PHOTO 52

9 EUT CONSTRUCTIONAL DETAILS 52

4 Test Summary

Test Item	Section	Result
Antenna requirement	FCC part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	FCC part 15.207	Pass
Conducted Peak Output Power	FCC part 15.247 (b)(3)	Pass
Channel Bandwidth & 99% OCB	FCC part 15.247 (a)(2)	Pass
Power Spectral Density	FCC part 15.247 (e)	Pass
Band Edge	FCC part 15.247(d)	Pass
Spurious Emission	FCC part 15.205/15.209	Pass

Remark: Test according to ANSI C63.10:2013 and RSS-Gen
Pass: The EUT complies with the essential requirements in the standard.

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)
Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.			

5 General Information

5.1 General Description of EUT

Product Name:	DLP Projector
Model No.:	Cylinder X2 Cylinder X2 Pro
Serial No.:	N/A
Hardware Version:	H1.0
Software Version:	S1.0
Test sample(s) ID:	GTSL202101000146-1
Sample(s) Status:	Engineer sample
Sample(s) Status	Engineer sample
Channel numbers:	802.11b/802.11g /802.11n(HT20):11 802.11n(HT40):7
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n(H20)/802.11n(HT40): Orthogonal Frequency Division Multiplexing (OFDM)
Antenna Type:	FPCB Antenna
Antenna gain:	0dBi
Power supply:	AC 100-240V, 50-60Hz, 0.35A max

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	**Frequency (MHz)**	
	802.11b/802.11g/802.11n(HT20)	802.11n(HT40)
Lowest channel	2412MHz	2422MHz
Middle channel	2437MHz	2437MHz
Highest channel	2462MHz	2452MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode

Remark: During the test, the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)
Data rate	1Mbps	6Mbps	6.5Mbps	13Mbps

5.3 Description of Support Units

None.

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383.

● **IC —Registration No.: 9079A**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A

● **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

5.7 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.
Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102
Tel: 0755-27798480
Fax: 0755-27798960

5.8 Additional Instructions

Test Software	Realtek Test Tool
Power level setup	<15dBm

6 Test Instruments list

Radiated Emission:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 02 2020	July. 01 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 25 2020	June. 24 2021
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 25 2020	June. 24 2021
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 25 2020	June. 24 2021
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 25 2020	June. 24 2021
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 25 2020	June. 24 2021
9	Coaxial Cable	GTS	N/A	GTS211	June. 25 2020	June. 24 2021
10	Coaxial cable	GTS	N/A	GTS210	June. 25 2020	June. 24 2021
11	Coaxial Cable	GTS	N/A	GTS212	June. 25 2020	June. 24 2021
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 25 2020	June. 24 2021
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 25 2020	June. 24 2021
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 25 2020	June. 24 2021
15	Band filter	Amindeon	82346	GTS219	June. 25 2020	June. 24 2021
16	Power Meter	Anritsu	ML2495A	GTS540	June. 25 2020	June. 24 2021
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 25 2020	June. 24 2021
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 25 2020	June. 24 2021
19	Splitter	Agilent	11636B	GTS237	June. 25 2020	June. 24 2021
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 25 2020	June. 24 2021
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 18 2020	Oct. 17 2021
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 18 2020	Oct. 17 2021
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 18 2020	Oct. 17 2021
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 25 2020	June. 24 2021

Conducted Emission						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.15 2019	May.14 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 25 2020	June. 24 2021
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 25 2020	June. 24 2021
4	ENV216 2-L-V-NETZNACHB.DE	ROHDE&SCHWARZ	ENV216	GTS226	June. 25 2020	June. 24 2021
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 25 2020	June. 24 2021
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 25 2020	June. 24 2021
9	ISN	SCHWARZBECK	NTFM 8158	GTD565	June. 25 2020	June. 24 2021

RF Conducted Test:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 25 2020	June. 24 2021
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 25 2020	June. 24 2021
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 25 2020	June. 24 2021
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 25 2020	June. 24 2021
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 25 2020	June. 24 2021
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 25 2020	June. 24 2021
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 25 2020	June. 24 2021
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 25 2020	June. 24 2021

General used equipment:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 25 2020	June. 24 2021
2	Barometer	ChangChun	DYM3	GTS255	June. 25 2020	June. 24 2021

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. **15.247(c) (1)(i) requirement:** (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
The antennas are FPCB permanent antenna, the best case gain of the antennas are 0dBi, reference to the appendix II for details	

7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto
Limit:	

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test setup:



Remark:
E.U.T: Equipment Under Test
LISN: Line Impedence Stabilization Network
Test table height=0.8m

Test procedure:

1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.

Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Remark: Both high and low voltages have been tested to show only the worst low voltage test data.

Measurement data
Line:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1545	21.46	12.91	34.37	55.75	-21.38	AVG	P	
2	0.1548	46.58	12.90	59.48	65.74	-6.26	QP	P	
3	0.2625	37.85	11.63	49.48	61.35	-11.87	QP	P	
4	0.2625	19.02	11.63	30.65	51.35	-20.70	AVG	P	
5	0.4335	33.81	10.85	44.66	57.19	-12.53	QP	P	
6	0.4380	27.12	10.83	37.95	47.10	-9.15	AVG	P	
7	1.5045	27.14	10.31	37.45	56.00	-18.55	QP	P	
8	1.5045	15.73	10.31	26.04	46.00	-19.96	AVG	P	
9	2.5080	27.08	10.06	37.14	56.00	-18.86	QP	P	
10	2.5080	16.41	10.06	26.47	46.00	-19.53	AVG	P	
11	11.5395	31.47	8.68	40.15	60.00	-19.85	QP	P	
12	11.5395	19.05	8.68	27.73	50.00	-22.27	AVG	P	

Neutral:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1545	45.43	12.91	58.34	65.75	-7.41	QP	P	
2	0.1545	20.77	12.91	33.68	55.75	-22.07	AVG	P	
3	0.4020	15.80	10.99	26.79	47.81	-21.02	AVG	P	
4	0.4065	32.56	10.97	43.53	57.72	-14.19	QP	P	
5	1.3290	6.11	10.36	16.47	46.00	-29.53	AVG	P	
6	1.3335	25.93	10.36	36.29	56.00	-19.71	QP	P	
7	5.5185	24.17	8.63	32.80	60.00	-27.20	QP	P	
8	5.5185	11.13	8.63	19.76	50.00	-30.24	AVG	P	
9	12.5475	35.09	8.82	43.91	60.00	-16.09	QP	P	
10	12.5475	20.68	8.82	29.50	50.00	-20.50	AVG	P	
11	16.5615	24.58	9.38	33.96	60.00	-26.04	QP	P	
12	16.5615	15.65	9.38	25.03	50.00	-24.97	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss

7.3 Conducted Peak Output Power

Test Requirement :	FCC Part15 C Section 15.247 (b)(3)
Test Method :	KDB558074 D01 DTS Meas Guidance v05or02
Limit:	30dBm
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test CH	Peak Output Power (dBm)				Limit(dBm)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	12.805	11.632	11.221	10.920	30.00	Pass
Middle	12.617	11.418	11.173	10.886		
Highest	12.525	11.369	11.182	10.732		

7.4 Channel Bandwidth & 99% Occupy Bandwidth

Test Requirement :	FCC Part15 C Section 15.247 (a)(2)
Test Method :	KDB558074 D01 DTS Meas Guidance v05or02
Limit:	>500KHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test CH	Channel Bandwidth (MHz)				Limit(KHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	9.019	15.10	15.05	35.09	>500	Pass
Middle	9.054	15.52	15.98	35.08		
Highest	8.991	15.03	15.04	35.07		

Test CH	99% Occupy Bandwidth (MHz)				Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)	
Lowest	14.009	16.303	17.426	35.699	Pass
Middle	13.996	16.309	17.471	35.735	
Highest	13.938	16.298	17.471	35.756	

Test plot as follows:

802.11b		802.11g	

Lowest channel





Middle channel





Highest channel





802.11n(HT20)		802.11n(HT40)	

Lowest channel





Middle channel





Highest channel





7.5 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D01 DTS Meas Guidance v05or02
Limit:	8dBm/3kHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test CH	Power Spectral Density (dBm/3kHz)				Limit (dBm/3kHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	-21.024	-27.682	-26.634	-32.543	8.00	Pass
Middle	-21.354	-27.351	-26.387	-33.860		
Highest	-22.133	-28.149	-27.619	-32.317		

Test plot as follows:

802.11b		802.11g	

Lowest channel





Middle channel





Highest channel





802.11n(HT20)		802.11n(HT40)	

Lowest channel





Middle channel





Highest channel





7.6 Band edges

7.6.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D01 DTS Meas Guidance v05or02
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Test plot as follows:

Test mode:	802.11b



Lowest channel



Highest channel

Test mode:	802.11g



Lowest channel



Highest channel

Test mode:	802.11n(HT20)



Lowest channel



Highest channel

Test mode:	802.11n(HT40)



Lowest channel



Highest channel

7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205
Test Method:	ANSI C63.10: 2013
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
Above 1GHz	Peak	1MHz	3MHz	Peak
	Average	1MHz	3MHz	Average

Limit:

Frequency	Limit (dBuV/m @3m)	Value
Above 1GHz	54.00	Average
	74.00	Peak

Test setup:



Test Procedure:

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
7. The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test worst case mode is recorded in the report.

Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement data:

Test mode:	802.11b	Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	61.23	20.15	7.42	38.06	50.74	74.00	-23.26	Horizontal
2400.00	51.28	20.15	7.42	38.06	40.79	74.00	-33.21	Horizontal
2390.00	60.35	20.15	7.42	38.06	49.86	74.00	-24.14	Vertical
2400.00	51.98	20.15	7.42	38.06	41.49	74.00	-32.51	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	52.33	20.15	7.42	38.06	41.84	54.00	-12.16	Horizontal
2400.00	44.58	20.15	7.42	38.06	34.09	54.00	-19.91	Horizontal
2390.00	51.87	20.15	7.42	38.06	41.38	54.00	-12.62	Vertical
2400.00	45.67	20.15	7.42	38.06	35.18	54.00	-18.82	Vertical

Test mode:	802.11b	Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	61.23	20.54	7.45	38.17	51.05	74.00	-22.95	Horizontal
2485.50	51.69	20.54	7.45	38.17	41.51	74.00	-32.49	Horizontal
2483.50	59.63	20.54	7.45	38.20	49.42	74.00	-24.58	Vertical
2485.50	50.16	20.54	7.45	38.20	39.95	74.00	-34.05	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	54.21	20.54	7.45	38.17	44.03	54.00	-9.97	Horizontal
2485.50	42.69	20.54	7.45	38.17	32.51	54.00	-21.49	Horizontal
2483.50	53.06	20.54	7.45	38.20	42.85	54.00	-11.15	Vertical
2485.50	42.69	20.54	7.45	38.20	32.48	54.00	-21.52	Vertical

Test mode:	802.11g	Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	62.05	20.15	7.42	38.06	51.56	74.00	-22.44	Horizontal
2400.00	54.63	20.15	7.42	38.06	44.14	74.00	-29.86	Horizontal
2390.00	63.30	20.15	7.42	38.06	52.81	74.00	-21.19	Vertical
2400.00	51.17	20.15	7.42	38.06	40.68	74.00	-33.32	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	53.22	20.15	7.42	38.06	42.73	54.00	-11.27	Horizontal
2400.00	45.38	20.15	7.42	38.06	34.89	54.00	-19.11	Horizontal
2390.00	54.29	20.15	7.42	38.06	43.80	54.00	-10.20	Vertical
2400.00	42.18	20.15	7.42	38.06	31.69	54.00	-22.31	Vertical

Test mode:	802.11g	Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	58.79	20.54	7.45	38.17	48.61	74.00	-25.39	Horizontal
2485.50	54.02	20.54	7.45	38.17	43.84	74.00	-30.16	Horizontal
2483.50	60.03	20.54	7.45	38.20	49.82	74.00	-24.18	Vertical
2485.50	52.17	20.54	7.45	38.20	41.96	74.00	-32.04	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	50.26	20.54	7.45	38.17	40.08	54.00	-13.92	Horizontal
2485.50	46.25	20.54	7.45	38.17	36.07	54.00	-17.93	Horizontal
2483.50	52.06	20.54	7.45	38.20	41.85	54.00	-12.15	Vertical
2485.50	42.28	20.54	7.45	38.20	32.07	54.00	-21.93	Vertical

Test mode:	802.11n(HT20)	Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	60.14	20.15	7.42	38.06	49.65	74.00	-24.35	Horizontal
2400.00	51.36	20.15	7.42	38.06	40.87	74.00	-33.13	Horizontal
2390.00	62.22	20.15	7.42	38.06	51.73	74.00	-22.27	Vertical
2400.00	53.07	20.15	7.42	38.06	42.58	74.00	-31.42	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	52.22	20.15	7.42	38.06	41.73	54.00	-12.27	Horizontal
2400.00	43.28	20.15	7.42	38.06	32.79	54.00	-21.21	Horizontal
2390.00	54.27	20.15	7.42	38.06	43.78	54.00	-10.22	Vertical
2400.00	45.24	20.15	7.42	38.06	34.75	54.00	-19.25	Vertical

Test mode:	802.11n(HT20)	Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	59.09	20.54	7.45	38.17	48.91	74.00	-25.09	Horizontal
2485.50	54.18	20.54	7.45	38.17	44.00	74.00	-30.00	Horizontal
2483.50	62.29	20.54	7.45	38.20	52.08	74.00	-21.92	Vertical
2485.50	53.13	20.54	7.45	38.20	42.92	74.00	-31.08	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	50.24	20.54	7.45	38.17	40.06	54.00	-13.94	Horizontal
2485.50	45.35	20.54	7.45	38.17	35.17	54.00	-18.83	Horizontal
2483.50	53.49	20.54	7.45	38.20	43.28	54.00	-10.72	Vertical
2485.50	45.28	20.54	7.45	38.20	35.07	54.00	-18.93	Vertical

Test mode:	802.11n(HT40)	Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	60.6	20.15	7.42	38.06	50.11	74.00	-23.89	Horizontal
2400.00	52.08	20.15	7.42	38.06	41.59	74.00	-32.41	Horizontal
2390.00	61.18	20.15	7.42	38.06	50.69	74.00	-23.31	Vertical
2400.00	51.12	20.15	7.42	38.06	40.63	74.00	-33.37	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	52.06	20.15	7.42	38.06	41.57	54.00	-12.43	Horizontal
2400.00	42.28	20.15	7.42	38.06	31.79	54.00	-22.21	Horizontal
2390.00	53.27	20.15	7.42	38.06	42.78	54.00	-11.22	Vertical
2400.00	43.06	20.15	7.42	38.06	32.57	54.00	-21.43	Vertical

Test mode:	802.11n(HT40)	Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	60.07	20.54	7.45	38.17	49.89	74.00	-24.11	Horizontal
2485.50	52.25	20.54	7.45	38.17	42.07	74.00	-31.93	Horizontal
2483.50	63.33	20.54	7.45	38.20	53.12	74.00	-20.88	Vertical
2485.50	50.49	20.54	7.45	38.20	40.28	74.00	-33.72	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	52.24	20.54	7.45	38.17	42.06	54.00	-11.94	Horizontal
2485.50	42.16	20.54	7.45	38.17	31.98	54.00	-22.02	Horizontal
2483.50	54.27	20.54	7.45	38.20	44.06	54.00	-9.94	Vertical
2485.50	42.06	20.54	7.45	38.20	31.85	54.00	-22.15	Vertical

Remarks:

1. *Only the worst case Main Antenna test data.*
2. *The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.*
3. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
4. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

7.7 Spurious Emission

7.7.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D01 DTS Meas Guidance v05or02
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Test plot as follows:

802.11b

Lowest channel



30MHz~26.5GHz

Middle channel





30MHz~26.5GHz

Highest channel



30MHz~26.5GHz

802.11g

Lowest channel



30MHz~26.5GHz

Middle channel





30MHz~26.5GHz

Highest channel





30MHz~26.5GHz

802.11n(HT20)

Lowest channel



30MHz~26.5GHz

Middle channel





30MHz~26.5GHz

Highest channel



30MHz~26.5GHz

802.11n(HT40)

Lowest channel





30MHz~26.5GHz

Middle channel



30MHz~26.5GHz

Highest channel



30MHz~26.5GHz

7.7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10: 2013
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m

Receiver setup:

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Limit:

Frequency	Limit (uV/m)	Value	Measurement Distance
0.009MHz-0.490MHz	2400/F(KHz)	QP	300m
0.490MHz-1.705MHz	24000/F(KHz)	QP	300m
1.705MHz-30MHz	30	QP	30m
30MHz-88MHz	100	QP	3m
88MHz-216MHz	150	QP	
216MHz-960MHz	200	QP	
960MHz-1GHz	500	QP	
Above 1GHz	500	Average	
	5000	Peak	

Test setup:

For radiated emissions from 9kHz to 30MHz



For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details

Test voltage:	AC120V 60Hz					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Remarks:

1. *Only the worst case Main Antenna test data.*
2. *Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.*

Measurement data:

■ **9kHz~30MHz**

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

■ **Below 1GHz**

Pre-scan all test modes, found worst case at 802.11b 2462MHz, and so only show the test result of 802.11b 2462MHz record the report.

Horizontal:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	60.4917	38.15	-14.36	23.79	40.00	-16.21	QP	125	125		
2	75.9772	42.95	-18.42	24.53	40.00	-15.47	QP	138	204		
3	85.1486	43.95	-19.84	24.11	40.00	-15.89	QP	114	128		
4	162.8959	41.11	-17.05	24.06	43.50	-19.44	QP	174	55		
5	192.4183	47.92	-19.37	28.55	43.50	-14.95	QP	125	17		
6	278.0668	43.43	-16.24	27.19	46.00	-18.81	QP	117	35		

Vertical:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	35.7490	51.15	-17.49	33.66	40.00	-6.34	QP	110	56		
2	41.1319	46.70	-16.91	29.79	40.00	-10.21	QP	105	124		
3	62.1037	48.38	-18.53	29.85	40.00	-10.15	QP	108	28		
4	78.0019	53.85	-21.36	32.49	40.00	-7.51	QP	112	33		
5	87.4175	52.76	-21.59	31.17	40.00	-8.83	QP	109	148		
6	164.3300	49.03	-20.75	28.28	40.00	-11.72	QP	105	254		

■ **Above 1GHz**

Test mode:	802.11b	Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	66.01	25.66	7.85	39.55	59.97	74.00	-14.03	Vertical
7236.00	66.12	24.55	7.52	38.33	59.86	74.00	-14.14	Vertical
9648.00	52.26	25.59	8.75	38.25	48.35	74.00	-25.65	Vertical
12060.00	52.09	26.59	9.72	38.33	50.07	74.00	-23.93	Vertical
4824.00	64.28	25.66	7.85	39.55	58.24	74.00	-15.76	Horizontal
7236.00	67.24	24.55	7.52	38.33	60.98	74.00	-13.02	Horizontal
9648.00	53.21	25.59	8.75	38.25	49.30	74.00	-24.70	Horizontal
12060.00	52.09	26.59	9.72	38.33	50.07	74.00	-23.93	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	56.18	25.66	7.85	39.55	50.14	54.00	-3.86	Vertical
7236.00	58.06	24.55	7.52	38.33	51.8	54.00	-2.2	Vertical
9648.00	44.02	25.59	8.75	38.25	40.11	54.00	-13.89	Vertical
12060.00	43.16	26.59	9.72	38.33	41.14	54.00	-12.86	Vertical
4824.00	56.25	25.66	7.85	39.55	50.21	54.00	-3.79	Horizontal
7236.00	58.23	24.55	7.52	38.33	51.97	54.00	-2.03	Horizontal
9648.00	46.13	25.59	8.75	38.25	42.22	54.00	-11.78	Horizontal
12060.00	44.23	26.59	9.72	38.33	42.21	54.00	-11.79	Horizontal

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11b	Test channel:	Middle

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	65.06	25.45	7.57	38.89	59.19	74.00	-14.81	Vertical
7311.00	50.30	24.78	7.35	38.78	43.65	74.00	-30.35	Vertical
9748.00	56.17	25.69	8.57	38.57	51.86	74.00	-22.14	Vertical
12185.00	50.10	26.11	9.62	38.78	47.05	74.00	-26.95	Vertical
4874.00	56.26	25.45	7.57	38.89	50.39	74.00	-23.61	Horizontal
7311.00	43.14	24.78	7.35	38.78	36.49	74.00	-37.51	Horizontal
9748.00	48.01	25.69	8.57	38.57	43.70	74.00	-30.30	Horizontal
12185.00	42.06	26.11	9.62	38.78	39.01	74.00	-34.99	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	55.32	25.45	7.57	38.89	49.45	54.00	-4.55	Vertical
7311.00	42.25	24.78	7.35	38.78	35.60	54.00	-18.40	Vertical
9748.00	48.24	25.69	8.57	38.57	43.93	54.00	-10.07	Vertical
12185.00	42.15	26.11	9.62	38.78	39.10	54.00	-14.90	Vertical
4874.00	48.36	25.45	7.57	38.89	42.49	54.00	-11.51	Horizontal
7311.00	36.28	24.78	7.35	38.78	29.63	54.00	-24.37	Horizontal
9748.00	40.23	25.69	8.57	38.57	35.92	54.00	-18.08	Horizontal
12185.00	34.26	26.11	9.62	38.78	31.21	54.00	-22.79	Horizontal

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11b	Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	63.21	25.45	7.46	38.75	57.37	74.00	-16.63	Vertical
7386.00	57.10	24.78	7.82	38.65	51.05	74.00	-22.95	Vertical
9848.00	52.05	26.47	8.35	38.58	48.29	74.00	-25.71	Vertical
12310.00	46.28	26.54	9.25	38.66	43.41	74.00	-30.59	Vertical
4924.00	59.12	25.45	7.46	38.75	53.28	74.00	-20.72	Horizontal
7386.00	56.12	24.78	7.82	38.65	50.07	74.00	-23.93	Horizontal
9848.00	53.18	26.47	8.35	38.58	49.42	74.00	-24.58	Horizontal
12310.00	47.27	26.54	9.25	38.66	44.40	74.00	-29.60	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	54.23	25.45	7.46	38.75	48.39	54.00	-5.61	Vertical
7386.00	49.17	24.78	7.82	38.65	43.12	54.00	-10.88	Vertical
9848.00	44.12	26.47	8.35	38.58	40.36	54.00	-13.64	Vertical
12310.00	37.33	26.54	9.25	38.66	34.46	54.00	-19.54	Vertical
4924.00	52.06	25.45	7.46	38.75	46.22	54.00	-7.78	Horizontal
7386.00	49.11	24.78	7.82	38.65	43.06	54.00	-10.94	Horizontal
9848.00	45.27	26.47	8.35	38.58	41.51	54.00	-12.49	Horizontal
12310.00	41.13	26.54	9.25	38.66	38.26	54.00	-15.74	Horizontal

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11g	Test channel:	lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	62.05	25.66	7.85	39.55	56.01	74.00	-17.99	Vertical
7236.00	58.13	24.55	7.52	38.33	51.87	74.00	-22.13	Vertical
9648.00	52.12	25.59	8.75	38.25	48.21	74.00	-25.79	Vertical
12060.00	46.23	26.59	9.72	38.33	44.21	74.00	-29.79	Vertical
4824.00	60.02	25.66	7.85	39.55	53.98	74.00	-20.02	Horizontal
7236.00	57.23	24.55	7.52	38.33	50.97	74.00	-23.03	Horizontal
9648.00	51.14	25.59	8.75	38.25	47.23	74.00	-26.77	Horizontal
12060.00	46.36	26.59	9.72	38.33	44.34	74.00	-29.66	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	53.13	25.66	7.85	39.55	47.09	54.00	-6.91	Vertical
7236.00	47.36	24.55	7.52	38.33	41.10	54.00	-12.90	Vertical
9648.00	44.27	25.59	8.75	38.25	40.36	54.00	-13.64	Vertical
12060.00	37.33	26.59	9.72	38.33	35.31	54.00	-18.69	Vertical
4824.00	50.22	25.66	7.85	39.55	44.18	54.00	-9.82	Horizontal
7236.00	49.23	24.55	7.52	38.33	42.97	54.00	-11.03	Horizontal
9648.00	45.06	25.59	8.75	38.25	41.15	54.00	-12.85	Horizontal
12060.00	41.15	26.59	9.72	38.33	39.13	54.00	-14.87	Horizontal

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11g	Test channel:	Middle

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	60.23	25.45	7.57	38.89	54.36	74.00	-19.64	Vertical
7311.00	57.12	24.78	7.35	38.78	50.47	74.00	-23.53	Vertical
9748.00	53.22	25.69	8.57	38.57	48.91	74.00	-25.09	Vertical
12185.00	47.11	26.11	9.62	38.78	44.06	74.00	-29.94	Vertical
4874.00	60.05	25.45	7.57	38.89	54.18	74.00	-19.82	Horizontal
7311.00	57.32	24.78	7.35	38.78	50.67	74.00	-23.33	Horizontal
9748.00	52.16	25.69	8.57	38.57	47.85	74.00	-26.15	Horizontal
12185.00	47.24	26.11	9.62	38.78	44.19	74.00	-29.81	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	53.07	25.45	7.57	38.89	47.20	54.00	-6.80	Vertical
7311.00	48.33	24.78	7.35	38.78	41.68	54.00	-12.32	Vertical
9748.00	45.15	25.69	8.57	38.57	40.84	54.00	-13.16	Vertical
12185.00	38.17	26.11	9.62	38.78	35.12	54.00	-18.88	Vertical
4874.00	51.14	25.45	7.57	38.89	45.27	54.00	-8.73	Horizontal
7311.00	49.28	24.78	7.35	38.78	42.63	54.00	-11.37	Horizontal
9748.00	45.17	25.69	8.57	38.57	40.86	54.00	-13.14	Horizontal
12185.00	42.12	26.11	9.62	38.78	39.07	54.00	-14.93	Horizontal

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11g	Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	61.14	25.45	7.46	38.75	55.30	74.00	-18.70	Vertical
7386.00	57.22	24.78	7.82	38.65	51.17	74.00	-22.83	Vertical
9848.00	53.31	26.47	8.35	38.58	49.55	74.00	-24.45	Vertical
12310.00	48.16	26.54	9.25	38.66	45.29	74.00	-28.71	Vertical
4924.00	60.03	25.45	7.46	38.75	54.19	74.00	-19.81	Horizontal
7386.00	57.21	24.78	7.82	38.65	51.16	74.00	-22.84	Horizontal
9848.00	52.14	26.47	8.35	38.58	48.38	74.00	-25.62	Horizontal
12310.00	47.35	26.54	9.25	38.66	44.48	74.00	-29.52	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	53.12	25.45	7.46	38.75	47.28	54.00	-6.72	Vertical
7386.00	48.36	24.78	7.82	38.65	42.31	54.00	-11.69	Vertical
9848.00	45.22	26.47	8.35	38.58	41.46	54.00	-12.54	Vertical
12310.00	39.07	26.54	9.25	38.66	36.2	54.00	-17.80	Vertical
4924.00	51.17	25.45	7.46	38.75	45.33	54.00	-8.67	Horizontal
7386.00	49.27	24.78	7.82	38.65	43.22	54.00	-10.78	Horizontal
9848.00	46.03	26.47	8.35	38.58	42.27	54.00	-11.73	Horizontal
12310.00	43.15	26.54	9.25	38.66	40.28	54.00	-13.72	Horizontal

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11n(HT20)	Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	60.23	25.66	7.85	39.55	54.19	74.00	-19.81	Vertical
7236.00	58.33	24.55	7.52	38.33	52.07	74.00	-21.93	Vertical
9648.00	54.17	25.59	8.75	38.25	50.26	74.00	-23.74	Vertical
12060.00	48.23	26.59	9.72	38.33	46.21	74.00	-27.79	Vertical
4824.00	60.05	25.66	7.85	39.55	54.01	74.00	-19.99	Horizontal
7236.00	57.32	24.55	7.52	38.33	51.06	74.00	-22.94	Horizontal
9648.00	53.13	25.59	8.75	38.25	49.22	74.00	-24.78	Horizontal
12060.00	48.22	26.59	9.72	38.33	46.20	74.00	-27.80	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	53.26	25.66	7.85	39.55	47.22	54.00	-6.78	Vertical
7236.00	48.33	24.55	7.52	38.33	42.07	54.00	-11.93	Vertical
9648.00	45.35	25.59	8.75	38.25	41.44	54.00	-12.56	Vertical
12060.00	39.17	26.59	9.72	38.33	37.15	54.00	-16.85	Vertical
4824.00	52.12	25.66	7.85	39.55	46.08	54.00	-7.92	Horizontal
7236.00	49.06	24.55	7.52	38.33	42.80	54.00	-11.20	Horizontal
9648.00	46.18	25.59	8.75	38.25	42.27	54.00	-11.73	Horizontal
12060.00	44.13	26.59	9.72	38.33	42.11	54.00	-11.89	Horizontal

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11n(HT20)	Test channel:	Middle

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	60.03	25.45	7.57	38.89	54.16	74.00	-19.84	Vertical
7311.00	57.36	24.78	7.35	38.78	50.71	74.00	-23.29	Vertical
9748.00	55.12	25.69	8.57	38.57	50.81	74.00	-23.19	Vertical
12185.00	48.23	26.11	9.62	38.78	45.18	74.00	-28.82	Vertical
4874.00	60.02	25.45	7.57	38.89	54.15	74.00	-19.85	Horizontal
7311.00	57.34	24.78	7.35	38.78	50.69	74.00	-23.31	Horizontal
9748.00	53.16	25.69	8.57	38.57	48.85	74.00	-25.15	Horizontal
12185.00	47.33	26.11	9.62	38.78	44.28	74.00	-29.72	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	53.06	25.45	7.57	38.89	47.19	54.00	-6.81	Vertical
7311.00	49.15	24.78	7.35	38.78	42.50	54.00	-11.50	Vertical
9748.00	44.28	25.69	8.57	38.57	39.97	54.00	-14.03	Vertical
12185.00	39.28	26.11	9.62	38.78	36.23	54.00	-17.77	Vertical
4874.00	52.26	25.45	7.57	38.89	46.39	54.00	-7.61	Horizontal
7311.00	49.35	24.78	7.35	38.78	42.7	54.00	-11.3	Horizontal
9748.00	46.26	25.69	8.57	38.57	41.95	54.00	-12.05	Horizontal
12185.00	44.36	26.11	9.62	38.78	41.31	54.00	-12.69	Horizontal

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11n(HT20)	Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	60.05	25.45	7.46	38.75	54.21	74.00	-19.79	Vertical
7386.00	58.14	24.78	7.82	38.65	52.09	74.00	-21.91	Vertical
9848.00	56.32	26.47	8.35	38.58	52.56	74.00	-21.44	Vertical
12310.00	48.55	26.54	9.25	38.66	45.68	74.00	-28.32	Vertical
4924.00	60.15	25.45	7.46	38.75	54.31	74.00	-19.69	Horizontal
7386.00	59.17	24.78	7.82	38.65	53.12	74.00	-20.88	Horizontal
9848.00	54.06	26.47	8.35	38.58	50.30	74.00	-23.70	Horizontal
12310.00	48.36	26.54	9.25	38.66	45.49	74.00	-28.51	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	53.12	25.45	7.46	38.75	47.28	54.00	-6.72	Vertical
7386.00	49.13	24.78	7.82	38.65	43.08	54.00	-10.92	Vertical
9848.00	45.03	26.47	8.35	38.58	41.27	54.00	-12.73	Vertical
12310.00	39.18	26.54	9.25	38.66	36.31	54.00	-17.69	Vertical
4924.00	51.17	25.45	7.46	38.75	45.33	54.00	-8.67	Horizontal
7386.00	49.28	24.78	7.82	38.65	43.23	54.00	-10.77	Horizontal
9848.00	47.23	26.47	8.35	38.58	43.47	54.00	-10.53	Horizontal
12310.00	44.21	26.54	9.25	38.66	41.34	54.00	-12.66	Horizontal

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11n(HT40)	Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4844.00	60.25	25.66	7.85	39.55	54.21	74.00	-19.79	Vertical
7266.00	58.34	24.55	7.52	38.33	52.08	74.00	-21.92	Vertical
9688.00	55.58	25.59	8.75	38.25	51.67	74.00	-22.33	Vertical
12110.00	49.25	26.59	9.72	38.33	47.23	74.00	-26.77	Vertical
4844.00	60.03	25.66	7.85	39.55	53.99	74.00	-20.01	Horizontal
7266.00	59.23	24.55	7.52	38.33	52.97	74.00	-21.03	Horizontal
9688.00	54.24	25.59	8.75	38.25	50.33	74.00	-23.67	Horizontal
12110.00	49.05	26.59	9.72	38.33	47.03	74.00	-26.97	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4844.00	53.23	25.66	7.85	39.55	47.19	54.00	-6.81	Vertical
7266.00	49.18	24.55	7.52	38.33	42.92	54.00	-11.08	Vertical
9688.00	45.25	25.59	8.75	38.25	41.34	54.00	-12.66	Vertical
12110.00	38.25	26.59	9.72	38.33	36.23	54.00	-17.77	Vertical
4844.00	51.16	25.66	7.85	39.55	45.12	54.00	-8.88	Horizontal
7266.00	49.26	24.55	7.52	38.33	43.00	54.00	-11.00	Horizontal
9688.00	46.33	25.59	8.75	38.25	42.42	54.00	-11.58	Horizontal
12110.00	45.08	26.59	9.72	38.33	43.06	54.00	-10.94	Horizontal

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11n(HT40)	Test channel:	Middle

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	60.03	25.45	7.57	38.89	54.16	74.00	-19.84	Vertical
7311.00	58.13	24.78	7.35	38.78	51.48	74.00	-22.52	Vertical
9748.00	55.21	25.69	8.57	38.57	50.90	74.00	-23.10	Vertical
12185.00	48.23	26.11	9.62	38.78	45.18	74.00	-28.82	Vertical
4874.00	60.05	25.45	7.57	38.89	54.18	74.00	-19.82	Horizontal
7311.00	58.13	24.78	7.35	38.78	51.48	74.00	-22.52	Horizontal
9748.00	54.24	25.69	8.57	38.57	49.93	74.00	-24.07	Horizontal
12185.00	48.35	26.11	9.62	38.78	45.30	74.00	-28.70	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	53.36	25.45	7.57	38.89	47.49	54.00	-6.51	Vertical
7311.00	48.26	24.78	7.35	38.78	41.61	54.00	-12.39	Vertical
9748.00	45.21	25.69	8.57	38.57	40.90	54.00	-13.10	Vertical
12185.00	39.29	26.11	9.62	38.78	36.24	54.00	-17.76	Vertical
4874.00	52.17	25.45	7.57	38.89	46.30	54.00	-7.70	Horizontal
7311.00	49.08	24.78	7.35	38.78	42.43	54.00	-11.57	Horizontal
9748.00	47.03	25.69	8.57	38.57	42.72	54.00	-11.28	Horizontal
12185.00	44.06	26.11	9.62	38.78	41.01	54.00	-12.99	Horizontal

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11n(HT40)	Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4904.00	60.22	25.45	7.46	38.75	54.38	74.00	-19.62	Vertical
7356.00	58.24	24.78	7.82	38.65	52.19	74.00	-21.81	Vertical
9808.00	55.03	26.47	8.35	38.58	51.27	74.00	-22.73	Vertical
12260.00	48.13	26.54	9.25	38.66	45.26	74.00	-28.74	Vertical
4904.00	60.05	25.45	7.46	38.75	54.21	74.00	-19.79	Horizontal
7356.00	57.24	24.78	7.82	38.65	51.19	74.00	-22.81	Horizontal
9808.00	53.32	26.47	8.35	38.58	49.56	74.00	-24.44	Horizontal
12260.00	48.33	26.54	9.25	38.66	45.46	74.00	-28.54	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4904.00	54.23	25.45	7.46	38.75	48.39	54.00	-5.61	Vertical
7356.00	48.25	24.78	7.82	38.65	42.20	54.00	-11.80	Vertical
9808.00	45.21	26.47	8.35	38.58	41.45	54.00	-12.55	Vertical
12260.00	39.28	26.54	9.25	38.66	36.41	54.00	-17.59	Vertical
4904.00	51.14	25.45	7.46	38.75	45.30	54.00	-8.70	Horizontal
7356.00	48.37	24.78	7.82	38.65	42.32	54.00	-11.68	Horizontal
9808.00	47.21	26.47	8.35	38.58	43.45	54.00	-10.55	Horizontal
12260.00	42.15	26.54	9.25	38.66	39.28	54.00	-14.72	Horizontal

Remark:

1 Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

2 "", means this data is the too weak instrument of signal is unable to test.*

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

------End------