

RF TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
Communication board

ISSUED TO
TT Electronics Sweden AB

Gullfossgratan 3, 164 40 Kista, Sweden



Report No.: BL-SZ2140097-501

EUT Name: Communication board

Model Name: S-2CONNECT Creo SOM

Brand Name: TT Electronics Sweden AB

Test Standard: 47 CFR Part 2

RSS-Gen (Issue 5, March 2019)
(Others refer to chapter 3.1)

FCC ID: 2AZF4-S19Y01

ISED Number: 27105-S19Y01

Test Conclusion: Pass

Test Date: Apr. 17, 2021 ~ May 17, 2021

Date of Issue: May 31, 2021

Tested by:

Wu Huihui

Date

May 31, 2021

Approved by:

Wei Yanguan
(Chief Engineer)

Date

May 31, 2021

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Revision History

<u>Version</u>	<u>Issue Date</u>	<u>Revisions Content</u>
<u>Rev. 01</u>	<u>May 31, 2021</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	ADMINISTRATIVE DATA (GENERAL INFORMATION)	4
1.1	Identification of the Testing Laboratory	4
1.2	Identification of the Responsible Testing Location	4
1.3	Laboratory Condition	4
1.4	Announce	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	Factory Information	5
2.4	General Description for Equipment under Test (EUT)	5
2.5	Technical Information	6
3	SUMMARY OF TEST RESULTS	9
3.1	Test Standards	9
3.2	Test Verdict	10
4	GENERAL TEST CONFIGURATIONS	12
4.1	Test Environments	12
4.2	Test Equipment List	12
4.3	Test Configurations	14
4.4	Test Setup	23
5	TEST ITEMS	26
5.1	Transmitter Radiated Power (EIRP/ERP)	26
5.2	Peak to Average Ratio	30
5.3	Occupied Bandwidth	32
5.4	Frequency Stability	34
5.5	Spurious Emission at Antenna Terminals	37
5.6	Band Edge	42

5.7	Field Strength of Spurious Radiation	47
5.8	Receiver Spurious Emissions	53
5.9	AC Power-line Conducted Emissions	55
ANNEX A	TEST RESULTS.....	57
A.1	Transmitter Radiated Power (EIRP/ERP)	57
A.2	Peak to Average Ratio	85
A.3	Occupied Bandwidth	90
A.4	Frequency Stability.....	96
A.5	Spurious Emission at Antenna Terminals	172
A.6	Band Edge	186
A.7	Field Strength of Spurious Radiation	205
A.8	Receiver Spurious Emissions	209
A.9	AC Power-line Conducted Emissions	213
ANNEX B	TEST SETUP PHOTOS	215
ANNEX C	EUT EXTERNAL PHOTOS	215
ANNEX D	EUT INTERNAL PHOTOS	215

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China.
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China.
Accreditation Certificate	The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1. The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20 °C to 35 °C
Ambient Relative Humidity	30 % to 60 %
Ambient Pressure	98 kPa to 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v2.9.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (7) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant. The applicant is responsible for the impact of the information provided on the validity of the results.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	TT Electronics Sweden AB
Address	Gullfossgatan 3, 164 40 Kista, Sweden

2.2 Manufacturer Information

Manufacturer	TT Electronics Sweden AB
Address	Gullfossgatan 3, 164 40 Kista, Sweden

2.3 Factory Information

Factory	N/A
Address	N/A

2.4 General Description for Equipment under Test (EUT)

EUT Name	Communication board
Model Name Under Test	S-2CONNECT Creo SOM
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	S19Y01-SOM004
Software Version	0.1.0.certification
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Technical Information

Note: The information provided by the applicant, except for The Max RF Output Power (EIRP/ERP).

All Network and Wireless connectivity for EUT	2G Network GPRS/EGPRS 850/ 1900 MHz 4G Network FDD LTE-M1 Band 2/4/5/12/13/25/26/66/85 FDD NB-IoT Band 2/4/5/12/13/25/66/85 Bluetooth BLE GPS, GLONASS
About the Product	The equipment is Communication board, intended for used with information technology equipment.

The requirement for the following technical information of the EUT was tested in this report:

Operating Bands	GPRS/EGPRS 850/ 1900 MHz FDD LTE CAT M1 Band 2/4/5/12/13/25/26/66/85 FDD LTE NB IOT Band 2/4/5/12/13/25/66/85	
Modulation Type	GPRS	GMSK
	EGPRS	8PSK
	LTE-M1	QPSK
		16QAM
	NB-IoT	BPSK
		QPSK
TX Frequency Range	GPRS/EGPRS 850: 824 MHz ~ 849 MHz GPRS/EGPRS 1900: 1850 MHz ~ 1910 MHz FDD LTE Band 2: 1850 MHz ~ 1910 MHz FDD LTE Band 4: 1710 MHz ~ 1755 MHz FDD LTE Band 5: 824 MHz ~ 849 MHz FDD LTE Band 12: 699 MHz ~ 716 MHz FDD LTE Band 13: 777 MHz ~ 787 MHz FDD LTE Band 25: 1850 MHz ~ 1915 MHz FDD LTE Band 26: 814 MHz ~ 849 MHz FDD LTE Band 66: 1710 MHz ~ 1780 MHz FDD LTE Band 85: 698 MHz ~ 716 MHz	
Rx Frequency Range	GPRS/EGPRS 850: 869 MHz ~ 894 MHz GPRS/EGPRS 1900: 1930 MHz ~ 1990 MHz FDD LTE Band 2: 1930 MHz ~ 1990 MHz FDD LTE Band 4: 2110 MHz ~ 2155 MHz FDD LTE Band 5: 869 MHz ~ 894 MHz FDD LTE Band 12: 729 MHz ~ 746 MHz FDD LTE Band 13: 746 MHz ~ 756 MHz FDD LTE Band 25: 1930 MHz ~ 1995 MHz FDD LTE Band 26: 859 MHz ~ 894 MHz FDD LTE Band 66: 2110 MHz ~ 2200 MHz FDD LTE Band 85: 728 MHz ~ 746 MHz	
Power Class	GPRS 850: 4 GPRS 1900: 1 EGPRS 850/1900: E2	

	FDD LTE-M1 Band 2: 5 FDD LTE-M1 Band 4: 5 FDD LTE-M1 Band 5: 5 FDD LTE-M1 Band 12: 5 FDD LTE-M1 Band 13: 5 FDD LTE-M1 Band 25: 5 FDD LTE-M1 Band 26 (part22): 5 FDD LTE-M1 Band 26 (part90): 5 FDD LTE-M1 Band 66: 5 FDD LTE-M1 Band 85: 5 FDD NB-IoT Band 2: 5 FDD NB-IoT Band 4: 5 FDD NB-IoT Band 5: 5 FDD NB-IoT Band 12: 5 FDD NB-IoT Band 13: 5 FDD NB-IoT Band 25: 5 FDD NB-IoT Band 66: 5 FDD NB-IoT Band 85: 5
Multislot Class	GPRS/EGPRS: 33
Antenna Type	New (Pulse) Antenna
Antenna Gain	GPRS/EGPRS 850: 0.25 dBi GPRS/EGPRS 1900: 1.15 dBi FDD LTE-M1 Band 2: 1.15 dBi FDD LTE-M1 Band 4: 1.15 dBi FDD LTE-M1 Band 5: 0.25 dBi FDD LTE-M1 Band 12: -0.17 dBi FDD LTE-M1 Band 13: 0.02 dBi FDD LTE-M1 Band 25: 1.15 dBi FDD LTE-M1 Band 26 (part22): 0.25 dBi FDD LTE-M1 Band 26 (part90): 0.25 dBi FDD LTE-M1 Band 66: 1.15 dBi FDD LTE-M1 Band 85: -0.17 dBi FDD NB-IoT Band 2: 1.15 dBi FDD NB-IoT Band 4: 1.15 dBi FDD NB-IoT Band 5: 0.25 dBi FDD NB-IoT Band 12: -0.17 dBi FDD NB-IoT Band 13: 0.02 dBi FDD NB-IoT Band 25: 1.15 dBi FDD NB-IoT Band 66: 1.15 dBi FDD NB-IoT Band 85: -0.17 dBi
The Max RF Output Power (EIRP/ERP)	GPRS/EGPRS 850: 31.78 dBm GPRS/EGPRS 1900: 30.96 dBm FDD LTE-M1 Band 2: 22.94 dBm FDD LTE-M1 Band 4: 22.23 dBm FDD LTE-M1 Band 5: 18.62 dBm FDD LTE-M1 Band 12: 18.25 dBm

	FDD LTE-M1 Band 13: 19.14 dBm
	FDD LTE-M1 Band 25: 22.29 dBm
	FDD LTE-M1 Band 26 (part22): 19.32 dBm
	FDD LTE-M1 Band 26 (part90): 19.41 dBm
	FDD LTE-M1 Band 66: 22.65 dBm
	FDD LTE-M1 Band 85: 18.26 dBm
	FDD NB-IoT Band 2: 22.05 dBm
	FDD NB-IoT Band 4: 21.83 dBm
	FDD NB-IoT Band 5: 18.53 dBm
	FDD NB-IoT Band 12: 18.25 dBm
	FDD NB-IoT Band 13: 19.04 dBm
	FDD NB-IoT Band 25: 22.3 dBm
	FDD NB-IoT Band 66: 22.01 dBm
	FDD NB-IoT Band 85: 18.42 dBm

Note 1: The EUT information are declared by manufacturer. For more detailed features description, please refer to the manufacturer's specifications or user's manual.

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 22 Subpart H	Cellular Radiotelephone Service
3	47 CFR Part 24 Subpart E	Broadband PCS
4	47 CFR Part 27	Miscellaneous Wireless Communications Services
5	47 CFR Part 90 Subpart S	Regulations Governing Licensing and Use of Frequencies in the 806-824, 851-869, 896-901, and 935-940 MHz Bands
7	RSS-Gen Issue5	General Requirements and Information for the Certification of Radio Apparatus
8	RSS-130 Issue2	Equipment Operating in the Frequency Bands 617-652 MHz, 663-698 MHz, 698-756 MHz and 777-787 MHz
9	RSS-132 Issue3	Cellular Telephone Systems Operating in the Bands 824-849 MHz and 869-894 MHz
10	RSS-133 Issue6	2 GHz Personal Communications Services
11	RSS-139 Issue3	Advanced Wireless Services (AWS) Equipment Operating in the Bands 1710-1780 MHz and 2110-2180 MHz
14	ANSI/TIA-603-E-2016	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
15	KDB 971168 D01 v03	Measurement Guidance for Certification of Licensed Digital Transmitters

3.2 Test Verdict

No.	Description	FCC Part No.	ISED Part No.	Test Result	Verdict
1	Conducted RF Output Power	2.1046	RSS-Gen 6.12 RSS-130 4.6 RSS-132 5.4 RSS-133 6.4 RSS-139 6.5 RSS-199 4.4 RSS-140 4.3	Reporting only (ANNEX A.1)	Pass
2	Effective (Isotropic) Radiated Power	2.1046 22.913 24.232 27.50 90.635(b) 90.542(a)	RSS-Gen 6.12 RSS-130 4.6 RSS-132 5.4 RSS-133 6.4 RSS-139 6.5 RSS-199 4.4 RSS-140 4.3	ANNEX A.1	Pass
3	Peak to Average Ratio	2.1046 24.232(d) 27.50(d)	RSS-130 4.6 RSS-132 5.4 RSS-133 6.4 RSS-139 6.5 RSS-199 4.4 RSS-140 4.3	ANNEX A.2	Pass
4	Occupied Bandwidth	2.1049 22.917 24.238 27.53 90.209	RSS-Gen 6.7	ANNEX A.3	Pass
5	Frequency Stability	2.1055 22.355 24.235 27.54 90.213	RSS-Gen 6.11 RSS-130 4.5 RSS-132 5.3 RSS-133 6.3 RSS-139 6.4 RSS-199 4.3 RSS-140 4.2	ANNEX A.4	Pass
6	Spurious Emission at Antenna Terminals	2.1051 22.917 24.238 27.53 90.691 90.543	RSS-Gen 6.13 RSS-130 4.7 RSS-132 5.5 RSS-133 6.5 RSS-139 6.6 RSS-199 4.5 RSS-140 4.4	ANNEX A.5	Pass
7	Band Edge	2.1051 22.917 24.238	RSS-130 4.7 RSS-132 5.5 RSS-133 6.5	ANNEX A.6	Pass

No.	Description	FCC Part No.	ISED Part No.	Test Result	Verdict
		27.53 90.691 90.543	RSS-139 6.6 RSS-199 4.5 RSS-140 4.4		
8	Field Strength of Spurious Radiation	2.1053 22.917 24.238 27.53 90.691 90.543	RSS-Gen 6.13 RSS-130 4.7 RSS-132 5.5 RSS-133 6.5 RSS-139 6.6 RSS-199 4.5 RSS-140 4.4	ANNEX A.7	Pass
9	Receiver Spurious Emissions	N/A	RSS-Gen 7 RSS-132 5.6 RSS-133 6.6	ANNEX A.8	Pass
10	AC Power-line Conducted Emissions	N/A	RSS-Gen 8.8	ANNEX A.9	Pass

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the environmental conditions were within the listed ranges:

Test Voltage of the EUT	NV (Normal Voltage)	18 V
	LV (Low Voltage)	12 V
	HV (High Voltage)	24 V
Test Temperature of the EUT	NT (Normal Temperature)	+25 °C
	LT (Low Temperature)	-30 °C
	HT (High Temperature)	+60 °C

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Software /Firmware Version	Cal. Date	Cal. Due
Conducted Test System						
Test Software 1	R&S	CMUgo	N/A	V2.0.1	N/A	N/A
Test Software 2	R&S	CMWRun	N/A	V1.9.8	N/A	N/A
Test Software 3	BALUN	BL410R	N/A	V2.1.1.48 8	N/A	N/A
Universal Radio Communication Tester	R&S	CMU 200	119280	V5.13	2021.01.14	2022.01.13
Wideband Radio Communication Tester	R&S	CMW 500	127794	V3.5.137	2020.06.08	2021.06.07
Wideband Radio Communication Tester	R&S	CMW 500	120598	V3.5.137	2021.01.14	2022.01.13
Spectrum Analyzer	R&S	FSV-30	103118	2.30.SP1	2020.06.08	2021.06.07
Spectrum Analyzer	Agilent	E4440A	MY45304434	A.11.21	2020.09.25	2021.09.24
Spectrum Analyzer	Agilent	E4440A	MY46181663	A.11.21	2020.10.21	2021.10.20
Temperature Chamber	AHK	SP20	1412	N/A	2020.06.10	2021.06.09
DC Power Supply	ITECH	IT6863A	6000140106 87210020	N/A	2020.06.12	2021.06.11
Power Sensor	Agilent	E9304A H18	MY41497164	N/A	2020.09.25	2021.09.24
Power Splitter	KMW	DCPD- LDC	1305003215	N/A	N/A	N/A
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	N/A	N/A	N/A

Description	Manufacturer	Model	Serial No.	Software /Firmware Version	Cal. Date	Cal. Due
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	N/A	N/A	N/A
Wideband Radio Communication Tester	R&S	CMW 500	168792	V3.5.137	2021.04.01	2022.03.31
Radiated Test System						
Test Software	BALUN	BL410_E	N/A	V16.921	N/A	N/A
Test Antenna-Bi-Log(30 MHz-3 GHz)	Schwarzbeck	VULB 9163	9163-624	N/A	2019.07.02	2021.07.01
Test Antenna-Horn(1-18 GHz)	Schwarzbeck	BBHA 9120D	9120D-1148	N/A	2019.07.02	2021.07.01
Test Antenna-Horn(18-40 GHz)	A-INFO	LB-180400KF	J211060273	N/A	2021.01.04	2023.01.03
Anechoic Chamber	YIHENG	9m*6m*6m	#3	N/A	2018.07.18	2021.07.17
Shielded Enclosure	ChangNing	CN-130701	130703	N/A	N/A	N/A
EMI Receiver	KEYSIGHT	N9038A	MY53220118	A.14.16	2020.09.18	2021.09.17
Spectrum Analyzer	R&S	FSV-30	103118	2.30.SP1	2020.06.08	2021.06.07
Wideband Radio Communication Tester	R&S	CMW 500	127794	V3.2.73	2020.06.08	2021.06.07
Wideband Radio Communication Tester	R&S	CMW 500	168792	V3.5.137	2021.04.01	2022.03.31

4.3 Test Configurations

Test Items	Test Mode	Test Channel		
		LCH	MCH	HCH
Effective (Isotropic) Radiated Power	GPRS 850	v	v	v
	GPRS 1900	v	v	v
	EGPRS 850	v	v	v
	EGPRS 1900	v	v	v
Occupied Bandwidth	GPRS 850	v	v	v
	GPRS 1900	v	v	v
	EGPRS 850	v	v	v
	EGPRS 1900	v	v	v
Frequency Stability	GPRS 850	v	v	v
	GPRS 1900	v	v	v
	EGPRS 850	v	v	v
	EGPRS 1900	v	v	v
Spurious Emission at Antenna Terminals	GPRS 850	v	v	v
	GPRS 1900	v	v	v
	EGPRS 850	v	v	v
	EGPRS 1900	v	v	v
Band Edge	GPRS 850	v	--	v
	GPRS 1900	v	--	v
	EGPRS 850	v	--	v
	EGPRS 1900	v	--	v
Field Strength of Spurious Radiation	GPRS 850	v	v	v
	GPRS 1900	v	v	v
	EGPRS 850	v	v	v
	EGPRS 1900	v	v	v

Note 1: The mark "v" means that this configuration is chosen for testing.

Test Mode	UL Channel	UL Channel No.	UL Frequency (MHz)
GPRS/EGPRS 850	Low Channel	128	824.2
	Middle Channel	190	836.6
	High Channel	251	848.8
GPRS/EGPRS 1900	Low Channel	512	1850.2
	Middle Channel	661	1880.0
	High Channel	810	1909.8

LTE-M1 Band	Bandwidth (MHz)						Modulation Type		RB#			Test Channel		
	1.4	3	5	10	15	20	QPSK	16-QAM	1	Half	Full	LCH	MCH	HCH
Effective (Isotropic) Radiated Power														
2	v	v	v	v	v	v	v	v	v	--	v	v	v	v
4	v	v	v	v	v	v	v	v	v	--	v	v	v	v
5	v	v	v	v	n	n	v	v	v	--	v	v	v	v
12	v	v	v	v	n	n	v	v	v	--	v	v	v	v
13	n	n	v	v	n	n	v	v	v	--	v	v	v	v
25	v	v	v	v	v	v	v	v	v	--	v	v	v	v
26(Part22)	v	v	v	v	v	n	v	v	v	--	v	v	v	v
26(Part90)	v	v	v	v	--	n	v	v	v	--	v	--	v	--
66	v	v	v	v	v	v	v	v	v	--	v	v	v	v
85	n	n	v	v	n	n	v	v	v	--	v	v	v	v
Peak to Average Ratio														
2	--	--	--	--	--	v	v	v	--	--	v	v	v	v
4	--	--	--	--	--	v	v	v	--	--	v	v	v	v
5	--	--	--	v	n	n	v	v	--	--	v	v	v	v
12	--	--	--	v	n	n	v	v	--	--	v	v	v	v
13	n	n	--	v	n	n	v	v	--	--	v	v	v	v
25	--	--	--	--	--	v	v	v	--	--	v	v	v	v
26(Part22)	--	--	--	--	v	n	v	v	--	--	v	v	v	v
26(Part90)	--	--	--	v	--	n	v	v	--	--	v	--	v	--
66	--	--	--	--	--	v	v	v	v	--	v	v	v	v
85	n	n	--	v	n	n	v	v	--	v	v	v	v	n
Occupied Bandwidth														
2	v	--	--	--	--	--	v	v	--	--	v	v	v	v
4	v	--	--	--	--	--	v	v	--	--	v	v	v	v
5	v	--	--	--	n	n	v	v	--	--	v	v	v	v
12	v	--	--	--	n	n	v	v	--	--	v	v	v	v
13	n	n	v	--	n	n	v	v	--	--	v	v	v	v
25	v	--	--	--	--	--	v	v	--	--	v	v	v	v
26(Part22)	v	--	--	--	--	n	v	v	--	--	v	v	v	v
26(Part90)	v	--	--	--	--	n	v	v	--	--	v	v	v	v
66	v	--	--	--	--	v	v	v	--	--	v	v	v	v
85	n	n	v	--	n	n	v	v	--	--	v	v	v	v
Frequency Stability														
2	--	--	--	--	--	v	v	v	--	--	v	v	v	v
4	--	--	--	--	--	v	v	v	--	--	v	v	v	v
5	--	--	--	v	n	n	v	v	--	--	v	v	v	v
12	--	--	--	v	n	n	v	v	--	--	v	v	v	v
13	n	n	--	v	n	n	v	v	--	--	v	v	v	v
25	--	--	--	--	--	v	v	v	--	--	v	v	v	v
26(Part22)	--	--	--	--	v	n	v	v	--	--	v	v	v	v
26(Part90)	--	--	--	v	--	n	v	v	--	--	v	v	v	v

LTE-M1 Band	Bandwidth (MHz)						Modulation Type		RB#			Test Channel		
	1.4	3	5	10	15	20	QPSK	16-QAM	1	Half	Full	LCH	MCH	HCH
66	--	--	--	--	--	v	v	v	--	--	v	v	v	v
85	n	n	--	v	n	n	v	v	--	--	v	v	v	v
Spurious Emission at Antenna Terminals														
2	v	v	v	v	v	v	v	v	v	--	--	v	v	v
4	v	v	v	v	v	v	v	v	v	--	--	v	v	v
5	v	v	v	v	n	n	v	v	v	--	--	v	v	v
12	v	v	v	v	n	n	v	v	v	--	--	v	v	v
13	n	n	v	v	n	n	v	v	v	--	--	v	v	v
25	v	v	v	v	v	v	v	v	v	--	--	v	v	v
26(Part22)	v	v	v	v	v	n	v	v	v	--	--	v	v	v
26(Part90)	v	v	v	v	--	n	v	v	v	--	--	v	v	v
66	v	v	v	v	v	v	v	v	v	--	--	v	v	v
85	n	n	v	v	n	n	v	v	v	--	--	v	v	v
Band Edge														
2	v	v	v	v	v	v	v	v	v	--	v	v	--	v
4	v	v	v	v	v	v	v	v	v	--	v	v	--	v
5	v	v	v	v	n	n	v	v	v	--	v	v	--	v
12	v	v	v	v	n	n	v	v	v	--	v	v	--	v
13	n	n	v	v	n	n	v	v	v	--	v	v	--	v
25	v	v	v	v	v	v	v	v	v	--	v	v	--	v
26(Part22)	v	v	v	v	v	n	v	v	v	--	v	v	--	v
26(Part90)	v	v	v	v	--	n	v	v	v	--	v	v	--	v
66	v	v	v	v	v	v	v	v	v	--	v	v	--	v
85	n	n	v	v	n	n	v	v	v	--	v	v	--	v
Field Strength of Spurious Radiation														
2	v	v	v	v	v	v	v	v	v	--	--	--	v	--
4	v	v	v	v	v	v	v	v	v	--	--	--	v	--
5	v	v	v	v	n	n	v	v	v	--	--	--	v	--
12	v	v	v	v	n	n	v	v	v	--	--	--	v	--
13	n	n	v	v	n	n	v	v	v	--	--	--	v	--
25	v	v	v	v	v	v	v	v	v	--	--	--	v	--
26(Part22)	v	v	v	v	v	n	v	v	v	--	--	--	v	--
26(Part90)	v	v	v	v	--	n	v	v	v	--	--	--	v	--
66	v	v	v	v	v	v	v	v	v	--	--	--	v	--
85	n	n	v	v	n	n	v	v	v	--	--	--	v	--
Note 1: The mark "v" means that this configuration is chosen for testing. Note 2: The mark "n" means that this bandwidth is not supported.														

NB-IoT Band	Sub-carrier spacing (kHz)		Modulation Type		Test Channel		
	3.75	15	BPSK	QPSK	LCH	MCH	HCH
Effective (Isotropic) Radiated Power							
2	v	v	v	v	v	v	v
4	v	v	v	v	v	v	v
5	v	v	v	v	v	v	v
12	v	v	v	v	v	v	v
13	v	v	v	v	v	v	v
65	v	v	v	v	v	v	v
85	v	v	v	v	v	v	v
Peak to Average Ratio							
2	v	v	v	v	v	v	v
4	v	v	v	v	v	v	v
5	v	v	v	v	v	v	v
12	v	v	v	v	v	v	v
13	v	v	v	v	v	v	v
65	v	v	v	v	v	v	v
85	v	v	v	v	v	v	v
Occupied Bandwidth							
2	v	v	v	v	v	v	v
4	v	v	v	v	v	v	v
5	v	v	v	v	v	v	v
12	v	v	v	v	v	v	v
13	v	v	v	v	v	v	v
65	v	v	v	v	v	v	v
85	v	v	v	v	v	v	v
Frequency Stability							
2	v	v	v	v	v	v	v
4	v	v	v	v	v	v	v
5	v	v	v	v	v	v	v
12	v	v	v	v	v	v	v
13	v	v	v	v	v	v	v
65	v	v	v	v	v	v	v
85	v	v	v	v	v	v	v
Spurious Emission at Antenna Terminals							
2	v	v	v	v	v	v	v
4	v	v	v	v	v	v	v
5	v	v	v	v	v	v	v
12	v	v	v	v	v	v	v
13	v	v	v	v	v	v	v
65	v	v	v	v	v	v	v
85	v	v	v	v	v	v	v
Band Edge							

NB-IoT Band	Sub-carrier spacing (kHz)		Modulation Type		Test Channel		
	3.75	15	BPSK	QPSK	LCH	MCH	HCH
2	v	v	v	v	v	--	v
4	v	v	v	v	v	--	v
5	v	v	v	v	v	--	v
12	v	v	v	v	v	--	v
13	v	v	v	v	v	--	v
65	v	v	v	v	v	--	v
85	v	v	v	v	v	--	v
Field Strength of Spurious Radiation							
2	v	v	v	v	--	v	--
4	v	v	v	v	--	v	--
5	v	v	v	v	--	v	--
12	v	v	v	v	--	v	--
13	v	v	v	v	--	v	--
65	v	v	v	v	--	v	--
85	v	v	v	v	--	v	--
Note 1: The mark “v” means that this configuration is chosen for testing. Note 2: The mark “n” means that this bandwidth is not supported.							

Test Mode	UL Channel	Channel Bandwidth (MHz)	UL Channel No.	UL Frequency (MHz)
LTE-M1 Band 2	Low Range	1.4	18607	1850.7
		3	18615	1851.5
		5	18625	1852.5
		10	18650	1855
		15	18675	1857.5
		20	18700	1860
	Middle Range	1.4/3/5/10/15/20	18900	1880
	High Range	1.4	19193	1909.3
		3	19185	1908.5
		5	19175	1907.5
		10	19150	1905
		15	19125	1902.5
		20	19100	1900
LTE-M1 Band 4	Low Range	1.4	19957	1710.7
		3	19965	1711.5
		5	19975	1712.5
		10	20000	1715
		15	20025	1717.5
		20	20050	1720
	Middle Range	1.4/3/5/10/15/20	20175	1732.5
	High Range	1.4	20393	1754.3
		3	20385	1753.5
		5	20375	1752.5
		10	20350	1750
		15	20325	1747.5
		20	20300	1745
LTE-M1 Band 5	Low Range	1.4	20407	824.7
		3	20415	825.5
		5	20425	826.5
		10	20450	829
	Middle Range	1.4/3/5/10	20525	836.5
	High Range	1.4	20643	848.3
		3	20635	847.5
		5	20625	846.5
		10	20600	844
LTE-M1 Band 12	Low Range	1.4	23017	699.7
		3	23025	700.5
		5	23035	701.5
		10	23060	704
	Middle Range	1.4/3/5/10	23095	707.5
	High Range	1.4	23173	715.3
		3	23165	714.5

Test Mode	UL Channel	Channel Bandwidth (MHz)	UL Channel No.	UL Frequency (MHz)
		5	23155	713.5
		10	23130	711
LTE-M1 Band 13	Low Range	5	23205	779.5
		10	23230	782
	Middle Range	5/10	23230	782
	High Range	5	23255	784.5
		10	23230	782
LTE-M1 Band 25	Low Range	1.4	26047	1850.7
		3	26055	1851.5
		5	26065	1852.5
		10	26090	1855
		15	26115	1857.5
		20	26140	1860
	Middle Range	1.4/3/5/10/15/20	26365	1882.5
	High Range	1.4	26683	1914.3
		3	26675	1913.5
		5	26665	1912.5
		10	26640	1910
		15	26615	1907.5
		20	26590	1905
LTE-M1 Band 26 (Part22)	Low Range	1.4	26797	824.7
		3	26805	825.5
		5	26815	826.5
		10	26840	829
		15	26865	831.5
	Middle Range	1.4/3/5/10/15	26915	836.5
	High Range	1.4	27033	848.3
		3	27025	847.5
		5	27015	846.5
		10	26990	844
		15	26965	841.5
LTE-M1 Band 26 (Part90)	Low Range	1.4	26697	814.7
		3	26705	815.5
		5	26715	816.5
		10	--	--
	Middle Range	1.4/3/5/10	26740	819
	High Range	1.4	26783	823.3
		3	26775	822.5
		5	26765	821.5
		10	--	--
LTE-M1 Band 66	Low Range	1.4	131979	1710.7
		3	131987	1711.5
		5	131997	1712.5


Test Mode	UL Channel	Channel Bandwidth (MHz)	UL Channel No.	UL Frequency (MHz)
		10	132022	1715
		15	132047	1717.5
		20	132072	1720
	Middle Range	1.4/3/5/10/15/20	132322	1745
	High Range	1.4	132665	1779.3
		3	132657	1778.5
		5	132647	1777.5
		10	132622	1775
		15	132597	1772.5
		20	132572	1770
LTE-M1 Band 85	Low Range	5	134027	700.5
		10	134052	703
	Middle Range	5/10	134092	707
	High Range	5	134157	713.5
		10	134132	711

Test Mode	UL Channel	Channel Bandwidth (MHz)	UL Channel No.	UL Frequency (MHz)
NB-IoT Band 2	Low Range	---	18601	1850.1
	Middle Range	---	18900	1880.0
	High Range	---	19199	1909.9
NB-IoT Band 4	Low Range	---	19951	1710.1
	Middle Range	---	20175	1732.5
	High Range	---	20399	1754.9
NB-IoT Band 5	Low Range	---	20401	824.1
	Middle Range	---	20525	836.5
	High Range	---	20649	848.9
NB-IoT Band 12	Low Range	---	23011	699.1
	Middle Range	---	23095	707.5
	High Range	---	23179	715.9
NB-IoT Band 13	Low Range	---	23181	777.1
	Middle Range	---	23230	782.0
	High Range	---	23279	786.9
NB-IoT Band 25	Low Range	---	26041	1850.1
	Middle Range	---	26365	1882.5
	High Range	---	26689	1914.9
NB-IoT Band 66	Low Range	---	131973	1710.1
	Middle Range	---	132322	1745.0
	High Range	---	132671	1779.9
NB-IoT Band 85	Low Range	---	134003	698.1
	Middle Range	---	134082	706.0
	High Range	---	134181	715.9

Test Items	Test Mode	Test Channel		
		LCH	MCH	HCH
Receiver Spurious Emissions	GPRS 850	--	v	--
AC Power-line Conducted Emissions	GPRS 850	--	v	--
Note 1: The mark “v” means that this configuration is the worst test mode for Receiver Spurious Emissions and AC Power-line Conducted Emissions measurement.				


4.4 Test Setup

4.4.1 For Antenna Port Test




(Diagram 1)

4.4.2 For Frequency Stability Test




(Diagram 2)

4.4.3 For Radiated Test (30 MHz ~ 1 GHz)




(Diagram 3)

4.4.4 For Radiated Test (Above 1 GHz)



(Diagram 4)

4.4.5 For AC Power-line Conducted Emissions



(Diagram 5)

5 TEST ITEMS

5.1 Transmitter Radiated Power (EIRP/ERP)

5.1.1 Limit

FCC § 2.1046 & 22.913(a) & 24.232(c) & 27.50(b) & 27.50(c) & 27.50(d) & 27.50(h) & 90.635(b) & 90.542(a)

According to FCC section 22.913(a) (5), the Effective Radiated Power (ERP) of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC section 24.232(c), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to FCC section 27.50(b) (10), portable stations (hand-held devices) transmitting in the 746-757MHz, 776-788MHz, and 805-806MHz bands are limited to 3 watts ERP.

FCC section 27.50(c) (10), portable stations (hand-held devices) in the 600MHz uplink band and the 698-746MHz band, and fixed and mobile stations in the 600MHz uplink band are limited to 3 watts ERP.

FCC section 27.50(d) (4), fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP. Fixed stations operating in the 1710-1755 MHz band are limited to a maximum antenna height of 10 meters above ground. Mobile and portable stations operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.

(7) Fixed, mobile, and portable (hand-held) stations operating in the 2000-2020 MHz band are limited to 2 watts EIRP.

And FCC section 27.50(h) (2), for mobile and other user stations, mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

According to FCC section 90.635(b), the maximum output power of the transmitter for mobile stations is 100 watts (20dBW).

According to FCC section 90.542(a) (7), portable stations (hand-held devices) transmitting in the 758-768 MHz band and the 788-798 MHz band are limited to 3 watts ERP.

RSS-Gen § 6.12 & RSS-130 § 4.6 & RSS-132 § 5.4 & RSS-133 § 6.4 & RSS-139 § 6.5 & RSS-199 § 4.4 & RSS-140 § 4.3

According to RSS-130 § 4.6.3, The e.r.p. shall not exceed 30 watts for mobile equipment and outdoor fixed subscriber equipment. The e.r.p. shall not exceed 3 watts for portable equipment and indoor fixed subscriber equipment.

According to RSS-132 § 5.4, the Effective Radiated Power (ERP) for mobile equipment shall not exceed 11.5 watts.

According to RSS-133 § 6.4 (SRSP 510), mobile stations and hand-held portables are limited to 2 watts maximum EIRP.

According to RSS-139 § 6.5, the EIRP for mobile and portable transmitters shall not exceed 1 watt.

According to RSS-199 § 4.4, for mobile subscriber equipment, the EIRP shall not exceed 2 watts.

According to RSS-140 § 4.3, the equivalent radiated power (e.r.p.) for control and mobile equipment shall not exceed 30 W. The e.r.p. for portable equipment including handheld devices shall not exceed 3 W.

5.1.2 Test Setup

The section 4.4.1 (Diagram 1) test setup description is used for conducted test, and the section 4.4.3 and 4.4.4 (Diagram 3, 4) test setup description is used for radiated test. The photo of test setup please refer to ANNEX B.

5.1.3 Test Procedure

Description of the Conducted Output Power Measurement

The EUT is coupled to the SS with attenuator through power splitter; the RF load attached to EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. A system simulator is used to establish communication with the EUT, and its parameters are set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The relevant equation for determining the conducted measured value is:

$$\text{Conducted Output Power Value (dBm)} = \text{Measured Value (dBm)} + \text{Path Loss (dB)}$$

where:

Conducted Output Power Value = final conducted measured value in the conducted power test, in dBm;

Measured Value = measured conducted power received by spectrum analyzer or power meter, in dBm;

Path Loss = signal attenuation in the connecting cable between the transmitter and spectrum analyzer or power meter, including external cable loss, in dB;

During the test, the data of Path Loss (dB) is added in the spectrum analyzer or power meter, so Measured Value (dBm) is the final values which contains the data of Path Loss (dB).

For example:

In the conducted output power test, when measured value for GSM850 is 24.7 dBm, and path loss is 8.5 dB, then final conducted output power value is:

$$\text{Conducted Output Power Value (dBm)} = 24.7 \text{ dBm} + 8.5 \text{ dB} = 33.2 \text{ dBm}$$

Description of the Transmitter Radiated Power Measurement

In many cases, the RF output power limits for licensed digital transmission devices is specified in terms of effective radiated power (ERP) or equivalent isotropic radiated power (EIRP). Typically, ERP is specified when the operating frequency is less than or equal to 1 GHz and EIRP is specified when the operating frequency is greater than 1 GHz. Both are determined by adding the transmit antenna gain to the conducted RF output power with the primary difference between the two being that when determining the ERP, the transmit antenna gain is referenced to a

dipole antenna (i.e., dBd) whereas when determining the EIRP, the transmit antenna gain is referenced to an isotropic antenna (dBi).

Final measurement calculation as below:

The relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP/EIRP} = P_{\text{Meas}} + \text{GT} - \text{LC}$$

where:

ERP/EIRP = effective or equivalent radiated power, respectively (expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

GT = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

dBd (ERP)=dBi (EIRP) -2.15 dB

LC = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

For devices utilizing multiple antennas, KDB 662911 provides guidance for determining the effective array transmit antenna gain term to be used in the above equation.

For example:

In the EIRP test, when P_{Meas} value for GSM1900 is 30.2 dBm, LC is 0.6 dB, and GT is -3.4 dB, then final EIRP value is:

$$\text{EIRP for GSM1900} = 30.2 \text{ dBm} - 3.4 \text{ dBi} - 0.6 \text{ dB} = 26.2 \text{ dBm}$$

The relevant equation for determining the ERP/EIRP from the radiated RF output power is:

$$\text{ERP/EIRP (dBm)} = \text{SA Read Value (dBm)} + \text{Correction Factor (dB)}$$

where:

ERP/EIRP = effective or equivalent radiated power, in dBm;

SA Read Value = measured transmitter power received by EMI receiver or spectrum analyzer, in dBm;

Correction Factor = total correction factor including cable loss, in dB;

During the test, the data of Correction Factor (dB) is added in the EMI receiver or spectrum analyzer, so SA Read Value (dBm) is the final values which contains the data of Correction Factor (dB).

For example:

In the ERP test, when SA read value for GSM850 is 21dBm, and correction factor is 8dB, then final ERP value for GSM850 is:

$$\text{ERP (dBm)} = 21\text{dBm} + 8\text{dB} = 29\text{dBm}$$

5.1.4 Test Result

Please refer to ANNEX A.1.

5.2 Peak to Average Ratio

5.2.1 Limit

FCC § 2.1046 & 24.232(d) & 27.50(d)

RSS-130 § 4.6 & RSS-132 § 5.4 & RSS-133 § 6.4 & RSS-139 § 6.5 & RSS-199 § 4.4 & RSS-140 § 4.3

In addition, when the transmitter power is measured in terms of average value, the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time using a signal corresponding to the highest PAPR during periods of continuous transmission.

According to FCC section 24.232(d), power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with 24.232 (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of § 24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

FCC section 24.232(e), peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, etc., so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.

According to FCC section 27.50(d) (5), in measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13dB.

5.2.2 Test Setup

The section 4.4.1 (Diagram 1) test setup description is used for this test. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Here the lowest, middle and highest channels are selected to perform testing to verify the peak-to-average ratio.

According to KDB 971168 D01, there is CCDF procedure for PAPR:

- a) Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- b) Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval as follows:
 - 1) for continuous transmissions, set to 1 ms,
 - 2) for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
- e) Record the maximum PAPR level associated with a probability of 0.1%.

Alternate procedure for PAPR:

Use one of the procedures presented in 4.1 to measure the total peak power and record as P_{Pk} . Use one of the applicable procedures presented 4.2 to measure the total average power and record as P_{Avg} . Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$PAPR (dB) = P_{Pk} (dBm) - P_{Avg} (dBm).$$

5.2.4 Test Result

Please refer to ANNEX A.2.

5.3 Occupied Bandwidth

5.3.1 Limit

FCC § 2.1049

RSS-Gen § 6.7

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.

Many of the individual rule parts specify a relative OBW in lieu of the 99% OBW. In such cases, the OBW is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated by at least X dB below the transmitter power, where the value of X is typically specified as 26.

5.3.2 Test Setup

The section 4.4.1 (Diagram 1) test setup description is used for this test. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The following procedure shall be used for measuring power bandwidth.

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (i.e., two to five times the anticipated OBW).
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- c) Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least $10\log(\text{OBW} / \text{RBW})$ below the reference level.
- d) NOTE—Steps a) through c) may require iteration to adjust within the specified tolerances.
- e) For -26 dB OBW, the dynamic range of the spectrum analyzer at the selected RBW shall be at least 10dB below the target “-X dB down” requirement, e.g. -26 dB OBW, the spectrum analyzer noise floor at the selected RBW shall be 36dB below the reference value.
- f) Set the detection mode to peak, and the trace mode to max hold.
- g) For 99% OBW, use the 99 % power bandwidth function of the spectrum analyzer (if available) and report the measured bandwidth.

If the instrument does not have a 99 % power bandwidth function, the trace data points are to be recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99 % power bandwidth is the difference between these two frequencies.

h) For -26 dB OBW, determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).

Determine the “-X dB down amplitude” as equal to (reference value -X). Alternatively, this calculation can be performed by the analyzer by using the marker-delta function.

Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below “-X dB down amplitude” determined in step g). If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.

i) The OBW shall be reported by providing plot(s) of the measuring instrument display. The frequency and amplitude axes and scale shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

j) Change variable modulations, coding, or channel bandwidth settings, then repeat above test procedures.

5.3.4 Test Result

Please refer to ANNEX A.3.

5.4 Frequency Stability

5.4.1 Limit

FCC § 2.1055 & 22.355 & 24.235 & 27.54 & 90.213

RSS-Gen § 6.11 & RSS-130 § 4.5 & RSS-132 § 5.3 & RSS-133 § 6.3 & RSS-139 § 6.4 & RSS-199 § 4.3 & RSS-140 § 4.2

FCC § 2.1055 & RSS-Gen § 6.11

The frequency stability shall be measured with variation of ambient temperature as follows:

- (1) The temperature is varied from -30°C to +50°C.
- (2) Frequency measurements shall be made at the extremes of the specified temperature range and at intervals of not more than 10°C through the range.

The frequency stability shall be measured with variation of primary supply voltage as follows:

- (1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than carried battery equipment.
- (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating and point which shall be specified by the manufacture.
- (3) The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

FCC § 22.355

Except as otherwise provided in this part, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table C-1 of this section.

Table C-1—Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency range (MHz)	Base, fixed (ppm)	Mobile > 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	n/a	n/a
929 to 960	1.5	n/a	n/a
2110 to 2220	10.0	n/a	n/a

FCC § 24.235

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

FCC § 27.54

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

FCC § 90.213

The frequency stability shall not depart from the reference frequency in excess of ± 2.5 ppm for mobile stations.

RSS-130 § 4.5

The frequency stability shall be sufficient to ensure that the occupied bandwidth remains within each frequency block range when tested at the temperature and supply voltage variations specified in RSS-Gen.

RSS-132 § 5.3

The carrier frequency shall not depart from the reference frequency in excess of ± 2.5 ppm for mobile stations and ± 1.5 ppm for base stations.

RSS-133 § 6.3

The carrier frequency shall not depart from the reference frequency in excess of ± 2.5 ppm for mobile stations and ± 1.0 ppm for base stations.

RSS-139 § 6.4

The frequency stability shall be sufficient to ensure that the occupied bandwidth stays within the operating frequency block when tested to the temperature and supply voltage variations specified in RSS-Gen.

RSS-199 § 4.3

The frequency stability shall be sufficient to ensure that the occupied bandwidth stays within the operating frequency block when tested to the temperature and supply voltage variations specified in RSS-Gen.

RSS-140 § 4.2

The frequency stability shall be sufficient to ensure that the occupied bandwidth stays within the operating frequency block when tested at the temperature and supply voltage variations specified in RSS-Gen.

5.4.2 Test Setup

The section 4.4.2 (Diagram 2) test setup description is used for this test. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

1. The EUT is placed in a temperature chamber.
2. The temperature is set to 25°C and allowed to stabilize. After sufficient soak time, the transmitting frequency error is measured.

3. The temperature is increased by not more than 10 degrees, allowed to stabilize and soak, and then repeat the frequency error measurement.
4. Repeat procedure 3 until +50°C and -30°C is reached.
5. Change supply voltage, and repeat measurement until extreme voltage is reached.

5.4.4 Test Result

Please refer to ANNEX A.4.

5.5 Spurious Emission at Antenna Terminals

5.5.1 Limit

FCC § 2.1051 & 22.917(a) & 24.238(a) & 27.53(c) & 27.53(f) & 27.53(g) & 27.53(h) & 27.53(m) & 90.691 & 90.543
RSS-Gen § 6.13 & RSS-130 § 4.7 & RSS-132 § 5.5 & RSS-133 § 6.5 & RSS-139 § 6.6 & RSS-199 § 4.5 & RSS-140 § 4.4

In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

FCC § 22.917(a) & 24.238(a) & RSS-132 § 5.5 & RSS-133 § 6.5

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. This is calculated to be -13 dBm.

FCC § 27.53(c)

For operations in the 746–758 MHz band and the 776–788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746–758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;
- (2) On any frequency outside the 776–788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;
- (3) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $76 + 10 \log(P)$ dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.

However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

- (6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

FCC § 27.53(f)

For operations in the 746–758 MHz, 775–788 MHz, and 805–806 MHz bands, emissions in the band 1559–1610 MHz shall be limited to - 70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and - 80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

FCC § 27.53(g)

For operations in the 600MHz band and the 698-746MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43+10\log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

FCC § 27.53(h) (1) & RSS-139 § 6.6

Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

FCC § 27.53(m) (4) & RSS-199 § 4.5

For mobile digital stations (BRS and EBS stations), the attenuation factor shall be not less than:

- $40+10\log P$ dB (-10 dBm, 100 nW) on all frequencies between the channel edge and 5 MHz from the channel edge.
- $43+10\log P$ dB (-13 dBm, 50 nW) on all frequencies between 5 MHz and X MHz from the channel edge,
- $55+10\log P$ dB (-25 dBm, 3 nW) on all frequencies more than X MHz from the channel edge, where X is the greater of 6 MHz or the actual emission bandwidth (26 dB).

In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

FCC § 90.691

(a) Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the

frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10\log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

(b) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

FCC § 90.543

(e) For operations in the 758–768 MHz and the 788–798 MHz bands, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On all frequencies between 769–775 MHz and 799–805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations.

(2) On all frequencies between 769–775 MHz and 799–805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775–788 MHz, above 805 MHz, and below 758 MHz, by at least $43 + 10 \log (P)$ dB.

(4) Compliance with the provisions of paragraphs (e)(1) and (2) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

(f) For operations in the 758–775 MHz and 788–805 MHz bands, all emissions including harmonics in the band 1559– 1610 MHz shall be limited to -70 dBW/ MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

RSS-130 § 4.7

The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10\log_{10}(P)$ (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.

In addition to the limit outlined above, equipment operating in the frequency bands 746-756 MHz and 777-787 MHz shall also comply with the following restrictions:

(a) The power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least:

(i) $76 + 10 \log_{10} p$ (watts), dB, for base and fixed equipment and

(ii) $65 + 10 \log_{10} p$ (watts), dB, for mobile and portable equipment

(b) The e.i.r.p. in the band 1559-1610 MHz shall not exceed -70 dBW/MHz for wideband signal and -80 dBW for discrete emission with bandwidth less than 700 Hz.

RSS-140 § 4.4

The power of any unwanted emission outside the bands 758-768 MHz and 788-798 MHz shall be attenuated below the transmitter output power P in dBW as follows, where p is the transmitter output power in watts:

For any frequency between 769-775 MHz and 799-806 MHz:

$76 + 10 \log(p)$, dB in a 6.25 kHz band for fixed and base station equipment

$65 + 10 \log(p)$, dB in a 6.25 kHz band for mobile and portable/hand-held equipment

For any frequency between 775-788 MHz, above 806 MHz, and below 758 MHz: $43 + 10 \log(p)$, dB in a bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency bands 758-768 MHz and 788-798 MHz, a resolution bandwidth of 30 kHz may be employed.

In addition, the equivalent isotropically radiated power (e.i.r.p.) of all emissions, including harmonics in the band 1559-1610 MHz, shall not exceed -70 dBW/MHz for wideband emissions, and -80 dBW/kHz for discrete emissions of less than 700 Hz bandwidth.

5.5.2 Test Setup

The section 4.4.1 (Diagram 1) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency blocks a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

1. The EUT is coupled to the system simulator and spectrum analyzer; the RF load attached to EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2. CMW500 is used to establish communication with the EUT, and its parameters are set to force the EUT transmitting at maximum output power.

3. The RF output of the transmitter is connected to the input of the spectrum analyzer through sufficient attenuation.
4. Spurious emissions are tested with 0.001MHz RBW for frequency less than 150kHz, 0.01MHz RBW for frequency less than 30MHz, 0.1MHz RBW for frequency less than 1GHz, and 1MHz RBW for frequency above 1GHz. And sweep point number are at least 401, referring to following formula.

Sweep point number = Span/RBW

VBW=3*RBW

Detector Mode=mean or average power

5. Record the frequencies and levels of spurious emissions.

5.5.4 Test Result

Please refer to ANNEX A.5.

5.6 Band Edge

5.6.1 Limit

FCC § 2.1051 & 22.917(a) & 24.238(a) & 27.53(c) & 27.53(g) & 27.53(h) & 27.53(m) & 90.691 & 90.543

RSS-130 § 4.7 & RSS-132 § 5.5 & RSS-133 § 6.5 & RSS-139 § 6.6 & RSS-199 § 4.5 & RSS-140 § 4.4

In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

FCC § 22.917(a) & 24.238(a) & RSS-132 § 5.5 & RSS-133 § 6.5

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. This is calculated to be -13 dBm.

FCC § 27.53(c)

For operations in the 746–758 MHz band and the 776–788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746–758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;
- (2) On any frequency outside the 776–788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;
- (3) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $76 + 10 \log(P)$ dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.

However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

- (6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

FCC § 27.53(g)

For operations in the 600MHz band and the 698-746MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43+10\log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

FCC § 27.53(h) (1) & RSS-139 § 6.6

Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

FCC § 27.53(m) (4) & RSS-199 § 4.5

For mobile digital stations (BRS and EBS stations), the attenuation factor shall be not less than:

- $40+10\log P$ dB (–10 dBm, 100 nW) on all frequencies between the channel edge and 5 MHz from the channel edge.
- $43+10\log P$ dB (–13 dBm, 50 nW) on all frequencies between 5 MHz and X MHz from the channel edge,
- $55+10\log P$ dB (–25 dBm, 3 nW) on all frequencies more than X MHz from the channel edge, where X is the greater of 6 MHz or the actual emission bandwidth (26 dB).

In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

FCC § 90.691

(a) Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10\log_{10}(P)$ decibels or 80

decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

(b) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

FCC § 90.543

(e) For operations in the 758–768 MHz and the 788–798 MHz bands, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On all frequencies between 769–775 MHz and 799–805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations.

(2) On all frequencies between 769–775 MHz and 799–805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775–788 MHz, above 805 MHz, and below 758 MHz, by at least $43 + 10 \log (P)$ dB.

(4) Compliance with the provisions of paragraphs (e)(1) and (2) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

RSS-130 § 4.7

The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10 \log_{10}(P)$ (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.

In addition to the limit outlined above, equipment operating in the frequency bands 746-756 MHz and 777-787 MHz shall also comply with the following restrictions:

(a) The power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least:

(i) $76 + 10 \log_{10} p$ (watts), dB, for base and fixed equipment and

(ii) $65 + 10 \log_{10} p$ (watts), dB, for mobile and portable equipment

(b) The e.i.r.p. in the band 1559-1610 MHz shall not exceed -70 dBW/MHz for wideband signal and -80 dBW for discrete emission with bandwidth less than 700 Hz.

RSS-140 § 4.4

The power of any unwanted emission outside the bands 758-768 MHz and 788-798 MHz shall be attenuated below the transmitter output power P in dBW as follows, where p is the transmitter output power in watts:

For any frequency between 769-775 MHz and 799-806 MHz:

$76 + 10 \log (p)$, dB in a 6.25 kHz band for fixed and base station equipment

$65 + 10 \log (p)$, dB in a 6.25 kHz band for mobile and portable/hand-held equipment

For any frequency between 775-788 MHz, above 806 MHz, and below 758 MHz: $43 + 10 \log (p)$, dB in a bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency bands 758-768 MHz and 788-798 MHz, a resolution bandwidth of 30 kHz may be employed.

In addition, the equivalent isotropically radiated power (e.i.r.p.) of all emissions, including harmonics in the band 1559-1610 MHz, shall not exceed -70 dBW/MHz for wideband emissions, and -80 dBW/kHz for discrete emissions of less than 700 Hz bandwidth.

5.6.2 Test Setup

The section 4.4.1 (Diagram 1) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading.

1. The EUT is coupled to the system simulator and spectrum analyzer; the RF load attached to EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading.

2. CMW500 is used to establish communication with the EUT, and its parameters are set to force the EUT transmitting at maximum output power.

3. The RF output of the transmitter is connected to the input of the spectrum analyzer through sufficient attenuation.

4. The center of the spectrum analyzer was set to block edge frequency.

5. Band edge are tested with $1\% \cdot \text{cBW}$ (RBW), and sweep point number referred to following formula.

$$\text{Sweep point number} = 2 \cdot \text{Span} / \text{RBW}$$

$$\text{VBW} = 3 \text{RBW}$$

6. Record the frequencies and levels of spurious emissions.

For mobile and portable stations, on all frequencies between 763–775 MHz and 793–806 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment. Since it was not possible to set the resolution

bandwidth to 6.25 kHz with the available equipment, a bandwidth of 10 kHz was used instead to show compliance. By using a 10 kHz bandwidth on the spectrum analyzer.

$$10 \cdot \log(10 \text{ kHz} / 6.25 \text{ kHz}) = 2.04 \text{ dB}$$

$$\text{Limit Line} = -35 \text{ dBm} + 2.04 \text{ dB} = -32.96 \text{ dBm}$$

5.6.4 Test Result

Please refer to ANNEX A.6.

5.7 Field Strength of Spurious Radiation

5.7.1 Limit

FCC § 2.1053 & 22.917(a) & 24.238(a) & 27.53(c) & 27.53(f) & 27.53(g) & 27.53(h) & 27.53(m) & 90.691 & 90.543
RSS-Gen § 6.13 & RSS-130 § 4.7 & RSS-132 § 5.5 & RSS-133 § 6.5 & RSS-139 § 6.6 & RSS-199 § 4.5 & RSS-140 § 4.4

FCC § 22.917(a) & 24.238(a) & RSS-132 § 5.5 & RSS-133 § 6.5

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. This is calculated to be -13 dBm.

FCC § 27.53(c)

For operations in the 746–758 MHz band and the 776–788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746–758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;
- (2) On any frequency outside the 776–788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;
- (3) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $76 + 10 \log(P)$ dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.

However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

- (6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

FCC § 27.53(f)

For operations in the 746–758 MHz, 775–788 MHz, and 805–806 MHz bands, emissions in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

FCC § 27.53(g)

For operations in the 600MHz band and the 698-746MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

FCC § 27.53(h) (1) & RSS-139 § 6.6

Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

FCC § 27.53(m) (4) & RSS-199 § 4.5

For mobile digital stations (BRS and EBS stations), the attenuation factor shall be not less than:

- $40 + 10 \log P$ dB (–10 dBm, 100 nW) on all frequencies between the channel edge and 5 MHz from the channel edge.
- $43 + 10 \log P$ dB (–13 dBm, 50 nW) on all frequencies between 5 MHz and X MHz from the channel edge,
- $55 + 10 \log P$ dB (–25 dBm, 3 nW) on all frequencies more than X MHz from the channel edge, where X is the greater of 6 MHz or the actual emission bandwidth (26 dB).

In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

FCC § 90.691

(a) Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

(b) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

FCC § 90.543

(e) For operations in the 758–768 MHz and the 788–798 MHz bands, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On all frequencies between 769–775 MHz and 799–805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations.

(2) On all frequencies between 769–775 MHz and 799–805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775–788 MHz, above 805 MHz, and below 758 MHz, by at least $43 + 10 \log (P)$ dB.

(4) Compliance with the provisions of paragraphs (e)(1) and (2) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

(f) For operations in the 758–775 MHz and 788–805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/ MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

RSS-130 § 4.7

The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10 \log_{10}(P)$ (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.

In addition to the limit outlined above, equipment operating in the frequency bands 746-756 MHz and 777-787 MHz shall also comply with the following restrictions:

(a) The power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least:

(i) $76 + 10 \log_{10} p$ (watts), dB, for base and fixed equipment and

(ii) $65 + 10 \log_{10} p$ (watts), dB, for mobile and portable equipment

(b) The e.i.r.p. in the band 1559-1610 MHz shall not exceed -70 dBW/MHz for wideband signal and -80 dBW for discrete emission with bandwidth less than 700 Hz.

RSS-140 § 4.4

The power of any unwanted emission outside the bands 758-768 MHz and 788-798 MHz shall be attenuated below the transmitter output power P in dBW as follows, where p is the transmitter output power in watts:

For any frequency between 769-775 MHz and 799-806 MHz:

$76 + 10 \log (p)$, dB in a 6.25 kHz band for fixed and base station equipment

$65 + 10 \log (p)$, dB in a 6.25 kHz band for mobile and portable/hand-held equipment

For any frequency between 775-788 MHz, above 806 MHz, and below 758 MHz: $43 + 10 \log (p)$, dB in a bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency bands 758-768 MHz and 788-798 MHz, a resolution bandwidth of 30 kHz may be employed.

In addition, the equivalent isotropically radiated power (e.i.r.p.) of all emissions, including harmonics in the band 1559-1610 MHz, shall not exceed -70 dBW/MHz for wideband emissions, and -80 dBW/kHz for discrete emissions of less than 700 Hz bandwidth.

5.7.2 Test Setup

The section 4.4.3 and 4.4.4 (Diagram 3, 4) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

1. On a test site, the EUT shall be placed at 80cm height on a turn table, and in the position close to normal use as declared by the applicant.
2. The test antenna shall be oriented initially for vertical polarization located 3 m from EUT to correspond to the fundamental frequency of the transmitter.
3. The output of the test antenna shall be connected to the measuring receiver and the peak detector is used for the measurement.
4. During the measurement of the EUT, the resolution bandwidth was to 1 MHz and the average bandwidth was set to 1 MHz.
5. The transmitter shall be switched on; the measuring receiver shall be tuned to the frequency of the transmitter under test.
6. The test antenna shall be raised and lowered through the specified range of height until the maximum signal level is detected by the measuring receiver.
7. The transmitter shall be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.

8. The test antenna shall be raised and lowered again through the specified range of height until the maximum signal level is detected by the measuring receiver.
9. The maximum signal level detected by the measuring receiver shall be noted.
10. The EUT was replaced by half-wave dipole (824 ~ 849 MHz) or horn antenna (1 850 ~ 1 910 MHz) connected to a signal generator.
11. In necessary, the input attenuator setting on the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
12. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
13. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring received, which is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
14. The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
15. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.

Final measurement calculation as below:

The relevant equation for determining the ERP/EIRP from the radiated RF output power is:

$$\text{ERP/EIRP (dBm)} = \text{SA Read Value (dBm)} + \text{Correction Factor (dB)}$$

where:

ERP/EIRP = effective or equivalent radiated power, in dBm;

SA Read Value = measured transmitter power received by EMI receiver or spectrum analyzer, in dBm;

Correction Factor = total correction factor including cable loss, in dB;

During the test, the data of Correction Factor (dB) is added in the EMI receiver or spectrum analyzer, so SA Read Value (dBm) is the final values which contains the data of Correction Factor (dB).

For example:

In the ERP test, when SA read value for GSM850 is 21dBm, and correction factor is 8dB, then final ERP value for GSM850 is:

$$\text{ERP (dBm)} = 21\text{dBm} + 8\text{dB} = 29\text{dBm}$$

5.7.4 Test Result

Please refer to ANNEX A.7.

5.8 Receiver Spurious Emissions

5.8.1 Limit

RSS-Gen § 7.3/4 & RSS-132 § 5.6 & RSS-133 § 6.6

For emissions at frequencies below 1 GHz, measurements shall be performed using a CISPR quasi-peak detector and the related measurement bandwidth. At frequencies above 1 GHz, measurements shall be performed using a linear average detector with a minimum resolution bandwidth of 1 MHz.

As an alternative to CISPR quasi-peak or average measurements, compliance with the emission limit can be demonstrated using measuring equipment employing a peak detector function properly adjusted for factors such as pulse desensitization, as required, with a measurement bandwidth equal to, or greater than, the applicable CISPR quasi-peak bandwidth or 1 MHz bandwidth, respectively.

Receiver Radiated Limits

Radiated emission measurements shall be performed with the receiver antenna connected to the receiver antenna ports. The search for spurious emissions shall be from the lowest frequency internally generated or used in the receiver (e.g. local oscillator, intermediate or carrier frequency), or 30 MHz, whichever is higher, to at least five times the highest tunable or local oscillator frequency, whichever is higher, without exceeding 40 GHz.

Spurious emissions from receivers shall not exceed the radiated emissions limits shown in Table 2 below.

Table 2 –Receiver radiated emissions limits

Frequency (MHz)	Field Strength ($\mu\text{V/m}$ at 3 metres)
30 - 88	100
88 - 216	150
216 - 960	200
Above 960	500

Receiver Conducted Limits

If the receiver has a detachable antenna of known impedance, an antenna-conducted spurious emissions measurement is permitted as an alternative to radiated measurement. However, the radiated method is preferred.

The antenna-conducted test shall be performed with the antenna disconnected and with the receiver antenna port connected to a measuring instrument having equal input impedance to that specified for the antenna. The RF cable connecting the receiver under test to the measuring instrument shall also have the same impedance to that specified for the receiver's antenna.

The spurious emissions from the receiver at any discrete frequency, measured at the antenna port by the antenna-conducted method, shall not exceed 2 nW in the frequency range 30-1000 MHz and 5 nW above 1 GHz.

5.8.2 Test Setup

The section 4.4.3 and 4.4.4 (Diagram 3, 4) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The test employing the methods of measurement described in the publication referenced in Section 3(b) (ANSI C63.4);

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.

5.8.4 Test Result

Please refer to ANNEX A.8.

5.9 AC Power-line Conducted Emissions

5.9.1 Limit

RSS-Gen § 8.8

For AC power-line conducted emissions, both quasi-peak and average detectors having the characteristics specified in CAN/CSA-CISPR 16-1-1:15 for the 150 kHz to 30 MHz frequency range shall be employed.

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 3, as measured using a 50 μ H / 50 Ω line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT.

For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 3 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.

Table 3 –AC power-line conducted emissions limits

Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 ^{Note1}	56 to 46 ^{Note1}
0.5 - 5	56	46
5 - 30	60	50

Note 1: The level decreases linearly with the logarithm of the frequency.

5.9.2 Test Setup

The section 4.4.5 (Diagram 5) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

The test employing the methods of measurement described in the publication referenced in Section 3(b) (ANSI C63.4);

The EUT is connected to the power mains through a LISN which provides 50 Ω /50 μ H of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.9.4 Test Result

Please refer to ANNEX A.9.

ANNEX A TEST RESULTS

A.1 Transmitter Radiated Power (EIRP/ERP)

GSM Mode Test Data

Test Band	Test Channel	Conducted Output Peak Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
GPRS 850	LCH	32.77	0.25	-1.90	30.87	1.222	7.00	Pass
	MCH	33.54	0.25	-1.90	31.64	1.459	7.00	Pass
	HCH	33.68	0.25	-1.90	31.78	1.507	7.00	Pass
EGPRS 850	LCH	28.09	0.25	-1.90	26.19	0.416	7.00	Pass
	MCH	28.21	0.25	-1.90	26.31	0.428	7.00	Pass
	HCH	27.94	0.25	-1.90	26.04	0.402	7.00	Pass

Test Band	Test Channel	Conducted Output Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
GPRS 1900	LCH	29.81	1.15	30.96	1.247	2.00	Pass
	MCH	29.59	1.15	30.74	1.186	2.00	Pass
	HCH	29.29	1.15	30.44	1.107	2.00	Pass
EGPRS 1900	LCH	28.66	1.15	29.81	0.957	2.00	Pass
	MCH	28.41	1.15	29.56	0.904	2.00	Pass
	HCH	28.14	1.15	29.29	0.849	2.00	Pass

Note 1: For the GPRS and EGPRS mode, all slots were tested and just the worst data were recorded in this table.

Note 2: $ERP/EIRP = P_{Meas} + GT - LC$

ERP/EIRP = effective or equivalent radiated power, respectively (expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

GT = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

LC = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

$ERP = EIRP - 2.15$; where ERP and EIRP are expressed in consistent units.

Note 3: Set PCL to 5 for GSM/GPRS 850 (power class 4) and 0 for GSM/GPRS 1900 (power class 1).

Set PCL to 8 for EGPRS850 (power class E2) and 2 for EGPRS1900 (power class E2).

GPRS Conducted Output Power

Band	Channel	Conducted Output Peak Power							
		1 Slot (dBm)	1 Slot (W)	2 Slots (dBm)	2 Slots (W)	3 Slots (dBm)	3 Slots (W)	4 Slots (dBm)	4 Slots (W)
GPRS 850	LCH	32.77	1.892	31.84	1.528	29.67	0.926	28.10	0.646
	MCH	33.54	2.259	32.52	1.787	30.29	1.070	28.75	0.750
	HCH	33.68	2.333	32.05	1.601	30.02	1.004	28.44	0.698
GPRS 1900	LCH	29.81	0.957	28.24	0.667	26.68	0.466	25.55	0.359
	MCH	29.59	0.910	28.41	0.693	26.14	0.411	25.01	0.317
	HCH	29.29	0.849	27.96	0.624	25.48	0.353	24.35	0.272

EGPRS Conducted Output Power

Band	Channel	Conducted Output Peak Power							
		1 Slot (dBm)	1 Slot (W)	2 Slots (dBm)	2 Slots (W)	3 Slots (dBm)	3 Slots (W)	4 Slots (dBm)	4 Slots (W)
EGPRS 850	LCH	28.09	0.644	27.81	0.604	26.28	0.424	24.98	0.315
	MCH	28.21	0.662	27.91	0.618	26.32	0.429	25.09	0.323
	HCH	27.94	0.622	27.63	0.579	26.05	0.403	24.81	0.303
EGPRS 1900	LCH	28.66	0.735	27.63	0.579	25.70	0.371	24.50	0.282
	MCH	28.41	0.693	27.21	0.526	25.16	0.328	24.06	0.254
	HCH	28.14	0.652	26.86	0.485	24.85	0.305	23.64	0.231

LTE-M1 Mode Test Data

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE-M1 BAND2									
1.4 MHz	LCH	QPSK	RB1#0	21.44	1.15	22.59	0.182	2.00	Pass
			RB6#0	19.26	1.15	20.41	0.110	2.00	Pass
		16-QAM	RB1#0	20.72	1.15	21.87	0.154	2.00	Pass
			RB5#0	19.38	1.15	20.53	0.113	2.00	Pass
	MCH	QPSK	RB1#0	21.13	1.15	22.28	0.169	2.00	Pass
			RB6#0	19.08	1.15	20.23	0.105	2.00	Pass
		16-QAM	RB1#0	20.09	1.15	21.24	0.133	2.00	Pass
			RB5#0	19.17	1.15	20.32	0.108	2.00	Pass
	HCH	QPSK	RB1#0	21.79	1.15	22.94	0.197	2.00	Pass
			RB6#0	19.35	1.15	20.50	0.112	2.00	Pass
		16-QAM	RB1#0	20.50	1.15	21.65	0.146	2.00	Pass
			RB5#0	19.34	1.15	20.49	0.112	2.00	Pass
3 MHz	LCH	QPSK	RB1#0	21.39	1.15	22.54	0.179	2.00	Pass
			RB6#0	19.22	1.15	20.37	0.109	2.00	Pass
		16-QAM	RB1#0	20.30	1.15	21.45	0.140	2.00	Pass
			RB5#0	19.21	1.15	20.36	0.109	2.00	Pass
	MCH	QPSK	RB1#0	21.23	1.15	22.38	0.173	2.00	Pass
			RB6#0	19.03	1.15	20.18	0.104	2.00	Pass
		16-QAM	RB1#0	20.29	1.15	21.44	0.139	2.00	Pass
			RB5#0	18.93	1.15	20.08	0.102	2.00	Pass
	HCH	QPSK	RB1#0	21.56	1.15	22.71	0.187	2.00	Pass
			RB6#0	19.38	1.15	20.53	0.113	2.00	Pass
		16-QAM	RB1#0	20.63	1.15	21.78	0.151	2.00	Pass
			RB5#0	19.31	1.15	20.46	0.111	2.00	Pass
5 MHz	LCH	QPSK	RB1#0	21.38	1.15	22.53	0.179	2.00	Pass
			RB6#0	20.16	1.15	21.31	0.135	2.00	Pass
		16-QAM	RB1#0	21.29	1.15	22.44	0.175	2.00	Pass
			RB5#0	20.25	1.15	21.40	0.138	2.00	Pass
	MCH	QPSK	RB1#0	21.10	1.15	22.25	0.168	2.00	Pass
			RB6#0	19.96	1.15	21.11	0.129	2.00	Pass
		16-QAM	RB1#0	21.25	1.15	22.40	0.174	2.00	Pass
			RB5#0	19.92	1.15	21.07	0.128	2.00	Pass
	HCH	QPSK	RB1#0	21.53	1.15	22.68	0.185	2.00	Pass
			RB6#0	20.28	1.15	21.43	0.139	2.00	Pass
		16-QAM	RB1#0	21.4	1.15	22.55	0.180	2.00	Pass
			RB5#0	20.37	1.15	21.52	0.142	2.00	Pass
10 MHz	LCH	QPSK	RB1#0	21.41	1.15	22.56	0.180	2.00	Pass
			RB6#0	20.14	1.15	21.29	0.135	2.00	Pass
		16-QAM	RB1#0	21.40	1.15	22.55	0.180	2.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE-M1 BAND2									
		MCH	RB5#0	21.34	1.15	22.49	0.177	2.00	Pass
			RB1#0	21.08	1.15	22.23	0.167	2.00	Pass
			RB6#0	19.92	1.15	21.07	0.128	2.00	Pass
			RB1#0	21.21	1.15	22.36	0.172	2.00	Pass
		HCH	RB5#0	21.14	1.15	22.29	0.169	2.00	Pass
			RB1#0	21.36	1.15	22.51	0.178	2.00	Pass
			RB6#0	20.17	1.15	21.32	0.136	2.00	Pass
			RB1#0	21.38	1.15	22.53	0.179	2.00	Pass
		LCH	RB5#0	21.27	1.15	22.42	0.175	2.00	Pass
			RB1#0	21.28	1.15	22.43	0.175	2.00	Pass
			RB6#0	21.27	1.15	22.42	0.175	2.00	Pass
			RB1#0	21.31	1.15	22.46	0.176	2.00	Pass
		MCH	RB5#0	21.17	1.15	22.32	0.171	2.00	Pass
			RB1#0	21.22	1.15	22.37	0.173	2.00	Pass
			RB6#0	21.23	1.15	22.38	0.173	2.00	Pass
			RB1#0	21.35	1.15	22.50	0.178	2.00	Pass
15 MHz		HCH	RB5#0	21.31	1.15	22.46	0.176	2.00	Pass
			RB1#0	21.36	1.15	22.51	0.178	2.00	Pass
			RB6#0	21.31	1.15	22.46	0.176	2.00	Pass
			RB1#0	21.43	1.15	22.58	0.181	2.00	Pass
		MCH	RB5#0	21.22	1.15	22.37	0.173	2.00	Pass
			RB1#0	21.31	1.15	22.46	0.176	2.00	Pass
			RB6#0	21.22	1.15	22.37	0.173	2.00	Pass
			RB1#0	21.29	1.15	22.44	0.175	2.00	Pass
20 MHz		HCH	RB5#0	21.31	1.15	22.46	0.176	2.00	Pass
			RB1#0	21.11	1.15	22.26	0.168	2.00	Pass
			RB6#0	21.28	1.15	22.43	0.175	2.00	Pass
			RB1#0	21.27	1.15	22.42	0.175	2.00	Pass
		MCH	RB5#0	21.22	1.15	22.37	0.173	2.00	Pass
			RB1#0	21.47	1.15	22.62	0.183	2.00	Pass
			RB6#0	21.33	1.15	22.48	0.177	2.00	Pass
			RB1#0	21	1.15	22.15	0.164	2.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE-M1 BAND4									
1.4 MHz	LCH	QPSK	RB1#0	21.02	1.15	22.17	0.165	1.00	Pass
			RB6#0	18.53	1.15	19.68	0.093	1.00	Pass
		16-QAM	RB1#0	19.66	1.15	20.81	0.121	1.00	Pass
			RB5#0	18.65	1.15	19.80	0.095	1.00	Pass
	MCH	QPSK	RB1#0	20.91	1.15	22.06	0.161	1.00	Pass
			RB6#0	18.69	1.15	19.84	0.096	1.00	Pass
		16-QAM	RB1#0	19.89	1.15	21.04	0.127	1.00	Pass
			RB5#0	18.67	1.15	19.82	0.096	1.00	Pass
	HCH	QPSK	RB1#0	20.96	1.15	22.11	0.163	1.00	Pass
			RB6#0	18.79	1.15	19.94	0.099	1.00	Pass
		16-QAM	RB1#0	19.89	1.15	21.04	0.127	1.00	Pass
			RB5#0	18.72	1.15	19.87	0.097	1.00	Pass
3 MHz	LCH	QPSK	RB1#0	20.7	1.15	21.85	0.153	1.00	Pass
			RB6#0	18.44	1.15	19.59	0.091	1.00	Pass
		16-QAM	RB1#0	19.78	1.15	20.93	0.124	1.00	Pass
			RB5#0	18.49	1.15	19.64	0.092	1.00	Pass
	MCH	QPSK	RB1#0	21.02	1.15	22.17	0.165	1.00	Pass
			RB6#0	18.66	1.15	19.81	0.096	1.00	Pass
		16-QAM	RB1#0	19.87	1.15	21.02	0.126	1.00	Pass
			RB5#0	18.72	1.15	19.87	0.097	1.00	Pass
	HCH	QPSK	RB1#0	21.04	1.15	22.19	0.166	1.00	Pass
			RB6#0	18.62	1.15	19.77	0.095	1.00	Pass
		16-QAM	RB1#0	19.69	1.15	20.84	0.121	1.00	Pass
			RB5#0	18.79	1.15	19.94	0.099	1.00	Pass
5 MHz	LCH	QPSK	RB1#0	20.91	1.15	22.06	0.161	1.00	Pass
			RB6#0	19.67	1.15	20.82	0.121	1.00	Pass
		16-QAM	RB1#0	20.81	1.15	21.96	0.157	1.00	Pass
			RB5#0	19.52	1.15	20.67	0.117	1.00	Pass
	MCH	QPSK	RB1#0	21.07	1.15	22.22	0.167	1.00	Pass
			RB6#0	19.77	1.15	20.92	0.124	1.00	Pass
		16-QAM	RB1#0	20.79	1.15	21.94	0.156	1.00	Pass
			RB5#0	19.63	1.15	20.78	0.120	1.00	Pass
	HCH	QPSK	RB1#0	21.06	1.15	22.21	0.166	1.00	Pass
			RB6#0	19.67	1.15	20.82	0.121	1.00	Pass
		16-QAM	RB1#0	20.83	1.15	21.98	0.158	1.00	Pass
			RB5#0	19.67	1.15	20.82	0.121	1.00	Pass
10 MHz	LCH	QPSK	RB1#0	20.67	1.15	21.82	0.152	1.00	Pass
			RB6#0	19.51	1.15	20.66	0.116	1.00	Pass
		16-QAM	RB1#0	20.81	1.15	21.96	0.157	1.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE-M1 BAND4									
		MCH	RB5#0	20.74	1.15	21.89	0.155	1.00	Pass
			RB1#0	20.83	1.15	21.98	0.158	1.00	Pass
			RB6#0	19.79	1.15	20.94	0.124	1.00	Pass
			RB1#0	21.08	1.15	22.23	0.167	1.00	Pass
		HCH	RB5#0	20.84	1.15	21.99	0.158	1.00	Pass
			RB1#0	20.91	1.15	22.06	0.161	1.00	Pass
			RB6#0	19.69	1.15	20.84	0.121	1.00	Pass
			RB1#0	21.01	1.15	22.16	0.164	1.00	Pass
		LCH	RB5#0	20.68	1.15	21.83	0.152	1.00	Pass
			RB1#0	20.76	1.15	21.91	0.155	1.00	Pass
			RB6#0	19.56	1.15	20.71	0.118	1.00	Pass
			RB1#0	20.71	1.15	21.86	0.153	1.00	Pass
		MCH	RB5#0	20.73	1.15	21.88	0.154	1.00	Pass
			RB1#0	21.06	1.15	22.21	0.166	1.00	Pass
			RB6#0	19.75	1.15	20.90	0.123	1.00	Pass
			RB1#0	20.6	1.15	21.75	0.150	1.00	Pass
15 MHz		HCH	RB5#0	20.78	1.15	21.93	0.156	1.00	Pass
			RB1#0	20.99	1.15	22.14	0.164	1.00	Pass
			RB6#0	19.67	1.15	20.82	0.121	1.00	Pass
			RB1#0	20.9	1.15	22.05	0.160	1.00	Pass
		16-QAM	RB5#0	20.91	1.15	22.06	0.161	1.00	Pass
			RB1#0	20.95	1.15	22.10	0.162	1.00	Pass
			RB6#0	19.62	1.15	20.77	0.119	1.00	Pass
			RB1#0	21.08	1.15	22.23	0.167	1.00	Pass
20 MHz		LCH	RB5#0	20.92	1.15	22.07	0.161	1.00	Pass
			RB1#0	21.08	1.15	22.23	0.167	1.00	Pass
			RB6#0	19.75	1.15	20.90	0.123	1.00	Pass
			RB1#0	20.62	1.15	21.77	0.150	1.00	Pass
		MCH	RB5#0	20.62	1.15	21.77	0.150	1.00	Pass
			RB1#0	20.9	1.15	22.05	0.160	1.00	Pass
			RB6#0	19.67	1.15	20.82	0.121	1.00	Pass
			RB1#0	20.91	1.15	22.06	0.161	1.00	Pass
		HCH	RB5#0	20.92	1.15	22.07	0.161	1.00	Pass
			RB1#0	20.95	1.15	22.10	0.162	1.00	Pass
			RB6#0	19.62	1.15	20.77	0.119	1.00	Pass
			RB1#0	21.08	1.15	22.23	0.167	1.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE-M1 BAND5										
1.4 MHz	LCH	QPSK	RB1#0	20.02	0.25	-1.9	18.12	0.065	7.00	Pass
			RB6#0	18.29	0.25	-1.9	16.39	0.044	7.00	Pass
		16-QAM	RB1#0	19.41	0.25	-1.9	17.51	0.056	7.00	Pass
			RB5#0	18.27	0.25	-1.9	16.37	0.043	7.00	Pass
	MCH	QPSK	RB1#0	20.51	0.25	-1.9	18.61	0.073	7.00	Pass
			RB6#0	18.72	0.25	-1.9	16.82	0.048	7.00	Pass
		16-QAM	RB1#0	19.54	0.25	-1.9	17.64	0.058	7.00	Pass
			RB5#0	18.58	0.25	-1.9	16.68	0.047	7.00	Pass
	HCH	QPSK	RB1#0	20.26	0.25	-1.9	18.36	0.069	7.00	Pass
			RB6#0	18.52	0.25	-1.9	16.62	0.046	7.00	Pass
		16-QAM	RB1#0	19.59	0.25	-1.9	17.69	0.059	7.00	Pass
			RB5#0	18.33	0.25	-1.9	16.43	0.044	7.00	Pass
3 MHz	LCH	QPSK	RB1#0	20.31	0.25	-1.9	18.41	0.069	7.00	Pass
			RB6#0	18.37	0.25	-1.9	16.47	0.044	7.00	Pass
		16-QAM	RB1#0	18.88	0.25	-1.9	16.98	0.050	7.00	Pass
			RB5#0	18.05	0.25	-1.9	16.15	0.041	7.00	Pass
	MCH	QPSK	RB1#0	20.52	0.25	-1.9	18.62	0.073	7.00	Pass
			RB6#0	18.49	0.25	-1.9	16.59	0.046	7.00	Pass
		16-QAM	RB1#0	19.21	0.25	-1.9	17.31	0.054	7.00	Pass
			RB5#0	18.25	0.25	-1.9	16.35	0.043	7.00	Pass
	HCH	QPSK	RB1#0	20.41	0.25	-1.9	18.51	0.071	7.00	Pass
			RB6#0	18.46	0.25	-1.9	16.56	0.045	7.00	Pass
		16-QAM	RB1#0	19.38	0.25	-1.9	17.48	0.056	7.00	Pass
			RB5#0	18.42	0.25	-1.9	16.52	0.045	7.00	Pass
5 MHz	LCH	QPSK	RB1#0	20.19	0.25	-1.9	18.29	0.067	7.00	Pass
			RB6#0	19.2	0.25	-1.9	17.30	0.054	7.00	Pass
		16-QAM	RB1#0	20.24	0.25	-1.9	18.34	0.068	7.00	Pass
			RB5#0	19.27	0.25	-1.9	17.37	0.055	7.00	Pass
	MCH	QPSK	RB1#0	20.27	0.25	-1.9	18.37	0.069	7.00	Pass
			RB6#0	19.3	0.25	-1.9	17.40	0.055	7.00	Pass
		16-QAM	RB1#0	20.31	0.25	-1.9	18.41	0.069	7.00	Pass
			RB5#0	19.48	0.25	-1.9	17.58	0.057	7.00	Pass
	HCH	QPSK	RB1#0	20.24	0.25	-1.9	18.34	0.068	7.00	Pass
			RB6#0	19.23	0.25	-1.9	17.33	0.054	7.00	Pass
		16-QAM	RB1#0	20.36	0.25	-1.9	18.46	0.070	7.00	Pass
			RB5#0	19.26	0.25	-1.9	17.36	0.054	7.00	Pass
10 MHz	LCH	QPSK	RB1#0	20.19	0.25	-1.9	18.29	0.067	7.00	Pass
			RB6#0	19.26	0.25	-1.9	17.36	0.054	7.00	Pass
		16-QAM	RB1#0	20.3	0.25	-1.9	18.40	0.069	7.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE-M1 BAND5										
	MCH	QPSK	RB5#0	20.39	0.25	-1.9	18.49	0.071	7.00	Pass
			RB1#0	20.32	0.25	-1.9	18.42	0.070	7.00	Pass
		16-QAM	RB6#0	19.22	0.25	-1.9	17.32	0.054	7.00	Pass
			RB1#0	20.43	0.25	-1.9	18.53	0.071	7.00	Pass
		16-QAM	RB5#0	20.52	0.25	-1.9	18.62	0.073	7.00	Pass
			RB1#0	20.3	0.25	-1.9	18.40	0.069	7.00	Pass
	HCH	QPSK	RB6#0	19.3	0.25	-1.9	17.40	0.055	7.00	Pass
			RB1#0	20.44	0.25	-1.9	18.54	0.071	7.00	Pass
		16-QAM	RB1#0	20.44	0.25	-1.9	18.54	0.071	7.00	Pass
			RB5#0	20.34	0.25	-1.9	18.44	0.070	7.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE-M1 BAND12										
1.4 MHz	LCH	QPSK	RB1#0	20.21	-0.17	-2.32	17.89	0.062	3.00	Pass
			RB6#0	18.35	-0.17	-2.32	16.03	0.040	3.00	Pass
		16-QAM	RB1#0	19.34	-0.17	-2.32	17.02	0.050	3.00	Pass
			RB5#0	18.36	-0.17	-2.32	16.04	0.040	3.00	Pass
	MCH	QPSK	RB1#0	20.15	-0.17	-2.32	17.83	0.061	3.00	Pass
			RB6#0	18.42	-0.17	-2.32	16.10	0.041	3.00	Pass
		16-QAM	RB1#0	19.36	-0.17	-2.32	17.04	0.051	3.00	Pass
			RB5#0	18.4	-0.17	-2.32	16.08	0.041	3.00	Pass
	HCH	QPSK	RB1#0	20.02	-0.17	-2.32	17.70	0.059	3.00	Pass
			RB6#0	18.5	-0.17	-2.32	16.18	0.041	3.00	Pass
		16-QAM	RB1#0	19.35	-0.17	-2.32	17.03	0.050	3.00	Pass
			RB5#0	18.34	-0.17	-2.32	16.02	0.040	3.00	Pass
3 MHz	LCH	QPSK	RB1#0	20.36	-0.17	-2.32	18.04	0.064	3.00	Pass
			RB6#0	18.33	-0.17	-2.32	16.01	0.040	3.00	Pass
		16-QAM	RB1#0	19.32	-0.17	-2.32	17.00	0.050	3.00	Pass
			RB5#0	18.35	-0.17	-2.32	16.03	0.040	3.00	Pass
	MCH	QPSK	RB1#0	20.57	-0.17	-2.32	18.25	0.067	3.00	Pass
			RB6#0	18.43	-0.17	-2.32	16.11	0.041	3.00	Pass
		16-QAM	RB1#0	19.68	-0.17	-2.32	17.36	0.054	3.00	Pass
			RB5#0	18.45	-0.17	-2.32	16.13	0.041	3.00	Pass
	HCH	QPSK	RB1#0	20.51	-0.17	-2.32	18.19	0.066	3.00	Pass
			RB6#0	18.39	-0.17	-2.32	16.07	0.040	3.00	Pass
		16-QAM	RB1#0	19.37	-0.17	-2.32	17.05	0.051	3.00	Pass
			RB5#0	18.41	-0.17	-2.32	16.09	0.041	3.00	Pass
5 MHz	LCH	QPSK	RB1#0	20.33	-0.17	-2.32	18.01	0.063	3.00	Pass
			RB6#0	19.43	-0.17	-2.32	17.11	0.051	3.00	Pass
		16-QAM	RB1#0	20.38	-0.17	-2.32	18.06	0.064	3.00	Pass
			RB5#0	19.34	-0.17	-2.32	17.02	0.050	3.00	Pass
	MCH	QPSK	RB1#0	20.35	-0.17	-2.32	18.03	0.064	3.00	Pass
			RB6#0	19.44	-0.17	-2.32	17.12	0.052	3.00	Pass
		16-QAM	RB1#0	20.29	-0.17	-2.32	17.97	0.063	3.00	Pass
			RB5#0	19.5	-0.17	-2.32	17.18	0.052	3.00	Pass
	HCH	QPSK	RB1#0	20.22	-0.17	-2.32	17.90	0.062	3.00	Pass
			RB6#0	19.38	-0.17	-2.32	17.06	0.051	3.00	Pass
		16-QAM	RB1#0	20.08	-0.17	-2.32	17.76	0.060	3.00	Pass
			RB5#0	19.51	-0.17	-2.32	17.19	0.052	3.00	Pass
10 MHz	LCH	QPSK	RB1#0	20.28	-0.17	-2.32	17.96	0.063	3.00	Pass
			RB6#0	19.41	-0.17	-2.32	17.09	0.051	3.00	Pass
		16-QAM	RB1#0	20.15	-0.17	-2.32	17.83	0.061	3.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE-M1 BAND12										
	MCH	QPSK	RB5#0	20.29	-0.17	-2.32	17.97	0.063	3.00	Pass
			RB1#0	20.28	-0.17	-2.32	17.96	0.063	3.00	Pass
		16-QAM	RB6#0	19.47	-0.17	-2.32	17.15	0.052	3.00	Pass
			RB1#0	20.49	-0.17	-2.32	18.17	0.066	3.00	Pass
		16-QAM	RB5#0	20.35	-0.17	-2.32	18.03	0.064	3.00	Pass
			RB1#0	20.19	-0.17	-2.32	17.87	0.061	3.00	Pass
	HCH	QPSK	RB6#0	19.43	-0.17	-2.32	17.11	0.051	3.00	Pass
			RB1#0	20.23	-0.17	-2.32	17.91	0.062	3.00	Pass
		16-QAM	RB1#0	20.23	-0.17	-2.32	17.91	0.062	3.00	Pass
			RB5#0	20.31	-0.17	-2.32	17.99	0.063	3.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE-M1 BAND13										
5 MHz	LCH	QPSK	RB1#0	21.12	0.02	-2.13	18.99	0.079	3.00	Pass
			RB6#0	20.11	0.02	-2.13	17.98	0.063	3.00	Pass
		16-QAM	RB1#0	21.01	0.02	-2.13	18.88	0.077	3.00	Pass
			RB5#0	20.05	0.02	-2.13	17.92	0.062	3.00	Pass
	MCH	QPSK	RB1#0	21.21	0.02	-2.13	19.08	0.081	3.00	Pass
			RB6#0	20.24	0.02	-2.13	18.11	0.065	3.00	Pass
		16-QAM	RB1#0	21.13	0.02	-2.13	19.00	0.079	3.00	Pass
			RB5#0	20.41	0.02	-2.13	18.28	0.067	3.00	Pass
	HCH	QPSK	RB1#0	21.22	0.02	-2.13	19.09	0.081	3.00	Pass
			RB6#0	20.23	0.02	-2.13	18.10	0.065	3.00	Pass
		16-QAM	RB1#0	21.22	0.02	-2.13	19.09	0.081	3.00	Pass
			RB5#0	20.35	0.02	-2.13	18.22	0.066	3.00	Pass
10 MHz	MCH	QPSK	RB1#0	21.27	0.02	-2.13	19.14	0.082	3.00	Pass
			RB6#0	20.03	0.02	-2.13	17.90	0.062	3.00	Pass
		16-QAM	RB1#0	20.71	0.02	-2.13	18.58	0.072	3.00	Pass
			RB5#0	20.86	0.02	-2.13	18.73	0.075	3.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE-M1 BAND25									
1.4 MHz	LCH	QPSK	RB1#0	21.06	1.15	22.21	0.166	2.00	Pass
			RB6#0	18.54	1.15	19.69	0.093	2.00	Pass
		16-QAM	RB1#0	19.77	1.15	20.92	0.124	2.00	Pass
			RB5#0	18.51	1.15	19.66	0.092	2.00	Pass
	MCH	QPSK	RB1#0	20.86	1.15	22.01	0.159	2.00	Pass
			RB6#0	18.78	1.15	19.93	0.098	2.00	Pass
		16-QAM	RB1#0	19.84	1.15	20.99	0.126	2.00	Pass
			RB5#0	18.81	1.15	19.96	0.099	2.00	Pass
	HCH	QPSK	RB1#0	21	1.15	22.15	0.164	2.00	Pass
			RB6#0	18.93	1.15	20.08	0.102	2.00	Pass
		16-QAM	RB1#0	20.05	1.15	21.20	0.132	2.00	Pass
			RB5#0	18.91	1.15	20.06	0.101	2.00	Pass
3 MHz	LCH	QPSK	RB1#0	20.74	1.15	21.89	0.155	2.00	Pass
			RB6#0	18.4	1.15	19.55	0.090	2.00	Pass
		16-QAM	RB1#0	19.44	1.15	20.59	0.115	2.00	Pass
			RB5#0	18.41	1.15	19.56	0.090	2.00	Pass
	MCH	QPSK	RB1#0	20.91	1.15	22.06	0.161	2.00	Pass
			RB6#0	18.7	1.15	19.85	0.097	2.00	Pass
		16-QAM	RB1#0	19.51	1.15	20.66	0.116	2.00	Pass
			RB5#0	18.79	1.15	19.94	0.099	2.00	Pass
	HCH	QPSK	RB1#0	21.13	1.15	22.28	0.169	2.00	Pass
			RB6#0	18.84	1.15	19.99	0.100	2.00	Pass
		16-QAM	RB1#0	19.99	1.15	21.14	0.130	2.00	Pass
			RB5#0	18.98	1.15	20.13	0.103	2.00	Pass
5 MHz	LCH	QPSK	RB1#0	20.64	1.15	21.79	0.151	2.00	Pass
			RB6#0	19.37	1.15	20.52	0.113	2.00	Pass
		16-QAM	RB1#0	20.61	1.15	21.76	0.150	2.00	Pass
			RB5#0	19.63	1.15	20.78	0.120	2.00	Pass
	MCH	QPSK	RB1#0	20.81	1.15	21.96	0.157	2.00	Pass
			RB6#0	19.54	1.15	20.69	0.117	2.00	Pass
		16-QAM	RB1#0	20.82	1.15	21.97	0.157	2.00	Pass
			RB5#0	19.4	1.15	20.55	0.114	2.00	Pass
	HCH	QPSK	RB1#0	21.06	1.15	22.21	0.166	2.00	Pass
			RB6#0	19.86	1.15	21.01	0.126	2.00	Pass
		16-QAM	RB1#0	21.14	1.15	22.29	0.169	2.00	Pass
			RB5#0	20.06	1.15	21.21	0.132	2.00	Pass
10 MHz	LCH	QPSK	RB1#0	20.63	1.15	21.78	0.151	2.00	Pass
			RB6#0	19.38	1.15	20.53	0.113	2.00	Pass
		16-QAM	RB1#0	20.67	1.15	21.82	0.152	2.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE-M1 BAND25									
	MCH	QPSK	RB5#0	20.6	1.15	21.75	0.150	2.00	Pass
			RB1#0	20.69	1.15	21.84	0.153	2.00	Pass
		16-QAM	RB6#0	19.59	1.15	20.74	0.119	2.00	Pass
			RB1#0	20.74	1.15	21.89	0.155	2.00	Pass
		HCH	RB5#0	20.62	1.15	21.77	0.150	2.00	Pass
			RB1#0	20.89	1.15	22.04	0.160	2.00	Pass
			RB6#0	19.66	1.15	20.81	0.121	2.00	Pass
			RB1#0	21.06	1.15	22.21	0.166	2.00	Pass
			RB5#0	19.69	1.15	20.84	0.121	2.00	Pass
15 MHz	LCH	QPSK	RB1#0	20.52	1.15	21.67	0.147	2.00	Pass
			RB6#0	20.51	1.15	21.66	0.147	2.00	Pass
		16-QAM	RB1#0	20.67	1.15	21.82	0.152	2.00	Pass
			RB5#0	20.36	1.15	21.51	0.142	2.00	Pass
	MCH	QPSK	RB1#0	20.72	1.15	21.87	0.154	2.00	Pass
			RB6#0	20.7	1.15	21.85	0.153	2.00	Pass
		16-QAM	RB1#0	20.84	1.15	21.99	0.158	2.00	Pass
			RB5#0	20.61	1.15	21.76	0.150	2.00	Pass
	HCH	QPSK	RB1#0	20.89	1.15	22.04	0.160	2.00	Pass
			RB6#0	20.86	1.15	22.01	0.159	2.00	Pass
		16-QAM	RB1#0	21.04	1.15	22.19	0.166	2.00	Pass
			RB5#0	21.06	1.15	22.21	0.166	2.00	Pass
20 MHz	LCH	QPSK	RB1#0	20.41	1.15	21.56	0.143	2.00	Pass
			RB6#0	20.36	1.15	21.51	0.142	2.00	Pass
		16-QAM	RB1#0	20.37	1.15	21.52	0.142	2.00	Pass
			RB5#0	20.39	1.15	21.54	0.143	2.00	Pass
	MCH	QPSK	RB1#0	20.63	1.15	21.78	0.151	2.00	Pass
			RB6#0	20.6	1.15	21.75	0.150	2.00	Pass
		16-QAM	RB1#0	20.73	1.15	21.88	0.154	2.00	Pass
			RB5#0	20.7	1.15	21.85	0.153	2.00	Pass
	HCH	QPSK	RB1#0	20.8	1.15	21.95	0.157	2.00	Pass
			RB6#0	20.78	1.15	21.93	0.156	2.00	Pass
		16-QAM	RB1#0	20.84	1.15	21.99	0.158	2.00	Pass
			RB5#0	20.94	1.15	22.09	0.162	2.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE-M1 BAND26 (part22)										
1.4 MHz	LCH	QPSK	RB1#0	20.73	0.25	-1.9	18.83	0.076	7.00	Pass
			RB6#0	18.91	0.25	-1.9	17.01	0.050	7.00	Pass
		16-QAM	RB1#0	20.14	0.25	-1.9	18.24	0.067	7.00	Pass
			RB5#0	18.92	0.25	-1.9	17.02	0.050	7.00	Pass
	MCH	QPSK	RB1#0	20.58	0.25	-1.9	18.68	0.074	7.00	Pass
			RB6#0	18.65	0.25	-1.9	16.75	0.047	7.00	Pass
		16-QAM	RB1#0	20	0.25	-1.9	18.10	0.065	7.00	Pass
			RB5#0	18.58	0.25	-1.9	16.68	0.047	7.00	Pass
	HCH	QPSK	RB1#0	21.22	0.25	-1.9	19.32	0.086	7.00	Pass
			RB6#0	18.88	0.25	-1.9	16.98	0.050	7.00	Pass
		16-QAM	RB1#0	19.75	0.25	-1.9	17.85	0.061	7.00	Pass
			RB5#0	18.91	0.25	-1.9	17.01	0.050	7.00	Pass
3 MHz	LCH	QPSK	RB1#0	21.05	0.25	-1.9	19.15	0.082	7.00	Pass
			RB6#0	18.77	0.25	-1.9	16.87	0.049	7.00	Pass
		16-QAM	RB1#0	20.16	0.25	-1.9	18.26	0.067	7.00	Pass
			RB5#0	18.88	0.25	-1.9	16.98	0.050	7.00	Pass
	MCH	QPSK	RB1#0	20.81	0.25	-1.9	18.91	0.078	7.00	Pass
			RB6#0	18.68	0.25	-1.9	16.78	0.048	7.00	Pass
		16-QAM	RB1#0	19.69	0.25	-1.9	17.79	0.060	7.00	Pass
			RB5#0	18.64	0.25	-1.9	16.74	0.047	7.00	Pass
	HCH	QPSK	RB1#0	21.02	0.25	-1.9	19.12	0.082	7.00	Pass
			RB6#0	18.82	0.25	-1.9	16.92	0.049	7.00	Pass
		16-QAM	RB1#0	19.71	0.25	-1.9	17.81	0.060	7.00	Pass
			RB5#0	18.9	0.25	-1.9	17.00	0.050	7.00	Pass
5 MHz	LCH	QPSK	RB1#0	21.04	0.25	-1.9	19.14	0.082	7.00	Pass
			RB6#0	19.94	0.25	-1.9	18.04	0.064	7.00	Pass
		16-QAM	RB1#0	20.9	0.25	-1.9	19.00	0.079	7.00	Pass
			RB5#0	20.11	0.25	-1.9	18.21	0.066	7.00	Pass
	MCH	QPSK	RB1#0	20.75	0.25	-1.9	18.85	0.077	7.00	Pass
			RB6#0	19.78	0.25	-1.9	17.88	0.061	7.00	Pass
		16-QAM	RB1#0	20.77	0.25	-1.9	18.87	0.077	7.00	Pass
			RB5#0	19.64	0.25	-1.9	17.74	0.059	7.00	Pass
	HCH	QPSK	RB1#0	20.78	0.25	-1.9	18.88	0.077	7.00	Pass
			RB6#0	20	0.25	-1.9	18.10	0.065	7.00	Pass
		16-QAM	RB1#0	20.83	0.25	-1.9	18.93	0.078	7.00	Pass
			RB5#0	19.72	0.25	-1.9	17.82	0.061	7.00	Pass
10 MHz	LCH	QPSK	RB1#0	21.01	0.25	-1.9	19.11	0.081	7.00	Pass
			RB6#0	19.85	0.25	-1.9	17.95	0.062	7.00	Pass
		16-QAM	RB1#0	21.09	0.25	-1.9	19.19	0.083	7.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE-M1 BAND26 (part22)										
		QPSK	RB5#0	21.1	0.25	-1.9	19.20	0.083	7.00	Pass
			RB1#0	20.74	0.25	-1.9	18.84	0.077	7.00	Pass
			RB6#0	19.65	0.25	-1.9	17.75	0.060	7.00	Pass
			RB1#0	20.82	0.25	-1.9	18.92	0.078	7.00	Pass
		16-QAM	RB5#0	20.64	0.25	-1.9	18.74	0.075	7.00	Pass
			RB1#0	20.71	0.25	-1.9	18.81	0.076	7.00	Pass
			RB6#0	19.79	0.25	-1.9	17.89	0.062	7.00	Pass
			RB1#0	20.78	0.25	-1.9	18.88	0.077	7.00	Pass
	HCH	16-QAM	RB5#0	21.02	0.25	-1.9	19.12	0.082	7.00	Pass
			RB1#0	21	0.25	-1.9	19.10	0.081	7.00	Pass
			RB6#0	20.94	0.25	-1.9	19.04	0.080	7.00	Pass
			RB1#0	21.01	0.25	-1.9	19.11	0.081	7.00	Pass
15 MHz		QPSK	RB5#0	21.04	0.25	-1.9	19.14	0.082	7.00	Pass
			RB1#0	20.77	0.25	-1.9	18.87	0.077	7.00	Pass
			RB6#0	20.81	0.25	-1.9	18.91	0.078	7.00	Pass
			RB1#0	20.99	0.25	-1.9	19.09	0.081	7.00	Pass
		16-QAM	RB5#0	20.93	0.25	-1.9	19.03	0.080	7.00	Pass
			RB1#0	20.67	0.25	-1.9	18.77	0.075	7.00	Pass
			RB6#0	20.76	0.25	-1.9	18.86	0.077	7.00	Pass
			RB1#0	20.81	0.25	-1.9	18.91	0.078	7.00	Pass
	MCH	QPSK	RB5#0	20.98	0.25	-1.9	19.08	0.081	7.00	Pass
			RB1#0	20.67	0.25	-1.9	18.77	0.075	7.00	Pass
			RB6#0	20.76	0.25	-1.9	18.86	0.077	7.00	Pass
			RB1#0	20.81	0.25	-1.9	18.91	0.078	7.00	Pass
	HCH	16-QAM	RB5#0	20.98	0.25	-1.9	19.08	0.081	7.00	Pass
			RB1#0	20.67	0.25	-1.9	18.77	0.075	7.00	Pass
			RB6#0	20.76	0.25	-1.9	18.86	0.077	7.00	Pass
			RB1#0	20.81	0.25	-1.9	18.91	0.078	7.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE-M1 BAND26 (part90)										
1.4 MHz	LCH	QPSK	RB1#0	20.81	0.25	-1.9	18.91	0.078	100	Pass
			RB6#0	19.07	0.25	-1.9	17.17	0.052	100	Pass
		16-QAM	RB1#0	20.12	0.25	-1.9	18.22	0.066	100	Pass
			RB5#0	19.15	0.25	-1.9	17.25	0.053	100	Pass
	MCH	QPSK	RB1#0	20.81	0.25	-1.9	18.91	0.078	100	Pass
			RB6#0	18.98	0.25	-1.9	17.08	0.051	100	Pass
		16-QAM	RB1#0	20.11	0.25	-1.9	18.21	0.066	100	Pass
			RB5#0	19.14	0.25	-1.9	17.24	0.053	100	Pass
	HCH	QPSK	RB1#0	20.78	0.25	-1.9	18.88	0.077	100	Pass
			RB6#0	18.99	0.25	-1.9	17.09	0.051	100	Pass
		16-QAM	RB1#0	20.16	0.25	-1.9	18.26	0.067	100	Pass
			RB5#0	18.92	0.25	-1.9	17.02	0.050	100	Pass
3 MHz	LCH	QPSK	RB1#0	21.05	0.25	-1.9	19.15	0.082	100	Pass
			RB6#0	18.9	0.25	-1.9	17.00	0.050	100	Pass
		16-QAM	RB1#0	20.26	0.25	-1.9	18.36	0.069	100	Pass
			RB5#0	18.99	0.25	-1.9	17.09	0.051	100	Pass
	MCH	QPSK	RB1#0	21.09	0.25	-1.9	19.19	0.083	100	Pass
			RB6#0	18.95	0.25	-1.9	17.05	0.051	100	Pass
		16-QAM	RB1#0	20.07	0.25	-1.9	18.17	0.066	100	Pass
			RB5#0	18.83	0.25	-1.9	16.93	0.049	100	Pass
	HCH	QPSK	RB1#0	21.09	0.25	-1.9	19.19	0.083	100	Pass
			RB6#0	18.96	0.25	-1.9	17.06	0.051	100	Pass
		16-QAM	RB1#0	20.24	0.25	-1.9	18.34	0.068	100	Pass
			RB5#0	18.82	0.25	-1.9	16.92	0.049	100	Pass
5 MHz	LCH	QPSK	RB1#0	21.05	0.25	-1.9	19.15	0.082	100	Pass
			RB6#0	19.98	0.25	-1.9	18.08	0.064	100	Pass
		16-QAM	RB1#0	21.22	0.25	-1.9	19.32	0.086	100	Pass
			RB5#0	20.28	0.25	-1.9	18.38	0.069	100	Pass
	MCH	QPSK	RB1#0	21.04	0.25	-1.9	19.14	0.082	100	Pass
			RB6#0	20.06	0.25	-1.9	18.16	0.065	100	Pass
		16-QAM	RB1#0	21.29	0.25	-1.9	19.39	0.087	100	Pass
			RB5#0	20.29	0.25	-1.9	18.39	0.069	100	Pass
	HCH	QPSK	RB1#0	21.06	0.25	-1.9	19.16	0.082	100	Pass
			RB6#0	19.88	0.25	-1.9	17.98	0.063	100	Pass
		16-QAM	RB1#0	21.31	0.25	-1.9	19.41	0.087	100	Pass
			RB5#0	20.22	0.25	-1.9	18.32	0.068	100	Pass
10 MHz	MCH	QPSK	RB1#0	21.02	0.25	-1.9	19.12	0.082	100	Pass
			RB6#0	19.99	0.25	-1.9	18.09	0.064	100	Pass
		16-QAM	RB1#0	21.09	0.25	-1.9	19.19	0.083	100	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE-M1 BAND26 (part90)										
			RB5#0	21.18	0.25	-1.9	19.28	0.085	100	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE-M1 BAND66									
1.4 MHz	LCH	QPSK	RB1#0	20.9	1.15	22.05	0.160	1.00	Pass
			RB6#0	18.65	1.15	19.80	0.095	1.00	Pass
		16-QAM	RB1#0	19.79	1.15	20.94	0.124	1.00	Pass
			RB5#0	18.71	1.15	19.86	0.097	1.00	Pass
	MCH	QPSK	RB1#0	20.85	1.15	22.00	0.158	1.00	Pass
			RB6#0	18.54	1.15	19.69	0.093	1.00	Pass
		16-QAM	RB1#0	19.72	1.15	20.87	0.122	1.00	Pass
			RB5#0	18.65	1.15	19.80	0.095	1.00	Pass
	HCH	QPSK	RB1#0	21.01	1.15	22.16	0.164	1.00	Pass
			RB6#0	18.97	1.15	20.12	0.103	1.00	Pass
		16-QAM	RB1#0	20.35	1.15	21.50	0.141	1.00	Pass
			RB5#0	18.83	1.15	19.98	0.100	1.00	Pass
3 MHz	LCH	QPSK	RB1#0	20.95	1.15	22.10	0.162	1.00	Pass
			RB6#0	18.5	1.15	19.65	0.092	1.00	Pass
		16-QAM	RB1#0	19.8	1.15	20.95	0.124	1.00	Pass
			RB5#0	18.49	1.15	19.64	0.092	1.00	Pass
	MCH	QPSK	RB1#0	20.93	1.15	22.08	0.161	1.00	Pass
			RB6#0	18.57	1.15	19.72	0.094	1.00	Pass
		16-QAM	RB1#0	19.46	1.15	20.61	0.115	1.00	Pass
			RB5#0	18.6	1.15	19.75	0.094	1.00	Pass
	HCH	QPSK	RB1#0	21.34	1.15	22.49	0.177	1.00	Pass
			RB6#0	18.99	1.15	20.14	0.103	1.00	Pass
		16-QAM	RB1#0	19.92	1.15	21.07	0.128	1.00	Pass
			RB5#0	18.89	1.15	20.04	0.101	1.00	Pass
5 MHz	LCH	QPSK	RB1#0	20.89	1.15	22.04	0.160	1.00	Pass
			RB6#0	19.6	1.15	20.75	0.119	1.00	Pass
		16-QAM	RB1#0	21.03	1.15	22.18	0.165	1.00	Pass
			RB5#0	19.78	1.15	20.93	0.124	1.00	Pass
	MCH	QPSK	RB1#0	20.66	1.15	21.81	0.152	1.00	Pass
			RB6#0	19.61	1.15	20.76	0.119	1.00	Pass
		16-QAM	RB1#0	21.07	1.15	22.22	0.167	1.00	Pass
			RB5#0	19.65	1.15	20.80	0.120	1.00	Pass
	HCH	QPSK	RB1#0	21.19	1.15	22.34	0.171	1.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE-M1 BAND66									
10 MHz		16-QAM	RB6#0	19.98	1.15	21.13	0.130	1.00	Pass
			RB1#0	21.5	1.15	22.65	0.184	1.00	Pass
			RB5#0	20.05	1.15	21.20	0.132	1.00	Pass
	LCH	QPSK	RB1#0	20.86	1.15	22.01	0.159	1.00	Pass
			RB6#0	19.62	1.15	20.77	0.119	1.00	Pass
		16-QAM	RB1#0	20.98	1.15	22.13	0.163	1.00	Pass
			RB5#0	20.84	1.15	21.99	0.158	1.00	Pass
	MCH	QPSK	RB1#0	20.88	1.15	22.03	0.160	1.00	Pass
			RB6#0	19.52	1.15	20.67	0.117	1.00	Pass
		16-QAM	RB1#0	21.06	1.15	22.21	0.166	1.00	Pass
			RB5#0	20.82	1.15	21.97	0.157	1.00	Pass
	HCH	QPSK	RB1#0	20.67	1.15	21.82	0.152	1.00	Pass
			RB6#0	20.63	1.15	21.78	0.151	1.00	Pass
15 MHz	LCH	QPSK	RB1#0	20.95	1.15	22.10	0.162	1.00	Pass
			RB6#0	20.89	1.15	22.04	0.160	1.00	Pass
		16-QAM	RB1#0	21.07	1.15	22.22	0.167	1.00	Pass
			RB5#0	20.92	1.15	22.07	0.161	1.00	Pass
	MCH	QPSK	RB1#0	20.94	1.15	22.09	0.162	1.00	Pass
			RB6#0	20.8	1.15	21.95	0.157	1.00	Pass
		16-QAM	RB1#0	20.67	1.15	21.82	0.152	1.00	Pass
			RB5#0	20.7	1.15	21.85	0.153	1.00	Pass
	HCH	QPSK	RB1#0	20.55	1.15	21.70	0.148	1.00	Pass
			RB6#0	20.61	1.15	21.76	0.150	1.00	Pass
		16-QAM	RB1#0	20.75	1.15	21.90	0.155	1.00	Pass
			RB5#0	20.6	1.15	21.75	0.150	1.00	Pass
20 MHz	LCH	QPSK	RB1#0	20.94	1.15	22.09	0.162	1.00	Pass
			RB6#0	20.88	1.15	22.03	0.160	1.00	Pass
		16-QAM	RB1#0	21.01	1.15	22.16	0.164	1.00	Pass
			RB5#0	20.84	1.15	21.99	0.158	1.00	Pass
	MCH	QPSK	RB1#0	20.98	1.15	22.13	0.163	1.00	Pass
			RB6#0	20.9	1.15	22.05	0.160	1.00	Pass
		16-QAM	RB1#0	21.29	1.15	22.44	0.175	1.00	Pass
			RB5#0	20.98	1.15	22.13	0.163	1.00	Pass
	HCH	QPSK	RB1#0	20.63	1.15	21.78	0.151	1.00	Pass
			RB6#0	20.58	1.15	21.73	0.149	1.00	Pass
		16-QAM	RB1#0	20.7	1.15	21.85	0.153	1.00	Pass
			RB5#0	20.63	1.15	21.78	0.151	1.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE-M1 BAND85										
5 MHz	LCH	QPSK	RB1#0	20.11	-0.17	-2.32	17.79	0.060	3.00	Pass
			RB6#0	19.08	-0.17	-2.32	16.76	0.047	3.00	Pass
		16-QAM	RB1#0	20.15	-0.17	-2.32	17.83	0.061	3.00	Pass
			RB5#0	18.99	-0.17	-2.32	16.67	0.046	3.00	Pass
	MCH	QPSK	RB1#0	20.45	-0.17	-2.32	18.13	0.065	3.00	Pass
			RB6#0	19.46	-0.17	-2.32	17.14	0.052	3.00	Pass
		16-QAM	RB1#0	20.48	-0.17	-2.32	18.16	0.065	3.00	Pass
			RB5#0	19.3	-0.17	-2.32	16.98	0.050	3.00	Pass
	HCH	QPSK	RB1#0	20.41	-0.17	-2.32	18.09	0.064	3.00	Pass
			RB6#0	19.33	-0.17	-2.32	17.01	0.050	3.00	Pass
		16-QAM	RB1#0	20.24	-0.17	-2.32	17.92	0.062	3.00	Pass
			RB5#0	19.35	-0.17	-2.32	17.03	0.050	3.00	Pass
10 MHz	LCH	QPSK	RB1#0	20.06	-0.17	-2.32	17.74	0.059	3.00	Pass
			RB6#0	19.12	-0.17	-2.32	16.80	0.048	3.00	Pass
		16-QAM	RB1#0	19.94	-0.17	-2.32	17.62	0.058	3.00	Pass
			RB5#0	20.09	-0.17	-2.32	17.77	0.060	3.00	Pass
	MCH	QPSK	RB1#0	20.3	-0.17	-2.32	17.98	0.063	3.00	Pass
			RB6#0	19.28	-0.17	-2.32	16.96	0.050	3.00	Pass
		16-QAM	RB1#0	20.41	-0.17	-2.32	18.09	0.064	3.00	Pass
			RB5#0	20.26	-0.17	-2.32	17.94	0.062	3.00	Pass
	HCH	QPSK	RB1#0	20.51	-0.17	-2.32	18.19	0.066	3.00	Pass
			RB6#0	19.46	-0.17	-2.32	17.14	0.052	3.00	Pass
		16-QAM	RB1#0	20.58	-0.17	-2.32	18.26	0.067	3.00	Pass
			RB5#0	20.54	-0.17	-2.32	18.22	0.066	3.00	Pass

NB-IoT Mode Test Data

Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
NB-IoT BAND2									
3.75kHz	LCH	QPSK	RB1#0	20.59	1.15	21.74	0.149	2.00	Pass
			RB1#47	20.52	1.15	21.67	0.147	2.00	Pass
		BPSK	RB1#0	20.56	1.15	21.71	0.148	2.00	Pass
			RB1#47	20.54	1.15	21.69	0.148	2.00	Pass
	MCH	QPSK	RB1#0	20.7	1.15	21.85	0.153	2.00	Pass
			RB1#47	20.71	1.15	21.86	0.153	2.00	Pass
		BPSK	RB1#0	20.69	1.15	21.84	0.153	2.00	Pass
			RB1#47	20.66	1.15	21.81	0.152	2.00	Pass
	HCH	QPSK	RB1#0	20.83	1.15	21.98	0.158	2.00	Pass
			RB1#47	20.76	1.15	21.91	0.155	2.00	Pass
		BPSK	RB1#0	20.76	1.15	21.91	0.155	2.00	Pass
			RB1#47	20.74	1.15	21.89	0.155	2.00	Pass
15kHz	LCH	QPSK	RB1#0	20.79	1.15	21.94	0.156	2.00	Pass
			RB1#11	20.66	1.15	21.81	0.152	2.00	Pass
			RB12#0	18.58	1.15	19.73	0.094	2.00	Pass
		BPSK	RB1#0	20.61	1.15	21.76	0.150	2.00	Pass
			RB1#11	20.66	1.15	21.81	0.152	2.00	Pass
	MCH	QPSK	RB1#0	20.76	1.15	21.91	0.155	2.00	Pass
			RB1#11	20.75	1.15	21.90	0.155	2.00	Pass
			RB12#0	18.55	1.15	19.70	0.093	2.00	Pass
		BPSK	RB1#0	20.68	1.15	21.83	0.152	2.00	Pass
			RB1#11	20.68	1.15	21.83	0.152	2.00	Pass
	HCH	QPSK	RB1#0	20.9	1.15	22.05	0.160	2.00	Pass
			RB1#11	20.83	1.15	21.98	0.158	2.00	Pass
			RB12#0	18.49	1.15	19.64	0.092	2.00	Pass
		BPSK	RB1#0	20.81	1.15	21.96	0.157	2.00	Pass
			RB1#11	20.69	1.15	21.84	0.153	2.00	Pass

Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
NB-IoT BAND4									
3.75kHz	LCH	QPSK	RB1#0	20.43	1.15	21.58	0.144	1.00	Pass
			RB1#47	20.38	1.15	21.53	0.142	1.00	Pass
		BPSK	RB1#0	20.39	1.15	21.54	0.143	1.00	Pass
			RB1#47	20.55	1.15	21.70	0.148	1.00	Pass
	MCH	QPSK	RB1#0	20.59	1.15	21.74	0.149	1.00	Pass
			RB1#47	20.52	1.15	21.67	0.147	1.00	Pass
		BPSK	RB1#0	20.48	1.15	21.63	0.146	1.00	Pass
			RB1#47	20.49	1.15	21.64	0.146	1.00	Pass
	HCH	QPSK	RB1#0	20.65	1.15	21.80	0.151	1.00	Pass
			RB1#47	20.64	1.15	21.79	0.151	1.00	Pass
		BPSK	RB1#0	20.58	1.15	21.73	0.149	1.00	Pass
			RB1#47	20.59	1.15	21.74	0.149	1.00	Pass
15kHz	LCH	QPSK	RB1#0	20.68	1.15	21.83	0.152	1.00	Pass
			RB1#11	20.6	1.15	21.75	0.150	1.00	Pass
			RB12#0	18.47	1.15	19.62	0.092	1.00	Pass
		BPSK	RB1#0	20.3	1.15	21.45	0.140	1.00	Pass
			RB1#11	20.42	1.15	21.57	0.144	1.00	Pass
	MCH	QPSK	RB1#0	20.47	1.15	21.62	0.145	1.00	Pass
			RB1#11	20.4	1.15	21.55	0.143	1.00	Pass
			RB12#0	18.23	1.15	19.38	0.087	1.00	Pass
		BPSK	RB1#0	20.35	1.15	21.50	0.141	1.00	Pass
			RB1#11	20.28	1.15	21.43	0.139	1.00	Pass
	HCH	QPSK	RB1#0	20.48	1.15	21.63	0.146	1.00	Pass
			RB1#11	20.45	1.15	21.60	0.145	1.00	Pass
			RB12#0	18.4	1.15	19.55	0.090	1.00	Pass
		BPSK	RB1#0	20.37	1.15	21.52	0.142	1.00	Pass
			RB1#11	20.35	1.15	21.50	0.141	1.00	Pass

Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Off set)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
NB-IoT BAND5										
3.75kHz	LCH	QPSK	RB1#0	20.19	0.25	-1.9	18.29	0.067	7.00	Pass
			RB1#47	20.15	0.25	-1.9	18.25	0.067	7.00	Pass
		BPSK	RB1#0	20.19	0.25	-1.9	18.29	0.067	7.00	Pass
			RB1#47	20.11	0.25	-1.9	18.21	0.066	7.00	Pass
	MCH	QPSK	RB1#0	20.29	0.25	-1.9	18.39	0.069	7.00	Pass
			RB1#47	20.22	0.25	-1.9	18.32	0.068	7.00	Pass
		BPSK	RB1#0	20.24	0.25	-1.9	18.34	0.068	7.00	Pass
			RB1#47	20.23	0.25	-1.9	18.33	0.068	7.00	Pass
	HCH	QPSK	RB1#0	20.29	0.25	-1.9	18.39	0.069	7.00	Pass
			RB1#47	20.25	0.25	-1.9	18.35	0.068	7.00	Pass
		BPSK	RB1#0	20.16	0.25	-1.9	18.26	0.067	7.00	Pass
			RB1#47	20.13	0.25	-1.9	18.23	0.067	7.00	Pass
15kHz	LCH	QPSK	RB1#0	20.42	0.25	-1.9	18.52	0.071	7.00	Pass
			RB1#11	20.33	0.25	-1.9	18.43	0.070	7.00	Pass
			RB12#0	18.28	0.25	-1.9	16.38	0.043	7.00	Pass
		BPSK	RB1#0	20.32	0.25	-1.9	18.42	0.070	7.00	Pass
			RB1#11	20.24	0.25	-1.9	18.34	0.068	7.00	Pass
	MCH	QPSK	RB1#0	20.43	0.25	-1.9	18.53	0.071	7.00	Pass
			RB1#11	20.39	0.25	-1.9	18.49	0.071	7.00	Pass
			RB12#0	18.42	0.25	-1.9	16.52	0.045	7.00	Pass
		BPSK	RB1#0	20.31	0.25	-1.9	18.41	0.069	7.00	Pass
			RB1#11	20.25	0.25	-1.9	18.35	0.068	7.00	Pass
	HCH	QPSK	RB1#0	20.37	0.25	-1.9	18.47	0.070	7.00	Pass
			RB1#11	20.43	0.25	-1.9	18.53	0.071	7.00	Pass
			RB12#0	18.5	0.25	-1.9	16.60	0.046	7.00	Pass
		BPSK	RB1#0	20.43	0.25	-1.9	18.53	0.071	7.00	Pass
			RB1#11	20.38	0.25	-1.9	18.48	0.070	7.00	Pass

Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Off set)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
NB-IoT BAND12										
3.75kHz	LCH	QPSK	RB1#0	20.25	-0.17	-2.32	17.93	0.062	3.00	Pass
			RB1#47	20.19	-0.17	-2.32	17.87	0.061	3.00	Pass
		BPSK	RB1#0	20.32	-0.17	-2.32	18.00	0.063	3.00	Pass
			RB1#47	20.18	-0.17	-2.32	17.86	0.061	3.00	Pass
	MCH	QPSK	RB1#0	20.4	-0.17	-2.32	18.08	0.064	3.00	Pass
			RB1#47	20.32	-0.17	-2.32	18.00	0.063	3.00	Pass
		BPSK	RB1#0	20.25	-0.17	-2.32	17.93	0.062	3.00	Pass
			RB1#47	20.27	-0.17	-2.32	17.95	0.062	3.00	Pass
	HCH	QPSK	RB1#0	20.34	-0.17	-2.32	18.02	0.063	3.00	Pass
			RB1#47	20.29	-0.17	-2.32	17.97	0.063	3.00	Pass
		BPSK	RB1#0	20.32	-0.17	-2.32	18.00	0.063	3.00	Pass
			RB1#47	20.32	-0.17	-2.32	18.00	0.063	3.00	Pass
15kHz	LCH	QPSK	RB1#0	20.06	-0.17	-2.32	17.74	0.059	3.00	Pass
			RB1#11	20.03	-0.17	-2.32	17.71	0.059	3.00	Pass
			RB12#0	18.16	-0.17	-2.32	15.84	0.038	3.00	Pass
		BPSK	RB1#0	20.24	-0.17	-2.32	17.92	0.062	3.00	Pass
			RB1#11	20.14	-0.17	-2.32	17.82	0.061	3.00	Pass
	MCH	QPSK	RB1#0	20.43	-0.17	-2.32	18.11	0.065	3.00	Pass
			RB1#11	20.39	-0.17	-2.32	18.07	0.064	3.00	Pass
			RB12#0	18.35	-0.17	-2.32	16.03	0.040	3.00	Pass
		BPSK	RB1#0	20.28	-0.17	-2.32	17.96	0.063	3.00	Pass
			RB1#11	20.26	-0.17	-2.32	17.94	0.062	3.00	Pass
	HCH	QPSK	RB1#0	20.57	-0.17	-2.32	18.25	0.067	3.00	Pass
			RB1#11	20.5	-0.17	-2.32	18.18	0.066	3.00	Pass
			RB12#0	18.46	-0.17	-2.32	16.14	0.041	3.00	Pass
		BPSK	RB1#0	20.39	-0.17	-2.32	18.07	0.064	3.00	Pass
			RB1#11	20.33	-0.17	-2.32	18.01	0.063	3.00	Pass

Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Off set)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
NB-IoT BAND13										
3.75kHz	LCH	QPSK	RB1#0	20.84	0.02	-2.13	18.71	0.074	3.00	Pass
			RB1#47	20.9	0.02	-2.13	18.77	0.075	3.00	Pass
		BPSK	RB1#0	20.94	0.02	-2.13	18.81	0.076	3.00	Pass
			RB1#47	20.92	0.02	-2.13	18.79	0.076	3.00	Pass
	MCH	QPSK	RB1#0	21	0.02	-2.13	18.87	0.077	3.00	Pass
			RB1#47	20.91	0.02	-2.13	18.78	0.076	3.00	Pass
		BPSK	RB1#0	20.93	0.02	-2.13	18.80	0.076	3.00	Pass
			RB1#47	20.92	0.02	-2.13	18.79	0.076	3.00	Pass
	HCH	QPSK	RB1#0	20.87	0.02	-2.13	18.74	0.075	3.00	Pass
			RB1#47	20.92	0.02	-2.13	18.79	0.076	3.00	Pass
		BPSK	RB1#0	20.91	0.02	-2.13	18.78	0.076	3.00	Pass
			RB1#47	20.89	0.02	-2.13	18.76	0.075	3.00	Pass
15kHz	LCH	QPSK	RB1#0	21.09	0.02	-2.13	18.96	0.079	3.00	Pass
			RB1#11	21.04	0.02	-2.13	18.91	0.078	3.00	Pass
			RB12#0	19.07	0.02	-2.13	16.94	0.049	3.00	Pass
		BPSK	RB1#0	21.02	0.02	-2.13	18.89	0.077	3.00	Pass
			RB1#11	21	0.02	-2.13	18.87	0.077	3.00	Pass
	MCH	QPSK	RB1#0	21.17	0.02	-2.13	19.04	0.080	3.00	Pass
			RB1#11	21.16	0.02	-2.13	19.03	0.080	3.00	Pass
			RB12#0	19.09	0.02	-2.13	16.96	0.050	3.00	Pass
		BPSK	RB1#0	21.02	0.02	-2.13	18.89	0.077	3.00	Pass
			RB1#11	20.95	0.02	-2.13	18.82	0.076	3.00	Pass
	HCH	QPSK	RB1#0	21.07	0.02	-2.13	18.94	0.078	3.00	Pass
			RB1#11	21	0.02	-2.13	18.87	0.077	3.00	Pass
			RB12#0	19.13	0.02	-2.13	17.00	0.050	3.00	Pass
		BPSK	RB1#0	20.88	0.02	-2.13	18.75	0.075	3.00	Pass
			RB1#11	20.88	0.02	-2.13	18.75	0.075	3.00	Pass

Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
NB-IoT BAND25									
3.75kHz	LCH	QPSK	RB1#0	20.48	1.15	21.63	0.146	2.00	Pass
			RB1#47	20.44	1.15	21.59	0.144	2.00	Pass
		BPSK	RB1#0	20.46	1.15	21.61	0.145	2.00	Pass
			RB1#47	20.42	1.15	21.57	0.144	2.00	Pass
	MCH	QPSK	RB1#0	20.66	1.15	21.81	0.152	2.00	Pass
			RB1#47	20.65	1.15	21.80	0.151	2.00	Pass
		BPSK	RB1#0	20.63	1.15	21.78	0.151	2.00	Pass
			RB1#47	20.54	1.15	21.69	0.148	2.00	Pass
	HCH	QPSK	RB1#0	21.11	1.15	22.26	0.168	2.00	Pass
			RB1#47	20.95	1.15	22.10	0.162	2.00	Pass
		BPSK	RB1#0	21.03	1.15	22.18	0.165	2.00	Pass
			RB1#47	21.03	1.15	22.18	0.165	2.00	Pass
15kHz	LCH	QPSK	RB1#0	20.47	1.15	21.62	0.145	2.00	Pass
			RB1#11	20.36	1.15	21.51	0.142	2.00	Pass
			RB12#0	18.36	1.15	19.51	0.089	2.00	Pass
		BPSK	RB1#0	20.2	1.15	21.35	0.136	2.00	Pass
			RB1#11	20.21	1.15	21.36	0.137	2.00	Pass
	MCH	QPSK	RB1#0	20.67	1.15	21.82	0.152	2.00	Pass
			RB1#11	20.69	1.15	21.84	0.153	2.00	Pass
			RB12#0	18.63	1.15	19.78	0.095	2.00	Pass
		BPSK	RB1#0	20.47	1.15	21.62	0.145	2.00	Pass
			RB1#11	20.52	1.15	21.67	0.147	2.00	Pass
	HCH	QPSK	RB1#0	21.1	1.15	22.25	0.168	2.00	Pass
			RB1#11	21.15	1.15	22.30	0.170	2.00	Pass
			RB12#0	18.91	1.15	20.06	0.101	2.00	Pass
		BPSK	RB1#0	21.01	1.15	22.16	0.164	2.00	Pass
			RB1#11	20.97	1.15	22.12	0.163	2.00	Pass

Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
NB-IoT BAND66									
3.75kHz	LCH	QPSK	RB1#0	20.56	1.15	21.71	0.148	1.00	Pass
			RB1#47	20.51	1.15	21.66	0.147	1.00	Pass
		BPSK	RB1#0	20.49	1.15	21.64	0.146	1.00	Pass
			RB1#47	20.49	1.15	21.64	0.146	1.00	Pass
	MCH	QPSK	RB1#0	20.53	1.15	21.68	0.147	1.00	Pass
			RB1#47	20.51	1.15	21.66	0.147	1.00	Pass
		BPSK	RB1#0	20.46	1.15	21.61	0.145	1.00	Pass
			RB1#47	20.43	1.15	21.58	0.144	1.00	Pass
	HCH	QPSK	RB1#0	20.48	1.15	21.63	0.146	1.00	Pass
			RB1#47	20.48	1.15	21.63	0.146	1.00	Pass
		BPSK	RB1#0	20.59	1.15	21.74	0.149	1.00	Pass
			RB1#47	20.48	1.15	21.63	0.146	1.00	Pass
15kHz	LCH	QPSK	RB1#0	20.45	1.15	21.60	0.145	1.00	Pass
			RB1#11	20.39	1.15	21.54	0.143	1.00	Pass
			RB12#0	18.12	1.15	19.27	0.085	1.00	Pass
		BPSK	RB1#0	20.26	1.15	21.41	0.138	1.00	Pass
			RB1#11	20.22	1.15	21.37	0.137	1.00	Pass
	MCH	QPSK	RB1#0	20.73	1.15	21.88	0.154	1.00	Pass
			RB1#11	20.63	1.15	21.78	0.151	1.00	Pass
			RB12#0	18.42	1.15	19.57	0.091	1.00	Pass
		BPSK	RB1#0	20.57	1.15	21.72	0.149	1.00	Pass
			RB1#11	20.54	1.15	21.69	0.148	1.00	Pass
	HCH	QPSK	RB1#0	20.86	1.15	22.01	0.159	1.00	Pass
			RB1#11	20.7	1.15	21.85	0.153	1.00	Pass
			RB12#0	18.38	1.15	19.53	0.090	1.00	Pass
		BPSK	RB1#0	20.29	1.15	21.44	0.139	1.00	Pass
			RB1#11	20.72	1.15	21.87	0.154	1.00	Pass

Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Off set)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
NB-IoT BAND85										
3.75kHz	LCH	QPSK	RB1#0	20.18	-0.17	-2.32	17.86	0.061	3.00	Pass
			RB1#47	20.11	-0.17	-2.32	17.79	0.060	3.00	Pass
		BPSK	RB1#0	20.16	-0.17	-2.32	17.84	0.061	3.00	Pass
			RB1#47	20.12	-0.17	-2.32	17.80	0.060	3.00	Pass
	MCH	QPSK	RB1#0	20.57	-0.17	-2.32	18.25	0.067	3.00	Pass
			RB1#47	20.53	-0.17	-2.32	18.21	0.066	3.00	Pass
		BPSK	RB1#0	20.54	-0.17	-2.32	18.22	0.066	3.00	Pass
			RB1#47	20.48	-0.17	-2.32	18.16	0.065	3.00	Pass
	HCH	QPSK	RB1#0	20.51	-0.17	-2.32	18.19	0.066	3.00	Pass
			RB1#47	20.39	-0.17	-2.32	18.07	0.064	3.00	Pass
		BPSK	RB1#0	20.41	-0.17	-2.32	18.09	0.064	3.00	Pass
			RB1#47	20.29	-0.17	-2.32	17.97	0.063	3.00	Pass
15kHz	LCH	QPSK	RB1#0	20.31	-0.17	-2.32	17.99	0.063	3.00	Pass
			RB1#11	20.24	-0.17	-2.32	17.92	0.062	3.00	Pass
			RB12#0	18.37	-0.17	-2.32	16.05	0.040	3.00	Pass
		BPSK	RB1#0	20.21	-0.17	-2.32	17.89	0.062	3.00	Pass
			RB1#11	20.13	-0.17	-2.32	17.81	0.060	3.00	Pass
	MCH	QPSK	RB1#0	20.74	-0.17	-2.32	18.42	0.070	3.00	Pass
			RB1#11	20.69	-0.17	-2.32	18.37	0.069	3.00	Pass
			RB12#0	18.7	-0.17	-2.32	16.38	0.043	3.00	Pass
		BPSK	RB1#0	20.63	-0.17	-2.32	18.31	0.068	3.00	Pass
			RB1#11	20.51	-0.17	-2.32	18.19	0.066	3.00	Pass
	HCH	QPSK	RB1#0	20.59	-0.17	-2.32	18.27	0.067	3.00	Pass
			RB1#11	20.54	-0.17	-2.32	18.22	0.066	3.00	Pass
			RB12#0	18.59	-0.17	-2.32	16.27	0.042	3.00	Pass
		BPSK	RB1#0	20.42	-0.17	-2.32	18.10	0.065	3.00	Pass
			RB1#11	20.39	-0.17	-2.32	18.07	0.064	3.00	Pass

A.2 Peak to Average Ratio

Note 1: For average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB. For GPRS and EGPRS, there are peak power to demonstrate compliance, PAR measurements are not required.

Note 2: Test plots please refer to the document "Annex No.: BL-SZ2140097-501 Data Part 1.pdf".

LTE-M1 Mode Test Data

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Peak to Average Ratio (dB)	Limit (dB)	Refer to Plot ^{Note2}	Verdict
LTE-M1 Band 2	20 MHz	LCH	QPSK	RB6#0	8.58	13	1.1	Pass
			16-QAM	RB5#0	8.91	13	1.2	Pass
		MCH	QPSK	RB6#0	8.77	13	1.3	Pass
			16-QAM	RB5#0	9	13	1.4	Pass
		HCH	QPSK	RB6#0	8.81	13	1.5	Pass
			16-QAM	RB5#0	9.05	13	1.6	Pass
LTE-M1 Band 4	20 MHz	LCH	QPSK	RB6#0	8.62	13	2.1	Pass
			16-QAM	RB5#0	8.91	13	2.2	Pass
		MCH	QPSK	RB6#0	8.72	13	2.3	Pass
			16-QAM	RB5#0	8.95	13	2.4	Pass
		HCH	QPSK	RB6#0	8.81	13	2.5	Pass
			16-QAM	RB5#0	9.14	13	2.6	Pass
LTE-M1 Band 5	10 MHz	LCH	QPSK	RB6#0	9.84	13	3.1	Pass
			16-QAM	RB5#0	10.12	13	3.2	Pass
		MCH	QPSK	RB6#0	9.84	13	3.3	Pass
			16-QAM	RB5#0	10.08	13	3.4	Pass
		HCH	QPSK	RB6#0	9.84	13	3.5	Pass
			16-QAM	RB5#0	10.08	13	3.6	Pass
LTE-M1 Band 12	10 MHz	LCH	QPSK	RB6#0	9.56	13	4.1	Pass
			16-QAM	RB5#0	9.7	13	4.2	Pass
		MCH	QPSK	RB6#0	9.56	13	4.3	Pass
			16-QAM	RB5#0	9.89	13	4.4	Pass
		HCH	QPSK	RB6#0	9.56	13	4.5	Pass
			16-QAM	RB5#0	9.75	13	4.6	Pass
LTE-M1 Band 13	10 MHz	MCH	QPSK	RB6#0	9.75	13	5.1	Pass
			16-QAM	RB5#0	9.84	13	5.2	Pass
LTE-M1 Band 25	20 MHz	LCH	QPSK	RB6#0	9.45	13	6.1	Pass
			16-QAM	RB5#0	9.77	13	6.2	Pass
		MCH	QPSK	RB6#0	9.48	13	6.3	Pass
			16-QAM	RB5#0	9.76	13	6.4	Pass
		HCH	QPSK	RB6#0	9.45	13	6.5	Pass
			16-QAM	RB5#0	9.72	13	6.6	Pass
LTE-M1 Band 26	10 MHz	LCH	QPSK	RB6#0	9.75	13	7.1	Pass
			16-QAM	RB5#0	9.8	13	7.2	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Peak to Average Ratio (dB)	Limit (dB)	Refer to Plot ^{Note2}	Verdict
(part22)		MCH	QPSK	RB6#0	9.75	13	7.3	Pass
			16-QAM	RB5#0	9.89	13	7.4	Pass
		HCH	QPSK	RB6#0	9.75	13	7.5	Pass
			16-QAM	RB5#0	9.94	13	7.6	Pass
LTE-M1 Band 26 (part90)	10 MHz	MCH	QPSK	RB6#0	9.23	13	8.1	Pass
			16-QAM	RB5#0	10.06	13	8.2	Pass
LTE-M1 Band 66	20 MHz	LCH	QPSK	RB6#0	9.11	13	9.1	Pass
			16-QAM	RB5#0	9.57	13	9.2	Pass
		MCH	QPSK	RB6#0	9.12	13	9.3	Pass
			16-QAM	RB5#0	9.43	13	9.4	Pass
		HCH	QPSK	RB6#0	9.26	13	9.5	Pass
			16-QAM	RB5#0	9.58	13	9.6	Pass
LTE-M1 Band 85	10 MHz	LCH	QPSK	RB6#0	9.67	13	10.1	Pass
			16-QAM	RB5#0	10.25	13	10.2	Pass
		MCH	QPSK	RB6#0	9.64	13	10.3	Pass
			16-QAM	RB5#0	10.15	13	10.4	Pass
		HCH	QPSK	RB6#0	9.65	13	10.5	Pass
			16-QAM	RB5#0	10.17	13	10.6	Pass

NB-IoT Mode Test Data

Test Band	Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Offset)	Peak to Average Ratio (dB)	Limit (dB)	Refer to Plot ^{Note2}	Verdict
NB-IoT Band 2	3.75kHz	LCH	QPSK	RB1#0	1.62	13	11.1	Pass
			BPSK	RB1#0	1.74	13	11.2	Pass
		MCH	QPSK	RB1#0	1.57	13	11.3	Pass
			BPSK	RB1#0	1.8	13	11.4	Pass
		HCH	QPSK	RB1#0	1.62	13	11.5	Pass
			BPSK	RB1#0	1.83	13	11.6	Pass
	15kHz	LCH	QPSK	RB1#0	1.43	13	11.7	Pass
			BPSK	RB1#0	1.38	13	11.8	Pass
		MCH	QPSK	RB1#0	1.45	13	11.9	Pass
			BPSK	RB1#0	1.43	13	11.10	Pass
		HCH	QPSK	RB1#0	1.46	13	11.11	Pass
			BPSK	RB1#0	1.44	13	11.12	Pass
NB-IoT Band 4	3.75kHz	LCH	QPSK	RB1#0	1.55	13	12.1	Pass
			BPSK	RB1#0	1.75	13	12.2	Pass
		MCH	QPSK	RB1#0	1.53	13	12.3	Pass
			BPSK	RB1#0	1.73	13	12.4	Pass
		HCH	QPSK	RB1#0	1.56	13	12.5	Pass
			BPSK	RB1#0	1.75	13	12.6	Pass
	15kHz	LCH	QPSK	RB1#0	1.46	13	12.7	Pass
			BPSK	RB1#0	1.37	13	12.8	Pass
		MCH	QPSK	RB1#0	1.43	13	12.9	Pass
			BPSK	RB1#0	1.42	13	12.10	Pass
		HCH	QPSK	RB1#0	1.48	13	12.11	Pass
			BPSK	RB1#0	1.43	13	12.12	Pass
NB-IoT Band 5	3.75kHz	LCH	QPSK	RB1#0	1.66	13	13.1	Pass
			BPSK	RB1#0	1.81	13	13.2	Pass
		MCH	QPSK	RB1#0	1.57	13	13.3	Pass
			BPSK	RB1#0	1.83	13	13.4	Pass
		HCH	QPSK	RB1#0	1.59	13	13.5	Pass
			BPSK	RB1#0	1.83	13	13.6	Pass
	15kHz	LCH	QPSK	RB1#0	1.44	13	13.7	Pass
			BPSK	RB1#0	1.39	13	13.8	Pass
		MCH	QPSK	RB1#0	1.48	13	13.9	Pass
			BPSK	RB1#0	1.38	13	13.10	Pass
		HCH	QPSK	RB1#0	1.46	13	13.11	Pass
			BPSK	RB1#0	1.37	13	13.12	Pass
NB-IoT Band 12	3.75kHz	LCH	QPSK	RB1#0	1.53	13	14.1	Pass
			BPSK	RB1#0	2.47	13	14.2	Pass
		MCH	QPSK	RB1#0	1.54	13	14.3	Pass
			BPSK	RB1#0	1.72	13	14.4	Pass
		HCH	QPSK	RB1#0	1.56	13	14.5	Pass
			BPSK	RB1#0				

Test Band	Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Offset)	Peak to Average Ratio (dB)	Limit (dB)	Refer to Plot ^{Note2}	Verdict
	15kHz	LCH	BPSK	RB1#0	1.73	13	14.6	Pass
			QPSK	RB1#0	1.38	13	14.7	Pass
		MCH	BPSK	RB1#0	1.3	13	14.8	Pass
			QPSK	RB1#0	1.37	13	14.9	Pass
		HCH	BPSK	RB1#0	1.3	13	14.10	Pass
			QPSK	RB1#0	1.41	13	14.11	Pass
NB-IoT Band 13	3.75kHz	LCH	BPSK	RB1#0	1.31	13	14.12	Pass
			QPSK	RB1#0	1.58	13	15.1	Pass
		MCH	BPSK	RB1#0	1.76	13	15.2	Pass
			QPSK	RB1#0	1.57	13	15.3	Pass
		HCH	BPSK	RB1#0	1.73	13	15.4	Pass
			QPSK	RB1#0	1.61	13	15.5	Pass
	15kHz	LCH	BPSK	RB1#0	1.73	13	15.6	Pass
			QPSK	RB1#0	1.41	13	15.7	Pass
		MCH	BPSK	RB1#0	1.34	13	15.8	Pass
			QPSK	RB1#0	1.4	13	15.9	Pass
		HCH	BPSK	RB1#0	1.35	13	15.10	Pass
			QPSK	RB1#0	1.38	13	15.11	Pass
NB-IoT Band 25	3.75kHz	LCH	BPSK	RB1#0	1.33	13	15.12	Pass
			QPSK	RB1#0	1.55	13	16.1	Pass
		MCH	BPSK	RB1#0	1.79	13	16.2	Pass
			QPSK	RB1#0	1.58	13	16.3	Pass
		HCH	BPSK	RB1#0	1.8	13	16.4	Pass
			QPSK	RB1#0	1.6	13	16.5	Pass
	15kHz	LCH	BPSK	RB1#0	1.81	13	16.6	Pass
			QPSK	RB1#0	1.43	13	16.7	Pass
		MCH	BPSK	RB1#0	1.38	13	16.8	Pass
			QPSK	RB1#0	1.51	13	16.9	Pass
		HCH	BPSK	RB1#0	1.4	13	16.10	Pass
			QPSK	RB1#0	1.43	13	16.11	Pass
NB-IoT Band 66	3.75kHz	LCH	BPSK	RB1#0	1.4	13	16.12	Pass
			QPSK	RB1#0	1.55	13	17.1	Pass
		MCH	BPSK	RB1#0	1.75	13	17.2	Pass
			QPSK	RB1#0	1.52	13	17.3	Pass
		HCH	BPSK	RB1#0	1.75	13	17.4	Pass
			QPSK	RB1#0	1.63	13	17.5	Pass
	15kHz	LCH	BPSK	RB1#0	1.79	13	17.6	Pass
			QPSK	RB1#0	1.39	13	17.7	Pass
		MCH	BPSK	RB1#0	1.38	13	17.8	Pass
			QPSK	RB1#0	1.48	13	17.9	Pass
		HCH	BPSK	RB1#0	1.44	13	17.10	Pass
			QPSK	RB1#0	1.42	13	17.11	Pass

Test Band	Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Offset)	Peak to Average Ratio (dB)	Limit (dB)	Refer to Plot ^{Note2}	Verdict
			BPSK	RB1#0	1.41	13	17.12	Pass
NB-IoT Band 85	3.75kHz	LCH	QPSK	RB1#0	1.53	13	18.1	Pass
			BPSK	RB1#0	1.72	13	18.2	Pass
		MCH	QPSK	RB1#0	1.46	13	18.3	Pass
			BPSK	RB1#0	1.71	13	18.4	Pass
		HCH	QPSK	RB1#0	1.53	13	18.5	Pass
			BPSK	RB1#0	1.7	13	18.6	Pass
	15kHz	LCH	QPSK	RB1#0	1.38	13	18.7	Pass
			BPSK	RB1#0	1.33	13	18.8	Pass
		MCH	QPSK	RB1#0	1.36	13	18.9	Pass
			BPSK	RB1#0	1.28	13	18.10	Pass
		HCH	QPSK	RB1#0	1.35	13	18.11	Pass
			BPSK	RB1#0	1.27	13	18.12	Pass

A.3 Occupied Bandwidth

Note 1: All modes were tested, but only the typical data were reported in this report.

Note 2: Test plots please refer to the document “Annex No.: BL-SZ2140097-501 Data Part 2.pdf”.

GSM Mode Test Data

Test Band	Test Channel	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
GPRS 850	LCH	0.24	0.31	1.1
	MCH	0.24	0.31	1.2
	HCH	0.24	0.32	1.3
GPRS 1900	LCH	0.24	0.32	2.1
	MCH	0.25	0.32	2.2
	HCH	0.25	0.31	2.3
EGPRS 850	LCH	0.24	0.31	3.1
	MCH	0.24	0.3	3.2
	HCH	0.24	0.3	3.3
EGPRS 1900	LCH	0.24	0.3	4.1
	MCH	0.24	0.31	4.2
	HCH	0.24	0.3	4.3

LTE-M1 Mode Test Data

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
LTE-M1 Band 2	1.4 MHz	LCH	QPSK	RB6#0	1.122637	1.38719	5.1
			16-QAM	RB5#0	1.094478	1.284414	5.2
		MCH	QPSK	RB6#0	1.116572	1.367411	5.3
			16-QAM	RB5#0	0.924555	1.137596	5.4
		HCH	QPSK	RB6#0	1.089305	1.338179	5.5
			16-QAM	RB5#0	0.924154	1.2147	5.6
LTE-M1 Band 4	1.4 MHz	LCH	QPSK	RB6#0	1.090454	1.269601	6.1
			16-QAM	RB5#0	0.92435	1.132778	6.2
		MCH	QPSK	RB6#0	1.08939	1.266542	6.3
			16-QAM	RB5#0	0.924061	1.136977	6.4
		HCH	QPSK	RB6#0	1.089012	1.271182	6.5
			16-QAM	RB5#0	0.924022	1.217702	6.6
LTE-M1 Band 5	1.4 MHz	LCH	QPSK	RB6#0	1.088788	1.270332	7.1
			16-QAM	RB5#0	0.923173	1.126374	7.2
		MCH	QPSK	RB6#0	1.09751	1.30172	7.3
			16-QAM	RB5#0	0.923276	1.12991	7.4
		HCH	QPSK	RB6#0	1.08758	1.342105	7.5
			16-QAM	RB5#0	0.919167	1.114729	7.6
LTE-M1 Band 12	1.4 MHz	LCH	QPSK	RB6#0	1.095907	1.307694	8.1
			16-QAM	RB5#0	0.921506	1.102892	8.2
		MCH	QPSK	RB6#0	1.088646	1.274167	8.3
			16-QAM	RB5#0	0.923239	1.117047	8.4
		HCH	QPSK	RB6#0	1.088843	1.273691	8.5
			16-QAM	RB5#0	0.923304	1.117249	8.6
LTE-M1 Band 13	5 MHz	LCH	QPSK	RB6#0	1.122757	1.335056	9.1
			16-QAM	RB5#0	0.958147	1.208591	9.2
		MCH	QPSK	RB6#0	1.11984	1.32554	9.3
			16-QAM	RB5#0	1.018762	1.43954	9.4
		HCH	QPSK	RB6#0	1.125941	1.321276	9.5
			16-QAM	RB5#0	0.962195	1.186869	9.6
LTE-M1 Band 25	1.4 MHz	LCH	QPSK	RB6#0	1.090319	1.271541	10.1
			16-QAM	RB5#0	0.924991	1.136464	10.2
		MCH	QPSK	RB6#0	1.094032	1.2704	10.3
			16-QAM	RB5#0	0.925681	1.13678	10.4
		HCH	QPSK	RB6#0	1.091509	1.274577	10.5
			16-QAM	RB5#0	1.091527	1.271687	10.6
LTE-M1 Band 26 (part22)	1.4 MHz	LCH	QPSK	RB6#0	1.110696	1.365244	11.1
			16-QAM	RB5#0	0.949802	1.168211	11.2
		MCH	QPSK	RB6#0	1.12091	1.380133	11.3
			16-QAM	RB5#0	0.946434	1.177888	11.4

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
		HCH	QPSK	RB6#0	1.110827	1.383474	11.5
			16-QAM	RB5#0	0.949831	1.166265	11.6
LTE-M1 Band 26 (part90)	1.4 MHz	LCH	QPSK	RB6#0	1.112159	1.364922	12.1
			16-QAM	RB5#0	0.949081	1.16637	12.2
		MCH	QPSK	RB6#0	1.111278	1.388819	12.3
			16-QAM	RB5#0	0.949291	1.166474	12.4
		HCH	QPSK	RB6#0	1.111174	1.36545	12.5
			16-QAM	RB5#0	0.949293	1.165694	12.6
LTE-M1 Band 66	1.4 MHz	LCH	QPSK	RB6#0	1.112074	1.389256	13.1
			16-QAM	RB5#0	0.949254	1.173466	13.2
		MCH	QPSK	RB6#0	1.111119	1.387573	13.3
			16-QAM	RB5#0	0.948673	1.173077	13.4
		HCH	QPSK	RB6#0	1.110721	1.363876	13.5
			16-QAM	RB5#0	0.949133	1.172473	13.6
LTE-M1 Band 85	5 MHz	LCH	QPSK	RB6#0	1.132184	1.347827	14.1
			16-QAM	RB5#0	0.974803	1.228781	14.2
		MCH	QPSK	RB6#0	1.1317	1.349795	14.3
			16-QAM	RB5#0	0.974813	1.222958	14.4
		HCH	QPSK	RB6#0	1.132497	1.350042	14.5
			16-QAM	RB5#0	0.974952	1.234172	14.6

NB-IoT Mode Test Data

Test Band	Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
NB-IoT Band 2	3.75kHz	LCH	QPSK	RB1#0	0.062904	0.039612	15.1
			BPSK	RB1#0	0.062918	0.039398	15.2
		MCH	QPSK	RB1#0	0.069873	0.039306	15.3
			BPSK	RB1#0	0.062723	0.039432	15.4
		HCH	QPSK	RB1#0	0.069578	0.038652	15.5
			BPSK	RB1#0	0.062795	0.039769	15.6
	15kHz	LCH	QPSK	RB1#0	0.117203	0.110623	15.7
				RB12#0	0.18539	0.246405	15.8
			BPSK	RB1#0	0.123128	0.106421	15.9
		MCH	QPSK	RB1#0	0.117739	0.114316	15.10
				RB12#0	0.185402	0.24642	15.11
			BPSK	RB1#0	0.121584	0.105129	15.12
		HCH	QPSK	RB1#0	0.118417	0.102793	15.13
				RB12#0	0.185697	0.246274	15.14
			BPSK	RB1#0	0.124786	0.106721	15.15
				RB1#0	0.124786	0.106721	15.15
NB-IoT Band 4	3.75kHz	LCH	QPSK	RB1#0	0.068353	0.04187	16.1
			BPSK	RB1#0	0.060614	0.035742	16.2
		MCH	QPSK	RB1#0	0.066672	0.039222	16.3
			BPSK	RB1#0	0.061621	0.035385	16.4
		HCH	QPSK	RB1#0	0.067517	0.039766	16.5
			BPSK	RB1#0	0.061223	0.037987	16.6
	15kHz	LCH	QPSK	RB1#0	0.120937	0.104745	16.7
				RB12#0	0.18522	0.238548	16.8
			BPSK	RB1#0	0.120237	0.1046	16.9
		MCH	QPSK	RB1#0	0.117234	0.107021	16.10
				RB12#0	0.185541	0.245949	16.11
			BPSK	RB1#0	0.12174	0.103829	16.12
		HCH	QPSK	RB1#0	0.117918	0.102949	16.13
				RB12#0	0.185485	0.246026	16.14
			BPSK	RB1#0	0.122632	0.103448	16.15
				RB1#0	0.122632	0.103448	16.15
NB-IoT Band 5	3.75kHz	LCH	QPSK	RB1#0	0.067261	0.038604	17.1
			BPSK	RB1#0	0.061122	0.039414	17.2
		MCH	QPSK	RB1#0	0.067001	0.038377	17.3
			BPSK	RB1#0	0.060475	0.039746	17.4
		HCH	QPSK	RB1#0	0.067826	0.039988	17.5
			BPSK	RB1#0	0.059622	0.038735	17.6
	15kHz	LCH	QPSK	RB1#0	0.118974	0.102604	17.7
				RB12#0	0.18491	0.237799	17.8
			BPSK	RB1#0	0.122338	0.111043	17.9
		MCH	QPSK	RB1#0	0.116585	0.103496	17.10
				RB12#0	0.185109	0.244756	17.11

Test Band	Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
		HCH	BPSK	RB1#0	0.121041	0.104762	17.12
			QPSK	RB1#0	0.119125	0.103015	17.13
				RB12#0	0.185138	0.235102	17.14
			BPSK	RB1#0	0.12057	0.1105	17.15
NB-IoT Band 12	3.75kHz	LCH	QPSK	RB1#0	0.068671	0.038376	18.1
			BPSK	RB1#0	0.060845	0.039718	18.2
		MCH	QPSK	RB1#0	0.06691	0.038302	18.3
			BPSK	RB1#0	0.059955	0.038403	18.4
		HCH	QPSK	RB1#0	0.070332	0.038975	18.5
			BPSK	RB1#0	0.060093	0.039325	18.6
	15kHz	LCH	QPSK	RB1#0	0.119955	0.11623	18.7
				RB12#0	0.185925	0.241526	18.8
			BPSK	RB1#0	0.120128	0.102264	18.9
		MCH	QPSK	RB1#0	0.11924	0.103652	18.10
				RB12#0	0.185099	0.247238	18.11
			BPSK	RB1#0	0.119739	0.09911	18.12
		HCH	QPSK	RB1#0	0.118306	0.115987	18.13
				RB12#0	0.185065	0.245924	18.14
			BPSK	RB1#0	0.120286	0.104167	18.15
NB-IoT Band 13	3.75kHz	LCH	QPSK	RB1#0	0.067887	0.038319	19.1
			BPSK	RB1#0	0.060296	0.039464	19.2
		MCH	QPSK	RB1#0	0.059692	0.038545	19.3
			BPSK	RB1#0	0.069242	0.038246	19.4
		HCH	QPSK	RB1#0	0.068758	0.040748	19.5
			BPSK	RB1#0	0.06022	0.039488	19.6
	15kHz	LCH	QPSK	RB1#0	0.117625	0.115054	19.7
				RB12#0	0.184844	0.246212	19.8
			BPSK	RB1#0	0.120634	0.103184	19.9
		MCH	QPSK	RB1#0	0.117058	0.114471	19.10
				RB12#0	0.185346	0.246221	19.11
			BPSK	RB1#0	0.120106	0.104417	19.12
		HCH	QPSK	RB1#0	0.119378	0.103547	19.13
				RB12#0	0.185175	0.245989	19.14
			BPSK	RB1#0	0.119849	0.103964	19.15
NB-IoT Band 25	3.75kHz	LCH	QPSK	RB1#0	0.066129	0.038491	20.1
			BPSK	RB1#0	0.062384	0.039696	20.2
		MCH	QPSK	RB1#0	0.067679	0.039693	20.3
			BPSK	RB1#0	0.061519	0.037716	20.4
		HCH	QPSK	RB1#0	0.065987	0.039873	20.5
			BPSK	RB1#0	0.061537	0.039382	20.6
	15kHz	LCH	QPSK	RB1#0	0.116601	0.114661	20.7
				RB12#0	0.185118	0.248081	20.8

Test Band	Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
		MCH	BPSK	RB1#0	0.120976	0.101582	20.9
			QPSK	RB1#0	0.117908	0.103454	20.10
				RB12#0	0.185732	0.248288	20.11
		HCH	BPSK	RB1#0	0.123804	0.104572	20.12
			QPSK	RB1#0	0.117258	0.104079	20.13
				RB12#0	0.185912	0.24075	20.14
			BPSK	RB1#0	0.121779	0.102407	20.15
NB-IoT Band 66	3.75kHz	LCH	QPSK	RB1#0	0.067298	0.038407	21.1
			BPSK	RB1#0	0.060317	0.036718	21.2
		MCH	QPSK	RB1#0	0.069204	0.041366	21.3
			BPSK	RB1#0	0.060666	0.035716	21.4
		HCH	QPSK	RB1#0	0.081657	0.041832	21.5
			BPSK	RB1#0	0.061554	0.039344	21.6
	15kHz	LCH	QPSK	RB1#0	0.117309	0.10393	21.7
				RB12#0	0.185032	0.245831	21.8
			BPSK	RB1#0	0.120431	0.103545	21.9
		MCH	QPSK	RB1#0	0.116903	0.113961	21.10
				RB12#0	0.185347	0.246032	21.11
			BPSK	RB1#0	0.120291	0.103039	21.12
		HCH	QPSK	RB1#0	0.117074	0.103299	21.13
				RB12#0	0.185614	0.246054	21.14
			BPSK	RB1#0	0.124871	0.10411	21.15
NB-IoT Band 85	3.75kHz	LCH	QPSK	RB1#0	0.068542	0.038069	22.1
			BPSK	RB1#0	0.061618	0.039449	22.2
		MCH	QPSK	RB1#0	0.068822	0.038318	22.3
			BPSK	RB1#0	0.05952	0.039261	22.4
		HCH	QPSK	RB1#0	0.065196	0.036816	22.5
			BPSK	RB1#0	0.060035	0.039499	22.6
	15kHz	LCH	QPSK	RB1#0	0.118198	0.103409	22.7
				RB12#0	0.185863	0.247335	22.8
			BPSK	RB1#0	0.12006	0.101057	22.9
		MCH	QPSK	RB1#0	0.120276	0.11591	22.10
				RB12#0	0.185336	0.248746	22.11
			BPSK	RB1#0	0.11977	0.105849	22.12
		HCH	QPSK	RB1#0	0.118566	0.115851	22.13
				RB12#0	0.185125	0.250712	22.14
			BPSK	RB1#0	0.119356	0.104049	22.15

A.4 Frequency Stability

GPRS 850

Test Conditions		Frequency Deviation						Verdict
Power (VDC)	Temperature (°C)	LCH 824.2 MHz		MCH 836.6 MHz		HCH 848.8 MHz		
		Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)	
18	-30	30.54	±2060.5	32.29	±2091.5	29.15	±2122	Pass
	-20	25.12		24.99		30.32		
	-10	27.96		29.15		35.39		
	0	32.25		33.77		29.28		
	+10	24.44		33.9		27.6		
	+20	31.51		30.67		25.86		
	+25	27.67		33.93		26.57		
	+30	27.8		27.8		30.93		
	+40	31.22		30.61		30.99		
	+50	30.83		31.03		35.03		
	+60	31.93		32.45		26.15		
24	+25	27.15	27.8	29.93				
12	+25	28.77	26.57	31.32				

GPRS 1900

Test Conditions		Frequency Deviation						Verdict
Power (VDC)	Temperature (°C)	LCH 1850.2 MHz		MCH 1880 MHz		HCH 1909.8 MHz		
		Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)	
18	-30	17.53	±4625.5	22.86	±4700.0	23.37	±4774.5	Pass
	-20	39.87		29.57		21.08		
	-10	40.39		32.03		24.7		
	0	44.75		42.42		33.77		
	+10	41.16		43.23		29.57		
	+20	40.07		47.75		27.09		
	+25	36.9		34.97		19.5		
	+30	31.58		44.72		22.31		
	+40	30.32		52.04		34.8		
	+50	45.59		44.39		38.84		
	+60	45.36		49.53		34.22		
24	+25	45.68		32.58		33		
12	+25	36.58		46.69		25.6		

EGPRS 850

Test Conditions		Frequency Deviation						Verdict
Power (VDC)	Temperature (°C)	LCH 824.2 MHz		MCH 836.6 MHz		HCH 848.8 MHz		
		Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)	
18	-30	24.73	±2060.5	21.5	±2091.5	27.77	±2122	Pass
	-20	29.54		27.15		34.19		
	-10	34.9		29.38		29.93		
	0	33.32		30.25		33.96		
	+10	32.61		29.93		29.61		
	+20	33.58		29.77		30.61		
	+25	27.31		33.13		35.39		
	+30	27.35		34.29		35.55		
	+40	31.28		27.02		38.84		
	+50	27.28		32.61		32.32		
	+60	35.51		32.12		35.42		
24	+25	33.03		29.93		33.25		
12	+25	30.77		34.74		35.9		

EGPRS 1900

Test Conditions		Frequency Deviation						Verdict
Power (VDC)	Temperature (°C)	LCH 1850.2 MHz		MCH 1880 MHz		HCH 1909.8 MHz		
		Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)	
18	-30	36.9	±4625.5	40.58	±4700.0	23.34	±4774.5	Pass
	-20	41.29		32.87		31.22		
	-10	39.87		53.82		26.93		
	0	48.78		54.37		29.8		
	+10	39.74		42.36		36.03		
	+20	39.65		40.84		20.57		
	+25	42.07		49.17		32.71		
	+30	40.78		40.45		21.24		
	+40	42		51.59		24.38		
	+50	45.01		36.22		38.19		
	+60	42.17		52.04		30.38		
24	+25	46.43		37.58		31.38		
12	+25	36.22		41		33.8		

LTE-M1 Band 2 QPSK 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1860 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-4.02	±4650	Pass
	-20	-3.13		
	-10	-5.94		
	0	-3.22		
	+10	-6.75		
	+20	-4.50		
	+25	-3.6		
	+30	-5.55		
	+40	-4.5		
	+50	-1.7		
	+60	-6.39		
24	+25	-1.31		
12	+25	-2.56		

LTE-M1 Band 2 16QAM 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1860 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-6.37	±4650	Pass
	-20	-11.18		
	-10	-7.82		
	0	-9.85		
	+10	-8.45		
	+20	-9.98		
	+25	-6.01		
	+30	-7.24		
	+40	-5.37		
	+50	-8.03		
	+60	-8.67		
24	+25	-6.24		
12	+25	-7.01		

LTE-M1 Band 2 QPSK 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1880 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	5.14	±4700	Pass
	-20	5.05		
	-10	6.59		
	0	5.56		
	+10	6.68		
	+20	5.15		
	+25	4.41		
	+30	6.42		
	+40	5.76		
	+50	4.06		
	+60	4.09		
24	+25	2.95		
12	+25	3.66		

LTE-M1 Band 2 16QAM 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1880 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	17.51	±4700	Pass
	-20	18.75		
	-10	20.8		
	0	18.63		
	+10	15.05		
	+20	18.47		
	+25	16.49		
	+30	16.02		
	+40	19.74		
	+50	17.37		
	+60	17.9		
24	+25	15.48		
12	+25	16.52		

LTE-M1 Band 2 QPSK 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1900 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	0.37	±4750	Pass
	-20	2.05		
	-10	2.92		
	0	2.38		
	+10	-0.44		
	+20	-1.01		
	+25	1.4		
	+30	-1.61		
	+40	2.23		
	+50	-0.17		
	+60	3.56		
24	+25	2.9		
12	+25	1.36		

LTE-M1 Band 2 16QAM 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1900 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	12.98	±4750	Pass
	-20	13.25		
	-10	11.79		
	0	12.07		
	+10	15.04		
	+20	16.89		
	+25	13.64		
	+30	15.16		
	+40	12.87		
	+50	13.27		
	+60	11.28		
24	+25	11.3		
12	+25	12.18		

LTE-M1 Band 4 QPSK 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1720 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-4.71	±4300	Pass
	-20	-3.54		
	-10	-2.85		
	0	-1.3		
	+10	-1.92		
	+20	-2.36		
	+25	-0.24		
	+30	-3.12		
	+40	-2.08		
	+50	-0.17		
	+60	-0.93		
24	+25	-2.71		
12	+25	-2.38		

LTE-M1 Band 4 16QAM 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1720 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	10.5	±4300	Pass
	-20	5.5		
	-10	6.7		
	0	7.95		
	+10	7.39		
	+20	9.17		
	+25	11.1		
	+30	7.2		
	+40	5.76		
	+50	7.78		
	+60	9.1		
24	+25	11.06		
12	+25	9.67		

LTE-M1 Band 4 QPSK 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1732.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	4.52	±4331.25	Pass
	-20	5.39		
	-10	4.01		
	0	3.37		
	+10	5.05		
	+20	3.53		
	+25	3.29		
	+30	3.75		
	+40	3.52		
	+50	5.59		
	+60	4.76		
24	+25	6.64		
12	+25	5.12		

LTE-M1 Band 4 16QAM 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1732.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	5.12	±4331.25	Pass
	-20	3.86		
	-10	4.15		
	0	3.68		
	+10	2.8		
	+20	4.46		
	+25	1.89		
	+30	4.32		
	+40	3.55		
	+50	2.05		
	+60	4.45		
24	+25	3.21		
12	+25	3.05		

LTE-M1 Band 4 QPSK 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1745 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	1.19	±4362.5	Pass
	-20	2.55		
	-10	-0.08		
	0	1.06		
	+10	0.87		
	+20	-0.16		
	+25	1.46		
	+30	3.32		
	+40	1.15		
	+50	2.82		
	+60	2.88		
24	+25	0.61		
12	+25	0.32		

LTE-M1 Band 4 16QAM 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1745 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-0.89	±4362.5	Pass
	-20	-1.93		
	-10	-4.91		
	0	-2.67		
	+10	-4.93		
	+20	-2.76		
	+25	-5.7		
	+30	-1.63		
	+40	-0.63		
	+50	-0.81		
	+60	-4.8		
24	+25	-4.82		
12	+25	-3.51		

LTE-M1 Band 5 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 829 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	5.21	±2072.5	Pass
	-20	4.87		
	-10	6.03		
	0	6.98		
	+10	5.63		
	+20	7.03		
	+25	5.27		
	+30	7.30		
	+40	5.66		
	+50	4.86		
	+60	5.93		
24	+25	6.6		
12	+25	7.55		

LTE-M1 Band 5 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 829 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	21.58	±2072.5	Pass
	-20	21.28		
	-10	22.15		
	0	19.5		
	+10	21.39		
	+20	21.25		
	+25	19.72		
	+30	20.89		
	+40	21.68		
	+50	21.49		
	+60	21.03		
24	+25	23.4		
12	+25	20.21		

LTE-M1 Band 5 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 836.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	2.35	±2091.25	Pass
	-20	2.06		
	-10	1.17		
	0	3.63		
	+10	3.18		
	+20	4.88		
	+25	3.2		
	+30	3.95		
	+40	2.05		
	+50	2.22		
	+60	3.35		
24	+25	3.99	±2091.25	Pass
12	+25	3.26		

LTE-M1 Band 5 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 836.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	14.52	±2091.25	Pass
	-20	14.39		
	-10	14.58		
	0	14.96		
	+10	13.45		
	+20	13.96		
	+25	13.23		
	+30	15.69		
	+40	15.66		
	+50	14.32		
	+60	13.86		
24	+25	14.28	±2091.25	Pass
12	+25	14.51		

LTE-M1 Band 5 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 844 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	6.42	±2110	Pass
	-20	5.81		
	-10	7.12		
	0	6.48		
	+10	7.18		
	+20	6.63		
	+25	5.34		
	+30	7.97		
	+40	6.81		
	+50	8.23		
	+60	7.73		
24	+25	6.02		
12	+25	8.43		

LTE-M1 Band 5 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 844 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	18.75	±2110	Pass
	-20	17.67		
	-10	19.11		
	0	19.1		
	+10	18.07		
	+20	18.5		
	+25	17.96		
	+30	17.76		
	+40	17.66		
	+50	17.77		
	+60	16.64		
24	+25	17.29		
12	+25	18.57		

LTE-M1 Band 12 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 704 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	11.07	±1760	Pass
	-20	11.5		
	-10	12.26		
	0	13.68		
	+10	11.65		
	+20	13.72		
	+25	12.99		
	+30	13.24		
	+40	12.76		
	+50	12.36		
	+60	13.11		
24	+25	14.34		
12	+25	13.05		

LTE-M1 Band 12 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 704 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	25.99	±1760	Pass
	-20	25.01		
	-10	24.61		
	0	26.11		
	+10	27.64		
	+20	27.26		
	+25	27.68		
	+30	26.56		
	+40	27.84		
	+50	28.97		
	+60	25.18		
24	+25	27.06		
12	+25	29.24		

LTE-M1 Band 12 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 707.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	1.95	±1768.75	Pass
	-20	4.18		
	-10	2.26		
	0	4.05		
	+10	3.53		
	+20	3.69		
	+25	3.10		
	+30	2.93		
	+40	2.15		
	+50	3.43		
	+60	3.10		
24	+25	2.37	±1768.75	Pass
12	+25	1.20		

LTE-M1 Band 12 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 707.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	18.53	±1768.75	Pass
	-20	18.9		
	-10	17.48		
	0	19.18		
	+10	17.65		
	+20	18.14		
	+25	17.67		
	+30	18.30		
	+40	18.84		
	+50	18.40		
	+60	16.54		
24	+25	19.38	±1768.75	Pass
12	+25	17.72		

LTE-M1 Band 12 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 711 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	8.77	±1777.5	Pass
	-20	8.21		
	-10	7.87		
	0	9		
	+10	9.57		
	+20	7.74		
	+25	9.93		
	+30	9.99		
	+40	9.27		
	+50	11.15		
	+60	9.25		
24	+25	9.23		
12	+25	8.85		

LTE-M1 Band 12 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 711 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	21.12	±1777.5	Pass
	-20	22.33		
	-10	20.5		
	0	23.4		
	+10	20.56		
	+20	19.23		
	+25	22.01		
	+30	21.31		
	+40	22.68		
	+50	20.59		
	+60	21.28		
24	+25	20.27		
12	+25	22.08		

LTE-M1 Band 13 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 782 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	0.6	±1955	Pass
	-20	1.49		
	-10	1.12		
	0	2.03		
	+10	1.76		
	+20	2.57		
	+25	3.16		
	+30	1.90		
	+40	2.60		
	+50	3.60		
	+60	2.35		
24	+25	1.95		
12	+25	3.00		

LTE-M1 Band 13 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 782 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	2.36	±1955	Pass
	-20	3.12		
	-10	5.04		
	0	4.43		
	+10	4.82		
	+20	3.50		
	+25	2.66		
	+30	3.95		
	+40	3.98		
	+50	3.15		
	+60	4.05		
24	+25	2.80		
12	+25	2.23		

LTE-M1 Band 25 QPSK 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1860 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-7.39	±4650	Pass
	-20	-5.73		
	-10	-3.78		
	0	-6.3		
	+10	2.53		
	+20	4.57		
	+25	-2.15		
	+30	-3.92		
	+40	-2.58		
	+50	3.27		
	+60	-5.1		
24	+25	-6.67	±4650	Pass
12	+25	7.74		

LTE-M1 Band 25 16QAM 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1860 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-10.25	±4650	Pass
	-20	-11.8		
	-10	-9.81		
	0	-8.08		
	+10	-10.44		
	+20	-9.4		
	+25	-5.7		
	+30	-4.88		
	+40	-10.39		
	+50	-11.59		
	+60	-8.01		
24	+25	-9.38	±4650	Pass
12	+25	-5.83		

LTE-M1 Band 25 QPSK 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1882.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-8.89	±4706.25	Pass
	-20	-6.11		
	-10	-6.64		
	0	-8.74		
	+10	-9.08		
	+20	-4.95		
	+25	-6.55		
	+30	-6.41		
	+40	-7.1		
	+50	-7.73		
	+60	-6.54		
24	+25	-5.17		
12	+25	-9.88		

LTE-M1 Band 25 16QAM 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1882.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	1.06	±4706.25	Pass
	-20	4.54		
	-10	3.52		
	0	4.55		
	+10	1.12		
	+20	1.26		
	+25	2.43		
	+30	2.54		
	+40	5.36		
	+50	3.7		
	+60	1.72		
24	+25	3.64		
12	+25	0.79		

LTE-M1 Band 25 QPSK 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1905 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-4.28	±4762.5	Pass
	-20	-3.42		
	-10	-3.11		
	0	-5.07		
	+10	-4.41		
	+20	-3.91		
	+25	-6.12		
	+30	-3.62		
	+40	-1.61		
	+50	-5.18		
	+60	-4.2		
24	+25	-4.94	±4762.5	Pass
12	+25	-6.3		

LTE-M1 Band 25 16QAM 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1905 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	9.74	±4762.5	Pass
	-20	4.03		
	-10	7.66		
	0	8.01		
	+10	12.15		
	+20	8.92		
	+25	8.31		
	+30	6.73		
	+40	9.78		
	+50	8.08		
	+60	7.49		
24	+25	9.38	±4762.5	Pass
12	+25	7.7		

LTE-M1 Band 26(part22) QPSK 15 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 831.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	2.81	±2078.75	Pass
	-20	2.26		
	-10	2.12		
	0	3.09		
	+10	1.75		
	+20	2.9		
	+25	4.25		
	+30	3.96		
	+40	4.31		
	+50	1.99		
	+60	2.59		
24	+25	3.42	±2078.75	Pass
12	+25	1.62		

LTE-M1 Band 26(part22) 16QAM 15 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 831.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	14.56	±2078.75	Pass
	-20	14.11		
	-10	14.55		
	0	13.24		
	+10	13.71		
	+20	12.77		
	+25	14.27		
	+30	14.77		
	+40	14.55		
	+50	15.73		
	+60	13.61		
24	+25	14.7	±2078.75	Pass
12	+25	14.17		

LTE-M1 Band 26(part22) QPSK 15 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 836.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	0.34	±2091.25	Pass
	-20	0.89		
	-10	1.23		
	0	2.73		
	+10	0.11		
	+20	0.69		
	+25	0.36		
	+30	0.49		
	+40	1		
	+50	1.27		
	+60	1.04		
24	+25	1.42	±2091.25	Pass
12	+25	2.16		

LTE-M1 Band 26(part22) 16QAM 15 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 836.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	6.59	±2091.25	Pass
	-20	5.58		
	-10	5.24		
	0	6.42		
	+10	9.11		
	+20	6.79		
	+25	8.36		
	+30	7.04		
	+40	7.36		
	+50	6.69		
	+60	6.85		
24	+25	5.75	±2091.25	Pass
12	+25	6.23		

LTE-M1 Band 26(part22) QPSK 15 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 841.5MHz		
		Value (Hz)	Limits (Hz)	
18	-30	1.15	±2103.75	Pass
	-20	-0.39		
	-10	0.35		
	0	0.15		
	+10	-0.69		
	+20	-0.19		
	+25	1.53		
	+30	0.14		
	+40	1.24		
	+50	0.01		
	+60	2.76		
24	+25	1.73		
12	+25	-0.93		

LTE-M1 Band 26(part22) 16QAM 15 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 841.5MHz		
		Value (Hz)	Limits (Hz)	
18	-30	12.79	±2103.75	Pass
	-20	15.07		
	-10	13.64		
	0	14.22		
	+10	12.68		
	+20	14.21		
	+25	12.42		
	+30	14.97		
	+40	13.62		
	+50	13.5		
	+60	14.6		
24	+25	15.36		
12	+25	14.03		

LTE-M1 Band 26(part90) QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 819 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-1.69	±2047.5	Pass
	-20	-1.63		
	-10	-1.29		
	0	-1.09		
	+10	-1.2		
	+20	-0.23		
	+25	-0.5		
	+30	-1.97		
	+40	-1.12		
	+50	-0.94		
	+60	-1.11		
24	+25	-0.34		
12	+25	-0.54		

LTE-M1 Band 26(part90) 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 819 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-0.7	±2047.5	Pass
	-20	-0.53		
	-10	-0.19		
	0	-0.56		
	+10	-0.89		
	+20	-0.09		
	+25	-1.86		
	+30	-0.01		
	+40	-2.2		
	+50	-0.41		
	+60	0.37		
24	+25	-0.57		
12	+25	-0.82		

LTE-M1 Band 66 QPSK 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1720 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-1.69	±4300	Pass
	-20	-2.41		
	-10	-3.33		
	0	-0.93		
	+10	-2.7		
	+20	-4.95		
	+25	-0.71		
	+30	-1.94		
	+40	-0.96		
	+50	-0.62		
	+60	-1.42		
24	+25	-0.28		
12	+25	-2.68		

LTE-M1 Band 66 16QAM 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1720 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	11.32	±4300	Pass
	-20	13.03		
	-10	10.17		
	0	9.93		
	+10	11.39		
	+20	10.65		
	+25	11.58		
	+30	12.67		
	+40	9.03		
	+50	9.29		
	+60	10.2		
24	+25	9.91		
12	+25	11.68		

LTE-M1 Band 66 QPSK 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1745 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-0.11	±4362.5	Pass
	-20	1.24		
	-10	0.32		
	0	0.54		
	+10	0.31		
	+20	0.9		
	+25	-1.13		
	+30	-0.93		
	+40	-0.95		
	+50	-1.4		
	+60	0.69		
24	+25	-1.93		
12	+25	-0.01		

LTE-M1 Band 66 16QAM 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1745 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	7.77	±4362.5	Pass
	-20	9.57		
	-10	6.97		
	0	9.94		
	+10	11.24		
	+20	10.34		
	+25	11.56		
	+30	7.69		
	+40	8.3		
	+50	10.92		
	+60	8.44		
24	+25	11.32		
12	+25	12.05		

LTE-M1 Band 66 QPSK 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1770 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	6.97	±4425	Pass
	-20	7.87		
	-10	9.08		
	0	8.66		
	+10	10.09		
	+20	9.99		
	+25	6.75		
	+30	9.69		
	+40	7.06		
	+50	5.79		
	+60	6.98		
24	+25	7.77		
12	+25	8.02		

LTE-M1 Band 66 16QAM 20 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1770 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	21.95	±4425	Pass
	-20	20.36		
	-10	21.55		
	0	21.54		
	+10	22.72		
	+20	21.6		
	+25	20.33		
	+30	23.42		
	+40	24.27		
	+50	21.2		
	+60	22.47		
24	+25	20.51		
12	+25	20.14		

LTE-M1 Band 85 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 703 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	6.52	±1757.5	Pass
	-20	7.48		
	-10	6.85		
	0	6.57		
	+10	6.59		
	+20	7.74		
	+25	6.68		
	+30	6.4		
	+40	8.48		
	+50	10.16		
	+60	9.01		
24	+25	7.32		
12	+25	6.99		

LTE-M1 Band 85 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 703 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	20.53	±1757.5	Pass
	-20	19.27		
	-10	20.57		
	0	19.5		
	+10	19.63		
	+20	19.46		
	+25	18.85		
	+30	19.74		
	+40	17.73		
	+50	19.72		
	+60	18.4		
24	+25	20.99		
12	+25	19.45		

LTE-M1 Band 85 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 707 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	5.57	±1767.5	Pass
	-20	6.72		
	-10	5.04		
	0	4.88		
	+10	4.69		
	+20	5.91		
	+25	5.77		
	+30	5.35		
	+40	4.15		
	+50	3.07		
	+60	4.62		
24	+25	4.13		
12	+25	5.85		

LTE-M1 Band 85 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 707 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	20.48	±1767.5	Pass
	-20	18.34		
	-10	20		
	0	18.42		
	+10	17.59		
	+20	18.42		
	+25	18.12		
	+30	20.65		
	+40	17.04		
	+50	16.65		
	+60	18.91		
24	+25	19.14		
12	+25	19.41		

LTE-M1 Band 85 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 711 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	11.93	±1777.5	Pass
	-20	10.89		
	-10	10.27		
	0	12.27		
	+10	10.7		
	+20	12.15		
	+25	12.92		
	+30	11.74		
	+40	10.72		
	+50	10.74		
	+60	11.5		
24	+25	11.23		
12	+25	10.38		

LTE-M1 Band 85 16QAM 10 MHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 711 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	21.98	±1777.5	Pass
	-20	21.36		
	-10	23.1		
	0	23.82		
	+10	21.02		
	+20	23.71		
	+25	24.01		
	+30	22.09		
	+40	23.47		
	+50	23.06		
	+60	23.55		
24	+25	24.82		
12	+25	22.51		

NB-IoT Band 2 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1850.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-15.72	±4625.25	Pass
	-20	-12.97		
	-10	-11.93		
	0	-11.36		
	+10	-8.93		
	+20	-12.15		
	+25	-9.36		
	+30	-11.14		
	+40	-11.37		
	+50	-10.34		
	+60	-14.46		
24	+25	-10.16		
12	+25	-13.35		

NB-IoT Band 2 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1850.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-12.46	±4625.25	Pass
	-20	-14.69		
	-10	-15.38		
	0	-15.39		
	+10	-11.76		
	+20	-14.02		
	+25	-15.13		
	+30	-14.26		
	+40	-14.65		
	+50	-13.65		
	+60	-16.01		
24	+25	-12.03		
12	+25	-7.02		

NB-IoT Band 2 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1880 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-18.36	±4700	Pass
	-20	-20.67		
	-10	-20.89		
	0	-21.02		
	+10	-17.52		
	+20	-16.2		
	+25	-15.44		
	+30	-17.38		
	+40	-13.26		
	+50	-15.36		
	+60	-19.82		
24	+25	-18.96	±4700	Pass
12	+25	-18.22		

NB-IoT Band 2 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1880 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-20.44	±4700	Pass
	-20	-22.67		
	-10	-20.47		
	0	-22.51		
	+10	-18.67		
	+20	-21.34		
	+25	-20.79		
	+30	-16.46		
	+40	-19.34		
	+50	-17.75		
	+60	-19.71		
24	+25	-19.85	±4700	Pass
12	+25	-19.61		

NB-IoT Band 2 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1909.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-9.87	±4774.75	Pass
	-20	-8.31		
	-10	-5.48		
	0	-7.42		
	+10	-6.49		
	+20	-9.18		
	+25	-7.02		
	+30	-9.58		
	+40	-6.34		
	+50	-8.07		
	+60	-7.2		
24	+25	-9.21		
12	+25	-6.09		

NB-IoT Band 2 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1909.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-14.26	±4774.75	Pass
	-20	-12.43		
	-10	-12.87		
	0	-10.17		
	+10	-13.36		
	+20	-10.24		
	+25	-9.16		
	+30	-9.87		
	+40	-8.33		
	+50	-10.53		
	+60	-5.62		
24	+25	-9.32		
12	+25	-9.26		

NB-IoT Band 2 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1850.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-15.23	±4625.25	Pass
	-20	-16.58		
	-10	-13.78		
	0	-13.65		
	+10	-14.13		
	+20	-11.97		
	+25	-8.85		
	+30	-9.81		
	+40	-10.33		
	+50	-8.54		
	+60	-10.34		
24	+25	-14.02		
12	+25	-8.94		

NB-IoT Band 2 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1850.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-13.73	±4625.25	Pass
	-20	-12.13		
	-10	-12.46		
	0	-17.81		
	+10	-12.39		
	+20	-11.93		
	+25	-12.33		
	+30	-12.65		
	+40	-13.35		
	+50	-16.45		
	+60	-13.32		
24	+25	-15.29		
12	+25	-16.55		

NB-IoT Band 2 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1880 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-16.17	±4700	Pass
	-20	-20.66		
	-10	-20.5		
	0	-20.72		
	+10	-19.75		
	+20	-17.37		
	+25	-18.86		
	+30	-17.25		
	+40	-15.23		
	+50	-20.17		
	+60	-14.55		
24	+25	-18.25		
12	+25	-20.27		

NB-IoT Band 2 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1880 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-24.13	±4700	Pass
	-20	-20.11		
	-10	-23.35		
	0	-22.13		
	+10	-23.91		
	+20	-22.85		
	+25	-22.91		
	+30	-22.82		
	+40	-23.84		
	+50	-23.34		
	+60	-21.03		
24	+25	-35.38		
12	+25	-21.49		

NB-IoT Band 2 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1909.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	0.97	±4774.75	Pass
	-20	1.02		
	-10	-4.02		
	0	-5.04		
	+10	-5.59		
	+20	-2.04		
	+25	-0.14		
	+30	-4.75		
	+40	0.83		
	+50	-4.63		
	+60	-3.79		
24	+25	-0.04		
12	+25	-1.09		

NB-IoT Band 2 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1909.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-6.35	±4774.75	Pass
	-20	-3.28		
	-10	-8.13		
	0	-7.8		
	+10	-6.12		
	+20	-2.99		
	+25	-1.97		
	+30	-9.26		
	+40	-5.58		
	+50	-3.36		
	+60	-6.38		
24	+25	-6.18		
12	+25	-3.95		

NB-IoT Band 4 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1710.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-12.53	±4275.25	Pass
	-20	-12.22		
	-10	-11.32		
	0	-9.47		
	+10	-11.34		
	+20	-12.57		
	+25	-11.86		
	+30	-12.35		
	+40	-7.6		
	+50	-7.98		
	+60	-6.54		
24	+25	-10		
12	+25	-8.53		

NB-IoT Band 4 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1710.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-14.72	±4275.25	Pass
	-20	-12.39		
	-10	-10.61		
	0	-9.08		
	+10	-12.56		
	+20	-10.53		
	+25	-13.36		
	+30	-10.59		
	+40	-10.17		
	+50	-13.17		
	+60	-11.57		
24	+25	-11.54		
12	+25	-13.55		

NB-IoT Band 4 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1732.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-20.18	±4331.25	Pass
	-20	-16.34		
	-10	-16.91		
	0	-16.32		
	+10	-20.69		
	+20	-16.05		
	+25	-16.18		
	+30	-20.03		
	+40	-19		
	+50	-19.23		
	+60	-16.74		
24	+25	-17.28		
12	+25	-17.78		

NB-IoT Band 4 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1732.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-19.77	±4331.25	Pass
	-20	-23.15		
	-10	-18.71		
	0	-40.1		
	+10	-29.57		
	+20	-28.8		
	+25	-25.03		
	+30	-26.14		
	+40	-22.37		
	+50	-22.29		
	+60	-26.01		
24	+25	-22.63		
12	+25	-20.64		

NB-IoT Band 4 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1754.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-10.17	±4387.25	Pass
	-20	-11.6		
	-10	-9.81		
	0	-12.07		
	+10	-9.78		
	+20	-9.5		
	+25	-9.3		
	+30	-9.02		
	+40	-8.28		
	+50	-9.45		
	+60	-6.64		
24	+25	-9.58		
12	+25	-8.86		

NB-IoT Band 4 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1754.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-11.17	±4387.25	Pass
	-20	-14.58		
	-10	-13.03		
	0	-13.19		
	+10	-13.32		
	+20	-11.96		
	+25	-6.91		
	+30	-11.14		
	+40	-7.98		
	+50	-7.55		
	+60	-7.65		
24	+25	-10.06		
12	+25	-8.77		

NB-IoT Band 4 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1710.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-9.33	±4275.25	Pass
	-20	-10.6		
	-10	-9.04		
	0	-6.69		
	+10	-10.23		
	+20	-8.17		
	+25	-10.3		
	+30	-8.83		
	+40	-9.18		
	+50	-7.1		
	+60	-8.1		
24	+25	-10.16		
12	+25	-8.04		

NB-IoT Band 4 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1710.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-12.97	±4275.25	Pass
	-20	-15.61		
	-10	-13.39		
	0	-11.64		
	+10	-11.16		
	+20	-14.78		
	+25	-10.04		
	+30	-10.24		
	+40	-11.54		
	+50	-11.47		
	+60	-13.45		
24	+25	-9.86		
12	+25	-13.89		

NB-IoT Band 4 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1732.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-21.87	±4331.25	Pass
	-20	-16.94		
	-10	-18.22		
	0	-22.53		
	+10	-20.67		
	+20	-21.94		
	+25	-20.59		
	+30	-20.41		
	+40	-21.47		
	+50	-20.64		
	+60	-23.45		
24	+25	-21.29		
12	+25	-22.8		

NB-IoT Band 4 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1732.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-19	±4331.25	Pass
	-20	-19.6		
	-10	-18.25		
	0	-19.66		
	+10	-21.96		
	+20	-19.54		
	+25	-19.44		
	+30	-18.1		
	+40	-23.32		
	+50	-19.88		
	+60	-18.3		
24	+25	-19.07		
12	+25	-24.09		

NB-IoT Band 4 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1754.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-4.88	±4387.25	Pass
	-20	-5.81		
	-10	-0.99		
	0	-4.26		
	+10	-2.93		
	+20	-1.06		
	+25	-5.78		
	+30	-3.22		
	+40	-4.21		
	+50	-2.96		
	+60	-2.06		
24	+25	-5.56	±4387.25	Pass
12	+25	-4.43		

NB-IoT Band 4 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1754.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-9.27	±4387.25	Pass
	-20	-8.35		
	-10	-3.03		
	0	-5.58		
	+10	-1.5		
	+20	-9.07		
	+25	-4.96		
	+30	-6.95		
	+40	-4.76		
	+50	-5.34		
	+60	-4.58		
24	+25	-3.3	±4387.25	Pass
12	+25	-7.8		

NB-IoT Band 5 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 824.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-8.21	±2060.25	Pass
	-20	-8.83		
	-10	-6.54		
	0	-8.6		
	+10	-6.19		
	+20	-8.15		
	+25	-6.84		
	+30	-7.31		
	+40	-6.22		
	+50	-6.28		
	+60	-5.89		
24	+25	-5.64		
12	+25	-6.98		

NB-IoT Band 5 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 824.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-8.2	±2060.25	Pass
	-20	-7.04		
	-10	-7.91		
	0	-8.67		
	+10	-8.04		
	+20	-6.72		
	+25	-5.29		
	+30	-6.59		
	+40	-6.27		
	+50	-5.87		
	+60	-6.18		
24	+25	-5.97		
12	+25	-6.85		

NB-IoT Band 5 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 836.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-6.51	±2091.25	Pass
	-20	-8.47		
	-10	-6.79		
	0	-6.74		
	+10	-8.01		
	+20	-7.98		
	+25	-6.75		
	+30	-5.69		
	+40	-7.68		
	+50	-7.84		
	+60	-7.93		
24	+25	-5.98		
12	+25	-7.98		

NB-IoT Band 5 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 836.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-8.53	±2091.25	Pass
	-20	-6.69		
	-10	-8.55		
	0	-8.47		
	+10	-8.04		
	+20	-6.97		
	+25	-7.82		
	+30	-8.37		
	+40	-6.69		
	+50	-6.12		
	+60	-9.1		
24	+25	-8.8		
12	+25	-5.59		

NB-IoT Band 5 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 848.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-8.97	±2122.25	Pass
	-20	-7.77		
	-10	-9.71		
	0	-9.86		
	+10	-8.67		
	+20	-8.83		
	+25	-8.13		
	+30	-6.05		
	+40	-7.74		
	+50	-6.78		
	+60	-7.88		
24	+25	-6.74		
12	+25	-7.37		

NB-IoT Band 5 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 848.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-9.97	±2122.25	Pass
	-20	-7.82		
	-10	-10.77		
	0	-8.7		
	+10	-6.61		
	+20	-8.6		
	+25	-7.01		
	+30	-8.21		
	+40	-7.61		
	+50	-7.51		
	+60	-8.1		
24	+25	-7.48		
12	+25	-8.28		

NB-IoT Band 5 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 824.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-9.8	±2060.25	Pass
	-20	-7.91		
	-10	-8.18		
	0	-8.81		
	+10	-7.59		
	+20	-8.25		
	+25	-8.21		
	+30	-7.28		
	+40	-6.11		
	+50	-9.68		
	+60	-9.44		
24	+25	-8.91		
12	+25	-7.84		

NB-IoT Band 5 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 824.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-10.4	±2060.25	Pass
	-20	-10.34		
	-10	-10.21		
	0	-10.94		
	+10	-11.01		
	+20	-10.77		
	+25	-11.32		
	+30	-10		
	+40	-7.61		
	+50	-9.97		
	+60	-9.61		
24	+25	-10.63		
12	+25	-8.88		

NB-IoT Band 5 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 836.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-9.26	±2091.25	Pass
	-20	-7.94		
	-10	-8.1		
	0	-8.87		
	+10	-8.88		
	+20	-6.95		
	+25	-9		
	+30	-8.13		
	+40	-6.95		
	+50	-7.93		
	+60	-8.31		
24	+25	-8.34		
12	+25	-7.67		

NB-IoT Band 5 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 836.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-11.69	±2091.25	Pass
	-20	-10.84		
	-10	-10.33		
	0	-10.53		
	+10	-11.22		
	+20	-11.77		
	+25	-11.50		
	+30	-11.42		
	+40	-9.13		
	+50	-10.67		
	+60	-10.17		
24	+25	-10.77		
12	+25	-10.09		

NB-IoT Band 5 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 848.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-7.95	±2122.25	Pass
	-20	-6.74		
	-10	-6.75		
	0	-8.14		
	+10	-4.88		
	+20	-7.17		
	+25	-6.54		
	+30	-5.76		
	+40	-5.79		
	+50	-6.68		
	+60	-6.08		
24	+25	-6.54		
12	+25	-6.05		

NB-IoT Band 5 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 848.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-7.4	±2122.25	Pass
	-20	-8.08		
	-10	-6.47		
	0	-8.24		
	+10	-6.32		
	+20	-6.94		
	+25	-6.75		
	+30	-6.41		
	+40	-7.1		
	+50	-6.95		
	+60	-9.21		
24	+25	-7.54		
12	+25	-7.25		

NB-IoT Band 12 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 699.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-2.52	±1747.75	Pass
	-20	-4.09		
	-10	-2.88		
	0	-1.75		
	+10	-3		
	+20	-2.72		
	+25	-1.49		
	+30	-2.68		
	+40	-1.5		
	+50	-1.1		
	+60	-0.94		
24	+25	-1.75		
12	+25	-2.86		

NB-IoT Band 12 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 699.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-4.21	±1747.75	Pass
	-20	-1.95		
	-10	-1.5		
	0	-3.51		
	+10	-3.66		
	+20	-3.76		
	+25	-3.26		
	+30	-3.38		
	+40	-2.98		
	+50	-4.28		
	+60	-2.89		
24	+25	-4.33		
12	+25	-1.54		

NB-IoT Band 12 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 707.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-2.23	±1768.75	Pass
	-20	-3.26		
	-10	-3.58		
	0	-3.29		
	+10	-0.84		
	+20	-2.93		
	+25	-4.39		
	+30	-3.91		
	+40	-3.32		
	+50	-1.66		
	+60	-1.95		
24	+25	-3.49	±1768.75	Pass
12	+25	-2.12		

NB-IoT Band 12 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 707.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-3.25	±1768.75	Pass
	-20	-3.42		
	-10	-3.46		
	0	-2.49		
	+10	-3.52		
	+20	-1.33		
	+25	-1.87		
	+30	-2.92		
	+40	-1.7		
	+50	-3.71		
	+60	-1.86		
24	+25	-3.62	±1768.75	Pass
12	+25	-2.52		

NB-IoT Band 12 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 715.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-3.78	±1789.75	Pass
	-20	-4.09		
	-10	-4.39		
	0	-3.86		
	+10	-4.26		
	+20	-3.98		
	+25	-4.53		
	+30	-3.52		
	+40	-2.63		
	+50	-2.5		
	+60	-1.65		
24	+25	-2.2	±1789.75	Pass
12	+25	-2.8		

NB-IoT Band 12 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 715.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-5.95	±1789.75	Pass
	-20	-3.12		
	-10	-4.82		
	0	-4.23		
	+10	-3.48		
	+20	-4.56		
	+25	-3.53		
	+30	-3.38		
	+40	-4.63		
	+50	-2.86		
	+60	-3.46		
24	+25	-3.42	±1789.75	Pass
12	+25	-3.3		

NB-IoT Band 12 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 699.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-1.77	±1747.75	Pass
	-20	-1.33		
	-10	-0.5		
	0	-1.7		
	+10	-1.02		
	+20	-1.87		
	+25	-2.21		
	+30	-0.97		
	+40	-2.22		
	+50	-1.26		
	+60	-0.11		
24	+25	-2.3		
12	+25	-2.02		

NB-IoT Band 12 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 699.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-1.23	±1747.75	Pass
	-20	-3.23		
	-10	-1.47		
	0	-2.33		
	+10	-2.76		
	+20	-2.75		
	+25	-0.72		
	+30	-0.79		
	+40	-3.12		
	+50	-1.87		
	+60	-1.77		
24	+25	-1.13		
12	+25	-4.35		

NB-IoT Band 12 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 707.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-2.05	±1768.75	Pass
	-20	-2.88		
	-10	-0.4		
	0	-0.11		
	+10	-0.72		
	+20	-2.29		
	+25	-0.54		
	+30	-0.99		
	+40	-1.39		
	+50	-0.77		
	+60	-2.42		
24	+25	-3.28		
12	+25	-3.25		

NB-IoT Band 12 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 707.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-3.42	±1768.75	Pass
	-20	-2.99		
	-10	-1.24		
	0	-2.98		
	+10	-2.95		
	+20	-2.8		
	+25	-2.17		
	+30	-3.06		
	+40	-3.68		
	+50	-3.86		
	+60	-1.02		
24	+25	-1.77		
12	+25	-4.25		

NB-IoT Band 12 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 715.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-2.96	±1789.75	Pass
	-20	-0.36		
	-10	-1.79		
	0	-0.8		
	+10	-0.01		
	+20	-0.16		
	+25	-0.23		
	+30	0.59		
	+40	-2.22		
	+50	-0.11		
	+60	-0.99		
24	+25	-0.29		
12	+25	-0.04		

NB-IoT Band 12 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 715.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-0.03	±1789.75	Pass
	-20	-2.27		
	-10	-3.6		
	0	-4.11		
	+10	-4.34		
	+20	-2.25		
	+25	-3.96		
	+30	-2.4		
	+40	-1.29		
	+50	-1.02		
	+60	-3.78		
24	+25	-3.66		
12	+25	-1.03		

NB-IoT Band 13 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 777.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-11.49	±1942.75	Pass
	-20	-11.72		
	-10	-10.32		
	0	-9.93		
	+10	-10.94		
	+20	-10.24		
	+25	-9.33		
	+30	-11.34		
	+40	-10.94		
	+50	-9.18		
	+60	-10.1		
24	+25	-9.57		
12	+25	-9.3		

NB-IoT Band 13 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 777.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-12.19	±1942.75	Pass
	-20	-12.56		
	-10	-10.92		
	0	-13.16		
	+10	-14.47		
	+20	-12.23		
	+25	-11.14		
	+30	-9.63		
	+40	-10.87		
	+50	-9.43		
	+60	-11.54		
24	+25	-12.26		
12	+25	-9.17		

NB-IoT Band 13 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 782 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-7.74	±1955	Pass
	-20	-7.04		
	-10	-7.81		
	0	-6.94		
	+10	-8.28		
	+20	-6.79		
	+25	-8.04		
	+30	-7.81		
	+40	-8.81		
	+50	-7.67		
	+60	-5.95		
24	+25	-7.74		
12	+25	-7.71		

NB-IoT Band 13 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 782 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-6.41	±1955	Pass
	-20	-6.67		
	-10	-7.04		
	0	-7.6		
	+10	-7.95		
	+20	-7.14		
	+25	-7.1		
	+30	-7.31		
	+40	-9.5		
	+50	-8.24		
	+60	-6.58		
24	+25	-6.38		
12	+25	-7.14		

NB-IoT Band 13 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 786.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-8.5	±1967.25	Pass
	-20	-9.53		
	-10	-9.17		
	0	-7.7		
	+10	-8.05		
	+20	-7.38		
	+25	-6.28		
	+30	-7.41		
	+40	-6.44		
	+50	-5.56		
	+60	-5.35		
24	+25	-6.49		
12	+25	-4.81		

NB-IoT Band 13 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 786.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-7.3	±1967.25	Pass
	-20	-8.27		
	-10	-7.71		
	0	-8.67		
	+10	-8.97		
	+20	-8.28		
	+25	-8.54		
	+30	-9.1		
	+40	-8.33		
	+50	-6.48		
	+60	-7.22		
24	+25	-7.61		
12	+25	-8.38		

NB-IoT Band 13 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 777.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-6.37	±1942.75	Pass
	-20	-7.51		
	-10	-6.78		
	0	-8.31		
	+10	-8.6		
	+20	-7.9		
	+25	-5.56		
	+30	-6.18		
	+40	-7.5		
	+50	-6.65		
	+60	-6.29		
24	+25	-8.37		
12	+25	-7.72		

NB-IoT Band 13 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 777.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-10.66	±1942.75	Pass
	-20	-8.37		
	-10	-8.21		
	0	-8.74		
	+10	-9.88		
	+20	-7.62		
	+25	-9.28		
	+30	-10.37		
	+40	-9.47		
	+50	-8.51		
	+60	-9.24		
24	+25	-7.48		
12	+25	-8.11		

NB-IoT Band 13 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 782 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-8.37	±1955	Pass
	-20	-8.61		
	-10	-8.68		
	0	-7.71		
	+10	-8.93		
	+20	-8.97		
	+25	-9.91		
	+30	-10.72		
	+40	-9.06		
	+50	-6.81		
	+60	-9.08		
24	+25	-7.71		
12	+25	-7.91		

NB-IoT Band 13 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 782 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-11.59	±1955	Pass
	-20	-10.63		
	-10	-12.71		
	0	-10.48		
	+10	-10.97		
	+20	-9.67		
	+25	-11.84		
	+30	-10.74		
	+40	-10.35		
	+50	-11.72		
	+60	-11.19		
24	+25	-11.53		
12	+25	-11.4		

NB-IoT Band 13 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 786.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-3.95	±1967.25	Pass
	-20	-3.35		
	-10	-2.92		
	0	-4.52		
	+10	-5.39		
	+20	-3.72		
	+25	-4.98		
	+30	-3.5		
	+40	-5.48		
	+50	-5.05		
	+60	-6.92		
24	+25	-5.28		
12	+25	-3.69		

NB-IoT Band 13 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 786.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-5.08	±1967.25	Pass
	-20	-7.35		
	-10	-7.24		
	0	-4.25		
	+10	-5.34		
	+20	-6.09		
	+25	-5.42		
	+30	-5.48		
	+40	-7.7		
	+50	-6.84		
	+60	-5.51		
24	+25	-6.48		
12	+25	-5.41		

NB-IoT Band 25 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1850.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-16.92	±4625.25	Pass
	-20	-14.82		
	-10	-13.7		
	0	-15.03		
	+10	-15.94		
	+20	-13.33		
	+25	-10.6		
	+30	-14.32		
	+40	-14.18		
	+50	-9.14		
	+60	-10.86		
24	+25	-12		
12	+25	-13.28		

NB-IoT Band 25 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1850.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-16.44	±4625.25	Pass
	-20	-17.77		
	-10	-16.72		
	0	-15.68		
	+10	-16.74		
	+20	-16.48		
	+25	-12.57		
	+30	-10.49		
	+40	-11.05		
	+50	-16.65		
	+60	-14.26		
24	+25	-14.05		
12	+25	-13.9		

NB-IoT Band 25 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1882.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-11.43	±4706.25	Pass
	-20	-15.59		
	-10	-11.22		
	0	-8.71		
	+10	-12.25		
	+20	-14.23		
	+25	-15.21		
	+30	-12.37		
	+40	-15.42		
	+50	-14.48		
	+60	-11.9		
24	+25	-9.48		
12	+25	-12.76		

NB-IoT Band 25 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1882.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-13.09	±4706.25	Pass
	-20	-14.86		
	-10	-15.89		
	0	-14.45		
	+10	-16.01		
	+20	-16.29		
	+25	-17.17		
	+30	-10.46		
	+40	-11.53		
	+50	-15.38		
	+60	-14.35		
24	+25	-16.74		
12	+25	-11.17		

NB-IoT Band 25 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1914.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-15.18	±4787.25	Pass
	-20	-18.8		
	-10	-16.89		
	0	-18.83		
	+10	-15.69		
	+20	-12.99		
	+25	-11.72		
	+30	-13.78		
	+40	-10.59		
	+50	-14.33		
	+60	-10.21		
24	+25	-11.54	±4787.25	Pass
12	+25	-15.32		

NB-IoT Band 25 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1914.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-14.93	±4787.25	Pass
	-20	-15.95		
	-10	-18.87		
	0	-18.47		
	+10	-13.83		
	+20	-17.88		
	+25	-12.2		
	+30	-12.46		
	+40	-12.43		
	+50	-12.68		
	+60	-12.97		
24	+25	-13.65	±4787.25	Pass
12	+25	-13.03		

NB-IoT Band 25 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1850.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-14.89	±4625.25	Pass
	-20	-12.9		
	-10	-10.03		
	0	-13.69		
	+10	-11.07		
	+20	-13.2		
	+25	-14.79		
	+30	-11.7		
	+40	-11.16		
	+50	-10.97		
	+60	-13.05		
24	+25	-13.75		
12	+25	-9.14		

NB-IoT Band 25 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1850.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-12.83	±4625.25	Pass
	-20	-16.26		
	-10	-12.26		
	0	-14.18		
	+10	-12.86		
	+20	-13.72		
	+25	-16.74		
	+30	-13.5		
	+40	-17.35		
	+50	-11.46		
	+60	-15.22		
24	+25	-16.29		
12	+25	-13.36		

NB-IoT Band 25 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1882.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-10.3	±4706.25	Pass
	-20	-7.87		
	-10	-13.26		
	0	-8.2		
	+10	-11.09		
	+20	-8.75		
	+25	-9.57		
	+30	-7.7		
	+40	-10.16		
	+50	-7.57		
	+60	-6.47		
24	+25	-8.21		
12	+25	-7.7		

NB-IoT Band 25 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1882.5 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-10.24	±4706.25	Pass
	-20	-13.75		
	-10	-9.81		
	0	-10.76		
	+10	-10.6		
	+20	-14.05		
	+25	-12.29		
	+30	-14.15		
	+40	-13.68		
	+50	-13.45		
	+60	-14.71		
24	+25	-12.75		
12	+25	-10.64		

NB-IoT Band 25 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1914.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-12.25	±4787.25	Pass
	-20	-11.06		
	-10	-17.92		
	0	-12.59		
	+10	-14.43		
	+20	-16.71		
	+25	-11.63		
	+30	-12.1		
	+40	-12.99		
	+50	-12.79		
	+60	-16.06		
24	+25	-12.03		
12	+25	-13.9		

NB-IoT Band 25 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1914.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-16.04	±4787.25	Pass
	-20	-14.75		
	-10	-17.44		
	0	-16.44		
	+10	-15.48		
	+20	-19.18		
	+25	-18.51		
	+30	-15.16		
	+40	-17.48		
	+50	-15.49		
	+60	-12.9		
24	+25	-13.52		
12	+25	-13.69		

NB-IoT Band 66 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1710.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-12.58	±4275.25	Pass
	-20	-13.75		
	-10	-12.66		
	0	-15.25		
	+10	-13.06		
	+20	-12.55		
	+25	-14.41		
	+30	-9.88		
	+40	-10.5		
	+50	-11.46		
	+60	-10.27		
24	+25	-10.63		
12	+25	-11.07		

NB-IoT Band 66 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1710.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-14.91	±4275.25	Pass
	-20	-11.8		
	-10	-16.31		
	0	-16.12		
	+10	-14.89		
	+20	-15.68		
	+25	-10.63		
	+30	-13.82		
	+40	-11.32		
	+50	-10.13		
	+60	-11.92		
24	+25	-13.85		
12	+25	-10.99		

NB-IoT Band 66 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1745 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-6.82	±4362.5	Pass
	-20	-9.01		
	-10	-3.03		
	0	-6.78		
	+10	-5.18		
	+20	-6.21		
	+25	-7.51		
	+30	-7.17		
	+40	-8.45		
	+50	-3.82		
	+60	-8.18		
24	+25	-7.93		
12	+25	-8.28		

NB-IoT Band 66 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1745 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-9.88	±4362.5	Pass
	-20	-7.05		
	-10	-10.44		
	0	-9.78		
	+10	-11.37		
	+20	-4.61		
	+25	-7.2		
	+30	-10.54		
	+40	-7.77		
	+50	-8.57		
	+60	-6.77		
24	+25	-10.09		
12	+25	-8.48		

NB-IoT Band 66 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1779.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-19.81	±4449.75	Pass
	-20	-23.06		
	-10	-20.48		
	0	-20.24		
	+10	-18.48		
	+20	-17.42		
	+25	-19.63		
	+30	-15.42		
	+40	-18.11		
	+50	-15.08		
	+60	-15.52		
24	+25	-18.87		
12	+25	-16.16		

NB-IoT Band 66 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1779.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-18.12	±4449.75	Pass
	-20	-15.98		
	-10	-20.27		
	0	-15.29		
	+10	-17.62		
	+20	-14.92		
	+25	-14.19		
	+30	-12.99		
	+40	-17.74		
	+50	-16.38		
	+60	-17.72		
24	+25	-15.48		
12	+25	-12.6		

NB-IoT Band 66 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1710.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-11.92	±4275.25	Pass
	-20	-11.14		
	-10	-8.6		
	0	-9.76		
	+10	-6.95		
	+20	-14.25		
	+25	-11.8		
	+30	-8.15		
	+40	-10.07		
	+50	-12.02		
	+60	-12.83		
24	+25	-7.87		
12	+25	-11.74		

NB-IoT Band 66 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 1710.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-13.36	±4275.25	Pass
	-20	-15.32		
	-10	-10		
	0	-9.44		
	+10	-11.24		
	+20	-13.09		
	+25	-8.83		
	+30	-10.8		
	+40	-13.72		
	+50	-10.87		
	+60	-10.5		
24	+25	-11.56		
12	+25	-8.25		

NB-IoT Band 66 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1745 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-5.45	±4362.5	Pass
	-20	-3.49		
	-10	-2.7		
	0	-4.94		
	+10	-5.02		
	+20	-5.38		
	+25	-4.13		
	+30	-4.39		
	+40	-5.08		
	+50	-4.69		
	+60	-5.15		
24	+25	-4.51		
12	+25	-4.15		

NB-IoT Band 66 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 1745 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-6.69	±4362.5	Pass
	-20	-4.85		
	-10	-7.57		
	0	-5.15		
	+10	-4.38		
	+20	-3.5		
	+25	-4.72		
	+30	-7.15		
	+40	-6.85		
	+50	-7.41		
	+60	-6.98		
24	+25	-6.44		
12	+25	-3.58		

NB-IoT Band 66 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1779.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-14.72	±4449.75	Pass
	-20	-18.85		
	-10	-12.56		
	0	-13.85		
	+10	-14.96		
	+20	-15.41		
	+25	-11.53		
	+30	-15.56		
	+40	-12.86		
	+50	-11.23		
	+60	-16.01		
24	+25	-15.52		
12	+25	-13.33		

NB-IoT Band 66 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 1779.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-15.29	±4449.75	Pass
	-20	-20.54		
	-10	-20.7		
	0	-19.2		
	+10	-19.87		
	+20	-17.28		
	+25	-17.65		
	+30	-15.94		
	+40	-19.93		
	+50	-15.72		
	+60	-14.81		
24	+25	-18.91		
12	+25	-19.96		

NB-IoT Band 85 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 698.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-9.73	±1745.25	Pass
	-20	-11.13		
	-10	-10.74		
	0	-9.74		
	+10	-10.03		
	+20	-6.72		
	+25	-7.28		
	+30	-7.77		
	+40	-7.32		
	+50	-8.04		
	+60	-6.35		
24	+25	-6.38		
12	+25	-8.86		

NB-IoT Band 85 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 698.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-11.36	±1745.25	Pass
	-20	-10.56		
	-10	-9.78		
	0	-9.87		
	+10	-10.53		
	+20	-7.28		
	+25	-7.44		
	+30	-7.78		
	+40	-8.45		
	+50	-7.52		
	+60	-10.21		
24	+25	-9.87		
12	+25	-7.38		

NB-IoT Band 85 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 706 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-6.07	±1765	Pass
	-20	-5.24		
	-10	-4.63		
	0	-5.21		
	+10	-5.54		
	+20	-5.01		
	+25	-5.35		
	+30	-5.36		
	+40	-4.13		
	+50	-4.08		
	+60	-5.15		
24	+25	-4.82		
12	+25	-3.79		

NB-IoT Band 85 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 706 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-3.82	±1765	Pass
	-20	-5.04		
	-10	-6.95		
	0	-5.65		
	+10	-4.82		
	+20	-3.52		
	+25	-4.95		
	+30	-3.89		
	+40	-5.21		
	+50	-6.91		
	+60	-4.38		
24	+25	-4.62		
12	+25	-6.51		

NB-IoT Band 85 QPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 715.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-1.46	±1789.75	Pass
	-20	-1.37		
	-10	-2.2		
	0	-2.95		
	+10	-3.65		
	+20	-0.51		
	+25	-0.16		
	+30	-1.36		
	+40	-2.9		
	+50	-1.97		
	+60	-4.51		
24	+25	-0.39		
12	+25	0		

NB-IoT Band 85 BPSK 3.75kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 715.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-7.1	±1789.75	Pass
	-20	-9.08		
	-10	-7.01		
	0	-8.47		
	+10	-6.48		
	+20	-5.91		
	+25	-4.96		
	+30	-5.02		
	+40	-4.39		
	+50	-3.64		
	+60	-4.43		
24	+25	-3.96		
12	+25	-4.94		

NB-IoT Band 85 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 698.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-8.1	±1745.25	Pass
	-20	-5.48		
	-10	-6.92		
	0	-6.37		
	+10	-5.91		
	+20	-6.14		
	+25	-4.76		
	+30	-7.73		
	+40	-8.08		
	+50	-7.74		
	+60	-4.38		
24	+25	-5.79		
12	+25	-6.5		

NB-IoT Band 85 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	LCH 698.1 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-9.06	±1745.25	Pass
	-20	-9.43		
	-10	-7.89		
	0	-7.91		
	+10	-7.4		
	+20	-9.16		
	+25	-9.26		
	+30	-7.55		
	+40	-9.53		
	+50	-6.97		
	+60	-8.85		
24	+25	-8.68		
12	+25	-6.69		

NB-IoT Band 85 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 706 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-4.72	±1765	Pass
	-20	-4.85		
	-10	-5.06		
	0	-3.12		
	+10	-5.72		
	+20	-5.56		
	+25	-4.66		
	+30	-3.75		
	+40	-5.59		
	+50	-3.92		
	+60	-4.99		
24	+25	-4.73		
12	+25	-3.53		

NB-IoT Band 85 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	MCH 706 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-6.11	±1765	Pass
	-20	-7.15		
	-10	-5.88		
	0	-5.68		
	+10	-6.29		
	+20	-7.51		
	+25	-5.28		
	+30	-5.56		
	+40	-6.49		
	+50	-6.05		
	+60	-5.64		
24	+25	-5.55		
12	+25	-4.96		

NB-IoT Band 85 QPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 715.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-4.91	±1789.75	Pass
	-20	-4.36		
	-10	-2.09		
	0	-3.05		
	+10	-1.72		
	+20	-2.16		
	+25	-2.68		
	+30	-0.8		
	+40	-3.09		
	+50	-0.74		
	+60	-3.82		
24	+25	-0.6		
12	+25	-1.95		

NB-IoT Band 85 BPSK 15kHz

Test Conditions		Frequency Deviation		Verdict
Power (VDC)	Temperature (°C)	HCH 715.9 MHz		
		Value (Hz)	Limits (Hz)	
18	-30	-3.39	±1789.75	Pass
	-20	-3.49		
	-10	-3.76		
	0	-2.05		
	+10	-4.13		
	+20	-2		
	+25	-1.36		
	+30	-3.88		
	+40	-1.34		
	+50	-0.83		
	+60	-2.5		
24	+25	-1.8		
12	+25	-3.88		

A.5 Spurious Emission at Antenna Terminals

Note 1: GPRS and EGPRS modes have been verified, and only the worst data with different bandwidth for LTE are shown here.

Note 2: The frequencies of verdict which are marked by "N/A" should be ignored because they are UE carrier frequency.

Note 3: Test plots please refer to the document "Annex No.: BL-SZ2140097-501 Data Part 3.pdf".

GSM Mode Test Verdict

Test Band	Test Channel	Refer to Plot ^{Note3}	Verdict
GPRS 850	LCH	1.1	Pass
	MCH	1.2	Pass
	HCH	1.3	Pass
GPRS 1900	LCH	2.1	Pass
	MCH	2.2	Pass
	HCH	2.3	Pass
EGPRS 850	LCH	3.1	Pass
	MCH	3.2	Pass
	HCH	3.3	Pass
EGPRS 1900	LCH	4.1	Pass
	MCH	4.2	Pass
	HCH	4.3	Pass

LTE-M1 Mode Test Data

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
LTE-M1 Band 2	1.4 MHz	LCH	QPSK	RB1#0	5.1	Pass
			16-QAM	RB1#0	5.2	Pass
		MCH	QPSK	RB1#0	5.3	Pass
			16-QAM	RB1#0	5.4	Pass
		HCH	QPSK	RB1#0	5.5	Pass
			16-QAM	RB1#0	5.6	Pass
	3 MHz	LCH	QPSK	RB1#0	5.7	Pass
			16-QAM	RB1#0	5.8	Pass
		MCH	QPSK	RB1#0	5.9	Pass
			16-QAM	RB1#0	5.10	Pass
		HCH	QPSK	RB1#0	5.11	Pass
			16-QAM	RB1#0	5.12	Pass
	5 MHz	LCH	QPSK	RB1#0	5.13	Pass
			16-QAM	RB1#0	5.14	Pass
		MCH	QPSK	RB1#0	5.15	Pass
			16-QAM	RB1#0	5.16	Pass
		HCH	QPSK	RB1#0	5.17	Pass
			16-QAM	RB1#0	5.18	Pass
	10 MHz	LCH	QPSK	RB1#0	5.19	Pass
			16-QAM	RB1#0	5.20	Pass
		MCH	QPSK	RB1#0	5.21	Pass
			16-QAM	RB1#0	5.22	Pass
		HCH	QPSK	RB1#0	5.23	Pass
			16-QAM	RB1#0	5.24	Pass
	15 MHz	LCH	QPSK	RB1#0	5.25	Pass
			16-QAM	RB1#0	5.26	Pass
		MCH	QPSK	RB1#0	5.27	Pass
			16-QAM	RB1#0	5.28	Pass
		HCH	QPSK	RB1#0	5.29	Pass
			16-QAM	RB1#0	5.30	Pass
	20 MHz	LCH	QPSK	RB1#0	5.31	Pass
			16-QAM	RB1#0	5.32	Pass
		MCH	QPSK	RB1#0	5.33	Pass
			16-QAM	RB1#0	5.34	Pass
		HCH	QPSK	RB1#0	5.35	Pass
			16-QAM	RB1#0	5.36	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
LTE-M1 Band 4	1.4 MHz	LCH	QPSK	RB1#0	6.1	Pass
			16-QAM	RB1#0	6.2	Pass
		MCH	QPSK	RB1#0	6.3	Pass
			16-QAM	RB1#0	6.4	Pass
		HCH	QPSK	RB1#0	6.5	Pass
			16-QAM	RB1#0	6.6	Pass
	3 MHz	LCH	QPSK	RB1#0	6.7	Pass
			16-QAM	RB1#0	6.8	Pass
		MCH	QPSK	RB1#0	6.9	Pass
			16-QAM	RB1#0	6.10	Pass
		HCH	QPSK	RB1#0	6.11	Pass
			16-QAM	RB1#0	6.12	Pass
	5 MHz	LCH	QPSK	RB1#0	6.13	Pass
			16-QAM	RB1#0	6.14	Pass
		MCH	QPSK	RB1#0	6.15	Pass
			16-QAM	RB1#0	6.16	Pass
		HCH	QPSK	RB1#0	6.17	Pass
			16-QAM	RB1#0	6.18	Pass
	10 MHz	LCH	QPSK	RB1#0	6.19	Pass
			16-QAM	RB1#0	6.20	Pass
		MCH	QPSK	RB1#0	6.21	Pass
			16-QAM	RB1#0	6.22	Pass
		HCH	QPSK	RB1#0	6.23	Pass
			16-QAM	RB1#0	6.24	Pass
	15 MHz	LCH	QPSK	RB1#0	6.25	Pass
			16-QAM	RB1#0	6.26	Pass
		MCH	QPSK	RB1#0	6.27	Pass
			16-QAM	RB1#0	6.28	Pass
		HCH	QPSK	RB1#0	6.29	Pass
			16-QAM	RB1#0	6.30	Pass
	20 MHz	LCH	QPSK	RB1#0	6.31	Pass
			16-QAM	RB1#0	6.32	Pass
		MCH	QPSK	RB1#0	6.33	Pass
			16-QAM	RB1#0	6.34	Pass
		HCH	QPSK	RB1#0	6.35	Pass
			16-QAM	RB1#0	6.36	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
LTE-M1 Band 5	1.4 MHz	LCH	QPSK	RB1#0	7.1	Pass
			16-QAM	RB1#0	7.2	Pass
		MCH	QPSK	RB1#0	7.3	Pass
			16-QAM	RB1#0	7.4	Pass
		HCH	QPSK	RB1#0	7.5	Pass
			16-QAM	RB1#0	7.6	Pass
	3 MHz	LCH	QPSK	RB1#0	7.7	Pass
			16-QAM	RB1#0	7.8	Pass
		MCH	QPSK	RB1#0	7.9	Pass
			16-QAM	RB1#0	7.10	Pass
		HCH	QPSK	RB1#0	7.11	Pass
			16-QAM	RB1#0	7.12	Pass
	5 MHz	LCH	QPSK	RB1#0	7.13	Pass
			16-QAM	RB1#0	7.14	Pass
		MCH	QPSK	RB1#0	7.15	Pass
			16-QAM	RB1#0	7.16	Pass
		HCH	QPSK	RB1#0	7.17	Pass
			16-QAM	RB1#0	7.18	Pass
	10 MHz	LCH	QPSK	RB1#0	7.19	Pass
			16-QAM	RB1#0	7.20	Pass
		MCH	QPSK	RB1#0	7.21	Pass
			16-QAM	RB1#0	7.22	Pass
		HCH	QPSK	RB1#0	7.23	Pass
			16-QAM	RB1#0	7.24	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
LTE-M1 Band 12	1.4 MHz	LCH	QPSK	RB1#0	8.1	Pass
			16-QAM	RB1#0	8.2	Pass
		MCH	QPSK	RB1#0	8.3	Pass
			16-QAM	RB1#0	8.4	Pass
		HCH	QPSK	RB1#0	8.5	Pass
			16-QAM	RB1#0	8.6	Pass
	3 MHz	LCH	QPSK	RB1#0	8.7	Pass
			16-QAM	RB1#0	8.8	Pass
		MCH	QPSK	RB1#0	8.9	Pass
			16-QAM	RB1#0	8.10	Pass
		HCH	QPSK	RB1#0	8.11	Pass
			16-QAM	RB1#0	8.12	Pass
	5 MHz	LCH	QPSK	RB1#0	8.13	Pass
			16-QAM	RB1#0	8.14	Pass
		MCH	QPSK	RB1#0	8.15	Pass
			16-QAM	RB1#0	8.16	Pass
		HCH	QPSK	RB1#0	8.17	Pass
			16-QAM	RB1#0	8.18	Pass
	10 MHz	LCH	QPSK	RB1#0	8.19	Pass
			16-QAM	RB1#0	8.20	Pass
		MCH	QPSK	RB1#0	8.21	Pass
			16-QAM	RB1#0	8.22	Pass
		HCH	QPSK	RB1#0	8.23	Pass
			16-QAM	RB1#0	8.24	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
LTE-M1 Band 13	5 MHz	LCH	QPSK	RB1#0	9.1	Pass
			16-QAM	RB1#0	9.2	Pass
		MCH	QPSK	RB1#0	9.3	Pass
			16-QAM	RB1#0	9.4	Pass
		HCH	QPSK	RB1#0	9.5	Pass
			16-QAM	RB1#0	9.6	Pass
	10 MHz	MCH	QPSK	RB1#0	9.7	Pass
			16-QAM	RB1#0	9.8	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
LTE-M1 Band 25	1.4 MHz	LCH	QPSK	RB1#0	10.1	Pass
			16-QAM	RB1#0	10.2	Pass
		MCH	QPSK	RB1#0	10.3	Pass
			16-QAM	RB1#0	10.4	Pass
		HCH	QPSK	RB1#0	10.5	Pass
			16-QAM	RB1#0	10.6	Pass
	3 MHz	LCH	QPSK	RB1#0	10.7	Pass
			16-QAM	RB1#0	10.8	Pass
		MCH	QPSK	RB1#0	10.9	Pass
			16-QAM	RB1#0	10.10	Pass
		HCH	QPSK	RB1#0	10.11	Pass
			16-QAM	RB1#0	10.12	Pass
	5 MHz	LCH	QPSK	RB1#0	10.13	Pass
			16-QAM	RB1#0	10.14	Pass
		MCH	QPSK	RB1#0	10.15	Pass
			16-QAM	RB1#0	10.16	Pass
		HCH	QPSK	RB1#0	10.17	Pass
			16-QAM	RB1#0	10.18	Pass
	10 MHz	LCH	QPSK	RB1#0	10.19	Pass
			16-QAM	RB1#0	10.20	Pass
		MCH	QPSK	RB1#0	10.21	Pass
			16-QAM	RB1#0	10.22	Pass
		HCH	QPSK	RB1#0	10.23	Pass
			16-QAM	RB1#0	10.24	Pass
	15 MHz	LCH	QPSK	RB1#0	10.25	Pass
			16-QAM	RB1#0	10.26	Pass
		MCH	QPSK	RB1#0	10.27	Pass
			16-QAM	RB1#0	10.28	Pass
		HCH	QPSK	RB1#0	10.29	Pass
			16-QAM	RB1#0	10.30	Pass
	20 MHz	LCH	QPSK	RB1#0	10.31	Pass
			16-QAM	RB1#0	10.32	Pass
		MCH	QPSK	RB1#0	10.33	Pass
			16-QAM	RB1#0	10.34	Pass
		HCH	QPSK	RB1#0	10.35	Pass
			16-QAM	RB1#0	10.36	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
LTE-M1 Band 26 (part22)	1.4 MHz	LCH	QPSK	RB1#0	11.1	Pass
			16-QAM	RB1#0	11.2	Pass
		MCH	QPSK	RB1#0	11.3	Pass
			16-QAM	RB1#0	11.4	Pass
		HCH	QPSK	RB1#0	11.5	Pass
			16-QAM	RB1#0	11.6	Pass
	3 MHz	LCH	QPSK	RB1#0	11.7	Pass
			16-QAM	RB1#0	11.8	Pass
		MCH	QPSK	RB1#0	11.9	Pass
			16-QAM	RB1#0	11.10	Pass
		HCH	QPSK	RB1#0	11.11	Pass
			16-QAM	RB1#0	11.12	Pass
	5 MHz	LCH	QPSK	RB1#0	11.13	Pass
			16-QAM	RB1#0	11.14	Pass
		MCH	QPSK	RB1#0	11.15	Pass
			16-QAM	RB1#0	11.16	Pass
		HCH	QPSK	RB1#0	11.17	Pass
			16-QAM	RB1#0	11.18	Pass
	10 MHz	LCH	QPSK	RB1#0	11.19	Pass
			16-QAM	RB1#0	11.20	Pass
		MCH	QPSK	RB1#0	11.21	Pass
			16-QAM	RB1#0	11.22	Pass
		HCH	QPSK	RB1#0	11.23	Pass
			16-QAM	RB1#0	11.24	Pass
	15 MHz	LCH	QPSK	RB1#0	11.25	Pass
			16-QAM	RB1#0	11.26	Pass
		MCH	QPSK	RB1#0	11.27	Pass
			16-QAM	RB1#0	11.28	Pass
		HCH	QPSK	RB1#0	11.29	Pass
			16-QAM	RB1#0	11.30	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
LTE-M1 Band 26 (part90)	1.4 MHz	LCH	QPSK	RB1#0	12.1	Pass
			16-QAM	RB1#0	12.2	Pass
		MCH	QPSK	RB1#0	12.3	Pass
			16-QAM	RB1#0	12.4	Pass
		HCH	QPSK	RB1#0	12.5	Pass
			16-QAM	RB1#0	12.6	Pass
	3 MHz	LCH	QPSK	RB1#0	12.7	Pass
			16-QAM	RB1#0	12.8	Pass
		MCH	QPSK	RB1#0	12.9	Pass
			16-QAM	RB1#0	12.10	Pass
		HCH	QPSK	RB1#0	12.11	Pass
			16-QAM	RB1#0	12.12	Pass
	5 MHz	LCH	QPSK	RB1#0	12.13	Pass
			16-QAM	RB1#0	12.14	Pass
		MCH	QPSK	RB1#0	12.15	Pass
			16-QAM	RB1#0	12.16	Pass
		HCH	QPSK	RB1#0	12.17	Pass
			16-QAM	RB1#0	12.18	Pass
	10 MHz	MCH	QPSK	RB1#0	12.19	Pass
			16-QAM	RB1#0	12.20	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
LTE-M1 Band 66	1.4 MHz	LCH	QPSK	RB1#0	13.1	Pass
			16-QAM	RB1#0	13.2	Pass
		MCH	QPSK	RB1#0	13.3	Pass
			16-QAM	RB1#0	13.4	Pass
		HCH	QPSK	RB1#0	13.5	Pass
			16-QAM	RB1#0	13.6	Pass
	3 MHz	LCH	QPSK	RB1#0	13.7	Pass
			16-QAM	RB1#0	13.8	Pass
		MCH	QPSK	RB1#0	13.9	Pass
			16-QAM	RB1#0	13.10	Pass
		HCH	QPSK	RB1#0	13.11	Pass
			16-QAM	RB1#0	13.12	Pass
	5 MHz	LCH	QPSK	RB1#0	13.13	Pass
			16-QAM	RB1#0	13.14	Pass
		MCH	QPSK	RB1#0	13.15	Pass
			16-QAM	RB1#0	13.16	Pass
		HCH	QPSK	RB1#0	13.17	Pass
			16-QAM	RB1#0	13.18	Pass
	10 MHz	LCH	QPSK	RB1#0	13.19	Pass
			16-QAM	RB1#0	13.20	Pass
		MCH	QPSK	RB1#0	13.21	Pass
			16-QAM	RB1#0	13.22	Pass
		HCH	QPSK	RB1#0	13.23	Pass
			16-QAM	RB1#0	13.24	Pass
	15 MHz	LCH	QPSK	RB1#0	13.25	Pass
			16-QAM	RB1#0	13.26	Pass
		MCH	QPSK	RB1#0	13.27	Pass
			16-QAM	RB1#0	13.28	Pass
		HCH	QPSK	RB1#0	13.29	Pass
			16-QAM	RB1#0	13.30	Pass
	20 MHz	LCH	QPSK	RB1#0	13.31	Pass
			16-QAM	RB1#0	13.32	Pass
		MCH	QPSK	RB1#0	13.33	Pass
			16-QAM	RB1#0	13.34	Pass
		HCH	QPSK	RB1#0	13.35	Pass
			16-QAM	RB1#0	13.36	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
LTE-M1 Band 85	5 MHz	LCH	QPSK	RB1#0	14.1	Pass
			16-QAM	RB1#0	14.2	Pass
		MCH	QPSK	RB1#0	14.3	Pass
			16-QAM	RB1#0	14.4	Pass
		HCH	QPSK	RB1#0	14.5	Pass
			16-QAM	RB1#0	14.6	Pass
	10 MHz	LCH	QPSK	RB1#0	14.7	Pass
			16-QAM	RB1#0	14.8	Pass
		MCH	QPSK	RB1#0	14.9	Pass
			16-QAM	RB1#0	14.10	Pass
		HCH	QPSK	RB1#0	14.11	Pass
			16-QAM	RB1#0	14.12	Pass

NB-IoT Mode Test Data

Test Band	Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
NB-IoT Band 2	3.75kHz	LCH	QPSK	RB1#0	15.1	Pass
			BPSK	RB1#0	15.2	Pass
		MCH	QPSK	RB1#0	15.3	Pass
			BPSK	RB1#0	15.4	Pass
		HCH	QPSK	RB1#0	15.5	Pass
			BPSK	RB1#0	15.6	Pass
	15kHz	LCH	QPSK	RB1#0	15.7	Pass
			BPSK	RB1#0	15.8	Pass
		MCH	QPSK	RB1#0	15.9	Pass
			BPSK	RB1#0	15.10	Pass
		HCH	QPSK	RB1#0	15.11	Pass
			BPSK	RB1#0	15.12	Pass
NB-IoT Band 4	3.75kHz	LCH	QPSK	RB1#0	16.1	Pass
			BPSK	RB1#0	16.2	Pass
		MCH	QPSK	RB1#0	16.3	Pass
			BPSK	RB1#0	16.4	Pass
		HCH	QPSK	RB1#0	16.5	Pass
			BPSK	RB1#0	16.6	Pass
	15kHz	LCH	QPSK	RB1#0	16.7	Pass
			BPSK	RB1#0	16.8	Pass
		MCH	QPSK	RB1#0	16.9	Pass
			BPSK	RB1#0	16.10	Pass
		HCH	QPSK	RB1#0	16.11	Pass
			BPSK	RB1#0	16.12	Pass
NB-IoT Band 5	3.75kHz	LCH	QPSK	RB1#0	17.1	Pass
			BPSK	RB1#0	17.2	Pass
		MCH	QPSK	RB1#0	17.3	Pass
			BPSK	RB1#0	17.4	Pass
		HCH	QPSK	RB1#0	17.5	Pass
			BPSK	RB1#0	17.6	Pass
	15kHz	LCH	QPSK	RB1#0	17.7	Pass
			BPSK	RB1#0	17.8	Pass
		MCH	QPSK	RB1#0	17.9	Pass
			BPSK	RB1#0	17.10	Pass
		HCH	QPSK	RB1#0	17.11	Pass
			BPSK	RB1#0	17.12	Pass
NB-IoT Band 12	3.75kHz	LCH	QPSK	RB1#0	18.1	Pass
			BPSK	RB1#0	18.2	Pass
		MCH	QPSK	RB1#0	18.3	Pass
			BPSK	RB1#0	18.4	Pass
		HCH	QPSK	RB1#0	18.5	Pass
			BPSK	RB1#0	18.6	Pass

Test Band	Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
	15kHz	LCH	QPSK	RB1#0	18.7	Pass
			BPSK	RB1#0	18.8	Pass
		MCH	QPSK	RB1#0	18.9	Pass
			BPSK	RB1#0	18.10	Pass
		HCH	QPSK	RB1#0	18.11	Pass
			BPSK	RB1#0	18.12	Pass
NB-IoT Band 13	3.75kHz	LCH	QPSK	RB1#0	19.1	Pass
			BPSK	RB1#0	19.2	Pass
		MCH	QPSK	RB1#0	19.3	Pass
			BPSK	RB1#0	19.4	Pass
		HCH	QPSK	RB1#0	19.5	Pass
			BPSK	RB1#0	19.6	Pass
	15kHz	LCH	QPSK	RB1#0	19.7	Pass
			BPSK	RB1#0	19.8	Pass
		MCH	QPSK	RB1#0	19.9	Pass
			BPSK	RB1#0	19.10	Pass
		HCH	QPSK	RB1#0	19.11	Pass
			BPSK	RB1#0	19.12	Pass
NB-IoT Band 25	3.75kHz	LCH	QPSK	RB1#0	20.1	Pass
			BPSK	RB1#0	20.2	Pass
		MCH	QPSK	RB1#0	20.3	Pass
			BPSK	RB1#0	20.4	Pass
		HCH	QPSK	RB1#0	20.5	Pass
			BPSK	RB1#0	20.6	Pass
	15kHz	LCH	QPSK	RB1#0	20.7	Pass
			BPSK	RB1#0	20.8	Pass
		MCH	QPSK	RB1#0	20.9	Pass
			BPSK	RB1#0	20.10	Pass
		HCH	QPSK	RB1#0	20.11	Pass
			BPSK	RB1#0	20.12	Pass
NB-IoT Band 66	3.75kHz	LCH	QPSK	RB1#0	21.1	Pass
			BPSK	RB1#0	21.2	Pass
		MCH	QPSK	RB1#0	21.3	Pass
			BPSK	RB1#0	21.4	Pass
		HCH	QPSK	RB1#0	21.5	Pass
			BPSK	RB1#0	21.6	Pass
	15kHz	LCH	QPSK	RB1#0	21.7	Pass
			BPSK	RB1#0	21.8	Pass
		MCH	QPSK	RB1#0	21.9	Pass
			BPSK	RB1#0	21.10	Pass
		HCH	QPSK	RB1#0	21.11	Pass
			BPSK	RB1#0	21.12	Pass
NB-IoT	3.75kHz	LCH	QPSK	RB1#0	22.1	Pass

Test Band	Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
Band 85			BPSK	RB1#0	22.2	Pass
		MCH	QPSK	RB1#0	22.3	Pass
			BPSK	RB1#0	22.4	Pass
		HCH	QPSK	RB1#0	22.5	Pass
			BPSK	RB1#0	22.6	Pass
	15kHz	LCH	QPSK	RB1#0	22.7	Pass
			BPSK	RB1#0	22.8	Pass
		MCH	QPSK	RB1#0	22.9	Pass
			BPSK	RB1#0	22.10	Pass
		HCH	QPSK	RB1#0	22.11	Pass
			BPSK	RB1#0	22.12	Pass

A.6 Band Edge

Note 1: Test plots please refer to the document “Annex No.: BL-SZ2140097-501 Data Part 4.pdf”.

GSM Mode Test Verdict

Test Band	Test Channel	Refer to Plot ^{Note1}	Verdict
GPRS 850	LCH	1.1	Pass
	HCH	1.2	Pass
GSM 1900	LCH	2.1	Pass
	HCH	2.2	Pass
GPRS 1900	LCH	3.1	Pass
	HCH	3.2	Pass
EGPRS 1900	LCH	4.1	Pass
	HCH	4.2	Pass

LTE-M1 Mode Test Data

Test Band	Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
LTE-M1 Band 2	1.4 MHz	LCH	QPSK	RB1#0	5.1	Pass
				RB6#0	5.2	Pass
			16-QAM	RB1#0	5.3	Pass
				RB5#0	5.4	Pass
		HCH	QPSK	RB1#5	5.5	Pass
				RB6#0	5.6	Pass
			16-QAM	RB1#5	5.7	Pass
				RB5#1	5.8	Pass
	3 MHz	LCH	QPSK	RB1#0	5.9	Pass
				RB6#0	5.10	Pass
			16-QAM	RB1#0	5.11	Pass
				RB5#0	5.12	Pass
		HCH	QPSK	RB1#5	5.13	Pass
				RB6#0	5.14	Pass
			16-QAM	RB1#5	5.15	Pass
				RB5#1	5.16	Pass
	5 MHz	LCH	QPSK	RB1#0	5.17	Pass
				RB6#0	5.18	Pass
			16-QAM	RB1#0	5.19	Pass
				RB5#0	5.20	Pass
		HCH	QPSK	RB1#5	5.21	Pass
				RB6#0	5.22	Pass
			16-QAM	RB1#5	5.23	Pass
				RB5#1	5.24	Pass
	10 MHz	LCH	QPSK	RB1#0	5.25	Pass
				RB6#0	5.26	Pass
			16-QAM	RB1#0	5.27	Pass
				RB5#0	5.28	Pass
		HCH	QPSK	RB1#5	5.29	Pass
				RB6#0	5.30	Pass
			16-QAM	RB1#5	5.31	Pass
				RB5#1	5.32	Pass
	15 MHz	LCH	QPSK	RB1#0	5.33	Pass
				RB6#0	5.34	Pass
			16-QAM	RB1#0	5.35	Pass
				RB5#0	5.36	Pass
		HCH	QPSK	RB1#5	5.37	Pass
				RB6#0	5.38	Pass
			16-QAM	RB1#5	5.39	Pass
				RB5#1	5.40	Pass
	20 MHz	LCH	QPSK	RB1#0	5.41	Pass
				RB6#0	5.42	Pass

Test Band	Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
			16-QAM	RB1#0	5.43	Pass
				RB5#0	5.44	Pass
		HCH	QPSK	RB1#5	5.45	Pass
				RB6#0	5.46	Pass
			16-QAM	RB1#5	5.47	Pass
				RB5#1	5.48	Pass

Test Band	Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
LTE-M1 Band 4	1.4 MHz	LCH	QPSK	RB1#0	6.1	Pass
				RB6#0	6.2	Pass
			16-QAM	RB1#0	6.3	Pass
				RB5#0	6.4	Pass
		HCH	QPSK	RB1#5	6.5	Pass
				RB6#0	6.6	Pass
			16-QAM	RB1#5	6.7	Pass
				RB5#1	6.8	Pass
	3 MHz	LCH	QPSK	RB1#0	6.9	Pass
				RB6#0	6.10	Pass
			16-QAM	RB1#0	6.11	Pass
				RB5#0	6.12	Pass
		HCH	QPSK	RB1#5	6.13	Pass
				RB6#0	6.14	Pass
			16-QAM	RB1#5	6.15	Pass
				RB5#1	6.16	Pass
	5 MHz	LCH	QPSK	RB1#0	6.17	Pass
				RB6#0	6.18	Pass
			16-QAM	RB1#0	6.19	Pass
				RB5#0	6.20	Pass
		HCH	QPSK	RB1#5	6.21	Pass
				RB6#0	6.22	Pass
			16-QAM	RB1#5	6.23	Pass
				RB5#1	6.24	Pass
	10 MHz	LCH	QPSK	RB1#0	6.25	Pass
				RB6#0	6.26	Pass
			16-QAM	RB1#0	6.27	Pass
				RB5#0	6.28	Pass
		HCH	QPSK	RB1#5	6.29	Pass
				RB6#0	6.30	Pass
			16-QAM	RB1#5	6.31	Pass
				RB5#1	6.32	Pass
	15 MHz	LCH	QPSK	RB1#0	6.33	Pass
				RB6#0	6.34	Pass
			16-QAM	RB1#0	6.35	Pass
				RB5#0	6.36	Pass
		HCH	QPSK	RB1#5	6.37	Pass
				RB6#0	6.38	Pass
			16-QAM	RB1#5	6.39	Pass
				RB5#1	6.40	Pass
	20 MHz	LCH	QPSK	RB1#0	6.41	Pass
				RB6#0	6.42	Pass

Test Band	Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
			16-QAM	RB1#0	6.43	Pass
				RB5#0	6.44	Pass
		HCH	QPSK	RB1#5	6.45	Pass
				RB6#0	6.46	Pass
			16-QAM	RB1#5	6.47	Pass
				RB5#1	6.48	Pass

Test Band	Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
LTE-M1 Band 5	1.4 MHz	LCH	QPSK	RB1#0	7.1	Pass
				RB6#0	7.2	Pass
			16-QAM	RB1#0	7.3	Pass
				RB5#0	7.4	Pass
		HCH	QPSK	RB1#5	7.5	Pass
				RB6#0	7.6	Pass
			16-QAM	RB1#5	7.7	Pass
				RB5#1	7.8	Pass
	3 MHz	LCH	QPSK	RB1#0	7.9	Pass
				RB6#0	7.10	Pass
			16-QAM	RB1#0	7.11	Pass
				RB5#0	7.12	Pass
		HCH	QPSK	RB1#5	7.13	Pass
				RB6#0	7.14	Pass
			16-QAM	RB1#5	7.15	Pass
				RB5#1	7.16	Pass
	5 MHz	LCH	QPSK	RB1#0	7.17	Pass
				RB6#0	7.18	Pass
			16-QAM	RB1#0	7.19	Pass
				RB5#0	7.20	Pass
		HCH	QPSK	RB1#5	7.21	Pass
				RB6#0	7.22	Pass
			16-QAM	RB1#5	7.23	Pass
				RB5#1	7.24	Pass
	10 MHz	LCH	QPSK	RB1#0	7.25	Pass
				RB6#0	7.26	Pass
			16-QAM	RB1#0	7.27	Pass
				RB5#0	7.28	Pass
		HCH	QPSK	RB1#5	7.29	Pass
				RB6#0	7.30	Pass
			16-QAM	RB1#5	7.31	Pass
				RB5#1	7.32	Pass

Test Band	Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
LTE-M1 Band 12	1.4 MHz	LCH	QPSK	RB1#0	8.1	Pass
				RB6#0	8.2	Pass
			16-QAM	RB1#0	8.3	Pass
				RB5#0	8.4	Pass
		HCH	QPSK	RB1#5	8.5	Pass
				RB6#0	8.6	Pass
			16-QAM	RB1#5	8.7	Pass
				RB5#1	8.8	Pass
	3 MHz	LCH	QPSK	RB1#0	8.9	Pass
				RB6#0	8.10	Pass
			16-QAM	RB1#0	8.11	Pass
				RB5#0	8.12	Pass
		HCH	QPSK	RB1#5	8.13	Pass
				RB6#0	8.14	Pass
			16-QAM	RB1#5	8.15	Pass
				RB5#1	8.16	Pass
	5 MHz	LCH	QPSK	RB1#0	8.17	Pass
				RB6#0	8.18	Pass
			16-QAM	RB1#0	8.19	Pass
				RB5#0	8.20	Pass
		HCH	QPSK	RB1#5	8.21	Pass
				RB6#0	8.22	Pass
			16-QAM	RB1#5	8.23	Pass
				RB5#1	8.24	Pass
	10 MHz	LCH	QPSK	RB1#0	8.25	Pass
				RB6#0	8.26	Pass
			16-QAM	RB1#0	8.27	Pass
				RB5#0	8.28	Pass
		HCH	QPSK	RB1#5	8.29	Pass
				RB6#0	8.30	Pass
			16-QAM	RB1#5	8.31	Pass
				RB5#1	8.32	Pass

Test Band	Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
LTE-M1 Band 13	5 MHz	LCH	QPSK	RB1#0	9.1	Pass
				RB6#0	9.2	Pass
			16-QAM	RB1#0	9.3	Pass
				RB5#0	9.4	Pass
		HCH	QPSK	RB1#5	9.5	Pass
				RB6#0	9.6	Pass
			16-QAM	RB1#5	9.7	Pass
				RB5#1	9.8	Pass
	10 MHz	LCH	QPSK	RB1#0	9.9	Pass
				RB6#0	9.10	Pass
			16-QAM	RB1#0	9.11	Pass
				RB5#0	9.12	Pass
		HCH	QPSK	RB1#5	9.13	Pass
				RB6#0	9.14	Pass
			16-QAM	RB1#5	9.15	Pass
				RB5#1	9.16	Pass

Test Band	Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
LTE-M1 Band 25	1.4 MHz	LCH	QPSK	RB1#0	10.1	Pass
				RB6#0	10.2	Pass
			16-QAM	RB1#0	10.3	Pass
				RB5#0	10.4	Pass
		HCH	QPSK	RB1#5	10.5	Pass
				RB6#0	10.6	Pass
			16-QAM	RB1#5	10.7	Pass
				RB5#1	10.8	Pass
	3 MHz	LCH	QPSK	RB1#0	10.9	Pass
				RB6#0	10.10	Pass
			16-QAM	RB1#0	10.11	Pass
				RB5#0	10.12	Pass
		HCH	QPSK	RB1#5	10.13	Pass
				RB6#0	10.14	Pass
			16-QAM	RB1#5	10.15	Pass
				RB5#1	10.16	Pass
	5 MHz	LCH	QPSK	RB1#0	10.17	Pass
				RB6#0	10.18	Pass
			16-QAM	RB1#0	10.19	Pass
				RB5#0	10.20	Pass
		HCH	QPSK	RB1#5	10.21	Pass
				RB6#0	10.22	Pass
			16-QAM	RB1#5	10.23	Pass
				RB5#1	10.24	Pass
	10 MHz	LCH	QPSK	RB1#0	10.25	Pass
				RB6#0	10.26	Pass
			16-QAM	RB1#0	10.27	Pass
				RB5#0	10.28	Pass
		HCH	QPSK	RB1#5	10.29	Pass
				RB6#0	10.30	Pass
			16-QAM	RB1#5	10.31	Pass
				RB5#1	10.32	Pass
	15 MHz	LCH	QPSK	RB1#0	10.33	Pass
				RB6#0	10.34	Pass
			16-QAM	RB1#0	10.35	Pass
				RB5#0	10.36	Pass
		HCH	QPSK	RB1#5	10.37	Pass
				RB6#0	10.38	Pass
			16-QAM	RB1#5	10.39	Pass
				RB5#1	10.40	Pass
	20 MHz	LCH	QPSK	RB1#0	10.41	Pass
				RB6#0	10.42	Pass

Test Band	Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
			16-QAM	RB1#0	10.43	Pass
				RB5#0	10.44	Pass
		HCH	QPSK	RB1#5	10.45	Pass
				RB6#0	10.46	Pass
			16-QAM	RB1#5	10.47	Pass
				RB5#1	10.48	Pass

Test Band	Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
LTE-M1 Band 26 (part22)	1.4 MHz	LCH	QPSK	RB1#0	11.1	Pass
				RB6#0	11.2	Pass
			16-QAM	RB1#0	11.3	Pass
				RB5#0	11.4	Pass
		HCH	QPSK	RB1#5	11.5	Pass
				RB6#0	11.6	Pass
			16-QAM	RB1#5	11.7	Pass
				RB5#1	11.8	Pass
	3 MHz	LCH	QPSK	RB1#0	11.9	Pass
				RB6#0	11.10	Pass
			16-QAM	RB1#0	11.11	Pass
				RB5#0	11.12	Pass
		HCH	QPSK	RB1#5	11.13	Pass
				RB6#0	11.14	Pass
			16-QAM	RB1#5	11.15	Pass
				RB5#1	11.16	Pass
	5 MHz	LCH	QPSK	RB1#0	11.17	Pass
				RB6#0	11.18	Pass
			16-QAM	RB1#0	11.19	Pass
				RB5#0	11.20	Pass
		HCH	QPSK	RB1#5	11.21	Pass
				RB6#0	11.22	Pass
			16-QAM	RB1#5	11.23	Pass
				RB5#1	11.24	Pass
	10 MHz	LCH	QPSK	RB1#0	11.25	Pass
				RB6#0	11.26	Pass
			16-QAM	RB1#0	11.27	Pass
				RB5#0	11.28	Pass
		HCH	QPSK	RB1#5	11.29	Pass
				RB6#0	11.30	Pass
			16-QAM	RB1#5	11.31	Pass
				RB5#1	11.32	Pass
	15 MHz	LCH	QPSK	RB1#0	11.33	Pass
				RB6#0	11.34	Pass
			16-QAM	RB1#0	11.35	Pass
				RB5#0	11.36	Pass
		HCH	QPSK	RB1#5	11.37	Pass
				RB6#0	11.38	Pass
			16-QAM	RB1#5	11.39	Pass
				RB5#1	11.40	Pass

Test Band	Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
LTE-M1 Band 26 (part90)	1.4 MHz	LCH	QPSK	RB1#0	12.1	Pass
				RB6#0	12.2	Pass
			16-QAM	RB1#0	12.3	Pass
				RB5#0	12.4	Pass
		HCH	QPSK	RB1#5	12.5	Pass
				RB6#0	12.6	Pass
			16-QAM	RB1#5	12.7	Pass
				RB5#1	12.8	Pass
	3 MHz	LCH	QPSK	RB1#0	12.9	Pass
				RB6#0	12.10	Pass
			16-QAM	RB1#0	12.11	Pass
				RB5#0	12.12	Pass
		HCH	QPSK	RB1#5	12.13	Pass
				RB6#0	12.14	Pass
			16-QAM	RB1#5	12.15	Pass
				RB5#1	12.16	Pass
	5 MHz	LCH	QPSK	RB1#0	12.17	Pass
				RB6#0	12.18	Pass
			16-QAM	RB1#0	12.19	Pass
				RB5#0	12.20	Pass
		HCH	QPSK	RB1#5	12.21	Pass
				RB6#0	12.22	Pass
			16-QAM	RB1#5	12.23	Pass
				RB5#1	12.24	Pass
	10 MHz	LCH	QPSK	RB1#0	12.25	Pass
				RB6#0	12.26	Pass
			16-QAM	RB1#0	12.27	Pass
				RB5#0	12.28	Pass
		HCH	QPSK	RB1#5	12.29	Pass
				RB6#0	12.30	Pass
			16-QAM	RB1#5	12.31	Pass
				RB5#1	12.32	Pass

Test Band	Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
LTE-M1 Band 66	1.4 MHz	LCH	QPSK	RB1#0	13.1	Pass
				RB6#0	13.2	Pass
			16-QAM	RB1#0	13.3	Pass
				RB5#0	13.4	Pass
		HCH	QPSK	RB1#5	13.5	Pass
				RB6#0	13.6	Pass
			16-QAM	RB1#5	13.7	Pass
				RB5#1	13.8	Pass
	3 MHz	LCH	QPSK	RB1#0	13.9	Pass
				RB6#0	13.10	Pass
			16-QAM	RB1#0	13.11	Pass
				RB5#0	13.12	Pass
		HCH	QPSK	RB1#5	13.13	Pass
				RB6#0	13.14	Pass
			16-QAM	RB1#5	13.15	Pass
				RB5#1	13.16	Pass
	5 MHz	LCH	QPSK	RB1#0	13.17	Pass
				RB6#0	13.18	Pass
			16-QAM	RB1#0	13.19	Pass
				RB5#0	13.20	Pass
		HCH	QPSK	RB1#5	13.21	Pass
				RB6#0	13.22	Pass
			16-QAM	RB1#5	13.23	Pass
				RB5#1	13.24	Pass
	10 MHz	LCH	QPSK	RB1#0	13.25	Pass
				RB6#0	13.26	Pass
			16-QAM	RB1#0	13.27	Pass
				RB5#0	13.28	Pass
		HCH	QPSK	RB1#5	13.29	Pass
				RB6#0	13.30	Pass
			16-QAM	RB1#5	13.31	Pass
				RB5#1	13.32	Pass
	15 MHz	LCH	QPSK	RB1#0	13.33	Pass
				RB6#0	13.34	Pass
			16-QAM	RB1#0	13.35	Pass
				RB5#0	13.36	Pass
		HCH	QPSK	RB1#5	13.37	Pass
				RB6#0	13.38	Pass
			16-QAM	RB1#5	13.39	Pass
				RB5#1	13.40	Pass
	20 MHz	LCH	QPSK	RB1#0	13.41	Pass
				RB6#0	13.42	Pass

Test Band	Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
			16-QAM	RB1#0	13.43	Pass
				RB5#0	13.44	Pass
		HCH	QPSK	RB1#5	13.45	Pass
				RB6#0	13.46	Pass
			16-QAM	RB1#5	13.47	Pass
				RB5#1	13.48	Pass

Test Band	Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
LTE-M1 Band 85	5 MHz	LCH	QPSK	RB1#0	14.1	Pass
				RB6#0	14.2	Pass
			16-QAM	RB1#0	14.3	Pass
				RB5#0	14.4	Pass
		HCH	QPSK	RB1#5	14.5	Pass
				RB6#0	14.6	Pass
			16-QAM	RB1#5	14.7	Pass
				RB5#1	14.8	Pass
	10 MHz	LCH	QPSK	RB1#0	14.9	Pass
				RB6#0	14.10	Pass
			16-QAM	RB1#0	14.11	Pass
				RB5#0	14.12	Pass
		HCH	QPSK	RB1#5	14.13	Pass
				RB6#0	14.14	Pass
			16-QAM	RB1#5	14.15	Pass
				RB5#1	14.16	Pass

Emission Mask						
Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{†Note1}	Verdict
LTE-M1 Band 13	5 MHz	LCH	QPSK	RB1#0	15.1	Pass
				RB6#0	15.2	Pass
			16-QAM	RB1#0	15.3	Pass
				RB5#0	15.4	Pass
		HCH	QPSK	RB1#5	15.5	Pass
				RB6#0	15.6	Pass
			16-QAM	RB1#5	15.7	Pass
				RB5#1	15.8	Pass
	10 MHz	LCH	QPSK	RB1#0	15.9	Pass
				RB6#0	15.10	Pass
			16-QAM	RB1#0	15.11	Pass
				RB5#0	15.12	Pass
		HCH	QPSK	RB1#5	15.13	Pass
				RB6#0	15.14	Pass
			16-QAM	RB1#5	15.15	Pass
				RB5#1	15.16	Pass

NB-IoT Mode Test Data

Test Band	Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
NB-IoT Band 2	3.75kHz	LCH	QPSK	RB1#0	16.1	Pass
			BPSK	RB1#0	16.2	Pass
		HCH	QPSK	RB1#47	16.3	Pass
			BPSK	RB1#47	16.4	Pass
	15kHz	LCH	QPSK	RB1#0	16.5	Pass
				RB12#0	16.6	Pass
			BPSK	RB1#0	16.7	Pass
		HCH	QPSK	RB1#11	16.8	Pass
				RB12#0	16.9	Pass
			BPSK	RB1#11	16.10	Pass
NB-IoT Band 4	3.75kHz	LCH	QPSK	RB1#0	17.1	Pass
			BPSK	RB1#0	17.2	Pass
		HCH	QPSK	RB1#47	17.3	Pass
			BPSK	RB1#47	17.4	Pass
	15kHz	LCH	QPSK	RB1#0	17.5	Pass
				RB12#0	17.6	Pass
			BPSK	RB1#0	17.7	Pass
		HCH	QPSK	RB1#11	17.8	Pass
				RB12#0	17.9	Pass
			BPSK	RB1#11	17.10	Pass
NB-IoT Band 5	3.75kHz	LCH	QPSK	RB1#0	18.1	Pass
			BPSK	RB1#0	18.2	Pass
		HCH	QPSK	RB1#47	18.3	Pass
			BPSK	RB1#47	18.4	Pass
	15kHz	LCH	QPSK	RB1#0	18.5	Pass
				RB12#0	18.6	Pass
			BPSK	RB1#0	18.7	Pass
		HCH	QPSK	RB1#11	18.8	Pass
				RB12#0	18.9	Pass
			BPSK	RB1#11	18.10	Pass
NB-IoT Band 12	3.75kHz	LCH	QPSK	RB1#0	19.1	Pass
			BPSK	RB1#0	19.2	Pass
		HCH	QPSK	RB1#47	19.3	Pass
			BPSK	RB1#47	19.4	Pass
	15kHz	LCH	QPSK	RB1#0	19.5	Pass
				RB12#0	19.6	Pass
			BPSK	RB1#0	19.7	Pass
		HCH	QPSK	RB1#11	19.8	Pass
				RB12#0	19.9	Pass
			BPSK	RB1#11	19.10	Pass
NB-IoT Band 13	3.75kHz	LCH	QPSK	RB1#0	20.1	Pass
			BPSK	RB1#0	20.2	Pass

Test Band	Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
	15kHz	HCH	QPSK	RB1#47	20.3	Pass
			BPSK	RB1#47	20.4	Pass
		LCH	QPSK	RB1#0	20.5	Pass
			BPSK	RB12#0	20.6	Pass
		HCH	QPSK	RB1#0	20.7	Pass
				RB1#11	20.8	Pass
			BPSK	RB12#0	20.9	Pass
				RB1#11	20.10	Pass
NB-IoT Band 25	3.75kHz	LCH	QPSK	RB1#0	21.1	Pass
			BPSK	RB1#0	21.2	Pass
		HCH	QPSK	RB1#47	21.3	Pass
			BPSK	RB1#47	21.4	Pass
	15kHz	LCH	QPSK	RB1#0	21.5	Pass
				RB12#0	21.6	Pass
			BPSK	RB1#0	21.7	Pass
		HCH	QPSK	RB1#11	21.8	Pass
				RB12#0	21.9	Pass
			BPSK	RB1#11	21.10	Pass
NB-IoT Band 66	3.75kHz	LCH	QPSK	RB1#0	22.1	Pass
			BPSK	RB1#0	22.2	Pass
		HCH	QPSK	RB1#47	22.3	Pass
			BPSK	RB1#47	22.4	Pass
	15kHz	LCH	QPSK	RB1#0	22.5	Pass
				RB12#0	22.6	Pass
			BPSK	RB1#0	22.7	Pass
		HCH	QPSK	RB1#11	22.8	Pass
				RB12#0	22.9	Pass
			BPSK	RB1#11	22.10	Pass
NB-IoT Band 85	3.75kHz	LCH	QPSK	RB1#0	23.1	Pass
			BPSK	RB1#0	23.2	Pass
		HCH	QPSK	RB1#47	23.3	Pass
			BPSK	RB1#47	23.4	Pass
	15kHz	LCH	QPSK	RB1#0	23.5	Pass
				RB12#0	23.6	Pass
			BPSK	RB1#0	23.7	Pass
		HCH	QPSK	RB1#11	23.8	Pass
				RB12#0	23.9	Pass
			BPSK	RB1#11	23.10	Pass

Emission Mask						
Test Band	Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{†Note1}	Verdict
NB-IoT Band 13	3.75kHz	LCH	QPSK	RB1#0	24.1	Pass
			BPSK	RB1#0	24.2	Pass
		HCH	QPSK	RB1#47	24.3	Pass
			BPSK	RB1#47	24.4	Pass
	15kHz	LCH	QPSK	RB1#0	24.5	Pass
				RB12#0	24.6	Pass
			BPSK	RB1#0	24.7	Pass
		HCH	QPSK	RB1#11	24.8	Pass
				RB12#0	24.9	Pass
			BPSK	RB1#11	24.10	Pass

A.7 Field Strength of Spurious Radiation

Note 1: GPRS and EGPRS modes have been verified, only the worst data with different transmit bandwidth for LTE are shown here.

Note 2: The frequencies of verdict which are marked by "N/A" should be ignored because they are UE carrier frequency.

Note 3: Test plots please refer to the document "Annex No.: BL-SZ2140097-501 Data Part 5.pdf".

GSM Mode Test Verdict

Test Band	Test Channel	Refer to Plot ^{Note3}	Verdict
GPRS 850	LCH	1.1	Pass
	MCH	1.2	Pass
	HCH	1.3	Pass
GPRS 1900	LCH	2.1	Pass
	MCH	2.2	Pass
	HCH	2.3	Pass
EGPRS 850	LCH	3.1	Pass
	MCH	3.2	Pass
	HCH	3.3	Pass
EGPRS 1900	LCH	4.1	Pass
	MCH	4.2	Pass
	HCH	4.3	Pass

LTE-M1 Mode Test Data

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
LTE-M1 Band 2	1.4 MHz	MCH	QPSK	RB1#0	5.1	Pass
	3 MHz	MCH	QPSK	RB1#0	5.2	Pass
	5 MHz	MCH	QPSK	RB1#0	5.3	Pass
	10 MHz	MCH	QPSK	RB1#0	5.4	Pass
	15 MHz	MCH	QPSK	RB1#0	5.5	Pass
	20 MHz	MCH	QPSK	RB1#0	5.6	Pass
LTE-M1 Band 4	1.4 MHz	MCH	QPSK	RB1#0	6.1	Pass
	3 MHz	MCH	QPSK	RB1#0	6.2	Pass
	5 MHz	MCH	QPSK	RB1#0	6.3	Pass
	10 MHz	MCH	QPSK	RB1#0	6.4	Pass
	15 MHz	MCH	QPSK	RB1#0	6.5	Pass
	20 MHz	MCH	QPSK	RB1#0	6.6	Pass
LTE-M1 Band 5	1.4 MHz	MCH	QPSK	RB1#0	7.1	Pass
	3 MHz	MCH	QPSK	RB1#0	7.2	Pass
	5 MHz	MCH	QPSK	RB1#0	7.3	Pass
	10 MHz	MCH	QPSK	RB1#0	7.4	Pass
LTE-M1 Band 12	1.4 MHz	MCH	QPSK	RB1#0	8.1	Pass
	3 MHz	MCH	QPSK	RB1#0	8.2	Pass
	5 MHz	MCH	QPSK	RB1#0	8.3	Pass
	10 MHz	MCH	QPSK	RB1#0	8.4	Pass
LTE-M1 Band 13	5 MHz	MCH	QPSK	RB1#0	9.1	Pass
	10 MHz	MCH	QPSK	RB1#0	9.2	Pass
LTE-M1 Band 25	1.4 MHz	MCH	QPSK	RB1#0	10.1	Pass
	3 MHz	MCH	QPSK	RB1#0	10.2	Pass
	5 MHz	MCH	QPSK	RB1#0	10.3	Pass
	10 MHz	MCH	QPSK	RB1#0	10.4	Pass
	15 MHz	MCH	QPSK	RB1#0	10.5	Pass
	20 MHz	MCH	QPSK	RB1#0	10.6	Pass
LTE-M1 Band 26 (part22)	1.4 MHz	MCH	QPSK	RB1#0	11.1	Pass
	3 MHz	MCH	QPSK	RB1#0	11.2	Pass
	5 MHz	MCH	QPSK	RB1#0	11.3	Pass
	10 MHz	MCH	QPSK	RB1#0	11.4	Pass
	15 MHz	MCH	QPSK	RB1#0	11.5	Pass
LTE-M1 Band 26 (part90)	1.4 MHz	MCH	QPSK	RB1#0	12.1	Pass
	3 MHz	MCH	QPSK	RB1#0	12.2	Pass
	5 MHz	MCH	QPSK	RB1#0	12.3	Pass
	10 MHz	MCH	QPSK	RB1#0	12.4	Pass
LTE-M1 Band 66	1.4 MHz	MCH	QPSK	RB1#0	13.1	Pass
	3 MHz	MCH	QPSK	RB1#0	13.2	Pass
	5 MHz	MCH	QPSK	RB1#0	13.3	Pass
	10 MHz	MCH	QPSK	RB1#0	13.4	Pass
	15 MHz	MCH	QPSK	RB1#0	13.5	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
	20 MHz	MCH	QPSK	RB1#0	13.6	Pass
LTE-M1 Band 85	5 MHz	MCH	QPSK	RB1#0	14.1	Pass
	10 MHz	MCH	QPSK	RB1#0	14.2	Pass

NB-IoT Mode Test Data


Test Band	Test Sub-carrier spacing	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
NB-IoT Band 2	3.75kHz	MCH	BPSK	RB1#0	15.1	Pass
			QPSK	RB1#0	15.2	Pass
	15kHz	MCH	BPSK	RB1#0	15.3	Pass
			QPSK	RB1#0	15.4	Pass
NB-IoT Band 4	3.75kHz	MCH	BPSK	RB1#0	16.1	Pass
			QPSK	RB1#0	16.2	Pass
	15kHz	MCH	BPSK	RB1#0	16.3	Pass
			QPSK	RB1#0	16.4	Pass
NB-IoT Band 5	3.75kHz	MCH	BPSK	RB1#0	17.1	Pass
			QPSK	RB1#0	17.2	Pass
	15kHz	MCH	BPSK	RB1#0	17.3	Pass
			QPSK	RB1#0	17.4	Pass
NB-IoT Band 12	3.75kHz	MCH	BPSK	RB1#0	18.1	Pass
			QPSK	RB1#0	18.2	Pass
	15kHz	MCH	BPSK	RB1#0	18.3	Pass
			QPSK	RB1#0	18.4	Pass
NB-IoT Band 13	3.75kHz	MCH	BPSK	RB1#0	19.1	Pass
			QPSK	RB1#0	19.2	Pass
	15kHz	MCH	BPSK	RB1#0	19.3	Pass
			QPSK	RB1#0	19.4	Pass
NB-IoT Band 25	3.75kHz	MCH	BPSK	RB1#0	20.1	Pass
			QPSK	RB1#0	20.2	Pass
	15kHz	MCH	BPSK	RB1#0	20.3	Pass
			QPSK	RB1#0	20.4	Pass
NB-IoT Band 66	3.75kHz	MCH	BPSK	RB1#0	21.1	Pass
			QPSK	RB1#0	21.2	Pass
	15kHz	MCH	BPSK	RB1#0	21.3	Pass
			QPSK	RB1#0	21.4	Pass
NB-IoT Band 85	3.75kHz	MCH	BPSK	RB1#0	22.1	Pass
			QPSK	RB1#0	22.2	Pass
	15kHz	MCH	BPSK	RB1#0	22.3	Pass
			QPSK	RB1#0	22.4	Pass

A.8 Receiver Spurious Emissions

Note: Only the worst test results were recorded in this report.

30MHz to 1GHz, ANT H


RE Test case_FCC Part 15B_FCC Part 15B Class B 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	49.982	16.11	-26.65	40.0	-23.89	Peak	177.00	200	Horizontal	Pass
2	82.283	19.09	-30.54	40.0	-20.91	Peak	320.00	200	Horizontal	Pass
3	149.989	24.80	-24.91	43.5	-18.70	Peak	68.00	200	Horizontal	Pass
4	249.996	28.98	-26.21	46.0	-17.02	Peak	360.00	200	Horizontal	Pass
5	399.958	31.08	-21.52	46.0	-14.92	Peak	172.00	100	Horizontal	Pass
6	549.969	31.00	-17.54	46.0	-15.00	Peak	99.00	200	Horizontal	Pass

30MHz to 1GHz, ANT V


RE Test case_FCC Part 15B_FCC Part 15B Class B 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	50.031	22.21	-26.65	40.0	-17.79	Peak	184.00	100	Vertical	Pass
2	58.421	23.65	-27.29	40.0	-16.35	Peak	71.00	100	Vertical	Pass
3	149.989	26.84	-24.91	43.5	-16.66	Peak	172.00	100	Vertical	Pass
4	350.003	30.15	-22.79	46.0	-15.85	Peak	162.00	200	Vertical	Pass
5	549.969	32.48	-17.54	46.0	-13.52	Peak	360.00	200	Vertical	Pass
6	924.583	29.34	-10.70	46.0	-16.66	Peak	162.00	200	Vertical	Pass

1GHz to 18GHz, ANT H


RE Test case_FCC Part 15B_FCC Part 15B Class B 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1472.400	37.20	-14.89	74.0	-36.80	Peak	177.00	100	Horizontal	Pass
1**	1472.400	28.44	-14.89	54.0	-25.56	AV	177.00	100	Horizontal	Pass
2	3019.800	43.66	-6.45	74.0	-30.34	Peak	326.00	100	Horizontal	Pass
2**	3019.800	33.95	-6.45	54.0	-20.05	AV	326.00	100	Horizontal	Pass
3	6170.200	51.17	2.38	74.0	-22.83	Peak	81.00	100	Horizontal	Pass
3**	6170.200	41.57	2.38	54.0	-12.43	AV	81.00	100	Horizontal	Pass
4	8622.075	48.56	18.18	74.0	-25.44	Peak	235.00	100	Horizontal	Pass
4**	8622.075	38.05	18.18	54.0	-15.95	AV	235.00	100	Horizontal	Pass
5	11022.125	49.71	18.92	74.0	-24.29	Peak	287.00	100	Horizontal	Pass
5**	11022.125	38.19	18.92	54.0	-15.81	AV	287.00	100	Horizontal	Pass
6	17285.474	57.20	24.52	74.0	-16.80	Peak	298.00	100	Horizontal	Pass
6**	17285.474	44.63	24.52	54.0	-9.37	AV	298.00	100	Horizontal	Pass

1GHz to 18GHz, ANT V

RE Test case_FCC Part 15B_FCC Part 15B Class B 1GHz-18GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1308.600	36.72	-14.75	74.0	-37.28	Peak	152.00	100	Vertical	Pass
1**	1308.600	28.08	-14.75	54.0	-25.92	AV	152.00	100	Vertical	Pass
2	2867.700	42.49	-7.83	74.0	-31.51	Peak	164.00	100	Vertical	Pass
2**	2867.700	34.54	-7.83	54.0	-19.46	AV	164.00	100	Vertical	Pass
3	6352.600	52.40	2.85	74.0	-21.60	Peak	345.00	100	Vertical	Pass
3**	6352.600	42.25	2.85	54.0	-11.75	AV	345.00	100	Vertical	Pass
4	8054.550	49.35	18.19	74.0	-24.65	Peak	187.00	100	Vertical	Pass
4**	8054.550	40.82	18.19	54.0	-13.18	AV	187.00	100	Vertical	Pass
5	10604.675	50.37	18.54	74.0	-23.63	Peak	165.00	100	Vertical	Pass
5**	10604.675	41.14	18.54	54.0	-12.86	AV	165.00	100	Vertical	Pass
6	17317.761	57.15	24.35	74.0	-16.85	Peak	212.00	100	Vertical	Pass
6**	17317.761	48.87	24.35	54.0	-5.13	AV	212.00	100	Vertical	Pass

A.9 AC Power-line Conducted Emissions

Note: Only the worst test results were recorded in this report.

L Phase


CE Test case_FCC_CE_FCC PART 15B_ Class B



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.150	48.73	10.41	66.00	-17.27	Peak	L	Pass
1**	0.150	29.46	10.41	56.00	-26.54	AV	L	Pass
2	0.174	46.34	10.39	64.77	-18.43	Peak	L	Pass
2**	0.174	27.79	10.39	54.77	-26.98	AV	L	Pass
3	0.210	39.99	10.38	63.21	-23.22	Peak	L	Pass
3**	0.210	27.00	10.38	53.21	-26.21	AV	L	Pass
4	0.504	35.98	10.30	56.00	-20.02	Peak	L	Pass
4**	0.504	23.79	10.30	46.00	-22.21	AV	L	Pass
5	0.652	36.11	10.27	56.00	-19.89	Peak	L	Pass
5**	0.652	24.98	10.27	46.00	-21.02	AV	L	Pass
6	2.686	35.94	10.28	56.00	-20.06	Peak	L	Pass
6**	2.686	23.47	10.28	46.00	-22.53	AV	L	Pass

N Phase

CE Test case_FCC_CE_FCC PART 15B_ Class B



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.150	48.16	10.41	66.00	-17.84	Peak	N	Pass
1**	0.150	29.02	10.41	56.00	-26.98	AV	N	Pass
2	0.174	44.92	10.39	64.77	-19.85	Peak	N	Pass
2**	0.174	28.19	10.39	54.77	-26.58	AV	N	Pass
3	0.194	43.95	10.38	63.86	-19.91	Peak	N	Pass
3**	0.194	26.84	10.38	53.86	-27.02	AV	N	Pass
4	0.232	39.89	10.36	62.38	-22.49	Peak	N	Pass
4**	0.232	26.43	10.36	52.38	-25.95	AV	N	Pass
5	0.944	37.12	10.24	56.00	-18.88	Peak	N	Pass
5**	0.944	23.90	10.24	46.00	-22.10	AV	N	Pass
6	4.484	35.79	10.31	56.00	-20.21	Peak	N	Pass
6**	4.484	24.05	10.31	46.00	-21.95	AV	N	Pass

ANNEX B TEST SETUP PHOTOS

Please refer to the document "BL-SZ2140097-AR.PDF".

ANNEX C EUT EXTERNAL PHOTOS

Please refer to the document "BL-SZ2140097-AW.PDF".

ANNEX D EUT INTERNAL PHOTOS

Please refer to the document "BL-SZ2140097-AI.PDF".

--END OF REPORT--