RF Test Data for Bluetooth LE (Conducted Measurements)

General Description of EUT	
Product Name:	**DVR**
Test Model:	**DVR-FTD4-8**
Sample ID:	**202211-0153-2-2**
Environmental Conditions	
Temperature:	**25℃**
Relative Humidity:	**55%**
Test Voltage:	**DC 5V**
Test Engineer:	**Huang jian ping**
Note: For a more detailed features description, please refer to the report TBR-C-202211-0153-2	

Contents

1. Duty Cycle 3
2. Maximum Conducted Output Power 7
3. -6dB Bandwidth 11
4. Occupied Channel Bandwidth 15
5. Maximum Power Spectral Density Level 19
6. Band Edge 23
7. Conducted RF Spurious Emission 28
8. Restrict Band 35

1. Duty Cycle

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1Mbps	2402	Ant1	42.86	3.68	3.7
NVNT	BLE 1Mbps	2440	Ant1	42.86	3.68	3.7
NVNT	BLE 1Mbps	2480	Ant1	43.55	3.61	3.7
NVNT	BLE 2Mbps	2402	Ant1	25.4	5.95	6.25
NVNT	BLE 2Mbps	2440	Ant1	25.81	5.88	6.25
NVNT	BLE 2Mbps	2480	Ant1	25.4	5.95	6.25

Test Graphs

Duty Cycle NVNT BLE 1Mbps 2402MHz Ant1



Duty Cycle NVNT BLE 1Mbps 2440MHz Ant1



Duty Cycle NVNT BLE 1Mbps 2480MHz Ant1



Duty Cycle NVNT BLE 2Mbps 2402MHz Ant1



Duty Cycle NVNT BLE 2Mbps 2440MHz Ant1



Duty Cycle NVNT BLE 2Mbps 2480MHz Ant1



2. Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	1.634	30	Pass
NVNT	BLE 1Mbps	2440	Ant1	2.19	30	Pass
NVNT	BLE 1Mbps	2480	Ant1	2.666	30	Pass
NVNT	BLE 2Mbps	2402	Ant1	2.034	30	Pass
NVNT	BLE 2Mbps	2440	Ant1	2.379	30	Pass
NVNT	BLE 2Mbps	2480	Ant1	2.919	30	Pass

Test Graphs

Power NVNT BLE 1Mbps 2402MHz Ant1



Power NVNT BLE 1Mbps 2440MHz Ant1



Power NVNT BLE 1Mbps 2480MHz Ant1



Power NVNT BLE 2Mbps 2402MHz Ant1

Power NVNT BLE 2Mbps 2440MHz Ant1



Power NVNT BLE 2Mbps 2480MHz Ant1

3. -6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	0.65	0.5	Pass
NVNT	BLE 1Mbps	2440	Ant1	0.65	0.5	Pass
NVNT	BLE 1Mbps	2480	Ant1	0.67	0.5	Pass
NVNT	BLE 2Mbps	2402	Ant1	1.12	0.5	Pass
NVNT	BLE 2Mbps	2440	Ant1	1.09	0.5	Pass
NVNT	BLE 2Mbps	2480	Ant1	1.12	0.5	Pass

Test Graphs

-6dB Bandwidth NVNT BLE 1Mbps 2402MHz Ant1

-6dB Bandwidth NVNT BLE 1Mbps 2440MHz Ant1



-6dB Bandwidth NVNT BLE 1Mbps 2480MHz Ant1



-6dB Bandwidth NVNT BLE 2Mbps 2402MHz Ant1

-6dB Bandwidth NVNT BLE 2Mbps 2440MHz Ant1

-6dB Bandwidth NVNT BLE 2Mbps 2480MHz Ant1

4. Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE 1Mbps	2402	Ant1	0.961
NVNT	BLE 1Mbps	2440	Ant1	0.958
NVNT	BLE 1Mbps	2480	Ant1	0.975
NVNT	BLE 2Mbps	2402	Ant1	1.971
NVNT	BLE 2Mbps	2440	Ant1	1.96
NVNT	BLE 2Mbps	2480	Ant1	1.963

Test Graphs

OBW NVNT BLE 1Mbps 2402MHz Ant1

OBW NVNT BLE 1Mbps 2440MHz Ant1



OBW NVNT BLE 1Mbps 2480MHz Ant1

OBW NVNT BLE 2Mbps 2402MHz Ant1



OBW NVNT BLE 2Mbps 2440MHz Ant1



OBW NVNT BLE 2Mbps 2480MHz Ant1



5. Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	-12.594	8	Pass
NVNT	BLE 1Mbps	2440	Ant1	-12.108	8	Pass
NVNT	BLE 1Mbps	2480	Ant1	-11.564	8	Pass
NVNT	BLE 2Mbps	2402	Ant1	-14.511	8	Pass
NVNT	BLE 2Mbps	2440	Ant1	-13.976	8	Pass
NVNT	BLE 2Mbps	2480	Ant1	-13.517	8	Pass

Test Graphs

PSD NVNT BLE 1Mbps 2402MHz Ant1



PSD NVNT BLE 1Mbps 2440MHz Ant1



PSD NVNT BLE 1Mbps 2480MHz Ant1



PSD NVNT BLE 2Mbps 2402MHz Ant1



PSD NVNT BLE 2Mbps 2440MHz Ant1



PSD NVNT BLE 2Mbps 2480MHz Ant1



6. Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	-56.88	-20	Pass
NVNT	BLE 1Mbps	2480	Ant1	-57.09	-20	Pass
NVNT	BLE 2Mbps	2402	Ant1	-55.96	-20	Pass
NVNT	BLE 2Mbps	2480	Ant1	-56.75	-20	Pass

Test Graphs

Band Edge NVNT BLE 1Mbps 2402MHz Ant1 Ref



Band Edge NVNT BLE 1Mbps 2402MHz Ant1 Emission



Band Edge NVNT BLE 1Mbps 2480MHz Ant1 Ref



Band Edge NVNT BLE 1Mbps 2480MHz Ant1 Emission



Band Edge NVNT BLE 2Mbps 2402MHz Ant1 Ref



Band Edge NVNT BLE 2Mbps 2402MHz Ant1 Emission



Band Edge NVNT BLE 2Mbps 2480MHz Ant1 Ref



Band Edge NVNT BLE 2Mbps 2480MHz Ant1 Emission



7. Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	-42.1	-20	Pass
NVNT	BLE 1Mbps	2440	Ant1	-42.95	-20	Pass
NVNT	BLE 1Mbps	2480	Ant1	-43.19	-20	Pass
NVNT	BLE 2Mbps	2402	Ant1	-42.86	-20	Pass
NVNT	BLE 2Mbps	2440	Ant1	-42.64	-20	Pass
NVNT	BLE 2Mbps	2480	Ant1	-42.11	-20	Pass

Test Graphs

Tx. Spurious NVNT BLE 1Mbps 2402MHz Ant1 Ref



Tx. Spurious NVNT BLE 1Mbps 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE 1Mbps 2440MHz Ant1 Ref



Tx. Spurious NVNT BLE 1Mbps 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 1Mbps 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 1Mbps 2480MHz Ant1 Emission



Tx. Spurious NVNT BLE 2Mbps 2402MHz Ant1 Ref



Tx. Spurious NVNT BLE 2Mbps 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE 2Mbps 2440MHz Ant1 Ref



Tx. Spurious NVNT BLE 2Mbps 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 2Mbps 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 2Mbps 2480MHz Ant1 Emission



8. Restrict Band

Condition	Mode	Frequency (MHz)	Antenna	Spur Freq (MHz)	Power (dBm)	Gain (dBi)	E (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	2310	-49.2	2	48.06	Peak	74	Pass
NVNT	BLE 1Mbps	2402	Ant1	2310	-56.23	2	41.03	Average	54	Pass
NVNT	BLE 1Mbps	2402	Ant1	2376.336	-44.52	2	52.74	Peak	74	Pass
NVNT	BLE 1Mbps	2402	Ant1	2359.344	-55.29	2	41.97	Average	54	Pass
NVNT	BLE 1Mbps	2402	Ant1	2390	-47.62	2	49.64	Peak	74	Pass
NVNT	BLE 1Mbps	2402	Ant1	2390	-55.79	2	41.47	Average	54	Pass
NVNT	BLE 1Mbps	2480	Ant1	2483.5	-45.57	2	51.69	Peak	74	Pass
NVNT	BLE 1Mbps	2480	Ant1	2483.5	-53.9	2	43.36	Average	54	Pass
NVNT	BLE 1Mbps	2480	Ant1	2487.016	-43.71	2	53.55	Peak	74	Pass
NVNT	BLE 1Mbps	2480	Ant1	2483.752	-53.62	2	43.64	Average	54	Pass
NVNT	BLE 1Mbps	2480	Ant1	2500	-47.44	2	49.82	Peak	74	Pass
NVNT	BLE 1Mbps	2480	Ant1	2500	-55.96	2	41.3	Average	54	Pass
NVNT	BLE 2Mbps	2402	Ant1	2310	-47.02	2	50.24	Peak	74	Pass
NVNT	BLE 2Mbps	2402	Ant1	2310	-55.5	2	41.76	Average	54	Pass
NVNT	BLE 2Mbps	2402	Ant1	2325.936	-44.77	2	52.49	Peak	74	Pass
NVNT	BLE 2Mbps	2402	Ant1	2355.984	-54.68	2	42.58	Average	54	Pass
NVNT	BLE 2Mbps	2402	Ant1	2390	-46.96	2	50.3	Peak	74	Pass
NVNT	BLE 2Mbps	2402	Ant1	2390	-55.75	2	41.51	Average	54	Pass
NVNT	BLE 2Mbps	2480	Ant1	2483.5	-45.7	2	51.56	Peak	74	Pass
NVNT	BLE 2Mbps	2480	Ant1	2483.5	-52.12	2	45.14	Average	54	Pass
NVNT	BLE 2Mbps	2480	Ant1	2483.608	-39.87	2	57.39	Peak	74	Pass
NVNT	BLE 2Mbps	2480	Ant1	2483.512	-52.12	2	45.14	Average	54	Pass
NVNT	BLE 2Mbps	2480	Ant1	2500	-46.44	2	50.82	Peak	74	Pass
NVNT	BLE 2Mbps	2480	Ant1	2500	-55.4	2	41.86	Average	54	Pass

Test Graphs

Restrict Band NVNT BLE 1Mbps 2402MHz Ant1 Peak



Restrict Band NVNT BLE 1Mbps 2402MHz Ant1 Average



Restrict Band NVNT BLE 1Mbps 2480MHz Ant1 Peak



Restrict Band NVNT BLE 1Mbps 2480MHz Ant1 Average

Restrict Band NVNT BLE 2Mbps 2402MHz Ant1 Peak



Restrict Band NVNT BLE 2Mbps 2402MHz Ant1 Average



Restrict Band NVNT BLE 2Mbps 2480MHz Ant1 Peak



Restrict Band NVNT BLE 2Mbps 2480MHz Ant1 Average



-----END OF THE REPORT-----