

RF EXPOSURE TEST REPORT

Application No.: SUCR2608000846AT
Applicant: Aura Home, Inc.
Address of Applicant: 148 Lafayette Street, Floor 5, New York, NY 10013, USA
Manufacturer: Aura Home, Inc.
Address of Manufacturer: 148 Lafayette Street, Floor 5, New York, NY 10013, USA
EUT Description: Digital Photo Frame
Model No.: AF330, AF33X-YYYY (X is an Arabic numeral, representing different sales channels and regions, YYYY are Latin alphabets, representing different colors of product housing enclosure) ♣
Trade Mark: AURA
FCC ID: 2AZGI-AF330
Standards: FCC 47CFR §2.1093
Date of Receipt: 2026-08-28
Date of Test: 2026-09-16 to 2026-09-23
Date of Issue: 2026-09-28

Test Result :	PASS *
----------------------	---------------

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN.Doccheck@sgs.com



Revision Record			
Version	Description	Date	Remark
00	Original	2026/09/28	/

Authorized for issue by:		
Prepared By		Leon Liu
		Leon Liu/ Project Engineer
Approved By		Nick Hu
		Nick Hu/ Reviewer

TEST SUMMARY

Frequency Band	Maximum Reported SAR(W/kg)	
	Body	Extremity
WI-FI (2.4GHz)	1.18	2.02
WI-FI (5GHz)	0.54	0.62
BLE	0.14	0.18
SAR Limited(W/kg)	1.6	4.0

Frequency Band	Maximum Reported Power Density
	(W/m ²)
60 GHz Radar	2.98
PD Limited(W/m ²)	10

Maximum Simultaneous Transmission TER		
Scenario	Body	Extremity
TER	0.74	0.75
Limited	1	

Contents

1	General Information	6
1.1	General Description of EUT	6
1.2	Test Specification	7
1.3	RF exposure limits.....	8
1.4	Test Location	9
1.5	Test Engineer	9
1.6	Test Facility	9
2	Laboratory Environment.....	10
3	SAR Measurements System Configuration	11
3.1	The SAR Measurement System	11
3.2	Isotropic E-field Probe EX3DV4	13
3.3	Data Acquisition Electronics (DAE)	14
3.4	SAM Twin Phantom.....	14
3.5	ELI Phantom.....	15
3.6	Device Holder for Transmitters.....	16
3.7	Measurement Procedure	17
3.7.1	Scanning procedure	17
3.7.2	Data storage	19
3.7.3	Data Evaluation by SEMCAD	19
4	PD Measurements System Configuration	21
4.1	Power density measurement system	21
4.2	EUmmWaVe probe	22
4.3	Data Acquisition Electronics (DAE)	23
4.4	Measurement Procedure	23
5	SAR measurement variability and uncertainty	24
5.1	SAR measurement variability	24
5.2	SAR measurement uncertainty	24
6	PD measurement uncertainty.....	25
7	Description of Test Position.....	27
7.1	Generic device	27
8	SAR System Verification Procedure.....	28
8.1	Tissue Simulate Liquid	28
8.1.1	Recipes for Tissue Simulate Liquid	28
8.1.2	Measurement for Tissue Simulate Liquid	29
8.2	SAR System Check.....	30
8.2.1	Justification for Extended SAR Dipole Calibrations	31
8.2.2	Summary System Check Result(s).....	32
8.2.3	Detailed System Check Results	32
9	PD System Verification Procedure	33
9.1	PD System Check Setting	33
9.2	PD System Check Results	35
9.3	Detailed System Check Results	35
10	Test Configuration	36
10.1	Operation Configurations	36
10.1.1	WIFI Test Configuration.....	36
10.1.2	BLE Test Configuration.....	43
11	Test Result	44
11.1	DUT Antenna Locations (Back View)	44
11.2	Measurement of RF Conducted Power and EIRP Data	45
11.2.1	RF Conducted Power Data of WIFI 2.4G	45
11.2.2	RF Conducted Power Data of WIFI 5G	46

11.2.3	RF Conducted Power Data of BLE	50
11.2.4	EIRP Data of 60 GHz Radar	50
11.3	Measurement of SAR Data	51
11.3.1	SAR Result of WIFI 2.4G	52
11.3.2	SAR Result of WIFI 5G	54
11.3.3	SAR Result of BLE	57
11.4	Measurement of PD Data	58
11.4.1	PD Result	59
11.5	Multiple Transmitter Evaluation	60
11.5.1	Simultaneous SAR test evaluation	60
11.5.2	Total Exposure Ratio	60
12	Equipment list.....	61
13	Calibration certificate.....	62
14	Photographs	62
	Appendix A: Detailed System Check Results	62
	Appendix B: Detailed Test Results	62
	Appendix C: Calibration certificate	62
	Appendix D: Photographs.....	62

1 General Information

1.1 General Description of EUT

Product Name:	Digital Photo Frame	
Model No.:	AF330, AF33X-YYYY (X is an Arabic numeral, representing different sales channels and regions, YYYY are Latin alphabets, representing different colors of product housing enclosure)	
Trade Mark:	AURA	
Product Phase:	production unit	
Device Type:	portable device	
Exposure Category:	uncontrolled environment / general population	
SN:	M16-30000127	
Hardware Version:	V1.1	
Software Version:	133-plus-20260820.010446	
Antenna Type:	FPC antenna	
Device Operating Configurations:		
Test Mode Configuration:	WiFi:DSSS,OFDM; BLE:GFSK; Radar: FMCW	
Frequency Bands:	Band	Tx(MHz)
	WIFI 2.4G	2412~2462
	WIFI 5G	5150~5250
		5250~5350
		5470~5725
		5725~5850
	BLE	2402~2480
	60 GHz Radar	57000-64000
RF Cable:	☒ Provided by applicant ☐ Provided by the laboratory	
Battery Information:	Model:	GSP12600HVPA-1S2P
	Normal Voltage:	3.87V
	Rated capacity:	12600mAh
	Manufacturer:	Guangzhou Great Power Energy & Technology Co, Ltd

Note:

Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, SGS is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.

Declaration of EUT Family Grouping:

Model No.: AF330, AF33X-YYYY (X is an Arabic numeral, representing different sales channels and regions, YYYY are Latin alphabets, representing different colors of product housing enclosure)

Only the model AF330 was tested, since according to the declaration from the applicant, the electrical circuit design, PCB layout, components used, internal wiring and functions were identical for all the above models, with the difference on the model no., SKU naming and colors of enclosure for marketing purpose.

1.2 Test Specification

Identity	Document Title
47 CFR § 2.1093	Radiofrequency Radiation Exposure Evaluation: Portable Devices
ANSI/IEEE C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.
IEEE 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
IEC/IEEE 63195-1:2022	Assessment of power density of human exposure to radio frequency fields from wireless devices in close proximity to the head and body (frequency range of 6 GHz to 300 GHz) – Part 1: Measurement procedure
KDB 248227 D01	SAR Guidance for IEEE 802.11 Wi-Fi SAR v02r02
KDB 447498 D01	General RF Exposure Guidance v06
KDB 865664 D01	SAR Measurement 100 MHz to 6 GHz v01r04
KDB 865664 D02	RF Exposure Reporting v01r02
KDB 690783 D01	SAR Listings on Grants v01r03

1.3 RF exposure limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR* (Brain*Trunk)	1.60 mW/g	8.00 mW/g
Spatial Average SAR** (Whole Body)	0.08 mW/g	0.40 mW/g
Spatial Peak SAR*** (Hands/Feet/Ankle/Wrist)	4.00 mW/g	20.00 mW/g

Notes:

* The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time

** The Spatial Average value of the SAR averaged over the whole body.

*** The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation.)

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Peak Spatially Averaged Power Density was evaluated over a circular area of 4cm² per interim FCC Guidance for near-field power density evaluations per October 2018 TCB Workshop notes.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

Note: 1.0 mW/cm² is equal to 10 W/m²

1.4 Test Location

All tests were performed at:

SGS Tongfang Technical Services (Suzhou) Co., Ltd.

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu)
Pilot Free Trade Zone

No tests were sub-contracted.

1.5 Test Engineer

Test Engineer: Leon Xu

1.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6336.01)**

SGS Tongfang Technical Services (Suzhou) Co., Ltd. is accredited by the American Association for Laboratory Accreditation (A2LA).

- **FCC (Designation Number: CN1312)**

SGS Tongfang Technical Services (Suzhou) Co., Ltd. has been recognized as an accredited testing laboratory. Test Firm Registration Number: 717327

- **ISED (CAB Identifier: CN0120)**

SGS Tongfang Technical Services (Suzhou) Co., Ltd. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

Company Number: 27594

2 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25 °C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

3 SAR Measurements System Configuration

3.1 The SAR Measurement System

This SAR Measurement System uses a Computer-controlled 3-D stepper motor system (SPEAG DASY professional system). A E-field probe is used to determine the internal electric fields. The SAR can be obtained from the equation $SAR = \sigma (|E|^2) / \rho$ where σ and ρ are the conductivity and mass density of the tissue-Simulate.


The DASY system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stabile RX family) with controller, teach pendant and software. An arm extension for accommodation the data acquisition electronics (DAE).

A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.




F-1. SAR Measurement System Configuration

- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows system.
- DASY software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand, right-hand and Body Worn usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing to validating the proper functioning of the system.

3.2 Isotropic E-field Probe EX3DV4

	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available.
Frequency	4 MHz - 10 GHz Linearity: ± 0.2 dB (30 MHz - 10 GHz)
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μ W/g - 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 337 mm (Tip: 9 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 10 GHz with precision of better 30%.
Compatibility	DASY52 SAR and higher, EASY4/MRI

3.3 Data Acquisition Electronics (DAE)

Model	DAE	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV,400mV)	
Input Offset Voltage	< 5μV (with auto zero)	
Input Bias Current	< 50 f A	
Dimensions	60 x 60 x 68 mm	

3.4 SAM Twin Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)	
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions (incl. Wooden Support)	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	
Wooden Support	SPEAG standard phantom table	

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.

Twin SAM V5.0 has the same shell geometry and is manufactured from the same material as Twin SAM V4.0, but has reinforced top structure.

3.5 ELI Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)	
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
Shell Thickness	2.0 ± 0.2 mm(bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	
Wooden Support	SPEAG standard phantom table	

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 4 MHz to 10 GHz. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles. ELI V5.0 has the same shell geometry and is manufactured from the same material as ELI4 but has reinforced top structure.

3.6 Device Holder for Transmitters



F-2. Device Holder for Transmitters

- The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centres for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.
- The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon=3$ and loss tangent $\delta=0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

3.7 Measurement Procedure

3.7.1 Scanning procedure

Step 1: Power reference measurement

The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure.

Step 2: Area scan

The SAR distribution at the exposed side of the head was measured at a distance of 4mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm*15mm or 12mm*12mm or 10mm*10mm. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation.

Step 3: Zoom scan

Around this point, a volume of 32mm*32mm*30mm ($f \leq 2\text{GHz}$), 30mm*30mm*30mm (f for 2-3GHz) and 24mm*24mm*22mm (f for 5-6GHz) was assessed by measuring 5x5x7 points ($f \leq 2\text{GHz}$), 7x7x7 points (f for 2-3GHz) and 7x7x12 points (f for 5-6GHz). On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

The data at the surface was extrapolated, since the centre of the dipoles is 2.0mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. (This can be variable. Refer to the probe specification). The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The volume was integrated with the trapezoidal algorithm. One thousand points were interpolated to calculate the average. All neighbouring volumes were evaluated until no neighboring volume with a higher average value was found.

If the zoom scan measured as specified in the preceding paragraphs complies with both i) and ii), or if the psSAR is below 0,1 W/kg, no additional measurements are needed.

i) The smallest horizontal distance from the local SAR peaks to all points 3 dB below the SAR peak shall be larger than the horizontal grid steps in both x- and y-directions (Δx , Δy). This shall be checked for the measured zoom scan plane conformal to the phantom at the distance zM1. The minimum distance shall be recorded in the SAR test report.

ii) The ratio of the SAR at the second measured point (M2) to the SAR at the closest measured point (M1) at the x-y location of the measured maximum SAR value shall be at least 30 %. This ratio (in %) shall be recorded in the SAR test report.

			$\leq 3 \text{ GHz}$	$> 3 \text{ GHz}$
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			$5 \pm 1 \text{ mm}$	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}			$\leq 2 \text{ GHz: } \leq 15 \text{ mm}$ $2 - 3 \text{ GHz: } \leq 12 \text{ mm}$	$3 - 4 \text{ GHz: } \leq 12 \text{ mm}$ $4 - 6 \text{ GHz: } \leq 10 \text{ mm}$
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			$\leq 2 \text{ GHz: } \leq 8 \text{ mm}$ $2 - 3 \text{ GHz: } \leq 5 \text{ mm}^*$	$3 - 4 \text{ GHz: } \leq 5 \text{ mm}^*$ $4 - 6 \text{ GHz: } \leq 4 \text{ mm}^*$
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		$\leq 5 \text{ mm}$	$3 - 4 \text{ GHz: } \leq 4 \text{ mm}$ $4 - 5 \text{ GHz: } \leq 3 \text{ mm}$ $5 - 6 \text{ GHz: } \leq 2 \text{ mm}$
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	$\leq 4 \text{ mm}$	$3 - 4 \text{ GHz: } \leq 3 \text{ mm}$ $4 - 5 \text{ GHz: } \leq 2.5 \text{ mm}$ $5 - 6 \text{ GHz: } \leq 2 \text{ mm}$
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		$\geq 30 \text{ mm}$	$3 - 4 \text{ GHz: } \geq 28 \text{ mm}$ $4 - 5 \text{ GHz: } \geq 25 \text{ mm}$ $5 - 6 \text{ GHz: } \geq 22 \text{ mm}$

Step 4: Power reference measurement (drift)

The Power Drift Measurement job measures the field at the same location as the most recent power reference measurement job within the same procedure, and with the same settings. The indicated drift is mainly the variation of the DUT's output power and should vary max $\pm 5 \%$.

3.7.2 Data storage

The DASY software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension “DAE”. The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated. The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [m W/g], [m W/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

3.7.3 Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Normi, ai0, ai1, ai2
- Conversion factor	ConvFi	
- Diode compression point	Dcpi	
Device parameters:	- Frequency	f
- Crest factor	cf	
Media parameters:	- Conductivity	ε
- Density	ρ	

These parameters must be set correctly in the software. They can be found in the component documents, or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot cf / dcpi$$

With V_i = compensated signal of channel I (I = x, y, z)

U_i = input signal of channel I (I = x, y, z)

cf = crest factor of exciting field (DASY parameter)

dcpi = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:

$$E_i = (V_i / Norm_i \cdot ConvF)^{1/2}$$

H-field probes:

$$H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1}f + a_{i2}f^2) / f$$

With V_i = compensated signal of channel i ($i = x, y, z$)

$Norm_i$ = sensor sensitivity of channel i ($i = x, y, z$)

[mV/(V/m)²] for E-field Probes

$ConvF$ = sensitivity enhancement in solution

a_{ij} = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E_i = electric field strength of channel i in V/m

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{tot}^2 \cdot \sigma) / (\epsilon \cdot 1000)$$

with SAR = local specific absorption rate in mW/g

E_{tot} = total field strength in V/m

σ = conductivity in [mho/m] or [Siemens/m]

ϵ = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = E_{tot}^2 / 3770 \text{ or } P_{pwe} = H_{tot}^2 \cdot 37.7$$

with P_{pwe} = equivalent power density of a plane wave in mW/cm²


E_{tot} = total electric field strength in V/m

H_{tot} = total magnetic field strength in A/m

4 PD Measurements System Configuration


4.1 Power density measurement system

Power density measurements for mmWave frequencies were performed using SPEAG DASY8 or Higher with mmWave module. The system included a high precision robotics system (Staubli), robot controller, desktop computer, near-field probe, probe alignment sensor, and the mmWave phantom cover.



4.2 EUmmWaVe probe

Frequency	750 MHz – 110 GHz
Probe Overall Length	320 mm
Probe Body Diameter	8.0 mm
Tip Length	23.0 mm
Tip Diameter	8.0 mm
Probe's two dipoles length	0.9 mm – Diode loaded
Dynamic Range	< 20 V/m - 10000 V/m with PRE-10 (min < 50 V/m - 3000 V/m)
Position Precision	< 0.2 mm
Distance between diode sensors and probe's tip	1.5 mm
Minimum Mechanical separation between probe tip and a Surface	0.5 mm
Applications	E-field measurements of 5G devices and other mm-wave transmitters operating above 10GHz in < 2 mm distance from device (free-space) Power density, H-field and far-field analysis using total field reconstruction.
Compatibility	cDASY8 + 5G-Module SW1.0 and higher



The EUmmWaVe probe is based on the pseudo-vector probe design, which not only measures the field magnitude but also derives its polarization ellipse. The design entails two small 0.8mm dipole sensors mechanically protected by high-density foam, printed on both sides of a 0.9mm wide and 0.12mm thick glass substrate. The body of the probe is specifically constructed to minimize distortion by the scattered fields. The probe consists of two sensors with different angles (1 and 2) arranged in the same plane in the probe axis. Three or more measurements of the two sensors are taken for different probe rotational angles to derive the amplitude and polarization information. The probe design allows measurements at distances as small as 2mm from the sensors to the surface of the device under test (DUT). The typical sensor to probe tip distance is 1.5 mm. The exact distance is calibrated.

4.3 Data Acquisition Electronics (DAE)

Model	DAE	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV,400mV)	
Input Offset Voltage	< 5μV (with auto zero)	
Input Bias Current	< 50 f A	
Dimensions	60 x 60 x 68 mm	

4.4 Measurement Procedure

Fine-resolution scans on 2 different planes are performed to reconstruct the E- and H-fields as well as the power density; the z-distance between the 2 planes is set to $\lambda/4$. The (x, y) grid step is also set $\lambda/4$, the grid extent is set to sufficiently large to identify the field pattern and the peak.

5 SAR measurement variability and uncertainty

5.1 SAR measurement variability

Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.

2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.

3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).

4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

5.2 SAR measurement uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

6 PD measurement uncertainty

Declaration of Conformity:

The test results with all measurement uncertainty excluded is presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience and knowledge of the behavior and properties of relevant materials and instruments, manufacturer's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in table below.

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multi plying Factor ^(a)	1/k ^(b)	1/√3	1/√6	1/√2

Standard Uncertainty for Assumed Distribution

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) k is the coverage factor

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.


Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. The judgment of conformity in the report is based on the measurement results excluding the measurement uncertainty.

a	b	c	d	e	f=b*e/d	g
Error Description	Uncertainty Value (±dB)	Probability	Div.	Ci	Standard Uncertainty (±dB)	Vi (Veff)
Probe Calibration	0.49	N	1	1	0.49	∞
Probe correction	0.00	R	1.732	1	0.00	∞
Frequency response (BW ≤1 GHz)	0.20	R	1.732	1	0.12	∞
Sensor cross coupling	0.00	R	1.732	1	0.00	∞
Isotropy	0.50	R	1.732	1	0.29	∞
Linearity	0.20	R	1.732	1	0.12	∞
Probe scattering	0.00	R	1.732	1	0.00	∞
Probe positioning offset	0.30	R	1.732	1	0.17	∞
Probe positioning repeatability	0.04	R	1.732	1	0.02	∞
Sensor mechanical offset	0.00	R	1.732	1	0.00	∞
Probe spatial resolution	0.00	R	1.732	1	0.00	∞
Field impedance dependance	0.00	R	1.732	1	0.00	∞
Amplitude and phase drift	0.00	R	1.732	1	0.00	∞
Amplitude and phase noise	0.04	R	1.732	1	0.02	∞
Measurement area truncation	0.00	R	1.732	1	0.00	∞
Data acquisition	0.03	N	1	1	0.03	∞
Sampling	0.00	R	1.732	1	0.00	∞
Field reconstruction	2.00	R	1.732	1	1.15	∞
Forward transformation	0.00	R	1.732	1	0.00	∞
Power density scaling	0.00	R	1.732	1	0.00	∞
Spatial averaging	0.10	R	1.732	1	0.06	∞
System detection limit	0.04	R	1.732	1	0.02	∞
Probe coupling with DUT	0.00	R	1.732	1	0.00	∞
Modulation response	0.40	R	1.732	1	0.23	∞
Integration time	0.00	R	1.732	1	0.00	∞
Response time	0.00	R	1.732	1	0.00	∞
Device holder influence	0.10	R	1.732	1	0.06	∞
DUT alignment	0.00	R	1.732	1	0.00	∞
RF ambient conditions	0.04	R	1.732	1	0.02	∞
Ambient reflections	0.04	R	1.732	1	0.02	∞
Immunity / secondary reception	0.00	R	1.732	1	0.00	∞
Drift of the DUT		R	1.732	1	0.00	∞
Combined Std. Uncertainty					1.33	
Expanded STD Uncertainty (95%), K=2					2.67	

7 Description of Test Position

7.1 Generic device

The SAR evaluation shall be performed for all surfaces of the DUT that are accessible during intended use, as indicated in the below Figure. The separation distance in testing shall correspond to the intended use distance as specified in the user instructions provided by the manufacturer. If the intended use is not specified, all surfaces of the DUT shall be tested directly against the flat phantom. The surface of the generic device (or the surface of the carry accessory holding the DUT) pointing towards the flat phantom shall be parallel to the surface of the phantom.



a) Test positions for a generic device

8 SAR System Verification Procedure

8.1 Tissue Simulate Liquid

8.1.1 Recipes for Tissue Simulate Liquid

The following tables give the recipes for tissue simulating liquids to be used in different frequency bands:

Ingredients (% by weight)	Frequency (MHz)				
	450	700-1000	1700-2000	2300-2500	2500-2700
Water	38.56	40.30	55.24	55.00	54.92
Salt (NaCl)	3.95	1.38	0.31	0.2	0.23
Sucrose	56.32	57.90	0	0	0
HEC	0.98	0.24	0	0	0
Bactericide	0.19	0.18	0	0	0
Tween	0	0	44.45	44.80	44.85
Salt: 99+% Pure Sodium Chloride Water: De-ionized, 16 MΩ+ resistivity Tween: Polyoxyethylene (20) sorbitan monolaurate Sucrose: 98+% Pure Sucrose HEC: Hydroxyethyl Cellulose					
1. Head Tissue Simulate Liquid (HBBL600-10000V6) is composed of the following ingredients : (Manufactured by SPEAG) Water: 50-65% Mineral oil: 10-30% Emulsifiers: 8-25% Sodium salt: 0-1.5%					

Table 1 : Recipe of Tissue Simulate Liquid

8.1.2 Measurement for Tissue Simulate Liquid

The Conductivity (σ) and Permittivity (ϵ_r) are listed in Table 2. For the SAR measurement given in this report.


The temperature variation of the Tissue Simulate Liquids was $22 \pm 2^\circ\text{C}$.

Measurement for Tissue Simulate Liquid for System check									
Tissue Type	Measured Frequency (MHz)	Measured Tissue		Target Tissue ($\pm 5\%$)		Deviation (Within $\pm 5\%$)		Liquid Temp. ($^\circ\text{C}$)	Test Date
		ϵ_r	$\sigma(\text{S/m})$	ϵ_r	$\sigma(\text{S/m})$	ϵ_r	$\sigma(\text{S/m})$		
2450 Head	2450	39.124	1.776	39.20	1.80	-0.19%	-1.33%	22.3	2026/9/18
5250 Head	5250	36.555	4.774	35.90	4.71	1.82%	1.36%	22.2	2026/9/23
5600 Head	5600	36.281	5.103	35.50	5.07	2.20%	0.65%	22.2	2026/9/23
5750 Head	5750	36.217	5.297	35.40	5.22	2.31%	1.48%	22.2	2026/9/23

Table 2 : Measurement result of Tissue electric parameters

8.2 SAR System Check

The microwave circuit arrangement for system Check is sketched in F-12. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within $\pm 10\%$ from the target SAR values. The tests were conducted on the same days as the measurement of the EUT. The obtained results from the system accuracy verification are displayed in the following table (A power level of 250mW (below 3GHz) or 100mW (3-6GHz) was input to the dipole antenna). During the tests, the ambient temperature of the laboratory was in the range $22\pm 2^{\circ}\text{C}$, the relative humidity was in the range 60% and the liquid depth above the ear reference points was above 15 ± 0.5 cm in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.



F-12.The microwave circuit arrangement used for SAR system Check

8.2.1 Justification for Extended SAR Dipole Calibrations

1) Instead of the typical annual calibration recommended by measurement standards, longer calibration intervals of up to three years may be considered when it is demonstrated that the SAR target, impedance and return loss of a dipole have remain stable according to the following requirements. Each measured dipole is expected to evaluate with the following criteria at least on annual interval in Appendix C.

- a) There is no physical damage on the dipole;
- b) System check with specific dipole is within 10% of calibrated value;
- c) Return-loss is within 20% of calibrated measurement;
- d) Impedance is within 5Ω from the previous measurement.

2) Network analyzer probe calibration against air, distilled water and a shorting block performed before measuring liquid parameters.

8.2.2 Summary System Check Result(s)

Validation Kit	Measured SAR 250mW	Measured SAR 250mW	Measured SAR (normalized to 1W)	Measured SAR (normalized to 1W)	Target SAR (normalized to 1W)	Target SAR (normalized to 1W)	Deviation (Within $\pm 10\%$)		Liquid Temp. ($^{\circ}\text{C}$)	Test Date
	1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)	1-g(W/kg)	10- g(W/kg)		
D2450V2_Head	13.50	6.17	54.00	24.68	51.90	24.50	4.05%	0.73%	22.3	2026/9/18
Validation Kit	Measured SAR 100mW	Measured SAR 100mW	Measured SAR (normalized to 1W)	Measured SAR (normalized to 1W)	Target SAR (normalized to 1W)	Target SAR (normalized to 1W)	Deviation (Within $\pm 10\%$)		Liquid Temp. ($^{\circ}\text{C}$)	Test Date
	1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)	1-g(W/kg)	10- g(W/kg)		
D5GHzV2_5.25G_Head	7.78	2.15	77.80	21.50	79.00	21.80	-1.52%	-1.38%	22.2	2026/9/23
D5GHzV2_5.6G_Head	7.88	2.09	78.80	20.90	81.60	22.50	-3.43%	-7.11%	22.2	2026/9/23
D5GHzV2_5.75G_Head	7.74	2.12	77.40	21.20	78.30	21.30	-1.15%	-0.47%	22.2	2026/9/23

Table 3 : SAR System Check Result

8.2.3 Detailed System Check Results

Please see the Appendix A

9 PD System Verification Procedure


9.1 PD System Check Setting


The system was verified to be within ± 0.66 dB of the power density targets on the calibration certificate according to the test system specification in the user's manual and calibration facility recommendation. The 0.66 dB deviation threshold represents the expanded uncertainty for system performance checks using SPEAG's mmWave verification sources. The same spatial resolution and measurement region used in the source calibration was applied during the system check.

The measured power density distribution of verification source was also confirmed through visual inspection to have no noticeable differences, both spatially (shape) and numerically (level) from the distribution provided by the manufacturer, per November 2017 TCBC Workshop Notes.

Settings for measurement of verification sources

Frequency [GHz]	Grid step	Grid extent X/Y [mm]	Measurement points
10	$0.25 \left(\frac{\lambda}{4}\right)$	120/120	16×16
30	$0.25 \left(\frac{\lambda}{4}\right)$	60/60	24×24
60	$0.25 \left(\frac{\lambda}{4}\right)$	32.5/32.5	26×26
90	$0.25 \left(\frac{\lambda}{4}\right)$	30/30	36×36





System Verification Setup Photo

9.2 PD System Check Results

PD System Validation Result(s)				
Frequent	Measured PD W/m ²	Target PD W/m ²	Circular Deviation (Within ±0.66dB)	Test Date
	4cm ²	4cm ²	4cm ²	
60 GHz Source	75.8	77.8	-0.11	2026/9/16

9.3 Detailed System Check Results

Please see the Appendix A

10 Test Configuration

10.1 Operation Configurations


10.1.1 WIFI Test Configuration

A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement.

10.1.1.1 Duty cycle


1) Wi-Fi 2.4GHz 802.11b:

Duty cycle=98.82%



2) Wi-Fi 5GHz 802.11a:

Duty cycle=93.16%



10.1.1.2 Initial Test Position SAR Test Reduction Procedure

DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures. The initial test position procedure is described in the following:

- 1) . When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other (remaining) test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band. SAR is also not required for that exposure configuration in the subsequent test configuration(s).
- 2) . When the reported SAR of the initial test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest extrapolated or estimated 1-g SAR conditions determined by area scans or next closest/smallest test separation distance and maximum RF coupling test positions based on manufacturer justification, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg or all required test positions (left, right, touch, tilt or subsequent surfaces and edges) are tested.
- 3) . For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested. a) Additional power measurements may be required for this step, which should be limited to those necessary for identifying the subsequent highest output power channels.

10.1.1.3 Subsequent Test Configuration Procedures

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. The initial test position procedure is applied to next to the ear, UMPC mini-tablet and hotspot mode configurations. When the same maximum output power is specified for multiple transmission modes, additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. The subsequent test configuration and SAR measurement procedures are described in the following.

- 1) . When SAR test exclusion provisions of KDB Publication 447498 are applicable and SAR measurement is not required for the initial test configuration, SAR is also not required for the next highest maximum output power transmission mode subsequent test configuration(s) in that frequency band or aggregated band and exposure configuration.
- 2) . When the highest reported SAR for the initial test configuration (when applicable, include subsequent highest output channels), according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.
- 3) . The number of channels in the initial test configuration and subsequent test configuration can be different due to differences in channel bandwidth. When SAR measurement is required for a subsequent test configuration and the channel bandwidth is smaller than that in the initial test configuration, all channels in the subsequent test configuration that overlap with the larger bandwidth channel tested in the initial test configuration should be used to determine the highest maximum output power channel. This step requires additional power measurement to identify the highest maximum output power channel in the subsequent test configuration to determine SAR test reduction.
 - a) SAR should first be measured for the channel with highest measured output power in the subsequent test configuration.
 - b) SAR for subsequent highest measured maximum output power channels in the subsequent test configuration is required only when the reported SAR of the preceding higher maximum output power channel(s) in the subsequent test configuration is > 1.2 W/kg or until all required channels are tested. i) For channels with the same measured maximum output power, SAR should be measured using the channel closest to the center frequency of the larger channel bandwidth channel in the initial test configuration.
- 4) . SAR measurements for the remaining highest specified maximum output power OFDM transmission mode configurations that have not been tested in the initial test configuration (highest maximum output) or subsequent test configuration(s) (subsequent next highest maximum output power) is determined by recursively applying the subsequent test configuration procedures in this section to the remaining configurations according to the following:
 - a) replace “subsequent test configuration” with “next subsequent test configuration” (i.e., subsequent next highest specified maximum output power configuration)
 - b) replace “initial test configuration” with “all tested higher output power configurations”

10.1.1.4 2.4 GHz WiFi SAR Procedures

Separate SAR procedures are applied to DSSS and OFDM configurations in the 2.4 GHz band to simplify DSSS test requirements. For 802.11b DSSS SAR measurements, DSSS SAR procedure applies to fixed exposure test position and initial test position procedure applies to multiple exposure test positions. When SAR measurement is required for an OFDM configuration, the initial test configuration, subsequent test configuration and initial test position procedures are applied. The SAR test exclusion requirements for 802.11g/n OFDM configurations are described in following.

- **802.11b DSSS SAR Test Requirements**

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) . When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) . When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

- **2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements**

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (section 5.3, including sub-sections). SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) . When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) . When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

- **SAR Test Requirements for OFDM configurations**

When SAR measurement is required for 802.11 g/n OFDM configurations, each standalone and frequency aggregated band is considered separately for SAR test reduction. In applying the initial test configuration and subsequent test configuration procedures, the 802.11 transmission configuration with the highest specified maximum output power and the channel within a test configuration with the highest measured maximum output power should be clearly distinguished to apply the procedures.

10.1.1.5 5 GHz WiFi SAR Procedures

- **U-NII-1 and U-NII-2A Bands**

For devices that operate in only one of the U-NII-1 and U-NII-2A bands, the normally required SAR procedures for OFDM configurations are applied. For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following:

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, both bands are tested independently for SAR.
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, both bands are tested independently for SAR.
- 3) The two U-NII bands may be aggregated to support a 160 MHz channel on channel number 50. Without additional testing, the maximum output power for this is limited to the lower of the maximum output power certified for the two bands. When SAR measurement is required for at least one of the bands and the highest reported SAR adjusted by the ratio of specified maximum output power of aggregated to standalone band is > 1.2 W/kg, SAR is required for the 160 MHz channel. This procedure does not apply to an aggregated band with maximum output higher than the standalone band(s); the aggregated band must be tested independently for SAR. SAR is not required when the 160 MHz channel is operating at a reduced maximum power and also qualifies for SAR test exclusion.

- **U-NII-2C and U-NII-3 Bands**

The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. when Terminal Doppler Weather Radar (TDWR) restriction applies, all channels that operate at 5.60 – 5.65 GHz must be included to apply the SAR test reduction and measurement procedures.

When the same transmitter and antenna(s) are used for U-NII-2C band and U-NII-3 band or 5.8 GHz band of §15.247, the bands may be aggregated to enable additional channels with 20, 40 or 80 MHz bandwidth to span across the band gap, as illustrated in Appendix B. The maximum output power for the additional band gap channels is limited to the lower of those certified for the bands. Unless band gap channels are permanently disabled, they must be considered for SAR testing. The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. To maintain SAR measurement accuracy and to facilitate test reduction, the channels in U-NII-2C band above 5.65 GHz may be grouped with the 5.8 GHz channels in U-NII-3 or §15.247 band to enable two SAR probe calibration frequency points to cover the bands, including the band gap channels. When band gap channels are supported and the bands are not aggregated for SAR testing, band gap channels must be considered independently in each band according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

OFDM Transmission Mode SAR Test Configuration and Channel Selection Requirements

The initial test configuration for 5 GHz OFDM transmission modes is determined by the 802.11 configuration with the highest maximum output power specified for production units, including tune-up tolerance, in each standalone and aggregated frequency band. SAR for the initial test configuration is measured using the highest maximum output power channel determined by the default power measurement procedures. When multiple configurations in a frequency band have the same specified maximum output power, the initial test configuration is determined according to the following steps applied sequentially.

- 1) The largest channel bandwidth configuration is selected among the multiple configurations with the same specified maximum output power.
- 2) If multiple configurations have the same specified maximum output power and largest channel bandwidth, the lowest order modulation among the largest channel bandwidth configurations is selected.
- 3) If multiple configurations have the same specified maximum output power, largest channel bandwidth and lowest order modulation, the lowest data rate configuration among these configurations is selected.
- 4) When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n. After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following. These channel selection procedures apply to both the initial test configuration and subsequent test configuration(s), with respect to the default power measurement procedures or additional power measurements required for further SAR test reduction. The same procedures also apply to subsequent highest output power channel(s) selection.
 - a) The channel closest to mid-band frequency is selected for SAR measurement.
 - b) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.


• SAR Test Requirements for OFDM configurations

When SAR measurement is required for 802.11 a/n/ac OFDM configurations, each standalone and frequency aggregated band is considered separately for SAR test reduction. When the same transmitter and antenna(s) are used for U-NII-1 and U-NII-2A bands, additional SAR test reduction applies. When band gap channels between U-NII-2C band and 5.8 GHz U-NII-3 or §15.247 band are supported, the highest maximum output power transmission mode configuration and maximum output power channel across the bands must be used to determine SAR test reduction, according to the initial test configuration and subsequent test configuration requirements. In applying the initial test configuration and subsequent test configuration procedures, the 802.11 transmission configuration with the highest specified maximum output power and the channel within a test configuration with the highest measured maximum output power should be clearly distinguished to apply the procedures.

10.1.2 BLE Test Configuration

For the BLE SAR tests, a communication link is set up with the test mode software for BLE mode test. The EUT transmitted data into packets and transmit the packets respectively through 40 designated BLE channels, the EUT is operated at the RF continuous emission mode.

BLE 1M Duty Cycle=63.36%





Report No.: SUCR260800084601

Page: 44 of 62

11 Test Result

11.1 DUT Antenna Locations (Back View)

The DUT Antenna Locations can be referred to Appendix D

11.2 Measurement of RF Conducted Power and EIRP Data

11.2.1 RF Conducted Power Data of WIFI 2.4G

WIFI 2.4G Ant1					
Mode	Channel	Frequency(MHz)	Data Rate	Average Power (dBm)	Tune up
802.11b	1	2412	1Mbps	19.29	19.50
	6	2437		19.19	19.50
	11	2462		19.10	19.50
802.11g	1	2412	6Mbps	16.52	17.00
	6	2437		16.59	17.00
	11	2462		16.38	17.00
802.11n HT20	1	2412	6.5Mbps	16.44	17.00
	6	2437		16.51	17.00
	11	2462		16.69	17.00

WIFI 2.4G Ant2					
Mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11b	1	2412	1Mbps	19.15	19.50
	6	2437		19.21	19.50
	11	2462		19.37	19.50
802.11g	1	2412	6Mbps	16.21	17.00
	6	2437		16.46	17.00
	11	2462		16.49	17.00
802.11n HT20	1	2412	6.5Mbps	16.49	17.00
	6	2437		16.23	17.00
	11	2462		16.46	17.00

11.2.2 RF Conducted Power Data of WIFI 5G

WIFI 5G Ant1						
5GHz		Channel	Frequency(MHz)	Data Rate	Average Power (dBm)	Tune up
5GHz U-NII-1	802.11a	36	5180	6Mbps	12.52	13.00
		40	5200	6Mbps	12.08	13.00
		44	5220	6Mbps	12.42	13.00
		48	5240	6Mbps	12.66	13.00
	802.11n HT20	36	5180	MCS0	12.10	13.00
		40	5200	MCS0	12.58	13.00
		44	5220	MCS0	12.30	13.00
		48	5240	MCS0	12.39	13.00
	802.11ac VHT20	36	5180	MCS0	12.45	13.00
		40	5200	MCS0	12.77	13.00
		44	5220	MCS0	12.24	13.00
		48	5240	MCS0	12.36	13.00
5GHz U-NII-2A	802.11a	52	5260	6Mbps	15.00	16.00
		56	5280	6Mbps	15.24	16.00
		60	5300	6Mbps	15.32	16.00
		64	5320	6Mbps	15.89	16.00
	802.11n HT20	52	5260	MCS0	14.81	16.00
		56	5280	MCS0	15.36	16.00
		60	5300	MCS0	15.47	16.00
		64	5320	MCS0	15.71	16.00
	802.11ac VHT20	52	5260	MCS0	12.45	14.00
		56	5280	MCS0	12.79	14.00
		60	5300	MCS0	12.85	14.00
		64	5320	MCS0	13.19	14.00
5GHz UNII-2C	802.11a	100	5500	6Mbps	14.98	16.00
		104	5520	6Mbps	14.90	16.00
		108	5540	6Mbps	14.82	16.00
		112	5560	6Mbps	14.65	16.00
		116	5580	6Mbps	14.70	16.00
		120	5600	6Mbps	14.61	16.00
		124	5620	6Mbps	14.63	16.00
		128	5640	6Mbps	14.66	16.00
		132	5660	6Mbps	14.92	16.00
		136	5680	6Mbps	14.96	16.00
		140	5700	6Mbps	15.05	16.00
		144	5720	6Mbps	15.00	16.00
	802.11n HT20	100	5500	MCS0	14.99	16.00
		104	5520	MCS0	14.92	16.00
		108	5540	MCS0	14.95	16.00
		112	5560	MCS0	15.00	16.00
		116	5580	MCS0	15.08	16.00
		120	5600	MCS0	14.96	16.00
		124	5620	MCS0	15.00	16.00

		128	5640	MCS0	14.92	16.00
		132	5660	MCS0	14.88	16.00
		136	5680	MCS0	14.86	16.00
		140	5700	MCS0	14.95	16.00
		144	5720	MCS0	15.09	16.00
	802.11ac VHT20	100	5500	MCS0	12.46	14.00
		104	5520	MCS0	12.42	14.00
		108	5540	MCS0	12.40	14.00
		112	5560	MCS0	12.35	14.00
		116	5580	MCS0	12.05	14.00
		120	5600	MCS0	12.10	14.00
		124	5620	MCS0	12.03	14.00
		128	5640	MCS0	12.32	14.00
		132	5660	MCS0	12.42	14.00
		136	5680	MCS0	12.50	14.00
		140	5700	MCS0	12.60	14.00
		144	5720	MCS0	12.56	14.00
5GHz UNII-3	802.11a	149	5745	6Mbps	14.92	16.00
		153	5765	6Mbps	14.51	16.00
		157	5785	6Mbps	14.56	16.00
		161	5805	6Mbps	14.46	16.00
		165	5825	6Mbps	14.61	16.00
	802.11n HT20	149	5745	MCS0	15.01	16.00
		153	5765	MCS0	14.78	16.00
		157	5785	MCS0	14.86	16.00
		161	5805	MCS0	14.67	16.00
		165	5825	MCS0	14.70	16.00
	802.11ac VHT20	149	5745	MCS0	12.55	14.00
		153	5765	MCS0	12.30	14.00
		157	5785	MCS0	12.35	14.00
		161	5805	MCS0	12.23	14.00
		165	5825	MCS0	12.27	14.00

WIFI 5G Ant2						
5GHz		Channel	Frequency(MHz)	Data Rate	Average Power (dBm)	Tune up
5GHz U-NII-1	802.11a	36	5180	6Mbps	12.02	13.00
		40	5200	6Mbps	11.68	13.00
		44	5220	6Mbps	12.20	13.00
		48	5240	6Mbps	12.26	13.00
	802.11n HT20	36	5180	MCS0	11.89	13.00
		40	5200	MCS0	12.35	13.00
		44	5220	MCS0	12.16	13.00
		48	5240	MCS0	12.24	13.00
	802.11ac VHT20	36	5180	MCS0	12.07	13.00
		40	5200	MCS0	12.41	13.00
		44	5220	MCS0	12.24	13.00
		48	5240	MCS0	12.30	13.00

5GHz U-NII-2A	802.11a	52	5260	6Mbps	14.91	16.00
		56	5280	6Mbps	14.85	16.00
		60	5300	6Mbps	15.60	16.00
		64	5320	6Mbps	15.71	16.00
	802.11n HT20	52	5260	MCS0	14.77	16.00
		56	5280	MCS0	14.72	16.00
		60	5300	MCS0	15.30	16.00
		64	5320	MCS0	15.77	16.00
	802.11ac VHT20	52	5260	MCS0	12.27	13.50
		56	5280	MCS0	12.24	13.50
		60	5300	MCS0	12.69	13.50
		64	5320	MCS0	13.08	13.50
5GHz UNII-2C	802.11a	100	5500	6Mbps	14.86	16.00
		104	5520	6Mbps	14.75	16.00
		108	5540	6Mbps	14.80	16.00
		112	5560	6Mbps	14.53	16.00
		116	5580	6Mbps	14.46	16.00
		120	5600	6Mbps	14.42	16.00
		124	5620	6Mbps	14.62	16.00
		128	5640	6Mbps	14.88	16.00
		132	5660	6Mbps	14.92	16.00
		136	5680	6Mbps	15.00	16.00
		140	5700	6Mbps	15.45	16.00
		144	5720	6Mbps	15.57	16.00
	802.11n HT20	100	5500	MCS0	14.82	16.00
		104	5520	MCS0	14.80	16.00
		108	5540	MCS0	14.68	16.00
		112	5560	MCS0	14.69	16.00
		116	5580	MCS0	14.70	16.00
		120	5600	MCS0	14.65	16.00
		124	5620	MCS0	14.82	16.00
		128	5640	MCS0	14.80	16.00
		132	5660	MCS0	14.86	16.00
		136	5680	MCS0	15.21	16.00
		140	5700	MCS0	15.52	16.00
		144	5720	MCS0	15.82	16.00
	802.11ac VHT20	100	5500	MCS0	12.54	13.50
		104	5520	MCS0	12.42	13.50
		108	5540	MCS0	12.40	13.50
		112	5560	MCS0	12.32	13.50
		116	5580	MCS0	11.80	13.50
		120	5600	MCS0	11.74	13.50
		124	5620	MCS0	11.76	13.50
		128	5640	MCS0	12.42	13.50
		132	5660	MCS0	12.56	13.50
		136	5680	MCS0	12.82	13.50
		140	5700	MCS0	13.10	13.50
		144	5720	MCS0	13.23	13.50

5GHz UNII-3	802.11a	149	5745	6Mbps	15.51	16.00
		153	5765	6Mbps	15.42	16.00
		157	5785	6Mbps	15.58	16.00
		161	5805	6Mbps	15.41	16.00
		165	5825	6Mbps	15.45	16.00
	802.11n HT20	149	5745	MCS0	15.46	16.00
		153	5765	MCS0	15.42	16.00
		157	5785	MCS0	15.42	16.00
		161	5805	MCS0	15.25	16.00
		165	5825	MCS0	15.29	16.00
	802.11ac VHT20	149	5745	MCS0	13.12	13.50
		153	5765	MCS0	13.06	13.50
		157	5785	MCS0	13.01	13.50
		161	5805	MCS0	13.00	13.50
		165	5825	MCS0	13.02	13.50

11.2.3 RF Conducted Power Data of BLE


BLE Ant 1		Average Conducted Power(dBm)			Tune up
Mode	Channel	0	19	39	
BLE 1M	GFSK	2.44	2.51	2.67	3.50
BLE 2M	GFSK	1.68	1.89	2.13	3.00

BLE Ant 2		Average Conducted Power(dBm)			Tune up
Mode	Channel	0	19	39	
BLE 1M	GFSK	2.41	2.61	2.63	3.50
BLE 2M	GFSK	1.46	1.37	2.09	3.00

11.2.4 EIRP Data of 60 GHz Radar

60GHz Radar				
Mode	Frequency band(GHz)	Frequency(GHz)	Max EIRP (dBm)	Tune up
Radar	57-64	61.158	1.47	2.00

Duty Cycle:



$561.3\mu s \times 2 = 1.1226ms$, Duty Cycle = $1.1226/33 = 3.4\%$

11.3 Measurement of SAR Data

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B.
- 2) For WiFi SAR test, since the highest reported SAR is smaller than the 75% SAR limit, and the tune-up of the other 802.11 modes is no higher than that of the SAR measurement mode, the adjusted SAR for those remaining 802.11 modes is $\leq$ the 75% SAR limit. Therefore, SAR tests for the other 802.11 modes are not required.
- 3) Ant1 and Ant2 cannot transmit simultaneously.

11.3.1 SAR Result of WIFI 2.4G

Ant1 Test Record												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Body Test data (Separate 10mm)												
Front side	802.11b	1/2412	98.82%	1.012	0.640	0.303	-0.05	19.29	19.50	1.050	0.680	22.3
Back side	802.11b	1/2412	98.82%	1.012	0.393	0.202	0.08	19.29	19.50	1.050	0.418	22.3
Left side	802.11b	1/2412	98.82%	1.012	0.753	0.376	-0.15	19.29	19.50	1.050	0.800	22.3
Right side	802.11b	1/2412	98.82%	1.012	0.003	0.001	-0.13	19.29	19.50	1.050	0.003	22.3
Top side	802.11b	1/2412	98.82%	1.012	0.005	0.002	-0.12	19.29	19.50	1.050	0.005	22.3
Bottom side	802.11b	1/2412	98.82%	1.012	0.008	0.003	-0.17	19.29	19.50	1.050	0.009	22.3
Front side	802.11b	6/2437	98.82%	1.012	0.673	0.322	0.12	19.19	19.50	1.074	0.731	22.3
Front side	802.11b	11/2462	98.82%	1.012	0.657	0.313	-0.15	19.10	19.50	1.096	0.729	22.3
Left side	802.11b	6/2437	98.82%	1.012	0.747	0.383	-0.09	19.19	19.50	1.074	0.812	22.3
Left side	802.11b	11/2462	98.82%	1.012	1.060	0.553	-0.11	19.10	19.50	1.096	1.176	22.3
Left side with repeated	802.11b	11/2462	98.82%	1.012	1.030	0.547	0.14	19.10	19.50	1.096	1.142	22.3
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm)												
Front side	802.11b	1/2412	98.82%	1.012	4.590	1.900	0.04	19.29	19.50	1.050	2.019	22.3
Back side	802.11b	1/2412	98.82%	1.012	2.100	0.875	-0.11	19.29	19.50	1.050	0.930	22.3
Left side	802.11b	1/2412	98.82%	1.012	2.840	1.200	-0.10	19.29	19.50	1.050	1.275	22.3
Right side	802.11b	1/2412	98.82%	1.012	0.015	0.006	-0.01	19.29	19.50	1.050	0.006	22.3
Top side	802.11b	1/2412	98.82%	1.012	0.026	0.010	0.12	19.19	19.50	1.074	0.011	22.3
Bottom side	802.11b	1/2412	98.82%	1.012	0.042	0.016	-0.11	19.10	19.50	1.096	0.018	22.3
Front side	802.11b	6/2437	98.82%	1.012	3.560	1.480	0.18	19.19	19.50	1.074	1.609	22.3
Front side	802.11b	11/2462	98.82%	1.012	3.330	1.390	-0.04	19.10	19.50	1.096	1.542	22.3
Ant2 Test Record												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Body Test data (Separate 10mm)												
Front side	802.11b	11/2462	98.82%	1.012	0.249	0.126	-0.19	19.37	19.50	1.030	0.260	22.3
Back side	802.11b	11/2462	98.82%	1.012	0.589	0.293	-0.07	19.37	19.50	1.030	0.614	22.3
Left side	802.11b	11/2462	98.82%	1.012	0.006	0.003	0.11	19.37	19.50	1.030	0.006	22.3
Right side	802.11b	11/2462	98.82%	1.012	0.551	0.274	0.19	19.37	19.50	1.030	0.574	22.3
Top side	802.11b	11/2462	98.82%	1.012	0.011	0.005	-0.11	19.37	19.50	1.030	0.011	22.3
Bottom side	802.11b	11/2462	98.82%	1.012	0.017	0.009	0.10	19.37	19.50	1.030	0.018	22.3
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm)												
Front side	802.11b	11/2462	98.82%	1.012	1.470	0.598	-0.16	19.37	19.50	1.030	0.623	22.3
Back side	802.11b	11/2462	98.82%	1.012	2.140	0.866	0.12	19.37	19.50	1.030	0.903	22.3

Left side	802.11b	11/2462	98.82%	1.012	0.022	0.009	-0.18	19.37	19.50	1.030	0.009	22.3
Right side	802.11b	11/2462	98.82%	1.012	1.780	0.727	-0.17	19.37	19.50	1.030	0.758	22.3
Top side	802.11b	11/2462	98.82%	1.012	0.039	0.016	0.07	19.37	19.50	1.030	0.017	22.3
Bottom side	802.11b	11/2462	98.82%	1.012	0.062	0.026	-0.09	19.37	19.50	1.030	0.027	22.3

Test Position	Test ch./Freq.	Measured SAR (W/kg)	1st Repeated	Ratio	2nd Repeated	3rd Repeated
Left side 10mm	11/2462	1.060	1.030	1.029	N/A	N/A

Note: 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.

2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).

3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

5) The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds. The repeated measurement results must be clearly identified in the SAR report.

11.3.2 SAR Result of WIFI 5G

Ant1 Test Record												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Body Test data of U-NII-2A (Separate 10mm)												
Front side	802.11a	64/5320	93.16%	1.073	0.171	0.048	0.19	15.89	16.00	1.026	0.188	22.2
Back side	802.11a	64/5320	93.16%	1.073	0.085	0.030	-0.13	15.89	16.00	1.026	0.094	22.2
Left side	802.11a	64/5320	93.16%	1.073	0.085	0.035	-0.10	15.89	16.00	1.026	0.094	22.2
Right side	802.11a	64/5320	93.16%	1.073	0.006	0.002	0.10	15.89	16.00	1.026	0.007	22.2
Top side	802.11a	64/5320	93.16%	1.073	0.010	0.004	-0.09	15.89	16.00	1.026	0.011	22.2
Bottom side	802.11a	64/5320	93.16%	1.073	0.021	0.010	0.06	15.89	16.00	1.026	0.023	22.2
Body Test data of U-NII-2C (Separate 10mm)												
Front side	802.11a	140/5700	93.16%	1.073	0.218	0.085	-0.01	15.05	16.00	1.245	0.291	22.2
Back side	802.11a	140/5700	93.16%	1.073	0.156	0.064	-0.01	15.05	16.00	1.245	0.208	22.2
Left side	802.11a	140/5700	93.16%	1.073	0.162	0.067	-0.15	15.05	16.00	1.245	0.216	22.2
Right side	802.11a	140/5700	93.16%	1.073	0.008	0.003	-0.06	15.05	16.00	1.245	0.011	22.2
Top side	802.11a	140/5700	93.16%	1.073	0.014	0.004	0.17	15.05	16.00	1.245	0.019	22.2
Bottom side	802.11a	140/5700	93.16%	1.073	0.040	0.015	-0.18	15.05	16.00	1.245	0.053	22.2
Body Test data of U-NII-3 (Separate 10mm)												
Front side	802.11a	149/5745	93.16%	1.073	0.246	0.088	0.05	14.92	16.00	1.282	0.338	22.2
Back side	802.11a	149/5745	93.16%	1.073	0.140	0.058	0.03	14.92	16.00	1.282	0.193	22.2
Left side	802.11a	149/5745	93.16%	1.073	0.180	0.071	0.06	14.92	16.00	1.282	0.248	22.2
Right side	802.11a	149/5745	93.16%	1.073	0.010	0.004	-0.11	14.92	16.00	1.282	0.014	22.2
Top side	802.11a	149/5745	93.16%	1.073	0.016	0.007	0.13	14.92	16.00	1.282	0.022	22.2
Bottom side	802.11a	149/5745	93.16%	1.073	0.035	0.014	-0.12	14.92	16.00	1.282	0.048	22.2
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data of U-NII-2A (Separate 0mm)												
Front side	802.11a	64/5320	93.16%	1.073	0.753	0.261	-0.10	15.89	16.00	1.026	0.287	22.2
Back side	802.11a	64/5320	93.16%	1.073	0.221	0.078	0.06	15.89	16.00	1.026	0.086	22.2
Left side	802.11a	64/5320	93.16%	1.073	0.260	0.085	-0.05	15.89	16.00	1.026	0.094	22.2
Right side	802.11a	64/5320	93.16%	1.073	0.019	0.005	0.15	15.89	16.00	1.026	0.006	22.2
Top side	802.11a	64/5320	93.16%	1.073	0.032	0.008	-0.16	15.89	16.00	1.026	0.009	22.2
Bottom side	802.11a	64/5320	93.16%	1.073	0.068	0.018	0.03	15.89	16.00	1.026	0.020	22.2
Extremity Test data of U-NII-2C (Separate 0mm)												
Front side	802.11a	140/5700	93.16%	1.073	0.869	0.304	-0.06	15.05	16.00	1.245	0.406	22.2
Back side	802.11a	140/5700	93.16%	1.073	0.293	0.108	-0.09	15.05	16.00	1.245	0.144	22.2
Left side	802.11a	140/5700	93.16%	1.073	0.339	0.117	0.17	15.05	16.00	1.245	0.156	22.2
Right side	802.11a	140/5700	93.16%	1.073	0.016	0.005	-0.06	15.05	16.00	1.245	0.007	22.2
Top side	802.11a	140/5700	93.16%	1.073	0.029	0.008	-0.19	15.05	16.00	1.245	0.011	22.2
Bottom side	802.11a	140/5700	93.16%	1.073	0.082	0.026	0.18	15.05	16.00	1.245	0.035	22.2
Extremity Test data of U-NII-3 (Separate 0mm)												
Front side	802.11a	149/5745	93.16%	1.073	1.150	0.331	-0.05	14.92	16.00	1.282	0.455	22.2
Back side	802.11a	149/5745	93.16%	1.073	0.271	0.096	-0.02	14.92	16.00	1.282	0.132	22.2

Left side	802.11a	149/5745	93.16%	1.073	0.310	0.111	0.07	14.92	16.00	1.282	0.153	22.2
Right side	802.11a	149/5745	93.16%	1.073	0.017	0.006	0.03	14.92	16.00	1.282	0.008	22.2
Top side	802.11a	149/5745	93.16%	1.073	0.028	0.008	-0.08	14.92	16.00	1.282	0.011	22.2
Bottom side	802.11a	149/5745	93.16%	1.073	0.061	0.017	-0.02	14.92	16.00	1.282	0.023	22.2
Front side	802.11a	165/5825	93.16%	1.073	1.510	0.416	0.05	14.61	16.00	1.377	0.615	22.2
Ant2 Test Record												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Body Test data of U-NII-2A (Separate 10mm)												
Front side	802.11a	64/5320	93.09%	1.074	0.063	0.019	-0.16	15.71	16.00	1.069	0.072	22.2
Back side	802.11a	64/5320	93.09%	1.074	0.094	0.041	0.03	15.71	16.00	1.069	0.108	22.2
Left side	802.11a	64/5320	93.09%	1.074	0.007	0.003	-0.01	15.71	16.00	1.069	0.008	22.2
Right side	802.11a	64/5320	93.09%	1.074	0.082	0.033	0.17	15.71	16.00	1.069	0.094	22.2
Top side	802.11a	64/5320	93.09%	1.074	0.012	0.005	0.10	15.71	16.00	1.069	0.014	22.2
Bottom side	802.11a	64/5320	93.09%	1.074	0.055	0.016	-0.03	15.71	16.00	1.069	0.063	22.2
Body Test data of U-NII-2C (Separate 10mm)												
Front side	802.11a	144/5720	93.09%	1.074	0.075	0.021	0.08	15.57	16.00	1.104	0.089	22.2
Back side	802.11a	144/5720	93.09%	1.074	0.285	0.120	-0.12	15.57	16.00	1.104	0.338	22.2
Left side	802.11a	144/5720	93.09%	1.074	0.009	0.004	-0.08	15.57	16.00	1.104	0.011	22.2
Right side	802.11a	144/5720	93.09%	1.074	0.093	0.035	-0.04	15.57	16.00	1.104	0.110	22.2
Top side	802.11a	144/5720	93.09%	1.074	0.015	0.006	0.09	15.57	16.00	1.104	0.018	22.2
Bottom side	802.11a	144/5720	93.09%	1.074	0.076	0.018	0.10	15.57	16.00	1.104	0.090	22.2
Body Test data of U-NII-3 (Separate 10mm)												
Front side	802.11a	157/5785	93.09%	1.074	0.087	0.025	0.10	15.58	16.00	1.102	0.103	22.2
Back side	802.11a	157/5785	93.09%	1.074	0.327	0.135	0.15	15.58	16.00	1.102	0.387	22.2
Left side	802.11a	157/5785	93.09%	1.074	0.011	0.005	-0.06	15.58	16.00	1.102	0.013	22.2
Right side	802.11a	157/5785	93.09%	1.074	0.095	0.036	0.09	15.58	16.00	1.102	0.112	22.2
Top side	802.11a	157/5785	93.09%	1.074	0.020	0.007	-0.16	15.58	16.00	1.102	0.024	22.2
Bottom side	802.11a	157/5785	93.09%	1.074	0.080	0.021	0.03	15.58	16.00	1.102	0.095	22.2
Back side	802.11a	149/5745	93.09%	1.074	0.452	0.187	0.03	15.51	16.00	1.119	0.543	22.2
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data of U-NII-2A (Separate 0mm)												
Front side	802.11a	64/5320	93.09%	1.074	0.363	0.112	-0.11	15.71	16.00	1.069	0.129	22.2
Back side	802.11a	64/5320	93.09%	1.074	0.386	0.113	0.11	15.71	16.00	1.069	0.130	22.2
Left side	802.11a	64/5320	93.09%	1.074	0.020	0.007	0.17	15.71	16.00	1.069	0.008	22.2
Right side	802.11a	64/5320	93.09%	1.074	0.301	0.090	-0.09	15.71	16.00	1.069	0.103	22.2
Top side	802.11a	64/5320	93.09%	1.074	0.041	0.013	-0.08	15.71	16.00	1.069	0.015	22.2
Bottom side	802.11a	64/5320	93.09%	1.074	0.097	0.021	-0.07	15.71	16.00	1.069	0.024	22.2
Extremity Test data of U-NII-2C (Separate 0mm)												
Front side	802.11a	144/5720	93.09%	1.074	0.229	0.078	0.18	15.57	16.00	1.104	0.092	22.2
Back side	802.11a	144/5720	93.09%	1.074	0.727	0.216	0.11	15.57	16.00	1.104	0.256	22.2
Left side	802.11a	144/5720	93.09%	1.074	0.022	0.008	-0.08	15.57	16.00	1.104	0.009	22.2
Right side	802.11a	144/5720	93.09%	1.074	0.310	0.097	-0.17	15.57	16.00	1.104	0.115	22.2
Top side	802.11a	144/5720	93.09%	1.074	0.045	0.014	0.07	15.57	16.00	1.104	0.017	22.2



Report No.: SUCR260800084601

Page: 56 of 62

Bottom side	802.11a	144/5720	93.09%	1.074	0.128	0.027	0.04	15.57	16.00	1.104	0.032	22.2
Extremity Test data of U-NII-3 (Separate 0mm)												
Front side	802.11a	157/5785	93.09%	1.074	0.176	0.072	-0.15	15.58	16.00	1.102	0.085	22.2
Back side	802.11a	157/5785	93.09%	1.074	0.733	0.230	-0.12	15.58	16.00	1.102	0.272	22.2
Left side	802.11a	157/5785	93.09%	1.074	0.021	0.008	0.07	15.58	16.00	1.102	0.009	22.2
Right side	802.11a	157/5785	93.09%	1.074	0.321	0.100	-0.17	15.58	16.00	1.102	0.118	22.2
Top side	802.11a	157/5785	93.09%	1.074	0.048	0.014	-0.15	15.58	16.00	1.102	0.017	22.2
Bottom side	802.11a	157/5785	93.09%	1.074	0.125	0.026	0.07	15.58	16.00	1.102	0.031	22.2

11.3.3 SAR Result of BLE

Ant1 Test Record												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Body Test data (Separate 10mm)												
Front side	1M	39/2480	63.36%	1.578	0.039	0.018	-0.16	2.67	3.50	1.211	0.075	22.3
Back side	1M	39/2480	63.36%	1.578	0.024	0.012	-0.16	2.67	3.50	1.211	0.046	22.3
Left side	1M	39/2480	63.36%	1.578	0.033	0.016	-0.03	2.67	3.50	1.211	0.063	22.3
Right side	1M	39/2480	63.36%	1.578	0.003	0.001	-0.09	2.67	3.50	1.211	0.006	22.3
Top side	1M	39/2480	63.36%	1.578	0.005	0.002	0.16	2.67	3.50	1.211	0.010	22.3
Bottom side	1M	39/2480	63.36%	1.578	0.009	0.004	0.01	2.67	3.50	1.211	0.017	22.3
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm)												
Front side	1M	39/2480	63.36%	1.578	0.139	0.053	-0.16	2.67	3.50	1.211	0.101	22.3
Back side	1M	39/2480	63.36%	1.578	0.095	0.041	0.11	2.67	3.50	1.211	0.078	22.3
Left side	1M	39/2480	63.36%	1.578	0.129	0.051	-0.07	2.67	3.50	1.211	0.097	22.3
Right side	1M	39/2480	63.36%	1.578	0.009	0.003	-0.05	2.67	3.50	1.211	0.006	22.3
Top side	1M	39/2480	63.36%	1.578	0.018	0.006	0.03	2.67	3.50	1.211	0.011	22.3
Bottom side	1M	39/2480	63.36%	1.578	0.032	0.011	0.19	2.67	3.50	1.211	0.021	22.3
Ant2 Test Record												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Body Test data (Separate 10mm)												
Front side	1M	39/2480	63.36%	1.578	0.021	0.010	0.15	2.63	3.50	1.222	0.040	22.3
Back side	1M	39/2480	63.36%	1.578	0.071	0.038	0.07	2.63	3.50	1.222	0.137	22.3
Left side	1M	39/2480	63.36%	1.578	0.003	0.002	0.00	2.63	3.50	1.222	0.006	22.3
Right side	1M	39/2480	63.36%	1.578	0.046	0.021	0.14	2.63	3.50	1.222	0.089	22.3
Top side	1M	39/2480	63.36%	1.578	0.007	0.004	0.08	2.63	3.50	1.222	0.013	22.3
Bottom side	1M	39/2480	63.36%	1.578	0.011	0.006	0.10	2.63	3.50	1.222	0.021	22.3
Back side	1M	0/2402	63.36%	1.578	0.016	0.008	0.06	2.41	3.50	1.285	0.032	22.3
Back side	1M	19/2440	63.36%	1.578	0.023	0.011	-0.11	2.61	3.50	1.227	0.045	22.3
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm)												
Front side	1M	39/2480	63.36%	1.578	0.098	0.041	0.13	2.63	3.50	1.222	0.079	22.3
Back side	1M	39/2480	63.36%	1.578	0.199	0.093	-0.18	2.63	3.50	1.222	0.179	22.3
Left side	1M	39/2480	63.36%	1.578	0.011	0.005	0.18	2.63	3.50	1.222	0.010	22.3
Right side	1M	39/2480	63.36%	1.578	0.165	0.069	0.06	2.63	3.50	1.222	0.133	22.3
Top side	1M	39/2480	63.36%	1.578	0.023	0.011	-0.07	2.63	3.50	1.222	0.021	22.3
Bottom side	1M	39/2480	63.36%	1.578	0.040	0.019	0.09	2.63	3.50	1.222	0.037	22.3
Back side	1M	0/2402	63.36%	1.578	0.059	0.025	0.13	2.41	3.50	1.285	0.051	22.3
Back side	1M	19/2440	63.36%	1.578	0.086	0.035	-0.07	2.61	3.50	1.227	0.068	22.3

11.4 Measurement of PD Data

Note:

- 1) The maximum Scaled PD value is marked in bold. Graph results refer to Appendix B.
- 2) Since there is no different PD limit on different exposure conditions, therefore the PD test was performed of a 2mm separation between sensor and EUT surface to cover all exposure conditions of EUT.
- 3) According to October 2020 TCB Workshop Interim procedures, power density results were scaled in cases where the portion of the measurement uncertainty > 30%. Total expanded uncertainty of 2.67 dB (85%) was used to determine the psPD measurement scaling factor.

11.4.1 PD Result

Test position	Band	Ch.	Distance (mm)	Grid Step (λ)	Duty Cycle	Duty Cycle Scaled factor	Measured PD 4cm ² (W/m ²)	Power drift (dB)	EIRP(dBm)	Tune up Limit(dBm)	Scaling Factor for measurement uncertainty	Tune up Scaled factor	Scaled PD 4cm ² (W/m ²)
Power Density Test DATA													
Front side	57-64G	61158	2	0.25	3.40%	29.412	0.048	-0.03	1.47	2.00	1.5493	1.129	2.469
Back side	57-64G	61158	2	0.25	3.40%	29.412	0.058	0.06	1.47	2.00	1.5493	1.129	2.983
Left side	57-64G	61158	2	0.25	3.40%	29.412	0.000	0.00	1.47	2.00	1.5493	1.129	0.000
Right side	57-64G	61158	2	0.25	3.40%	29.412	0.048	-0.05	1.47	2.00	1.5493	1.129	2.469
Top side	57-64G	61158	2	0.25	3.40%	29.412	0.000	0.00	1.47	2.00	1.5493	1.129	0.000
Bottom side	57-64G	61158	2	0.25	3.40%	29.412	0.032	0.09	1.47	2.00	1.5493	1.129	1.646

11.5 Multiple Transmitter Evaluation

11.5.1 Simultaneous SAR test evaluation

No.	Simultaneous Tx Combination	Body	Extremity
1	WIFI2.4G Ant1+60 GHz	Yes	Yes
2	WIFI2.4G Ant2+60 GHz	Yes	Yes
3	WIFI5G Ant1+60 GHz	Yes	Yes
4	WIFI5G Ant2+60 GHz	Yes	Yes
5	Bluetooth Ant1+60 GHz	Yes	Yes
6	Bluetooth Ant2+60 GHz	Yes	Yes

11.5.2 Total Exposure Ratio

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Body:

Test position	ER							TER					
	WiFi 2.4G Ant1	WiFi 2.4G Ant2	WiFi 5G Ant1	WiFi 5G Ant2	BLE Ant1	BLE Ant2	60GHz						
	1	2	3	4	5	6	7	1+7	2+7	3+7	4+7	5+7	6+7
Front side	0.457	0.163	0.211	0.064	0.047	0.047	0.247	0.704	0.409	0.458	0.311	0.294	0.294
Back side	0.261	0.384	0.130	0.339	0.029	0.029	0.298	0.560	0.682	0.428	0.638	0.327	0.327
Left side	0.735	0.004	0.155	0.008	0.039	0.039	0.000	0.735	0.004	0.155	0.008	0.039	0.039
Right side	0.002	0.359	0.009	0.070	0.004	0.004	0.247	0.249	0.606	0.256	0.317	0.251	0.251
Top side	0.003	0.007	0.014	0.015	0.006	0.006	0.000	0.003	0.007	0.014	0.015	0.006	0.006
Bottom side	0.006	0.011	0.033	0.059	0.011	0.011	0.165	0.170	0.176	0.198	0.224	0.175	0.175

Extremity:

Test position	ER							TER					
	WiFi 2.4G Ant1	WiFi 2.4G Ant2	WiFi 5G Ant1	WiFi 5G Ant2	BLE Ant1	BLE Ant2	60GHz						
	1	2	3	4	5	6	7	1+7	2+7	3+7	4+7	5+7	6+7
Front side	0.505	0.156	0.154	0.032	0.025	0.025	0.247	0.752	0.403	0.401	0.279	0.272	0.272
Back side	0.233	0.226	0.036	0.068	0.045	0.045	0.298	0.531	0.524	0.334	0.366	0.343	0.343
Left side	0.319	0.002	0.039	0.002	0.024	0.024	0.000	0.319	0.002	0.039	0.002	0.024	0.024
Right side	0.002	0.190	0.002	0.030	0.033	0.033	0.247	0.248	0.436	0.249	0.276	0.280	0.280
Top side	0.003	0.004	0.003	0.004	0.005	0.005	0.000	0.003	0.004	0.003	0.004	0.005	0.005
Bottom side	0.005	0.007	0.009	0.008	0.009	0.009	0.165	0.169	0.171	0.173	0.173	0.174	0.174

12 Equipment list

Test Platform		SPEAG DASY Professional				
Software Reference		DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)				
		cDASY8 Module mmWave_V3.0.0.841				
Hardware Reference						
Equipment		Manufacturer	Model	Serial Number	Calibration Date	Due date of calibration
☒	Test Phantom	SPEAG	ELI V5.0	1239	NCR	NCR
☒	Test Phantom	SPEAG	mmWave	1777	NCR	NCR
☒	DAE	SPEAG	DAE4	1740	2026-09-11	2027-09-10
☒	DAE	SPEAG	DAE4ip	1826	2026-04-27	2027-04-26
☒	E-Field Probe	SPEAG	EX3DV4	3923	2026-01-12	2027-01-11
☒	E-Field Probe	SPEAG	EUmmWV4	9533	2025-09-19	2026-09-18
☒	Validation Kits	SPEAG	D2450V2	733	2025-10-15	2028-10-14
☒	Validation Kits	SPEAG	D5GHzV2	1174	2025-10-14	2028-10-13
☒	Validation Kits	SPEAG	60GHz	1050	2024-08-20	2027-08-19
☒	Dielectric parameter probes	SPEAG	DAK-3.5	1308	2026-06-16	2027-06-17
☒	Agilent Network Analyzer	Agilent	E5071C	MY46523590	2026-07-29	2027-07-28
☒	Universal Radio Communication Tester	R&S	CMW500	111637	2026-01-15	2027-01-14
☒	RF Bi-Directional Coupler	Agilent	86205-60001	MY31400031	NCR	NCR
☒	Signal Generator	R&S	SMB100A	182393	2026-01-14	2027-01-13
☒	Preamplifier	Qiji	YX28980933	202104001	NCR	NCR
☒	USB Average Power Sensor	Agilent	U2002H	MY48200110	2025-11-20	2026-11-19
☒	Attenuator	SHX	TS2-3dB	30704	NCR	NCR
☒	Coaxial low pass filter	Mini-Circuits	VLF-2500(+)	NA	NCR	NCR
☒	Coaxial low pass filter	Microlab Fxr	LA-F13	NA	NCR	NCR
☒	DC POWER SUPPLY	SAKO	SK1730SL5A	NA	NCR	NCR
☒	Speed reading thermometer	DTM SPEZLAL	DTM3000	NA	2026-09-16	2027-09-15
☒	Humidity and Temperature Indicator	ASONE	THA-02L	2201-1017	2026-09-16	2027-09-15

Note: All the equipment are within the valid period when the tests are performed.



Report No.: SUCR260800084601
Page: 62 of 62

13 Calibration certificate

Please see the Appendix C

14 Photographs

Please see the Appendix D

Appendix A: Detailed System Check Results

Appendix B: Detailed Test Results

Appendix C: Calibration certificate

Appendix D: Photographs

--- End of report ---