RF Exposure Evaluation

FCC ID: 2AZIX-K207

1. Client Information

Applicant	:	SHENZHEN KEDING HARDWARE CO.,LTD
Address	:	No.18 Tangkeng 3Rd, Pingshan District, Shenzhen, Guangdong, China
Manufacturer	:	SHENZHEN KEDING HARDWARE CO.,LTD
Address	:	No.18 Tangkeng 3Rd, Pingshan District, Shenzhen, Guangdong, China

2. General Description of EUT

EUT Name	:	Multifunctional Outlet Socket	
Model(s)	:	K207, K265A	
Sample ID	:	TBBJ-20210128-04_#1	
Model Difference	:	All PCB boards and circuit diagrams are the same, the only difference is the appearance.	
Product Description	:	Operation Frequency:	110KHz-205KHz
		Modulation Type:	ASK
		Antenna:	Coil Antenna
Power Supply	:	Input: AC 125V/12A USB Output: DC 5V/2.1A Max Wireless Charge Output: 5W	
Software Version	:	N/A	
Hardware Version	:	N/A	
Connecting I/O Port(S)	:	Please refer to the User's Manual	
Accessories	:	HONOR V30 PRO	

Note: More test information about the EUT please refer the RF Test Report.

1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, China
Tel: +86 75526509301 Fax: +86 75526509195

RF Exposure Considerations

1. Measuring Standard

KDB 680106 D01 RF Exposure Wireless Charging App v03.

2. Requirements

According to the item 5.2 of KDB 680106 D01v03:
Inductive wireless power transfer applications that meet all of the following requirements are excluded from submitting an RF exposure evaluation:

(1) Power transfer frequency is less than 1 MHz.

(2) Output power from each primary coil is less than or equal to 15 watts.

(3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.

(4) Client device is placed directly in contact with the transmitter.

(5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).

(6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Limits For Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm^2)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f^2)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f^2)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz
*=Plane-wave equivalent power density
RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

3. Test Setup



Note: The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface.

4.Test Procedure

1) The RF exposure test was performed in anechoic chamber.
2) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface.
3) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
4) The EUT was measured according to the dictates of KDB 680106 D01 v03.

Remark:
The EUT's test position A, B, C, D and E is valid for the E and H field measurements.

5. Test Equipment List

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Magnetic field meter	NARDA	ELT-400	EE030	Sep. 11, 2020	Sep. 10, 2021

6. Deviation From Test Standard

No deviation

7. Mode of operation during the test / Test peripherals used

Test Modes:		
TM1	AC/DC Adapter + EUT + Mobile Phone (Battery Status: <1%)	record
TM2	AC/DC Adapter + EUT + Mobile Phone (Battery Status: <50%)	record
TM3	AC/DC Adapter + EUT + Mobile Phone (Battery Status: <99%)	record

8. Test Result

E-Filed Strength at 15 cm from the edges surrounding the EUT and 15 cm above the top surface

Charging Battery Level	Frequency Range (MHz)	Measured E-Field Strength Values (V/m) Test Position					E-Field Strength 50% Limits (V/m)	E-Field Strength Limits (V/m)
		A	B	C	D	E		
1%	0.118	42.601	43.355	61.451	43.732	47.125	307.0	614.0
50%	0.118	46.748	42.978	49.387	47.125	42.978	307.0	614.0
99%	0.118	61.074	49.387	42.978	34.684	41.847	307.0	614.0

Note: V/m= A/m *377

H-Filed Strength at 15 cm from the edges surrounding the EUT and 15 cm above the top surface

Charging Battery Level	unit	Frequency Range (MHz)	Measured H-Field Strength Values (A/m) Test Position					H-Field Strength 50% Limits (A/m)	H-Field Strength Limits (A/m)
			A	B	C	D	E		
1%	uT	0.118	0.1413	0.1438	0.2038	0.145	0.1563	--	--
1%	A/m	0.118	0.113	0.115	0.163	0.116	0.125	0.815	1.63
50%	uT	0.118	0.155	0.1425	0.1638	0.1563	0.1425	--	--
50%	A/m	0.118	0.124	0.114	0.131	0.125	0.114	0.815	1.63
99%	uT	0.118	0.2025	0.1638	0.1425	0.1150	0.1388	--	--
99%	A/m	0.118	0.162	0.131	0.114	0.092	0.111	0.815	1.63

H-Field Strength at 20cm from the top surface of the EUT

Charging Battery Level	Unit	Frequency Range (MHz)	Measured H-Field Strength Values (A/m) Test Position E	FCC H-Field Strength 50% Limits (A/m)	FCC H-Field Strength Limits (A/m)
1%	uT	0.118	0.1338	--	--
1%	A/m	0.118	0.107	0.815	1.63
50%	uT	0.118	0.1225	--	--
50%	A/m	0.118	0.098	0.815	1.63
99%	uT	0.118	0.1375	--	--
99%	A/m	0.118	0.11	0.815	1.63

Note: A/m=uT/1.25

9. Test Set-up Photo

Test Set-up Photo

-----END OF REPORT-----