



REPORT No.: SZ24090015W09

TEST REPORT

APPLICANT : Securus Technologies, LLC

PRODUCT NAME : Tablet

MODEL NAME : EVOTAB

BRAND NAME : SECURUS

FCC ID : 2AZJPEVOTAB

STANDARD(S) : 47 CFR Part 2
47 CFR Part 22 Subpart H
47 CFR Part 24 Subpart E
47 CFR Part 27 Subpart L

RECEIPT DATE : 2025-05-12

TEST DATE : 2025-05-16 to 2025-06-03

ISSUE DATE : 2025-06-17



Edited by:

Peng Mi

Peng Mi (Rapporteur)

Approved by:

Shen Junsheng

Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Technical Information	3
1.1. Applicant and Manufacturer Information	3
1.2. Equipment Under Test (EUT) Description	3
1.3. Maximum E.R.P./E.I.R.P. and Emission Designator	5
1.4. Test Standards and Results	6
1.5. Environmental Conditions	7
2. 47 CFR Part 2, Part 22H, 24E&27L Requirements	8
2.1. Conducted RF Output Power	8
2.2. Peak to Average Ratio	12
2.3. Occupied Bandwidth	16
2.4. Frequency Stability	21
2.5. Conducted Out of Band Emissions	24
2.6. Band Edge	28
2.7. Determining E.R.P. and/or E.I.R.P. from conducted RF output power measurements	31
2.8. Radiated Out of Band Emissions	35
Annex A Test Uncertainty	55
Annex B Testing Laboratory Information	56

Change History		
Version	Date	Reason for change
1.0	2025-06-17	First edition





1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Securus Technologies, LLC
Applicant Address:	5360 Legacy Drive, Suite 300, Plano, Texas, United States, 75024
Manufacturer:	Rhino Mobility LLC
Manufacturer Address:	8 The Green, Suite A, Dover, Delaware, 19901, USA

1.2. Equipment Under Test (EUT) Description

Product Name:	Tablet	
Sample No.:	30#, 28#, 14#	
Hardware Version:	T8006_MB_V1.0	
Software Version:	T81R(001)_20250530	
Modulation Type:	WCDMA Mode with QPSK Modulation HSDPA Mode with QPSK Modulation HSUPA Mode with QPSK Modulation HSPA+ Mode with 16QAM Modulation	
Operating Frequency Range:	WCDMA Band V	Tx: 824MHz-849MHz Rx: 869MHz-894MHz
	WCDMA Band IV	Tx: 1710MHz-1755MHz Rx: 2110MHz-2155MHz
	WCDMA Band II	Tx: 1850MHz-1910MHz Rx: 1930MHz-1990MHz
Antenna Type:	PIFA Antenna	
Antenna Gain:	WCDMA Band V:	1.37dBi
	WCDMA Band IV	2.78dBi
	WCDMA Band II:	4.31dBi



Accessory Information:	Battery	
	Brand Name:	N/A
	Model No.:	ST-E6
	Serial No.:	N/A
	Capacity:	6000mAh
	Rated Voltage:	3.87V
	Charge Limit:	4.45V
	Manufacturer:	PHENIX NEW ENERGY (HUIZHOU) CO., LTD.
	AC Adapter	
	Brand Name:	N/A
	Model No.:	DCT18W090200US-T0
	Serial No.:	N/A
	Rated Output:	9V=2A
	Rated Input:	100-240V~50/60Hz, 0.7A
	Manufacturer:	Zhuzhou Dachuan Electronic Technology Co.,Ltd

Note 1: The transmitter (Tx) frequency arrangement of the WCDMA Band V used by the EUT can be represented with the formula $F(n)=826.4+0.2*(n-4132)$, $4132 \leq n \leq 4233$; the lowest, middle and highest channel numbers (ARFCHs) used and tested in this report are separately 4132 (826.4MHz), 4182(836.4MHz) and 4233 (846.6MHz).

Note 2: The transmitter (Tx) frequency arrangement of the WCDMA Band II used by the EUT can be represented with the formula $F(n)=1852.4+0.2*(n-9262)$, $9262 \leq n \leq 9538$; the lowest, middle and highest channel numbers (ARFCHs) used and tested in this report are separately 9262 (1852.4MHz), 9400 (1880MHz) and 9538 (1907.6MHz).

Note 3: All test modes and data rates were considered and evaluated respectively by performing full test. Test modes are chosen to be reported as the worst case below:

WCDMA mode for WCDMA band V;

WCDMA mode for WCDMA band IV;

WCDMA mode for WCDMA band II;

Note 4: The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.





1.3. Maximum E.R.P./E.I.R.P. and Emission Designator

Test Mode	Maximum E.R.P./E.I.R.P. (W)	Emission Designator
WCDMA Band V	0.167	4M16F9W
WCDMA Band IV	0.386	4M14F9W
WCDMA Band II	0.561	4M16F9W





1.4. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 2, Part 22, Part 24 and Part 27 for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 2 (10-1-12 Edition)	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 22 (10-1-12 Edition)	Public Mobile Services
3	47 CFR Part 24 (10-1-12 Edition)	Personal Communications Services
4	47 CFR Part 27 (10-1-12 Edition)	Miscellaneous Wireless Communications Services

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Remark
1	2.1046	Conducted RF Output Power	May 16, 2025	Shen Biaohong	PASS	/
2	24.232(d)	Peak -Average Ratio	May 27, 2025	Liu Huiyan	PASS	/
3	2.1049	Occupied Bandwidth	May 27, 2025	Liu Huiyan	PASS	/
4	2.1055, 22.355, 24.235, 27.54	Frequency Stability	May 27, 2025	Liu Huiyan	PASS	/
5	2.1051, 22.917(a), 24.238(a), 27.53(h)	Conducted Out of Band Emissions	May 27, 2025	Liu Huiyan	PASS	/
6	2.1051, 22.917(a), 24.238(a), 27.53(h)	Band Edge	May 27, 2025	Liu Huiyan	PASS	/
7	22.913(a), 24.232(c) 27.50(d)	Transmitter Radiated Power (EIPR/E.R.P.)	May 27, 2025	Liu Huiyan	PASS _{Note3}	/
8	2.1053, 22.917(a), 24.238(a), 27.53(h)	Radiated Out of Band Emissions	May 26, 2024 to Jun. 03, 2025	Li Hanbin	PASS	/

Note 1: The tests were performed according to the method of measurements prescribed in KDB971168 D01 v03r01 and ANSI/TIA-603-E-2016.





Note 2: Any additions, deviation, or exclusions from the method shall be noted in the "Remark".
Note 3: The antenna gain presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information.

1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106



2.47 CFR Part 2, Part 22H, 24E&27L Requirements


2.1. Conducted RF Output Power

2.1.1. Requirement

According to FCC section 2.1046(a), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in FCC section 2.1033(c)(8).

2.1.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.



**2.1.3.Test Results**

WCDMA Band V	Average Power (dBm)		
TX Channel	4132	4182	4233
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2Kbps	22.91	23.02	23.00
HSDPA Subtest-1	21.68	21.69	21.52
HSDPA Subtest-2	21.61	21.64	21.46
HSDPA Subtest-3	21.05	21.08	20.95
HSDPA Subtest-4	21.03	21.03	20.98
DC-HSDPA Subtest-1	21.68	21.67	21.46
DC-HSDPA Subtest-2	21.67	21.66	21.48
DC-HSDPA Subtest-3	21.17	21.16	20.99
DC-HSDPA Subtest-4	21.16	21.15	20.97
HSUPA Subtest-1	21.63	21.70	21.51
HSUPA Subtest-2	21.21	21.20	21.03
HSUPA Subtest-3	21.68	21.66	21.49
HSUPA Subtest-4	21.66	21.69	21.53
HSUPA Subtest-5	21.62	21.67	21.48
HSPA+ (16QAM) Subtest-1	21.60	21.58	21.41





WCDMA Band IV	Average Power (dBm)		
TX Channel	1312	1413	1513
Frequency (MHz)	1712.4	1732.6	1752.6
RMC 12.2Kbps	23.07	23.09	22.98
HSDPA Subtest-1	21.87	21.97	21.91
HSDPA Subtest-2	21.97	22.00	21.90
HSDPA Subtest-3	21.46	21.48	21.37
HSDPA Subtest-4	21.49	21.50	21.31
DC-HSDPA Subtest-1	21.82	21.81	21.75
DC-HSDPA Subtest-2	21.85	21.82	21.76
DC-HSDPA Subtest-3	21.34	21.32	21.27
DC-HSDPA Subtest-4	21.33	21.33	21.26
HSUPA Subtest-1	21.84	21.95	21.89
HSUPA Subtest-2	21.34	21.44	21.39
HSUPA Subtest-3	21.89	21.92	21.78
HSUPA Subtest-4	21.78	21.95	21.88
HSUPA Subtest-5	21.86	21.94	21.80
HSPA+ (16QAM) Subtest-1	21.97	21.96	21.88





WCDMA Band II	Average Power (dBm)		
TX Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880.0	1907.6
RMC 12.2Kbps	23.11	23.18	23.16
HSDPA Subtest-1	22.05	22.21	22.19
HSDPA Subtest-2	22.01	22.21	22.11
HSDPA Subtest-3	21.54	21.68	21.59
HSDPA Subtest-4	21.55	21.63	21.55
DC-HSDPA Subtest-1	22.04	22.20	22.21
DC-HSDPA Subtest-2	22.08	22.19	22.22
DC-HSDPA Subtest-3	21.56	21.70	21.73
DC-HSDPA Subtest-4	21.57	21.69	21.74
HSUPA Subtest-1	22.06	22.21	22.08
HSUPA Subtest-2	21.54	21.74	21.64
HSUPA Subtest-3	22.07	22.20	22.03
HSUPA Subtest-4	22.08	22.18	22.21
HSUPA Subtest-5	22.06	22.17	22.11
HSPA+ (16QAM) Subtest-1	22.09	22.16	22.03




2.2. Peak to Average Ratio

2.2.1. Requirement

According to FCC 24.232(d) and 27.50(d), the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

2.2.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.

2.2.3. Test procedure

1. For GSM/EDGE operating mode:
 - a. Set RBW=1MHz, VBW=3MHz, peak detector in spectrum analyzer.
 - b. Set EUT in maximum output power, and triggered the bust signal.
 - c. Measured respectively the peak level and mean level, and the deviation was recorded as Peak to Average ratio.
2. For UMTS operating mode:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1%.





2.2.4. Test Result

The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

A. Test Verdict:


WCDMA Band IV					
Mode	Channel	Frequency (MHz)	Peak to Average ratio (dB)	Limit (dB)	Verdict
WCDMA	1312	1712.4	3.64	13	PASS
	1413	1732.6	3.95		PASS
	1513	1752.6	2.92		PASS

WCDMA Band II					
Mode	Channel	Frequency (MHz)	Peak to Average ratio (dB)	Limit (dB)	Verdict
WCDMA	9262	1852.4	2.82	13	PASS
	9400	1880.0	2.90		PASS
	9538	1907.6	2.82		PASS






WCDMA Band IV, CH1312, 1712.4MHz






WCDMA Band IV, CH1413, 1732.6MHz



WCDMA Band IV, CH1513, 1752.6MHz



**WCDMA Band II, CH9262, 1852.4MHz****WCDMA Band II, CH9400, 1880.0MHz****WCDMA Band II, CH9538, 1907.6MHz**


2.3. Occupied Bandwidth

2.3.1. Requirement

According to FCC section 2.1049, the occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission. Occupied bandwidth is also known as the 99% emission bandwidth.

2.3.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.






**2.3.3.Test Result**



WCDMA Band V				
Mode	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)
WCDMA	4132	826.4	4.14	4.73
	4182	836.4	4.16	4.73
	4233	846.6	4.11	4.72



WCDMA Band IV				
Mode	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)
WCDMA	1312	1712.4	4.14	4.74
	1413	1732.6	4.14	4.73
	1513	1752.6	4.14	4.72

WCDMA Band II				
Mode	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)
WCDMA	9262	1852.4	4.15	4.73
	9400	1880.0	4.15	4.74
	9538	1907.6	4.16	4.76



**WCDMA Band V, CH4132, 826.4MHz****WCDMA Band V, CH4182, 836.4MHz****WCDMA Band V, CH4233, 846.6MHz**

**WCDMA Band IV, CH1312, 1712.4MHz****WCDMA Band IV, CH1413, 1732.6MHz****WCDMA Band IV, CH1513, 1752.6MHz**

**WCDMA Band II, CH9262, 1852.4MHz****WCDMA Band II, CH9400, 1880.0MHz****WCDMA Band II, CH9538, 1907.6MHz**

2.4. Frequency Stability

2.4.1. Requirement


According to FCC section 22.355, 24.235 and 27.54 the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. According to FCC section 2.1055, the test conditions are:

- (a) The temperature is varied from -30°C to $+50^{\circ}\text{C}$ at intervals of not more than 10°C .
- (b) For hand carried battery powered equipment, the primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacture. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

Note: The operating temperature of EUT is from 0°C to 45°C , which are specified by the applicant.

2.4.2. Test Description

Test Setup:



The EUT, which is powered by the DC Power Supply directly, is located in the Temperature Chamber. The EUT is commanded by the System Simulator (SS) to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS via a Common Antenna.





2.4.3. Test Result

The nominal, highest and lowest extreme voltages are separately 3.87V, 4.45V and 3.50V, which are specified by the applicant; the normal temperature here used is 20°C.

WCDMA Band V, CH4182, 836.4MHz					
Limit =±2.5ppm					
Voltage (%)	Power (VDC)	Temp (°C)	Fre. Dev. (Hz)	Deviation (ppm)	Result
Normal	3.87	+20(Ref)	-15	-0.018	PASS
Normal		0	50	0.060	
Normal		+10	34	0.041	
Normal		+20	-45	-0.054	
Normal		+30	-25	-0.030	
Normal		+40	23	0.027	
Normal		+45	34	0.041	
High	4.45	+20	27	0.032	
BATT.ENDPOINT	3.50	+20	24	0.029	

WCDMA Band IV, CH1413, Frequency 1732.6MHz					
Limit =Within Authorized Band					
Voltage (%)	Power (VDC)	Temp (°C)	Fre. Dev. (Hz)	Deviation (ppm)	Result
Normal	3.87	+20(Ref)	29	0.017	PASS
Normal		0	44	0.025	
Normal		+10	45	0.026	
Normal		+20	-41	-0.024	
Normal		+30	-17	-0.010	
Normal		+40	-25	-0.014	
Normal		+45	37	0.021	
High	4.45	+20	-50	-0.029	
BATT.ENDPOINT	3.50	+20	-30	-0.017	





REPORT No.: SZ24090015W09

WCDMA Band II, CH9400, 1880.0MHz					
Limit =Within Authorized Band					
Voltage (%)	Power (VDC)	Temp (°C)	Fre. Dev. (Hz)	Deviation (ppm)	Result
Normal	3.87	+20(Ref)	48	0.026	PASS
Normal		0	16	0.009	
Normal		+10	50	0.027	
Normal		+20	53	0.028	
Normal		+30	30	0.016	
Normal		+40	20	0.011	
Normal		+45	-41	-0.022	
High	4.45	+20	45	0.024	
BATT.ENDPOINT	3.50	+20	18	0.010	




2.5. Conducted Out of Band Emissions

2.5.1. Requirement

According to FCC section 22.917(a), 24.238(a) and 27.53(h) the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \cdot \log(P)$ dB. This calculated to be -13dBm. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency.

2.5.2. Test Description

Test Setup:




The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.






2.5.3. Test Result

WCDMA Band V, CH4132, 826.4MHz



WCDMA Band V, CH4182, 836.4MHz




WCDMA Band V, CH4233, 846.6MHz






WCDMA Band IV, CH1312, 1712.4MHz



WCDMA Band IV, CH1413, 1732.6MHz




WCDMA Band IV, CH1513, 1752.6MHz







WCDMA Band II, CH9262, 1852.4MHz



WCDMA Band II, CH9400, 1880.0MHz



WCDMA Band II, CH9538, 1907.6MHz




2.6. Band Edge

2.6.1. Requirement

According to FCC section 22.917(a), 24.238(a) and 27.53(h) the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \cdot \log(P)$ dB.

2.6.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.







2.6.3. Test Result

The lowest and highest channels are tested to verify the band edge emissions.

WCDMA Band V, CH4132, 826.4MHz




WCDMA Band V, CH4233, 846.6MHz



WCDMA Band IV, CH1312, 1712.4MHz




WCDMA Band IV, CH1513, 1752.6MHz






WCDMA Band II, CH9262, 1852.4MHz



WCDMA Band II, CH9538, 1907.6MHz



2.7. Determining E.R.P. and/or E.I.R.P. from conducted RF output power measurements

2.7.1. Requirement

According to FCC section 22.913, the Effective Radiated Power (E.R.P.) of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

According to FCC section 24.232, the broadband PCS mobile station is limited to 2 Watts e.i.r.p. peak power.

According to FCC section 27.50, mobile, and portable (hand-held) stations is limited to 1 Watts e.i.r.p. peak power.

2.7.2. Test Description

The test setups refer to section 2.1.3

A call is established between the EUT and the SS via a Common Antenna. The EUT is commanded by the SS to operate at the maximum and minimum output power (i.e. GSM850MHz band Power Control Level (PCL) = 5/19 and Power Class = 4, GSM1900MHz band Power Control Level (PCL) = 0/15 and Power Class = 1), and only the test result of the maximum output power was recorded. Please refer to section 2.1.3 of this report.

The relevant equation for determining the maximum E.R.P. or E.I.R.P. from the measured RF output power is given in Equation (1) as follows:

$$\text{E.R.P. or E.I.R.P.} = P_{\text{Meas}} + G_{\text{T}}$$

Where:

E.R.P. or E.I.R.P. effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as P_{Meas} , e.g., dBm or dBW)

P_{Meas} measured transmitter output power or PSD, in dBm or dBW

G_{T} gain of the transmitting antenna, in dBd (E.R.P.) or dBi (E.I.R.P.)

For devices utilizing multiple antennas, see ANSI C63.25-2015 6.4 for guidance with respect to determining the effective array transmit antenna gain term to be used in the above equation.

The following equations demonstrate the mathematical relationship between E.R.P. and E.I.R.P.:

a) E.R.P. = E.I.R.P. - 2.15, where E.R.P. and E.I.R.P. are expressed in consistent units.

b) E.I.R.P. = E.R.P. + 2.15, where E.R.P. and E.I.R.P. are expressed in consistent units.





2.7.3.Test Result

WCDMA Band V							
Band	Channel	Frequency (MHz)	Measured E.R.P.		Limit		Verdict
			dBm	W	dBm	W	
WCDMA	4132	826.4	22.13	0.163	38.5	7	PASS
	4182	836.4	22.24	0.167			PASS
	4233	846.6	22.22	0.167			PASS
HSDPA	4132	826.4	20.90	0.123	38.5	7	PASS
	4182	836.4	20.91	0.123			PASS
	4233	846.6	20.74	0.119			PASS
DC-HSD PA	4132	826.4	20.90	0.123	38.5	7	PASS
	4182	836.4	20.89	0.123			PASS
	4233	846.6	20.70	0.117			PASS
HSUPA	4132	826.4	20.90	0.123	38.5	7	PASS
	4182	836.4	20.92	0.124			PASS
	4233	846.6	20.75	0.119			PASS
HSPA+	4132	826.4	20.82	0.121	38.5	7	PASS
	4182	836.4	20.80	0.120			PASS
	4233	846.6	20.63	0.116			PASS
Note 1: For the HSDPA and HSUPA mode, all the subtests were tested and just the worst data were recorded in this report.							





WCDMA Band IV							
Band	Channel	Frequency (MHz)	Measured E.I.R.P.		Limit		Verdict
			dBm	W	dBm	W	
WCDMA	1312	1712.4	25.85	0.385	30	1	PASS
	1413	1732.6	25.87	0.386			PASS
	1513	1752.6	25.76	0.377			PASS
HSDPA	1312	1712.4	24.75	0.299	30	1	PASS
	1413	1732.6	24.78	0.301			PASS
	1513	1752.6	24.69	0.294			PASS
DC-HSD PA	1312	1712.4	24.63	0.290	30	1	PASS
	1413	1732.6	24.60	0.288			PASS
	1513	1752.6	24.54	0.284			PASS
HSUPA	1312	1712.4	24.67	0.293	30	1	PASS
	1413	1732.6	24.73	0.297			PASS
	1513	1752.6	24.67	0.293			PASS
HSPA+	1312	1712.4	24.75	0.299	30	1	PASS
	1413	1732.6	24.74	0.298			PASS
	1513	1752.6	24.66	0.292			PASS
Note 1: For the HSDPA and HSUPA mode, all the subtests were tested and just the worst data were recorded in this report.							





WCDMA Band II							
Band	Channel	Frequency (MHz)	Measured E.I.R.P.		Limit		Verdict
			dBm	W	dBm	W	
WCDMA	9262	1852.4	27.42	0.552	33	2	PASS
	9400	1880.0	27.49	0.561			PASS
	9538	1907.6	27.47	0.558			PASS
HSDPA	9262	1852.4	26.36	0.433	33	2	PASS
	9400	1880.0	26.52	0.449			PASS
	9538	1907.6	26.50	0.447			PASS
DC-HSD PA	9262	1852.4	26.39	0.436	33	2	PASS
	9400	1880.0	26.51	0.448			PASS
	9538	1907.6	26.53	0.450			PASS
HSUPA	9262	1852.4	26.39	0.436	33	2	PASS
	9400	1880.0	26.52	0.449			PASS
	9538	1907.6	26.52	0.449			PASS
HSPA+	9262	1852.4	26.40	0.437	33	2	PASS
	9400	1880.0	26.47	0.444			PASS
	9538	1907.6	26.34	0.431			PASS
Note 1: For the HSDPA and HSUPA mode, all the subtests were tested and just the worst data were recorded in this report.							




2.8. Radiated Out of Band Emissions

2.8.1. Requirement


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \cdot \log(P)$ dB. This calculated to be -13dBm. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency.

2.8.2. Test Description



(For the test frequency from 30MHz to 1GHz)





(For the test frequency above 1GHz)

The EUT is located in a 3m Full-Anechoic Chamber, the cable loss, air loss and so on of the site as factors are pre-calibrated using the "Substitution" method, and calculated to correct the reading. A call is established between the EUT and the SS via a Common Antenna. The EUT is commanded by the SS to operate at the maximum and minimum output power and only the test result of the maximum output power was recorded.

In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground and the Turn Table is actuated to turn from 0° to 360° to determine the maximum value of the radiated power. The emission levels at both horizontal and vertical polarizations should be tested. The Filters consists of Notch Filters and High Pass Filter.

Note: When doing measurements above 1GHz, the EUT has been within the 3dB cone width of the horn antenna during horizontal antenna.

2.8.3.Test Procedure

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements.



2.8.4.Test Result

Note1: The power of the EUT transmitting frequency should be ignored.

Note2: All test mode and condition mentioned were considered and evaluated respectively by performing full test, only the worst data were recorded and reported.


Note3: All spurious emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note4: N/A means the frequency is the basic frequency or the base station frequency, they are no need to verdict.

Note5: The amplitude of emissions(18GHz to 10th harmonics) which are attenuated more than 20 dB below the limit are not be reported.


WCDMA Band V(WCDMA)

Plot for Low Channel



Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
188.6999	-41.55	-61.09	-19.5	-13.0	48.1	Horizontal	PK	PASS
236.9598	-45.83	-61.17	-15.3	-13.0	48.2	Horizontal	PK	PASS
825.3428	-44.49	-50.28	-5.8	-	-	Horizontal	PK	NA
872.5841	-45.53	-50.36	-4.8	-	-	Horizontal	PK	NA
2955.5911	-59.90	-44.75	15.2	-13.0	31.8	Horizontal	PK	PASS
12630.556	-69.05	-46.09	23.0	-13.0	33.1	Horizontal	PK	PASS






Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
31.8431	-36.94	-61.52	-24.6	-13.0	48.5	Vertical	PK	PASS
91.8406	-42.13	-64.09	-22.0	-13.0	51.1	Vertical	PK	PASS
825.2943	-53.50	-59.41	-5.9	-	-	Vertical	PK	NA
872.5356	-32.25	-36.99	-4.7	-	-	Vertical	PK	NA
2994.3989	-59.58	-42.94	16.6	-13.0	29.9	Vertical	PK	PASS
11138.244	-67.07	-45.20	21.9	-13.0	32.2	Vertical	PK	PASS




Plot for Mid Channel



Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
31.2126	-31.46	-46.63	-15.2	-13.0	33.6	Horizontal	PK	PASS
237.2509	-46.08	-61.44	-15.4	-13.0	48.4	Horizontal	PK	PASS
835.4313	-46.42	-51.98	-5.6	-	-	Horizontal	PK	NA
880.49	-45.03	-49.78	-4.8	-	-	Horizontal	PK	NA
2987.9976	-59.62	-44.81	14.8	-13.0	31.8	Horizontal	PK	PASS
10521.526	-65.69	-45.88	19.8	-13.0	32.9	Horizontal	PK	PASS






Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
40.622	-43.47	-65.11	-21.6	-13.0	52.1	Vertical	PK	PASS
483.3522	-51.33	-63.93	-12.6	-13.0	50.9	Vertical	PK	PASS
835.4313	-54.11	-59.96	-5.9	-	-	Vertical	PK	NA
881.1206	-33.27	-37.75	-4.5	-	-	Vertical	PK	NA
2998.7998	-60.25	-43.12	17.1	-13.0	30.1	Vertical	PK	PASS
11079.741	-67.56	-45.24	22.3	-13.0	32.2	Vertical	PK	PASS




Plot for High Channel



Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
237.3479	-45.87	-61.24	-15.4	-13.0	48.2	Horizontal	PK	PASS
483.5947	-49.94	-62.57	-12.6	-13.0	49.6	Horizontal	PK	PASS
847.8479	-43.11	-48.33	-5.2	-	-	Horizontal	PK	NA
891.5001	-43.82	-48.51	-4.7	-	-	Horizontal	PK	NA
2959.1918	-59.64	-44.55	15.1	-13.0	31.6	Horizontal	PK	PASS
12536.464	-69.34	-45.99	23.4	-13.0	33.0	Horizontal	PK	PASS






Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
40.0885	-41.60	-63.42	-21.8	-13.0	50.4	Vertical	PK	PASS
246.5148	-47.03	-65.21	-18.2	-13.0	52.2	Vertical	PK	PASS
847.7994	-51.99	-57.54	-5.6	-	-	Vertical	PK	NA
890.045	-31.71	-36.16	-4.5	-	-	Vertical	PK	NA
2997.5995	-60.37	-43.37	17.0	-13.0	30.4	Vertical	PK	PASS
11097.292	-67.27	-44.87	22.4	-13.0	31.9	Vertical	PK	PASS




WCDMA Band IV(WCDMA)

Plot for Low Channel



Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
34.2197	-42.85	-58.09	-15.2	-13.0	45.1	Horizontal	PK	PASS
180.8425	-37.84	-58.97	-21.1	-13.0	46.0	Horizontal	PK	PASS
485.0012	-46.82	-59.97	-13.2	-13.0	47.0	Horizontal	PK	PASS
1711.3423	-32.30	-28.97	3.3	-	-	Horizontal	PK	NA
2112.6225	-48.50	-42.71	5.8	-	-	Horizontal	PK	NA
3427.3468	-52.52	-52.08	0.4	-13.0	39.1	Horizontal	PK	PASS
5141.0201	-54.51	-48.84	5.7	-13.0	35.8	Horizontal	PK	PASS
17676.467	-69.72	-44.62	25.1	-13.0	31.6	Horizontal	PK	PASS






Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
44.3082	-36.30	-56.74	-20.4	-13.0	43.7	Vertical	PK	PASS
248.6974	-43.70	-62.16	-18.5	-13.0	49.2	Vertical	PK	PASS
1711.3423	-45.60	-42.12	3.5	-	-	Vertical	PK	NA
2111.8224	-37.84	-32.26	5.6	-	-	Vertical	PK	NA
5141.4488	-53.68	-48.46	5.2	-13.0	35.5	Vertical	PK	PASS
17357.734	-68.98	-44.25	24.7	-13.0	31.3	Vertical	PK	PASS




Plot for Mid Channel



Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
151.4501	-35.57	-60.88	-25.3	-13.0	47.9	Horizontal	PK	PASS
184.7227	-39.61	-60.06	-20.5	-13.0	47.1	Horizontal	PK	PASS
485.0983	-48.11	-61.26	-13.2	-13.0	48.3	Horizontal	PK	PASS
1741.3483	-34.50	-31.52	3.0	-	-	Horizontal	PK	NA
2139.828	-49.77	-43.75	6.0	-	-	Horizontal	PK	NA
3482.2117	-50.64	-49.73	0.9	-13.0	36.7	Horizontal	PK	PASS
5223.3176	-54.52	-49.32	5.2	-13.0	36.3	Horizontal	PK	PASS
17329.893	-68.75	-44.50	24.3	-13.0	31.5	Horizontal	PK	PASS






Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
197.8184	-41.65	-63.23	-21.6	-13.0	50.2	Vertical	PK	PASS
246.2723	-45.17	-63.69	-18.5	-13.0	50.7	Vertical	PK	PASS
1741.3483	-47.09	-43.66	3.4	-	-	Vertical	PK	NA
2141.0282	-39.10	-33.22	5.9	-	-	Vertical	PK	NA
5217.3168	-52.69	-47.74	5.0	-13.0	34.7	Vertical	PK	PASS
16593.063	-70.15	-44.32	25.8	-13.0	31.3	Vertical	PK	PASS




Plot for High Channel



Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
184.6257	-40.65	-61.12	-20.5	-13.0	184.6257	Horizontal	PK	PASS
237.6874	-45.33	-61.15	-15.8	-13.0	237.6874	Horizontal	PK	PASS
484.8072	-48.67	-61.84	-13.2	-13.0	484.8072	Horizontal	PK	PASS
1750.9502	-42.76	-39.84	2.9	-	1750.950	Horizontal	PK	NA
2152.6305	-50.14	-44.11	6.0	-	2152.630	Horizontal	PK	NA
3502.3575	-49.51	-48.44	1.1	-13.0	3502.357	Horizontal	PK	PASS
5254.1792	-53.76	-48.47	5.3	-13.0	5254.179	Horizontal	PK	PASS
12498.019	-68.26	-44.96	23.3	-13.0	12498.01	Horizontal	PK	PASS






Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
36.3053	-41.01	-64.14	-23.1	-13.0	51.1	Vertical	PK	PASS
245.9328	-45.93	-64.47	-18.5	-13.0	51.5	Vertical	PK	PASS
1750.9502	-54.91	-51.44	3.5	-	-	Vertical	PK	NA
2151.0302	-39.50	-33.78	5.7	-	-	Vertical	PK	NA
5253.7505	-51.18	-46.11	5.1	-13.0	33.1	Vertical	PK	PASS
17278.051	-69.22	-44.74	24.5	-13.0	31.7	Vertical	PK	PASS




WCDMA Band II(WCDMA)

Plot for Low Channel



Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
58.7134	-43.32	-60.10	-16.8	-13.0	47.1	Horizontal	PK	PASS
188.4574	-33.81	-53.64	-19.8	-13.0	40.6	Horizontal	PK	PASS
484.7587	-44.94	-58.13	-13.2	-13.0	45.1	Horizontal	PK	PASS
1851.7704	-31.58	-27.28	4.3	-	-	Horizontal	PK	NA
1932.9866	-47.39	-43.42	4.0	-	-	Horizontal	PK	NA
3707.6725	-53.62	-51.92	1.7	-13.0	38.9	Horizontal	PK	PASS
5554.222	-51.47	-44.80	6.7	-13.0	31.8	Horizontal	PK	PASS
17896.315	-69.52	-45.03	24.5	-13.0	32.0	Horizontal	PK	PASS






Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
58.6164	-43.44	-61.32	-17.9	-13.0	48.3	Vertical	PK	PASS
246.5148	-38.73	-57.30	-18.6	-13.0	44.3	Vertical	PK	PASS
1851.7704	-42.72	-38.43	4.3	-	-	Vertical	PK	NA
1933.7868	-36.66	-32.77	3.9	-	-	Vertical	PK	NA
5555.5079	-50.96	-44.57	6.4	-13.0	31.6	Vertical	PK	PASS
16622.824	-70.15	-44.32	25.8	-13.0	31.3	Vertical	PK	PASS




Plot for Mid Channel



Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
181.2306	-31.53	-52.61	-21.1	-13.0	39.6	Horizontal	PK	PASS
486.2138	-44.01	-57.13	-13.1	-13.0	44.1	Horizontal	PK	PASS
1878.9758	-38.30	-33.05	5.3	-	-	Horizontal	PK	NA
1961.3923	-48.88	-44.37	4.5	-	-	Horizontal	PK	NA
7947.4379	-62.18	-49.03	13.2	-13.0	36.0	Horizontal	PK	PASS
17947.197	-68.60	-44.43	24.2	-13.0	31.4	Horizontal	PK	PASS






Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
59.053	-43.14	-61.13	-18.0	-13.0	48.1	Vertical	PK	PASS
247.9214	-38.83	-57.36	-18.5	-13.0	44.4	Vertical	PK	PASS
1878.9758	-47.86	-42.79	5.1	-	-	Vertical	PK	NA
1959.792	-36.58	-32.39	4.2	-	-	Vertical	PK	NA
7300.852	-62.72	-50.81	11.9	-13.0	37.8	Vertical	PK	PASS
17320.772	-69.14	-44.51	24.6	-13.0	31.5	Vertical	PK	PASS




Plot for High Channel



Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
183.0737	-35.90	-56.66	-20.8	-13.0	43.7	Horizontal	PK	PASS
484.8072	-46.26	-59.45	-13.2	-13.0	46.5	Horizontal	PK	PASS
1906.5813	-29.55	-25.27	4.3	-	-	Horizontal	PK	NA
1986.1972	-48.63	-44.19	4.4	-	-	Horizontal	PK	NA
8083.7634	-63.47	-49.94	13.5	-13.0	36.9	Horizontal	PK	PASS
17932.317	-68.03	-43.76	24.3	-13.0	30.8	Horizontal	PK	PASS





Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
244.6232	-42.28	-60.89	-18.6	-13.0	47.9	Vertical	PK	PASS
485.2923	-48.14	-61.32	-13.2	-13.0	48.3	Vertical	PK	PASS
1906.5813	-39.16	-34.15	5.0	-	-	Vertical	PK	NA
1986.1972	-35.43	-30.87	4.6	-	-	Vertical	PK	NA
8004.5602	-62.69	-49.71	13.0	-13.0	36.7	Vertical	PK	PASS
17979.359	-68.12	-43.98	24.1	-13.0	31.0	Vertical	PK	PASS





Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test Items	Uncertainty
Output Power	$\pm 2.22\text{dB}$
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77\text{dB}$
Radiated Emission	$\pm 2.95\text{dB}$

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$





Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.





4. Test Equipment Utilized

4.1 Conducted Test Equipment

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY51511149	N9020A	Agilent	2024.06.19	2025.06.18
Communication Test Station	6200995016	MT8820C	Anritsu	2024.09.11	2025.09.10
Temperature Chamber	S022177101 00089002	KMT-36LF 1A0	KOMEG	2024.09.11	2025.09.10

4.2 List of Software Used

Description	Manufacturer	Software Version
TS+ -[JS36-RSE]	Tonscend	5.0.0



**4.3 Radiated Test Equipment**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
System Simulator	152038	CMW500	R&S	2024.09.11	2025.09.10
Receiver	MY56060145	N9020A	Agilent	2024.05.30	2025.05.29
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna - Horn	9120D-963	BBHA 9120D	Schwarzbeck	2024.06.22	2025.06.21
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-K K-0.5	Qualwave	2024.07.03	2025.07.02
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-K KF-2	Qualwave	2024.07.03	2025.07.02
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2024.05.30	2025.05.29
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2024.05.30	2025.05.29
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118- 40C-S	Decentest	2024.05.30	2025.05.29
Notch Filter	N/A	WRCGV-W Band V	Wainwright	N/A	N/A
Notch Filter	N/A	WRCGV-W Band IV	Wainwright	N/A	N/A
Notch Filter	N/A	WRCGV-W Band II	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2025.04.19	2028.04.18
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.11.30	2025.11.29

END OF REPORT

