

acknowledgement

SPECIFICATION FOR

CUSTOMER: JI WU

CUS T P /N :

TX P /N : TX -D 50*5.3*0.8-6.5UH

DESC: 20.5*41-0.08*105P -10TS -40mm -
D 50* 5.3 * 0.8Double slot outlet with backing tape-6.5 uh

DATE : 2024/05/27

Version : A .0

P R EPAREDBY	CHECKED B Y	APP ROVEDBY	CUSTOMER APPROVE
Chengjia Chen	Yan Zhang	Yongjun Luo	


Shenzhen Tianxia Technology Co., LTD

Address: Room 523-525,
C 33 Science and TechnologyInnovation Park,
District 33, Bao'an District,Shenzhen City

Tel: 18718699959

[illegible]

S PECIFICATION

DESC	20.5*41-0.08 * 1 0 5 P-10TS- 40mm-D 50* 5.3 * 0.8 Double channel outlet tape back glue- 6.5 uh	Rev : A.0	CUST:	
			Customer material number CUST P / N:	
1. Dimension DIMENSION: (mm)			A The inner hole of the magnetic plate	5.3±0.3mm
			B coil inner diameter	20.5±0.3mm
			C The coiled-coil outer diameter	41±0.5mm
			D Magnetic sheet outer diameter	50±2mm
			E length of lead	40±2mm
			The length of the F dip tin	4mmMAX
			T-sheet thickness	0.8±0.05mm
			H aggregate thickness (excluding lead lines)	2.2mmMAX
			3. Winding parameter Winding Specification:	

NO .	TERMINA		WI RE	T u rns	Winding Direction
1	L	S F	0.08*105P	10Ts	ant iclockwise

4. Electrical characteristics E LECTRICAL CHARACTERISTICS:
Temperature TEMPERATURE: 25 ± 10°C, humidity RELATIVE HUMIDITY: 65 ± 20%
orde

r num ber NO.	The Proje ct ITE M	Terminal, TERMINA L	standard SPECIFICATIO N	test condition TEST FREQU ENCY	measuring and test instruments TEST EQUIP MENTS
1	IND .	S -F	4.0 uH ± 20%, individual coil	100KHz/1.0V	LCR METER 106X
2	IND .	S -F	6.5 uH ± 10% tape magnetic chip	100KHz/1.0V	LCR METER 106X
3	DCR	S -F	600mΩ Max	100KHz/1.0V	LCR METER 106X

PREPARED BY / DATE		CHECKED BYDATE	
Chengjia Chen2024 / 05/ 2 7		Yan Zhang 2024 / 05/ 2 7	