


深圳市雨辰科技有限公司

Shenzhen Yuchen Technology Co.,Ltd.

Antenna test report

			NX3		2022. 10. 10
RF Engineer	Wang Jiaxi	Structural engineer	Zhou Lei	Frequency band	2400~2500MHz




E5071C Network Analyzer


1 Active Ch/Trace 2 Response 3 Stimulus 4 Mkr/Analysis 5 Instr State

Resize


Tr1 S11 Log Mag 10.00dB/ Ref 0.000dB [F1]



Tr2 S11 Smith (R+jX) Scale 1.000U [F1]



Tr3 S11 SWR 1.000/ Ref 1.000 [F1]



1 Center 2.45 GHz

IFBW 70 kHz

Span 1 GHz Cor |

Format

SWR

Log Mag

Phase

Group Delay

Smith

Polar

Lin Mag

SWR

Real

Imaginary

Expand
Phase


Positive
Phase

Return



Frequency ID	1	2	3	4	5	6	7	8	9	10	11
Frequency (MHz)	2400.0	2410.0	2420.0	2430.0	2440.0	2450.0	2460.0	2470.0	2480.0	2490.0	2500.0
Efficiency (dBi)	-8.42	-8.38	-8.34	-8.53	-8.62	-8.77	-8.84	-8.85	-8.79	-9.20	-9.53
Gain (dBi)	-3.45	-3.48	-3.46	-3.64	-3.69	-3.76	-3.88	-4.12	-4.36	-4.91	-5.01
Efficiency (%)	14.39	14.53	14.66	14.02	13.73	13.28	13.08	13.04	13.20	12.03	11.15
Directivity (dB)	4.97	4.89	4.88	4.90	4.93	5.01	4.96	4.72	4.43	4.29	4.52
Peak Gain Position (Theta)	98.00	98.00	98.00	98.00	98.00	98.00	98.00	98.00	98.00	97.00	97.00
Peak Gain Position (Phi)	332.00	333.00	333.00	332.00	333.00	334.00	337.00	338.00	338.00	336.00	333.00
Efficiency ThetaPol (%)	10.97	11.11	11.19	10.72	10.46	10.09	9.97	9.73	9.69	8.73	8.28
Efficiency PhiPol (%)	3.42	3.42	3.47	3.29	3.27	3.19	3.11	3.30	3.52	3.29	2.87
Upper Hem. Efficiency (%)	7.29	7.47	7.60	7.30	7.17	6.89	6.64	6.50	6.54	5.92	5.52
Lower Hem. Efficiency (%)	7.10	7.06	7.05	6.71	6.56	6.39	6.44	6.54	6.66	6.11	5.63

VER7[illegible]


2400.0MHz H+V, Eff: 14.4%




Back View




2400.0MHz Total(E2-YZ), Max=-4.73dBi





Total(H-XY), Max=-3.90dBi, CirD=8.87




2450.0MHz H+V, Eff: 13.3%




Back View




2450.0MHz Total(E2-YZ), Max=-5.22dBi





Total(H-XY), Max=-4.28dBi, CirD=9.36




2500.0MHz H+V, Eff: 11.1%




Back View



2500.0MHz Total(E2-YZ), Max=-6.42dBi



Total(H-XY), Max=-5.31dBi, CirD=8.95



Frequency ID	1	
Frequency (MHz)	2400.0	
Efficiency (dBi)	-8.42	
Gain (dBi)	-3.45	
Efficiency (%)	14.39	
Directivity (dB)	4.97	
Peak Gain Position (Theta)	98.00	
Peak Gain Position (Phi)	332.00	
Efficiency ThetaPol (%)	10.97	
Efficiency PhiPol (%)	3.42	
Upper Hem. Efficiency (%)	7.29	
Lower Hem. Efficiency (%)	7.10	

2400.0MHz H+V, Eff: 14.4%

