

11N20MIMO	5180	3.67	≤9.23	PASS
	5220	3.27	≤9.23	PASS
	5240	3.71	≤9.23	PASS
	5260	3.69	≤9.23	PASS
	5300	4.82	≤9.23	PASS
	5320	4.77	≤9.23	PASS
	5500	4.94	≤9.23	PASS
	5580	4.89	≤9.23	PASS
	5700	4.07	≤9.23	PASS
	5745	1.03	≤28.23	PASS
	5785	1.12	≤28.23	PASS
	5825	1.87	≤28.23	PASS
11N40MIMO	5190	1.68	≤9.23	PASS
	5230	1.38	≤9.23	PASS
	5270	1.72	≤9.23	PASS
	5310	2.79	≤9.23	PASS
	5510	2.84	≤9.23	PASS
	5550	2.67	≤9.23	PASS
	5670	2.43	≤9.23	PASS
	5755	-1.40	≤28.23	PASS
11AC20MIMO	5795	-0.74	≤28.23	PASS
	5180	3.77	≤9.23	PASS
	5220	3.27	≤9.23	PASS
	5240	3.77	≤9.23	PASS
	5260	3.78	≤9.23	PASS
	5300	4.81	≤9.23	PASS
	5320	4.84	≤9.23	PASS
	5500	4.92	≤9.23	PASS
	5580	4.86	≤9.23	PASS
	5700	4.07	≤9.23	PASS
	5745	1.03	≤28.23	PASS
	5785	1.37	≤28.23	PASS
11AC40MIMO	5825	1.85	≤28.23	PASS
	5190	1.72	≤9.23	PASS
	5230	1.32	≤9.23	PASS
	5270	1.67	≤9.23	PASS
	5310	2.76	≤9.23	PASS
	5510	2.86	≤9.23	PASS
	5550	2.81	≤9.23	PASS
	5670	2.33	≤9.23	PASS
11AC80MIMO	5755	-1.23	≤28.23	PASS
	5795	-1.12	≤28.23	PASS
	5210	-1.93	≤9.23	PASS
	5290	-1.03	≤9.23	PASS
	5530	-0.32	≤9.23	PASS
11AX20MIMO	5610	-0.97	≤9.23	PASS
	5775	-4.54	≤28.23	PASS
	5180	3.44	≤9.23	PASS
	5220	2.98	≤9.23	PASS
	5240	3.37	≤9.23	PASS
	5260	3.41	≤9.23	PASS
	5300	4.63	≤9.23	PASS
	5320	4.65	≤9.23	PASS
	5500	4.67	≤9.23	PASS
	5580	4.64	≤9.23	PASS
	5700	3.88	≤9.23	PASS
	5745	0.55	≤28.23	PASS
11AX40MIMO	5785	0.89	≤28.23	PASS
	5825	1.53	≤28.23	PASS
	5190	1.47	≤9.23	PASS
	5230	1.21	≤9.23	PASS

	5270	1.37	≤ 9.23	PASS
	5310	2.55	≤ 9.23	PASS
	5510	2.70	≤ 9.23	PASS
	5550	2.63	≤ 9.23	PASS
	5670	2.23	≤ 9.23	PASS
	5755	-1.45	≤ 28.23	PASS
	5795	-1.00	≤ 28.23	PASS
11AX80MIMO	5210	-1.63	≤ 9.23	PASS
	5290	-0.78	≤ 9.23	PASS
	5530	-0.24	≤ 9.23	PASS
	5610	-0.61	≤ 9.23	PASS
	5775	-4.21	≤ 28.23	PASS

Note: 1. The Result and Limit Unit is dBm/500 kHz in the band 5.725–5.85 GHz.
 2. The Duty Cycle Factor and RBW Factor is compensated in the graph.















































