

RF Exposure Evaluation

FCC ID: 2AZP4-C9

1. Client Information

Applicant	:	Shenzhen Wellstec Communications Co., Ltd
Address	:	608,6/F, Building A, UNIS Cyber Port, Hi-Tech park, Nanshan District, Shenzhen, China
Manufacturer	:	Shenzhen Wellstec Communications Co., Ltd
Address	:	608,6/F, Building A, UNIS Cyber Port, Hi-Tech park, Nanshan District, Shenzhen, China

2. General Description of EUT

EUT Name	:	Smart Watch
Model(s) No.	:	C9, C9 Pro
Model Different	:	All modles are based on the same circuit and structure, the differenes are size.
Sample ID	:	TBBJ-20210401-02-1# & TBBJ-20210401-02-2#
Product Description	Operation Frequency:	Bluetooth 5.0(BLE): 2402MHz~2480MHz
	Number of Channel:	Bluetooth 5.0(BLE): 40 channels
	RF Output Power:	0.963dBm (Max)
	Antenna Gain:	1.0 dBi Wire Antenna
	Modulation Type:	GFSK
	Bit Rate of Transmitter:	1Mbps
Power Rating	:	Input: DC 5V DC 3.7V by 250mAh Li-ion battery
Software Version	:	N/A
Hardware Version	:	N/A
Connecting I/O Port(S)	:	Please refer to the User's Manual
Remark: The antenna gain provided by the applicant, the adapter and verified for the RF conduction test and adapter provided by TOBY test lab.		

Note: More test information about the EUT please refer the RF Test Report.

TB-RF-074-1.0

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

- [(max. power of channel, including tune-up tolerance, mW)/(min. test separation, mm)] * $\sqrt{f_{\text{GHz}}}$ ≤ 3.0 for 1-g SAR

- [(max. power of channel, including tune-up tolerance, mW)/(min. test separation, mm)] * $\sqrt{f_{\text{GHz}}}$ $\leq 7.5.0$ for 10-g SAR

2. Calculation:

Test separation: 5mm

BLE Mode (1Mbps)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-0.244	0±1	1	1.26	0.39	3.0
2.442	0.766	0±1	1	1.26	0.39	3.0
2.480	0.963	0±1	1	1.26	0.39	3.0

Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

-----END OF REPORT-----