# TEST Report

| | |
|---|---|
| **Applicant:** | ZTARX CORPORATION LIMITED |
| **Address of Applicant:** | 317, Bldg 3,108 Huarong Rd, Longhua New District, Shenzhen, China |
| **Manufacturer :** | ZTARX CORPORATION LIMITED |
| **Address of Manufacturer :** | 317, Bldg 3,108 Huarong Rd, Longhua New District, Shenzhen, China |
| **Equipment Under Test (EUT)** | |
| Product Name: | Multifunctional LED Light |
| Model No.: | V11 |
| Series model: | S07,J22,V03 |
| Trade Mark: | Ztarx |
| FCC ID: | 2AZPG-V11 |
| **Applicable standards:** | FCC CFR Title 47 Part 15 Subpart C Section 15.247 |
| **Date of sample receipt:** | Apr.12,2021 |
| **Date of Test:** | Apr.12,2021- Apr.21,2021 |
| **Date of report issued:** | Apr.21,2021 |
| **Test Result :** | PASS * |

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

**Robinson Luo**
**Laboratory Manager**

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

## 2 Version

| Version No. | Date | Description |
|---|---|---|
| *00* | *Apr.21,2021* | *Original* |
| | | |
| | | |
| | | |
| | | |

| | | | |
|---|---|---|---|
| ***Tested/ Prepared By*** | ***Project Engineer*** | ***Date:*** | ***Apr.21,2021*** |
| ***Check By:*** | ***Reviewer*** | ***Date:*** | ***Apr.21,2021*** |

# 3 Contents

Page

**1 COVER PAGE ..... 1**

**2 VERSION ..... 2**

**3 CONTENTS ..... 3**

**4 TEST SUMMARY ..... 4**

**5 GENERAL INFORMATION ..... 5**

5.1 GENERAL DESCRIPTION OF EUT ..... 5
5.2 TEST MODE ..... 7
5.3 DESCRIPTION OF SUPPORT UNITS ..... 7
5.4 DEVIATION FROM STANDARDS ..... 7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS ..... 7
5.6 TEST FACILITY ..... 7
5.7 TEST LOCATION ..... 7
5.8 ADDITIONAL INSTRUCTIONS ..... 7

**6 TEST INSTRUMENTS LIST ..... 8**

**7 TEST RESULTS AND MEASUREMENT DATA ..... 10**

7.1 ANTENNA REQUIREMENT ..... 10
7.2 CONDUCTED EMISSIONS ..... 11
7.3 CONDUCTED PEAK OUTPUT POWER ..... 14
7.4 20DB EMISSION BANDWIDTH ..... 15
7.5 FREQUENCIES SEPARATION ..... 18
7.6 HOPPING CHANNEL NUMBER ..... 20
7.7 DWELL TIME ..... 22
7.8 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE ..... 26
7.9 BAND EDGE ..... 27
*7.9.1 Conducted Emission Method ..... 27*
*7.9.2 Radiated Emission Method ..... 30*
7.10 SPURIOUS EMISSION ..... 33
*7.10.1 Conducted Emission Method ..... 33*
*7.10.2 Radiated Emission Method ..... 37*

**8 TEST SETUP PHOTO ..... 45**

**9 EUT CONSTRUCTIONAL DETAILS ..... 45**

# 4 Test Summary

| Test Item | Section in CFR 47 | Result |
|---|---|---|
| Antenna Requirement | 15.203/15.247 (c) | Pass |
| AC Power Line Conducted Emission | 15.207 | Pass |
| Conducted Peak Output Power | 15.247 (b)(1) | Pass |
| 20dB Occupied Bandwidth | 15.247 (a)(1) | Pass |
| Carrier Frequencies Separation | 15.247 (a)(1) | Pass |
| Hopping Channel Number | 15.247 (a)(1) | Pass |
| Dwell Time | 15.247 (a)(1) | Pass |
| Pseudorandom Frequency Hopping Sequence | 15.247(b)(4) | Pass |
| Radiated Emission | 15.205/15.209 | Pass |
| Band Edge | 15.247(d) | Pass |

*Remarks:*

1. *Pass: The EUT complies with the essential requirements in the standard.*
2. *Test according to ANSI C63.10:2013*

**Measurement Uncertainty**

| Test Item | Frequency Range | Measurement Uncertainty | Notes |
|---|---|---|---|
| Radiated Emission | 30MHz-200MHz | 3.8039dB | (1) |
| Radiated Emission | 200MHz-1GHz | 3.9679dB | (1) |
| Radiated Emission | 1GHz-18GHz | 4.29dB | (1) |
| Radiated Emission | 18GHz-40GHz | 3.30dB | (1) |
| AC Power Line Conducted Emission | 0.15MHz ~ 30MHz | 3.44dB | (1) |
| Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%. | | | |

# 5 General Information

## 5.1 General Description of EUT

| | |
|---|---|
| Product Name: | Multifunctional LED Light |
| Model No.: | V11 |
| Series model: | S07,J22,V03 |
| Test sample(s) ID: | GTSL202104000166-1(Engineer sample)<br>GTSL202104000166-2(Normal sample) |
| Operation Frequency: | 2402MHz~2480MHz |
| Channel numbers: | 79 |
| Channel separation: | 1MHz |
| Modulation type: | GFSK, π /4-DQPSK |
| Antenna Type: | PCB Antenna |
| Antenna gain: | -0.58dBi |
| Power supply: | DC 3.7V Form Battery and DC 5V From External Circuit |
| Adapter Information (auxiliary test equipment supplied by test Lab) | Mode: CD122<br>Input: AC100-240V, 50/60Hz, 500mA<br>Output: DC 5V, 2A |

| Operation Frequency each of channel | | | | | | | |
|---|---|---|---|---|---|---|---|
| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 1 | 2402MHz | 21 | 2422MHz | 41 | 2442MHz | 61 | 2462MHz |
| 2 | 2403MHz | 22 | 2423MHz | 42 | 2443MHz | 62 | 2463MHz |
| 3 | 2404MHz | 23 | 2424MHz | 43 | 2444MHz | 63 | 2464MHz |
| 4 | 2405MHz | 24 | 2425MHz | 44 | 2445MHz | 64 | 2465MHz |
| 5 | 2406MHz | 25 | 2426MHz | 45 | 2446MHz | 65 | 2466MHz |
| 6 | 2407MHz | 26 | 2427MHz | 46 | 2447MHz | 66 | 2467MHz |
| 7 | 2408MHz | 27 | 2428MHz | 47 | 2448MHz | 67 | 2468MHz |
| 8 | 2409MHz | 28 | 2429MHz | 48 | 2449MHz | 68 | 2469MHz |
| 9 | 2410MHz | 29 | 2430MHz | 49 | 2450MHz | 69 | 2470MHz |
| 10 | 2411MHz | 30 | 2431MHz | 50 | 2451MHz | 70 | 2471MHz |
| 11 | 2412MHz | 31 | 2432MHz | 51 | 2452MHz | 71 | 2472MHz |
| 12 | 2413MHz | 32 | 2433MHz | 52 | 2453MHz | 72 | 2473MHz |
| 13 | 2414MHz | 33 | 2434MHz | 53 | 2454MHz | 73 | 2474MHz |
| 14 | 2415MHz | 34 | 2435MHz | 54 | 2455MHz | 74 | 2475MHz |
| 15 | 2416MHz | 35 | 2436MHz | 55 | 2456MHz | 75 | 2476MHz |
| 16 | 2417MHz | 36 | 2437MHz | 56 | 2457MHz | 76 | 2477MHz |
| 17 | 2418MHz | 37 | 2438MHz | 57 | 2458MHz | 77 | 2478MHz |
| 18 | 2419MHz | 38 | 2439MHz | 58 | 2459MHz | 78 | 2479MHz |
| 19 | 2420MHz | 39 | 2440MHz | 59 | 2460MHz | 79 | 2480MHz |
| 20 | 2421MHz | 40 | 2441MHz | 60 | 2461MHz | | |

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Channel | Frequency |
|---|---|
| The lowest channel | 2402MHz |
| The middle channel | 2441MHz |
| The Highest channel | 2480MHz |

## 5.2 Test mode

| | |
|---|---|
| Transmitting mode | Keep the EUT in continuously transmitting mode. |
| *Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.* | |

## 5.3 Description of Support Units

None.

## 5.4 Deviation from Standards

None.

## 5.5 Abnormalities from Standard Conditions

None.

## 5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383.

● **IC —Registration No.: 9079A**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A

● **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

## 5.7 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.
Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102
Tel: 0755-27798480
Fax: 0755-27798960

## 5.8 Additional Instructions

| | |
|---|---|
| Test Software | Special AT test command provided by manufacturer to Keep the EUT in continuously transmitting mode and hopping mode |
| Power level setup | Default |

# 6 Test Instruments list

| Radiated Emission: | | | | | | |
|---|---|---|---|---|---|---|
| **Item** | **Test Equipment** | **Manufacturer** | **Model No.** | **Inventory No.** | **Cal.Date (mm-dd-yy)** | **Cal.Due date (mm-dd-yy)** |
| 1 | 3m Semi- Anechoic Chamber | ZhongYu Electron | 9.2(L)*6.2(W)* 6.4(H) | GTS250 | July. 02 2020 | July. 01 2025 |
| 2 | Control Room | ZhongYu Electron | 6.2(L)*2.5(W)* 2.4(H) | GTS251 | N/A | N/A |
| 3 | EMI Test Receiver | Rohde & Schwarz | ESU26 | GTS203 | June. 25 2020 | June. 24 2021 |
| 4 | BiConiLog Antenna | SCHWARZBECK MESS-ELEKTRONIK | VULB9163 | GTS214 | June. 25 2020 | June. 24 2021 |
| 5 | Double -ridged waveguide horn | SCHWARZBECK MESS-ELEKTRONIK | BBHA 9120 D | GTS208 | June. 25 2020 | June. 24 2021 |
| 6 | Horn Antenna | ETS-LINDGREN | 3160 | GTS217 | June. 25 2020 | June. 24 2021 |
| 7 | EMI Test Software | FARAD | EZ-EMC | N/A | N/A | N/A |
| 8 | Coaxial Cable | GTS | N/A | GTS213 | June. 25 2020 | June. 24 2021 |
| 9 | Coaxial Cable | GTS | N/A | GTS211 | June. 25 2020 | June. 24 2021 |
| 10 | Coaxial cable | GTS | N/A | GTS210 | June. 25 2020 | June. 24 2021 |
| 11 | Coaxial Cable | GTS | N/A | GTS212 | June. 25 2020 | June. 24 2021 |
| 12 | Amplifier(100kHz-3GHz) | HP | 8347A | GTS204 | June. 25 2020 | June. 24 2021 |
| 13 | Amplifier(2GHz-20GHz) | HP | 84722A | GTS206 | June. 25 2020 | June. 24 2021 |
| 14 | Amplifier (18-26GHz) | Rohde & Schwarz | AFS33-18002 650-30-8P-44 | GTS218 | June. 25 2020 | June. 24 2021 |
| 15 | Band filter | Amindeon | 82346 | GTS219 | June. 25 2020 | June. 24 2021 |
| 16 | Power Meter | Anritsu | ML2495A | GTS540 | June. 25 2020 | June. 24 2021 |
| 17 | Power Sensor | Anritsu | MA2411B | GTS541 | June. 25 2020 | June. 24 2021 |
| 18 | Wideband Radio Communication Tester | Rohde & Schwarz | CMW500 | GTS575 | June. 25 2020 | June. 24 2021 |
| 19 | Splitter | Agilent | 11636B | GTS237 | June. 25 2020 | June. 24 2021 |
| 20 | Loop Antenna | ZHINAN | ZN30900A | GTS534 | June. 25 2020 | June. 24 2021 |
| 21 | Breitband hornantenne | SCHWARZBECK | BBHA 9170 | GTS579 | Oct. 18 2020 | Oct. 17 2021 |
| 22 | Amplifier | TDK | PA-02-02 | GTS574 | Oct. 18 2020 | Oct. 17 2021 |
| 23 | Amplifier | TDK | PA-02-03 | GTS576 | Oct. 18 2020 | Oct. 17 2021 |
| 24 | PSA Series Spectrum Analyzer | Rohde & Schwarz | FSP | GTS578 | June. 25 2020 | June. 24 2021 |

| Conducted Emission | | | | | | |
|---|---|---|---|---|---|---|
| **Item** | **Test Equipment** | **Manufacturer** | **Model No.** | **Inventory No.** | **Cal.Date (mm-dd-yy)** | **Cal.Due date (mm-dd-yy)** |
| 1 | Shielding Room | ZhongYu Electron | 7.3(L)x3.1(W)x2.9(H) | GTS252 | May.15 2019 | May.14 2022 |
| 2 | EMI Test Receiver | R&S | ESCI 7 | GTS552 | June. 25 2020 | June. 24 2021 |
| 3 | Coaxial Switch | ANRITSU CORP | MP59B | GTS225 | June. 25 2020 | June. 24 2021 |
| 4 | ENV216 2-L-V-NETZNACHB.DE | ROHDE&SCHWARZ | ENV216 | GTS226 | June. 25 2020 | June. 24 2021 |
| 5 | Coaxial Cable | GTS | N/A | GTS227 | N/A | N/A |
| 6 | EMI Test Software | FARAD | EZ-EMC | N/A | N/A | N/A |
| 7 | Thermo meter | KTJ | TA328 | GTS233 | June. 25 2020 | June. 24 2021 |
| 8 | Absorbing clamp | Elektronik-Feinmechanik | MDS21 | GTS229 | June. 25 2020 | June. 24 2021 |
| 9 | ISN | SCHWARZBECK | NTFM 8158 | GTD565 | June. 25 2020 | June. 24 2021 |

| RF Conducted Test: | | | | | | |
|---|---|---|---|---|---|---|
| **Item** | **Test Equipment** | **Manufacturer** | **Model No.** | **Serial No.** | **Cal.Date (mm-dd-yy)** | **Cal.Due date (mm-dd-yy)** |
| 1 | MXA Signal Analyzer | Agilent | N9020A | GTS566 | June. 25 2020 | June. 24 2021 |
| 2 | EMI Test Receiver | R&S | ESCI 7 | GTS552 | June. 25 2020 | June. 24 2021 |
| 3 | Spectrum Analyzer | Agilent | E4440A | GTS533 | June. 25 2020 | June. 24 2021 |
| 4 | MXG vector Signal Generator | Agilent | N5182A | GTS567 | June. 25 2020 | June. 24 2021 |
| 5 | ESG Analog Signal Generator | Agilent | E4428C | GTS568 | June. 25 2020 | June. 24 2021 |
| 6 | USB RF Power Sensor | DARE | RPR3006W | GTS569 | June. 25 2020 | June. 24 2021 |
| 7 | RF Switch Box | Shongyi | RFSW3003328 | GTS571 | June. 25 2020 | June. 24 2021 |
| 8 | Programmable Constant Temp & Humi Test Chamber | WEWON | WHTH-150L-40-880 | GTS572 | June. 25 2020 | June. 24 2021 |
| 9 | Power Sensor | Agilent | E9300A | GTS589 | June. 25 2020 | June. 24 2021 |
| 10 | Spectrum analyzer | Agilent | N9020A | GTS591 | June. 25 2020 | June. 24 2021 |

| General used equipment: | | | | | | |
|---|---|---|---|---|---|---|
| **Item** | **Test Equipment** | **Manufacturer** | **Model No.** | **Inventory No.** | **Cal.Date (mm-dd-yy)** | **Cal.Due date (mm-dd-yy)** |
| 1 | Humidity/ Temperature Indicator | KTJ | TA328 | GTS243 | June. 25 2020 | June. 24 2021 |
| 2 | Barometer | ChangChun | DYM3 | GTS255 | June. 25 2020 | June. 24 2021 |

# 7 Test results and Measurement Data

## 7.1 Antenna requirement

| **Standard requirement:** | FCC Part15 C Section 15.203 /247(c) |
|---|---|
| **15.203 requirement:**<br>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.<br>**15.247(c) (1)(i) requirement:**<br>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi. | |
| **E.U.T Antenna:** | |
| *The antenna is PCB Antenna, the best case gain of the is -0.58dBi, reference to the appendix II for details* | |

## 7.2 Conducted Emissions

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.207 |
| Test Method: | ANSI C63.10:2013 |
| Test Frequency Range: | 150KHz to 30MHz |
| Class / Severity: | Class B |
| Receiver setup: | RBW=9KHz, VBW=30KHz, Sweep time=auto |
| Limit: | Frequency range (MHz) / Limit (dBuV): Quasi-peak / Average<br>0.15-0.5: 66 to 56* / 56 to 46*<br>0.5-5: 56 / 46<br>5-30: 60 / 50<br>* Decreases with the logarithm of the frequency. |
| Test setup: |  <br>*Remark:*<br>*E.U.T: Equipment Under Test*<br>*LISN: Line Impedence Stabilization Network*<br>*Test table height=0.8m* |
| Test procedure: | 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.<br>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).<br>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement. |
| Test Instruments: | Refer to section 6.0 for details |
| Test mode: | Refer to section 5.2 for details |
| Test environment: | Temp.: 25 °C / Humid.: 52% / Press.: 1012mbar |
| Test voltage: | AC 120V, 60Hz |
| Test results: | Pass |

Remark: Both high and low voltages have been tested to show only the worst low voltage test data.

**Measurement data:**

**Line:**




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Over | |
|---|---|---|---|---|---|---|---|---|
| | | MHz | dBuV | dB | dBuV | dBuV | dB | Detector |
| 1 | | 0.5712 | 28.55 | 10.92 | 39.47 | 56.00 | -16.53 | QP |
| 2 | * | 0.5712 | 23.59 | 10.92 | 34.51 | 46.00 | -11.49 | AVG |
| 3 | | 1.7217 | 27.13 | 10.96 | 38.09 | 56.00 | -17.91 | QP |
| 4 | | 1.7217 | 21.67 | 10.96 | 32.63 | 46.00 | -13.37 | AVG |
| 5 | | 2.8878 | 20.38 | 11.00 | 31.38 | 56.00 | -24.62 | QP |
| 6 | | 2.8878 | 15.08 | 11.00 | 26.08 | 46.00 | -19.92 | AVG |
| 7 | | 3.9945 | 20.18 | 11.06 | 31.24 | 56.00 | -24.76 | QP |
| 8 | | 3.9945 | 4.92 | 11.06 | 15.98 | 46.00 | -30.02 | AVG |
| 9 | | 10.9482 | 20.31 | 11.38 | 31.69 | 60.00 | -28.31 | QP |
| 10 | | 10.9482 | 12.35 | 11.38 | 23.73 | 50.00 | -26.27 | AVG |
| 11 | | 12.7617 | 22.17 | 11.41 | 33.58 | 60.00 | -26.42 | QP |
| 12 | | 12.7617 | 11.69 | 11.41 | 23.10 | 50.00 | -26.90 | AVG |

**Neutral:**




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Over | |
|---|---|---|---|---|---|---|---|---|
| | | MHz | dBuV | dB | dBuV | dBuV | dB | Detector |
| 1 | | 0.5790 | 29.50 | 10.92 | 40.42 | 56.00 | -15.58 | QP |
| 2 | * | 0.5790 | 23.18 | 10.92 | 34.10 | 46.00 | -11.90 | AVG |
| 3 | | 1.7256 | 28.05 | 10.96 | 39.01 | 56.00 | -16.99 | QP |
| 4 | | 1.7256 | 13.36 | 10.96 | 24.32 | 46.00 | -21.68 | AVG |
| 5 | | 2.9502 | 28.31 | 11.00 | 39.31 | 56.00 | -16.69 | QP |
| 6 | | 2.9502 | 16.21 | 11.00 | 27.21 | 46.00 | -18.79 | AVG |
| 7 | | 4.0725 | 29.17 | 11.06 | 40.23 | 56.00 | -15.77 | QP |
| 8 | | 4.0725 | 19.20 | 11.06 | 30.26 | 46.00 | -15.74 | AVG |
| 9 | | 5.2698 | 28.13 | 11.11 | 39.24 | 60.00 | -20.76 | QP |
| 10 | | 5.2698 | 19.75 | 11.11 | 30.86 | 50.00 | -19.14 | AVG |
| 11 | | 7.6254 | 19.20 | 11.24 | 30.44 | 60.00 | -29.56 | QP |
| 12 | | 7.6254 | 9.29 | 11.24 | 20.53 | 50.00 | -29.47 | AVG |

*Notes:*

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Los

## 7.3 Conducted Peak Output Power

| | | | | | | |
|---|---|---|---|---|---|---|
| Test Requirement: | FCC Part15 C Section 15.247 (b)(3) | | | | | |
| Test Method: | ANSI C63.10:2013 | | | | | |
| Limit: | 30dBm(for GFSK),20.97dBm(for EDR) | | | | | |
| Test setup: |  | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test results: | Pass | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |

**Measurement Data**

| Mode | Test channel | Peak Output Power (dBm) | Limit (dBm) | Result |
|---|---|---|---|---|
| GFSK | Lowest | 0.39 | 30.00 | Pass |
| | Middle | 0.20 | | |
| | Highest | -0.47 | | |
| π/4-DQPSK | Lowest | 1.24 | 20.97 | Pass |
| | Middle | 0.97 | | |
| | Highest | 0.22 | | |

## 7.4 20dB Emission Bandwidth

| | | | | | | |
|---|---|---|---|---|---|---|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(2) | | | | | |
| Test Method: | ANSI C63.10:2013 | | | | | |
| Limit: | N/A | | | | | |
| Test setup: |  | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test results: | Pass | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |

**Measurement Data**

| Mode | Test channel | 20dB Emission Bandwidth (MHz) | Result |
|---|---|---|---|
| GFSK | Lowest | 0.958 | Pass |
| | Middle | 0.952 | |
| | Highest | 0.953 | |
| π/4-DQPSK | Lowest | 1.315 | Pass |
| | Middle | 1.314 | |
| | Highest | 1.315 | |

**Test plot as follows:**

| Test mode: | GFSK mode |
|---|---|




Lowest channel




Middle channel




Highest channel

| Test mode: | π/4-DQPSK mode |
|---|---|




Lowest channel




Middle channel




Highest channel

## 7.5 Frequencies Separation

| | | | | | | |
|---|---|---|---|---|---|---|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1) | | | | | |
| Test Method: | ANSI C63.10:2013 | | | | | |
| Receiver setup: | RBW=100KHz, VBW=300KHz, detector=Peak | | | | | |
| Limit: | GFSK: 20dB bandwidth<br>π/4-DQPSK & 8DSK: 0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater) | | | | | |
| Test setup: |  | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test results: | Pass | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |

**Measurement Data**

| Mode | Test channel | Frequencies Separation (MHz) | Limit (kHz) | Result |
|---|---|---|---|---|
| GFSK | Middle | 1.000 | 25KHz or 2/3*20dB bandwidth | Pass |
| π/4-DQPSK | Middle | 0.999 | 25KHz or 2/3*20dB bandwidth | Pass |

Remark: We have tested all mode at high, middle and low channel, and recorded worst case at middle

**Test plot as follows:**

| Modulation mode: | GFSK |
|---|---|




| Test mode: | π/4-DQPSK |
|---|---|



## 7.6 Hopping Channel Number

| | | | | | | |
|---|---|---|---|---|---|---|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1) | | | | | |
| Test Method: | ANSI C63.10:2013 | | | | | |
| Receiver setup: | RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak | | | | | |
| Limit: | 15 channels | | | | | |
| Test setup: |  | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test results: | Pass | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |

**Measurement Data:**

| Mode | Hopping channel numbers | Limit | Result |
|---|---|---|---|
| GFSK | 79 | ≥15 | Pass |
| π/4-DQPSK | 79 | | Pass |

**Test plot as follows:**

| Test mode: | GFSK |
|---|---|




| Test mode: | π/4-DQPSK |
|---|---|



## 7.7 Dwell Time

| | | | | | | |
|---|---|---|---|---|---|---|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1) | | | | | |
| Test Method: | ANSI C63.10:2013 | | | | | |
| Receiver setup: | RBW=1MHz, VBW=1MHz, Span=0Hz, Detector=Peak | | | | | |
| Limit: | 0.4 Second | | | | | |
| Test setup: |  | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test results: | Pass | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |

**Measurement Data**

**GFSK mode:**

| Frequency | Packet | Pulse time (ms) | Dwell time(ms) | Limit(ms) | Result |
|---|---|---|---|---|---|
| 2441MHz | DH1 | 0.395 | 126.400 | 400 | Pass |
| 2441MHz | DH3 | 1.645 | 254.975 | 400 | Pass |
| 2441MHz | DH5 | 2.893 | 280.621 | 400 | Pass |

Note:We have tested all mode at high,middle and low channel,and recoreded worst case at middle channel.

Dwell time=Pulse time (ms) × (1600 ÷ 2 ÷ 79) ×31.6 Second for DH1, 2-DH1

Dwell time=Pulse time (ms) × (1600 ÷ 4 ÷ 79) ×31.6 Second for DH3, 2-DH3

Dwell time=Pulse time (ms) × (1600 ÷ 6 ÷ 79) ×31.6 Second for DH5, 2-DH5

**π/4-DQPSK mode:**

| Frequency | Packet | Pulse time (ms) | Dwell time(ms) | Limit(ms) | Result |
|---|---|---|---|---|---|
| 2441MHz | 2DH1 | 0.401 | 128.320 | 400 | Pass |
| 2441MHz | 2DH3 | 1.655 | 276.385 | 400 | Pass |
| 2441MHz | 2DH5 | 2.899 | 321.789 | 400 | Pass |

Note:We have tested all mode at high,middle and low channel,and recoreded worst case at middle channel.

Dwell time=Pulse time (ms) × (1600 ÷ 2 ÷ 79) ×31.6 Second for DH1, 2-DH1

Dwell time=Pulse time (ms) × (1600 ÷ 4 ÷ 79) ×31.6 Second for DH3, 2-DH3

Dwell time=Pulse time (ms) × (1600 ÷ 6 ÷ 79) ×31.6 Second for DH5, 2-DH5

**Test plot as follows:**

**GFSK mode:**

| Test channel: | 2441MHz |
|---|---|




DH1




DH3




DH5

**π/4-DQPSK mode:**

| Test channel: | 2441MHz |
|---|---|




DH1




DH3




DH5

## 7.8 Pseudorandom Frequency Hopping Sequence

| Test Requirement: | FCC Part15 C Section 15.247 (a)(1)/g/h requirement: |
|---|---|

*a(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.*

*Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.*

*(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.*

*(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.*

**EUT Pseudorandom Frequency Hopping Sequence**

*The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.*

- *Number of shift register stages: 9*
- *Length of pseudo-random sequence: $2^9$ -1 = 511 bits*
- *Longest sequence of zeros: 8 (non-inverted signal)*



*Linear Feedback Shift Register for Generation of the PRBS sequence*

*An example of Pseudorandom Frequency Hopping Sequence as follow:*




*Each frequency used equally on the average by each transmitter.*

*The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.*

*it permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted.*

## 7.9 Band Edge

### 7.9.1 Conducted Emission Method

| | | | | | | |
|---|---|---|---|---|---|---|
| Test Requirement: | FCC Part15 C Section 15.247 (d) | | | | | |
| Test Method: | ANSI C63.10:2013 | | | | | |
| Receiver setup: | RBW=100kHz, VBW=300kHz, Detector=Peak | | | | | |
| Limit: | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. | | | | | |
| Test setup: |  | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test results: | Pass | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |

**Test plot as follows:**

**GFSK Mode:**

| Test channel | Lowest channel |
|---|---|
|  |  |
| No-hopping mode | Hopping mode |





| Test channel: | Highest channel |
|---|---|
|  |  |
| No-hopping mode | Hopping mode |

**π/4-DQPSK Mode:**

| Test channel | Lowest channel |
|---|---|
|  |  |
| No-hopping mode | Hopping mode |





| Test channel: | Highest channel |
|---|---|
|  |  |
| No-hopping mode | Hopping mode |

### 7.9.2 Radiated Emission Method

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.209 and 15.205 |
| Test Method: | ANSI C63.10:2013 |
| Test Frequency Range: | All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed. |
| Test site: | Measurement Distance: 3m |
| Receiver setup: | Frequency / Detector / RBW / VBW / Remark<br>Above 1GHz / Peak / 1MHz / 3MHz / Peak Value<br>Above 1GHz / Peak / 1MHz / 10Hz / Average Value |
| Limit: | Frequency / Limit (dBuV/m @3m) / Remark<br>Above 1GHz / 54.00 / Average Value<br>Above 1GHz / 74.00 / Peak Value |
| Test setup: |  |
| Test Procedure: | 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.<br>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.<br>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.<br>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.<br>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.<br>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. |
| Test Instruments: | Refer to section 6.0 for details |
| Test mode: | Refer to section 5.2 for details |
| Test results: | Pass |
| Test environment: | Temp.: 25 °C / Humid.: 52% / Press.: 1012mbar |

**Measurement Data**

Remark: GFSK, Pi/4 DQPSK all have been tested, only worse case GFSK is reported.

Operation Mode: GFSK TX Low channel(2402MHz)

Horizontal (Worst case)

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
|---|---|---|---|---|---|---|
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | |
| 2390 | 59.12 | -5.68 | 53.44 | 74 | -20.56 | peak |
| 2390 | 43.25 | -5.68 | 37.57 | 54 | -16.43 | AVG |
| Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

Vertical:

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
|---|---|---|---|---|---|---|
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | |
| 2390 | 60.79 | -5.68 | 55.11 | 74 | -18.89 | peak |
| 2390 | 45.35 | -5.68 | 39.67 | 54 | -14.33 | AVG |
| Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

Operation Mode: GFSK TX High channel (2480MHz)

Horizontal (Worst case)

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
|---|---|---|---|---|---|---|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | |
| 2483.5 | 59.33 | -5.85 | 53.48 | 74 | -20.52 | peak |
| 2483.5 | 45.69 | -5.85 | 39.84 | 54 | -14.16 | AVG |
| Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

Vertical:

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
|---|---|---|---|---|---|---|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | |
| 2483.5 | 61.39 | -5.85 | 55.54 | 74 | -18.46 | peak |
| 2483.5 | 45.98 | -5.85 | 40.13 | 54 | -13.87 | AVG |
| Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

## 7.10 Spurious Emission

### 7.10.1 Conducted Emission Method

| | | | | | | |
|---|---|---|---|---|---|---|
| Test Requirement: | FCC Part15 C Section 15.247 (d) | | | | | |
| Test Method: | ANSI C63.10:2013 | | | | | |
| Limit: | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. | | | | | |
| Test setup: |  | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test results: | Pass | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |

| Reference |
| --- |
|   |
| ***GFSK*** |
|   |
| ***π /4DQPSK*** |

## GFSK




## CH00




## CH39




## CH78

## π /4DQPSK




## CH00




## CH39




## CH78

### 7.10.2 Radiated Emission Method

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.209 |
| Test Method: | ANSI C63.10:2013 |
| Test Frequency Range: | 9kHz to 25GHz |
| Test site: | Measurement Distance: 3m |

**Receiver setup:**

| Frequency | Detector | RBW | VBW | Value |
|---|---|---|---|---|
| 9KHz-150KHz | Quasi-peak | 200Hz | 600Hz | Quasi-peak |
| 150KHz-30MHz | Quasi-peak | 9KHz | 30KHz | Quasi-peak |
| 30MHz-1GHz | Quasi-peak | 120KHz | 300KHz | Quasi-peak |
| Above 1GHz | Peak | 1MHz | 3MHz | Peak |
| | Peak | 1MHz | 10Hz | Average |

**Limit:**

| Frequency | Limit (uV/m) | Value | Measurement Distance |
|---|---|---|---|
| 0.009MHz-0.490MHz | 2400/F(KHz) | QP | 300m |
| 0.490MHz-1.705MHz | 24000/F(KHz) | QP | 30m |
| 1.705MHz-30MHz | 30 | QP | 30m |
| 30MHz-88MHz | 100 | QP | 3m |
| 88MHz-216MHz | 150 | QP | |
| 216MHz-960MHz | 200 | QP | |
| 960MHz-1GHz | 500 | QP | |
| Above 1GHz | 500 | Average | |
| | 5000 | Peak | |

**Test setup:**

For radiated emissions from 9kHz to 30MHz



| | |
|---|---|
| | For radiated emissions from 30MHz to1GHz<br>  <br><br>For radiated emissions above 1GHz<br>  <br> |
| Test Procedure: | 1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.<br>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.<br>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.<br>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.<br>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.<br>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. |
| Test Instruments: | Refer to section 6.0 for details |
| Test mode: | Refer to section 5.2 for details |

| | | | | | | |
|---|---|---|---|---|---|---|
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |
| Test voltage: | AC 120V, 60Hz | | | | | |
| Test results: | Pass | | | | | |

**Measurement data:**

*Remarks:*

1. *During the test, pre-scan the GFSK, π/4-DQPSK modulation, and found the GFSK modulation which it is worse case.*
2. *Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.*

■ **9kHz~30MHz**

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

**For 30MHz-1GHz**

Horizontal




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Over | |
|---|---|---|---|---|---|---|---|---|
| | | MHz | dBuV | dB | dBuV/m | dB/m | dB | Detector |
| 1 | | 43.8119 | 33.33 | -17.90 | 15.43 | 40.00 | -24.57 | QP |
| 2 | | 67.2022 | 37.60 | -19.60 | 18.00 | 40.00 | -22.00 | QP |
| 3 | | 85.2980 | 37.28 | -21.07 | 16.21 | 40.00 | -23.79 | QP |
| 4 | | 114.5146 | 38.50 | -20.07 | 18.43 | 43.50 | -25.07 | QP |
| 5 | * | 205.6751 | 45.94 | -19.96 | 25.98 | 43.50 | -17.52 | QP |
| 6 | | 294.1137 | 44.80 | -18.49 | 26.31 | 46.00 | -19.69 | QP |

Final Level =Receiver Read level + Correct Factor

Vertical

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Over | |
|---|---|---|---|---|---|---|---|---|
| | | MHz | dBuV | dB | dBuV/m | dB/m | dB | Detector |
| 1 | * | 46.5030 | 51.28 | -18.33 | 32.95 | 40.00 | -7.05 | QP |
| 2 | | 57.9992 | 46.53 | -18.69 | 27.84 | 40.00 | -12.16 | QP |
| 3 | | 63.9827 | 47.30 | -19.22 | 28.08 | 40.00 | -11.92 | QP |
| 4 | | 106.3850 | 48.56 | -20.32 | 28.24 | 43.50 | -15.26 | QP |
| 5 | | 207.8500 | 47.27 | -19.88 | 27.39 | 43.50 | -16.11 | QP |
| 6 | | 299.3158 | 40.74 | -18.32 | 22.42 | 46.00 | -23.58 | QP |

Final Level =Receiver Read level + Correct Factor

**For 1GHz to 25GHz**

Remark: For test above 1GHz GFSK and π /4-DQPSK were test at Low, Middle, and High channel; only the worst result of GFSK was reported as below:

CH Low (2402MHz)

Horizontal:

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Detector Type |
|---|---|---|---|---|---|---|
| 4804 | 61.39 | -3.61 | 57.78 | 74 | -16.22 | peak |
| 4804 | 44.58 | -3.61 | 40.97 | 54 | -13.03 | AVG |
| 7206 | 54.93 | -0.85 | 54.08 | 74 | -19.92 | peak |
| 7206 | 44.09 | -0.85 | 43.24 | 54 | -10.76 | AVG |
| --- | --- | --- | --- | --- | --- | --- |
| --- | --- | --- | --- | --- | --- | --- |
| Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

Vertical:

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Detector Type |
|---|---|---|---|---|---|---|
| 4804 | 58.95 | -3.61 | 55.34 | 74 | -18.66 | peak |
| 4804 | 45.72 | -3.61 | 42.11 | 54 | -11.89 | AVG |
| 7206 | 57.22 | -0.85 | 56.37 | 74 | -17.63 | peak |
| 7206 | 43.26 | -0.85 | 42.41 | 54 | -11.59 | AVG |
| --- | --- | --- | --- | --- | --- | --- |
| --- | --- | --- | --- | --- | --- | --- |
| Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

CH Middle (2441MHz)

Horizontal:

| Frequency (MHz) | Meter Reading (dBµV) | Factor (dB) | Emission Level (dBµV/m) | Limits (dBµV/m) | Margin (dB) | Detector Type |
|---|---|---|---|---|---|---|
| 4882 | 60.89 | -3.49 | 57.4 | 74 | -16.6 | peak |
| 4882 | 45.31 | -3.49 | 41.82 | 54 | -12.18 | AVG |
| 7326 | 58.20 | -0.80 | 57.40 | 74.00 | -16.60 | peak |
| 7326 | 44.11 | -0.8 | 43.31 | 54 | -10.69 | AVG |
| --- | --- | --- | --- | --- | --- | --- |
| --- | --- | --- | --- | --- | --- | --- |
| Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

Vertical:

| Frequency (MHz) | Meter Reading (dBµV) | Factor (dB) | Emission Level (dBµV/m) | Limits (dBµV/m) | Margin (dB) | Detector Type |
|---|---|---|---|---|---|---|
| 4882 | 62.03 | -3.49 | 58.54 | 74 | -15.46 | peak |
| 4882 | 45.36 | -3.49 | 41.87 | 54 | -12.13 | AVG |
| 7326 | 57.01 | -0.80 | 56.21 | 74 | -17.79 | peak |
| 7326 | 44.06 | -0.8 | 43.26 | 54 | -10.74 | AVG |
| --- | --- | --- | --- | --- | --- | --- |
| --- | --- | --- | --- | --- | --- | --- |
| Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

CH High (2480MHz)

Horizontal:

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Detector Type |
|---|---|---|---|---|---|---|
| 4960 | 61.35 | -3.41 | 57.94 | 74 | -16.06 | peak |
| 4960 | 45.28 | -3.41 | 41.87 | 54 | -12.13 | AVG |
| 7440 | 55.36 | -0.72 | 54.64 | 74 | -19.36 | peak |
| 7440 | 43.26 | -0.8 | 42.46 | 54 | -11.54 | AVG |
| --- | --- | --- | --- | --- | --- | --- |
| --- | --- | --- | --- | --- | --- | --- |
| Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

Vertical:

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Detector Type |
|---|---|---|---|---|---|---|
| 4960 | 61.25 | -3.41 | 57.84 | 74 | -16.16 | peak |
| 4960 | 46.66 | -3.41 | 43.25 | 54 | -10.75 | AVG |
| 7440 | 55.68 | -0.72 | 54.96 | 74 | -19.04 | peak |
| 7440 | 43.21 | -0.8 | 42.41 | 54 | -11.59 | AVG |
| --- | --- | --- | --- | --- | --- | --- |
| --- | --- | --- | --- | --- | --- | --- |
| Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

Remark:
(1) Data of measurement within this frequency range shown “--- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
(2) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed.

# 8 Test Setup Photo

Reference to the **appendix I** for details.

# 9 EUT Constructional Details

Reference to the **appendix II** for details.

------End------