FCC RADIO TEST REPORT
FCC ID: 2AZQY-A156

Product： 15.6-inch notebook

Trade Mark： Visionsky

Model Name： A156

Family Model： N/A

Report No.： S21030300406003

Prepared for

Visionsky (SZ) Industrial Co., Ltd
303A, Xiagu, MeishengChuanggu, no. 10, Longchang Road, 68 district, Xingdong community, Xin 'an street, Bao 'an district, Shenzhen

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao’an District, Shenzhen 518126 P.R. China
Tel. 400-800-6106, 0755-3699 5508
Website: http://www.ntek.org.cn

TEST RESULT CERTIFICATION

Applicant's name ..... : Visionsky (SZ) Industrial Co., Ltd

Address ..... : 303A, Xiagu, MeishengChuanggu, no. 10, Longchang Road, 68 district, Xingdong community, Xin 'an street, Bao 'an district, Shenzhen

Manufacturer's Name ..... : Visionsky (SZ) Industrial Co., Ltd Shiyan Branch

Address ..... : Floor 4, building a, east Shilongzi road, Shuitian community, Shiyar Street, Bao 'an district, Shenzhen

Product description

Product name ..... : 15.6-inch notebook

Model and/or type reference : A156

Family Model..... : N/A

Standards ..... : FCC Part15.407

Test procedure ..... ANSI C63.10-2013 and KDB 789033 D02 General UNII Test Procedures New Rules v02r01

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements/ the Industry Canada requirements.. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test .....

Date (s) of performance of tests ..... 15 Mar. 2021 ~ 20 Apr. 2021

Date of Issue..... 22 Apr. 2021

Test Result..... **Pass**

Testing Engineer : Allen Liu

(Allen Liu)

Technical Manager : Jason Chen

(Jason Chen)

Authorized Signatory : Alex

(Alex Li)

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	6
1.1 FACILITIES AND ACCREDITATIONS	7
1.2 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	10
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	12
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
3 . TEST REQUIREMENTS	15
3.1 CONDUCTED EMISSION MEASUREMENT	15
3.2 RADIATED EMISSION MEASUREMENT	20
3.3 POWER SPECTRAL DENSITY TEST	37
3.4 26DB & 99% EMISSION BANDWIDTH	40
3.5 MINIMUM 6 DB BANDWIDTH	42
3.6 MAXIMUM CONDUCTED OUTPUT POWER	44
3.7 OUT OF BAND EMISSIONS	48
3.8 SPURIOUS RF CONDUCTED EMISSIONS	50
3.9 FREQUENCY STABILITY MEASUREMENT	51
4. ANTENNA REQUIREMENT	58
4.1 STANDARD REQUIREMENT	58
4.2 EUT ANTENNA	58
5. TEST RESULTS	59
5.2G:	59
DUTY CYCLE	59
MAXIMUM CONDUCTED OUTPUT POWER	66
-26DB BANDWIDTH	67
OCCUPIED CHANNEL BANDWIDTH	75
MAXIMUM POWER SPECTRAL DENSITY LEVEL	83
BAND EDGE	91
CONDUCTED RF SPURIOUS EMISSION	97
5.8G	105
DUTY CYCLE	105
MAXIMUM CONDUCTED OUTPUT POWER	112

Table of Contents

	Page
-6DB BANDWIDTH	113
OCCUPIED CHANNEL BANDWIDTH	121
MAXIMUM POWER SPECTRAL DENSITY LEVEL	129
BAND EDGE	137
CONDUCTED RF SPURIOUS EMISSION	143

Revision History

Report No.	Version	Description	Issued Date
S21030300406003	Rev.01	Initial issue of report	22 Apr. 2021

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207	AC Power Line Conducted Emissions	PASS	
15.209(a), 15.407 (b)(1) 15.407 (b)(4) 15.407 (b)(8)(9)	Spurious Radiated Emissions	PASS	
15.407 (a)(1) 15.407 (a)(3)	26 dB and 99% Emission Bandwidth	PASS	
15.407(e)	Minimum 6 dB bandwidth	PASS	
15.407 (a)(1) 15.407 (a)(3)	Maximum Conducted Output Power	PASS	
15.407(b)(1) 15.407(b)(4)	Band Edge	PASS	
15.407 (a)(1) 15.407 (a)(3)	Power Spectral Density	PASS	
15.407(b)	Spurious Emissions at Antenna Terminals	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 FACILITIES AND ACCREDITATIONS

FACILITIES

All measurement facilities used to collect the measurement data are located at

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab.	:	The Certificate Registration Number is L5516.
IC-Registration		The Certificate Registration Number is 9270A. CAB identifier:CN0074
FCC- Accredited		Test Firm Registration Number: 463705. Designation Number: CN1184
A2LA-Lab.		The Certificate Registration Number is 4298.01
Name of Firm	:	Shenzhen NTEK Testing Technology Co., Ltd.
Site Location	:	1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	±2.80dB
2	RF power, conducted	±0.16dB
3	Spurious emissions, conducted	±0.21dB
4	All emissions, radiated(30MHz~1GHz)	±2.64dB
5	All emissions, radiated(1GHz~6GHz)	±2.40dB
6	All emissions, radiated(＞6GHz)	±2.52dB
7	Temperature	±0.5°C
8	Humidity	±2%

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	15.6-inch notebook
Trade Mark	Visionsky
Model Name	A156
Family Model	N/A
Model Difference	N/A
FCC ID	2AZQY-A156
Product Description	

IEEE 802.11 WLAN Mode Supported	☒802.11a/n/ac (20MHz channel bandwidth) ☒802.11n/ac (40MHz channel bandwidth) ☒802.11ac (80MHz channel bandwidth)
Data Rate	802.11a: 6,9,12,18,24,36,48,54Mbps; 802.11n(HT20/HT40):MCS0-MCS15; 802.11ac(VHT20):MCS0-MCS8; 802.11ac(VHT40/VHT80):MCS0-MCS9;
Modulation	OFDM with BPSK/QPSK/16QAM/64QAM/256QAM for 802.11a/n/ac;
Operating Frequency Range	☒5180-5240MHz for 802.11a/n(HT20) / ac(VHT20); 5190-5230MHz for 802.11n(HT40)/ac(VHT40); 5210MHz for 802.11ac(VHT80) ☒5745-5825 MHz for 802.11a/n(HT20)/ ac(VHT20); 5755-5795 MHz for 802.11a/n(HT40)/ ac(VHT40); 5775MHz for 802.11ac(VHT80)
Number of Channels	☒4 channels for 802.11a/n20/ac20 in the 5180-5240MHz band ; 2 channels for 802.11 n40/ac40 in the 5190-5230MHz band ; 1 channels for 802.11 ac80 in the 5210MHz band ; ☒5 channels for 802.11a/n20/ac20 in the 5745-5825MHz band ; 2 channels for 802.11 n40/ac40 in the 5755-5795MHz band ; 1 channels for 802.11 ac80 in the 5775MHz band ;
Antenna Type	FPCB Antenna
Antenna Gain	0.3dBi

Based on the application, features, or specification exhibited in User's Manual, More details of EUT technical specification, please refer to the User's Manual.

Ratings	DC 7.6V/5000mAh from battery or DC 19V from Adapter
Adapter	Model: A653-1903420DI Input: 100-240V~50/60Hz 1.5A Output: 19.0V⎓3.42A 65.0W
Connecting I/O Port(s)	Please refer to the User's Manual
HW Version	HCAR357-N V03 & HCAR357-N-GL V02
SW Version	HCAR357-N BIOS_R01
Firmware version	HCAR357-N EC_V04

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. Frequency and Channel list for 802.11a/n/ac(20MHz) band I (5180-5240MHz):

802.11a/n/ac(20MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220	-	-	-	-
40	5200	48	5240	-	-	-	-

Frequency and Channel list for 802.11n/ac(40MHz) band I (5190-5230MHz):

802.11n/ac(40MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	-	-	-	-	-	-
46	5230	-	-	-	-	-	-

Frequency and Channel list for 802.11ac(80MHz) band I (5210MHz):

802.11ac(80MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	-	-	-	-	-	-

Frequency and Channel list for 802.11a/n/ac(20 MHz) band IV (5745-5825MHz):

802.11a/n/ac(20 MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	153	5765	157	5785	161	5805
165	5825	-	-	-	-	-	-

Frequency and Channel list for 802.11n/ac(40MHz) band IV (5755-5795MHz):

802.11n/ac(40MHz) Carrier Frequency Channel					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795	-	-

Frequency and Channel list for 802.11ac(80MHz) band IV (5775MHz):

802.11ac(80MHz) Carrier Frequency Channel					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
155	5775			-	-

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a / n 20 /ac 20 CH36/ CH40/ CH 48 802.11a / n 20 / ac 20 CH149/ CH157/ CH 165
Mode 3	802.11n40 / ac40 CH38/ CH 46 802.11n 40 / ac 40 CH 151 / CH 159
Mode 4	802.11ac80 CH 42 802.11ac 80 CH 155

For Radiated Emission	
Final Test Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a / n 20 /ac 20 CH36/ CH40/ CH 48 802.11a / n 20 / ac 20 CH149/ CH157/ CH 165
Mode 3	802.11n40 / ac40 CH38/ CH 46 802.11n 40 / ac 40 CH 151 / CH 159
Mode 4	802.11ac80 CH 42 802.11ac 80 CH 155

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

(2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note:1.The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.
2.EUT built-in battery-powered, the battery is fully-charged.

2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
AE-1	Adapter	A653-1903420DI	N/A	Peripherals
AE-2	Mouse	N/A	N/A	Peripherals
AE-3	Earphone	N/A	N/A	Peripherals
AE-4	Monitor	N/A	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	Power Cable	NO	NO	1.0m
C-2	USB Cable	NO	NO	1.2m
C-3	Earphone Cable	NO	NO	1.2m
C-4	HDMI	NO	NO	1.0m
C-5	RF Cable	YES	NO	0.1m

Note:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Aglient	E4407B	MY45108040	2020.05.11	2021.05.10	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2020.07.13	2021.07.12	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2020.07.13	2021.07.12	1 year
4	Test Receiver	R&S	ESPI7	101318	2020.05.11	2021.05.10	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2020.04.11 2021.03.29	2021.04.10 2022.03.28	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2020.05.11	2023.05.10	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2020.04.11 2021.03.29	2021.04.10 2022.03.28	1 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2020.05.11	2021.05.10	1 year
9	Amplifier	EMC	EMC051835SE	980246	2020.07.13	2021.07.12	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519 B	055	2020.07.13	2021.07.12	1 year
11	Power Meter	DARE	RPR3006W	15I00041SNO84	2020.07.13	2021.07.12	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2019.08.6	2022.08.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2019.08.6	2022.08.05	3 year
14	High Test Cable(1G-40GHz)	N/A	R-03	N/A	2019.06.28	2022.06.27	3 year
15	High Test Cable(1G-40GHz)	N/A	R-04	N/A	2020.04.11 2021.03.29	2021.04.10 2022.03.28	1 year
16	Filter	TRILTHIC	2400MHz	29	2020.07.13	2021.07.12	1 year
17	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:
We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2020.05.11	2021.05.10	1 year
2	LISN	R&S	ENV216	101313	2020.05.11	2021.05.10	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2020.05.11	2021.05.10	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2020.05.11	2023.05.10	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2020.05.11	2023.05.10	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2020.05.11	2023.05.10	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2020.05.11	2021.05.10	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable& Aux Equipment which is scheduled for calibration every 3 years.

3. TEST REQUIREMENTS

3.1CONDUCTED EMISSION MEASUREMENT

3.1.1 APPLICABLE STANDARD

According to FCC Part 15.207(a)

3.1.2 CONFORMANCE LIMIT

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
2. The lower limit shall apply at the transition frequencies
3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3.1.3 TEST CONFIGURATION



3.1.4 TEST PROCEDURE

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.5 TEST RESULTS

EUT：	15.6-inch notebook	Model Name ：	A156
Temperature：	23 ℃	Relative Humidity：	40%
Pressure：	1010hPa	Phase：	L
Test Voltage ：	DC 19V from Adapter AC 120V/60Hz	Test Mode：	Mode 1(5.2G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1539	46.36	9.56	55.92	65.78	-9.86	QP
0.1539	28.38	9.56	37.94	55.78	-17.84	AVG
0.1900	42.28	9.55	51.83	64.03	-12.20	QP
0.1900	25.27	9.55	34.82	54.03	-19.21	AVG
0.2139	40.05	9.55	49.60	63.05	-13.45	QP
0.2139	24.16	9.55	33.71	53.05	-19.34	AVG
0.2779	33.99	9.54	43.53	60.88	-17.35	QP
0.2779	20.00	9.54	29.54	50.88	-21.34	AVG
0.4939	29.76	9.55	39.31	56.10	-16.79	QP
0.4939	26.37	9.55	35.92	46.10	-10.18	AVG
8.3099	39.38	9.67	49.05	60.00	-10.95	QP
8.3099	30.72	9.67	40.39	50.00	-9.61	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	15.6-inch notebook	Model Name ：	A156
Temperature：	23 ℃	Relative Humidity：	40%
Pressure：	1010hPa	Phase：	N
Test Voltage ：	DC 19V from Adapter AC 120V/60Hz	Test Mode：	Mode 1(5.2G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1500	45.35	9.55	54.90	65.99	-11.09	QP
0.1500	27.76	9.55	37.31	55.99	-18.68	AVG
0.2020	42.52	9.54	52.06	63.52	-11.46	QP
0.2020	24.16	9.54	33.70	53.52	-19.82	AVG
0.2700	34.56	9.53	44.09	61.12	-17.03	QP
0.2700	19.33	9.53	28.86	51.12	-22.26	AVG
0.4899	29.38	9.54	38.92	56.17	-17.25	QP
0.4899	22.06	9.54	31.60	46.17	-14.57	AVG
0.5380	30.60	9.54	40.14	56.00	-15.86	QP
0.5380	22.03	9.54	31.57	46.00	-14.43	AVG
8.3779	38.97	9.66	48.63	60.00	-11.37	QP
8.3779	30.07	9.66	39.73	50.00	-10.27	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	15.6-inch notebook	Model Name ：	A156
Temperature：	23 ℃	Relative Humidity：	40%
Pressure：	1010hPa	Phase：	L
Test Voltage ：	DC 19V from Adapter AC 120V/60Hz	Test Mode：	Mode 1(5.8G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1500	46.42	9.56	55.98	65.99	-10.01	QP
0.1500	27.81	9.56	37.37	55.99	-18.62	AVG
0.2060	40.07	9.55	49.62	63.36	-13.74	QP
0.2060	30.11	9.55	39.66	53.36	-13.70	AVG
0.5100	30.24	9.55	39.79	56.00	-16.21	QP
0.5100	21.04	9.55	30.59	46.00	-15.41	AVG
0.5860	29.83	9.55	39.38	56.00	-16.62	QP
0.5860	20.16	9.55	29.71	46.00	-16.29	AVG
3.0140	26.65	9.60	36.25	56.00	-19.75	QP
3.0140	10.72	9.60	20.32	46.00	-25.68	AVG
9.5540	39.64	9.70	49.34	60.00	-10.66	QP
9.5540	30.41	9.70	40.11	50.00	-9.89	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	15.6-inch notebook	Model Name ：	A156
Temperature：	23 ℃	Relative Humidity：	40%
Pressure：	1010hPa	Phase：	N
Test Voltage ：	DC 19V from Adapter AC 120V/60Hz	Test Mode：	Mode 1(5.8G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1500	45.51	9.55	55.06	65.99	-10.93	QP
0.1500	27.13	9.55	36.68	55.99	-19.31	AVG
0.2180	38.60	9.54	48.14	62.89	-14.75	QP
0.2180	29.61	9.54	39.15	52.89	-13.74	AVG
0.3899	30.85	9.54	40.39	58.06	-17.67	QP
0.3899	22.51	9.54	32.05	48.06	-16.01	AVG
0.5299	30.49	9.54	40.03	56.00	-15.97	QP
0.5299	24.61	9.54	34.15	46.00	-11.85	AVG
3.8740	26.18	9.59	35.77	56.00	-20.23	QP
3.8740	10.16	9.59	19.75	46.00	-26.25	AVG
9.3940	39.34	9.68	49.02	60.00	-10.98	QP
9.3940	29.84	9.68	39.52	50.00	-10.48	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 APPLICABLE STANDARD

According to FCC Part 15.407(b) and 15.209

3.2.2 CONFORMANCE LIMIT

According to FCC Part 15.407(b)(7): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	24000/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. For Frequency 9kHz~30MHz:

Distance extrapolation factor =40log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

For Frequency above 30MHz:

Distance extrapolation factor =20log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

3.2.3 MEASURING INSTRUMENTS

The Measuring equipment is listed in the section 6.3 of this test report.

3.2.4 TEST CONFIGURATION

(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



3.2.5 TEST PROCEDURE

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.
This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.
Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1MHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	1 MHz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10*lg(100 [kHz]/narrower RBW [kHz]). , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

3.2.6 TEST RESULTS (9KHz – 30 MHz)

EUT：	15.6-inch notebook	Model Name. ：	A156
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 7.6V
Test Mode ：	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	N/A
--	--	--	--	N/A

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

3.2.7 TEST RESULTS (30MHz – 1GHz)

EUT：	15.6-inch notebook	Model Name. ：	A156
Temperature：	25 ℃	Relative Humidity：	55%
Pressure：	1010 hPa	Test Voltage ：	DC 7.6V
Test Mode ：	TX(5.2G)- 802.11a (Low CH)		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	60.2800	26.83	5.97	32.80	40.00	-7.20	QP
V	78.1389	24.77	7.79	32.56	40.00	-7.44	QP
V	116.5400	22.01	12.42	34.43	43.50	-9.07	QP
V	385.2805	20.54	17.15	37.69	46.00	-8.31	QP
V	631.6884	20.20	22.46	42.66	46.00	-3.34	QP
V	922.5157	14.93	27.30	42.23	46.00	-3.77	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
H	54.2610	19.73	7.07	26.80	40.00	-13.20	QP
H	63.3132	22.88	6.15	29.03	40.00	-10.97	QP
H	237.4755	23.03	11.47	34.50	46.00	-11.50	QP
H	312.1792	19.46	15.37	34.83	46.00	-11.17	QP
H	468.8761	15.78	19.08	34.86	46.00	-11.14	QP
H	798.9796	11.88	25.03	36.91	46.00	-9.09	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



EUT：	15.6-inch notebook	Model Name. ：	A156
Temperature：	26℃	Relative Humidity：	53%
Pressure：	1010 hPa	Test Voltage ：	DC 7.6V
Test Mode ：	TX(5.8G)- 802.11a (Low CH)		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	63.9827	27.41	6.30	33.71	40.00	-6.29	QP
V	78.1389	24.27	7.79	32.06	40.00	-7.94	QP
V	116.5400	20.01	12.42	32.43	43.50	-11.07	QP
V	531.9633	17.03	21.04	38.07	46.00	-7.93	QP
V	631.6884	20.20	22.46	42.66	46.00	-3.34	QP
V	922.5157	13.93	27.30	41.23	46.00	-4.77	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
H	63.3132	20.38	6.15	26.53	40.00	-13.47	QP
H	70.5836	18.24	6.35	24.59	40.00	-15.41	QP
H	180.0165	18.68	10.05	28.73	43.50	-14.77	QP
H	237.4755	22.03	11.47	33.50	46.00	-12.50	QP
H	312.1792	19.46	15.37	34.83	46.00	-11.17	QP
H	377.2590	18.47	16.97	35.44	46.00	-10.56	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



3.2.8 TEST RESULTS (1GHz-18GHz)

EUT：	15.6-inch notebook	Model Name. ：	A156
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 7.6V
Test Mode ：	TX(5.2G) - 802.11a _5180~5240MHz		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G									
Vertical	3694.38	58.91	5.94	35.40	44.00	56.25	74.00	-17.75	Pk
Vertical	3694.38	39.73	5.94	35.40	44.00	37.07	54.00	-16.93	AV
Vertical	10360.43	55.88	8.46	39.75	44.50	59.59	68.20	-8.61	Pk
Vertical	15540.50	58.41	10.12	38.80	44.10	63.23	74.00	-10.77	Pk
Vertical	15540.50	37.09	10.12	38.80	42.70	43.31	54.00	-10.69	AV
Horizontal	3713.28	60.79	5.94	35.18	44.00	57.91	74.00	-16.09	Pk
Horizontal	3713.28	41.19	5.94	35.18	44.00	38.31	54.00	-15.69	AV
Horizontal	10360.75	56.28	8.46	38.71	44.50	58.95	68.20	-9.25	Pk
Horizontal	15540.66	54.86	10.12	38.38	44.10	59.26	74.00	-14.74	Pk
Horizontal	15540.66	38.32	10.12	38.38	44.10	42.72	54.00	-11.28	AV
middle Channel (5200 MHz)-Above 1G									
Vertical	3624.41	56.03	6.48	36.35	44.05	54.81	74.00	-19.19	Pk
Vertical	3624.41	40.45	6.48	36.35	44.05	39.23	54.00	-14.77	AV
Vertical	10400.37	57.35	8.47	37.88	44.51	59.19	68.20	-9.01	Pk
Vertical	15600.43	57.57	10.12	38.80	44.10	62.39	74.00	-11.61	Pk
Vertical	15600.43	37.02	10.12	38.80	42.70	43.24	54.00	-10.76	AV
Horizontal	4202.42	55.71	6.48	36.37	44.05	54.51	74.00	-19.49	Pk
Horizontal	4202.42	42.38	6.48	36.37	44.05	41.18	54.00	-12.82	AV
Horizontal	10400.42	58.85	8.47	38.64	44.50	61.46	68.20	-6.74	Pk
Horizontal	15600.79	57.43	10.12	38.38	44.10	61.83	74.00	-12.17	Pk
Horizontal	15600.79	38.64	10.12	38.38	44.10	43.04	54.00	-10.96	AV

High Channel (5240 MHz)-Above 1G									
Vertical	4597.98	61.37	7.10	37.24	43.50	62.21	74.00	-11.79	Pk
Vertical	4597.98	40.77	7.10	37.24	43.50	41.61	54.00	-12.39	AV
Vertical	10480.51	57.58	8.46	37.68	44.50	59.22	68.20	-8.98	Pk
Vertical	15720.43	58.96	10.12	38.80	44.10	63.78	74.00	-10.22	Pk
Vertical	15720.43	37.74	10.12	38.80	42.70	43.96	54.00	-10.04	AV
Horizontal	4589.54	58.65	7.10	37.24	43.50	59.49	74.00	-14.51	Pk
Horizontal	4589.54	38.92	7.10	37.24	43.50	39.76	54.00	-14.24	AV
Horizontal	10480.87	59.61	8.46	38.57	44.50	62.14	68.20	-6.06	Pk
Horizontal	15720.46	57.18	10.12	38.38	44.10	61.58	74.00	-12.42	Pk
Horizontal	15720.46	40.50	10.12	38.38	44.10	44.90	54.00	-9.10	AV

Note:"802.11a (5G)" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

EUT：	15.6-inch notebook	Model Name. ：	A156
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 7.6V
Test Mode ：	TX (5.8G) -- 802.11a_5745~5825MHz		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G									
Vertical	5122.79	62.00	5.94	35.40	44.00	59.34	74.00	-14.66	Pk
Vertical	5122.79	43.71	5.94	35.40	44.00	41.05	54.00	-12.95	AV
Vertical	11490.88	58.33	8.46	39.75	44.50	62.04	74.00	-11.96	Pk
Vertical	11490.88	41.58	8.46	39.75	44.50	45.29	54.00	-8.71	AV
Vertical	17235.93	50.31	10.12	38.80	44.10	55.13	68.20	-13.07	Pk
Horizontal	5166.88	57.81	5.94	35.18	44.00	54.93	68.20	-13.27	Pk
Horizontal	11490.75	57.26	8.46	38.71	44.50	59.93	74.00	-14.07	Pk
Horizontal	11490.75	40.66	8.46	38.71	44.50	43.33	54.00	-10.67	AV
Horizontal	17235.75	59.79	10.12	38.38	44.10	64.19	68.20	-4.01	Pk
middle Channel (5785 MHz)-Above 1G									
Vertical	5433.68	60.92	6.48	36.35	44.05	59.70	74.00	-14.30	Pk
Vertical	5433.68	41.27	6.48	36.35	44.05	40.05	54.00	-13.95	AV
Vertical	11570.69	58.78	8.47	37.88	44.51	60.62	74.00	-13.38	Pk
Vertical	11570.69	41.34	8.47	37.88	44.51	43.18	54.00	-10.82	AV
Vertical	17356.12	59.67	10.12	38.80	44.10	64.49	68.20	-3.71	Pk
Horizontal	4866.88	58.23	6.48	36.37	44.05	57.03	74.00	-16.97	Pk
Horizontal	4866.88	41.08	6.48	36.37	44.05	39.88	54.00	-14.12	AV
Horizontal	11570.56	60.97	8.47	38.64	44.50	63.58	74.00	-10.42	Pk
Horizontal	11570.56	42.21	8.47	38.64	44.50	44.82	54.00	-9.18	AV
Horizontal	17355.77	60.78	10.12	38.38	44.10	65.18	68.20	-3.02	Pk

High Channel (5825 MHz)-Above 1G									
Vertical	5244.76	61.18	7.10	37.24	43.50	62.02	68.20	-6.18	Pk
Vertical	11652.70	60.89	8.46	37.68	44.50	62.53	74.00	-11.47	Pk
Vertical	11652.70	42.28	8.46	37.68	44.50	43.92	54.00	-10.08	AV
Vertical	17474.02	59.75	10.12	38.80	44.10	64.57	68.20	-3.63	Pk
Horizontal	5285.57	59.41	7.10	37.24	43.50	60.25	68.20	-7.95	Pk
Horizontal	11652.95	59.46	8.46	38.57	44.50	61.99	74.00	-12.01	Pk
Horizontal	11652.95	41.01	8.46	38.57	44.50	43.54	54.00	-10.46	AV
Horizontal	17474.96	57.37	10.12	38.38	44.10	61.77	68.20	-6.43	Pk

Note:"802.11a (5G)" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.2.9 TEST RESULTS (18GHz-40GHz)

EUT：	15.6-inch notebook	Model Name. ：	A156
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 7.6V
Test Mode ：	TX (5.2G)-802.11a 5180MHz~5240MHz, TX (5.8G)-802.11a 5745MHz~5825MHz		

All the modulation modes have been tested, and the worst result was report as below:

Low Channel (5180 MHz)-Above 1G

Horizontal



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamp Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39769.27	38.72	20.09	44.07	43.48	59.4	68.2	8.8	Peak
39767.19	27.02	20.09	44.04	43.48	47.67	54	6.33	AVG

Vertical



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamp Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39769.546	35.58	20.09	44.07	43.48	56.26	68.2	11.94	Peak
39769.365	26.88	20.09	44.04	43.48	47.53	54	6.47	AVG

High Channel (5240 MHz)-Above 1G

Horizontal



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamp Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
35628.37	40.73	19.11	42.73	44.61	57.96	68.2	10.24	Peak
35596.986	31.3	19.11	42.73	44.61	48.53	54	5.47	AVG

Vertical



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamp Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39769.476	36.68	20.09	44.07	43.48	57.36	68.2	10.84	Peak
39769.476	24.91	20.09	44.04	43.48	45.56	54	8.44	AVG

Low Channel (5745 MHz)-Above 1G

Horizontal



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamp Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39670.224	38.27	20.09	44.16	43.48	59.04	68.2	9.16	Peak
39670.224	29.3	20.09	44.16	43.48	50.07	54	3.93	AVG

Vertical



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamp Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39731.342	36.98	20.06	44.07	43.21	57.9	68.2	10.3	Peak
39731.342	27.95	20.06	44.07	43.21	48.87	54	5.13	AVG

High Channel (5825 MHz)-Above 1G

Horizontal



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamp Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
35628.534	39.32	19.11	42.63	43.48	57.58	68.2	10.62	Peak
35636.158	29.87	19.12	42.63	43.48	48.14	54	5.86	AVG

Vertical



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamp Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39821.763	37.97	20.1	44.1	43.22	58.95	68.2	9.25	Peak
39821.763	28.85	20.1	44.1	43.22	49.83	54	4.17	AVG

3.2.10 Spurious Emission in Restricted Band 4.5GHz~5.150 GHz& 5.350GHz~5460GHz

EUT：	15.6-inch notebook	Model Name. ：	A156
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 7.6V
Test Mode ：	TX (5.2G)-802.11a 5150MHz~5250MHz,		

All the modulation modes have been tested, The report just record the worst data mode.

Frequency (MHz)	Meter Reading (dBμV)	Cable Loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
5.2G WIFI-802.11a Mode									
4500	54.17	5.2	35.6	44.2	50.77	74	-23.23	Pk	Horizontal
4500	45.17	5.2	35.6	44.2	41.77	54	-12.23	AV	Horizontal
4500	57.12	5.2	35.6	44.2	53.72	74	-20.28	Pk	Horizontal
4500	44.14	5.2	35.6	44.2	40.74	54	-13.26	AV	Horizontal
5150	68.13	5.36	35.66	44.22	64.93	74	-9.07	Pk	Horizontal
5150	46.55	5.36	35.66	44.22	43.35	54	-10.65	AV	Horizontal
5150	54.8	5.36	35.66	44.22	51.6	74	-22.4	Pk	Vertical
5150	50.47	5.36	35.66	44.22	47.27	54	-6.73	AV	Vertical
5350	63.46	5.68	35.68	44.22	60.6	74	-13.4	Pk	Vertical
5350	45.09	5.68	35.68	44.22	42.23	54	-11.77	AV	Vertical
5350	58.84	5.68	35.68	44.22	55.98	74	-18.02	Pk	Horizontal
5350	43.55	5.68	35.68	44.22	40.69	54	-13.31	AV	Horizontal

Note: (1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor

(2) “802.11a ” mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

3.3 POWER SPECTRAL DENSITY TEST

3.3.1 Applied procedures / limit

According to FCC §15.407(a)(3)

For the band 5.15-5.25 GHz,

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz

(3)For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

,

3.3.2 TEST PROCEDURE

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, "provided that the measured power is integrated over the full reference bandwidth" to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

a) Set RBW ≥ 1/T, where T is defined in section II.B.I.a).

b) Set VBW ≥ 3 RBW.

c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add 10log(500kHz/RBW) to the measured result, whereas RBW (< 500 KHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.

d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add 10log(1MHz/RBW) to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.

e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since RBW=100 KHZ is available on nearly all spectrum analyzers.

3.3.3 DEVIATION FROM STANDARD

No deviation.

3.3.4 TEST SETUP



3.3.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

3.3.6 **TEST RESULTS**

EUT：	15.6-inch notebook	Model Name. ：	A156
Temperature：	25 ℃	Relative Humidity：	56%
Pressure：	1015 hPa	Test Voltage ：	DC 7.6V
Test Mode ：	TX Frequency Band I (5150-5250MHz), Band IV (5725-5850MHz)		

Test data reference attachment.

3.4 26DB & 99% EMISSION BANDWIDTH

3.4.1 Applied procedures / limit

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

3.4.2 TEST PROCEDURE

a) Set RBW = approximately 1% of the emission bandwidth.

b) Set the VBW > RBW.

c) Detector = Peak.

d) Trace mode = max hold.

e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW ≥ 3 · RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.



3.4.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.4.4 TEST RESULTS

EUT：	15.6-inch notebook	Model Name. ：	A156
Temperature：	25 ℃	Relative Humidity：	56%
Pressure：	1012 hPa	Test Voltage ：	DC 7.6V
Test Mode ：	TX Frequency Band I (5150-5250MHz), Band IV (5725-5850MHz)		

Test data reference attachment.

3.5 MINIMUM 6 DB BANDWIDTH

3.5.1 Applied procedures / limit

According to FCC §15.407(e)
(e) Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

3.5.2 TEST PROCEDURE

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

a) Set RBW = 100 kHz.

b) Set the video bandwidth (VBW) ≥ 3 × RBW.

c) Detector = Peak.

d) Trace mode = max hold.

e) Sweep = auto couple.

f) Allow the trace to stabilize.

g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.5.3 DEVIATION FROM STANDARD

No deviation.

3.5.4 TEST SETUP



3.5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.5.6 TEST RESULTS

EUT：	15.6-inch notebook	Model Name. ：	A156
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 7.6V
Test Mode ：	TX (5G) Mode Frequency Band IV (5725-5850MHz)		

Test data reference attachment.

3.6 MAXIMUM CONDUCTED OUTPUT POWER

3.6.1 PPLIED PROCEDURES / LIMIT

According to FCC §15.407

The maximum conduced output power should not exceed:

Frequency Band(MHz)	Limit
5150~5250	250mW
5725~5850	1W

3.6.2 TEST PROCEDURE

· Maximum conducted output power may be measured using a spectrum analyzer/EMI receiver or an RF power meter.

1. Device Configuration

If possible, configure or modify the operation of the EUT so that it transmits continuously at its maximum power control level (see section II.B.).

a) The intent is to test at 100 percent duty cycle; however a small reduction in duty cycle (to no lower than 98 percent) is permitted if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test lab to permit such continuous operation.

b) If continuous transmission (or at least 98 percent duty cycle) cannot be achieved due to hardware limitations (e.g., overheating), the EUT shall be operated at its maximum power control level with the transmit duration as long as possible and the duty cycle as high as possible.

2. Measurement using a Spectrum Analyzer or EMI Receiver (SA)

Measurement of maximum conducted output power using a spectrum analyzer requires integrating the spectrum across a frequency span that encompasses, at a minimum, either the EBW or the 99-percent occupied bandwidth of the signal.1 However, the EBW must be used to determine bandwidth dependent limits on maximum conducted output power in accordance with § 15.407(a).

a) The test method shall be selected as follows: (i) Method SA-1 or SA-1 Alternative (averaging with the EUT transmitting at full power throughout each sweep) shall be applied if either of the following conditions can be satisfied:

• The EUT transmits continuously (or with a duty cycle ≥ 98 percent).

• Sweep triggering or gating can be implemented in a way that the device transmits at the maximum power control level throughout the duration of each of the instrument sweeps to be averaged. This condition can generally be achieved by triggering the instrument's sweep if the duration of the sweep (with the analyzer configured as in Method SA-1, below) is equal to or shorter than the duration T of each transmission from the EUT and if those transmissions exhibit full power throughout their durations.

(ii) Method SA-2 or SA-2 Alternative (averaging across on and off times of the EUT transmissions, followed by duty cycle correction) shall be applied if the conditions of (i) cannot be achieved and the transmissions exhibit a constant duty cycle during the measurement duration. Duty cycle will be considered to be constant if variations are less than ± 2 percent.

(iii) Method SA-3 (RMS detection with max hold) or SA-3 Alternative (reduced VBW with max hold) shall be applied if the conditions of (i) and (ii) cannot be achieved.

b) Method SA-1 (trace averaging with the EUT transmitting at full power throughout each sweep): (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.

(ii) Set RBW = 1 MHz.

(iii) Set VBW ≥ 3 MHz.

(iv) Number of points in sweep ≥ 2 Span / RBW. (This ensures that bin-to-bin spacing is ≤ RBW/2, so that narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".

(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum

3.6.3 DEVIATION FROM STANDARD

No deviation.

3.6.4 TEST SETUP



3.6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.6.6 TEST RESULTS

EUT：	15.6-inch notebook	Model Name. ：	A156
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 7.6V
Test Mode ：	TX (5G) Mode Frequency Band I (5150-5250MHz), Band IV (5725-5850MHz)		

Test data reference attachment.

3.7 OUT OF BAND EMISSIONS

3.7.1 Applicable Standard

According to FCC §15.407(b)

Undesirable emission limits. Except as shown in paragraph (b)(8)(9) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.

(2) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of −27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

3.7.2 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

3.7.3 DEVIATION FROM STANDARD

No deviation.

3.7.4 TEST SETUP



3.7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.7.6 TEST RESULTS

EUT：	15.6-inch notebook	Model Name. ：	A156
Temperature：	25 ℃	Relative Humidity：	56%
Pressure：	1012 hPa	Test Voltage ：	DC 7.6V

Test data reference attachment.

3.8 SPURIOUS RF CONDUCTED EMISSIONS

3.8.1Conformance Limit

According to FCC §15.407(b)(1)(4)

3.8.2Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

3.8.3Test Setup

Please refer to Section 6.1 of this test report.

3.8.4Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=1MHz and VBW= 3MHz to measure the peak field strength , and measure frequency range from 30MHz to 40GHz.

3.8.5Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.

Test data reference attachment.

3.9 FREQUENCY STABILITY MEASUREMENT

3.9.1 LIMIT

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

3.9.2 TEST PROCEDURES

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. fc is declaring of channel frequency. Then the frequency error formula is $(fc-f)/fc \times 10^6$ ppm .
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is -20°C~70°C.

3.9.3 TEST SETUP LAYOUT



3.9.4 EUT OPERATION DURING TEST

The EUT was programmed to be in continuously un-modulation transmitting mode.

3.9.5 TEST RESULTS

EUT：	15.6-inch notebook	Model Name. ：	A156
Temperature：	25 ℃	Relative Humidity：	56%
Pressure：	1012 hPa	Test Voltage ：	DC 7.6V
Test Mode ：	TX Frequency Band I (5150-5250MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency：5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	7.6	5180.0242	5180	0.0242	-4.6718
		V max (V)	8.74	5180.0160	5180	0.0160	-3.0888
		V min (V)	6.46	5180.0131	5180	0.0131	-2.5290
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency：5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	7.6	T (°C)	-20	5180.0130	5180	0.0130	-2.5097
		T (°C)	-10	5180.0134	5180	0.0134	-2.5869
		T (°C)	0	5180.0272	5180	0.0272	-5.2510
		T (°C)	10	5180.0155	5180	0.0155	-2.9923
		T (°C)	20	5180.0139	5180	0.0139	-2.6834
		T (°C)	30	5180.0153	5180	0.0153	-2.9537
		T (°C)	40	5180.0136	5180	0.0136	-2.6255
		T (°C)	50	5180.0162	5180	0.0162	-3.1274
		T (°C)	60	5180.0180	5180	0.0180	-3.4749
		T (°C)	70	5180.0136	5180	0.0136	-2.6255
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency：5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	7.6	5200.0154	5200	0.0154	-2.9615
		V max (V)	8.74	5200.0112	5200	0.0112	-2.1538
		V min (V)	6.46	5200.0130	5200	0.0130	-2.5000
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency：5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	7.6	T (°C)	-20	5200.0309	5200	0.0309	-5.9423
		T (°C)	-10	5200.0121	5200	0.0121	-2.3269
		T (°C)	0	5200.0309	5200	0.0309	-5.9423
		T (°C)	10	5200.0204	5200	0.0204	-3.9231
		T (°C)	20	5200.0132	5200	0.0132	-2.5385
		T (°C)	30	5200.0119	5200	0.0119	-2.2885
		T (°C)	40	5200.0178	5200	0.0178	-3.4231
		T (°C)	50	5200.0170	5200	0.0170	-3.2692
		T (°C)	60	5200.0127	5200	0.0127	-2.4423
		T (°C)	70	5200.0120	5200	0.0120	-2.3077
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency：5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	7.6	5240.0114	5240	0.0114	-2.1756
		V max (V)	8.74	5240.0171	5240	0.0171	-3.2634
		V min (V)	6.46	5240.0154	5240	0.0154	-2.9389
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency：5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	7.6	T (°C)	-20	5240.0111	5240	0.0111	-2.1183
		T (°C)	-10	5240.0153	5240	0.0153	-2.9198
		T (°C)	0	5240.0151	5240	0.0151	-2.8817
		T (°C)	10	5240.0226	5240	0.0226	-4.3130
		T (°C)	20	5240.0122	5240	0.0122	-2.3282
		T (°C)	30	5240.0144	5240	0.0144	-2.7481
		T (°C)	40	5240.0174	5240	0.0174	-3.3206
		T (°C)	50	5240.0162	5240	0.0162	-3.0916
		T (°C)	60	5240.0124	5240	0.0124	-2.3664
		T (°C)	70	5240.0108	5240	0.0108	-2.0611
Limits				Within 5150-5250MHz			
Result				Complies			

EUT：	15.6-inch notebook	Model Name. ：	A156
Temperature：	25 ℃	Relative Humidity：	56%
Pressure：	1012 hPa	Test Voltage ：	DC 7.6V
Test Mode ：	TX Frequency(5745-5825MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency：5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	7.6	5745.0194	5745	0.0194	-3.3691
		V max (V)	8.74	5745.0137	5745	0.0137	-2.3924
		V min (V)	6.46	5745.0207	5745	0.0207	-3.6078
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency：5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.85	T (°C)	-20	5745.01955	5745	0.01955	-3.4024
		T (°C)	-10	5745.01790	5745	0.01790	-3.1165
		T (°C)	0	5745.01145	5745	0.01145	-1.9926
		T (°C)	10	5745.01312	5745	0.01312	-2.2835
		T (°C)	20	5745.01069	5745	0.01069	-1.8601
		T (°C)	30	5745.01194	5745	0.01194	-2.0780
		T (°C)	40	5745.01621	5745	0.01621	-2.8215
		T (°C)	50	5745.01585	5745	0.01585	-2.7586
		T (°C)	60	5745.01444	5745	0.01444	-2.5138
		T (°C)	70	5745.01230	5745	0.01230	-2.1408
Limits				Within 5745-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency：5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	7.6	5785.00998	5785	0.00998	-1.7259
		V max (V)	8.74	5785.01462	5785	0.01462	-2.5279
		V min (V)	6.46	5785.01254	5785	0.01254	-2.1681
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency：5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.85	T (°C)	-20	5785.01061	5785	0.01061	-1.8347
		T (°C)	-10	5785.01278	5785	0.01278	-2.2096
		T (°C)	0	5785.01587	5785	0.01587	-2.7431
		T (°C)	10	5785.00896	5785	0.00896	-1.5490
		T (°C)	20	5785.01369	5785	0.01369	-2.3673
		T (°C)	30	5785.01035	5785	0.01035	-1.7898
		T (°C)	40	5785.00792	5785	0.00792	-1.3686
		T (°C)	50	5785.01212	5785	0.01212	-2.0951
		T (°C)	60	5785.01544	5785	0.01544	-2.6687
		T (°C)	70	5785.01522	5785	0.01522	-2.6316
Limits				Within 5745-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency：5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	7.6	5825.0085	5825	0.00848	-1.4565
		V max (V)	8.74	5825.0116	5825	0.01159	-1.9895
		V min (V)	6.46	5825.0172	5825	0.01715	-2.9444
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency：5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.85	T (°C)	-20	5825.0090	5825	0.00904	-1.5527
		T (°C)	-10	5825.0146	5825	0.01457	-2.5015
		T (°C)	0	5825.0109	5825	0.01088	-1.8686
		T (°C)	10	5825.0080	5825	0.00802	-1.3764
		T (°C)	20	5825.0089	5825	0.00891	-1.5304
		T (°C)	30	5825.0167	5825	0.01670	-2.8670
		T (°C)	40	5825.0149	5825	0.01491	-2.5600
		T (°C)	50	5825.0090	5825	0.00898	-1.5420
		T (°C)	60	5825.0163	5825	0.01633	-2.8034
		T (°C)	70	5825.0134	5825	0.01342	-2.3033
Limits				Within 5745-5850MHz			
Result				Complies			

4. ANTENNA REQUIREMENT

4.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

4.2 EUT ANTENNA

The EUT antenna is permanent attached FPCB antenna (antenna gain: 0.3dBi). It comply with the standard requirement.

5. TEST RESULTS

5.2G:

DUTY CYCLE

Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)
NVNT	802.11a	5180	100	0
NVNT	802.11a	5200	100	0
NVNT	802.11a	5240	100	0
NVNT	802.11ac20	5180	100	0
NVNT	802.11ac20	5200	100	0
NVNT	802.11ac20	5240	100	0
NVNT	802.11ac40	5190	100	0
NVNT	802.11ac40	5230	100	0
NVNT	802.11n(HT20)	5180	100	0
NVNT	802.11n(HT20)	5200	100	0
NVNT	802.11n(HT20)	5240	100	0
NVNT	802.11n(HT40)	5190	100	0
NVNT	802.11n(HT40)	5230	100	0

Duty Cycle NVNT 802.11a 5180MHz



Duty Cycle NVNT 802.11a 5200MHz



Duty Cycle NVNT 802.11a 5240MHz



Duty Cycle NVNT 802.11ac20 5180MHz



Duty Cycle NVNT 802.11ac20 5200MHz



Duty Cycle NVNT 802.11ac20 5240MHz



Duty Cycle NVNT 802.11ac40 5190MHz



Duty Cycle NVNT 802.11ac40 5230MHz



Duty Cycle NVNT 802.11n(HT20) 5180MHz



Duty Cycle NVNT 802.11n(HT20) 5200MHz



Duty Cycle NVNT 802.11n(HT20) 5240MHz



Duty Cycle NVNT 802.11n(HT40) 5190MHz



Duty Cycle NVNT 802.11n(HT40) 5230MHz



MAXIMUM CONDUCTED OUTPUT POWER

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	a	5180	Ant1	10.156	0	10.156	24	Pass
NVNT	a	5200	Ant1	9.281	0	9.281	24	Pass
NVNT	a	5240	Ant1	10.333	0	10.333	24	Pass
NVNT	ac20	5180	Ant1	7.238	0	7.238	24	Pass
NVNT	ac20	5200	Ant1	8.055	0	8.055	24	Pass
NVNT	ac20	5240	Ant1	8.516	0	8.516	24	Pass
NVNT	ac40	5190	Ant1	7.079	0	7.079	24	Pass
NVNT	ac40	5230	Ant1	7.507	0	7.507	24	Pass
NVNT	ac80	5210	Ant1	5.324	0	5.324	24	Pass
NVNT	n20	5180	Ant1	7.958	0	7.958	24	Pass
NVNT	n20	5200	Ant1	8.134	0	8.134	24	Pass
NVNT	n20	5240	Ant1	8.417	0	8.417	24	Pass
NVNT	n40	5190	Ant1	6.826	0	6.826	24	Pass
NVNT	n40	5230	Ant1	8.059	0	8.059	24	Pass

-26DB BANDWIDTH

Condition	Mode	Frequency (MHz)	Antenna	-26 dB Bandwidth (MHz)	Verdict
NVNT	a	5180	Ant1	20.235	Pass
NVNT	a	5200	Ant1	19.905	Pass
NVNT	a	5240	Ant1	20.205	Pass
NVNT	ac20	5180	Ant1	20.439	Pass
NVNT	ac20	5200	Ant1	20.364	Pass
NVNT	ac20	5240	Ant1	20.284	Pass
NVNT	ac40	5190	Ant1	41.828	Pass
NVNT	ac40	5230	Ant1	41.479	Pass
NVNT	ac80	5210	Ant1	81.148	Pass
NVNT	n20	5180	Ant1	20.608	Pass
NVNT	n20	5200	Ant1	20.255	Pass
NVNT	n20	5240	Ant1	20.547	Pass
NVNT	n40	5190	Ant1	41.722	Pass
NVNT	n40	5230	Ant1	41.106	Pass

-26dB Bandwidth NVNT a 5180MHz Ant1



-26dB Bandwidth NVNT a 5200MHz Ant1



-26dB Bandwidth NVNT a 5240MHz Ant1



-26dB Bandwidth NVNT ac20 5180MHz Ant1



-26dB Bandwidth NVNT ac20 5200MHz Ant1



-26dB Bandwidth NVNT ac20 5240MHz Ant1



-26dB Bandwidth NVNT ac40 5190MHz Ant1



-26dB Bandwidth NVNT ac40 5230MHz Ant1



-26dB Bandwidth NVNT ac80 5210MHz Ant1



-26dB Bandwidth NVNT n20 5180MHz Ant1



-26dB Bandwidth NVNT n20 5200MHz Ant1



-26dB Bandwidth NVNT n20 5240MHz Ant1



-26dB Bandwidth NVNT n40 5190MHz Ant1



-26dB Bandwidth NVNT n40 5230MHz Ant1



OCCUPIED CHANNEL BANDWIDTH

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	a	5180	Ant1	16.523
NVNT	a	5200	Ant1	16.532
NVNT	a	5240	Ant1	16.509
NVNT	ac20	5180	Ant1	17.601
NVNT	ac20	5200	Ant1	17.603
NVNT	ac20	5240	Ant1	17.595
NVNT	ac40	5190	Ant1	36.121
NVNT	ac40	5230	Ant1	36.08
NVNT	ac80	5210	Ant1	75.375
NVNT	n20	5180	Ant1	17.616
NVNT	n20	5200	Ant1	17.624
NVNT	n20	5240	Ant1	17.595
NVNT	n40	5190	Ant1	36.123
NVNT	n40	5230	Ant1	36.118

OBW NVNT a 5180MHz Ant1



OBW NVNT a 5200MHz Ant1



OBW NVNT a 5240MHz Ant1



OBW NVNT ac20 5180MHz Ant1



OBW NVNT ac20 5200MHz Ant1



OBW NVNT ac20 5240MHz Ant1



OBW NVNT ac40 5190MHz Ant1



OBW NVNT ac40 5230MHz Ant1



OBW NVNT ac80 5210MHz Ant1



OBW NVNT n20 5180MHz Ant1



OBW NVNT n20 5200MHz Ant1



OBW NVNT n20 5240MHz Ant1



OBW NVNT n40 5190MHz Ant1



OBW NVNT n40 5230MHz Ant1



MAXIMUM POWER SPECTRAL DENSITY LEVEL

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	a	5180	Ant1	9.212	11	Pass
NVNT	a	5200	Ant1	9.013	11	Pass
NVNT	a	5240	Ant1	9.502	11	Pass
NVNT	ac20	5180	Ant1	6.481	11	Pass
NVNT	ac20	5200	Ant1	7.359	11	Pass
NVNT	ac20	5240	Ant1	7.345	11	Pass
NVNT	ac40	5190	Ant1	5.181	11	Pass
NVNT	ac40	5230	Ant1	5.619	11	Pass
NVNT	ac80	5210	Ant1	2.4	11	Pass
NVNT	n20	5180	Ant1	7.495	11	Pass
NVNT	n20	5200	Ant1	7.494	11	Pass
NVNT	n20	5240	Ant1	7.337	11	Pass
NVNT	n40	5190	Ant1	4.531	11	Pass
NVNT	n40	5230	Ant1	5.262	11	Pass

PSD NVNT a 5180MHz Ant1



PSD NVNT a 5200MHz Ant1



PSD NVNT a 5240MHz Ant1



PSD NVNT ac20 5180MHz Ant1



PSD NVNT ac20 5200MHz Ant1



PSD NVNT ac20 5240MHz Ant1



PSD NVNT ac40 5190MHz Ant1



PSD NVNT ac40 5230MHz Ant1



PSD NVNT ac80 5210MHz Ant1



PSD NVNT n20 5180MHz Ant1



PSD NVNT n20 5200MHz Ant1



PSD NVNT n20 5240MHz Ant1



PSD NVNT n40 5190MHz Ant1



PSD NVNT n40 5230MHz Ant1



BAND EDGE

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	a	5180	Ant1	-36.39	-27	Pass
NVNT	a	5240	Ant1	-47.25	-27	Pass
NVNT	ac20	5180	Ant1	-37.91	-27	Pass
NVNT	ac20	5240	Ant1	-47.65	-27	Pass
NVNT	ac40	5190	Ant1	-29.95	-27	Pass
NVNT	ac40	5230	Ant1	-48.97	-27	Pass
NVNT	ac80	5210	Ant1	-44.11	-27	Pass
NVNT	n20	5180	Ant1	-46.1	-27	Pass
NVNT	n20	5240	Ant1	-47.79	-27	Pass
NVNT	n40	5190	Ant1	-29.2	-27	Pass
NVNT	n40	5230	Ant1	-48.18	-27	Pass

Band Edge NVNT a 5180MHz Low Ant1



Band Edge NVNT a 5240MHz High Ant1



Band Edge NVNT ac20 5180MHz Low Ant1



Band Edge NVNT ac20 5240MHz High Ant1



Band Edge NVNT ac40 5190MHz Low Ant1



Band Edge NVNT ac40 5230MHz High Ant1



Band Edge NVNT ac80 5210MHz High Ant1



Band Edge NVNT n20 5180MHz Low Ant1



Band Edge NVNT n20 5240MHz High Ant1



Band Edge NVNT n40 5190MHz Low Ant1



Band Edge NVNT n40 5230MHz High Ant1



CONDUCTED RF SPURIOUS EMISSION

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	802.11a	5180	Ant 1	-36.54	-27	Pass
NVNT	802.11a	5200	Ant 1	-36.7	-27	Pass
NVNT	802.11a	5240	Ant 1	-35.62	-27	Pass
NVNT	802.11ac20	5180	Ant 1	-37.38	-27	Pass
NVNT	802.11ac20	5200	Ant 1	-37.75	-27	Pass
NVNT	802.11ac20	5240	Ant 1	-37.06	-27	Pass
NVNT	802.11ac40	5190	Ant 1	-37.47	-27	Pass
NVNT	802.11ac40	5230	Ant 1	-30.26	-27	Pass
NVNT	802.11ac80	5210	Ant 1	-37.29	-27	Pass
NVNT	802.11n(HT20)	5180	Ant 1	-37.01	-27	Pass
NVNT	802.11n(HT20)	5200	Ant 1	-31.82	-27	Pass
NVNT	802.11n(HT20)	5240	Ant 1	-37.35	-27	Pass
NVNT	802.11n(HT40)	5190	Ant 1	-37.54	-27	Pass
NVNT	802.11n(HT40)	5230	Ant 1	-36.74	-27	Pass

Tx. Spurious NVNT 802.11a 5180MHz Ant1 Emission



Tx. Spurious NVNT 802.11a 5200MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	5.1986 GHz	7.73 dBm		
M2		1	39.66558 GHz	-36.70 dBm		
M3		1	10.4 GHz	-49.01 dBm		
M4		1	15.6 GHz	-45.50 dBm		
M5		1	20.8 GHz	-48.17 dBm		

Tx. Spurious NVNT 802.11a 5240MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	5.2412 GHz	8.49 dBm		
M2		1	2.42953 GHz	-35.62 dBm		
M3		1	10.48 GHz	-48.73 dBm		
M4		1	15.72 GHz	-44.40 dBm		
M5		1	20.96 GHz	-48.76 dBm		

Tx. Spurious NVNT 802.11ac20 5180MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	5.1813 GHz	6.43 dBm		
M2		1	39.67758 GHz	-37.39 dBm		
M3		1	10.36 GHz	-49.38 dBm		
M4		1	15.54 GHz	-46.41 dBm		
M5		1	20.72 GHz	-50.21 dBm		

Tx. Spurious NVNT 802.11ac20 5200MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	5.1973 GHz	6.05 dBm		
M2		1	39.67358 GHz	-37.76 dBm		
M3		1	10.4 GHz	-51.63 dBm		
M4		1	15.6 GHz	-46.38 dBm		
M5		1	20.8 GHz	-48.84 dBm		

Tx. Spurious NVNT 802.11ac20 5240MHz Ant1 Emission



Tx. Spurious NVNT 802.11ac40 5190MHz Ant1 Emission



Tx. Spurious NVNT 802.11ac40 5230MHz Ant1 Emission



Tx. Spurious NVNT 802.11ac80 5210MHz Ant1 Emission



Tx. Spurious NVNT 802.11n(HT20) 5180MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	5.1786 GHz	5.73 dBm		
M2		1	39.62029 GHz	-37.02 dBm		
M3		1	10.36 GHz	-48.97 dBm		
M4		1	15.54 GHz	-47.31 dBm		
M5		1	20.72 GHz	-49.75 dBm		

Tx. Spurious NVNT 802.11n(HT20) 5200MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	5.1986 GHz	6.36 dBm		
M2		1	2.40955 GHz	-31.83 dBm		
M3		1	10.4 GHz	-50.69 dBm		
M4		1	15.6 GHz	-46.10 dBm		
M5		1	20.8 GHz	-49.99 dBm		

Tx. Spurious NVNT 802.11n(HT20) 5240MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	5.2412 GHz	6.16 dBm		
M2		1	39.6416 GHz	-37.35 dBm		
M3		1	10.48 GHz	-50.38 dBm		
M4		1	15.72 GHz	-45.96 dBm		
M5		1	20.96 GHz	-49.34 dBm		

Tx. Spurious NVNT 802.11n(HT40) 5190MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	5.192 GHz	1.15 dBm		
M2		1	39.65093 GHz	-37.55 dBm		
M3		1	10.38 GHz	-48.37 dBm		
M4		1	15.57 GHz	-47.58 dBm		
M5		1	20.76 GHz	-49.82 dBm		

Tx. Spurious NVNT 802.11n(HT40) 5230MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	5.2319 GHz	3.43 dBm		
M2		1	39.66692 GHz	-36.75 dBm		
M3		1	10.46 GHz	-50.73 dBm		
M4		1	15.69 GHz	-45.39 dBm		
M5		1	20.92 GHz	-48.89 dBm		

5.8G

DUTY CYCLE

Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)
NVNT	802.11a	5745	100	0
NVNT	802.11a	5785	100	0
NVNT	802.11a	5825	100	0
NVNT	802.11ac20	5745	100	0
NVNT	802.11ac20	5785	100	0
NVNT	802.11ac20	5825	100	0
NVNT	802.11ac40	5755	100	0
NVNT	802.11ac40	5795	100	0
NVNT	802.11n(HT20)	5745	100	0
NVNT	802.11n(HT20)	5785	100	0
NVNT	802.11n(HT20)	5825	100	0
NVNT	802.11n(HT40)	5755	100	0
NVNT	802.11n(HT40)	5795	100	0

Duty Cycle NVNT 802.11a 5745MHz



Duty Cycle NVNT 802.11a 5785MHz



Duty Cycle NVNT 802.11a 5825MHz



Duty Cycle NVNT 802.11ac20 5745MHz



Duty Cycle NVNT 802.11ac20 5785MHz



Duty Cycle NVNT 802.11ac20 5825MHz



Duty Cycle NVNT 802.11ac40 5755MHz



Duty Cycle NVNT 802.11ac40 5795MHz



Duty Cycle NVNT 802.11n(HT20) 5745MHz



Duty Cycle NVNT 802.11n(HT20) 5785MHz



Duty Cycle NVNT 802.11n(HT20) 5825MHz