



CFR 47 FCC PART 15 SUBPART C

CERTIFICATION TEST REPORT

For

433 Remote Control

MODEL NUMBER: OL1700501RM

FCC ID: 2AZR9-OL1700501RM

REPORT NUMBER: 4790967874-1

ISSUE DATE: August 28, 2023

Prepared for

Syvio Technology CO., LIMITED

Room A, 8/F, Kwok Cheung Building, 635-637 Shanghai Street, Mong Kok, Hong Kong , China

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	08/28/2023	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC Rules	Test Results
1	Transmitter Timeout	CFR 47 FCC §15.231 (a) (1)	Pass
2	20 dB Bandwidth and 99 % Occupied Bandwidth	CFR 47 FCC §15.231 (c)	Pass
3	Radiated Emission	CFR 47 FCC §15.231 (b)(e) CFR 47 FCC §15.205 and §15.209	Pass
4	Antenna Requirement	CFR 47 FCC §15.203	Pass
Note 1: This test report is only published to and used by the applicant, and it is not for evidence purpose in China.			
Note 2: The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART C and > when <Accuracy Method> decision rule is applied.			



TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. MEASURING INSTRUMENT CALIBRATION	7
4.2. MEASUREMENT UNCERTAINTY.....	7
5. EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF EUT	8
5.2. MAXIMUM FIELD STRENGTH.....	8
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	8
5.4. TEST ENVIRONMENT	8
5.5. DESCRIPTION OF TEST SETUP.....	9
5.6. MEASURING INSTRUMENT AND SOFTWARE USED.....	10
6. ANTENNA PORT TEST RESULTS	11
6.1. ON TIME AND DUTY CYCLE.....	11
6.2. TRANSMITTER TIMEOUT	14
6.3. 20 dB BANDWIDTH AND 99 % OCCUPIED BANDWIDTH	17
6.4. RADIATED TEST RESULTS	20
6.4.1. FIELD STRENGTH AND SPURIOUS EMISSIONS BELOW 1 GHz AND ABOVE 30 MHz	27
6.4.2. SPURIOUS EMISSIONS ABOVE 1 GHz	31
6.4.3. SPURIOUS EMISSIONS BELOW 30 MHz	35
7. ANTENNA REQUIREMENTS.....	38



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Syvio Technology CO., LIMITED
Address: Room A, 8/F, Kwok Cheung Building, 635-637 Shanghai Street,
Mong Kok, Hong Kong China

Manufacturer Information

Company Name: Linkzone Technology Co., Limited
Address: 4001, Block C, Building 1, Section 1, Chuangzhi Yuncheng,
Liuxian Avenue, Xili Communityxili Street, Nanshan District

EUT Information

EUT Name: 433 Remote Control
Model: OL1700501RM
Sample Received Date: August 15, 2023
Sample Status: Normal
Sample ID: 6360861
Date of Tested: August 15, 2023 ~ August 28, 2023

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS

Prepared By:

Fanny Huang

Engineer Project Associate

Checked By:

Denny Huang

Senior Project Engineer

Approved By:

Stephen Guo

Operations Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 414788 D01 Radiated Test Site v01r01, FCC CFR 47 Part 2, FCC CFR 47 Part 15, ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with Industry Canada. The Company Number is 21320. VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011
---------------------------	---

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognize national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiation Emission test (include Fundamental emission) (9 kHz-30 MHz)	2.2 dB
Radiation Emission test (include Fundamental emission) (30 MHz-1 GHz)	4.00 dB
Radiation Emission test (1 GHz to 26GHz) (include Fundamental emission)	5.78 dB (1 GHz-18 GHz)
	5.23 dB (18 GHz-26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	433 Remote Control	
Model	OL1700501RM	
Product Description	Operation Frequency	433.92 MHz
Power Supply	Battery 1.5 Vdc*2	

5.2. MAXIMUM FIELD STRENGTH

Frequency (MHz)	Maximum Peak Field Strength (dBμV/m)
433.92	89.60

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

Frequency (MHz)	Antenna Type	Antenna Gain (dBi)
433.92	PCB Antenna	4

Note: The value of the antenna gain was declared by customer.

5.4. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests	
Relative Humidity	55 ~ 70 %	
Atmospheric Pressure:	1025 Pa	
Temperature	TN	23 ~ 28 °C
Voltage:	VL	/
	VN	1.5 Vdc*2
	VH	/

Note: VL= Lower Extreme Test Voltage

VN= Nominal Voltage

VH= Upper Extreme Test Voltage

TN= Normal Temperature



5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	P/N
/	/	/	/	/

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
/	/	/	/	/	/

ACCESSORY


Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

SETUP DIAGRAM FOR TEST

A fully charged battery was used for all tests.

The test sample can be into a transmission mode through the power on.

Setup Diagram For Tests



Note: New battery was used during all tests.



5.6. MEASURING INSTRUMENT AND SOFTWARE USED

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Oct.17, 2022	Oct.16, 2023
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	Aug.02, 2021	Aug.01, 2024
Preamplifier	HP	8447D	2944A09099	Oct.17, 2022	Oct.16, 2023
EMI Measurement Receiver	R&S	ESR26	101377	Oct.17, 2022	Oct.16, 2023
Horn Antenna	TDK	HRN-0118	130940	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Oct.17, 2022	Oct.16, 2023
Loop antenna	Schwarzbeck	1519B	00008	Dec.14, 2021	Dec.13, 2024
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Oct.17, 2022	Oct.16, 2023
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

Other instruments						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
☒	Spectrum Analyzer	Keysight	N9010A	MY55150514	Oct.17, 2022	Oct.16, 2023
☒	Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Oct.22, 2022	Oct.21, 2023

6. ANTENNA PORT TEST RESULTS

6.1. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only

PROCEDURE

FCC Reference:	CFR 47 §15.35(c)
Test Method Used:	ANSI C63.10 Section 7.5

TEST SETUP



- Set RBW of spectrum analyzer to 100 kHz and VBW to 100 kHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is at least a 100 ms.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.

TEST ENVIRONMENT

Temperature	25.5 °C	Relative Humidity	61 %
Atmosphere Pressure	101 kPa	Test Voltage	1.5 Vdc*2

**RESULTS**

	On Time (ms)	Times	Ton (ms)	Total Ton times (ms)
Ton1	0.2904	21	6.0984	17.5560
Ton2	0.8184	14	11.4576	

Note: Total Ton times= Ton1*21+Ton2*14

Ton 1=1Δ2=0.2904ms


Ton 2=3Δ4=0.8184ms

Total Ton times (ms)	Period (ms)	Duty Cycle (Linear)	Duty Cycle Correction Factor
17.5560	66.30	0.2648	-11.54

Note: Duty Cycle Correction Factor=20log(x).

Where: x is Duty Cycle, X= Total Ton times/ Period

Ton 1/ Ton 2



Period
(ms)




Note: The remote will send the different codes for each button which could result in same duty cycle and power.

6.2. TRANSMITTER TIMEOUT

TEST PROCEDURE

FCC Reference:	CFR 47 FCC §15.231(a)
Test Method Used:	The EUT transmitter was activated and monitored using a spectrum analyser for a period of 10 seconds.

TEST SETUP





For CFR 47 Part 15.231(a):

- a. Set RBW of spectrum analyzer to 100 kHz and VBW to 100 kHz.
- b. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- c. Set Sweep Time to 10 s.
- d. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- e. Measure the maximum time duration of one single pulse.

LIMITS

CFR 47 §15.231(a):

A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

TEST ENVIRONMENT

Temperature	25.2 °C	Relative Humidity	58 %
Atmosphere Pressure	101 kPa	Test Voltage	1.5 Vdc*2

RESULTS

Manually transmitting mode			
Deactivation Time (seconds)	Limit (seconds)	Margin (seconds)	Result
0.3188	5.000	-4.6812	PASS



Note: All the modes had been tested, only the worst data record in the report.



6.3. 20 dB BANDWIDTH AND 99 % OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC §15.231 (c)


The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5 % of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

So, the limit calculated as: $0.0025 * 433.92 \text{ MHz} = 1.0848 \text{ MHz}$

TEST PROCEDURE

FCC Reference:	CFR 47 Part 15.231(c)
Test Method Used:	ANSI C63.10 Section 6.9.2

TEST SETUP



1. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
2. The EUT was placed on a turntable with 0.8 meter above ground.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower
4. Set the spectrum analyzer in the following setting as:

The RBW is set to 1kHz. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.


Note: Because the measured signal is CW or CW-like adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

TEST ENVIRONMENT

Temperature	25.5 °C	Relative Humidity	61 %
Atmosphere Pressure	101 kPa	Test Voltage	1.5 Vdc*2

RESULTS

20 dB Bandwidth (kHz)	99 % Occupied Bandwidth (kHz)	Limit (MHz)	Result
8.777	12.729	1.0848	Pass



6.4. RADIATED TEST RESULTS

LIMITS

CFR 47 FCC §15.231 (b)(e)

CFR 47 FCC §15.205 and §15.209

1. In addition to the provisions of §15.205, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	¹ 1,250 to 3,750	¹ 125 to 375
174-260	3,750	375
260-470	¹ 3,750 to 12,500	¹ 375 to 1,250
Above 470	12,500	1,250

Note:

1. To obtain the average limit at the test frequency the values given in the table of FCC part 15.231(b) have to be linear interpolated and then converted to dBμV/m. The limit at 260 MHz is 3750 μV/m and at 470 MHz it is 12500 μV/m. Limit at 433.92 MHz is calculated as shown in ANSI C63.10 Section 7.6.2:

Limit [μV/m] = Limlower + ΔF [(Limupper – Limlower) / (fupper – flower)]
where ΔF = fc – flower = 433.92 – 260 = 173.92

Limit = 3750 + 173.92 * [(12500 – 3750) / (470 -260)]
= 3750 + 173.92 * [8750 / 210]
= 10996.7 μV/m

dBμV/m = 20 * log (μV/m)
= 20 * log (10996.7)

Average Limit at 433.92 MHz = 80.8 dBμV/m

2. If the average limit is specified for the EUT, the peak limit is 20 dB above the average limit as specified in FCC 15.35 (b)

2. Please refer to CFR 47 FCC part 15.231(e)

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emission (microvolts/meter)
40.66-40.70	1,000	100
70-130	500	50
130-174	500 to 1,500 ¹	50 to 150 ¹
174-260	1,500	150
260-470	1,500 to 5,000 ¹	150 to 500 ¹
Above 470	5,000	500

Note:

1. To obtain the average limit at the test frequency the values given in the table of FCC part 15.231(b) have to be linear interpolated and then converted to dBμV/m. The limit at 260 MHz is 3750 μV/m and at 470 MHz it is 12500 μV/m. Limit at 433.92 MHz is calculated as shown in ANSI C63.10 Section 7.6.2:

Limit [μV/m] = Limlower + ΔF [(Limupper – Limlower) / (fupper – flower)]
where ΔF = fc – flower = 433.92 – 260 = 173.92

Limit = 1500 + 173.92 * [(5000 – 1500) / (470 -260)]
= 1500 + 173.92 * [3500 / 210]
= 4398.7 μV/m

dBμV/m = 20 * log (μV/m)
= 20 * log (4398.7)

Average Limit at 433.92 MHz = 72.87 dBμV/m

If the average limit is specified for the EUT, the peak limit is 20 dB above the average limit as specified in FCC 15.35 (b)

3. Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

4. Radiation Disturbance Test Limit for FCC (Class B) (9 kHz-1 GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Note: (1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

Note: (2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.

Restricted bands of operation


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST SETUP AND PROCEDURE

Below 30 MHz




The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto
Trace	Max hold

- The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
- The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
- The EUT was placed on a turntable with 80 cm above ground.
- The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
- The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
- For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
- Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
- The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω; For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same

Below 1 GHz




The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
7. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

Above 1 GHz




The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements. Where necessary, average emission are determined by applying the Duty Cycle Correction Factor to the peak measurements. For the Duty Cycle and Correction Factor please refer to clause 6.1. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.


TEST ENVIRONMENT

Radiated Emissions - Below 1 GHz		Radiated Emissions - Above 1 GHz	
Temperature:	22.7 °C	Temperature:	24.3 °C
Humidity:	61 %	Humidity:	61 %
Atmosphere Pressure	101 kPa	Atmosphere Pressure	101 kPa
Test Voltage	1.5 Vdc*2	Test Voltage	1.5 Vdc*2

RESULTS


6.4.1. FIELD STRENGTH AND SPURIOUS EMISSIONS BELOW 1 GHz AND ABOVE 30 MHz

FIELD STRENGTH AND SPURIOUS EMISSIONS (HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	433.9230	71.16	18.44	89.60	100.8	-11.20	peak
/	/	/	/	78.06	80.8	-2.74	average

- Note: 1. Result Level = Read Level + Correct Factor.
2. Peak: Peak detector.
3. Average Result = Peak Result + Duty Correction Factor.



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	299.6600	46.13	-15.32	30.81	46.00	-15.19	QP
2	380.1700	47.94	-12.86	35.08	46.00	-10.92	QP
3	433.5200	101.65	-12.10	89.55	/	/	Fundamental
4	487.8400	41.86	-10.95	30.91	46.00	-15.09	QP
5	697.3600	34.81	-7.97	26.84	46.00	-19.16	QP
6(2 th harmonic)	868.0800	57.36	-5.66	51.70	80.8	-29.10	PEAK
/	/	/	/	40.16	60.8	-20.64	AVERAGE

Note: 1. Result Level = Read Level + Correct Factor.
2. Peak: Peak detector.
3. Average Result = Peak Result + Duty Correction Factor.
4. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
5. Mark 4 is the fundamental frequency, Mark 6 is 2th harmonic.


**FIELD STRENGTH HARMONICS AND SPURIOUS EMISSIONS (VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	433.9159	64.73	18.44	83.17	100.8	-17.63	peak
/	/	/	/	71.63	80.8	-9.17	average

Note: 1. Result Level = Read Level + Correct Factor.

2. Peak: Peak detector.

3. Average Result = Peak Result + Duty Correction Factor.




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	273.4700	54.07	-17.20	36.87	46.00	-9.13	QP
2	426.7300	54.88	-12.28	42.60	46.00	-3.40	QP
3	433.5200	94.35	-12.10	82.25	/	/	Fundamental
4	487.8400	39.06	-10.95	28.11	46.00	-17.89	QP
5	793.3900	42.21	-6.66	35.55	46.00	-10.45	QP
6(2 th harmonic)	868.0800	49.61	-5.66	43.95	80.80	-36.85	PEAK
/	/	/	/	32.41	60.80	-28.39	AVERAGE

Note: 1. Result Level = Read Level + Correct Factor.
2. Peak: Peak detector.
3. Average Result = Peak Result + Duty Correction Factor.
4. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
5. Mark 3 is the fundamental frequency, Mark 6 is 2th harmonic.

6.4.2. SPURIOUS EMISSIONS ABOVE 1 GHz

HARMONICS AND SPURIOUS EMISSIONS (HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
*1(3 th harmonic)	1301.76	63.77	-13.64	50.13	74.00	-23.87	peak
/	/	/	/	38.59	54.00	-15.41	average
2(4 th harmonic)	1735.68	71.04	-11.94	59.10	80.80	-21.70	peak
/	/	/	/	47.56	60.80	-13.24	average
3(5 th harmonic)	2169.6	57.22	-10.19	47.03	80.80	-33.77	peak
/	/	/	/	35.49	60.80	-25.31	average
4(6 th harmonic)	2603.52	68.05	-8.19	59.86	80.80	-20.94	peak
/	/	/	/	48.32	60.80	-12.48	average
5(7 th harmonic)	3037.44	63.69	-6.90	56.79	80.80	-24.01	peak
/	/	/	/	45.25	60.80	-15.55	average
6(8 th harmonic)	3471.36	66.72	-5.92	60.80	80.80	-20.00	peak
/	/	/	/	49.26	60.80	-11.54	average
*7(9 th harmonic)	3905.28	58.16	-4.74	53.42	74.00	-20.58	peak
/	/	/	/	41.88	54.00	-12.12	average
*8(10 th harmonic)	4339.20	56.88	-2.89	53.99	74.00	-20.01	peak
/	/	/	/	42.45	54.00	-11.55	average
*9(11 th harmonic)	4773.12	52.27	-1.04	51.23	74.00	-22.77	peak
/	/	/	/	39.69	54.00	-14.31	average
10(12 th harmonic)	5207.04	51.3	0.09	51.39	80.80	-29.41	peak
/	/	/	/	39.85	60.80	-20.95	average
11(13 th harmonic)	5640.96	46.71	0.84	47.55	80.80	-33.25	peak
/	/	/	/	36.01	60.80	-24.79	average



- Note:
1. Result Level = Read Level + Correct Factor.
 2. Peak: Peak detector.
 3. Average Result = Peak Result + Duty Correction Factor.
 4. The average limit for harmonics out of the restrict bands are 60.8 dBuV/m, the average limit in the restrict bands is 54 dBuV/m.
 5. If peak result complies with average limit, the average result is deemed to comply with average limit.
 6. Mark 2~6 and 10~11 are harmonics in nonrestricted bands.
 7. *-indicates frequency is in the restricted bands.

HARMONICS AND SPURIOUS EMISSIONS (VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
*1(3 th harmonic)	1301.76	62.31	-13.64	48.67	74.00	-25.33	peak
/	/	/	/	37.13	54.00	-16.87	average
2(4 th harmonic)	1735.68	63.26	-11.94	51.32	80.80	-29.48	peak
/	/	/	/	39.78	60.80	-21.02	average
3(5 th harmonic)	2169.6	53.36	-10.19	43.17	80.80	-37.63	peak
/	/	/	/	31.63	60.80	-29.17	average
4(6 th harmonic)	2603.52	57.62	-8.18	49.44	80.80	-31.36	peak
/	/	/	/	37.9	60.80	-22.90	average
5(7 th harmonic)	3037.44	55.15	-6.9	48.25	80.80	-32.55	peak
/	/	/	/	36.71	60.80	-24.09	average
6(8 th harmonic)	3471.36	57.05	-5.92	51.13	80.80	-29.67	peak
/	/	/	/	39.59	60.80	-21.21	average
*7(9 th harmonic)	3905.28	48.28	-4.74	43.54	74.00	-30.46	peak
/	/	/	/	32	54.00	-22.00	average
*8(10 th harmonic)	4339.2	53.45	-2.89	50.56	74.00	-23.44	peak
/	/	/	/	39.02	54.00	-14.98	average
*9(11 th harmonic)	4773.12	51.34	-1.04	50.3	74.00	-23.70	peak
/	/	/	/	38.76	54.00	-15.24	average
10(12 th harmonic)	5207.04	43.27	0.09	43.36	80.80	-37.44	peak
/	/	/	/	31.82	60.80	-28.98	average
11(13 th harmonic)	5640.96	43.41	0.84	44.25	80.80	-36.55	peak
/	/	/	/	32.71	60.80	-28.09	average




- Note:
1. Result Level = Read Level + Correct Factor.
 2. Peak: Peak detector.
 3. Average Result = Peak Result + Duty Correction Factor.
 4. The average limit for harmonics out of the restrict bands are 60.8 dBuV/m, the average limit in the restrict bands is 54 dBuV/m.
 5. If peak result complies with average limit, the average result is deemed to comply with average limit.
 6. Mark 2~6 and 10~11 are harmonics in nonrestricted bands.
 7. *-indicates frequency is in the restricted bands.

6.4.3. SPURIOUS EMISSIONS BELOW 30 MHz

SPURIOUS EMISSIONS (LOOP ANTENNA FACE ON TO THE EUT)

0.09 kHz ~ 150 kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0100	76.72	-101.40	-24.68	47.60	-72.28	peak
2	0.0120	74.66	-101.39	-26.73	46.02	-72.75	peak
3	0.0131	73.95	-101.38	-27.43	45.25	-72.68	peak
4	0.0165	71.84	-101.37	-29.53	43.25	-72.78	peak
5	0.0221	70.13	-101.35	-31.22	40.71	-71.93	peak
6	0.0300	68.18	-101.39	-33.21	38.06	-71.27	peak

Note: 1. Measurement = Reading Level + Correct Factor. (dBuA/m= dBuV/m- 20Log10[120π] = dBuV/m- 51.5).

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

150 kHz ~ 490 kHz


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1554	76.27	-101.65	-25.38	23.77	-49.15	peak
2	0.1621	75.42	-101.65	-26.23	23.41	-49.64	peak
3	0.1877	72.23	-101.70	-29.47	22.14	-51.61	peak
4	0.2053	70.29	-101.73	-31.44	21.35	-52.79	peak
5	0.2442	67.53	-101.79	-34.26	19.85	-54.11	peak
6	0.3163	63.20	-101.87	-38.67	17.60	-56.27	peak

Note: 1. Measurement = Reading Level + Correct Factor. (dBuA/m= dBuV/m- 20Log10[120π] = dBuV/m- 51.5).

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

490 kHz ~ 30 MHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.5298	64.03	-62.08	1.95	33.12	-31.17	peak
2	0.6169	63.55	-62.08	1.47	31.80	-30.33	peak
3	0.8679	61.35	-62.18	-0.83	28.83	-29.66	peak
4	1.2214	58.12	-62.16	-4.04	25.87	-29.91	peak
5	1.5564	57.68	-62.02	-4.34	23.76	-28.10	peak
6	3.1598	55.73	-61.53	-5.80	29.54	-35.34	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Note: All the modes had been tested, only the worst data was recorded in the report.



7. ANTENNA REQUIREMENTS

APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

RESULTS

Complies

END OF REPORT