



Product Name: Remote Control Bulb	Report No: FCC022022-1002MPE
Product Model: YL-QP-APP-01	Security Classification: Open
Version: V1.0	Total Page: 5

TIRT Testing Report

Prepared By:	Checked By:	Approved By:	
Stone Tang	Randy Lv	Daniel Chen	
Stone Tang	Randy Lv	Daniel Chen	

FCC RF EXPOSURE REPORT

FCC ID: 2AZRW-YLLEDQAP

Equipment : Remote Control Bulb
Model Number : YL-QP-APP-01
Trade Mark : /
Product No. : 20220310003198
Applicant : Dong Guan Ya Li Electric Appliance Co., Ltd.
Address : THE FIVE STREET JINQIANLING JITIGANG HUANGJIANG
TOWN,DONGGUAN CITY, GUANGDONG 523000 CHINA
Manufacturer : Dong Guan Ya Li Electric Appliance Co., Ltd.
Address : THE FIVE STREET JINQIANLING JITIGANG HUANGJIANG
TOWN,DONGGUAN CITY, GUANGDONG 523000 CHINA
Factory : Dong Guan Ya Li Electric Appliance Co., Ltd.
Address : THE FIVE STREET JINQIANLING JITIGANG HUANGJIANG
TOWN,DONGGUAN CITY, GUANGDONG 523000 CHINA
Date of Receipt : 2022.03.09
Date of Test : 2022.03.09-2022.04.29
Test Sample : Final Sample
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

- The above equipment has been tested and found compliance with the requirement of the relative standards by TIRT Inc.
- The test result referred exclusively to the presented test model /sample.
- Without written approval of TIRT Inc., the test report shall not be reproduced except in full.

Lab: Beijing TIRT Technology Service Co.,Ltd Shenzhen

Add: 101, 3 # Factory Building, Gongjin Electronics Shatin Community, Kengzi Street, Pingshan

District, Shenzhen, China

TEL: +86-0755-27087573

History of this test report

Original Report Issue Date: 2022.05.25

- ☒ No additional attachment
- ☐ Additional attachments were issued following record

Attachment No.	Issue Date	Description

1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Both 2.4G WiFi and BLE

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	PCB	N/A	1.9

2. TEST RESULTS

For 2.4G WiFi:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. tune up Power (dBm)	Max. tune up Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
1.9	1.5488	19.39	86.8960	0.02679	1	Complies

For BLE:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. tune up Power (dBm)	Max. tune up Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
1.9	1.5488	6.16	4.1305	0.00127	1	Complies

For the max simultaneous transmission MPE:

2.4G WiFi + BLE

Power Density (S) (mW/cm ²)	Power Density (S) (mW/cm ²)	Total	Limit of Power Density (S) (mW/cm ²)	Test Result
2.4G WiFi	BLE			
0.02679	0.00127	0.02806	1	Complies

Note: The calculated distance is 20 cm.
Output power including tune up tolerance.

(END OF REPORT)