FCC Part 15CTest Report
FCC ID:2AZSY-SHRPTWS10

Applicant:	**Dongguan Symsta Electronics.,LTD**
Address:	Building 1,No.9,Xifa Road,Lincun,Tangxia Town, Dongguan, China
Manufacturer:	**Dongguan Symsta Electronics.,LTD**
Address:	Building 1,No.9,Xifa Road,Lincun,Tangxia Town, Dongguan, China
EUT:	True Wireless Earbuds
Trade Mark:	N/A
Model Number:	SHRP-TWS10 ACR-TWS01
Date of Receipt:	Jan. 01, 2026
Test Date:	Jan. 01, 2026 - Jan. 23, 2026
Date of Report:	Jan. 23, 2026
Prepared By:	Shenzhen DL Testing Technology Co., Ltd.
Address:	101-201, Building C, Shuanghuan, No.8, Baoqing Roa Baolong Industrial Zone, Baolong Street, Longgang Shenzhen, Guangdong, China
Applicable Standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247 ANSI C63.10:2020
Test Result:	Pass
Report Number:	DLE-260123021R

Prepared (Test Engineer):	Dimon Tan
Reviewer (Supervisor):	Jack Bu
Approved (Manager):	Jade Yang

This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.

Table of Contents

Page
1. VERSION 4
2. TEST SUMMARY 5
2.1 TEST FACILITY 6
2.2 MEASUREMENT UNCERTAINTY 6
3. GENERAL INFORMATION 7
3.1 GENERAL DESCRIPTION OF EUT 7
3.2 Test Setup Configuration 9
3.3 Support Equipment 9
3.4 Test Mode 10
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS 11
4. EMC EMISSION TEST 12
4.1 Conducted emissions 12
4.1.1 POWER LINE CONDUCTED EMISSION Limits 12
4.1.2 TEST PROCEDURE 12
4.1.3 DEVIATION FROM TEST STANDARD 12
4.1.4 TEST SETUP 13
4.1.5 EUT OPERATING CONDITIONS 13
4.1.6 Test Result 14
4.2 Radiated emissions 16
4.2.1 Radiated Emission Limits 16
4.2.2 TEST PROCEDURE 16
4.2.3 DEVIATION FROM TEST STANDARD 17
4.2.4 TEST SETUP 17
4.2.5 EUT OPERATING CONDITIONS 18
4.2.6 TEST RESULTS 19
5. RADIATED BAND EMISSION MEASUREMENT 25
5.1 Test Requirement: 25
5.2 TEST PROCEDURE 25
5.3 DEVIATION FROM TEST STANDARD 26
5.4 TEST SETUP 26
5.5 EUT OPERATING CONDITIONS 26
5.6 TEST RESULT 27
6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION 28
6.1 Limit 28
6.2 Test Setup 28
6.3 Test procedure 28
6.4 DEVIATION FROM STANDARD 28
6.5 Test Result 29
7. 20DB BANDWIDTH 41
7.1 Test Setup 41

7.2 Limit 41
7.3 Test procedure 41
7.4 DEVIATION FROM STANDARD 41
7.5 Test Result 42
8. MAXIMUM PEAK OUTPUT POWER 45
8.1 Block Diagram Of Test Setup 45
8.2 Limit 45
8.3 Test procedure 45
8.4 DEVIATION FROM STANDARD 45
8.5 Test Result 45
9. HOPPING CHANNEL SEPARATION 48
9.1 Test Setup 48
9.2 Test procedure 48
9.3 DEVIATION FROM STANDARD 48
9.4 Test Result 49
10.NUMBER OF HOPPING FREQUENCY 52
10.1 Test Setup 52
10.2 Test procedure 52
10.3 DEVIATION FROM STANDARD 52
10.4 Test Result 53
11. DWELL TIME 54
11.1 Test Setup 54
11.2 Test procedure 54
11.3 DEVIATION FROM STANDARD 54
11.4 Test Result 55
13. TEST SETUP PHOTO 59
14. EUT CONSTRUCTIONAL DETAILS 59

1. VERSION

Report No.	Version	Description	Approved
DLE-260123021R	Rev.01	Initial issue of report	Jan. 23, 2026

2. TEST SUMMARY

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
15.203/15.247 (c)	Antenna Requirement	PASS	
15.207	AC Power Line Conducted Emission	PASS	
15.247 (b)(1)	Conducted Peak Output Power	PASS	
15.247 (a)(1)	20dB Occupied Bandwidth	PASS	
15.247 (a)(1)	Carrier Frequencies Separation	PASS	
15.247 (a)(1)(iii)	Hopping Channel Number	PASS	
15.247 (a)(1)(iii)	Dwell Time	PASS	
15.205/15.209	Radiated Emission and Restricted Band	PASS	
15.247(d)	Conducted Unwanted emissions and Band Edge	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen DL Testing Technology Co., Ltd.
Add. : 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

FCC Test Firm Registration Number: 854456
Designation Number: CN1307
IC Registered No.:CN0118
ISED Registration number: 27485

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ± U，where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2，providing a level of confidence of approximately 95 %。

No.	Item	Uncertainty
1	3m camber Radiated spurious emission(9KHz-30MHz)	U=4.5dB
2	3m camber Radiated spurious emission(30MHz-1GHz)	U=4.8dB
3	3m chamber Radiated spurious emission(1GHz-6GHz)	U=4.9dB
4	3m chamber Radiated spurious emission(6GHz-40GHz)	U=5.0dB
5	Conducted disturbance	U=3.2dB
6	RF Band Edge	U=1.68dB
7	RF power conducted	U=1.86dB
8	RF conducted Spurious Emission	U=2.2dB
9	RF Occupied Bandwidth	U=1.8dB
10	RF Power Spectral Density	U=1.75dB
11	humidity uncertainty	U=5.3%
12	Temperature uncertainty	U=0.59℃

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	True Wireless Earbuds
Model No.:	SHRP-TWS10 ACR-TWS01
Model Different.:	all the models are electrically identical, including the same software parameters and hardware design (i.e., circuit design, PCB Layout, RF module/circuit, antenna type(s) and antenna location, components on PCB, etc.), as well as the same mechanical structure and design (including product enclosure, materials, etc.). The only differences are the model name and the external color (appearance color).
Sample ID	DLE-260123021R
Sample(s) Status:	Engineer sample
Channel numbers:	79
Operation Frequency:	2402MHz~2480MHz
Modulation technology:	GFSK, π/4-DQPSK
Antenna Type:	Chip Antenna
Antenna gain:	2.7 dBi
Power Supply:	Input: DC 5V, 1A Battery: 3.7V, 1200mAh, 4.4Wh

Note1: For a more detailed features description, please refer to the manufacturer’s specifications or the User's Manual.

Note2: The EUT's all information provided by client.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

3.2 Test Setup Configuration

Conducted Emission



Radiated Emission



Conducted Spurious



3.3 Support Equipment

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	True Wireless Earbuds	N/A	SHRP-TWS10	N/A	EUT
A1	AC/DC adapter	N/A	H6157-W1	N/A	Auxiliary
A2	USB line	N/A	ZKT-A2	N/A	Auxiliary

Item	Shielded Type	Ferrite Core	Length	Note

Note:
(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.

3.4 Test Mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Test Software	BT Test Tool
Power level setup	7dBm

3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Oct. 25, 2025	Oct. 24, 2026
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Oct. 27, 2025	Oct. 24, 2026
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Oct. 27, 2025	Oct. 26, 2026
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Oct. 25, 2025	Oct. 26, 2026
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Oct. 25, 2025	Oct. 24, 2026
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Oct. 25, 2025	Oct. 24, 2026
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Oct. 25, 2025	Oct. 24, 2026
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Oct. 25, 2025	Oct. 24, 2026
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Oct. 25, 2025	Oct. 24, 2026
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Oct. 25, 2025	Oct. 24, 2026
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Oct. 25, 2025	Oct. 24, 2026
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Oct. 25, 2025	Oct. 24, 2026
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Oct. 25, 2025	Oct. 24, 2026
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Oct. 25, 2025	Oct. 24, 2026
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Oct. 25, 2025	Oct. 24, 2026
16	D.C. Power Supply	LongWei	PS-305D	010964729	Oct. 25, 2025	Oct. 24, 2026

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	YIHENG	843 Room	843	Nov. 05, 2023	Nov. 04, 2026
2	EMI Receiver	R&S	ESR	101421	Oct. 25, 2025	Oct. 24, 2026
3	LISN	R&S	ENV216	102417	Oct. 25, 2025	Oct. 24, 2026
4	843 Cable 1#	ChengYu	CE Cable	001	Oct. 25, 2025	Oct. 24, 2026

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0

4. EMC EMISSION TEST

4.1 Conducted emissions

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2020
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6 Test Result

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Model:	GFSK 2402MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.2353	15.98	19.66	35.64	62.26	-26.62	QP	P
2	0.2353	10.03	19.66	29.69	52.26	-22.57	AVG	P
3	0.5954	14.24	19.63	33.87	56.00	-22.13	QP	P
4	0.5954	6.02	19.63	25.65	46.00	-20.35	AVG	P
5	3.8309	1.75	19.71	21.46	46.00	-24.54	AVG	P
6	3.9479	14.10	19.71	33.81	56.00	-22.19	QP	P
7	12.4483	1.74	19.76	21.50	50.00	-28.50	AVG	P
8	12.4664	14.11	19.76	33.87	60.00	-26.13	QP	P
9	23.8064	16.46	19.78	36.24	60.00	-23.76	QP	P
10	24.1528	1.92	19.78	21.70	50.00	-28.30	AVG	P
11	27.7078	13.10	19.76	32.86	60.00	-27.14	QP	P
12	27.7078	2.85	19.76	22.61	50.00	-27.39	AVG	P

Notes: All modes are tested. The report only shows data from the worst mode.
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Model:	GFSK 2402MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.2310	15.01	19.64	34.65	62.41	-27.76	QP	P
2	0.2353	10.19	19.64	29.83	52.26	-22.43	AVG	P
3	0.5907	14.05	19.62	33.67	56.00	-22.33	QP	P
4	0.5907	4.93	19.62	24.55	46.00	-21.45	AVG	P
5	3.8984	15.50	19.69	35.19	56.00	-20.81	QP	P
6	3.8984	1.38	19.69	21.07	46.00	-24.93	AVG	P
7	8.6730	12.44	19.74	32.18	60.00	-27.82	QP	P
8	8.6952	1.76	19.74	21.50	50.00	-28.50	AVG	P
9	12.5250	12.69	19.75	32.44	60.00	-27.56	QP	P
10	12.5834	1.48	19.76	21.24	50.00	-28.76	AVG	P
11	22.9875	1.11	19.76	20.87	50.00	-29.13	AVG	P
12	23.5048	13.97	19.75	33.72	60.00	-26.28	QP	P

Notes: All modes are tested. The report only shows data from the worst mode.
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

4.2 Radiated emissions

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10:2020
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	MX5Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

4.2.1 Radiated Emission Limits

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation

4.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS

Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	DC 3.7V	Model:	GFSK 2402MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.8534	32.90	-15.54	17.36	40.00	-22.64	QP
2	59.6492	30.67	-15.59	15.08	40.00	-24.92	QP
3	276.1234	30.19	-18.80	11.39	46.00	-34.61	QP
4	560.6928	30.13	-15.21	14.92	46.00	-31.08	QP
5	833.3170	31.28	-13.17	18.11	46.00	-27.89	QP
6	929.0081	32.92	-12.87	20.05	46.00	-25.95	QP

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	DC 3.7V	Model:	GFSK 2402MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.0000	35.82	-19.62	16.20	40.00	-23.80	QP
2	34.2760	32.90	-18.94	13.96	40.00	-26.04	QP
3	53.8817	30.03	-19.02	11.01	40.00	-28.99	QP
4	629.4772	30.22	-13.25	16.97	46.00	-29.03	QP
5	833.3170	33.28	-8.84	24.44	46.00	-21.56	QP
6	982.6200	30.68	-6.94	23.74	54.00	-30.26	QP

Remarks:
1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2.The emission levels of other frequencies are very lower than the limit and not show in test report.
3.The test data shows only the worst case GFSK 2402MHzmode

1GHz~25GHz

GFSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.00	53.79	30.55	5.77	24.66	53.67	74.00	-20.33	Pk
V	4804.00	43.47	30.55	5.77	24.66	43.35	54.00	-10.65	AV
V	7206.00	53.54	30.33	6.32	24.55	54.08	74.00	-19.92	Pk
V	7206.00	43.11	30.33	6.32	24.55	43.65	54.00	-10.35	AV
V	9608.00	54.85	30.85	7.45	24.69	56.14	74.00	-17.86	Pk
V	9608.00	43.41	30.85	7.45	24.69	44.70	54.00	-9.30	AV
V	12010.00	51.85	31.02	8.99	25.57	55.39	74.00	-18.61	Pk
V	12010.00	43.81	31.02	8.99	25.57	47.35	54.00	-6.65	AV
H	4804.00	52.21	30.55	5.77	24.66	52.09	74.00	-21.91	Pk
H	4804.00	43.76	30.55	5.77	24.66	43.64	54.00	-10.36	AV
H	7206.00	52.97	30.33	6.32	24.55	53.51	74.00	-20.49	Pk
H	7206.00	43.97	30.33	6.32	24.55	44.51	54.00	-9.49	AV
H	9608.00	51.99	30.85	7.45	24.69	53.28	74.00	-20.72	Pk
H	9608.00	43.28	30.85	7.45	24.69	44.57	54.00	-9.43	AV
H	12010.00	51.01	31.02	8.99	25.57	54.55	74.00	-19.45	Pk
H	12010.00	43.75	31.02	8.99	25.57	47.29	54.00	-6.71	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2441MHz									
V	4882.00	52.03	30.55	5.77	24.66	51.91	74.00	-22.09	Pk
V	4882.00	43.22	30.55	5.77	24.66	43.10	54.00	-10.90	AV
V	7323.00	50.61	30.33	6.32	24.55	51.15	74.00	-22.85	Pk
V	7323.00	43.51	30.33	6.32	24.55	44.05	54.00	-9.95	AV
V	9764.00	52.58	30.85	7.45	24.69	53.87	74.00	-20.13	Pk
V	9764.00	43.35	30.85	7.45	24.69	44.64	54.00	-9.36	AV
V	12205.00	52.03	31.02	8.99	25.57	55.57	74.00	-18.43	Pk
V	12205.00	43.58	31.02	8.99	25.57	47.12	54.00	-6.88	AV
H	4882.00	50.90	30.55	5.77	24.66	50.78	74.00	-23.22	Pk
H	4882.00	43.06	30.55	5.77	24.66	42.94	54.00	-11.06	AV
H	7323.00	53.12	30.33	6.32	24.55	53.66	74.00	-20.34	Pk
H	7323.00	43.53	30.33	6.32	24.55	44.07	54.00	-9.93	AV
H	9764.00	54.08	30.85	7.45	24.69	55.37	74.00	-18.63	Pk
H	9764.00	43.34	30.85	7.45	24.69	44.63	54.00	-9.37	AV
H	12205.00	52.87	31.02	8.99	25.57	56.41	74.00	-17.59	Pk
H	12205.00	43.05	31.02	8.99	25.57	46.59	54.00	-7.41	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	52.14	30.55	5.77	24.66	52.02	74.00	-21.98	Pk
V	4960.00	43.25	30.55	5.77	24.66	43.13	54.00	-10.87	AV
V	7440.00	50.66	30.33	6.32	24.55	51.20	74.00	-22.80	Pk
V	7440.00	43.31	30.33	6.32	24.55	43.85	54.00	-10.15	AV
V	9920.00	54.50	30.85	7.45	24.69	55.79	74.00	-18.21	Pk
V	9920.00	43.17	30.85	7.45	24.69	44.46	54.00	-9.54	AV
V	12400.00	50.89	31.02	8.99	25.57	54.43	74.00	-19.57	Pk
V	12400.00	43.69	31.02	8.99	25.57	47.23	54.00	-6.77	AV
H	4960.00	50.33	30.55	5.77	24.66	50.21	74.00	-23.79	Pk
H	4960.00	43.51	30.55	5.77	24.66	43.39	54.00	-10.61	AV
H	7440.00	52.40	30.33	6.32	24.55	52.94	74.00	-21.06	Pk
H	7440.00	43.60	30.33	6.32	24.55	44.14	54.00	-9.86	AV
H	9920.00	52.35	30.85	7.45	24.69	53.64	74.00	-20.36	Pk
H	9920.00	43.98	30.85	7.45	24.69	45.27	54.00	-8.73	AV
H	12400.00	54.70	31.02	8.99	25.57	58.24	74.00	-15.76	Pk
H	12400.00	43.56	31.02	8.99	25.57	47.10	54.00	-6.90	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

π/4-DQPSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.00	52.57	30.55	5.77	24.66	52.45	74.00	-21.55	Pk
V	4804.00	43.70	30.55	5.77	24.66	43.58	54.00	-10.42	AV
V	7206.00	51.24	30.33	6.32	24.55	51.78	74.00	-22.22	Pk
V	7206.00	43.89	30.33	6.32	24.55	44.43	54.00	-9.57	AV
V	9608.00	52.89	30.85	7.45	24.69	54.18	74.00	-19.82	Pk
V	9608.00	43.06	30.85	7.45	24.69	44.35	54.00	-9.65	AV
V	12010.00	52.70	31.02	8.99	25.57	56.24	74.00	-17.76	Pk
V	12010.00	43.13	31.02	8.99	25.57	46.67	54.00	-7.33	AV
H	4804.00	54.38	30.55	5.77	24.66	54.26	74.00	-19.74	Pk
H	4804.00	43.49	30.55	5.77	24.66	43.37	54.00	-10.63	AV
H	7206.00	50.24	30.33	6.32	24.55	50.78	74.00	-23.22	Pk
H	7206.00	43.30	30.33	6.32	24.55	43.84	54.00	-10.16	AV
H	9608.00	54.45	30.85	7.45	24.69	55.74	74.00	-18.26	Pk
H	9608.00	43.97	30.85	7.45	24.69	45.26	54.00	-8.74	AV
H	12010.00	50.46	31.02	8.99	25.57	54.00	74.00	-20.00	Pk
H	12010.00	43.30	31.02	8.99	25.57	46.84	54.00	-7.16	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2441MHz									
V	4882.00	52.00	30.55	5.77	24.66	51.88	74.00	-22.12	Pk
V	4882.00	43.26	30.55	5.77	24.66	43.14	54.00	-10.86	AV
V	7323.00	50.11	30.33	6.32	24.55	50.65	74.00	-23.35	Pk
V	7323.00	43.56	30.33	6.32	24.55	44.10	54.00	-9.90	AV
V	9764.00	52.33	30.85	7.45	24.69	53.62	74.00	-20.38	Pk
V	9764.00	43.52	30.85	7.45	24.69	44.81	54.00	-9.19	AV
V	12205.00	51.55	31.02	8.99	25.57	55.09	74.00	-18.91	Pk
V	12205.00	43.30	31.02	8.99	25.57	46.84	54.00	-7.16	AV
H	4882.00	52.47	30.55	5.77	24.66	52.35	74.00	-21.65	Pk
H	4882.00	43.19	30.55	5.77	24.66	43.07	54.00	-10.93	AV
H	7323.00	51.45	30.33	6.32	24.55	51.99	74.00	-22.01	Pk
H	7323.00	43.33	30.33	6.32	24.55	43.87	54.00	-10.13	AV
H	9764.00	53.68	30.85	7.45	24.69	54.97	74.00	-19.03	Pk
H	9764.00	43.48	30.85	7.45	24.69	44.77	54.00	-9.23	AV
H	12205.00	52.03	31.02	8.99	25.57	55.57	74.00	-18.43	Pk
H	12205.00	43.83	31.02	8.99	25.57	47.37	54.00	-6.63	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	51.30	30.55	5.77	24.66	51.18	74.00	-22.82	Pk
V	4960.00	43.35	30.55	5.77	24.66	43.23	54.00	-10.77	AV
V	7440.00	52.22	30.33	6.32	24.55	52.76	74.00	-21.24	Pk
V	7440.00	43.96	30.33	6.32	24.55	44.50	54.00	-9.50	AV
V	9920.00	51.98	30.85	7.45	24.69	53.27	74.00	-20.73	Pk
V	9920.00	43.50	30.85	7.45	24.69	44.79	54.00	-9.21	AV
V	12400.00	50.51	31.02	8.99	25.57	54.05	74.00	-19.95	Pk
V	12400.00	43.26	31.02	8.99	25.57	46.80	54.00	-7.20	AV
H	4960.00	51.99	30.55	5.77	24.66	51.87	74.00	-22.13	Pk
H	4960.00	43.69	30.55	5.77	24.66	43.57	54.00	-10.43	AV
H	7440.00	53.87	30.33	6.32	24.55	54.41	74.00	-19.59	Pk
H	7440.00	43.47	30.33	6.32	24.55	44.01	54.00	-9.99	AV
H	9920.00	50.81	30.85	7.45	24.69	52.10	74.00	-21.90	Pk
H	9920.00	43.49	30.85	7.45	24.69	44.78	54.00	-9.22	AV
H	12400.00	50.60	31.02	8.99	25.57	54.14	74.00	-19.86	Pk
H	12400.00	43.93	31.02	8.99	25.57	47.47	54.00	-6.53	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5. RADIATED BAND EMISSION MEASUREMENT

5.1 Test Requirement:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205
Test Method:	ANSI C63.10: 2020
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2390MHz to 2500MHz) data was showed.
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
Above 1GHz	Peak	1MHz	3MHz	Peak
	Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2390MHz
Stop Frequency	2500MHz
RB / VB (emission in restricted band)	1 MHz / 3 MHz for Peak, 1 MHz / 3MHz for Average

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

g. Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Detector Type	Result
GFSK	Low Channel: 2402MHz									
	H	2390.00	54.43	30.22	4.85	23.98	53.04	74.00	PK	PASS
	H	2390.00	44.02	30.22	4.85	23.98	42.63	54.00	AV	PASS
	H	2400.00	53.35	30.22	4.85	23.98	51.96	74.00	PK	PASS
	H	2400.00	44.77	30.22	4.85	23.98	43.38	54.00	AV	PASS
	V	2390.00	54.48	30.22	4.85	23.98	53.09	74.00	PK	PASS
	V	2390.00	44.47	30.22	4.85	23.98	43.08	54.00	AV	PASS
	V	2400.00	53.74	30.22	4.85	23.98	52.35	74.00	PK	PASS
	V	2400.00	44.76	30.22	4.85	23.98	43.37	54.00	AV	PASS
	High Channel: 2480MHz									
	H	2483.50	53.99	30.22	4.85	23.98	52.60	74.00	Pk	PASS
	H	2483.50	44.76	30.22	4.85	23.98	43.37	54.00	AV	PASS
	H	2500.00	54.60	30.22	4.85	23.98	53.21	74.00	Pk	PASS
	H	2500.00	44.48	30.22	4.85	23.98	43.09	54.00	AV	PASS
	V	2483.50	53.59	30.22	4.85	23.98	52.20	74.00	Pk	PASS
	V	2483.50	44.41	30.22	4.85	23.98	43.02	54.00	AV	PASS
	V	2500.00	54.67	30.22	4.85	23.98	53.28	74.00	Pk	PASS
	V	2500.00	44.17	30.22	4.85	23.98	42.78	54.00	AV	PASS
π/4-DQPSK	Low Channel: 2402MHz									
	H	2390.00	53.11	30.22	4.85	23.98	51.72	74.00	PK	PASS
	H	2390.00	44.05	30.22	4.85	23.98	42.66	54.00	AV	PASS
	H	2400.00	53.50	30.22	4.85	23.98	52.11	74.00	PK	PASS
	H	2400.00	44.82	30.22	4.85	23.98	43.43	54.00	AV	PASS
	V	2390.00	53.28	30.22	4.85	23.98	51.89	74.00	PK	PASS
	V	2390.00	44.47	30.22	4.85	23.98	43.08	54.00	AV	PASS
	V	2400.00	53.92	30.22	4.85	23.98	52.53	74.00	PK	PASS
	V	2400.00	44.89	30.22	4.85	23.98	43.50	54.00	AV	PASS
	High Channel: 2480MHz									
	H	2483.50	54.44	30.22	4.85	23.98	53.05	74.00	PK	PASS
	H	2483.50	44.51	30.22	4.85	23.98	43.12	54.00	AV	PASS
	H	2500.00	54.98	30.22	4.85	23.98	53.59	74.00	PK	PASS
	H	2500.00	44.98	30.22	4.85	23.98	43.59	54.00	AV	PASS
	V	2483.50	53.47	30.22	4.85	23.98	52.08	74.00	PK	PASS
	V	2483.50	44.91	30.22	4.85	23.98	43.52	54.00	AV	PASS
	V	2500.00	54.54	30.22	4.85	23.98	53.15	74.00	PK	PASS
	V	2500.00	44.40	30.22	4.85	23.98	43.01	54.00	AV	PASS

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

6.1 Limit

Regulation 15.247 (d),In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.2 Test Setup

30

6.3 Test procedure

Using the following spectrum analyzer setting:
A) Set the RBW = 100KHz.
B) Set the VBW = 300KHz.
C) Sweep time = auto couple.
D) Detector function = peak.
E) Trace mode = max hold.
F) Allow trace to fully stabilize.

6.4 DEVIATION FROM STANDARD

No deviation.

6.5 Test Result

GFSK mode:

Test channel:	Lowest channel





30MHz~26.5GHz

Test channel:	Middle channel





30MHz~26.5GHz

Test channel:	Highest channel





30MHz~26.5GHz

π/4-DQPSK mode:

Test channel:	Lowest channel





30MHz~26.5GHz

Test channel:	Middle channel





30MHz~26.5GHz

Test channel:	Highest channel





30MHz~26.5GHz

Test Graphs

Band Edge NVNT 1-DH1 2402MHz No-Hopping Ref



Band Edge NVNT 1-DH1 2402MHz No-Hopping Emission



Band Edge NVNT 1-DH1 2480MHz No-Hopping Ref



Band Edge NVNT 1-DH1 2480MHz No-Hopping Emission



Band Edge NVNT 2-DH1 2402MHz No-Hopping Ref



Band Edge NVNT 2-DH1 2402MHz No-Hopping Emission



Band Edge NVNT 2-DH1 2480MHz No-Hopping Ref



Band Edge NVNT 2-DH1 2480MHz No-Hopping Emission



Test Graphs

Band Edge(Hopping) NVNT 1-DH1 2402MHz Hopping Ref

Band Edge(Hopping) NVNT 1-DH1 2402MHz Hopping Emission



Band Edge(Hopping) NVNT 1-DH1 2480MHz Hopping Ref

Band Edge(Hopping) NVNT 1-DH1 2480MHz Hopping Emission



Band Edge(Hopping) NVNT 2-DH1 2402MHz Hopping Ref

Band Edge(Hopping) NVNT 2-DH1 2402MHz Hopping Emission



Band Edge(Hopping) NVNT 2-DH1 2480MHz Hopping Ref

Band Edge(Hopping) NVNT 2-DH1 2480MHz Hopping Emission



7. 20DB BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2020

7.1 Test Setup

7.2 Limit

N/A

7.3 Test procedure

1. Set RBW = 30 kHz.
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

7.4 DEVIATION FROM STANDARD

No deviation.

7.5 Test Result

Mode	Test channel	20dB Emission Bandwidth (MHz)	Result
GFSK	Lowest	0.894	Pass
	Middle	0.893	
	Highest	0.892	
π/4-DQPSK	Lowest	1.242	Pass
	Middle	1.247	
	Highest	1.248	

Test Graphs

-20dB Bandwidth NVNT 1-DH1 2402MHz

-20dB Bandwidth NVNT 1-DH1 2441MHz

-20dB Bandwidth NVNT 1-DH1 2480MHz

-20dB Bandwidth NVNT 2-DH1 2402MHz



-20dB Bandwidth NVNT 2-DH1 2441MHz



-20dB Bandwidth NVNT 2-DH1 2480MHz



8. Maximum Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2020
Limit:	GFSK:30 dBm π/4-DQPSK & 8-DPSK:20.97 dBm

8.1 Block Diagram Of Test Setup

8.2 Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels. The e.i.r.p. shall not exceed 4 W.

8.3 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.

2. Set the spectrum analyzer: RBW = 2MHz. VBW =6MHz. Sweep = auto; Detector Function = Peak.

3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

8.4 DEVIATION FROM STANDARD

No deviation.

8.5 Test Result

Mode	Test channel	Peak Output Power (dBm)	FCC Limit (dBm)	Result
GFSK	Lowest	-2.252	30.00	Pass
	Middle	-3.327		
	Highest	-4.587		
π/4-DQPSK	Lowest	-1.557	21.00	Pass
	Middle	-2.619		
	Highest	-4.007		

Test Graphs

Power NVNT 1-DH1 2402MHz



Power NVNT 1-DH1 2441MHz



Power NVNT 1-DH1 2480MHz



Power NVNT 2-DH1 2402MHz



Power NVNT 2-DH1 2441MHz



Power NVNT 2-DH1 2480MHz



9. HOPPING CHANNEL SEPARATION

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2020
Receiver setup:	RBW=30KHz, VBW=100KHz, detector=Peak
Limit:	GFSK: 20dB bandwidth π/4-DQPSK & 8DSK: 0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)

9.1 Test Setup

9.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.

2. Set the spectrum analyzer: RBW = 30kHz. VBW = 100kHz , Span = 2.0MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.

3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 Test Result

Modulation	Test Channel	Separation (MHz)	Limit(MHz)	Result
GFSK	Low	1.02	0.894	PASS
GFSK	Middle	1.011	0.893	PASS
GFSK	High	0.897	0.892	PASS
π/4-DQPSK	Low	0.987	0.828	PASS
π/4-DQPSK	Middle	1.218	0.831	PASS
π/4-DQPSK	High	0.984	0.832	PASS

Test plots
GFSK Low Channel

GFSK Middle Channel

GFSK High Channel

π/4-DQPSK Low Channel



π/4-DQPSK Middle Channel



π /4-DQPSK High Channel



10.NUMBER OF HOPPING FREQUENCY

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	ANSI C63.10:2020
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	GFSK 75 channels, π/4-DQPSK 15channels

10.1 Test Setup

10.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.

2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.

3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.

4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz. Sweep=auto;

10.3 DEVIATION FROM STANDARD

No deviation.

10.4 Test Result

Modulation	Packet	Hopping Number	Limit	Result
GFSK	1-DH1	79	≥75	Pass
π/4-DQPSK	2-DH1	79	≥15	Pass

Test Graphs

Hopping No. NVNT 1-DH1 2441MHz



Hopping No. NVNT 2-DH1 2441MHz



11. DWELL TIME

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	ANSI C63.10:2020
Receiver setup:	RBW=1MHz, VBW=3MHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second

11.1 Test Setup

11.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.

2. Set spectrum analyzer span = 0Hz;

3. Set RBW = 1MHz and VBW = 3MHz.Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3, DH1, 2DH5, 2DH3 and 2DH1 packet transmitting.

4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g.. data rate. modulation format. etc.). repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

11.3 DEVIATION FROM STANDARD

No deviation.

11.4 Test Result

Mode	Frequency (MHz)	Pulse Time (ms)	Total Dwell Time (ms)	Period Time (ms)	Limit (ms)	Verdict
1-DH1	2441	0.402	128.64	31600	400	Pass
1-DH3	2441	1.657	265.12	31600	400	Pass
1-DH5	2441	2.906	309.973	31600	400	Pass
2-DH1	2441	0.412	131.84	31600	400	Pass
2-DH3	2441	1.663	266.08	31600	400	Pass
2-DH5	2441	2.912	310.613	31600	400	Pass

Remarks:

The test period: T= 0.4 Second/Channel x 79 Channel = 31600ms

Test channel: as blow

CH:2441MHz time slot=test data(ms)*(1600/ (2*79))*31600ms

CH:2441MHz time slot=test data(ms)*(1600/ (4*79))*31600ms

CH:2441MHz time slot=test data(ms)*(1600/ (6*79))*31600ms

Test Graphs

Dwell NVNT 1-DH1 2441MHz



Dwell NVNT 1-DH3 2441MHz



Dwell NVNT 1-DH5 2441MHz



Dwell NVNT 2-DH1 2441MHz



Dwell NVNT 2-DH3 2441MHz



Dwell NVNT 2-DH5 2441MHz



12. Antenna Requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
The antenna is Chip Antenna, the best case gain of the antennas is 2.7 dBi, reference to the appendix II for details	

13. Test Setup Photo

Reference to the appendix I for details.

14. EUT Constructional Details

Reference to the appendix II for details.

※※※※※ END OF REPORT ※※※※※