






BLE\_2M-Ant1-2440-0~Reference-PASS




BLE\_2M-Ant1-2440-30~1000-PASS




BLE\_2M-Ant1-2440-1000~26500-PASS



BLE\_2M-Ant1-2480-0~Reference-PASS



BLE\_2M-Ant1-2480-30~1000-PASS



BLE\_2M-Ant1-2480-1000~26500-PASS

## 8.5 RADIATED SPURIOUS EMISSION

### 8.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 Meas Guidance v05r02.

### 8.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands:

| MHz               | MHz                 | MHz           | GHz         |
|-------------------|---------------------|---------------|-------------|
| 0.090-0.110       | 16.42-16.423        | 399.9-410     | 4.5-5.15    |
| 10.495-0.505      | 16.69475-16.69525   | 608-614       | 5.35-5.46   |
| 2.1735-2.1905     | 16.80425-16.80475   | 960-1240      | 7.25-7.75   |
| 4.125-4.128       | 25.5-25.67          | 1300-1427     | 8.025-8.5   |
| 4.17725-4.17775   | 37.5-38.25          | 1435-1626.5   | 9.0-9.2     |
| 4.20725-4.20775   | 73-74.6             | 1645.5-1646.5 | 9.3-9.5     |
| 6.215-6.218       | 74.8-75.2           | 1660-1710     | 10.6-12.7   |
| 6.26775-6.26825   | 123-138             | 2200-2300     | 14.47-14.5  |
| 8.291-8.294       | 149.9-150.05        | 2310-2390     | 15.35-16.2  |
| 8.362-8.366       | 156.52475-156.52525 | 2483.5-2500   | 17.7-21.4   |
| 8.37625-8.38675   | 156.7-156.9         | 2690-2900     | 22.01-23.12 |
| 8.41425-8.41475   | 162.0125-167.17     | 3260-3267     | 23.6-24.0   |
| 12.29-12.293      | 167.72-173.2        | 3332-3339     | 31.2-31.8   |
| 12.51975-12.52025 | 240-285             | 3345.8-3358   | 36.43-36.5  |
| 12.57675-12.57725 | 322-335.4           | 3600-4400     | (2)         |
| 13.36-13.41       |                     |               |             |

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table.

| Restricted Frequency(MHz) | Field Strength (μV/m) | Field Strength (dBμV/m) | Measurement Distance |
|---------------------------|-----------------------|-------------------------|----------------------|
| 0.009-0.490               | 2400/F(KHz)           | 20 log (uV/m)           | 300                  |
| 0.490-1.705               | 24000/F(KHz)          | 20 log (uV/m)           | 30                   |
| 1.705-30                  | 30                    | 29.5                    | 30                   |
| 30-88                     | 100                   | 40                      | 3                    |
| 88-216                    | 150                   | 43.5                    | 3                    |
| 216-960                   | 200                   | 46                      | 3                    |
| Above 960                 | 500                   | 54                      | 3                    |

### 8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2.

### 8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured.

RBW = 1 MHz for  $f \geq 1$  GHz (1GHz to 25GHz), 100 kHz for  $f < 1$  GHz (30MHz to 1GHz).

VBW  $\geq$  RBW.

Sweep = auto.

Detector function = peak.

Trace = max hold.

Follow the guidelines in ANSI C63.10-2020/Cor 1-2021 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.



### 8.5.5 Test Results

Temperature : 25°C      ATM Pressure: 1011 mbar  
Humidity : 60 %      Test Engineer: LJM

All of the configurations or modes are tested, the data of the worst case is recorded as below.

#### ■ Spurious Emission below 30MHz (9KHz to 30MHz)

| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Emission<br>Level(dBuV/m) |    | Limit 3m(dBuV/m) |    | Over(dB) |    |
|----------------|-----------------|---------------------------|----|------------------|----|----------|----|
|                |                 | PK                        | AV | PK               | AV | PK       | AV |
| --             | --              | --                        | -- | --               | -- | --       | -- |

Note: Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


#### ■ Spurious Emission Above 1GHz (1GHz to 25GHz)

no any obvious emission were detected from 18 GHz to 40 GHz, so below finaltest was performed with frequency range from 1GHz to 18 GHz.


Test mode: BLE(1M)      Frequency: Channel 0: 2402MHz

| Freq.<br>(MHz) | Ant.Pol. | Emission<br>Level(dBuV/m) | Limit<br>3m(dBuV/m) | Over(dB) | Detector |
|----------------|----------|---------------------------|---------------------|----------|----------|
| 4406.25        | V        | 49.06                     | 74.00               | 24.94    | peak     |
| 8401.87        | V        | 58.83                     | 74.00               | 15.17    | peak     |
| 16666.8        | V        | 66.70                     | 74.00               | 7.30     | peak     |
| 4406.25        | V        | 31.08                     | 54.00               | 22.92    | AVG      |
| 8401.87        | V        | 39.04                     | 54.00               | 14.96    | AVG      |
| 16666.8        | V        | 46.41                     | 54.00               | 7.59     | AVG      |
| 4218.75        | H        | 48.53                     | 74.00               | 25.47    | peak     |
| 8368.12        | H        | 58.64                     | 74.00               | 15.36    | peak     |
| 16635          | H        | 66.90                     | 74.00               | 7.10     | peak     |
| 4218.75        | H        | 30.73                     | 54.00               | 23.27    | AVG      |
| 8368.1         | H        | 38.69                     | 54.00               | 15.31    | AVG      |
| 16635          | H        | 46.43                     | 54.00               | 7.57     | AVG      |

Vertical




## Horizontal




Test mode: BLE(1M) Frequency: Channel 19: 2440MHz

| Freq. (MHz) | Ant.Pol. | Emission Level(dBuV/m) | Limit 3m(dBuV/m) | Over(dB) | Detector |
|-------------|----------|------------------------|------------------|----------|----------|
| 4400.62     | V        | 48.54                  | 74.00            | 25.46    | peak     |
| 8353.12     | V        | 58.94                  | 74.00            | 15.06    | peak     |
| 16575       | V        | 66.75                  | 74.00            | 7.25     | peak     |
| 4400.62     | V        | 30.55                  | 54.00            | 23.45    | AVG      |
| 8353.12     | V        | 38.30                  | 54.00            | 15.70    | AVG      |
| 16575       | V        | 46.22                  | 54.00            | 7.78     | AVG      |
| 4183.12     | H        | 47.94                  | 74.00            | 26.06    | peak     |
| 8473.12     | H        | 59.03                  | 74.00            | 14.97    | peak     |
| 16606.8     | H        | 66.88                  | 74.00            | 7.12     | peak     |
| 4183.12     | H        | 30.82                  | 54.00            | 23.18    | AVG      |
| 8473.12     | H        | 37.96                  | 54.00            | 16.04    | AVG      |
| 16606.8     | H        | 45.54                  | 54.00            | 8.46     | AVG      |

## Vertical




## Horizontal




Test mode: BLE(1M) Frequency: Channel 39: 2480MHz

| Freq. (MHz) | Ant. Pol. | Emission Level(dBuV/m) | Limit 3m(dBuV/m) | Over(dB) | Detector |
|-------------|-----------|------------------------|------------------|----------|----------|
| 4241.25     | V         | 48.47                  | 74.00            | 25.53    | peak     |
| 8456.25     | V         | 59.70                  | 74.00            | 14.30    | peak     |
| 16642.5     | V         | 66.71                  | 74.00            | 7.29     | peak     |
| 4241.25     | V         | 31.23                  | 54.00            | 22.77    | AVG      |
| 8456.25     | V         | 38.80                  | 54.00            | 15.20    | AVG      |
| 16642.5     | V         | 46.44                  | 54.00            | 7.56     | AVG      |
| 4241.25     | H         | 48.38                  | 74.00            | 25.62    | peak     |
| 8356.87     | H         | 58.70                  | 74.00            | 15.30    | peak     |
| 16635       | H         | 66.65                  | 74.00            | 7.35     | peak     |
| 4241.25     | H         | 30.99                  | 54.00            | 23.01    | AVG      |
| 8356.87     | H         | 38.18                  | 54.00            | 15.82    | AVG      |
| 16635       | H         | 46.67                  | 54.00            | 7.33     | AVG      |

## Vertical



## Horizontal



- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
  - (2) Emission Level= Reading Level+Correct Factor.
  - (3) Correct Factor= Ant\_F + Cab\_L - Preamp
  - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Test mode: BLE(1M) Frequency: Channel 0: 2402MHz

| Freq.<br>(MHz) | Ant.Pol. | Emission<br>Level(dBuV/m) | Limit<br>3m(dBuV/m) | Over(dB) | Detector |
|----------------|----------|---------------------------|---------------------|----------|----------|
| 2389.65        | V        | 50.53                     | 74.00               | 23.47    | peak     |
| 2389.65        | V        | 38.67                     | 54.00               | 15.33    | AVG      |
| 2383.27        | H        | 49.21                     | 74.00               | 24.79    | peak     |
| 2383.27        | H        | 38.77                     | 54.00               | 15.23    | AVG      |

Test mode: BLE(1M) Frequency: Channel 39: 2480MHz

| Freq.<br>(MHz) | Ant.Pol. | Emission<br>Level(dBuV/m) | Limit<br>3m(dBuV/m) | Over(dB) | Detector |
|----------------|----------|---------------------------|---------------------|----------|----------|
| 2483.93        | V        | 51.96                     | 74.00               | 22.04    | peak     |
| 2483.93        | V        | 39.03                     | 54.00               | 14.97    | AVG      |
| 2483.57        | H        | 51.39                     | 74.00               | 22.61    | peak     |
| 2483.57        | H        | 38.41                     | 54.00               | 15.59    | AVG      |


- Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).  
 (2) Emission Level= Reading Level+Correct Factor.  
 (3) Correct Factor= Ant\_F + Cab\_L - Preamp  
 ((4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Test Model

Spurious Emission in Restricted Band 2310-2390MHz  
BLE(1M)

Channel 0: 2402MHz

H




Test Model

Spurious Emission in Restricted Band 2310-2390MHz  
BLE(1M)

Channel 0: 2402MHz

V




Test Model

Spurious Emission in Restricted Band 2483.5-2500MHz  
BLE(1M)

Channel 39: 2480MHz

H




Test Model

Spurious Emission in Restricted Band 2483.5-2500MHz  
BLE(1M)


Channel 39: 2480MHz

V




■ Spurious Emission below 1GHz (30MHz to 1GHz)

Test mode: BLE(1M) Frequency: Channel 0: 2402MHz



| Suspected Data List |             |                |               |                |          |                |             |          |
|---------------------|-------------|----------------|---------------|----------------|----------|----------------|-------------|----------|
| NO.                 | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Detector | Limit [dBμV/m] | Margin [dB] | Polarity |
| 1                   | 48.4484     | 27.69          | -8.84         | 18.85          | PK       | 40.00          | 21.15       | Vertical |
| 2                   | 65.9259     | 29.68          | -10.67        | 19.01          | PK       | 40.00          | 20.99       | Vertical |
| 3                   | 596.076     | 25.14          | 0.41          | 25.55          | PK       | 46.00          | 20.45       | Vertical |
| 4                   | 689.289     | 25.79          | 0.46          | 26.25          | PK       | 46.00          | 19.75       | Vertical |
| 5                   | 835.905     | 25.75          | 2.07          | 27.82          | PK       | 46.00          | 18.18       | Vertical |
| 6                   | 956.306     | 26.20          | 3.72          | 29.92          | PK       | 46.00          | 16.08       | Vertical |


| Final Data List |             |               |                   |                   |                |
|-----------------|-------------|---------------|-------------------|-------------------|----------------|
| NO.             | Freq. [MHz] | Factor [dB/m] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] |
| 1               | 48.4484     | -8.84         | 18.51             | 40.00             | 21.49          |
| 2               | 65.9259     | -10.67        | 18.67             | 40.00             | 21.33          |
| 3               | 596.0761    | 0.41          | 25.04             | 46.00             | 20.96          |
| 4               | 689.2893    | 0.46          | 25.74             | 46.00             | 20.26          |
| 5               | 835.9059    | 2.07          | 27.67             | 46.00             | 18.33          |
| 6               | 956.3063    | 3.72          | 29.77             | 46.00             | 16.23          |



| Suspected Data List |             |                |               |                |          |                |             |            |
|---------------------|-------------|----------------|---------------|----------------|----------|----------------|-------------|------------|
| NO.                 | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Detector | Limit [dBμV/m] | Margin [dB] | Polarity   |
| 1                   | 33.8839     | 29.49          | -11.09        | 18.40          | PK       | 40.00          | 21.60       | Horizontal |
| 2                   | 430.04      | 28.61          | -4.20         | 24.41          | PK       | 46.00          | 21.59       | Horizontal |
| 3                   | 438.778     | 30.09          | -3.87         | 26.22          | PK       | 46.00          | 19.78       | Horizontal |
| 4                   | 585.395     | 25.60          | -0.08         | 25.52          | PK       | 46.00          | 20.48       | Horizontal |
| 5                   | 714.534     | 25.20          | 1.05          | 26.25          | PK       | 46.00          | 19.75       | Horizontal |
| 6                   | 825.225     | 25.92          | 1.79          | 27.71          | PK       | 46.00          | 18.29       | Horizontal |

| Final Data List |             |               |                   |                   |                |
|-----------------|-------------|---------------|-------------------|-------------------|----------------|
| NO.             | Freq. [MHz] | Factor [dB/m] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] |
| 1               | 33.8839     | -11.09        | 18.00             | 40.00             | 22.00          |
| 2               | 430.04      | -4.20         | 24.01             | 46.00             | 21.99          |
| 3               | 438.7788    | -3.87         | 26.18             | 46.00             | 19.82          |
| 4               | 585.3954    | -0.08         | 24.83             | 46.00             | 21.17          |
| 5               | 714.5345    | 1.05          | 25.56             | 46.00             | 20.44          |
| 6               | 825.2252    | 1.79          | 27.02             | 46.00             | 18.98          |

Test mode: BLE(1M) Frequency: Channel 19: 2440MHz




#### Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Detector | Limit [dBμV/m] | Margin [dB] | Polarity |
|-----|-------------|----------------|---------------|----------------|----------|----------------|-------------|----------|
| 1   | 65.9259     | 29.25          | -10.67        | 18.58          | PK       | 40.00          | 21.42       | Vertical |
| 2   | 72.7227     | 28.95          | -11.60        | 17.35          | PK       | 40.00          | 22.65       | Vertical |
| 3   | 591.221     | 25.43          | 0.17          | 25.60          | PK       | 46.00          | 20.40       | Vertical |
| 4   | 698.999     | 25.49          | 0.86          | 26.35          | PK       | 46.00          | 19.65       | Vertical |
| 5   | 845.615     | 25.57          | 2.39          | 27.96          | PK       | 46.00          | 18.04       | Vertical |
| 6   | 959.219     | 25.93          | 3.86          | 29.79          | PK       | 46.00          | 16.21       | Vertical |

#### Final Data List


| NO. | Freq. [MHz] | Factor [dB/m] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] |
|-----|-------------|---------------|-------------------|-------------------|----------------|
| 1   | 65.9259     | -10.67        | 18.08             | 40.00             | 21.92          |
| 2   | 72.7227     | -11.60        | 16.85             | 40.00             | 23.15          |
| 3   | 591.2212    | 0.17          | 25.46             | 46.00             | 20.54          |
| 4   | 698.999     | 0.86          | 26.21             | 46.00             | 19.79          |
| 5   | 845.6156    | 2.39          | 27.66             | 46.00             | 18.34          |
| 6   | 959.2192    | 3.86          | 29.49             | 46.00             | 16.51          |



| Suspected Data List |             |                |               |                |          |                |             |            |
|---------------------|-------------|----------------|---------------|----------------|----------|----------------|-------------|------------|
| NO.                 | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Detector | Limit [dBμV/m] | Margin [dB] | Polarity   |
| 1                   | 33.8839     | 29.63          | -11.09        | 18.54          | PK       | 40.00          | 21.46       | Horizontal |
| 2                   | 49.4194     | 24.97          | -8.69         | 16.28          | PK       | 40.00          | 23.72       | Horizontal |
| 3                   | 51.3614     | 25.29          | -8.78         | 16.51          | PK       | 40.00          | 23.49       | Horizontal |
| 4                   | 590.250     | 25.01          | 0.12          | 25.13          | PK       | 46.00          | 20.87       | Horizontal |
| 5                   | 673.753     | 26.81          | 0.12          | 26.93          | PK       | 46.00          | 19.07       | Horizontal |
| 6                   | 830.080     | 26.25          | 1.94          | 28.19          | PK       | 46.00          | 17.81       | Horizontal |


| Final Data List |             |               |                   |                   |                |
|-----------------|-------------|---------------|-------------------|-------------------|----------------|
| NO.             | Freq. [MHz] | Factor [dB/m] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] |
| 1               | 33.8839     | -11.09        | 17.95             | 40.00             | 22.05          |
| 2               | 49.4194     | -8.69         | 16.05             | 40.00             | 23.95          |
| 3               | 51.3614     | -8.78         | 16.28             | 40.00             | 23.72          |
| 4               | 590.2503    | 0.12          | 24.74             | 46.00             | 21.26          |
| 5               | 673.7538    | 0.12          | 26.54             | 46.00             | 19.46          |
| 6               | 830.0801    | 1.94          | 28.16             | 46.00             | 17.84          |

Test mode: BLE(1M) Frequency: Channel 39: 2480MHz



| Suspected Data List |             |                |               |                |          |                |             |          |
|---------------------|-------------|----------------|---------------|----------------|----------|----------------|-------------|----------|
| NO.                 | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Detector | Limit [dBμV/m] | Margin [dB] | Polarity |
| 1                   | 33.8839     | 28.63          | -11.09        | 17.54          | PK       | 40.00          | 22.46       | Vertical |
| 2                   | 54.2743     | 26.46          | -9.15         | 17.31          | PK       | 40.00          | 22.69       | Vertical |
| 3                   | 66.8969     | 29.55          | -10.79        | 18.76          | PK       | 40.00          | 21.24       | Vertical |
| 4                   | 601.901     | 26.28          | 0.49          | 26.77          | PK       | 46.00          | 19.23       | Vertical |
| 5                   | 698.028     | 25.49          | 0.82          | 26.31          | PK       | 46.00          | 19.69       | Vertical |
| 6                   | 826.196     | 25.92          | 1.82          | 27.74          | PK       | 46.00          | 18.26       | Vertical |

| Final Data List |             |               |                   |                   |                |
|-----------------|-------------|---------------|-------------------|-------------------|----------------|
| NO.             | Freq. [MHz] | Factor [dB/m] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] |
| 1               | 33.8839     | -11.09        | 16.97             | 40.00             | 23.03          |
| 2               | 54.2743     | -9.15         | 16.57             | 40.00             | 23.43          |
| 3               | 66.8969     | -10.79        | 18.02             | 40.00             | 21.98          |
| 4               | 601.9019    | 0.49          | 26.39             | 46.00             | 19.61          |
| 5               | 698.028     | 0.82          | 25.93             | 46.00             | 20.07          |
| 6               | 826.1962    | 1.82          | 27.72             | 46.00             | 18.28          |



| Suspected Data List |             |                |               |                |          |                |             |            |
|---------------------|-------------|----------------|---------------|----------------|----------|----------------|-------------|------------|
| NO.                 | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Detector | Limit [dBμV/m] | Margin [dB] | Polarity   |
| 1                   | 33.8839     | 29.75          | -11.09        | 18.66          | PK       | 40.00          | 21.34       | Horizontal |
| 2                   | 47.4775     | 25.33          | -9.00         | 16.33          | PK       | 40.00          | 23.67       | Horizontal |
| 3                   | 474.704     | 27.60          | -3.08         | 24.52          | PK       | 46.00          | 21.48       | Horizontal |
| 4                   | 597.047     | 25.17          | 0.46          | 25.63          | PK       | 46.00          | 20.37       | Horizontal |
| 5                   | 715.505     | 25.39          | 1.03          | 26.42          | PK       | 46.00          | 19.58       | Horizontal |
| 6                   | 840.760     | 24.95          | 2.19          | 27.14          | PK       | 46.00          | 18.86       | Horizontal |

| Final Data List |             |               |                   |                   |                |
|-----------------|-------------|---------------|-------------------|-------------------|----------------|
| NO.             | Freq. [MHz] | Factor [dB/m] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] |
| 1               | 33.8839     | -11.09        | 18.58             | 40.00             | 21.42          |
| 2               | 47.4775     | -9.00         | 15.61             | 40.00             | 24.39          |
| 3               | 474.7047    | -3.08         | 24.16             | 46.00             | 21.84          |
| 4               | 597.047     | 0.46          | 25.27             | 46.00             | 20.73          |
| 5               | 715.5055    | 1.03          | 25.89             | 46.00             | 20.11          |
| 6               | 840.7608    | 2.19          | 26.61             | 46.00             | 19.39          |

## 8.6 CONDUCTED EMISSIONS TEST

### 8.6.1 Applicable Standard

According to FCC Part 15.207(a).

### 8.6.2 Conformance Limit

| Frequency(MHz) | Conducted Emission Limit |         |
|----------------|--------------------------|---------|
|                | Quasi-peak               | Average |
| 0.15-0.5       | 66-56                    | 56-46   |
| 0.5-5.0        | 56                       | 46      |
| 5.0-30.0       | 60                       | 50      |

Note: 1. The lower limit shall apply at the transition frequencies  
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 8.6.3 Test Configuration

Test according to clause 7.3 conducted emission test setup

### 8.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.  
Maximum procedure was performed on the highest emissions to ensure EUT compliance.  
Repeat above procedures until all frequency measured were complete.

### 8.6.5 Test Results

N/A

Not applicable, since EUT is DC power.

## 8.7 ANTENNA APPLICATION

### 8.7.1 Antenna Requirement

| Standard            | Requirement                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FCC CRF Part 15.203 | An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded. |

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 8.7.2 Result

#### PASS

|               |       |                |             |
|---------------|-------|----------------|-------------|
| Temperature : | 23.5℃ | ATM Pressure:  | 1011 mbar   |
| Humidity :    | 52 %  | Test Engineer: | Yi Xingpeng |

- ☐ Antenna use a permanently attached antenna which is not replaceable.
- ☒ Not using a standard antenna jack or electrical connector for antenna replacement
- ☐ The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.

Detail of factor for radiated emission:

| Frequency(MHz) | Ant_F(dB) | Cab_L(dB) | Preamp(dB) | Correct Factor(dB) |
|----------------|-----------|-----------|------------|--------------------|
| 0.009          | 20.6      | 0.03      | \          | 20.63              |
| 0.15           | 20.7      | 0.1       | \          | 20.8               |
| 1              | 20.9      | 0.15      | \          | 21.05              |
| 10             | 20.1      | 0.28      | \          | 20.38              |
| 30             | 18.8      | 0.45      | \          | 19.25              |
|                |           |           |            |                    |
| 30             | 11.7      | 0.62      | 27.9       | -15.58             |
| 100            | 12.5      | 1.02      | 27.8       | -14.28             |
| 300            | 12.9      | 1.91      | 27.5       | -12.69             |
| 600            | 19.2      | 2.92      | 27         | -4.88              |
| 800            | 21.1      | 3.54      | 26.6       | -1.96              |
| 1000           | 22.3      | 4.17      | 26.2       | 0.27               |
|                |           |           |            |                    |
| 1000           | 25.6      | 1.76      | 41.4       | -14.04             |
| 3000           | 28.9      | 3.27      | 43.2       | -11.03             |
| 5000           | 31.1      | 4.2       | 44.6       | -9.3               |
| 8000           | 36.2      | 5.95      | 44.7       | -2.55              |
| 10000          | 38.4      | 6.3       | 43.9       | 0.8                |
| 12000          | 38.5      | 7.14      | 42.3       | 3.34               |
| 15000          | 40.2      | 8.15      | 41.4       | 6.95               |
| 18000          | 45.4      | 9.02      | 41.3       | 13.12              |
|                |           |           |            |                    |
| 18000          | 37.9      | 1.81      | 47.9       | -8.19              |
| 21000          | 37.9      | 1.95      | 48.7       | -8.85              |
| 25000          | 39.3      | 2.01      | 42.8       | -1.49              |
| 28000          | 39.6      | 2.16      | 46.0       | -4.24              |
| 31000          | 41.2      | 2.24      | 44.5       | -1.06              |
| 34000          | 41.5      | 2.29      | 46.6       | -2.81              |
| 37000          | 43.8      | 2.30      | 46.4       | -0.3               |
| 40000          | 43.2      | 2.50      | 42.2       | 3.5                |

--- End of Report ---

## 声 明 Statement

1. 本报告无授权批准人签字及“检验检测专用章”无效。

1. This report is invalid without the signature of the authorized approver and "special seal for testing".

2. 未经许可本报告不得部分复制。

2. This report shall not be copied partly without authorization.

3. 本报告的检测结果仅对送测样品有效，委托方对样品的代表性和资料的真实性负责。

3. The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.

4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内，仅作为客户委托、科研、教学或内部质量控制等目的使用。

4. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.

5. 本检测报告以实测值进行符合性判定，未考虑不确定度所带来的风险，本实验室不承担相关责任，特别约定、标准或规范中有明确规定的除外。

5. The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.

6. 对本检验报告若有异议，请于收到报告之日起 20 日内提出。

6. Objections shall be raised within 20 days from the date receiving the report.