

TEST REPORT

Product Name : Wireless Module
Model Number : WXT04R2111
FCC ID : 2AZTZ-WXT04R

Prepared for : Kontech Electronics Co., Ltd.
Address : 10F, Bldg 1, Longhua Digital Intelligence Mfg Center, 238
Longsheng Rd, Longhua

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Bldg 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China

Tel: (0755) 26954280
Fax: (0755) 26954282

Report Number : ENS2602030067W00104R
Date(s) of Tests : February 4, 2026 to March 26, 2026
Date of Issue : March 26, 2026

TABLE OF CONTENTS

1 TEST RESULT CERTIFICATION	4
2 EUT TECHNICAL DESCRIPTION.....	5
2.1 FEATURE OF EUT	6
3 SUMMARY OF TEST RESULT.....	7
4 TEST METHODOLOGY.....	8
4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	8
4.2 MEASUREMENT EQUIPMENT USED.....	8
4.3 DESCRIPTION OF TEST MODES	9
5 FACILITIES AND ACCREDITATIONS.....	13
5.1 EQUIPMENT	13
5.2 DESCRIPTION OF TEST FACILITY	13
6 TEST SYSTEM UNCERTAINTY.....	14
7 SETUP OF EQUIPMENT UNDER TEST	15
7.1 RADIO FREQUENCY TEST SETUP	15
7.2 RADIO FREQUENCY TEST SETUP	15
7.3 CONDUCTED EMISSION TEST SETUP	17
7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM	18
7.5 SUPPORT EQUIPMENT	18
8 TEST REQUIREMENTS	19
8.1 BANDWIDTH MEASUREMENT	19
8.2 MAXIMUM CONDUCTED OUTPUT POWER	97
8.3 MAXIMUM PEAK POWER DENSITY	159
8.4 UNDESIRABLE RADIATED SPURIOUS EMISSION	223
8.5 POWER LINE CONDUCTED EMISSIONS.....	260
8.6 ANTENNA APPLICATION.....	261

Modified Information

Version	Report No.	Revision Date	Summary
Ver.1.0	ENS2602030067W00104R	/	Original Report




1 TEST RESULT CERTIFICATION

Applicant : Kontech Electronics Co., Ltd.
Address : 10F, Bldg 1, Longhua Digital Intelligence Mfg Center, 238 Longsheng Rd, Longhua
Manufacturer : Kontech Electronics Co., Ltd.
Address : 10F, Bldg 1, Longhua Digital Intelligence Mfg Center, 238 Longsheng Rd, Longhua
EUT : Wireless Module
Model Name : WXT04R2111
Trademark : N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15, Subpart E	PASS

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2020/Cor 1-2021 and the energy emitted by the sample EUT tested as described in this report is in compliance with the above table standards requirement. The test results of this report relate only to the tested sample identified in this report.

Date of Test : February 4, 2026 to March 26, 2026
Prepared by : 
Yu Xiaolan/Editor
Reviewer : 
Xia Lili/Supervisor
Approved & Authorized Signer : 
Wang Li/Manager



2 EUT TECHNICAL DESCRIPTION

Product Name:	Wireless Module
Model Number:	WXT04R2111
WIFI Type:	UNII-1: 5150MHz-5250MHz Band UNII-2A: 5250MHz-5350MHz Band UNII-2C: 5470MHz-5725MHz Band UNII-3: 5725MHz-5850MHz Band
WLAN Supported:	IEEE 802.11a IEEE 802.11n(20MHz channel bandwidth) IEEE 802.11n(40MHz channel bandwidth) IEEE 802.11ac(20MHz channel bandwidth) IEEE 802.11ac(40MHz channel bandwidth) IEEE 802.11ac(80MHz channel bandwidth) IEEE 802.11ax(20MHz channel bandwidth) IEEE 802.11ax(40MHz channel bandwidth) IEEE 802.11ax(80MHz channel bandwidth)
Frequency Range:	5150MHz-5250MHz Band: 5180-5240MHz for 802.11a 5180-5240MHz for 802.11n(20) 5190-5230MHz for 802.11n(40) 5180-5240MHz for 802.11ac(20) 5190-5230MHz for 802.11ac(40) 5210MHz for 802.11ac(80) 5180-5240MHz for 802.11ax(20) 5190-5230MHz for 802.11ax(40) 5210MHz for 802.11ax(80)
	5250MHz-5350MHz Band: 5260-5320MHz for 802.11a 5260-5320MHz for 802.11n(20) 5270-5310MHz for 802.11n(40) 5260-5320MHz for 802.11ac(20) 5270-5310MHz for 802.11ac(40) 5290MHz for 802.11ac(80) 5260-5320MHz for 802.11ax(20) 5270-5310MHz for 802.11ax(40) 5290MHz for 802.11ax(80)
	5470MHz-5725MHz Band: 5500-5700MHz for 802.11a 5500-5700MHz for 802.11n(20) 5510-5670MHz for 802.11n(40) 5500-5700MHz for 802.11ac(20) 5510-5670MHz for 802.11ac(40) 5530-5610MHz for 802.11ac(80) 5500-5700MHz for 802.11ax(20) 5510-5670MHz for 802.11ax(40) 5530-5610MHz for 802.11ax(80)

	5725MHz-5850MHz Band: 5745-5825MHz for 802.11a 5745-5825MHz for 802.11n(20) 5755-5795MHz for 802.11n(40) 5745-5825MHz for 802.11ac(20) 5755-5795MHz for 802.11ac(40) 5775MHz for 802.11ac(80) 5745-5825MHz for 802.11ax(20) 5755-5795MHz for 802.11ax(40) 5775MHz for 802.11ax(80)
Modulation:	OFDM, OFDMA
TPC Function:	Not Support
Beamforming:	Not Support
DFS Function:	Slave
Smart System:	MIMO
Power Supply:	DC 5V
Temperature Range:	0°C~70°C

2.1 FEATURE OF EUT

a) Antenna information

Specification	Antenna	Brand	Model	Antenna Type	Gain
BT	1	/	/	PCB Antenna	2.43 dBi
BLE	1	/	/	PCB Antenna	2.43 dBi
2.4G WIFI	1	/	/	PCB Antenna	2.51 dBi
2.4G WIFI	2	/	/	PCB Antenna	2.51 dBi
5G WIFI	1	/	/	PCB Antenna	3.72 dBi
5G WIFI	2	/	/	PCB Antenna	3.72 dBi

Note: The antenna information provided by the manufacturer will have a certain impact on the test results.

b) Modification Record

There were no modifications required for compliance.

c) For more details, please refer to the user's manual of the EUT.

3 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark
15.407 (a) 15.407 (e)	99% , 6dB and 26dB Bandwidth	PASS	
15.407 (a)	Maximum Conducted Output Power	PASS	
15.407 (a)	Peak Power Spectral Density	PASS	
15.407 (b)	Radiated Spurious Emission	PASS	
15.407 (b)(6) 15.207	Power Line Conducted Emission	N/A	
15.407(a) 15.203	Antenna Application	PASS	
NOTE 1: N/A is an abbreviation for not applicable. NOTE 2: The results of this report do not take into account the uncertainty. NOTE 3: According to FCC OET KDB 789033 D2 General UNII Test Procedures New Rules v02r01, In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.			

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is filing to comply with the above table standards requirement.

4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:
FCC 47 CFR Part 15, Subpart E
FCC KDB 789033 D2 General UNII Test Procedures New Rules v02r01

4.2 MEASUREMENT EQUIPMENT USED

For Spurious Emissions Test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Pre-Amplifier	Bonn	BLMA 011001N	2213967A	2025/10/16	1Year
EMI Test Receiver	Rohde & Schwarz	ESR7	102551	2025/10/16	1Year
Bilog Antenna	Schwarzbeck	VULB9163	9163142	2024/7/8	2Year
Horn antenna	Schwarzbeck	BBHA9120D	9120D-1198	2025/5/13	2Year
Pre-Amplifier	Bonn	BLMA 0118-5G	2213967B-01	2025/10/16	1Year
Spectrum Analyzer	Rohde & Schwarz	FSV3044	101290	2025/10/16	1Year
Horn antenna	Schwarzbeck	BBHA9170	9170-399	2025/5/13	2Year
Pre-Amplifier	Lunar EM	LNA18G26-40	J1012131010001	2025/5/9	1Year
Pre-Amplifier	Lunar EM	LNA26G40-40	J1013131028001	2025/5/9	1Year
Loop Antenna	Schwarzbeck	FMZB1519	1519-012	2025/5/13	2Year
Wideband Radio Communication Tester	R&S	CMW500	171168	2025/9/9	1Year
Coaxial Cable	TIMES	NmNm-7-C15702	N/A	2025/5/22	1Year
Coaxial Cable	TIMES	HF290-NMSM-6.5M	N/A	2025/5/22	1Year
Coaxial Cable	TIMES	LMR-240 N-N	N/A	2025/5/22	1Year

For Other Test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Wideband Radio Communication Tester	R&S	CMW500	171168	2025/9/9	1Year
Frequency Extender	R&S	CMW-Z800A	100430	2025/9/9	1Year
Spectrum Analyzer	R&S	FSV3044	101289	2025/12/16	1Year
Analog Signal Generator	R&S	SMB100A	183237	2025/9/9	1Year
Vector Signal Generator	R&S	SMM100A	101808	2025/9/9	1Year
RF Control Unit(Power Meter)	Tonscend	JS0806-2	22C8060567	2025/9/9	1Year
Temperature&Humidity Chamber	ESPEC	EL-02KA	12107166	2025/5/10	1 Year
DC Power Supply	KEYSIGHT	E3642A	MY53030016	2025/9/9	1 Year

4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Wifi 5G with 5150-5250MHz

Frequency and Channels list for 802.11a/n(20)/ac(20)/ax(20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220	-	-
40	5200	48	5240	-	-

Frequency and Channels list for 802.11n (40)/ac(40)/ax(40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	-	-	-	-
46	5230	-	-	-	-

Frequency and Channel list for 802.11ac(80)/ax(80):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	-	-	-	-

Test Frequency and Channels for 802.11a/n(20)/ac(20)/ax(20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	40	5200	48	5240

Test Frequency and channels for 802.11n (40)/ac(40)/ax(40):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	-	-	46	5230

Test Frequency and channels for 802.11ac(80)/ax(80):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	-	-	-	-

WIFI 5G with 5250-5350MHz

Frequency and Channels list for 802.11a/n(20)/ac(20)/ax(20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	60	5300	-	-
56	5280	64	5320	-	-

Frequency and Channels list for 802.11n (40)/ac(40)/ax(40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
54	5270	-	-	-	-
62	5310	-	-	-	-

Frequency and Channels list for 802.11ac(80)/ax(80):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
58	5290	-	-	-	-

Test Frequency and Channels for 802.11a/n(20)/ac(20)/ax(20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	56	5280	64	5320

Test Frequency and channels for 802.11n (40)/ac(40)/ax(40):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
54	5270	-	-	62	5310

Test Frequency and channels for 802.11ac(80)/ax(80):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
58	5290	-	-	-	-

WIFI 5G with 5470-5725MHz

Frequency and Channels list for 802.11a/n(20)/ac(20)/ax(20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	116	5580	132	5660
104	5520	120	5600	136	5680
108	5540	124	5620	140	5700
112	5560	128	5640	-	-

Frequency and Channels list for 802.11n(40)/ac(40)/ax(40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
102	5510	118	5590	134	5670
110	5550	126	5630	-	-

Frequency and Channels list for 802.11ac(80)/ax(80):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
106	5530	122	5610	-	-

Test Frequency and Channels for 802.11a/n(20)/ac(20)/ax(20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	116	5580	140	5700

Test Frequency and channels for 802.11n (40)/ac(40)/ax(40):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
102	5510	-	-	134	5670

Test Frequency and channels for 802.11ac(80)/ax(80):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
106	5530	122	5610	-	-

Wifi 5G with 5725MHz-5850MHz

Frequency and Channels list for 802.11a/n(20)/802.11ac(20)/ax(20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	157	5785	165	5825
153	5765	161	5805	-	-

Frequency and Channels list for 802.11n(40)/ac(40)/ax(40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	-	-	-	-
159	5795	-	-	-	-

Frequency and Channels list for 802.11ac(80)/ax(80):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
155	5775	-	-	-	-

Test Frequency and Channels for 802.11a/n(20)/ac(20)/ax(20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	157	5785	165	5825

Test Frequency and channels for 802.11n(40)/ac(40)/ax(40):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	-	-	159	5795

Test Frequency and channels for 802.11ac(80)/ax(80):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
155	5775	-	-	-	-

Multi-antenna correlation:

☒	Transmit Signals are Correlated
	Directional gain = $10 \log[(10^{G^1/20} + 10^{G^2/20} + \dots + 10^{G^N/20})^2 / N_{ANT}]$ dBi
☐	All Transmit Signals are Completely Uncorrelated
	Directional gain = $10 \log[(10^{G^1/10} + 10^{G^2/10} + \dots + 10^{G^N/10}) / N_{ANT}]$ dBi

Ant1: 3.72dBi, Ant2: 3.72dBi, Directional gain = 6.73dBi

5 FACILITIES AND ACCREDITATIONS

5.1 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged wave guide, horn. Spectrum analyzers with preselectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wide band preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods".

5.2 DESCRIPTION OF TEST FACILITY

Site Description

EMC Lab.

: **Accredited by CNAS**

The Certificate Registration Number is L2291

The Laboratory has been assessed and proved to be in compliance with CNAS-CL01 (identical to ISO/IEC 17025:2017)

Accredited by FCC

Designation Number: CN1204

Test Firm Registration Number: 882943

Accredited by A2LA

The Certificate Number is 4321.01

Accredited by Industry Canada

The Conformity Assessment Body Identifier is CN0008

Name of Firm

: EMTEK (SHENZHEN) CO., LTD.

Site Location

: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China

6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\text{dB}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Power Density	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
Band Edge Test	$\pm 3\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 0.5^\circ\text{C}$
Humidity	$\pm 3\%$

Measurement Uncertainty for a level of Confidence of 95%.

7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP

The WLAN component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2020/Cor 1-2021. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2020/Cor 1-2021 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.

Above 30MHz:


The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Above 1GHz:


(Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.)

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




7.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.


Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2020/Cor 1-2021

Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



7.5 SUPPORT EQUIPMENT

N/A

Notes:

- 1.All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2.Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

8 TEST REQUIREMENTS

8.1 BANDWIDTH MEASUREMENT

8.1.1 Applicable Standard

According to FCC Part 15.407(a)(1) for UNII Band I
According to FCC Part 15.407(a)(2) for UNII Band II-A and UNII Band II-C
According to FCC Part 15.407(a)(3) for UNII Band III
According to FCC Part 15.407(e) for UNII Band III
According to 789033 D02 Section II(C)
According to 789033 D02 Section II(D)

8.1.2 Conformance Limit

(1) For the band 5.15-5.25 GHz.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(e) Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

8.1.3 Test Configuration

Test according to clause 6.1 radio frequency test setup.

8.1.4 Test Procedure

According to 789033 D02 v02r01 section C&D, the following is the measurement procedure.

1. Emission Bandwidth (EBW)

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = Peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the maximum of the emission.

Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85 GHz

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

D. 99 Percent Occupied Bandwidth

The 99-percent occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5 % of the total mean power of the given emission. Measurement of the 99-percent occupied bandwidth is required only as a condition for using the optional band-edge measurement techniques described in section II.G.3.d). Measurements of 99-percent occupied bandwidth may also optionally be used in lieu of the EBW to 789033 D02 v01r02 General UNII Test Procedures New Rules v01 define the minimum frequency range over which the spectrum is integrated when measuring maximum conducted output power as described in section II.E. However, the EBW must be measured to determine bandwidth dependent limits on maximum conducted output power in accordance with 15.407(a).

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW.
4. Set VBW $\geq 3 \times \text{RBW}$.
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

8.1.5 Test Results

Temperature : 21.1℃
Humidity : 55 %

ATM Pressure:: 1011 mbar
Test Engineer: Yi Xingpeng

Emission Bandwidth (26dB)

TestMode	Antenna	Frequency [MHz]	26db EBW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	18.240	5170.960	5189.200	---	---
11A	Ant2	5180	18.320	5170.960	5189.280	---	---
11A	Ant1	5200	18.600	5190.720	5209.320	---	---
11A	Ant2	5200	18.560	5190.800	5209.360	---	---
11A	Ant1	5240	18.600	5230.720	5249.320	---	---
11A	Ant2	5240	18.200	5230.920	5249.120	---	---
11A	Ant1	5260	18.440	5250.760	5269.200	---	---
11A	Ant2	5260	18.680	5250.640	5269.320	---	---
11A	Ant1	5280	18.400	5270.920	5289.320	---	---
11A	Ant2	5280	18.600	5270.720	5289.320	---	---
11A	Ant1	5320	18.320	5310.880	5329.200	---	---
11A	Ant2	5320	18.400	5310.800	5329.200	---	---
11A	Ant1	5500	18.520	5490.760	5509.280	---	---
11A	Ant2	5500	18.600	5490.720	5509.320	---	---
11A	Ant1	5580	18.480	5570.840	5589.320	---	---
11A	Ant2	5580	18.440	5570.840	5589.280	---	---
11A	Ant1	5700	18.480	5690.880	5709.360	---	---
11A	Ant2	5700	18.360	5690.880	5709.240	---	---
11A	Ant1	5745	18.240	5736.040	5754.280	---	---
11A	Ant2	5745	18.480	5735.720	5754.200	---	---
11A	Ant1	5785	18.320	5775.920	5794.240	---	---
11A	Ant2	5785	18.360	5775.920	5794.280	---	---
11A	Ant1	5825	18.480	5815.840	5834.320	---	---
11A	Ant2	5825	18.560	5815.680	5834.240	---	---
11N20MIMO	Ant1	5180	19.360	5170.280	5189.640	---	---
11N20MIMO	Ant2	5180	19.520	5170.320	5189.840	---	---
11N20MIMO	Ant1	5200	19.440	5190.240	5209.680	---	---
11N20MIMO	Ant2	5200	19.600	5190.240	5209.840	---	---
11N20MIMO	Ant1	5240	19.520	5230.280	5249.800	---	---
11N20MIMO	Ant2	5240	19.360	5230.360	5249.720	---	---
11N20MIMO	Ant1	5260	19.480	5250.320	5269.800	---	---
11N20MIMO	Ant2	5260	19.440	5250.320	5269.760	---	---
11N20MIMO	Ant1	5280	19.560	5270.280	5289.840	---	---
11N20MIMO	Ant2	5280	19.320	5270.280	5289.600	---	---
11N20MIMO	Ant1	5320	19.480	5310.280	5329.760	---	---
11N20MIMO	Ant2	5320	19.400	5310.320	5329.720	---	---
11N20MIMO	Ant1	5500	19.400	5490.280	5509.680	---	---
11N20MIMO	Ant2	5500	19.400	5490.360	5509.760	---	---
11N20MIMO	Ant1	5580	19.360	5570.400	5589.760	---	---
11N20MIMO	Ant2	5580	19.240	5570.440	5589.680	---	---
11N20MIMO	Ant1	5700	19.560	5690.280	5709.840	---	---
11N20MIMO	Ant2	5700	19.280	5690.320	5709.600	---	---
11N20MIMO	Ant1	5745	19.560	5735.320	5754.880	---	---
11N20MIMO	Ant2	5745	19.320	5735.400	5754.720	---	---
11N20MIMO	Ant1	5785	19.320	5775.360	5794.680	---	---


11N20MIMO	Ant2	5785	19.400	5775.320	5794.720	---	---
11N20MIMO	Ant1	5825	19.560	5815.200	5834.760	---	---
11N20MIMO	Ant2	5825	19.320	5815.440	5834.760	---	---
11N40MIMO	Ant1	5190	39.040	5170.480	5209.520	---	---
11N40MIMO	Ant2	5190	38.880	5170.640	5209.520	---	---
11N40MIMO	Ant1	5230	39.440	5210.160	5249.600	---	---
11N40MIMO	Ant2	5230	39.040	5210.560	5249.600	---	---
11N40MIMO	Ant1	5270	39.360	5250.240	5289.600	---	---
11N40MIMO	Ant2	5270	39.200	5250.480	5289.680	---	---
11N40MIMO	Ant1	5310	39.120	5290.560	5329.680	---	---
11N40MIMO	Ant2	5310	39.360	5290.400	5329.760	---	---
11N40MIMO	Ant1	5510	39.120	5490.480	5529.600	---	---
11N40MIMO	Ant2	5510	39.200	5490.400	5529.600	---	---
11N40MIMO	Ant1	5550	39.120	5530.560	5569.680	---	---
11N40MIMO	Ant2	5550	39.040	5530.640	5569.680	---	---
11N40MIMO	Ant1	5670	39.360	5650.480	5689.840	---	---
11N40MIMO	Ant2	5670	38.960	5650.560	5689.520	---	---
11N40MIMO	Ant1	5755	39.520	5735.240	5774.760	---	---
11N40MIMO	Ant2	5755	39.040	5735.480	5774.520	---	---
11N40MIMO	Ant1	5795	38.960	5775.560	5814.520	---	---
11N40MIMO	Ant2	5795	39.040	5775.400	5814.440	---	---
11AC20MIMO	Ant1	5180	19.480	5170.120	5189.600	---	---
11AC20MIMO	Ant2	5180	19.440	5170.320	5189.760	---	---
11AC20MIMO	Ant1	5200	19.400	5190.280	5209.680	---	---
11AC20MIMO	Ant2	5200	19.480	5190.320	5209.800	---	---
11AC20MIMO	Ant1	5240	19.320	5230.400	5249.720	---	---
11AC20MIMO	Ant2	5240	19.440	5230.240	5249.680	---	---
11AC20MIMO	Ant1	5260	19.400	5250.320	5269.720	---	---
11AC20MIMO	Ant2	5260	19.240	5250.360	5269.600	---	---
11AC20MIMO	Ant1	5280	19.400	5270.400	5289.800	---	---
11AC20MIMO	Ant2	5280	19.360	5270.320	5289.680	---	---
11AC20MIMO	Ant1	5320	19.680	5310.240	5329.920	---	---
11AC20MIMO	Ant2	5320	19.440	5310.200	5329.640	---	---
11AC20MIMO	Ant1	5500	19.560	5490.240	5509.800	---	---
11AC20MIMO	Ant2	5500	19.600	5490.320	5509.920	---	---
11AC20MIMO	Ant1	5580	19.400	5570.400	5589.800	---	---
11AC20MIMO	Ant2	5580	19.560	5570.280	5589.840	---	---
11AC20MIMO	Ant1	5700	19.640	5690.200	5709.840	---	---
11AC20MIMO	Ant2	5700	19.440	5690.360	5709.800	---	---
11AC20MIMO	Ant1	5745	19.520	5735.240	5754.760	---	---
11AC20MIMO	Ant2	5745	19.400	5735.360	5754.760	---	---
11AC20MIMO	Ant1	5785	19.360	5775.360	5794.720	---	---
11AC20MIMO	Ant2	5785	19.440	5775.320	5794.760	---	---
11AC20MIMO	Ant1	5825	19.400	5815.320	5834.720	---	---
11AC20MIMO	Ant2	5825	19.440	5815.360	5834.800	---	---
11AC40MIMO	Ant1	5190	39.120	5170.560	5209.680	---	---
11AC40MIMO	Ant2	5190	39.360	5170.400	5209.760	---	---
11AC40MIMO	Ant1	5230	39.120	5210.400	5249.520	---	---
11AC40MIMO	Ant2	5230	39.040	5210.560	5249.600	---	---
11AC40MIMO	Ant1	5270	39.440	5250.480	5289.920	---	---
11AC40MIMO	Ant2	5270	38.880	5250.640	5289.520	---	---
11AC40MIMO	Ant1	5310	39.200	5290.640	5329.840	---	---
11AC40MIMO	Ant2	5310	38.720	5290.640	5329.360	---	---
11AC40MIMO	Ant1	5510	38.880	5490.640	5529.520	---	---
11AC40MIMO	Ant2	5510	38.960	5490.720	5529.680	---	---


11AC40MIMO	Ant1	5550	39.200	5530.480	5569.680	---	---
11AC40MIMO	Ant2	5550	39.040	5530.640	5569.680	---	---
11AC40MIMO	Ant1	5670	39.360	5650.560	5689.920	---	---
11AC40MIMO	Ant2	5670	39.360	5650.320	5689.680	---	---
11AC40MIMO	Ant1	5755	39.200	5735.400	5774.600	---	---
11AC40MIMO	Ant2	5755	38.960	5735.480	5774.440	---	---
11AC40MIMO	Ant1	5795	39.040	5775.400	5814.440	---	---
11AC40MIMO	Ant2	5795	39.280	5775.560	5814.840	---	---
11AC80MIMO	Ant1	5210	86.400	5167.120	5253.520	---	---
11AC80MIMO	Ant2	5210	86.400	5167.600	5254.000	---	---
11AC80MIMO	Ant1	5290	86.240	5247.280	5333.520	---	---
11AC80MIMO	Ant2	5290	87.200	5246.480	5333.680	---	---
11AC80MIMO	Ant1	5530	86.720	5487.760	5574.480	---	---
11AC80MIMO	Ant2	5530	87.360	5486.320	5573.680	---	---
11AC80MIMO	Ant1	5610	86.880	5565.840	5652.720	---	---
11AC80MIMO	Ant2	5610	86.880	5567.440	5654.320	---	---
11AC80MIMO	Ant1	5775	114.720	5704.760	5819.480	---	---
11AC80MIMO	Ant2	5775	85.920	5731.480	5817.400	---	---
11AX20MIMO	Ant1	5180	20.320	5169.880	5190.200	---	---
11AX20MIMO	Ant2	5180	20.080	5170.040	5190.120	---	---
11AX20MIMO	Ant1	5200	20.360	5189.840	5210.200	---	---
11AX20MIMO	Ant2	5200	20.320	5189.960	5210.280	---	---
11AX20MIMO	Ant1	5240	20.400	5229.800	5250.200	---	---
11AX20MIMO	Ant2	5240	20.120	5229.920	5250.040	---	---
11AX20MIMO	Ant1	5260	20.440	5249.800	5270.240	---	---
11AX20MIMO	Ant2	5260	20.320	5249.880	5270.200	---	---
11AX20MIMO	Ant1	5280	20.480	5269.800	5290.280	---	---
11AX20MIMO	Ant2	5280	20.440	5269.840	5290.280	---	---
11AX20MIMO	Ant1	5320	20.360	5309.920	5330.280	---	---
11AX20MIMO	Ant2	5320	20.440	5309.840	5330.280	---	---
11AX20MIMO	Ant1	5500	20.400	5490.000	5510.400	---	---
11AX20MIMO	Ant2	5500	20.520	5489.680	5510.200	---	---
11AX20MIMO	Ant1	5580	20.600	5569.720	5590.320	---	---
11AX20MIMO	Ant2	5580	20.240	5569.960	5590.200	---	---
11AX20MIMO	Ant1	5700	20.480	5689.680	5710.160	---	---
11AX20MIMO	Ant2	5700	20.240	5689.960	5710.200	---	---
11AX20MIMO	Ant1	5745	20.240	5734.880	5755.120	---	---
11AX20MIMO	Ant2	5745	20.360	5734.960	5755.320	---	---
11AX20MIMO	Ant1	5785	20.480	5774.880	5795.360	---	---
11AX20MIMO	Ant2	5785	20.400	5774.880	5795.280	---	---
11AX20MIMO	Ant1	5825	20.560	5814.760	5835.320	---	---
11AX20MIMO	Ant2	5825	20.440	5814.760	5835.200	---	---
11AX40MIMO	Ant1	5190	39.840	5170.160	5210.000	---	---
11AX40MIMO	Ant2	5190	39.920	5170.160	5210.080	---	---
11AX40MIMO	Ant1	5230	39.840	5210.160	5250.000	---	---
11AX40MIMO	Ant2	5230	39.600	5210.240	5249.840	---	---
11AX40MIMO	Ant1	5270	39.520	5250.400	5289.920	---	---
11AX40MIMO	Ant2	5270	39.840	5250.160	5290.000	---	---
11AX40MIMO	Ant1	5310	39.840	5290.080	5329.920	---	---
11AX40MIMO	Ant2	5310	39.760	5290.320	5330.080	---	---
11AX40MIMO	Ant1	5510	39.840	5490.080	5529.920	---	---
11AX40MIMO	Ant2	5510	39.840	5490.160	5530.000	---	---
11AX40MIMO	Ant1	5550	39.920	5530.160	5570.080	---	---
11AX40MIMO	Ant2	5550	40.160	5530.080	5570.240	---	---
11AX40MIMO	Ant1	5670	40.080	5650.160	5690.240	---	---

11AX40MIMO	Ant2	5670	40.080	5650.000	5690.080	---	---
11AX40MIMO	Ant1	5755	39.920	5735.080	5775.000	---	---
11AX40MIMO	Ant2	5755	39.920	5735.080	5775.000	---	---
11AX40MIMO	Ant1	5795	39.920	5775.000	5814.920	---	---
11AX40MIMO	Ant2	5795	40.080	5775.000	5815.080	---	---
11AX80MIMO	Ant1	5210	81.120	5170.000	5251.120	---	---
11AX80MIMO	Ant2	5210	81.280	5169.840	5251.120	---	---
11AX80MIMO	Ant1	5290	81.120	5249.040	5330.160	---	---
11AX80MIMO	Ant2	5290	81.120	5249.200	5330.320	---	---
11AX80MIMO	Ant1	5530	80.960	5490.160	5571.120	---	---
11AX80MIMO	Ant2	5530	84.960	5488.720	5573.680	---	---
11AX80MIMO	Ant1	5610	81.120	5569.680	5650.800	---	---
11AX80MIMO	Ant2	5610	83.040	5569.840	5652.880	---	---
11AX80MIMO	Ant1	5775	85.120	5733.560	5818.680	---	---
11AX80MIMO	Ant2	5775	81.120	5734.040	5815.160	---	---




Emission Bandwidth (26dB) Test Graphs







11A-Ant2-5200




11A-Ant1-5240




11A-Ant2-5240




11A-Ant1-5260




11A-Ant2-5260




11A-Ant1-5280




11A-Ant2-5280




11A-Ant1-5320




11A-Ant2-5320




11A-Ant1-5500




11A-Ant2-5500




11A-Ant1-5580




11A-Ant2-5580




11A-Ant1-5700




11A-Ant2-5700






11A-Ant2-5785



11A-Ant1-5825



11A-Ant2-5825

