



1. Limit for Portable Equipment Exposure

Frequency	1-g SAR
100MHz-6GHz	3.0

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g

SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

2. Estimation Result

Frequency (MHz)	PK Output Power(dBm)	Output Power(mW)	Test Separation Distance (mm)	Measurement Result	1-g SAR
433.92	-14.84	0.033	5	0.004	3.0

Note:

1. use the maximum E-field strength(80.36dBuV/m) for the RF exposure evaluation
2. $E(\text{dBuV/m}) = \text{EIRP}(\text{dBm}) - 95.2$ for distance 3m
so the $\text{EIRP} = 80.36\text{dBuV/m} - 95.2 = -14.84\text{dBm}$

-----The End-----