FCC PART 15.247

TEST REPORT

For

Mediafly (HongKong) Co.,Limited

09 and 27/F,Ho King Commercial Centre,2-16 Fa Yuen Street,Mong Kok

FCC ID:2AZY4-T2000

Report Type:	**Product Type:**
Original Report	Tablet PC

Report Number: SZ4210419-12287E-00B

Report Date: 2021-05-20

Reviewed By: Candy Li, RF Engineer

Prepared By: Shenzhen Accurate Technology Co., Ltd.
1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: (0755) 26503290
Fax: (0755) 26503396
Http://www.atc-lab.com

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION **4**
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
OBJECTIVE 4
TEST METHODOLOGY 4
MEASUREMENT UNCERTAINTY 5
SYSTEM TEST CONFIGURATION **6**
DESCRIPTION OF TEST CONFIGURATION 6
EQUIPMENT MODIFICATIONS 7
EUT EXERCISE SOFTWARE 7
DUTY CYCLE 7
SUPPORT EQUIPMENT LIST AND DETAILS 7
EXTERNAL I/O CABLE 7
BLOCK DIAGRAM OF TEST SETUP 8
SUMMARY OF TEST RESULTS **9**
TEST EQUIPMENT LIST **10**
FCC §1.1307(b) & §2.1093 - RF EXPOSURE INFORMATION **11**
APPLICABLE STANDARD 11
TEST RESULT: 11
FCC §15.203 - ANTENNA REQUIREMENT **12**
APPLICABLE STANDARD 12
ANTENNA CONNECTOR CONSTRUCTION 12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS **13**
APPLICABLE STANDARD 13
EUT SETUP 13
EMI TEST RECEIVER SETUP 13
TEST PROCEDURE 13
TRANSD FACTOR & MARGIN CALCULATION 14
TEST DATA 14
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS **17**
APPLICABLE STANDARD 17
EUT SETUP 17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP 18
TEST PROCEDURE 18
FACTOR & MARGIN CALCULATION 18
TEST DATA 18
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH **26**
APPLICABLE STANDARD 26
TEST PROCEDURE 26
TEST DATA 26
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER **27**
APPLICABLE STANDARD 27
TEST PROCEDURE 27
TEST DATA 27
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE **28**

APPLICABLE STANDARD 28
TEST PROCEDURE 28
TEST DATA 28

FCC §15.247(e) - POWER SPECTRAL DENSITY 29

APPLICABLE STANDARD 29
TEST PROCEDURE 29
TEST DATA 29

APPENDIX Wi-Fi.....30

APPENDIX A: 6DB EMISSION BANDWIDTH.....30
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH 37
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER 44
APPENDIX D: POWER SPECTRAL DENSITY 45
APPENDIX E: BAND EDGE MEASUREMENTS.....52
APPENDIX F: DUTY CYCLE 56

APPENDIX BLE.....63

APPENDIX A: 6DB EMISSION BANDWIDTH.....63
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH 67
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER 71
APPENDIX D: POWER SPECTRAL DENSITY 75
APPENDIX E: BAND EDGE MEASUREMENTS.....79
APPENDIX F: DUTY CYCLE 81

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Tablet PC
Trade	HAOVM
Tested Model	T2000
Frequency Range	BLE: 2402-2480MHz Wi-Fi: 2412-2462MHz
Maximum Conducted Peak Output Power	BLE: 3.22dBm Wi-Fi: 12.54dBm(802.11b), 12.41dBm(802.11g), 12.65dBm(802.11n20), 11.36dBm(802.11n40)
Modulation Technique	BLE: GFSK Wi-Fi: DSSS, OFDM
Antenna Specification*	FPC Antenna: 1.2dBi(provided by the applicant)
Voltage Range	DC3.7V by battery or DC 5V from adapter.
Date of Test	2021-04-21 to 2021-04-25
Sample serial number	SZ4210419-12287E-RF-S1(Assigned by ATC)
Received date	2021-04-19
Sample/EUT Status	Good condition
Adapter information	Model: YMK-12W050200 INPUT: 100-240V, 50/60Hz, 0.3A OUTPUT: 5V, 2000mA

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF output power, conducted		±0.73dB
Unwanted Emission, conducted		±1.6dB
RF Frequency		$\pm 0.082*10^{-7}$
Emissions, Radiated	30MHz - 1GHz	±4.28dB
	1GHz- 18GHz	±4.98dB
	18GHz- 26.5GHz	±5.06dB
Temperature		±1℃
Humidity		±6%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISEDC), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g, 802.11n-HT20 and 802.11n-HT40 mode, total 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

802.11b, 802.11g and 802.11n-HT20 mode was tested with Channel 1, 6 and 11.
802.11n-HT40 mode was tested with Channel 3, 6 and 9.

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

BLE & WIFI test in the engineer mode during testing and power level as below:

Item	Mode	Data Rate (Mbps)	Power Level*
Wi-Fi	802.11 b	1	12
	802.11 g	6	11
	802.11 n20	MCS0	11
	802.11 n40	MCS0	14
BLE	BLE-1M	Default	9
	BLE-2M	Default	9

Duty cycle

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
Unshielded Detachable USB Cable	0.8	Adapter	EUT

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307 , §2.1093	RF Exposure (SAR)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	Test Receiver	ESPI3	100396	2020/12/24	2021/12/23
R & S	L.I.S.N.	ENV216	101314	2020/12/25	2021/12/24
Anritsu Corp	50Ω Coaxial Switch	MP59B	6200506474	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-2m	No.2	2020/12/25	2021/12/24
Radiated Emissions Test					
Rohde&Schwarz	Test Receiver	ESR	101817	2020/12/24	2021/12/23
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2020/12/24	2021/12/23
A.H. Systems, inc.	Preamplifier	PAM-0118P	531	2020/07/08	2021/07/07
SONOMA INSTRUMENT	Amplifier	310 N	186131	2020/12/25	2021/12/24
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2020/11/28	2021/11/27
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2020/01/04	2023/01/03
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Unknown	RF Coaxial Cable	N-5m	No.3	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-5m	No.4	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-1m	No.5	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-1m	No.6	2020/12/25	2021/12/24
RF Conducted Test					
Rohde&Schwarz	Spectrum Analyzer	FSV40	101495	2020/12/24	2021/12/23
Rohde & Schwarz	Open Switch and Control Unit	OSP120 + OSP-B157	101244 + 100866	2020/12/24	2021/12/23

*** Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307(b) & §2.1093 - RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] · [√f(GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where
1. f(GHz) is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Test Result:

For worst case:

BLE:

Mode	Frequency (MHz)	Maximum Tune-up power		Calculated Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
		(dBm)	(mW)				
BLE	2480	3.5	2.24	5	0.7	3.0	Yes

Result: No Standalone SAR test is required for BLE mode.

Wi-Fi:

Compliance, please refer to the SAR report: SZ4210419-12287E-SA.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

a. Antenna must be permanently attached to the unit.
b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.
And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 1.2dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Transd Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Transd Factor = LISN VDF + Cable Loss

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – level
Level= reading level+ Transd Factor

Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Charley Lin on 2021-04-27.

EUT operation mode: Transmitting (Worst case as below)

Wi-Fi:

AC 120V/60 Hz, Line



MEASUREMENT RESULT: "12046-11_fin"

2021-4-27 11:00

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.345980	37.90	11.8	59	21.1	QP	L1	GND
0.572280	43.40	12.5	56	12.6	QP	L1	GND
1.143204	40.90	12.4	56	15.1	QP	L1	GND
3.463132	44.30	12.3	56	11.7	QP	L1	GND
11.968930	40.50	12.1	60	19.5	QP	L1	GND
13.016117	45.80	12.1	60	14.2	QP	L1	GND

MEASUREMENT RESULT: "12046-11_fin2"

2021-4-27 11:00

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.150000	36.20	10.3	56	19.8	AV	L1	GND
0.568861	32.90	12.5	46	13.1	AV	L1	GND
1.139785	28.00	12.4	46	18.0	AV	L1	GND
3.600652	29.50	12.3	46	16.5	AV	L1	GND
11.755734	27.10	12.1	50	22.9	AV	L1	GND
17.197615	33.80	12.1	50	16.2	AV	L1	GND

AC 120V/60 Hz, Neutral



MEASUREMENT RESULT: "12046-10_fin"

2021-4-27 10:58

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.161181	42.60	10.5	65	22.4	QP	N	GND
0.555391	45.80	12.5	56	10.2	QP	N	GND
1.707847	42.70	12.3	56	13.3	QP	N	GND
3.600652	42.80	12.3	56	13.2	QP	N	GND
11.826374	42.30	12.1	60	17.7	QP	N	GND
13.173015	46.30	12.1	60	13.7	QP	N	GND

MEASUREMENT RESULT: "12046-10_fin2"

2021-4-27 10:58

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.150000	36.20	10.3	56	19.8	AV	N	GND
0.563772	34.40	12.5	46	11.6	AV	N	GND
1.712970	30.50	12.3	46	15.5	AV	N	GND
3.557767	34.90	12.3	46	11.1	AV	N	GND
5.575931	29.50	12.2	50	20.5	AV	N	GND
13.055166	32.40	12.1	50	17.6	AV	N	GND

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz Note 1	/	Average
	1MHz	＞1/T Note 2	/	Average

Note 1: when duty cycle is no less than 98%
Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Factor = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Result-Limit
Result = Reading + Factor

Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Charley Lin on 2021-04-25.

EUT operation mode: Transmitting

***Note: 18~25GHz**: The test values lower than 20dBm of the limits, the test data were not recorded in the report.*

30MHz-1GHz: (Worst case)

BLE 1M, low Channel

Horizontal



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	59.0251	44.32	-20.38	23.94	40.00	-16.06	QP			
2	99.8777	45.12	-21.15	23.97	43.50	-19.53	QP			
3	192.4186	45.33	-19.19	26.14	43.50	-17.36	QP			
4	323.3204	46.15	-17.19	28.96	46.00	-17.04	QP			
5	435.5898	42.95	-13.12	29.83	46.00	-16.17	QP			
6	801.7863	37.55	-5.41	32.14	46.00	-13.86	QP			

Vertical



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	33.3279	44.15	-16.60	27.55	40.00	-12.45	QP			
2	40.5591	45.13	-18.42	26.71	40.00	-13.29	QP			
3	58.4074	44.81	-20.14	24.67	40.00	-15.33	QP			
4	173.8135	47.68	-20.44	27.24	43.50	-16.26	QP			
5	435.5898	36.84	-13.12	23.72	46.00	-22.28	QP			
6	824.5968	38.51	-4.91	33.60	46.00	-12.40	QP			

Wi-Fi: 802.11B mode, low Channel

Horizontal



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	34.8823	37.95	-16.92	21.03	40.00	-18.97	QP			
2	68.6310	43.85	-23.58	20.27	40.00	-19.73	QP			
3	98.4866	44.11	-21.36	22.75	43.50	-20.75	QP			
4	181.9199	46.15	-18.49	27.66	43.50	-15.84	QP			
5	312.1794	41.82	-16.63	25.19	46.00	-20.81	QP			
6	896.9965	33.48	-4.25	29.23	46.00	-16.77	QP			

Vertical



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	33.3279	44.13	-16.60	27.53	40.00	-12.47	QP			
2	40.8446	44.65	-18.42	26.23	40.00	-13.77	QP			
3	70.3365	48.11	-23.75	24.36	40.00	-15.64	QP			
4	175.0368	47.24	-20.11	27.13	43.50	-16.37	QP			
5	543.2742	39.78	-11.03	28.75	46.00	-17.25	QP			
6	935.5463	8.15	26.40	34.55	46.00	-11.45	QP			

1-18 GHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
BLE 1M Low Channel									
2310.00	49.32	PK	153	1.8	H	-6.84	42.48	74.00	31.52
2310.00	50.12	PK	329	1.6	V	-6.84	43.28	74.00	30.72
2390.00	49.18	PK	251	1.8	H	-6.44	42.74	74.00	31.26
2390.00	49.87	PK	52	1.5	V	-6.44	43.43	74.00	30.57
4804.00	43.38	PK	231	1.4	H	2.81	46.19	74.00	27.81
4804.00	41.92	PK	167	1.7	V	2.81	44.73	74.00	29.27
BLE 1M, Middle Channel									
4880.00	43.01	PK	311	1.6	H	3.04	46.05	74.00	27.95
4880.00	42.87	PK	218	1.8	V	3.04	45.91	74.00	28.09
BLE 1M, High Channel									
2483.50	49.12	PK	118	1.5	H	-5.96	43.16	74.00	30.84
2483.50	49.38	PK	142	1.6	V	-5.96	43.42	74.00	30.58
2500.00	51.06	PK	352	1.7	H	-5.88	45.18	74.00	28.82
2500.00	49.76	PK	71	1.4	V	-5.88	43.88	74.00	30.12
4960.00	41.92	PK	125	1.4	H	3.29	45.21	74.00	28.79
4960.00	41.28	PK	83	1.5	V	3.29	44.57	74.00	29.43
BLE 2M, Low Channel									
2310.00	49.12	PK	48	1.7	H	-6.84	42.28	74.00	31.72
2310.00	50.32	PK	254	1.5	V	-6.84	43.48	74.00	30.52
2390.00	48.95	PK	38	1.4	H	-6.44	42.51	74.00	31.49
2390.00	50.14	PK	48	1.0	V	-6.44	43.70	74.00	30.30
4804.00	43.51	PK	51	1.4	H	2.81	46.32	74.00	27.68
4804.00	42.11	PK	34	1.1	V	2.81	44.92	74.00	29.08
BLE 2M , Middle Channel									
4880.00	43.25	PK	25	1.3	H	3.04	46.29	74.00	27.71
4880.00	42.48	PK	211	1.7	V	3.04	45.52	74.00	28.48
BLE 2M , High Channel									
2483.50	49.55	PK	85	1.9	H	-5.96	43.59	74.00	30.41
2483.50	49.51	PK	135	1.2	V	-5.96	43.55	74.00	30.45
2500.00	51.26	PK	258	1.4	H	-5.88	45.38	74.00	28.62
2500.00	49.38	PK	41	1.1	V	-5.88	43.50	74.00	30.50
4960.00	41.58	PK	184	1.0	H	3.29	44.87	74.00	29.13
4960.00	41.21	PK	52	1.3	V	3.29	44.50	74.00	29.50

Wi-Fi:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave		Height (m)	Polar (H/V)				
802.11B, Low Channel									
2310.00	49.63	PK	251	1.6	H	-6.84	42.79	74.00	31.21
2310.00	51.69	PK	194	1.7	V	-6.84	44.85	74.00	29.15
2390.00	52.36	PK	319	1.5	H	-6.44	45.92	74.00	28.08
2390.00	52.06	PK	158	1.8	V	-6.44	45.62	74.00	28.38
4824.00	45.31	PK	35	1.5	H	2.87	48.18	74.00	25.82
4824.00	42.69	PK	74	1.6	V	2.87	45.56	74.00	28.44
802.11B, Middle Channel									
4874.00	44.95	PK	150	1.70	H	3.01	47.96	74.00	26.04
4874.00	45.31	PK	350	1.5	V	3.01	48.32	74.00	25.68
11B, High Channel									
2483.50	51.05	PK	30	1.6	H	-5.96	45.09	74.00	28.91
2483.50	51.11	PK	294	1.5	V	-5.96	45.15	74.00	28.85
2500.00	49.81	PK	51	1.6	H	-5.88	43.93	74.00	30.07
2500.00	49.82	PK	360	1.8	V	-5.88	43.94	74.00	30.06
4924.00	45.68	PK	154	1.4	H	3.17	48.85	74.00	25.15
4924.00	45.12	PK	36	1.9	V	3.17	48.29	74.00	25.71
802.11G, Low Channel									
2310.00	48.25	PK	235	1.3	H	-6.84	41.41	74.00	32.59
2310.00	50.92	PK	313	1.5	V	-6.84	44.08	74.00	29.92
2390.00	52.13	PK	236	1.6	H	-6.44	45.69	74.00	28.31
2390.00	52.35	PK	135	1.5	V	-6.44	45.91	74.00	28.09
4824.00	44.82	PK	61	1.3	H	2.87	47.69	74.00	26.31
4824.00	43.25	PK	59	1.8	V	2.87	46.12	74.00	27.88
802.11G, Middle Channel									
4,874.00	44.13	PK	233	2.0	H	3.01	47.14	74.00	26.86
4,874.00	44.39	PK	265	1.6	V	3.01	47.40	74.00	26.60
802.11G, High Channel									
2483.50	50.58	PK	295	1.5	H	-5.96	44.62	74.00	29.38
2483.50	52.01	PK	351	1.8	V	-5.96	46.05	74.00	27.95
2500.00	50.13	PK	136	1.4	H	-5.88	44.25	74.00	29.75
2500.00	48.92	PK	211	1.6	V	-5.88	43.04	74.00	30.96
4924.00	45.36	PK	120	1.5	H	3.17	48.53	74.00	25.47
4924.00	45.22	PK	360	1.8	V	3.17	48.39	74.00	25.61
802.11N20, Low Channel									
2310.00	51.92	PK	264	1.8	H	-6.84	45.08	74.00	28.92
2310.00	51.52	PK	135	2.2	V	-6.84	44.68	74.00	29.32
2390.00	52.15	PK	255	1.6	H	-6.44	45.71	74.00	28.29
2390.00	52.03	PK	360	2.1	V	-6.44	45.59	74.00	28.41
4824.00	42.95	PK	12	2.3	H	2.87	45.82	74.00	28.18
4824.00	41.82	PK	19	1.8	V	2.87	44.69	74.00	29.31
802.11N20, Middle Channel									
4874.00	42.09	PK	108	1.40	H	3.01	45.10	74.00	28.90
4874.00	41.84	PK	225	1.1	V	3.01	44.85	74.00	29.15
802.11N20, High Channel									
2483.50	51.31	PK	138	2.10	H	-5.96	45.35	74.00	28.65

2483.50	51.29	PK	146	1.50	V	-5.96	45.33	74.00	28.67
2500.00	51.72	PK	215	1.80	H	-5.88	45.84	74.00	28.16
2500.00	50.61	PK	184	1.60	V	-5.88	44.73	74.00	29.27
4924.00	41.99	PK	65	1.40	H	3.17	45.16	74.00	28.84
4924.00	41.26	PK	84	1.00	V	3.17	44.43	74.00	29.57
802.11N40, Low Channel									
2310.00	49.12	PK	264	1.0	H	-6.84	42.28	74.00	31.72
2310.00	51.60	PK	135	1.1	V	-6.84	44.76	74.00	29.24
2390.00	52.11	PK	255	1.6	H	-6.44	45.67	74.00	28.33
2390.00	51.92	PK	360	1.8	V	-6.44	45.48	74.00	28.52
4844.00	44.92	PK	12	1.6	H	2.92	47.84	74.00	26.16
4844.00	43.15	PK	0	1.5	V	2.92	46.07	74.00	27.93
802.11N40, Middle Channel									
4874.00	43.55	PK	112	1.6	H	3.01	46.56	74.00	27.44
4874.00	45.81	PK	135	1.8	V	3.01	48.82	74.00	25.18
802.11N40, High Channel									
2483.50	50.82	PK	158	1.3	H	-5.96	44.86	74.00	29.14
2483.50	51.36	PK	164	1.2	V	-5.96	45.40	74.00	28.60
2500.00	48.25	PK	255	1.6	H	-5.88	42.37	74.00	31.63
2500.00	47.51	PK	291	1.0	V	-5.88	41.63	74.00	32.37
4904.00	46.01	PK	144	1.1	H	3.11	49.12	74.00	24.88
4904.00	45.25	PK	36	1.5	V	3.11	48.36	74.00	25.64

Note:
Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude = Corrected Factor + Reading
Margin = Limit - Corrected. Amplitude
The other spurious emission which is 20dB to the limit was not recorded.
The test result of peak was less than the limit of average, so just peak values were recorded.

1-18 GHz:

Pre-scan for Peak
802.11 b Middle Channel
Horizontal



Vertical



18 -25GHz:

Pre-scan for Peak
802.11 b Middle Channel
Horizontal



Vertical



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Charley Lin on 2021-04-25.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Charley Lin on 2021-04-25.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Charley Lin on 2021-04-25.

EUT operation mode: Transmitting

Test Result: Compliant.

Conducted Band Edge Result:

Please refer to the Appendix Wi-Fi and Appendix BLE.

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: 3kHz≤ RBW≤100 kHz.
3. Set the VBW ≥ 3×RBW.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Charley Lin to 2021-04-25.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.

APPENDIX Wi-Fi

Appendix A: 6dB Emission Bandwidth

Test Result

TestMode	Antenna	Channel [MHz]	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	9.160	0.5	PASS
		2437	8.120	0.5	PASS
		2462	9.640	0.5	PASS
11G	Ant1	2412	15.800	0.5	PASS
		2437	15.800	0.5	PASS
		2462	16.480	0.5	PASS
11N20SISO	Ant1	2412	16.440	0.5	PASS
		2437	16.280	0.5	PASS
		2462	17.720	0.5	PASS
11N40SISO	Ant1	2422	36.000	0.5	PASS
		2437	35.200	0.5	PASS
		2452	35.280	0.5	PASS

Test Graphs

11B_Ant1_2412MHz



11B_Ant1_2437MHz



11B_Ant1_2462MHz



11B_Ant1_2412MHz



11B_Ant1_2437MHz



11B_Ant1_2462MHz



11N20SISO_Ant1_2412MHz



11N20SISO_Ant1_2437MHz



11N20SISO_Ant1_2462MHz



11N40SISO_Ant1_2422MHz



11N40SISO_Ant1_2437MHz



11N40SISO_Ant1_2452MHz



Appendix B: Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Channel[MHz]	OCB [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	12.068	---	PASS
		2437	11.828	---	PASS
		2462	12.428	---	PASS
11G	Ant1	2412	17.862	---	PASS
		2437	17.383	---	PASS
		2462	19.66	---	PASS
11N20SISO	Ant1	2412	18.302	---	PASS
		2437	17.982	---	PASS
		2462	19.381	---	PASS
11N40SISO	Ant1	2422	37.003	---	PASS
		2437	35.964	---	PASS
		2452	36.444	---	PASS

Test Graphs

11B_Ant1_2412MHz



11B_Ant1_2437MHz



11B_Ant1_2462MHz



11G_Ant1_2412MHz



11G_Ant1_2437MHz



11G_Ant1_2462MHz



11N20SISO_Ant1_2412MHz



11N20SISO_Ant1_2437MHz



11N20SISO_Ant1_2462MHz



11N40SISO _Ant1_2422MHz



11N40SISO _Ant1_2437MHz

11N40SISO _Ant1_2452MHz



Appendix C: Maximum conducted output power

Test Result

Test Mode	Antenna	Channel [MHz]	Peak Power Result [dBm]	Average Power Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	12.54	11.16	<=30	PASS
		2437	11.57	10.42	<=30	PASS
		2462	10.43	9.01	<=30	PASS
11G	Ant1	2412	12.41	11.38	<=30	PASS
		2437	9.82	8.43	<=30	PASS
		2462	10.4	9.01	<=30	PASS
11N20SISO	Ant1	2412	10.84	9.34	<=30	PASS
		2437	9.71	8.25	<=30	PASS
		2462	12.65	11.13	<=30	PASS
11N40SISO	Ant1	2412	11.36	10.12	<=30	PASS
		2437	10.5	9.25	<=30	PASS
		2462	11.03	10.16	<=30	PASS

Appendix D: Power spectral density

Test Result

TestMode	Antenna	Channel[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-13.96	<=8	PASS
		2437	-12.92	<=8	PASS
		2462	-15.48	<=8	PASS
11G	Ant1	2412	-17.79	<=8	PASS
		2437	-17.35	<=8	PASS
		2462	-17.96	<=8	PASS
11N20SISO	Ant1	2412	-16.88	<=8	PASS
		2437	-16.80	<=8	PASS
		2462	-20.64	<=8	PASS
11N40SISO	Ant1	2422	-17.95	<=8	PASS
		2437	-16.73	<=8	PASS
		2452	-17.84	<=8	PASS

Test Graphs

11B_Ant1_2412MHz



11B_Ant1_2437MHz



11B_Ant1_2462MHz



11G_Ant1_2412MHz



11G_Ant1_2437MHz



11G_Ant1_2462MHz



11N20SISO_Ant1_2412MHz



11N20SISO_Ant1_2437MHz



11N20SISO_Ant1_2462MHz



11N40SISO _Ant1_2422MHz



11N40SISO _Ant1_2437MHz



11N40SISO _Ant1_2452MHz



Appendix E: Band edge measurements

Test Graphs

11B_Ant1_Low_2412MHz



11B_Ant1_High_2462MHz



11G _Ant1_Low_2412MHz



11G_Ant1_High_2462MHz



11N20SISO_Ant1_Low_2412MHz

11N20SISO_Ant1_High_2462MHz



11N40SISO_Ant1_Low_2422MHz



11N40SISO_Ant1_High_2452MHz



Appendix F: Duty Cycle

Test Result

TestMode	Antenna	Channel [MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	Ant1	2412	0.70	0.86	81.40
		2437	0.70	0.88	79.55
		2462	0.70	0.86	81.40
11G	Ant1	2412	0.10	0.24	41.67
		2437	0.10	0.24	41.67
		2462	0.10	0.24	41.67
11N20SISO	Ant1	2412	0.10	0.25	40.00
		2437	0.10	0.24	41.67
		2462	0.10	0.24	41.67
11N40SISO	Ant1	2422	0.06	0.20	30.00
		2437	0.06	0.20	30.00
		2452	0.06	0.20	30.00

Test Graphs

11B_Ant1_2412MHz



11B_Ant1_2437MHz



11B_Ant1_2462MHz



11G _Ant1_2412MHz



11G _Ant1_2437MHz



11G_Ant1_2462MHz



11N20SISO_Ant1_2412MHz



11N20SISO_Ant1_2437MHz



11N20SISO_Ant1_2462MHz



11N40SISO_Ant1_2422MHz

Date: 25.APR.2021 11:32:36

11N40SISO_Ant1_2437MHz



Date: 25.APR.2021 11:36:11

11N40SISO_Ant1_2452MHz



APPENDIX BLE

Appendix A: 6dB Emission Bandwidth

Test Result

Test Mode	Antenna	Channel [MHz]	DTS BW [MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.648	0.5	PASS
		2440	0.644	0.5	PASS
		2480	0.644	0.5	PASS
BLE_2M	Ant1	2402	0.876	0.5	PASS
		2440	0.876	0.5	PASS
		2480	0.876	0.5	PASS

Test Graphs

BLE_1M_ Ant1_2402MHz



BLE_1M_Ant1_2440MHz



BLE_1M_Ant1_2480MHz



BLE_2M_Ant1_2402MHz



BLE_2M_Ant1_2440MHz



BLE_2M_Ant1_2480MHz



Appendix B: Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Channel [MHz]	OCB [MHz]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	1.003	---	PASS
		2440	1.007	---	PASS
		2480	1.011	---	PASS
BLE_2M	Ant1	2402	2.03	---	PASS
		2440	2.03	---	PASS
		2480	2.034	---	PASS

Test Graphs

BLE_1M_Ant1_2402MHz

BLE_1M_Ant1_2440MHz



BLE_1M_Ant1_2480MHz

BLE_2M_Ant1_2402MHz



BLE_2M_Ant1_2440MHz

BLE_2M_Ant1_2480MHz

Appendix C: Maximum conducted output power

Test Result

Test Mode	Antenna	Channel [MHz]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	3.22	<=30	PASS
		2440	2.93	<=30	PASS
		2480	2.72	<=30	PASS
BLE_2M	Ant1	2402	3.01	<=30	PASS
		2440	2.81	<=30	PASS
		2480	2.55	<=30	PASS

Test Graphs

BLE_1M_Ant1_2402MHz



BLE_1M_Ant1_2440MHz



BLE_1M_Ant1_2480MHz



BLE_2M_Ant1_2402MHz



BLE_2M_Ant1_2440MHz



BLE_2M_Ant1_2480MHz



Appendix D: Power spectral density

Test Result

Test Mode	Antenna	Channel[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-14.29	<=8	PASS
		2440	-14.67	<=8	PASS
		2480	-14.81	<=8	PASS
BLE_2M	Ant1	2402	-20.60	<=8	PASS
		2440	-20.15	<=8	PASS
		2480	-19.80	<=8	PASS

Test Graphs

BLE_1M_Ant1_2402MHz



BLE_1M_Ant1_2440MHz



Date: 26.APR.2021 11:54:04

BLE_1M_Ant1_2480MHz



Date: 26.APR.2021 11:55:01

BLE_2M_Ant1_2402MHz



BLE_2M_Ant1_2440MHz



BLE_2M_Ant1_2480MHz



Appendix E: Band edge measurements

Test Graphs

BLE_1M_Ant1_Low_2402MHz



BLE_1M_Ant1_High_2480MHz



BLE_2M_Ant1_Low_2402MHz



Date: 21.APR.2021 13:58:18

BLE_2M_Ant1_High_2480MHz



Date: 21.APR.2021 14:04:24

Appendix F: Duty Cycle

Test Result

Test Mode	Antenna	Channel [MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
BLE_1M	Ant1	2402	0.10	0.62	16.21
		2440	0.10	0.62	16.21
		2480	0.10	0.62	16.21
BLE_2M	Ant1	2402	0.06	0.64	9.38
		2440	0.06	0.64	9.38
		2480	0.06	0.64	9.38

Test Graphs

BLE_1M_Ant1_2402MHz



BLE_1M_Ant1_2440MHz



BLE_1M_Ant1_2480MHz



BLE_2M_Ant1_2402MHz



BLE_ 2M_Ant1_2440MHz



BLE_2M_Ant1_2480MHz



******* END OF REPORT *******