


18 MINIMUM 6DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.8.1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Charlie
Temperature	25°C
Humidity	60%

18.1 LIMITS

Limit:	≥ 500 kHz
--------	----------------

18.2 BLOCK DIAGRAM OF TEST SETUP



18.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details


19 APPENDIX

Appendix1


19.1 MAXIMUM CONDUCTED OUTPUT POWER

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-1.91	30	Pass
NVNT	BLE 1M	2442	Ant1	-2.938	30	Pass
NVNT	BLE 1M	2480	Ant1	-3.079	30	Pass
NVNT	BLE 2M	2402	Ant1	-1.871	30	Pass
NVNT	BLE 2M	2442	Ant1	-2.918	30	Pass
NVNT	BLE 2M	2480	Ant1	-3.084	30	Pass


Power NVNT BLE 1M 2402MHz Ant1




Power NVNT BLE 1M 2442MHz Ant1




Power NVNT BLE 1M 2480MHz Ant1




Power NVNT BLE 2M 2402MHz Ant1



Power NVNT BLE 2M 2442MHz Ant1




Power NVNT BLE 2M 2480MHz Ant1




19.2 -6DB BANDWIDTH

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.674	0.5	Pass
NVNT	BLE 1M	2442	Ant1	0.668	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.668	0.5	Pass
NVNT	BLE 2M	2402	Ant1	1.127	0.5	Pass
NVNT	BLE 2M	2442	Ant1	1.124	0.5	Pass
NVNT	BLE 2M	2480	Ant1	1.134	0.5	Pass


-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1




-6dB Bandwidth NVNT BLE 1M 2442MHz Ant1




-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1




-6dB Bandwidth NVNT BLE 2M 2402MHz Ant1



-6dB Bandwidth NVNT BLE 2M 2442MHz Ant1




-6dB Bandwidth NVNT BLE 2M 2480MHz Ant1




19.3 OCCUPIED CHANNEL BANDWIDTH

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE 1M	2402	Ant1	1.0238
NVNT	BLE 1M	2442	Ant1	1.0268
NVNT	BLE 1M	2480	Ant1	1.0304
NVNT	BLE 2M	2402	Ant1	2.0438
NVNT	BLE 2M	2442	Ant1	2.0488
NVNT	BLE 2M	2480	Ant1	2.0532


OBW NVNT BLE 1M 2402MHz Ant1




OBW NVNT BLE 1M 2442MHz Ant1




OBW NVNT BLE 1M 2480MHz Ant1




OBW NVNT BLE 2M 2402MHz Ant1



OBW NVNT BLE 2M 2442MHz Ant1




OBW NVNT BLE 2M 2480MHz Ant1




19.4 MAXIMUM POWER SPECTRAL DENSITY LEVEL

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-16.479	8	Pass
NVNT	BLE 1M	2442	Ant1	-17.754	8	Pass
NVNT	BLE 1M	2480	Ant1	-17.779	8	Pass
NVNT	BLE 2M	2402	Ant1	-19.989	8	Pass
NVNT	BLE 2M	2442	Ant1	-20.613	8	Pass
NVNT	BLE 2M	2480	Ant1	-20.853	8	Pass


PSD NVNT BLE 1M 2402MHz Ant1




PSD NVNT BLE 1M 2442MHz Ant1




PSD NVNT BLE 1M 2480MHz Ant1




PSD NVNT BLE 2M 2402MHz Ant1



PSD NVNT BLE 2M 2442MHz Ant1



PSD NVNT BLE 2M 2480MHz Ant1




19.5 BAND EDGE

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-46.99	-30	Pass
NVNT	BLE 1M	2480	Ant1	-38.79	-30	Pass
NVNT	BLE 2M	2402	Ant1	-47.3	-30	Pass
NVNT	BLE 2M	2480	Ant1	-38.29	-30	Pass


Band Edge NVNT BLE 1M 2402MHz Ant1 Ref




Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



Band Edge NVNT BLE 1M 2480MHz Ant1 Ref



Band Edge NVNT BLE 1M 2480MHz Ant1 Emission



Band Edge NVNT BLE 2M 2402MHz Ant1 Ref



Band Edge NVNT BLE 2M 2402MHz Ant1 Emission