

Dates of Tests: October 23, 2023
Test Report S/N: LR500112310H
Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID.

2BA2CAD-DX

APPLICANT

Good Doctors Co., Ltd.

Equipment Class	:	Digital Transmission System (DTS)
Manufacturing Description	:	Direct X
Manufacturer	:	Good Doctors Co., Ltd.
Model name	:	AD-DX
Contains	:	2AL6KBL-M8821CS1
Test Device Serial No.:	:	Identical prototype
Rule Part(s)	:	FCC Part 15.407 Subpart C ; ANSI C63.10 - 2013
Frequency Range	:	5180 MHz ~ 5240 MHz - 802.11a/n20/n40/ac20/ac40/ac80 5745 MHz ~ 5825 MHz - 802.11a/n20/n40/ac20/ac40/ac80
Max. Output Power	:	0.0158 W
Data of issue	:	October 23 ,2023

This test report is issued under the authority of:



Ja-Beom Koo, Manager

The test was supervised by:



Eun-Hwan Jung, Test Engineer

TABLE OF CONTENTS

1. GENERAL INFORMATION ----- 3

2. INFORMATION ABOUT TEST ITEM ----- 4

3. TEST REPORT ----- 5

 3.1 SUMMARY OF TESTS ----- 5

 3.2 RF EXPOSURE EVULATION----- 6

1. General information

1-1 Test Performed

Company name : LTA Co., Ltd.
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2024-09-28	ECT accredited Lab.
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2024-03-25	FCC CAB
VCCI	JAPAN	C-4948,	2025-09-10	VCCI registration
VCCI	JAPAN	T-2416,	2025-09-10	VCCI registration
VCCI	JAPAN	R-4483(10 m),	2025-08-15	VCCI registration
VCCI	JAPAN	G-847	2025-12-13	VCCI registration
IC	CANADA	5799A-1	2025-10-18	IC filing

2. Information about test item

2-1 Client & Manufacturer

Client Company name : Good Doctors Co., Ltd.
 #208, B-dong, 283 Bupyeong-daero, Bupyeong-gu
 Address : (Woolim Lions Valley ,Cheongchoen-dong) Incheon, 21315, Republic of
 Korea
 Tel / Fax : TEL No : +82-32-424-6325 / FAX No : +82-32-424-6326

2-2 Equipment Under Test (EUT)

Model name : AD-DX
 Serial number : Identical prototype
 Date of receipt : October 06, 2023
 EUT condition : Pre-production, not damaged
 Antenna type : Ceramic Antenna (Max Gain : 2.2 dBi)
 Frequency Range : 5180 MHz ~ 5240 MHz - 802.11a/n20/n40/ac20/ac40/ac80
 : 5745 MHz ~ 5825 MHz - 802.11a/n20/n40/ac20/ac40/ac80
 Type of Modulation : GFSK, CCK, DQPSK, DBPSK for DSSS,
 : 64QAM, 16QAM, QPSK, BPSK for OFDM
 Power Source : DC 5 V

2-3 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
Notebook	-	MS-1736	MSI

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
§ 1.1310 and §2.1091	RF EXPOSURE EVULATION	-	-	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

-

3.2 RF EXPOSURE EVALUATION

1.1 Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength	Magnetic field Strength	Power density (mW/cm ²)	Averaging time
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....			f/1500	30
1500 - 100.000.....			1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

1.2 MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

Power density at the specific separation:

$S = PG/(4R^2\pi)$ $S = (15.81 * 1.66) / (4 * 20^2 * \pi)$ $S = 0.23 \text{ mW/cm}^2$	Where, S = Maximum power density (mW/cm²) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20 cm = limit for MPE)
---	--

1.3 MAXIMUM PERMISSIBLE EXPOSURE Prediction

- Calculated under the worst-case conditions of each mode.

(Measured power 12 dBm $\pm$ 0.5dB)

5GHz Mode

Max Peak output Power at antenna input terminal	11.99	dBm
Max Peak output Power at antenna input terminal	15.81	mW
Prediction distance	5	cm
Prediction frequency	5825	MHz
Antenna Gain(typical)	2.2	dBi
Antenna Gain(numeric)	1.66	-

SAR Test exclusion thresholds for 100MHz to 6GHz at test separation distance $\leq$ 50 mm = **Used**

$[(\text{max.power of channel, including tune-up torelance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f}(\text{GHz})]$

$= [15.81 / 20] * [\sqrt{5.825}] = 1.91 \leq 3.0$, for 1g SAR

Thus, SAR for this device is not required.