Report No.: ET-23030267E

TEST REPORT

Applicant:	Shenzhen Zhuoyuetai Technology Co., Ltd.
Address of Applicant:	Rm 02-A222, Shanling Digital Bldg A,No.10 Chiwan Rd, Chiwan Community,Zhaoshang St,Nanshan Dist, Shenzhen CHINA
Manufacturer/Factory:	Shenzhen Zhuoyuetai Technology Co., Ltd.
Address of Manufacturer	Rm 02-A222, Shanling Digital Bldg A,No.10 Chiwan Rd, Chiwan Community,Zhaoshang St,Nanshan Dist, Shenzhen CHINA
Product Name:	Item Locator and Personal Alarm
Model No.:	A1, A1 Pro, A2, A2 Pro, A3, A3 Pro, A4, A4Pro, A5, A5P
Trade Mark:	N/A
FCC ID:	2BA2F-A1
Applicable standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of Test:	March.25, 2023- April.14, 2023
Date of report issued:	April.14, 2023
Test Result :	PASS *

Remark:
* In the configuration tested, the EUT complied with the standards specified above.

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full without prior written permission of the company.

The report would be invalid without specific stamp of test institute and the signatures of compiler and approver

Prepared By

Shenzhen ETR Standard Technology Co., Ltd.

Address: No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Compiled by:	Reviewed by:	Approved by:
Carr Kang	Smith Chen	Smith Chen
Project Engineer	Project Manager	Authorized Signature

This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen ETR Standard Technology Co., Ltd.

Report Revision History		
Report No.	Description	Issue Date
ET-23030267E	Original	April.14, 2023

Contents

Page

1. TEST SUMMARY 4

2. GENERAL INFORMATION 5

2.1 GENERAL DESCRIPTION OF EUT 5
2.2 TEST MODE 7
2.3 DESCRIPTION OF SUPPORT UNITS 7
2.4 DEVIATION FROM STANDARDS 7
2.5 ABNORMALITIES FROM STANDARD CONDITIONS 7
2.6 TEST FACILITY 7
2.7 TEST LOCATION 7
2.8 ADDITIONAL INSTRUCTIONS 7

3. TEST INSTRUMENTS LIST 8

4. TEST RESULTS AND MEASUREMENT DATA 9

4.1 ANTENNA REQUIREMENT 9
4.2 CONDUCTED EMISSIONS 10
4.3 CONDUCTED PEAK OUTPUT POWER 13
4.4CHANNEL BANDWIDTH 14
4.5 POWER SPECTRAL DENSITY 16
4.6 BAND EDGES 17
Conducted Emission Method 17
Radiated Emission Method 19
4.7 SPURIOUS EMISSION 21
Conducted Emission Method 21
Radiated Emission Method 23

5. TEST SETUP PHOTO 31

6. EUT CONSTRUCTIONAL DETAILS 31

1. Test Summary

Test Item	Section	Result	Test by
Antenna requirement	FCC part 15.203/15.247 (c) RSS-Gen §6.8	Pass	/
AC Power Line Conducted Emission	FCC part 15.207 RSS-Gen §8.8	Pass	Qiao Li
Conducted Peak Output Power	FCC part 15.247 (b)(3) RSS-247 §5.4.d	Pass	Yvan Fan
Channel Bandwidth & 99% OCB	FCC part 15.247 (a)(2) RSS-247 §5.2.a RSS-Gen § 6.7	Pass	Yvan Fan
Power Spectral Density	FCC part 15.247 (e) RSS-247 §5.2.b	Pass	Yvan Fan
Band Edge	FCC part 15.247(d) RSS-247 §5.5	Pass	Yvan Fan
Spurious Emission	FCC part 15.205/15.209 RSS-Gen §8.9 §8.10	Pass	Qiao Li

Remark: Test according to ANSI C63.10:2013 and RSS-Gen

Pass: The EUT complies with the essential requirements in the standard.

Measurement Uncertainty

Test Item	Uncertainty Criterion	Measurement Uncertainty	Notes
Occupied Channel Bandwidth	±5%	±0.55%	(1)
RF output power, conducted	±1.5dB	±0.99dB	(1)
Power Spectral Density, conducted	±3dB	±0.61dB	(1)
Unwanted Emissions, conducted	±3dB	±0.64dB	(1)
AC Power Line Conducted Emission	±6dB	± 3.02 dB	(1)
Radiated emissions Below 1GHz	±6dB	±4.30 dB	(1)
Radiated emissions Above 1GHz	±6dB	±4.35 dB	(1)
Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.			

2. General Information

2.1 General Description of EUT

Product Name:	Item Locator and Personal Alarm
Model No.:	A1, A1 Pro, A2, A2 Pro, A3, A3 Pro, A4, A4Pro, A5, A5P
Test Model:	A1
Difference of model(s)	There is no difference between the except for different names of sales regions. So all the test were performed on the model A1
Hardware version:	V1.0
Software version:	V1.0
Sample(s) Status	Engineer sample
Operation Frequency:	2402MHz~2480MHz
Channel Numbers:	40
Channel separation:	2MHz
Modulation technology:	GFSK
Battery:	DC 3.7V 140mAh
Antenna Type:	PCB Antenna
Antenna gain:	1.08 dBi(Declare by applicant)
Power supply:	DC 5V for adapter with AC 120V 60Hz

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402 MHz	11	2422 MHz	21	2442 MHz	31	2462 MHz
2	2404 MHz	12	2424 MHz	22	2444 MHz	32	2464 MHz
3	2406 MHz	13	2426 MHz	23	2446 MHz	33	2466 MHz
4	2408 MHz	14	2428 MHz	24	2448 MHz	34	2468 MHz
5	2410 MHz	15	2430 MHz	25	2450 MHz	35	2470 MHz
6	2412 MHz	16	2432 MHz	26	2452 MHz	36	2472 MHz
7	2414 MHz	17	2434 MHz	27	2454 MHz	37	2474 MHz
8	2416 MHz	18	2436 MHz	28	2456 MHz	38	2476 MHz
9	2418 MHz	19	2438 MHz	29	2458 MHz	39	2478 MHz
10	2420 MHz	20	2440 MHz	30	2460 MHz	40	2480 MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)
Lowest channel	2402MHz
Middle channel	2440MHz
Highest channel	2480MHz

2.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: For battery operated equipment, the EUT was performed using a new DC 3.8V battery.	

2.3 Description of Support Units

No.	Description	Manufacturer	Model	Serial Number
/	/	/	/	/

2.4 Deviation from Standards

None.

2.5 Abnormalities from Standard Conditions

None.

2.6 Test Facility

Test laboratory:	Shenzhen ETR Standard Technology Co., Ltd.
CNAS Registration Number:	L11864
A2LA Certificate Number:	6640.01
FCC Designation Number:	CN1326
FCC Test Firm Registration:	183064

2.7 Test Location

All tests were performed at:	
Laboratory location:	No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	+86 755 85259392
Fax:	+86 755 27219460

2.8 Additional Instructions

Test Software	FR8010H_Download_Tool.exe
Power level setup	Default

3. Test Instruments list

Item	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	EMI Test Receiver	Rohde&schwarz	ESPI7	100605	2022.3.09	2023.3.08
2	EMI Test Receiver	Rohde&schwarz	ESCI3	102696	2022.3.09	2023.3.08
3	Broadband antenna	schwarabeck	VULB9168	1064	2022.3.11	2024.3.10
4	Horn antenna	schwarabeck	BBHA9120D	9120D-1145	2022.3.09	2023.3.08
5	amplifier	EMtrace	RP01A	50117	2022.3.09	2023.3.08
6	Artificial power network	schwarabeck	NSLK8127	8127483	2022.3.09	2023.3.08
	Artificial power network	ETS	3186/2NM	1132	2022.3.09	2023.3.08
7	10dB attenuator	HUBER+SUHNER	10dB	/	2022.3.09	2023.3.08
8	amplifier	Space-Dtronics	EWLAN0118 G-P40	19113001	2022.3.09	2023.3.08
9	Spectrum analyzer	KEYSIGHT	N9020A	MY55370280	2022.3.09	2023.3.08
10	Power detector box	MWRFtest	MW100-PSB	MW201020JYT	2022.11.18	2023.11.17

Note: the calibration interval of the above test instruments is 12 or 24 months and the calibrations are traceable to international system unit (SI).

Software Name	Manufacturer	Model	Version
RF test software	MWRFtest	MTS 8310	V2.0.0.0
Conducted test software	EZ-EMC	Farad	Ver.EMC-CON 3A1.1
Radiated test software	EZ-EMC	Farad	Ver.FA-03A2 RE

4. Test results and Measurement Data

4.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c) ,RSS-Gen §6.8
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. **15.247(c) (1)(i) requirement:** (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
The antenna is PCB antenna, the best case gain of the antenna is 1.08 dBi, reference to the appendix II for details.	

4.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207, RSS-Gen §8.8
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto
Limit:	

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test setup:



Remark:
E.U.T: Equipment Under Test
LISN: Line Impedence Stabilization Network
Test table height=0.8m

Test procedure:

1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.

Test Instruments:	Refer to section 3.0 for details					
Test mode:	Refer to section 2.2 for details					
Test environment:	Temp.:	25.4°C	Humid.:	53%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement data

Line:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.3885	19.32	9.89	29.21	48.10	-18.89	AVG
2	0.3930	32.62	9.89	42.51	58.00	-15.49	QP
3	0.4605	20.97	9.93	30.90	46.68	-15.78	AVG
4	0.4695	34.67	9.93	44.60	56.52	-11.92	QP
5	0.5279	31.01	9.94	40.95	56.00	-15.05	QP
6	0.5369	17.28	9.94	27.22	46.00	-18.78	AVG
7	0.6987	14.17	9.94	24.11	46.00	-21.89	AVG
8	0.7167	28.62	9.94	38.56	56.00	-17.44	QP
9	1.3424	29.64	9.92	39.56	56.00	-16.44	QP
10	1.3424	16.14	9.92	26.06	46.00	-19.94	AVG
11	2.1525	31.63	9.85	41.48	56.00	-14.52	QP
12	2.2065	16.89	9.85	26.74	46.00	-19.26	AVG

Neutral:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.4650	26.39	9.93	36.32	46.60	-10.28	AVG
2	0.4784	36.91	9.93	46.84	56.37	-9.53	QP
3	0.7034	20.10	9.94	30.04	46.00	-15.96	AVG
4	0.7078	30.44	9.94	40.38	56.00	-15.62	QP
5	1.2882	20.28	9.92	30.20	46.00	-15.80	AVG
6	1.3468	30.55	9.92	40.47	56.00	-15.53	QP
7	2.1253	19.63	9.85	29.48	46.00	-16.52	AVG
8	2.1478	31.53	9.85	41.38	56.00	-14.62	QP
9	3.0480	17.63	9.84	27.47	46.00	-18.53	AVG
10	3.1650	30.37	9.84	40.21	56.00	-15.79	QP
11	4.5868	29.08	9.84	38.92	56.00	-17.08	QP
12	4.6950	14.39	9.84	24.23	46.00	-21.77	AVG

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Level =Receiver Read level + Factor (Factor= LISN Factor + Cable Loss+ Attenuator Factor)
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

4.3 Conducted Peak Output Power

Test Requirement :	FCC Part15 C Section 15.247 (b)(3) , RSS-247 §5.4.d
Test Method :	ANSI C63.10:2013 and KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	30dBm
Test setup:	
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Measurement Data

Test channel	Peak Output Power (dBm)	Limit(dBm)	Result
Lowest	-1.66	30.00	Pass
Middle	-1.51		
Highest	-2.29		

4.4Channel Bandwidth

Test Requirement :	FCC Part15 C Section 15.247 (a)(2), RSS-247 §5.2.a
Test Method :	ANSI C63.10:2013 and KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	>500KHz
Test setup:	
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Measurement Data

Test channel	Channel Bandwidth (MHz)	Limit(KHz)	Result
Lowest	0.5049	>500	Pass
Middle	0.5159		
Highest	0.5231		

Test plot as follows:

Lowest channel



Middle channel

Highest channel

4.5 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e), RSS-247 §5.2.b
Test Method:	ANSI C63.10:2013 and KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	8dBm/3kHz
Test setup:	
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Measurement Data

Test channel	Power Spectral Density (dBm/3kHz)	Limit(dBm/3kHz)	Result
Lowest	-21.706	8.00	Pass
Middle	-21.964		
Highest	-23.212		

Test plot as follows:

Lowest channel

Middle channel

Highest channel

4.6 Band edges

Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d), RSS-247 §5.5

Test Method:	KDB558074 D01 DTS Meas Guidance v05or02
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Test plot as follows:



Lowest channel



Highest channel

Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205, RSS-Gen §8.9 §8.10
Test Method:	ANSI C63.10: 2013
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.
Test site:	Measurement Distance: 3m
Receiver setup:	Frequency / Detector / RBW / VBW / Value Above 1GHz / Peak / 1MHz / 3MHz / Peak Above 1GHz / Average / 1MHz / 3MHz / Average
Limit:	Frequency / Limit (dBuV/m @3m) / Value Above 1GHz / 54.00 / Average Above 1GHz / 74.00 / Peak
Test setup:	
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 7. The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test worst case mode is recorded in the report.
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Measurement data:

Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	62.19	27.4	3.41	45.4	47.60	74.00	-26.40	Horizontal
2390.00	62.74	27.1	3.43	45.4	47.87	74.00	-26.13	Horizontal
2310.00	60.28	27.1	3.43	45.4	45.41	74.00	-28.59	Vertical
2390.00	62.19	27.4	3.41	45.4	47.60	74.00	-26.40	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	44.18	27.4	3.41	45.4	29.59	54.00	-24.41	Horizontal
2390.00	46.44	27.1	3.43	45.4	31.57	54.00	-22.43	Horizontal
2310.00	45.48	27.1	3.43	45.4	30.61	54.00	-23.39	Vertical
2390.00	48.16	27.4	3.41	45.4	33.57	54.00	-20.43	Vertical

Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	54.90	27.8	3.56	45.4	40.86	74.00	-33.14	Horizontal
2500.00	54.30	27.8	3.56	45.4	40.26	74.00	-33.74	Horizontal
2483.50	57.20	27.8	3.56	45.4	43.16	74.00	-30.84	Vertical
2500.00	56.33	27.8	3.56	45.4	42.29	74.00	-31.71	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	45.37	27.8	3.56	45.4	31.33	54.00	-22.67	Horizontal
2500.00	47.32	27.8	3.56	45.4	33.28	54.00	-20.72	Horizontal
2483.50	46.43	27.8	3.56	45.4	32.39	54.00	-21.61	Vertical
2500.00	46.52	27.8	3.56	45.4	32.48	54.00	-21.52	Vertical

Remarks:

1. *Level = Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
3. *The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.*

4.7 Spurious Emission

Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d), RSS-Gen §8.9 §8.10
Test Method:	KDB558074 D01 DTS Meas Guidance v05or02
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Test plot as follows:

Lowest channel



30MHz~26.5GHz

Middle channel



30MHz~26.5GHz

Highest channel



30MHz~26.5GHz

Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 , RSS-Gen §8.9 §8.10
Test Method:	ANSI C63.10: 2013
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m

Receiver setup:

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Limit:

Frequency	Limit (uV/m)	Value	Measurement Distance
0.009MHz-0.490MHz	2400/F(KHz)	QP	300m
0.490MHz-1.705MHz	24000/F(KHz)	QP	300m
1.705MHz-30MHz	30	QP	30m
30MHz-88MHz	100	QP	3m
88MHz-216MHz	150	QP	
216MHz-960MHz	200	QP	
960MHz-1GHz	500	QP	
Above 1GHz	500	Average	
	5000	Peak	

Test setup:

For radiated emissions from 9kHz to 30MHz



For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details

Test voltage:	DC 3.8V					
Test environment:	Temp.:	25.6 °C	Humid.:	55%	Press.:	1012mbar
Test results:	Pass					

Remarks:

1. *The report only shows the worst mode.*
2. *Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.*

Measurement data:

■ **9kHz~30MHz**

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

■ **Below 1GHz**

Vertical:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.1052	48.34	-21.55	26.79	40.00	-13.21	QP
2	63.9827	48.52	-20.63	27.89	40.00	-12.11	QP
3	69.6003	50.12	-20.54	29.58	40.00	-10.42	QP
4	143.8294	44.54	-18.99	25.55	43.50	-17.95	QP
5	184.4898	42.78	-18.48	24.30	43.50	-19.20	QP
6	250.3010	49.22	-18.25	30.97	46.00	-15.03	QP

Horizontal:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	54.2608	45.89	-20.86	25.03	40.00	-14.97	QP
2	72.0841	45.43	-20.48	24.95	40.00	-15.05	QP
3	153.2002	51.29	-18.95	32.34	43.50	-11.16	QP
4	250.3010	48.64	-18.25	30.39	46.00	-15.61	QP
5	378.5842	39.15	-16.95	22.20	46.00	-23.80	QP
6	955.4380	34.14	-4.80	29.34	46.00	-16.66	QP

Remarks:

Level =Receiver Reading + Factor

Factor= Antenna Factor + Cable Factor – Preamplifier Factor

■ **Above 1GHz**

Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	62.66	32.10	5.96	45.70	55.02	74.00	-18.98	Vertical
7206.00	57.00	36.10	6.86	45.50	54.46	74.00	-19.54	Vertical
9608.00	52.28	38.30	8.25	46.20	52.63	74.00	-21.37	Vertical
12010.00	*	--	--	--	--	74.00	--	Vertical
14412.00	*	--	--	--	--	74.00	--	Vertical
4804.00	61.50	32.10	5.96	45.70	53.86	74.00	-20.14	Horizontal
7206.00	57.85	36.10	6.86	45.50	55.31	74.00	-18.69	Horizontal
9608.00	51.45	38.30	8.25	46.20	51.80	74.00	-22.20	Horizontal
12010.00	*	--	--	--	--	74.00	--	Horizontal
14412.00	*	--	--	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	40.97	32.10	5.96	45.70	33.33	54.00	-20.67	Vertical
7206.00	37.13	36.10	6.86	45.50	34.59	54.00	-19.41	Vertical
9608.00	31.00	38.30	8.25	46.20	31.35	54.00	-22.65	Vertical
12010.00	*	--	--	--	--	54.00	--	Vertical
14412.00	*	--	--	--	--	54.00	--	Vertical
4804.00	43.25	32.10	5.96	45.70	35.61	54.00	-18.39	Horizontal
7206.00	37.30	36.10	6.86	45.50	34.76	54.00	-19.24	Horizontal
9608.00	31.29	38.30	8.25	46.20	31.64	54.00	-22.36	Horizontal
12010.00	*	--	--	--	--	54.00	--	Horizontal
14412.00	*	--	--	--	--	54.00	--	Horizontal

Remarks:

1. *Level = Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

Test channel:	Middle

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	60.60	32.10	5.96	45.70	52.96	74.00	-21.04	Vertical
7320.00	56.43	36.10	6.86	45.50	53.89	74.00	-20.11	Vertical
9760.00	53.35	38.30	8.25	46.20	53.70	74.00	-20.30	Vertical
12200.00	*	--	--	--	--	74.00	--	Vertical
14640.00	*	--	--	--	--	74.00	--	Vertical
4880.00	60.86	32.10	5.96	45.70	53.22	74.00	-20.78	Horizontal
7320.00	58.85	36.10	6.86	45.50	56.31	74.00	-17.69	Horizontal
9760.00	52.34	38.30	8.25	46.20	52.69	74.00	-21.31	Horizontal
12200.00	*	--	--	--	--	74.00	--	Horizontal
14640.00	*	--	--	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	41.62	32.10	5.96	45.70	33.98	54.00	-20.02	Vertical
7320.00	37.31	36.10	6.86	45.50	34.77	54.00	-19.23	Vertical
9760.00	33.69	38.30	8.25	46.20	34.04	54.00	-19.96	Vertical
12200.00	*	--	--	--	--	54.00	--	Vertical
14640.00	*	--	--	--	--	54.00	--	Vertical
4880.00	42.12	32.10	5.96	45.70	34.48	54.00	-19.52	Horizontal
7320.00	36.73	36.10	6.86	45.50	34.19	54.00	-19.81	Horizontal
9760.00	32.02	38.30	8.25	46.20	32.37	54.00	-21.63	Horizontal
12200.00	*	--	--	--	--	54.00	--	Horizontal
14640.00	*	--	--	--	--	54.00	--	Horizontal

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	61.33	32.10	5.96	45.70	53.69	74.00	-20.31	Vertical
7440.00	57.29	36.10	6.86	45.50	54.75	74.00	-19.25	Vertical
9920.00	52.99	38.30	8.25	46.20	53.34	74.00	-20.66	Vertical
12400.00	*	--	--	--	--	74.00	--	Vertical
14880.00	*	--	--	--	--	74.00	--	Vertical
4960.00	61.64	32.10	5.96	45.70	54.00	74.00	-20.00	Horizontal
7440.00	57.99	36.10	6.86	45.50	55.45	74.00	-18.55	Horizontal
9920.00	51.44	38.30	8.25	46.20	51.79	74.00	-22.21	Horizontal
12400.00	*	--	--	--	--	74.00	--	Horizontal
14880.00	*	--	--	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	42.14	32.10	5.96	45.70	34.50	54.00	-19.50	Vertical
7440.00	35.26	36.10	6.86	45.50	32.72	54.00	-21.28	Vertical
9920.00	33.20	38.30	8.25	46.20	33.55	54.00	-20.45	Vertical
12400.00	*	--	--	--	--	54.00	--	Vertical
14880.00	*	--	--	--	--	54.00	--	Vertical
4960.00	41.95	32.10	5.96	45.70	34.31	54.00	-19.69	Horizontal
7440.00	37.71	36.10	6.86	45.50	35.17	54.00	-18.83	Horizontal
9920.00	32.03	38.30	8.25	46.20	32.38	54.00	-21.62	Horizontal
12400.00	*	--	--	--	--	54.00	--	Horizontal
14880.00	*	--	--	--	--	54.00	--	Horizontal

Remarks:

1. *Level = Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

5. Test Setup Photo

Reference to the **appendix I** for details.

6. EUT Constructional Details

Reference to the **appendix II** external photos and **appendix III** internal photos for details.

------End------