



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR251200329806

Page: 1 of 14

1 Cover Page

RF Exposure Evaluation Report

Application No.: SHCR2512003298HS
FCC ID: 2BA2LG7
Applicant: MGI Golf Inc
Address of Applicant: 6825 Speedway Blvd Suite #B101B Las Vegas, NEVADA 89115
Manufacturer: CADDIESTER GOLF BUGGY TECHNOLOGY LTD
Address of Manufacturer: NO.16-8 TONGZI RIVER WEST ROAD, ZHONGLOU DEVELOPMENT DIST, CHANGZHOU, CHINA
Factory: CADDIESTER GOLF BUGGY TECHNOLOGY LTD
Address of Factory: NO.16-8 TONGZI RIVER WEST ROAD, ZHONGLOU DEVELOPMENT DIST, CHANGZHOU, CHINA
Equipment Under Test (EUT):
EUT Name: Golf Trolley
Model No.: NAVIGATOR Ai, AI NAVIGATOR HALO
Trade Mark: MGI
Standard(s) : FCC Rules 47 CFR §2.1093
KDB 447498 D04 interim General RF Exposure Guidance v01
Date of Receipt: 2025-12-15
Date of Test: 2026-02-03 to 2026-02-25
Date of Issue: 2026-03-03

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Member of the SGS Group (SGS SA)



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR251200329806

Page: 2 of 14

Revision Record			
Version	Description	Date	Remark
00	Add test data for new model	2026-03-03	Based on SHCR230300042407

Authorized for issue by:			
Tested By		Wade Zhang	
		Wade Zhang/Project Engineer	
Approved By		Parlam Zhan	
		Parlam Zhan / Reviewer	



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR251200329806

Page: 3 of 14

2 Contents

	Page
1 Cover Page	1
2 Contents	3
3 General Information.....	4
3.1 General Description of E.U.T.	4
3.2 Technical Specifications.....	4
3.3 Separation Distance.....	6
3.4 Test Location.....	7
3.5 Test Facility	7
4 Test Standards and Limits.....	8
4.1 Blanket 1 mW Blanket Exemption.....	8
4.2 MPE-based Exemption	8
4.3 SAR-based Exemption.....	9
5 Measurement and Calculation.....	11
5.1 Maximum transmit power	11
5.2 RF Exposure Calculation	14

3 General Information

3.1 General Description of E.U.T.

Power supply:	DC24V 10.4Ah Li-ion Battery Charger Model: FLC-108 Input: AC100-240V 50/60Hz 1.5A Max Output: DC 28.8V 2.0A & DC5V 0.5A
Product Type:	☒ Portable device ☐ Mobile device ☐ Fixed device

3.2 Technical Specifications

BT

Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK, pi/4DQPSK, 8DPSK
Number of Channels:	79
Channel Spacing:	1MHz
Spectrum Spread Technology:	Frequency Hopping Spread Spectrum(FHSS)
Antenna Type:	FPC Antenna
Antenna Gain:	2.2 dBi (Provided by manufacturer)

BLE 4.0 (For SC20-WL module)

Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V4.0 LE
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	FPC Antenna
Antenna Gain:	2.2 dBi (Provided by manufacturer)

BLE 5.0 (For nRF52811 module)

Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V5.0 LE
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	PCB Antenna
Antenna Gain:	-3.86dBi (Provided by manufacturer)

2.4GHz WiFi

Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz;802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK);802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	802.11b/g/n(HT20):11;802.11n(HT40):7
Channel Spacing:	5MHz
Antenna Type:	FPC Antenna
Antenna Gain:	2.2 dBi (Provided by manufacturer)

5GHz WiFi

Operation Frequency/Number of channels (20MHz):	U-NII-1: 5180-5240MHz (4 Channels); U-NII-2A: 5260-5320MHz (4 Channels); U-NII-2C: 5500-5700MHz (11 Channels); U-NII-3: 5745-5825MHz (5 Channels)
---	---



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023


Report No.: SHCR251200329806

Page: 5 of 14


Operation Frequency/Number of channels/(40MHz):	U-NII-1: 5190-5230MHz (2 Channels); U-NII-2A: 5270-5310MHz (2 Channels); U-NII-2C: 5510-5670MHz (5 Channels); U-NII-3: 5755-5795MHz (2 Channels)
Modulation Type:	802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK); 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Channel Spacing:	802.11a/n(HT20): 20MHz; 802.11n(HT40): 40MHz
DFS Function:	Slave without Radar detection
TPC Function:	Without TPC function
Antenna Type:	FPC Antenna
Antenna Gain:	3.8 dBi (Provided by manufacturer)

3.3 Separation Distance

Separation distance between the antenna to person (R):	7cm (SC20-WL WIFI&BT Antenna) 1cm (NRF52811 BLE Antenna)
Remark: This minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander.	



The WIFI Antenna to Handle(Where the hand holds) Distance



The NRF52811 BLE Antenna to LCD screen Distance (1cm)

3.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shanghai Branch
588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China.

Tel: +86 21 6191 5666

Fax: +86 21 6191 5678

No tests were sub-contracted.

Note:

1. SGS is not responsible for wrong test results due to incorrect information (e.g. max. clock frequency, highest internal frequency, antenna gain, cable loss, etc) is provided by the applicant. (if applicable).
2. SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (if applicable).

3.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6332.01)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the American Association for Laboratory Accreditation(A2LA).

- **FCC (Designation Number: CN1301)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

- **ISED (CAB Identifier: CN0020)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory
Company Number: 8617A

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.

4 Test Standards and Limits

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds.

4.1 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of §1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1-mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph §1.1307(b)(3)(ii)(A).

The 1-mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

4.2 MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table B.1—Thresholds For Single RF Sources Subject to Routine Environmental Evaluation

RF Source Frequency			Minimum Distance			Threshold ERP
f_L MHz		f_H MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W
0.3	–	1.34	159 m	–	35.6 m	1,920 R ²
1.34	–	30	35.6 m	–	1.6 m	3,450 R ² /f ²
30	–	300	1.6 m	–	159 mm	3.83 R ²
300	–	1,500	159 mm	–	31.8 mm	0.0128 R ² f
1,500	–	100,000	31.8 mm	–	0.5 mm	19.2R ²
Subscripts L and H are low and high; λ is wavelength. From §1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.						

The table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

For mobile devices that are not exempt per Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in §1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from §2.1091(c)(1); also in §1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

Limit calculation			
Frequency range	Frequency(MHz)	$R(\lambda/2\pi)(\text{m})$	Threshold ERP(W)
300~1500MHz	915	0.0522	0.032
1500~100000MHz	2462	0.0194	0.007

4.3 SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of $\lambda/4$.

As for devices with antennas of length greater than $\lambda/4$ where the gain is not well defined, but always less than that of a half-wave dipole (length $\lambda/2$), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

The SAR-based exemption formula of §1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR251200329806

Page: 10 of 14

Frequency (MHz)	Distance(mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

Limit calculation				
Frequency range(GHz)	Frequency(GHz)	X	Distance(cm)	Pth (mW)
0.3~1.5	0.915	1.474	0.5	8.13
1.5~6	2.441	1.901	7	415.75
1.5~6	2.44	1.901	7	415.79
1.5~6	2.462	1.903	7	414.94
1.5~6	5.51	2.078	7	345.33
1.5~6	2.402	1.898	1	10.39

5 Measurement and Calculation

5.1 Maximum transmit power

BT

The Power Data is based on the RF Test Report SHCR230300042401

TestMode	Antenna	Channel	Maximum Peak Conducted Output Power (dBm)	Maximum Peak Conducted Output Power (mW)
DH5	Ant1	2402	3.85	2.43
		2441	4.51	2.82
		2480	3.6	2.29
2DH5	Ant1	2402	3.94	2.48
		2441	4.52	2.83
		2480	3.65	2.32
3DH5	Ant1	2402	4.27	2.67
		2441	4.87	3.07
		2480	3.96	2.49

BLE 4.0

The Power Data is based on the RF Test Report SHCR230300042402

Mode	TX Type	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)	Maximum Peak Conducted Output Power (mW)
1M	SISO	2402	-0.22	0.95
		2440	0.42	1.10
		2480	-0.51	0.89

BLE 5.0

The Power Data is based on the RF Test Report SHCR230300042405

TestMode	Antenna	Channel	Maximum Peak Conducted Output Power (dBm)	Maximum Peak Conducted Output Power (mW)
BLE_1M	Ant1	2402	-2.47	0.57
		2440	-3.19	0.48
		2480	-2.94	0.51
BLE_2M	Ant1	2402	-2.54	0.56
		2440	-3.2	0.48
		2480	-2.99	0.50

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR251200329806

Page: 12 of 14

2.4GHz WiFi

The Power Data is based on the RF Test Report SHCR230300042403

Test Mode	Test Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)	Maximum Peak Conducted Output Power (mW)
11B	2412	15.93	39.17
	2437	15.73	37.41
	2462	16.71	46.88
11G	2412	11.03	12.68
	2437	12.12	16.29
	2462	12.26	16.83
11N20 SISO	2412	11.02	12.65
	2437	12.15	16.41
	2462	12.34	17.14
11N40 SISO	2422	10.24	10.57
	2437	10.80	12.02
	2452	10.03	10.07

5GHz WiFi:

The Power Data is based on the RF Test Report SHCR230300042404

Test Mode	Antenna	Channel	Maximum Peak Conducted Output Power (dBm)	Maximum Peak Conducted Output Power (mW)
11A	Ant1	5180	9.43	8.77
		5220	9.65	9.23
		5240	10.18	10.42
		5260	10.38	10.91
		5300	9.97	9.93
		5320	10.00	10.00
		5500	9.62	9.16
		5580	7.15	5.19
		5700	6.75	4.73
		5745	6.67	4.65
		5785	6.28	4.25
		5825	6.88	4.88
11N20SISO	Ant1	5180	8.60	7.24
		5220	7.97	6.27
		5240	8.94	7.83
		5260	9.82	9.59
		5300	10.63	11.56
		5320	10.10	10.23
		5500	11.29	13.46
		5580	9.57	9.06



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR251200329806

Page: 13 of 14

		5700	7.74	5.94
		5745	6.62	4.59
		5785	5.85	3.85
		5825	6.65	4.62
11N40SISO	Ant1	5190	9.24	8.39
		5230	9.33	8.57
		5270	9.75	9.44
		5310	9.83	9.62
		5510	11.50	14.13
		5550	11.14	13.00
		5670	8.50	7.08
		5755	7.02	5.04
		5795	5.89	3.88

5.2 RF Exposure Calculation

Band	Frequency	Max power (dBm)	Ant Gain (dBi)	EIRP (dBm)	Max EIRP (mW)	Max Power (mW)	Distance R (cm)	Limit (mW)	Result	Ratio
BT	2441	4.87	2.2	7.07	5.09	3.07	7	415.75	Pass	0.012
BLE	2440	0.42	2.2	2.62	1.83	1.10	7	415.79	Pass	0.004
WLAN 2.4GHz	2462	16.71	2.2	18.91	77.80	46.88	7	414.94	Pass	0.188
WLAN 5GHz	5510	11.50	3.8	15.3	33.88	14.13	7	345.33	Pass	0.098
BLE 5.0	2402	-2.47	-3.86	-2.47	0.57	0.57	1	10.39	Pass	0.055

The BT,BLE,2.4GHz WiFi,5GHz WiFi modules can transmit simultaneously, but the maximum rate of MPE is $0.012+0.188+0.098+0.055 = 0.353 \leq 1$

Remark: we used the maximum power between the conducted power and ERP/EIRP to perform RF exposure exemption evaluation.

So, the device is to qualify for FCC SAR test exemption, the exemption report is in lieu of the SAR report.

-End of the Report-