

TEST REPORT

Application No.: SHCR2512003298HS
FCC ID: 2BA2LG7
Applicant: MGI Golf Inc
Address of Applicant: 6825 Speedway Blvd Suite #B101B Las Vegas, NEVADA 89115
Manufacturer: CADDIESTER GOLF BUGGY TECHNOLOGY LTD
Address of Manufacturer: NO.16-8 TONGZI RIVER WEST ROAD, ZHONGLOU DEVELOPMENT DIST, CHANGZHOU, CHINA
Factory: CADDIESTER GOLF BUGGY TECHNOLOGY LTD
Address of Factory: NO.16-8 TONGZI RIVER WEST ROAD, ZHONGLOU DEVELOPMENT DIST, CHANGZHOU, CHINA
Equipment Under Test (EUT):
EUT Name: Golf Trolley
Model No.: NAVIGATOR Ai, AI NAVIGATOR HALO
Trade Mark: MGI
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2025-12-15
Date of Test: 2026-02-03 to 2026-02-25
Date of Issue: 2026-03-03

Test Result:
Pass*

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Member of the SGS Group (SGS SA)



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR251200329803

Page: 2 of 84

Revision Record			
Version	Description	Date	Remark
00	Add test data for new model	2026-03-03	Based on SHCR230300042403

Authorized for issue by:				
Tested By		Wade Zhang		
		Wade Zhang/Project Engineer		
Approved By		Parlam Zhan		
		Parlam Zhan / Reviewer		

2 Test Summary

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.10.5 & 11.12	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6 & 11.12	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

Note1: There are series models mentioned in this report, and they are the similar in electrical and electronic characters. We test the new model AI NAVIGATOR HALO since their differences in appearance and minor circuitry for non-transmitter (refer more to the Declaration Letter about Identity of Products).

Note2: Considering to the difference, pre-scan was performed on the sample in this report to find the items which can be influential to the result in the original test report for fully retest. This report only RSE was fully retested on model AI NAVIGATOR HALO and shown the data in new report SHCR251200329803, other test data in this report are refer to original report SHCR230300042403.

Note3: This test report (Ref. No.: SHCR251200329803) is only valid with the original test report (Ref. No.: SHCR230300042403)

3 Contents

	Page
1 COVER PAGE	1
2 Test Summary	3
3 Contents	4
4 General Information.....	5
4.1 Details of E.U.T.	5
4.2 Description of Support Units	5
4.3 Measurement Uncertainty	5
4.4 Test Location.....	6
4.5 Test Facility	6
4.6 Deviation from Standards.....	6
4.7 Abnormalities from Standard Conditions	6
5 Equipment List	7
6 Radio Spectrum Matter Test Results	8
6.1 Radiated Emissions which fall in the restricted bands	8
6.1.1 E.U.T. Operation	8
6.1.2 Test Mode Description	8
6.1.3 Test Setup Diagram	9
6.1.4 Measurement Procedure and Data.....	9
6.2 Radiated Spurious Emissions Below 1GHz	26
6.2.1 E.U.T. Operation	26
6.2.2 Test Mode Description	26
6.2.3 Test Setup Diagram	27
6.2.4 Measurement Procedure and Data.....	27
6.3 Radiated Spurious Emissions Above 1GHz.....	32
6.3.1 E.U.T. Operation	32
6.3.2 Test Mode Description	32
6.3.3 Test Setup Diagram	32
6.3.4 Measurement Procedure and Data.....	33
7 Test Setup Photo	84
8 EUT Constructional Details (EUT Photos)	84

4 General Information

4.1 Details of E.U.T.

Power supply:	DC24V 10.4Ah Li-ion Battery Charger Model: FLC-108 Input: AC100-240V 50/60Hz 1.5A Max Output: DC 28.8V 2.0A & DC5V 0.5A
Test voltage:	DC 24V
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz;802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK);802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	802.11b/g/n(HT20):11;802.11n(HT40):7
Channel Spacing:	5MHz
Antenna Type:	FPC Antenna
Antenna Gain:	2.2 dBi (Provided by manufacturer)

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Laptop	LENOVO	L460	-
SecureCRT	VanDyke	V 6.2.0	-
Serial port adapter plate	-	Test Plate 3	-

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	8.4×10^{-8}
2	Timeout	2s
3	Duty cycle	0.4%
4	Occupied Bandwidth	3%
5	RF conducted power	0.6dB
6	RF power density	2.9dB
7	Conducted Spurious emissions	0.75dB
8	RF Radiated power	5.2dB (Below 1GHz)
		5.9dB (Above 1GHz)
9	Radiated Spurious emission test	4.2dB (Below 30MHz)
		4.5dB (30MHz-1GHz)
		4.8dB (1GHz-6GHz)
		5.0dB (6GHz-18GHz)
		5.4dB (18GHz-40GHz)
10	Temperature test	1°C
11	Humidity test	3%
12	Supply voltages	1.5%
13	Time	3%

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. E&E Lab

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666

Fax: +86 21 6191 5678

No tests were sub-contracted.

Note:

1. SGS is not responsible for wrong test results due to incorrect information (e.g. max. clock frequency, highest internal frequency, antenna gain, cable loss, etc) is provided by the applicant. (if applicable).
2. SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (if applicable).
3. Sample source: sent by customer.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **A2LA (Certificate No. 6332.01)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the American Association for Laboratory Accreditation(A2LA).

• **FCC (Designation Number: CN1301)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

• **ISED (CAB Identifier: CN0020)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.
Company Number: 8617A

• **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None

5 Equipment List

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Conducted Test					
Spectrum Analyzer	Keysight	N9020B	SHEM241-1	2025/12/17	2026/12/16
Spectrum Analyzer	Agilent	N9020A	SHEM181-1	2025/04/30	2026/04/29
Signal Generator	R&S	SMR20	SHEM006-1	2025/07/30	2026/07/29
Signal Generator	Agilent	N5182A	SHEM182-1	2025/07/30	2026/07/29
Communication Tester	R&S	CMW270	SHEM183-1	2025/04/30	2026/04/29
Communication Tester	R&S	CMW500	SHEM268-1	2025/04/30	2026/04/29
Power Sensor	Keysight	U2021XA * 4	SHEM293-1	2025/07/30	2026/07/29
Splitter	Anritsu	MA1612A	SHEM185-1	/	/
Coupler	e-meca	803-S-1	SHEM186-1	/	/
High-low Temp Cabinet	Suzhou Zhihe	TL-40	SHEM087-1	2024/11/05	2026/11/04
AC Power Stabilizer	APC	KDF-31020T-V0-F0	SHEM216-1	2025/12/17	2026/12/16
DC Power Supply	HP	6010A	SHEM222-1	2025/12/17	2026/12/16
Conducted test Cable	/	RF01~RF04	/	2025/12/17	2026/12/16
Switcher	Tonscend	JS0806	SHEM293-1	2025/07/30	2026/07/29
Test software	Tonscend	JS Tonscend BT/WIFI System	Version: 2.6	/	/
Switcher+Power Sensor	TST	TSPS2023R	SHEM263-1	2025/07/30	2026/07/29
Test software	TST	TST PASS	Version: 2.0	/	/
RF Radiated Test					
Spectrum Analyzer	Keysight	N9010A	SHEM181-2	2025/04/30	2026/04/29
Communication Tester	R&S	CMW500	SHEM268-1	2025/04/30	2026/04/29
Loop Antenna (9kHz-30MHz)	Schwarzbeck	FMZB1519	SHEM135-1	2025/12/17	2026/12/16
Antenna (25MHz-2GHz)	Schwarzbeck	VULB9168	SHEM048-1	2025/08/31	2027/08/30
Antenna (25MHz-2GHz)	Schwarzbeck	VULB9168	SHEM202-1	2025/04/12	2027/04/11
Horn Antenna (1-18GHz)	Schwarzbeck	HF906	SHEM009-1	2024/08/05	2026/08/04
Horn Antenna (1-18GHz)	Schwarzbeck	BBHA9120D	SHEM050-1	2025/08/31	2027/08/30
Horn Antenna (14-40GHz)	Schwarzbeck	BBHA 9170	SHEM049-1	2025/08/31	2027/08/30
Pre-Amplifier	HP	8447D	SHEM236-1	2025/12/17	2026/12/16
High-amplifier (14-40GHz)	Schwarzbeck	10001	SHEM049-2	2025/12/17	2026/12/16
Band Filter	LORCH	9BRX-875/X150	SHEM156-1	/	/
Band Filter	LORCH	13BRX-1950/X500	SHEM083-2	/	/
Band Filter	LORCH	5BRX-2400/X200	SHEM155-1	/	/
Band Filter	LORCH	5BRX-5500/X1000	SHEM157-2	/	/
High pass Filter	Wainwright	WHK3.0/18G	SHEM157-1	/	/
High pass Filter	Wainwright	WHKS1700	SHEM157-3	/	/
Semi/Fully Anechoic	ST	11*6*6M	SHEM078-2	2023/05/06	2026/05/05
RE test Cable	/	PT18-NMMN-10M	SHEM217-2	2025/07/30	2026/07/29
Test software	ESE	E3	Version: 6.111221a	/	/

6 Radio Spectrum Matter Test Results

6.1 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.10.5 & 11.12

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

6.1.1 E.U.T. Operation

Operating Environment:

Temperature: 18.2 °C


Humidity: 30.6 % RH

Atmospheric Pressure: 1010 mbar

6.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

6.1.3 Test Setup Diagram




6.1.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters for table-top or 0.01 meters for floor-standing arrangement above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2365.284	47.52	28.68	3.31	35.16	44.35	74.00	-29.65	Peak
2390.000	49.07	28.80	3.33	35.18	46.02	74.00	-27.98	Peak
2410.756	104.59	28.89	3.34	35.20	101.62	74.00	27.62	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2388.879	50.91	28.80	3.33	35.18	47.86	74.00	-26.14	Peak
2390.000	50.09	28.80	3.33	35.18	47.04	74.00	-26.96	Peak
2410.756	103.41	28.89	3.34	35.20	100.44	74.00	26.44	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2460.805	100.46	29.05	3.39	35.24	97.66	74.00	23.66	Peak
2483.500	49.03	29.09	3.41	35.26	46.27	74.00	-27.73	Peak
2488.525	48.41	29.09	3.41	35.26	45.65	74.00	-28.35	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2460.707	101.06	29.05	3.39	35.24	98.26	74.00	24.26	Peak
2483.500	49.75	29.09	3.41	35.26	46.99	74.00	-27.01	Peak
2487.430	49.60	29.09	3.41	35.26	46.84	74.00	-27.16	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2382.596	48.81	28.76	3.32	35.17	45.72	74.00	-28.28	Peak
2390.000	46.57	28.80	3.33	35.18	43.52	74.00	-30.48	Peak
2407.705	103.06	28.89	3.34	35.20	100.09	74.00	26.09	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2384.045	48.96	28.80	3.33	35.18	45.91	74.00	-28.09	Peak
2390.000	46.99	28.80	3.33	35.18	43.94	74.00	-30.06	Peak
2405.511	104.77	28.89	3.34	35.20	101.80	74.00	27.80	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL
EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2467.212	103.34	29.05	3.39	35.24	100.54	74.00	26.54	Peak
2483.500	49.60	29.09	3.41	35.26	46.84	74.00	-27.16	Peak
2490.417	48.90	29.10	3.41	35.26	46.15	74.00	-27.85	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2456.576	103.37	29.04	3.38	35.24	100.55	74.00	26.55	Peak
2483.500	48.35	29.09	3.41	35.26	45.59	74.00	-28.41	Peak
2487.729	49.31	29.09	3.41	35.26	46.55	74.00	-27.45	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2372.963	48.44	28.71	3.32	35.17	45.30	74.00	-28.70	Peak
2390.000	46.81	28.80	3.33	35.18	43.76	74.00	-30.24	Peak
2409.291	103.44	28.89	3.34	35.20	100.47	74.00	26.47	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2369.720	48.93	28.68	3.31	35.16	45.76	74.00	-28.24	Peak
2390.000	48.27	28.80	3.33	35.18	45.22	74.00	-28.78	Peak
2418.092	103.73	28.90	3.35	35.20	100.78	74.00	26.78	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2457.755	100.90	29.04	3.38	35.24	98.08	74.00	24.08	Peak
2483.500	49.02	29.09	3.41	35.26	46.26	74.00	-27.74	Peak
2488.425	49.31	29.09	3.41	35.26	46.55	74.00	-27.45	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity :VERTICAL
EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2460.116	103.09	29.04	3.38	35.24	100.27	74.00	26.27	Peak
2483.500	48.64	29.09	3.41	35.26	45.88	74.00	-28.12	Peak
2488.226	49.25	29.09	3.41	35.26	46.49	74.00	-27.51	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2376.312	49.43	28.71	3.32	35.17	46.29	74.00	-27.71	Peak
2390.000	48.27	28.80	3.33	35.18	45.22	74.00	-28.78	Peak
2411.385	98.14	28.90	3.35	35.20	95.19	74.00	21.19	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity :VERTICAL
EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2378.131	49.05	28.76	3.32	35.17	45.96	74.00	-28.04	Peak
2390.000	47.98	28.80	3.33	35.18	44.93	74.00	-29.07	Peak
2410.392	97.85	28.89	3.34	35.20	94.88	74.00	20.88	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2447.751	100.60	29.02	3.38	35.23	97.77	74.00	23.77	Peak
2483.500	49.03	29.09	3.41	35.26	46.27	74.00	-27.73	Peak
2494.562	48.75	29.10	3.41	35.26	46.00	74.00	-28.00	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Antenna Polarity :VERTICAL
EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2449.640	96.74	29.02	3.38	35.23	93.91	74.00	19.91	Peak
2483.500	48.68	29.09	3.41	35.26	45.92	74.00	-28.08	Peak
2502.270	49.14	29.12	3.42	35.27	46.41	74.00	-27.59	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

6.2 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.4,6.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

Note

1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

2. At frequencies below 1GHz, measurements may be performed at a distance different to specified in the regulations.

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Below 30MHz, Aux Factor = 40 dB/decade of distance, the aux factor is $40\log(3/300) = -80\text{dB}$ (for 3m test distance).

EX. Above 30MHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(10/3) = 10.46\text{dB}$ (for 10m test distance).

6.2.1 E.U.T. Operation

Operating Environment:

Temperature: 20.5 °C


Humidity: 54.6 % RH

Atmospheric Pressure: 1023 mbar

6.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

6.2.3 Test Setup Diagram




6.2.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters for table-top or 0.01 meters for floor-standing arrangement above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3m or 10m away from the interference-receiving antenna, which was mounted on the variable-height antenna tower.
- The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1m) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only below points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the worst-case test curve is displayed.

Test Mode: 02; Polarity: Horizontal




Antenna Polarity :HORIZONTAL
EUT/Project :3298HS
Test mode :02

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	100.934	55.27	9.40	2.02	33.10	33.59	43.50	-9.91	QP
2	161.474	48.23	12.80	2.63	32.97	30.69	43.50	-12.81	QP
3	169.599	47.90	12.80	2.69	32.96	30.43	43.50	-13.07	QP
4	468.876	40.90	16.17	4.64	32.60	29.11	46.00	-16.89	QP
5	642.861	41.69	19.98	5.48	32.60	34.55	46.00	-11.45	QP
6	938.833	33.17	23.76	6.78	31.52	32.19	46.00	-13.81	QP

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical



Antenna Polarity :VERTICAL

EUT/Project :3298HS


Test mode :02

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	30.105	49.62	12.70	1.10	33.20	30.22	40.00	-9.78	QP
2	35.005	48.81	12.80	1.19	33.20	29.60	40.00	-10.40	QP
3	52.025	49.52	13.30	1.44	33.18	31.08	40.00	-8.92	QP
4	82.648	51.38	9.00	1.82	33.10	29.10	40.00	-10.90	QP
5	140.342	49.36	12.20	2.44	33.02	30.98	43.50	-12.52	QP
6	169.599	51.45	12.80	2.69	32.96	33.98	43.50	-9.52	QP

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Radiated Emissions(9kHz-30MHz)

Test Mode: 02; Polarity: Coaxial




Item	Freq.	Read Level	Antenna Factor	Cable Loss	Result Level@3m	Result Level@SPEC	Limit Line@SPEC	Over Limit	Detector
(Mark)	(MHz)	(dBμV)	(dB/m)	(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	0.159	16.60	17.30	0.30	34.20	-45.80	23.57	-69.37	Average
2	0.239	14.16	17.30	0.30	31.76	-48.24	20.05	-68.29	Average
3	0.852	12.24	17.50	0.30	30.04	-9.96	29.01	-38.97	QP
4	1.541	10.81	17.66	0.30	28.77	-11.23	23.88	-35.11	QP
5	2.972	11.37	17.80	0.30	29.47	-10.53	29.50	-40.03	QP
6	8.061	8.77	18.09	0.30	27.16	-12.84	29.50	-42.34	QP

Remark: Result Level@3m = Read Level + Antenna Factor + Cable Loss

Result Level@SPEC= Result Level@3m+ Distance Extrapolation Factor

Test Mode: 02; Polarity: Coplanar



Item	Freq.	Read Level	Antenna Factor	Cable Loss	Result Level@3m	Result Level@SPEC	Limit Line@SPEC	Over Limit	Detector
(Mark)	(MHz)	(dBμV)	(dB/m)	(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	0.171	17.80	17.30	0.30	35.40	-44.60	22.94	-67.54	Average
2	0.252	14.71	17.30	0.30	32.31	-47.69	19.56	-67.25	Average
3	0.438	10.96	17.30	0.30	28.56	-51.44	14.77	-66.21	Average
4	0.873	13.31	17.50	0.30	31.11	-8.89	28.80	-37.69	QP
5	1.658	12.67	17.67	0.30	30.64	-9.36	23.24	-32.60	QP
6	2.854	13.12	17.79	0.30	31.21	-8.79	29.50	-38.29	QP

Remark: Result Level@3m = Read Level + Antenna Factor + Cable Loss

Result Level@SPEC= Result Level@3m+ Distance Extrapolation Factor

Note: For test distance other than what is specified, but fulfilling the requirements of section 15.31(f) (2) the field strength is calculated by adding additionally an extrapolation factor of 40dB/decade (inverse linear distance for field strength measurements). So the Distance Extrapolation Factor in dB is $40 \cdot \log(D_{TEST} / D_{SPEC})$ where D_{TEST} = Test Distance and D_{SPEC} = Specified Distance. Field strength limit (dBμV/m)@test distance= Field strength limit (dBμV/m)@specified distance +Distance Extrapolation Factor

6.3 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.6 & 11.12
 Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

Note:

At Above 18GHz, measurements may be performed at a distance shorter than that specified in the regulations

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Above 18GHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(1/3) = -9.54\text{dB}$ (for 1m test distance).

6.3.1 E.U.T. Operation

Operating Environment:

Temperature: 18.2 °C


Humidity: 30.7 % RH

Atmospheric Pressure: 1010 mbar

6.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

6.3.3 Test Setup Diagram




6.3.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5m above the ground at a 3m fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3m away from the interference-receiving antenna from 1GHz to 18GHz, and 3m away from the interference-receiving antenna above 18GHz.
- b. The interference-receiving antenna was mounted on the variable-height antenna tower, with its boresight facing the EUT throughout the test.
- c. The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- g. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- h. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Scan from 1GHz to 10th harmonic of the highest frequency or 40 GHz, whichever is lower.
2. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
3. For the frequency above 18GHz, testing had been executed under all test modes, only the worst-case test curve is displayed in the report.
4. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst-case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.

Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5631.875	41.49	34.53	5.80	37.00	44.82	74.00	-29.18	Peak
11906.070	36.16	38.18	9.87	38.32	45.89	74.00	-28.11	Peak
17793.090	34.25	42.90	13.75	40.64	50.26	74.00	-23.74	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6195.508	30.15	35.47	6.37	36.78	35.21	54.00	-18.79	Average
11633.930	26.84	38.29	9.66	37.31	37.48	54.00	-16.52	Average
17844.590	24.75	42.99	13.79	40.57	40.96	54.00	-13.04	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6159.797	39.41	35.42	6.34	36.83	44.34	74.00	-29.66	Peak
10885.670	35.15	38.28	9.26	36.84	45.85	74.00	-28.15	Peak
17793.090	33.63	42.90	13.75	40.64	49.64	74.00	-24.36	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5680.921	31.42	34.50	5.83	37.01	34.74	54.00	-19.26	Average
11871.710	27.15	38.18	9.84	38.19	36.98	54.00	-17.02	Average
17793.090	24.82	42.90	13.75	40.64	40.83	54.00	-13.17	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5535.047	40.58	34.52	5.74	36.99	43.85	74.00	-30.15	Peak
11769.210	35.52	38.21	9.76	37.82	45.67	74.00	-28.33	Peak
17136.920	33.51	41.74	13.35	39.53	49.07	74.00	-24.93	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5567.137	31.37	34.52	5.76	36.99	34.66	54.00	-19.34	Average
12761.300	27.29	39.01	10.52	39.54	37.28	54.00	-16.72	Average
17537.800	24.58	42.28	13.60	39.98	40.48	54.00	-13.52	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
4859.975	41.72	33.66	5.27	36.80	43.85	74.00	-30.15	Peak
10885.670	34.12	38.28	9.26	36.84	44.82	74.00	-29.18	Peak
15577.900	34.46	43.29	12.37	40.81	49.31	74.00	-24.69	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5697.365	31.67	34.48	5.84	37.01	34.98	54.00	-19.02	Average
12184.580	27.10	38.59	10.09	38.66	37.12	54.00	-16.88	Average
17537.800	24.41	42.28	13.60	39.98	40.31	54.00	-13.69	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
4888.151	41.73	33.66	5.29	36.81	43.87	74.00	-30.13	Peak
10575.540	34.95	37.93	9.14	37.68	44.34	74.00	-29.66	Peak
17844.590	33.61	42.99	13.79	40.57	49.82	74.00	-24.18	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5680.921	31.36	34.50	5.83	37.01	34.68	54.00	-19.32	Average
11633.930	26.24	38.29	9.66	37.31	36.88	54.00	-17.12	Average
17793.090	24.73	42.90	13.75	40.64	40.74	54.00	-13.26	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Antenna Polarity :VERTICAL
EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6249.464	39.51	35.50	6.43	36.70	44.74	74.00	-29.26	Peak
12255.220	35.73	38.62	10.14	38.65	45.84	74.00	-28.16	Peak
17844.590	33.14	42.99	13.79	40.57	49.35	74.00	-24.65	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5046.062	32.04	33.69	5.41	36.85	34.29	54.00	-19.71	Average
7263.015	29.13	36.30	7.38	37.48	35.33	54.00	-18.67	Average
17793.090	25.09	42.90	13.75	40.64	41.10	54.00	-12.90	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6285.695	37.93	35.53	6.46	36.65	43.27	74.00	-30.73	Peak
12149.420	35.77	38.44	10.06	38.67	45.60	74.00	-28.40	Peak
17793.090	32.99	42.90	13.75	40.64	49.00	74.00	-25.00	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6340.436	30.97	35.51	6.52	37.58	35.42	54.00	-18.58	Average
11667.600	26.23	38.27	9.68	37.44	36.74	54.00	-17.26	Average
17793.090	24.11	42.90	13.75	40.64	40.12	54.00	-13.88	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL
EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6142.019	38.16	35.39	6.32	36.86	43.01	74.00	-30.99	Peak
11633.930	34.76	38.29	9.66	37.31	45.40	74.00	-28.60	Peak
17793.090	32.78	42.90	13.75	40.64	48.79	74.00	-25.21	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6855.063	29.90	35.96	7.01	37.89	34.98	54.00	-19.02	Average
12835.290	26.96	39.05	10.57	39.52	37.06	54.00	-16.94	Average
17844.590	24.74	42.99	13.79	40.57	40.95	54.00	-13.05	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL
EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6545.263	39.64	35.46	6.72	37.30	44.52	74.00	-29.48	Peak
11368.000	35.58	38.27	9.44	37.30	45.99	74.00	-28.01	Peak
17537.800	33.87	42.28	13.60	39.98	49.77	74.00	-24.23	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6159.797	30.20	35.42	6.34	36.83	35.13	54.00	-18.87	Average
10885.670	25.87	38.28	9.26	36.84	36.57	54.00	-17.43	Average
17537.800	24.90	42.28	13.60	39.98	40.80	54.00	-13.20	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:middle




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6285.695	38.47	35.53	6.46	36.65	43.81	74.00	-30.19	Peak
11467.000	36.19	38.28	9.52	37.68	46.31	74.00	-27.69	Peak
17136.920	33.69	41.74	13.35	39.53	49.25	74.00	-24.75	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:middle




Antenna Polarity :VERTICAL
EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
7076.516	29.40	36.07	7.22	37.64	35.05	54.00	-18.95	Average
12798.240	27.34	39.02	10.54	39.53	37.37	54.00	-16.63	Average
17537.800	24.41	42.28	13.60	39.98	40.31	54.00	-13.69	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL
EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6267.553	38.45	35.51	6.45	36.68	43.73	74.00	-30.27	Peak
11433.910	36.36	38.27	9.49	38.55	45.57	74.00	-28.43	Peak
17793.090	33.41	42.90	13.75	40.64	49.42	74.00	-24.58	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5631.875	31.65	34.53	5.80	37.00	34.98	54.00	-19.02	Average
11701.380	26.30	38.25	9.71	37.56	36.70	54.00	-17.30	Average
17136.920	24.71	41.74	13.35	39.53	40.27	54.00	-13.73	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Antenna Polarity :VERTICAL
EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
6815.551	38.34	35.91	6.98	36.94	44.29	74.00	-29.71	Peak
11769.210	35.73	38.21	9.76	37.82	45.88	74.00	-28.12	Peak
15221.820	36.44	43.17	12.16	41.84	49.93	74.00	-24.07	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Antenna Polarity :VERTICAL
EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
6815.551	29.35	35.91	6.98	36.94	35.30	54.00	-18.70	Average
10885.670	26.45	38.28	9.26	36.84	37.15	54.00	-16.85	Average
14916.940	26.68	42.65	11.97	40.99	40.31	54.00	-13.69	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6285.695	39.13	35.53	6.46	36.65	44.47	74.00	-29.53	Peak
10885.670	35.14	38.28	9.26	36.84	45.84	74.00	-28.16	Peak
17793.090	33.66	42.90	13.75	40.64	49.67	74.00	-24.33	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6815.551	29.46	35.91	6.98	36.94	35.41	54.00	-18.59	Average
12361.950	26.99	38.66	10.22	38.62	37.25	54.00	-16.75	Average
17844.590	24.66	42.99	13.79	40.57	40.87	54.00	-13.13	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
4888.151	41.01	33.66	5.29	36.81	43.15	74.00	-30.85	Peak
7432.914	37.67	36.31	7.53	37.34	44.17	74.00	-29.83	Peak
16221.190	34.75	42.14	12.75	40.54	49.10	74.00	-24.90	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6795.879	29.30	35.88	6.96	36.96	35.18	54.00	-18.82	Average
12798.240	27.08	39.02	10.54	39.53	37.11	54.00	-16.89	Average
17537.800	24.48	42.28	13.60	39.98	40.38	54.00	-13.62	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6285.695	37.89	35.53	6.46	36.65	43.23	74.00	-30.77	Peak
12184.580	36.00	38.59	10.09	38.66	46.02	74.00	-27.98	Peak
17793.090	33.34	42.90	13.75	40.64	49.35	74.00	-24.65	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5648.176	31.00	34.53	5.81	37.00	34.34	54.00	-19.66	Average
11368.000	25.78	38.27	9.44	37.30	36.19	54.00	-17.81	Average
17896.250	23.87	43.04	13.82	40.51	40.22	54.00	-13.78	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5551.069	41.00	34.52	5.75	36.99	44.28	74.00	-29.72	Peak
11667.600	35.46	38.27	9.68	37.44	45.97	74.00	-28.03	Peak
17793.090	33.21	42.90	13.75	40.64	49.22	74.00	-24.78	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Antenna Polarity :VERTICAL
EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6340.436	30.77	35.51	6.52	37.58	35.22	54.00	-18.78	Average
12219.850	26.89	38.60	10.11	38.65	36.95	54.00	-17.05	Average
17537.800	24.51	42.28	13.60	39.98	40.41	54.00	-13.59	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5016.977	41.12	33.69	5.39	36.84	43.36	74.00	-30.64	Peak
9923.991	35.05	37.62	8.88	37.41	44.14	74.00	-29.86	Peak
14916.940	35.50	42.65	11.97	40.99	49.13	74.00	-24.87	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5664.525	31.37	34.51	5.82	37.01	34.69	54.00	-19.31	Average
11633.930	26.00	38.29	9.66	37.31	36.64	54.00	-17.36	Average
17844.590	24.81	42.99	13.79	40.57	41.02	54.00	-12.98	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity :VERTICAL
EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5031.499	42.11	33.69	5.40	36.85	44.35	74.00	-29.65	Peak
11368.000	34.72	38.27	9.44	37.30	45.13	74.00	-28.87	Peak
17793.090	33.10	42.90	13.75	40.64	49.11	74.00	-24.89	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5503.143	31.55	34.52	5.72	36.98	34.81	54.00	-19.19	Average
11467.000	27.08	38.28	9.52	37.68	37.20	54.00	-16.80	Average
17844.590	24.61	42.99	13.79	40.57	40.82	54.00	-13.18	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL
EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
6142.019	39.62	35.39	6.32	36.86	44.47	74.00	-29.53	Peak
12219.850	35.99	38.60	10.11	38.65	46.05	74.00	-27.95	Peak
15622.990	35.04	43.19	12.40	40.81	49.82	74.00	-24.18	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6358.789	30.84	35.50	6.54	37.55	35.33	54.00	-18.67	Average
12798.240	27.37	39.02	10.54	39.53	37.40	54.00	-16.60	Average
17844.590	24.70	42.99	13.79	40.57	40.91	54.00	-13.09	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6303.890	39.49	35.54	6.48	37.63	43.88	74.00	-30.12	Peak
11566.870	35.30	38.33	9.60	38.06	45.17	74.00	-28.83	Peak
15577.900	35.05	43.29	12.37	40.81	49.90	74.00	-24.10	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6545.263	30.00	35.46	6.72	37.30	34.88	54.00	-19.12	Average
11633.930	26.06	38.29	9.66	37.31	36.70	54.00	-17.30	Average
17793.090	24.82	42.90	13.75	40.64	40.83	54.00	-13.17	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5648.176	39.70	34.53	5.81	37.00	43.04	74.00	-30.96	Peak
10885.670	35.49	38.28	9.26	36.84	46.19	74.00	-27.81	Peak
17286.170	33.78	42.05	13.44	40.32	48.95	74.00	-25.05	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:middle




Antenna Polarity :HORIZONTAL
EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6815.551	29.47	35.91	6.98	36.94	35.42	54.00	-18.58	Average
12290.700	26.66	38.66	10.17	38.64	36.85	54.00	-17.15	Average
17844.590	24.33	42.99	13.79	40.57	40.54	54.00	-13.46	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:middle




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
6795.879	38.23	35.88	6.96	36.96	44.11	74.00	-29.89	Peak
10885.670	35.45	38.28	9.26	36.84	46.15	74.00	-27.85	Peak
17793.090	33.04	42.90	13.75	40.64	49.05	74.00	-24.95	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:middle




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
7432.914	28.83	36.31	7.53	37.34	35.33	54.00	-18.67	Average
12798.240	26.88	39.02	10.54	39.53	36.91	54.00	-17.09	Average
17844.590	24.67	42.99	13.79	40.57	40.88	54.00	-13.12	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6249.464	38.80	35.50	6.43	36.70	44.03	74.00	-29.97	Peak
14450.130	35.53	41.35	11.67	41.78	46.77	74.00	-27.23	Peak
17844.590	33.24	42.99	13.79	40.57	49.45	74.00	-24.55	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6340.436	30.98	35.51	6.52	37.58	35.43	54.00	-18.57	Average
12835.290	27.06	39.05	10.57	39.52	37.16	54.00	-16.84	Average
17537.800	24.31	42.28	13.60	39.98	40.21	54.00	-13.79	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
4874.043	41.46	33.66	5.28	36.81	43.59	74.00	-30.41	Peak
10885.670	35.18	38.28	9.26	36.84	45.88	74.00	-28.12	Peak
17537.800	32.62	42.28	13.60	39.98	48.52	74.00	-25.48	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Antenna Polarity :VERTICAL
EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6564.209	30.37	35.47	6.74	37.27	35.31	54.00	-18.69	Average
10885.670	25.71	38.28	9.26	36.84	36.41	54.00	-17.59	Average
14916.940	26.71	42.65	11.97	40.99	40.34	54.00	-13.66	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
29887.020	52.53	40.41	4.00	54.44	42.50	74.00	-31.50	Peak
37018.740	51.86	41.25	4.48	55.50	42.09	74.00	-31.91	Peak
39808.820	53.80	43.68	4.93	55.61	46.80	74.00	-27.20	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



Antenna Polarity :VERTICAL

EUT/Project :3298HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
30078.550	52.27	40.48	4.00	54.40	42.35	74.00	-31.65	Peak
33395.350	54.20	41.05	3.77	56.47	42.55	74.00	-31.45	Peak
39840.620	53.31	43.68	4.94	55.55	46.38	74.00	-27.62	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR251200329803

Page: 84 of 84

7 Test Setup Photo

Refer to Appendix - Test Setup Photo for SHCR2512003298HS

8 EUT Constructional Details (EUT Photos)

Refer to Appendix_Photographs of EUT Constructional Details for SHCR2512003298HS

- End of the Report -