



# RF Exposure Evaluation Report

**Application No.:** DNT2603090414R00733-01050

**Applicant:** Xiamen Zoomcare Technology Co.,Ltd

**Address of Applicant:** Room 307, Jinfeng Building, No. 1, Linhou West Rd, Huli Dist,Xiamen

**EUT Description:** Desk Lamp

**Model No.:** DL003

**Additional Model(s):** DL004,DL005,DL006,DL007,DL008,DL009,DL010,DL011,DL012,DL013,DL014,DL015,DL016,DL017,DL018,DL019,DL020,DL021,DL022,DL023,DL024,DL025,DL030,DL031,DL032,DL033,DL034,DL035,DL040,DL041,DL042,DL043,DL044,DL045,DL050,DL051,DL052,DL053,DL054,DL055

**FCC ID:** 2BA3B-DL003

**Power supply** DC 5V From Adapter Input AC 120V/60Hz

**Trade Mark:** /

47 CFR Part 2.1091

**Standards:** FCC KDB 447498 D01 v06

**Date of Receipt:** 2026/03/09

**Date of Test:** 2026/03/09 to 2026/03/18

**Date of Issue:** 2026/03/19

**Test Result:** PASS

**Prepared By:** Carl. Lin (Testing Engineer)

**Reviewed By:** Wayne. Lin (Project Engineer)

**Approved By:** Heise Shen (Manager)



Note: If there is any objection to the results in this report, please submit a written inquiry to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp, and is issued by the company in accordance with the requirements of the "Conditions of Issuance of Test Reports" printed in the attached page. Unless otherwise stated, the results presented in this report only apply to the samples tested this time. Partial reproduction of this report is not allowed unless approved by the company in writing.

**Dongguan DN Testing Co., Ltd.**

Add: No. 1, West Fourth Street, Xingfa South Road, Wusha Community, Chang 'an Town, Dongguan City, Guangdong P.R.China

Web: [www.dn-testing.com](http://www.dn-testing.com)

Tel: +86-769-88087383

E-mail: [service@dn-testing.com](mailto:service@dn-testing.com)



Report Revise Record

| Report Version | Revise Time | Issued Date    | Valid Version | Notes           |
|----------------|-------------|----------------|---------------|-----------------|
| V1.0           | /           | March 19, 2026 | Valid         | Original Report |



Contents

1 GENERAL INFORMATION .....4

1.1 TEST LOCATION .....4

1.2 GENERAL DESCRIPTION OF EUT .....4

2 RF EXPOSURE EVALUATION .....5

2.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....5

2.1.1 Limits .....5

2.1.2 Test Procedure .....6

2.1.3 EUT RF Exposure Evaluation .....6



# 1 General Information

## 1.1 Test Location

|                |                                                                                                              |
|----------------|--------------------------------------------------------------------------------------------------------------|
| Company:       | Dongguan DN Testing Co., Ltd                                                                                 |
| Address:       | No. 1, West Fourth Street, South Xinfu Road, Wusha Liwu, Chang ' an Town, Dongguan City, Guangdong P.R.China |
| Test engineer: | Gali Lin                                                                                                     |

## 1.2 General Description of EUT

|                          |                                                                                                                                                                                                                                                 |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Manufacturer:            | Xiamen Zoomcare Technology Co.,Ltd                                                                                                                                                                                                              |
| Address of Manufacturer: | Room 307, Jinfeng Building, No. 1, Linhou West Rd, Huli Dist,Xiamen                                                                                                                                                                             |
| EUT Description:         | Desk Lamp                                                                                                                                                                                                                                       |
| Model No.:               | DL003                                                                                                                                                                                                                                           |
| Additional Model(s):     | DL004,DL005,DL006,DL007,DL008,DL009,DL010,DL011,DL012,DL013,DL014,DL015,DL016,DL017,DL018,DL019,DL020,DL021,DL022,DL023,DL024,DL025,DL030,DL031,DL032,DL033,DL034,DL035,DL040,DL041,DL042,DL043,DL044,DL045,DL050,DL051,DL052,DL053,DL054,DL055 |
| Power Supply:            | DC 5V From Adapter Input AC 120V/60Hz                                                                                                                                                                                                           |
| Trade Mark:              | /                                                                                                                                                                                                                                               |
| Hardware Version:        | V1.0                                                                                                                                                                                                                                            |
| Software Version:        | V1.0                                                                                                                                                                                                                                            |
| Chip Type:               | T1-CHL                                                                                                                                                                                                                                          |
| Serial number            | PR2603090414R00733                                                                                                                                                                                                                              |
| Sample Type:             | <input type="checkbox"/> Portable Device, <input type="checkbox"/> Module, <input checked="" type="checkbox"/> Mobile Device                                                                                                                    |
| Antenna Type:            | <input type="checkbox"/> External, <input checked="" type="checkbox"/> Integrated                                                                                                                                                               |
| Antenna Ports:           | <input checked="" type="checkbox"/> Ant 1, <input type="checkbox"/> Ant 2, <input type="checkbox"/> Ant 3                                                                                                                                       |
| Antenna Gain:            | <input checked="" type="checkbox"/> Provided by applicant<br>-0.23dBi                                                                                                                                                                           |

**Note:**

\*Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, DNT is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.

\*All models are just color differences, motherboard, PCB circuit board, chip, electronic components, appearance is all the same.



## 2 RF Exposure Evaluation

### 2.1 RF Exposure Compliance Requirement

#### 2.1.1 Limits

| Frequency range (MHz)                                                                                                                                                                                                                                                                           | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| <b>(A) Limits for Occupational/Controlled Exposures</b>                                                                                                                                                                                                                                         |                               |                               |                                     |                          |
| 0.3-3.0                                                                                                                                                                                                                                                                                         | 614                           | 1.63                          | *(100)                              | 6                        |
| 3.0-30                                                                                                                                                                                                                                                                                          | 1842/f                        | 4.89/f                        | *(900/f <sup>2</sup> )              | 6                        |
| 30-300                                                                                                                                                                                                                                                                                          | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300-1500                                                                                                                                                                                                                                                                                        | /                             | /                             | f/300                               | 6                        |
| 1500-100,000                                                                                                                                                                                                                                                                                    | /                             | /                             | 5                                   | 6                        |
| <b>(B) Limits for General Population/Uncontrolled Exposure</b>                                                                                                                                                                                                                                  |                               |                               |                                     |                          |
| 0.3-1.34                                                                                                                                                                                                                                                                                        | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34-30                                                                                                                                                                                                                                                                                         | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30-300                                                                                                                                                                                                                                                                                          | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1500                                                                                                                                                                                                                                                                                        | /                             | /                             | f/1500                              | 30                       |
| 1500-100,000                                                                                                                                                                                                                                                                                    | /                             | /                             | 1.0                                 | 30                       |
| F=frequency in MHz<br>*=Plane-wave equivalent power density<br>RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m). |                               |                               |                                     |                          |

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

**2.1.2 Test Procedure**

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually

**2.1.3 EUT RF Exposure Evaluation**

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.0 / 2.0 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

This confirmed that the device comply with MPE limit.

| Test Mode | Antenna | Freq(MHz) | Power [dBm] |
|-----------|---------|-----------|-------------|
| 11b       | Ant1    | 2412      | 13.52       |
|           |         | 2437      | 12.87       |
|           |         | 2462      | 13.19       |
| 11g       | Ant1    | 2412      | 12.43       |
|           |         | 2437      | 12.38       |
|           |         | 2462      | 12.47       |
| 11n20     | Ant1    | 2412      | 11.39       |
|           |         | 2437      | 11.12       |
|           |         | 2462      | 11.21       |

| The Worst Mode | Antenna | output power (dBm) | Target power (dBm) | MAX Target power (dBm) | Antenna gain |          | Power Density (S) (mW /cm²) | Limited of Power Density (S) (mW /cm²) | Test Result | Distance (cm) |
|----------------|---------|--------------------|--------------------|------------------------|--------------|----------|-----------------------------|----------------------------------------|-------------|---------------|
|                |         |                    |                    |                        | (dBi)        | (Linear) |                             |                                        |             |               |
| 2.4G Band      |         |                    |                    |                        |              |          |                             |                                        |             |               |
| 11b            | Ant1    | 13.52              | 13±1               | 14                     | -0.23        | 0.95     | 0.00474                     | 1                                      | Complies    | 20            |

The End Report