

1 Cover Page

RF Exposure Evaluation Report

Application No.:	KSCR2605001145AT
FCC ID:	2BA3NS70
Applicant:	Shandong New Beiyang Information Technology Co., Ltd.
Address of Applicant:	169 HUOJU ROAD, HDZ, WEIHAI, SHANDONG, CHINA
Manufacturer:	Shandong New Beiyang Information Technology Co., Ltd.
Address of Manufacturer:	169 HUOJU ROAD, HDZ, WEIHAI, SHANDONG, CHINA
Factory:	Shandong New Beiyang Information Technology Co., Ltd
Address of Factory:	No.6, Chuhe North Road, Huoju Hi-Tech Zone, Weihai Shandong 264210 China
Equipment Under Test (EUT):	
EUT Name:	Receipt Printer
Model No.:	BTP-S70,BTP-S70A,BTP-S70B,BTP-S70C,BTP-S70D,BTP-S70E,BTP-S70F,BTP-S71,BTP-S72,BTP-S73,BTP-S74,BTP-S75,BTP-S76,BTP-S77,BTP-S78,BTP-S79,BTP-S70II,BTP-S70III,BTP-S70IV,BTP-S70V, BTP-S70VII,BTP-S70VIII,BTP-S70VIII,BY-S100,BY-S101,BY-S102,BY-S103,BY-S104,BY-S105,BY-S106,BY-S107,BY-S108,BY-S109,BY-S110,BY-S111,BY-S112,BY-S113,BY-S114,BY-S115,BY-S116,BY-S117,BY-S118,BY-S119
Standard(s) :	FCC Rules 47 CFR §2.1091 KDB447498 D04 Interim General RF Exposure Guidance v01
Date of Receipt:	2026-05-20
Date of Test:	2026-06-03 to 2026-07-01
Date of Issue:	2026-07-01
Test Result:	Pass*

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record			
Version	Description	Date	Remark
00	Original	2026-07-01	/

Authorized for issue by:				
Prepared By		Maker Qi		
		Maker_Qi/Project Engineer		
Approved By		Terry Hou		
		Terry Hou /Reviewer		



2 Contents

	Page
1 Cover Page	1
2 Contents	3
3 General Information	4
3.1 General Description of E.U.T.	4
3.2 Details of E.U.T.	4
3.3 Test Location	6
3.4 Test Facility	6
4 RF Exposure Test Exemptions	7
4.1 FCC RF Exposure Test Exemptions for single RF sources	7
5 Measurement and Calculation	11
5.1 Maximum transmit power	11
5.2 RF Exposure Calculation	13

3 General Information

3.1 General Description of E.U.T.

Power supply:	AC/DC Adapter 1: Model: DA-60H24 Input: 110~240V~, 50-60Hz, 2A Max Output: 24V/2.5A 60W AC/DC Adapter 2: Model: SW-0692 Input: 100~240V~, 50-60Hz, 2A Output: 24V/2.5A 60W
---------------	---

3.2 Details of E.U.T.

BLE

Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	PCB Antenna
Antenna Gain:	0.56dBi (Provided by the manufacturer)

BT

Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK, pi/4DQPSK, 8DPSK
Number of Channels:	79
Channel Spacing:	1MHz
Spectrum Spread Technology:	Frequency Hopping Spread Spectrum(FHSS)
Antenna Type:	PCB Antenna
Antenna Gain:	0.56dBi (Provided by the manufacturer)

**2.4GHz Wi-Fi(Contains WiFi module FCC ID:2AHMR-BW16)**

Operation Frequency:	802.11b/g/n(HT20):2412MHz to 2462MHz; 802.11n(HT40):2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (DBPSK, DQPSK, CCK); 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Number of Channels:	802.11b/g/n(HT20):11;802.11n(HT40):7
Channel Spacing:	5MHz
Antenna Type:	PCB Antenna
Antenna Gain:	2dBi (Provided by the manufacturer)

5GHz Wi-Fi(Contains WiFi module FCC ID:2AHMR-BW16)

Operation Frequency / Number of channels (20MHz):	U-NII-1: 5180-5240MHz (4 Channels); U-NII-3: 5745-5825MHz(5 Channels)
Operation Frequency / Number of channels(40MHz):	U-NII-1: 5190-5230MHz (2 Channels); U-NII-3: 5755-5795MHz (2 Channels)
Modulation Type:	802.11a: OFDM (BPSK, QPSK, 16QAM, 64QAM); 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM);
Antenna Type:	PCB Antenna
Antenna Gain:	2dBi (Provided by the manufacturer)
DFS Function:	Not Support
TPC Function:	Not Support
Channel Spacing:	802.11a/n 20: 20MHz; 802.11n 40: 40MHz

3.3 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

Note:

1. SGS is not responsible for wrong test results due to incorrect information (e.g., max. internal working frequency, antenna gain, cable loss, etc) is provided by the applicant. (If applicable).
2. SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (If applicable).
3. Sample source: sent by customer.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 2541.01)**

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA).

- **FCC (Designation Number: CN1172)**

Compliance Certification Services (Kunshan) Inc. has been recognized as an accredited testing laboratory.

- **ISED (CAB Identifier: CN0072)**

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

Company Number: 2324E

- **VCCI (Member No: 1938)**

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-20134, R-11600, C-11707, T-11499, G-10216 respectively.



4 RF Exposure Test Exemptions

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds.

4.1 FCC RF Exposure Test Exemptions for single RF sources

4.1.1 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of §1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1-mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph §1.1307(b)(3)(ii)(A).

The 1-mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

4.1.2 MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz. The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, **R must be at least $\lambda/2\pi$** , where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table B.1—Thresholds For Single RF Sources Subject to Routine Environmental Evaluation

RF Source Frequency			Minimum Distance			Threshold ERP
f_L MHz		f_H MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W
0.3	–	1.34	159 m	–	35.6 m	1,920 R ²
1.34	–	30	35.6 m	–	1.6 m	3,450 R ² /f ²
30	–	300	1.6 m	–	159 mm	3.83 R ²
300	–	1,500	159 mm	–	31.8 mm	0.0128 R ² f
1,500	–	100,000	31.8 mm	–	0.5 mm	19.2R ²
Subscripts L and H are low and high; λ is wavelength. R: Separation distance between the antenna to person						

The table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

Limit calculation				
Frequency range	Frequency(MHz)	$\lambda/2\pi$ (m)	R(m)	Threshold ERP(W)
1500~100000MHz	24115	0.0020	0.0500	0.048

4.1.3 SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of $\lambda/4$.

As for devices with antennas of length greater than $\lambda/4$ where the gain is not well defined, but always less than that of a half-wave dipole (length $\lambda/2$), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known. The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

The SAR-based exemption formula of §1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from **0.5cm to 40cm** and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

Limit calculation				
Frequency range(GHz)	Frequency(GHz)	X	d(cm)	Pth (mW)
1.5~6	2.462	1.903	20	3060.000
1.5~6	2.48	1.905	20	3060.000

4.1.4 RF Exposure Test Exemptions for Simultaneous Transmission

The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (Evaluated k term) shall be used to determine exemption for simultaneous transmission. In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure \ Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for P_{th} , including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.



c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source *i* at a distance between 0.5 cm and 40 cm (inclusive).

P_{th,i} = the exemption threshold power (P_{th}) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source *i*.

ERP_j = the ERP of fixed, mobile, or portable RF source *j*.

ERP_{th,j} = exemption threshold ERP for fixed, mobile, or portable RF source *j*, at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

Evaluated_k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source *k* either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit_k = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source *k*, as applicable from § 1.1310 of this chapter.

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report KSCR260500114501; KSCR260500114502

BLE

Test Mode	Test Channel	ANT1 Power[dBm]	ANT1 Power[mW]
1MHz	2402	6.66	4.63
	2440	7.67	5.85
	2480	8.01	6.32

BT

Test Mode	Test Channel	ANT1 Power[dBm]	ANT1 Power[mW]
GFSK	2402	6.87	4.86
	2441	7.90	6.17
	2480	8.77	7.53
Pi/4DQPSK	2402	6.96	4.97
	2441	8.03	6.35
	2480	8.89	7.74
8DPSK	2402	6.98	4.99
	2441	8.00	6.31
	2480	8.88	7.73

2.4GHz WiFi(Contains FCC ID:2AHMR-BW16)

Test Mode	Test Channel	ANT1 Power[dBm]	ANT1 Power[mW]
802.11b	2412	13.783	23.89
	2437	14.186	26.22
	2462	14.171	26.13
802.11g	2412	12.408	17.41
	2437	12.285	16.92
	2462	12.419	17.45
802.11n (HT20)	2412	11.34	13.61
	2437	11.801	15.14
	2462	11.907	15.51
802.11n (HT40)	2422	10.089	10.21
	2437	10.133	10.31
	2452	10.14	10.33

**5GHz WiFi(Contains FCC ID:2AHMR-BW16)**

Test Mode	Test Channel	ANT1 Power[dBm]	ANT1 Power[mW]
802.11a	5180	12.726	18.73
	5200	12.651	18.41
	5240	12.797	19.04
	5745	12.375	17.28
	5785	12.669	18.49
	5825	12.162	16.45
802.11n (HT20)	5180	12.42	17.46
	5200	12.093	16.19
	5240	12.452	17.59
	5745	12.011	15.89
	5785	11.997	15.84
	5825	12.105	16.24
802.11n (HT40)	5190	10.591	11.46
	5230	10.7	11.75
	5755	9.981	9.96
	5795	9.983	9.96

5.2 RF Exposure Calculation

	Evaluation method	Separation distance between the antenna to person (R)
☐	Blanket 1 mW Blanket Exemption	Regardless of separation distance
☐	MPE-based Exemption(ERP)	$R \geq (\lambda/2\pi)$
☒	SAR-based Exemption(P_{th})	$0.5\text{cm} < R < 40\text{cm}$

Band	Frequency	Max power (dBm)	Ant Gain (dBi)	EIRP (dBm)	Max power (mW)	Limit (mW)	Distance R (cm)
BLE	2480	8.01	0.56	8.57	7.19	3060	20
BT	2480	8.89	0.56	9.45	8.81	3060	20
WLAN 2.4GHz	2437	14.186	2	16.19	41.59	3060	20
WLAN 5GHz	5240	12.797	2	14.80	30.20	3060	20

For multiple RF sources:

The BLE & 2.4GHz WiFi can transmit simultaneously, but the maximum rate of MPE is $8.81/3060 + 41.59/3060 = 0.02 \leq 1$. So the MPE of collocated transmitter is compliant.

--End of the Report--