



시험 성적서

TEST REPORT

페이지(page) : (1) / 총(Total) (31)

성적서 번호 Report No.		ICRT-TR-E261495-0A	
신청자 Client	기관명 Name	invant Inc.	
	주 소 Address	A-401, Giheung ICT Valley, 58-1 Giheung-ro, Giheung-gu, Yongin-si, Gyeonggi-do, 16976, Republic of Korea	
시험대상품목 Sample description		Squaregolf Omni	
모델명 Type description		SQGOE300A	
정 격 Ratings		DC 14.8 V	
시험장소 Place of test		☒ 고정시험실(Permanent Testing Lab) ☐ 현장시험(On Site Testing) 주소지(Address): 112, 113 Hwanggeum 3-ro 7beon-gil, Hagun-ri, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea	
시험기간 Date of test		11. Mar. 2026 ~ 19. May. 2026	
시험방법/항목 Test Method/Item		FCC Part 15 Subpart C & IC RSS-Gen & RSS-247	
시험결과 Test Results		Refer to 3. Test Summary	
확 인 Affirmation	작성자 Tested by	기술책임자 Technical Manager	
	성명 Name Seong-Hun, Jeong	성명 Name Yong-Min, Won	

2026. 05. 19

주식회사 아이씨알 대표이사

The head of INTERNATIONAL CERTIFICATION REGISTRAR

- ☐ 위 성적서는 고객이 제공한 시료에 대한 시험결과입니다.
- ☐ The above test report is certified that the above mentioned products have been tested for the sample.
- ☐ 위 성적서는 KS Q ISO/IEC 17025 및 한국인정기구(KOLAS)인정과 관련이 없습니다.
- ☐ The above test report is not related to accreditation by KS Q ISO/IEC 17025 and Korea Laboratory Accreditation scheme.
- ☐ 위 성적서는 주식회사 아이씨알의 승인 없이는 일부 복제에 대해 금지됩니다.
- ☐ The test report is prohibited for some reproduction without the approval of the ICR.

본 성적서의 진위 확인은 G4B 혹은 ICR 홈페이지에서 가능합니다.

The authenticity of the test report can be checked on the G4B or ICR website.

경기도 김포시 양촌읍 황금3로7번길 112 / Tel: 02-6351-9001 ~ 6

112, Hwanggeum3-ro 7beon-gil, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea / Tel: 02-6351-9001 ~ 6



Contents

1. Applicant & Manufacturer & Test Laboratory Information	<u>4</u>
2. Equipment under Test(EUT) Information	<u>5</u>
3. Test Summary	<u>6</u>
4. Test Result	<u>8</u>
5. Used equipment	<u>31</u>



Revision History

Issued Report No.	Issued Date	Revisions	Effect Section
ICRT-TR-E261495-0A	2026. 05. 19	Initial Issue	All



1. Applicant & Manufacturer & Test Laboratory Information

1.1 Applicant information

Applicant	invant Inc.
Address	A-401, Giheung ICT Valley, 58-1 Giheung-ro, Giheung-gu, Yongin-si, Gyeonggi-do, 16976, Republic of Korea

1.2 Manufacturer Information

Applicant	invant Inc.
Address	A-401, Giheung ICT Valley, 58-1 Giheung-ro, Giheung-gu, Yongin-si, Gyeonggi-do, 16976, Republic of Korea

1.3 Test Laboratory Information

Laboratory	ICR Co., Ltd.
Address	112, Hwanggeum 3-ro 7beon-gil, Hagun-ri, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea
Telephone No.	+82-2-6351-9002
Fax No.	+82-2-6351-9007
KOLAS No.	KT652
KC & FCC	KR0165

1.4 Measurement Uncertainty

Parameter	Uncertainty	Limit
Occupied Channel Bandwidth	0.14 %	±5 %
RF output power, conducted	0.85 dB	±1.5 dB
Power Spectral Density, conducted	1.44 dB	±3 dB
Unwanted Emissions, conducted	1.35 dB	±3 dB
Supply voltages	0.02 %	±3 %
Time	0.58 %	±5 %
All emissions, radiated (Under the 30 MHz)	2.10 dB	±6 dB
All emissions, radiated (Range 30 MHz ~ 1 GHz)	1.95 dB	±6 dB
All emissions, radiated (Range 1 GHz ~ 18 GHz)	2.47 dB	±6 dB
All emissions, radiated (Range 18 GHz ~ 26.5 GHz)	2.61 dB	±6 dB



2. Equipment under Test(EUT) Information

2.1 General Information

Product Name	Squaregolf Omni
Model Name	SQGOE300A
Additional Model Name	-
FCC ID	2BA47SQGOE300A
ISED Certification Number	30551-SQGOE300A
Power Supply	DC 14.8 V
Serial Number	INVT-SQ-0001

2.2 Additional Information

Equipment Class	DTS-Digital Transmission System	
Device Type	Stand-alone	
Operating Frequency	Bluetooth LE 1M	2 402 MHz ~ 2 480 MHz
RF Output Power	Bluetooth LE 1M	2.76 dBm
Number of Channel	Bluetooth LE 1M	40
Modulation Type	Bluetooth LE 1M	GFSK
Antenna Type	FPCB Antenna	
Antenna Gain	2 dBi	

2.3 Modifications of EUT

- None



3. Test Summary

3.1 Test standards and results

FCC Part 15 Subpart C & IC RSS-Gen & RSS-247				
FCC Part Section	RSS Section	Test items	Applied	Results
§15.247 (a) (2)	RSS-Gen 6.7 & RSS-247 6.3.1(a)	6 dB Bandwidth	■	PASS
N/A	RSS-Gen 6.7	99 % Bandwidth	■	PASS
§15.247 (b) (3)	RSS-Gen 6.12 & RSS-247 6.3.2	Maximum Conducted Output Power	■	PASS
§15.247 (e)	RSS-247 6.3.1(b)	Power Spectral Density	■	PASS
§15.247 (d)	RSS-247 6.6	Conducted Spurious Emission & Band edge	■	PASS
§15.247 (d) & §15.209 & §15.205	RSS-Gen 8.9 & RSS-Gen 8.10 & RSS-247 6.6	Radiated Spurious Emission	■	PASS
§15.207	RSS-Gen 8.8	AC Line Conducted Emission	■	PASS

3.2 Purpose of the test

- To determine whether the equipment under test fulfills the requirements of the standards stated in FCC Part 15 Subpart C Section 15.247 and IC RSS-Gen & RSS-247

3.3 Test Methodology

- Both conducted and radiated testing was performed according to the procedures in ANSI C63.10-2020 and IC RSS-Gen & RSS-247. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

3.4 Configuration of Test System

3.4.1 Radiated emission test

- Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10-2020 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 m Semi Anechoic Chamber.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization



3.5 Antenna requirement

- According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section.

The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.

Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

- According to RSS-Gen Section 6.8, The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

Result: Pass

The transmitter uses an **FPCB antenna** with a **gain of 2 dBi**.

which is installed inside the host device and connected to the RF circuitry through a U.FL connector. The antenna is located inside the host enclosure and is not accessible to end users. No provision is provided for the connection of an external antenna. The antenna can only be replaced by the manufacturer or authorized service personnel. Therefore, the antenna installation complies with the requirements of FCC §15.203.



4. Test Result

4.1. 6 dB Bandwidth & 99 % Bandwidth

4.1.1 Test procedure

ANSI C63.10-2020 Clause 11.8

RSS Gen 6.7

4.1.2 Limit

§15.247 (a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

RSS-247 6.3.1(a)

The minimum 6 dB bandwidth shall be 500 kHz.


4.1.3 Test data

Result : Pass

Mode	Frequency (MHz)	6 dB Bandwidth Measured Value (kHz)	99% Bandwidth Measured Value (kHz)	Limit (kHz)
Bluetooth LE 1M	2 402	668.3	1041.5	at least 500
	2 440	671.7	1031.5	
	2 480	660.8	1049.0	




Low ch_6 dB Bandwidth



Date: 11.MAR.2026 15:10:30


Mid ch_6 dB Bandwidth



Date: 11.MAR.2026 15:11:39




High ch_6 dB Bandwidth



Date: 11.MAR.2026 15:27:48


Low ch_99% Bandwidth



Date: 11.MAR.2026 15:10:33




Mid ch_99% Bandwidth



Date: 11.MAR.2026 15:11:43

High ch_99% Bandwidth



Date: 11.MAR.2026 15:27:51



4.2 Maximum Conducted Output Power

4.2.1 Test procedure

ANSI C63.10-2020 Clause 11.9

RSS-Gen 6.12

4.2.2 Limit

§15.247 (b) (3)

For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

RSS-247 6.3.2

For DTS operating in the band 902-928 MHz, the maximum peak conducted output power shall not exceed 1W, and the e.i.r.p. shall not exceed 4 W.

For DTS operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W, and the e.i.r.p. shall not exceed 4 W, except as provided in section 6.5 a) and b).

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power.


4.2.3 Test data

Result : Pass

Mode	Frequency (MHz)	Measured Value (dBm)	Limit (dBm)
Bluetooth LE 1M	2 402	2.76	30
	2 440	2.05	
	2 480	2.27	




Low ch_Conducted Output Power




Date: 11.MAR.2026 15:10:36

Mid ch_Conducted Output Power



Date: 11.MAR.2026 15:11:46





4.3 Power Spectral Density

4.3.1 Test procedure

ANSI C63.10-2020 Clause 11.10

4.3.2 Limit

§15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

RSS-247 6.3.1(b)

the transmitter power spectral density conducted from the transmitter to the antenna(s) shall not be greater than 8 dBm/3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 6.3.2 The power spectral density shall be determined using the same method as is used to determine the maximum conducted output power.


4.3.3 Test data

Result : Pass

Mode	Frequency (MHz)	Measured Value (dBm/3 kHz)	Limit (dBm/3 kHz)
Bluetooth LE 1M	2 402	-12.99	8
	2 440	-14.65	
	2 480	-12.45	




Low ch_Power Spectral Density




Date: 11.MAR.2026 15:10:42

Mid ch_Power Spectral Density



Date: 11.MAR.2026 15:11:52





4.4 Conducted Spurious Emission & Band Edge

4.4.1 Test procedure

ANSI C63.10-2020 Clause 11.11, 11.12

4.4.2 Limit

§15.247 (d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

RSS-247 6.6



In any 100 kHz bandwidth outside the frequency band in which the spread spectrum device, digitally modulated device, or hybrid system is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power – based on either an RF conducted or a radiated measurement – provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 6.3.2, the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.


4.4.3 Test data


Result : Pass



Mode : Bluetooth LE 1M









4.5 Radiated Spurious Emission

4.5.1 Test procedure

ANSI C63.10-2020 Clause 11.11, 11.12

4.5.2 Limit

§15.247 (d) & RSS Gen-8.9

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

§15.209 Radiated emission limits; general requirements.(a)

Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100 **	3
88–216	150 **	3
216–960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.



§15.205 Restricted bands of operation.(a),(b)

MHz	MHz	MHz	GHz
0.090–0.110	16.42–16.423	399.9–410	4.5–5.15
¹ 0.495–0.505	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225	123–138	2200–2300	14.47–14.5
8.291–8.294	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675	156.7–156.9	2690–2900	22.01–23.12
8.41425–8.41475	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025	240–285	3345.8–3358	36.43–36.5
12.57675–12.57725	322–335.4	3600–4400	(²)
13.36–13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490–0.510 MHz.

² Above 38.6

Except as provided in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements.



4.5.3 Test data

Result : Pass

Mode : Bluetooth LE 1M_Worst Case

- Below 30 MHz

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
0.009	29.36	QP	H	21.0	50.36	128.52	78.16	
0.016	15.63	QP	H	20.5	36.13	123.75	87.62	
0.281	22.24	QP	H	19.8	42.04	98.62	56.58	
0.443	31.24	QP	H	19.9	51.14	94.69	43.55	
0.493	30.27	QP	H	19.9	50.17	73.74	23.57	
0.878	22.37	QP	H	19.9	42.27	68.73	26.46	

- 30 MHz ~ 1 GHz

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
36.301	53.00	QP	V	-17.0	36.00	40.00	4.00	
47.945	46.72	QP	V	-14.5	32.22	43.52	11.30	
59.973	49.32	QP	V	-15.6	33.72	46.02	12.30	
182.387	54.80	QP	V	-18.4	36.4	46.02	9.62	
249.996	52.14	QP	H	-14.4	37.74	46.02	8.28	
313.240	45.27	QP	H	-13.0	32.27	46.02	13.75	



Mode : Bluetooth LE 1M

- 1 GHz Above_Low ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
2375.30	53.80	PK	V	-10.9	42.90	74.00	31.10	Restricted band
	44.45	AVG	V		33.55	54.00	20.45	
4802.90	44.18	PK	H	-2.8	41.38	74.00	32.62	2nd Harmonic
	31.10	AVG	H		28.30	54.00	25.70	
7205.00	46.17	PK	V	1.0	47.17	74.00	26.83	3rd Harmonic
	33.22	AVG	V		34.22	54.00	19.78	
9607.10	46.63	PK	H	3.5	50.13	74.00	23.87	4th Harmonic
	33.68	AVG	H		37.18	54.00	16.82	
26447.30	34.76	PK	V	9.6	44.36	74.00	29.64	
	22.13	AVG	V		31.73	54.00	22.27	

- 1 GHz Above_Mid ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
3167.50	50.37	PK	V	-6.8	43.57	74.00	30.43	
	41.03	AVG	V		34.23	54.00	19.77	
4879.40	50.82	PK	V	-2.4	48.42	74.00	25.58	2nd Harmonic
	39.51	AVG	V		37.11	54.00	16.89	
7320.60	46.68	PK	V	0.9	47.58	74.00	26.42	3rd Harmonic
	33.87	AVG	V		34.77	54.00	19.23	
9760.10	47.18	PK	V	3.7	50.88	74.00	23.12	4th Harmonic
	34.21	AVG	V		37.91	54.00	16.09	
17745.00	52.17	PK	H	13.5	65.67	74.00	8.33	
	39.16	AVG	H		52.66	54.00	1.34	


- 1 GHz Above_High ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
2484.10	47.45	PK	V	-10.2	37.25	74.00	36.75	Restricted band
	33.33	AVG	V		23.13	54.00	30.87	
4959.30	51.10	PK	V	-2.3	48.80	74.00	25.20	2nd Harmonic
	39.23	AVG	V		36.93	54.00	17.07	
7441.30	47.03	PK	H	1.0	48.03	74.00	25.97	3rd Harmonic
	34.15	AVG	H		35.15	54.00	18.85	
9921.60	47.14	PK	H	4.0	51.14	74.00	22.86	4th Harmonic
	34.07	AVG	H		38.07	54.00	15.93	
17755.20	52.32	PK	H	13.5	65.82	74.00	8.18	
	39.05	AVG	H		52.55	54.00	1.45	




4.5.4 Test plot

Mode : Bluetooth LE 1M_Worst Case






Above_1 GHz



Above_18 GHz





4.6 Power Line Conducted Emission

4.6.1 Test procedure

ANSI C63.10-2020 Clause 6.2

4.6.2 Limit

§15.207 (a) & RSS Gen-8.8

Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

*Decreases with the logarithm of the frequency.



4.6.3 Test data

Result : Pass

- L-Line Conducted Emission


Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	note
0.150	35.09	QP	9.8	44.89	66.00	21.11	
	12.58	AVG		22.38	56.00	33.62	
0.191	29.17	QP	9.9	39.07	64.02	24.95	
	10.69	AVG		20.59	54.02	33.43	
0.456	27.55	QP	10.0	37.55	56.77	19.22	
	16.68	AVG		26.68	46.77	20.09	
0.821	22.47	QP	9.9	32.37	56.00	23.63	
	12.24	AVG		22.14	46.00	23.86	
5.579	18.84	QP	9.8	28.64	60.00	31.36	
	9.93	AVG		19.73	50.00	30.27	

- N-Line Conducted Emission

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	note
0.155	34.93	QP	9.9	44.83	65.75	20.92	
	15.00	AVG		24.90	55.75	30.85	
0.182	29.87	QP	10.0	39.87	64.42	24.55	
	12.35	AVG		22.35	54.42	32.07	
0.461	24.80	QP	10.0	34.80	56.68	21.88	
	17.71	AVG		27.71	46.68	18.97	
0.794	17.13	QP	9.9	27.03	56.00	28.97	
	8.74	AVG		18.64	46.00	27.36	
1.280	14.99	QP	9.8	24.79	56.00	31.21	
	7.00	AVG		16.80	46.00	29.20	



4.6.4 Test plot





5. Used equipment

	Description	Model Name	Manufacturer	Serial Number	Next Cal
■	SIGNAL GENERATOR	SMB100A	ROHDE & SCHWARZ	180607	2027-02-24
■	SIGNAL ANALYZER	FSV40	ROHDE & SCHWARZ	101455	2027-02-23
■	DC BLOCK	PDCB-00012650-SMSF-4	PSATEK	-	2027-02-26
■	DC POWER SUPPLY	E3632A	AGILENT	MY51250107	2027-02-24
■	LOOP ANTENNA	HFH2-Z2	ROHDE & SCHWARZ	100271	2027-03-04
■	BAND REJECTION FILTER	WT-A1205-R12	WT MICROWAVE	WT171201-6-1	2027-02-24
■	TRILOG BROADBAND ANTENNA	VULB 9162	SCHWARZBECK	120	2026-12-09
■	RF Pre Amplifier	SCU 08	ROHDE & SCHWARZ	100746	2027-03-23
■	EMI Test Receiver	ESR 26	ROHDE & SCHWARZ	101462	2027-03-23
■	HORN ANTENNA	HF907	ROHDE & SCHWARZ	102556	2026-07-28
■	RF Pre Amplifier	SCU 18	ROHDE & SCHWARZ	102342	2027-03-23
■	EMI Test Receiver	ESR 26	ROHDE & SCHWARZ	101461	2027-03-23
■	HORN ANTENNA	DRH0844	RF SPIN	KV2E08A0844	2027-02-27
■	RF PRE AMPLIFIER	ELNA40-50	EXYNOD	631300	2027-02-26
■	LISN	ENV216	ROHDE & SCHWARZ	102193	2026-06-24
■	EMI TEST RECEIVER	ESR3	ROHDE & SCHWARZ	102119	2027-03-23

- END OF REPORT.