CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China
Tel: +86-755- 27521059 Fax: +86-755- 27521011 Http://www.sz-ctc.org.cn

TEST REPORT

Report No. ……:	**CTC20230015E01**
FCC ID……:	**2BA4O-I-MX**
IC……:	**30524-IMX**
Applicant……:	**HEALTH DEVICES CORPORATION DBA DOC JOHNSON ENTERPRISES**
Address……:	11933 VOSE STREET, NORTH HOLLYWOOD CA 91605
Manufacturer……:	**Hong Kong Passkey Industry Co. Limited**
Address……:	2/F, Block #6, Hua Feng Industry Park, Datianyang, Dongfang, SonggangTown, Bao'An District, Shen Zhen, China, 518105
Product Name……:	**FUCK MACHINE**
Trade Mark……:	/
Model/Type reference……:	I-MX-1100-00
Listed Model(s) ……:	/
Standard……:	**FCC CFR Title 47 Part 15 Subpart C Section 15.247** **RSS 247 Issue 2**
Date of receipt of test sample…:	May 2, 2023
Date of testing……..:	May 2~7, 2023
Date of issue……....:	May 7, 2023
Result……:	**PASS**

Compiled by: (Printed name+signature)	Zoe Xie	Zoe Xie
Supervised by: (Printed name+signature)	Miller Ma	Miller Ma
Approved by: (Printed name+signature)	Walter Chen	Walter Chen

Testing Laboratory Name……:	**CTC Laboratories, Inc.**
Address……:	1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CTC. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CTC within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely correspond to the test sample.

Table of Contents Page

1. 7TEST SUMMARY 3
1.1. TEST STANDARDS 3
1.2. REPORT VERSION 3
1.3. TEST DESCRIPTION 4
1.4. TEST FACILITY 5
1.5. MEASUREMENT UNCERTAINTY 5
1.6. ENVIRONMENTAL CONDITIONS 6
2. GENERAL INFORMATION 7
2.1. CLIENT INFORMATION 7
2.2. GENERAL DESCRIPTION OF EUT 7
2.3. ACCESSORY EQUIPMENT INFORMATION 8
2.4. OPERATION STATE 9
2.5. MEASUREMENT INSTRUMENTS LIST 10
3. TEST ITEM AND RESULTS 11
3.1. CONDUCTED EMISSION 11
3.2. RADIATED EMISSION 14
3.3. BAND EDGE EMISSIONS (RADIATED) 19
3.4. BAND EDGE AND SPURIOUS EMISSIONS (CONDUCTED) 22
3.5. DTS BANDWIDTH 27
3.6. PEAK OUTPUT POWER 30
3.7. POWER SPECTRAL DENSITY 31
3.8. ANTENNA REQUIREMENT 33

1. 7TEST SUMMARY

1.1. Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.
RSS 247 Issue 2: Standard Specifications for Frequency Hopping Systems (FHSs) and Digital Transmission Systems (DTSs) Operating in the Bands 902-928MHz, 2400-2483.5MHz and 5725-5850MHz.
ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
RSS-Gen Issue 5: 2018: General Requirements for Compliance of Radio Apparatus

1.2. Report version

Revised No.	Date of issue	Description
01	May 07, 2023	Original

1.3. Test Description

FCC Part 15 Subpart C (15.247) / RSS 247 Issue 2				
Test Item	Standard Section		Result	Test Engineer
	FCC	IC		
Antenna Requirement	15.203	/	Pass	Alicia Liu
Conducted Emission	15.207	RSS-Gen 8.8	Pass	Eva Feng
Conducted Band Edge and Spurious Emissions	15.247(d)	RSS 247 5.5	Pass	Alicia Liu
Radiated Band Edge and Spurious Emissions	15.205&15.209& 15.247(d)	RSS 247 5.5	Pass	Alicia Liu
6dB Bandwidth	15.247(a)(2)	RSS 247 5.2 (a)	Pass	Alicia Liu
99% Occupied Bandwidth	/	RSS-Gen 6.7	Pass	Alicia Liu
Conducted Max Output Power	15.247(b)(3)	RSS 247 5.4 (d)	Pass	Alicia Liu
Power Spectral Density	15.247(e)	RSS 247 5.2 (b)	Pass	Alicia Liu
Transmitter Radiated Spurious	15.209&15.247(d)	RSS 247 5.5& RSS-Gen 8.9	Pass	Alicia Liu

Note: The measurement uncertainty is not included in the test result.

1.4. Test Facility

CTC Laboratories, Inc.
Add: 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Laboratory accreditation
The test facility is recognized, certified, or accredited by the following organizations:

A2LA-Lab Cert. No.: 4340.01
CTC Laboratories, Inc. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025:2017 General Requirements fo r the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

Industry Canada (Registration No.: 9783A, CAB Identifier: CN0029)
CTC Laboratories, Inc. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 9783A on Jan, 2016.

FCC (Registration No.: 951311, Designation Number CN1208)
CTC Laboratories, Inc. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained inour files. Registration 951311, Aug 26, 2017.

1.5. Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01" Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the CTC Laboratories, Inc. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Below is the best measurement capability for CTC Laboratories, Inc.

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.42 dB	(1)
Transmitter power Radiated	2.14 dB	(1)
Conducted spurious emissions 9kHz~40GHz	1.60 dB	(1)
Radiated spurious emissions 9kHz~40GHz	2.20 dB	(1)
Conducted Emissions 9kHz~30MHz	3.08 dB	(1)
Radiated Emissions 30~1000MHz	4.51 dB	(1)
Radiated Emissions 1~18GHz	5.84 dB	(1)
Radiated Emissions 18~40GHz	6.12 dB	(1)
Occupied Bandwidth	---------	(1)

Note (1): This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

1.6. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	21°C ~ 27°C
Relative Humidity:	40% ~ 60%
Air Pressure:	101kPa

2. GENERAL INFORMATION

2.1. Client Information

Applicant:	HEALTH DEVICES CORPORATION DBA DOC JOHNSON ENTERPRISES
Address:	11933 VOSE STREET, NORTH HOLLYWOOD CA 91605
Manufacturer:	Hong Kong Passkey Industry Co. Limited
Address:	2/F, Block #6, Hua Feng Industry Park, Datianyang, Dongfang, SonggangTown, Bao'An District, Shen Zhen, China, 518105

2.2. General Description of EUT

Product Name/PMN:	FUCK MACHINE
Trade Mark:	/
Model/Type reference/HVIN:	I-MX-1100-00
Listed Model(s):	/
Power supply:	DC 3.3V from Battery and DC 5V from USB
Adapter model:	/
Hardware version:	/
Software version:	/
Serial number:	S01
GFSK	
Modulation:	GFSK
Operation frequency:	2404MHz~2480MHz
Channel number:	65
Channel separation:	1MHz
Antenna type:	FPC antenna
Antenna gain:	-0.62dBi

2.3. Accessory Equipment information

Equipment Information			
Name	Model	S/N	Manufacturer
Adapter	HW-050200C3W	/	HUAWEI
/	/	/	/
/	/	/	/
Cable Information			
Name	Shielded Type	Ferrite Core	Length
USB cable	unshielded	No	0.8m
/	/	/	/
Test Software Information			
Name	Versions	Power Level	/
PuTTY	0.78	Index	/

2.4. Operation state

Operation Frequency List: The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing. GFSK, 65 channels are provided to the EUT. Channels 01/31/65 were selected for testing.
Operation Frequency List:

Channel	Frequency (MHz)
01	**2404**
02	2405
⋮	⋮
30	2439
31	**2440**
32	2441
⋮	⋮
64	2479
65	**2480**

Note: The display in grey were the channel selected for testing.

Test mode

For RF test items:
The engineering test program was provided and enabled to make EUT continuous transmit(100% duty cycle).
For AC power line conducted emissions:
The EUT was set to connect with the Bluetooth instrument under large package sizes transmission.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

2.5. Measurement Instruments List

Tonscend JS0806-2 Test system					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Spectrum Analyzer	Rohde & Schwarz	FSU26	100105	Dec. 23, 2023
2	Spectrum Analyzer	Rohde & Schwarz	FUV40-N	101331	Mar. 15, 2024
3	MXG Vector Signal Generator	Agilent	N5182A	MY47420864	Dec. 23, 2023
4	Signal Generator	Agilent	E8257D	MY46521908	Dec. 23, 2023
5	Power Sensor	Agilent	U2021XA	MY5365004	Mar. 15, 2024
6	Power Sensor	Agilent	U2021XA	MY5365006	Mar. 15, 2024
7	High and low temperature box	ESPEC	MT3035	N/A	Mar. 24, 2024
8	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	102414	Dec. 23, 2022
9	300328 v2.2.2 test system	TONSCEND	v2.6	/	/

Radiated emission(3m chamber 2)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated Until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	9168-1013	Jan. 12, 2024
2	Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-647	Dec. 23, 2023
3	Spectrum Analyzer	R&S	FSU26	100105	Dec. 23, 2023
4	Spectrum Analyzer	R&S	FSV40-N	101331	Mar. 15, 2024
5	Pre-Amplifier	SONOMA	310	186194	Dec. 23, 2023
6	Low Noise Pre-Amplifier	EMCI	EMC051835	980075	Dec. 23, 2023
7	Test Receiver	R&S	ESCI7	100967	Dec. 23, 2023

Radiated emission(3m chamber 3)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated Until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	9168-759	Nov. 09, 2023
2	Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-647	Dec. 23, 2023
3	Test Receiver	Keysight	N9038A	MY56400071	Dec. 23, 2023
4	Broadband Premplifier	SCHWARZBECK	BBV9743B	259	Dec. 23, 2023
5	Mirowave Broadband Amplifier	SCHWARZBECK	BBV9718C	111	Dec. 23, 2023
6	Loop Antenna	ZHINAN	ZN30900A	/	Dec. 25, 2023

Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	LISN	R&S	ENV216	101112	Dec. 23, 2023
2	LISN	R&S	ENV216	101113	Dec. 23, 2023
3	EMI Test Receiver	R&S	ESCS30	100353	Dec. 23, 2023

Note:1. The Cal. Interval was one year.
2. The cable loss has calculated in test result which connection between each test instruments.

3. TEST ITEM AND RESULTS

3.1. Conducted Emission

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.207/ RSS - Gen 8.8

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test Configuration



Test Procedure

1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
4. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
5. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
6. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
7. During the above scans, the emissions were maximized by cable manipulation.

Test Mode:

Please refer to the clause 2.4.

Test Results

Test Voltage:	AC 120V/60 Hz
Terminal:	Line



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1660	48.98	0.00	48.98	65.16	-16.18	QP
2		0.1660	40.06	0.00	40.06	55.16	-15.10	AVG
3		0.3380	38.01	0.00	38.01	59.25	-21.24	QP
4		0.3420	25.30	0.00	25.30	49.15	-23.85	AVG
5		0.6020	32.11	0.00	32.11	46.00	-13.89	AVG
6	*	0.8100	44.47	0.00	44.47	56.00	-11.53	QP
7		0.9020	25.34	0.00	25.34	46.00	-20.66	AVG
8		1.1860	31.92	0.00	31.92	56.00	-24.08	QP
9		1.8980	19.20	0.00	19.20	46.00	-26.80	AVG
10		2.2460	32.27	0.00	32.27	56.00	-23.73	QP
11		3.0740	18.55	0.00	18.55	46.00	-27.45	AVG
12		3.9700	31.60	0.00	31.60	56.00	-24.40	QP

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Measure Level= Read Level+ Correct Factor
3.Margin = Measure Level-Limit level

Test Voltage:	AC 120V/60 Hz
Terminal:	Neutral



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1660	50.38	0.00	50.38	65.16	-14.78	QP
2		0.1700	37.66	0.00	37.66	54.96	-17.30	AVG
3		0.3020	28.04	0.00	28.04	50.19	-22.15	AVG
4		0.3380	41.58	0.00	41.58	59.25	-17.67	QP
5		0.4220	22.36	0.00	22.36	47.41	-25.05	AVG
6	*	0.8660	43.03	0.00	43.03	56.00	-12.97	QP
7		0.8660	27.87	0.00	27.87	46.00	-18.13	AVG
8		1.1820	20.12	0.00	20.12	46.00	-25.88	AVG
9		1.2740	33.96	0.00	33.96	56.00	-22.04	QP
10		2.0300	33.79	0.00	33.79	56.00	-22.21	QP
11		2.0660	20.37	0.00	20.37	46.00	-25.63	AVG
12		3.7220	32.92	0.00	32.92	56.00	-23.08	QP

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Measure Level= Read Level+ Correct Factor
3.Margin = Measure Level-Limit level

3.2. Radiated Emission

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.209/ RSS – Gen 8.9

Frequency	Limit (dBuV/m @3m)	Value
30 MHz ~ 88 MHz	40.00	Quasi-peak
88 MHz ~ 216 MHz	43.50	Quasi-peak
216 MHz ~ 960 MHz	46.00	Quasi-peak
960 MHz ~ 1 GHz	54.00	Quasi-peak
Above 1 GHz	54.00	Average
	74.00	Peak

Note:

(1) The tighter limit applies at the band edges.

(2) Emission Level (dBuV/m)=20log Emission Level (uV/m).

Test Configuration



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2013
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable(from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings

(1) Span shall wide enough to fully capture the emission being measured;
(2) Below 1 GHz:
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
(3) From 1 GHz to 10th harmonic:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW⩾1/T Peak detector for Average value.
Note 1: For the 1/T& Duty Cycle please refer to clause 3.8 Duty Cycle.

Test Mode

Please refer to the clause 2.4.

Test Result

9 KHz~30 MHz

From 9 KHz to 30 MHz: Conclusion: PASS
Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissiblevalue has no need to be reported.

30MHz-1GHz

Ant. Pol.	Horizontal
Test Mode:	TX GFSK Mode 2404MHz
Remark:	Only worse case is reported



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		195.1365	44.22	-15.68	28.54	43.50	-14.96	QP
2		234.1684	46.35	-14.37	31.98	46.00	-14.02	QP
3		267.5455	47.25	-13.45	33.80	46.00	-12.20	QP
4	*	301.4224	50.19	-12.77	37.42	46.00	-8.58	QP
5		318.8170	42.81	-12.27	30.54	46.00	-15.46	QP
6		332.5187	45.08	-11.88	33.20	46.00	-12.80	QP

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Measure Level= Read Level+ Correct Factor
3.Over = Limit -Measure Level

Ant. Pol.	Vertical
Test Mode:	TX GFSK Mode 2404MHz
Remark:	Only worse case is reported



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		166.0680	47.27	-17.68	29.59	43.50	-13.91	QP
2		199.2855	45.06	-15.67	29.39	43.50	-14.11	QP
3		267.5455	45.85	-13.45	32.40	46.00	-13.60	QP
4		399.0302	39.66	-11.04	28.62	46.00	-17.38	QP
5		465.5994	39.60	-9.38	30.22	46.00	-15.78	QP
6	*	492.4685	41.48	-8.71	32.77	46.00	-13.23	QP

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Measure Level= Read Level+ Correct Factor
3.Over = Limit -Measure Level

Above 1GHz

Frequency (MHz)	Reading (dBuV)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2404MHz							
4810	58.17	-4.86	53.31	74	-20.69	H	PK
4810	42.9	-4.86	38.04	54	-15.96	H	AV
7215	54.31	1.6	55.91	74	-18.09	H	PK
7215	39.86	1.6	41.46	54	-12.54	H	AV
4810	61	-4.86	56.14	74	-17.86	V	PK
4810	40.9	-4.86	36.04	54	-17.96	V	AV
7215	51.95	1.6	53.55	74	-20.45	V	PK
7215	40.1	1.6	41.7	54	-12.3	V	AV
Middle Channel-2440MHz							
4880	58.02	-4.87	53.15	74	-20.85	H	PK
4880	41.14	-4.87	36.27	54	-17.73	H	AV
7320	52.19	1.51	53.7	74	-20.3	H	PK
7320	38.16	1.51	39.67	54	-14.33	H	AV
4880	58.11	-4.87	53.24	74	-20.76	V	PK
4880	41.31	-4.87	36.44	54	-17.56	V	AV
7320	55.3	1.51	56.81	74	-17.19	V	PK
7320	37.87	1.51	39.38	54	-14.62	V	AV
High Channel-2480MHz							
4960	58.53	-4.26	54.27	74	-19.73	H	PK
4960	41.43	-4.26	37.17	54	-16.83	H	AV
7440	53.02	1.69	54.71	74	-19.29	H	PK
7440	37.5	1.69	39.19	54	-14.81	H	AV
4960	56.9	-4.26	52.64	74	-21.36	V	PK
4960	41.47	-4.26	37.21	54	-16.79	V	AV
7440	52.2	1.69	53.89	74	-20.11	V	PK
7440	38.3	1.69	39.99	54	-14.01	V	AV

Remarks:
1. Correct (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2. Measure Level= Read Level+ Correct Factor
3. Margin = Measure Level-Limit
4. Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3h Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

3.3. Band Edge Emissions (Radiated)

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d)/ RSS 247 5.5:

Restricted Frequency Band (MHz)	(dBuV/m)(at 3m)	
	Peak	Average
2310 ~ 2390	74	54
2483.5 ~ 2500	74	54

Test Configuration



Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2013 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:
   RBW=1MHz, VBW=3MHz Peak detector for Peak value.
   RBW=1MHz, VBW see note 1 with Peak Detector for Average Value.

   Note 1: For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 3.8 Duty Cycle.

Test Mode

Please refer to the clause 2.4.

Test Results

Ant. Pol.	Vertical (worst case)
Test Mode:	GFSK Mode 2404MHz



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	35.52	-11.50	24.02	73.90	49.88	peak
2		2390.000	34.64	-11.28	23.36	73.90	50.54	peak
3	*	2310.000	24.28	-11.50	12.78	53.90	41.12	AVG
4		2390.000	23.91	-11.28	12.63	53.90	41.27	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Measure Level= Read Level+ Correct Factor
3.Over = Measure Level-Limit

Ant. Pol.	Vertical(worst case)
Test Mode:	GFSKMode 2480MHz(worst case)



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	52.14	-11.04	41.10	73.90	32.80	peak
2	*	2483.500	39.14	-11.04	28.10	53.90	25.80	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Measure Level= Read Level+ Correct Factor
3.Over = Measure Level-Limit

3.4. Band edge and Spurious Emissions (Conducted)

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

Test Configuration



Test Procedure

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
   RBW = 100 kHz, VBW ≥ RBW, scan up through 10th harmonic.
   Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

Test Mode

Please refer to the clause 2.4.

Test Results

(1) Band edge Conducted Test

Test Item:	Band edge
Low	
High	

Test Item:	SE
Low Reference level	
Low 30MHz~1000MHz	
Low 1GHz~26GHz	

中国国家认证认可监督管理委员会
Certification and Accreditation Administration of the People's Republic of China
For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn

Middle Reference level	
Middle 30MHz~1000MHz	
Middle 1GHz~26GHz	

High Reference level	
High 30MHz~1000MHz	
High 1GHz~26GHz	

3.5. DTS Bandwidth

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2)/ RSS-247 5.2 a:

Test Item	Limit	Frequency Range(MHz)
DTS Bandwidth	>=500 KHz (6dB bandwidth)	2400~2483.5

Test Configuration



Test Procedure

5. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
6. DTS Spectrum Setting:
   (1) Set RBW = 100 kHz.
   (2) Set the video bandwidth (VBW) ≥ 3 RBW.
   (3) Detector = Peak.
   (4) Trace mode = Max hold.
   (5) Sweep = Auto couple.
   OCB Spectrum Setting:
   (1) Set RBW = 1% ~ 5% occupied bandwidth.
   (2) Set the video bandwidth (VBW) ≥ 3 RBW.
   (3) Detector = Peak.
   (4) Trace mode = Max hold.
   (5) Sweep = Auto couple.

Test Mode

Please refer to the clause 2.4.

Test Results

Test Mode	Frequency[MHz]	DTS BW[MHz]	OBW[MHz]	Limit[MHz]	Verdict
GFSK	2404	0.80	1.04	>=0.5	PASS
	2440	0.80	1.04	>=0.5	PASS
	2480	0.81	1.04	>=0.5	PASS

Low	 
Middle	

中国国家认证认可监督管理委员会 Certification and Accreditation Administration of the People's Republic of China
For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn

	 Spectrum Ref Level 10.50 dBm Offset 1.00 dB RBW 30 kHz Att 20 dB SWT 63.3 µs VBW 100 kHz Mode Auto FFT Count 500/500 1Pk View M1[1] -18.92 dBm 2.43996600 GHz Occ Bw 1.034965035 MHz M1 T1 T2 CF 2.44 GHz 1001 pts Span 2.0 MHz
High	 Spectrum Ref Level 10.50 dBm Offset 1.00 dB RBW 100 kHz Att 20 dB SWT 19.1 µs VBW 300 kHz Mode Auto FFT Count 500/500 1Pk View M1[1] -25.59 dBm 2.47954600 GHz M2[1] -19.55 dBm 2.48026600 GHz D1 -25.548 dBm M1 M2 D3 CF 2.48 GHz 1001 pts Span 2.0 MHz Marker Type Ref Trc X-value Y-value Function Function Result M1 1 2.479546 GHz -25.59 dBm M2 1 2.480266 GHz -19.55 dBm D3 M1 1 810.0 kHz -0.08 dB  Spectrum Ref Level 10.50 dBm Offset 1.00 dB RBW 30 kHz Att 20 dB SWT 63.3 µs VBW 100 kHz Mode Auto FFT Count 500/500 1Pk View M1[1] -19.58 dBm 2.47996600 GHz Occ Bw 1.038961039 MHz M1 T1 T2 CF 2.48 GHz 1001 pts Span 2.0 MHz

3.6. Peak Output Power

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3)/ RSS-247 5.4 d:

Section	Test Item	Limit	Frequency Range(MHz)
CFR 47 FCC 15.247(b)(3)	Maximum conducted output power	1 Watt or 30dBm	2400~2483.5
ISED RSS-247 5.4 d	EIRP	4 Watt or 36dBm	2400~2483.5

Test Configuration



Test Procedure

1. The EUT was tested according to ANSI C63.10: 2013 and KDB 558074 D01 for compliance to FCC 47 CFR 15.247 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.
4. Record the measurement data.

Test Mode

Please refer to the clause 2.4.

Test Result

Test Mode	Frequency[MHz]	Result[dBm]	Limit[dBm]	Verdict
BLE	2402	-10.92	<=30	PASS
	2440	-10.82	<=30	PASS
	2480	-10.51	<=30	PASS

3.7. Power Spectral Density

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e)/ RSS-247 5.2 b:

Test Item	Limit	Frequency Range(MHz)
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

Test Configuration



Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v05r02.
3. Spectrum Setting:

Set analyzer center frequency to DTS channel center frequency.
Set the span to 1.5 times the DTS bandwidth.
Set the RBW to: 3 kHz
Set the VBW to: 10 kHz
Detector: peak
Sweep time: auto
Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

Test Mode

Please refer to the clause 2.4.

Test Result

Test Mode	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE	2402	-25.32	<=8	PASS
	2440	-26.56	<=8	PASS
	2480	-27.52	<=8	PASS

Test plot as follows:

Low	
Middle	
High	

3.8. Antenna requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):
(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Test Result

This product has a FPC antenna, fulfill the requirement of this section.

**********THE END**********