


ANTENNA SPECIFICATION

Specifications

Summary

ITEM	SPEC.					
Model Name						
Center Frequency	Horizontal			Vertical		
	2402MHz	2440MHz	2480MHz	2402MHz	2440MHz	2480MHz
	-2.64	-1.89	-1.66	-7.09	-4.70	-3.15
MAX. Gain	-1.66 dbi					
Polarization	Horizontal and Vertical					
Azimuth Beam Pattern	Omni-directional					
Impedance	50 Ohm					
Antenna Length	84.1mm					


Antenna Photo & Length (mm)



Manufacturer	Hong Kong Passkey Industry Co. Limited
Manufacturer's address	2/F, Block #6, Hua Feng Industry Park, Datianyang, Dongfang, SonggangTown, Bao'An District, Shen Zhen, China, 518105

Horizontal:

2402MHz 2440MHz 2480MHz




Frequency (MHz)	Gain(dBi)		
	Max.	Min.	Avg.
2402	-2.64776	-30.6718	-9.77028
2440	-1.89964	-35.918	-8.87095
2480	-1.66516	-24.7457	-7.99065

Vertical:

2402MHz

2440MHz

2480MHz



Frequency (MHz)	Gain(dBi)		
	Max.	Min.	Avg.
2402	-7.09317	-24.1891	-13.5194
2440	-4.7048	-27.8246	-11.666
2480	-3.1576	-29.4867	-10.5684