FCC Test Report

Report No: FCS202304214W01

Issued for

Applicant:	GUANGDONG G-SUN TECHNOLOGY CO,.LTD.
Address:	No. 426, Block A, YangXieChengShiShang Factory, Chigangxi Road, Haizhu District, Guangzhou City, Guangdong Province
Product Name:	WIRELESS DESKTOP USB CONDENSER MICROPHONE
Brand Name:	N/A
Model Name:	IRON MINI-WL
Series Model:	N/A
FCC ID:	2BA4T-IRONMINI-WL
Issued By: Flux Compliance Service Laboratory Add: Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan Tel: 769-27280901 Fax:769-27280901 http://www.fcs-lab.com	

TEST RESULT CERTIFICATION

Applicant Name.....:	GUANGDONG G-SUN TECHNOLOGY CO,.LTD.
Address..... :	No. 426, Block A, YangXieChengShiShang Factory, Chigangxi Road, Haizhu District, Guangzhou City, Guangdong Province
Manufacture Name.....:	FUZHOU KINGWAY INFORMATION TECHNOLOGY CO., LTD
Address..... :	2nd Floor, Building 69, Area A, Pushang Industrial Park, Jinshan Industrial Concentration Area, No.1, Hongjiang Road, Jianxin Town, Cangshan District, Fuzhou, Fujian, China

Product Description

Product Name..... :	WIRELESS DESKTOP USB CONDENSER MICROPHONE
Brand Name .....:	N/A
Model Name..... :	IRON MINI-WL
Series Model.....:	N/A
Test Standards.....:	FCC Rules and Regulations Part 15 Subpart C, Section 249
Test Procedure.....:	ANSI C63.10:2013

This device described above has been tested FCS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of FCS, this document may be altered or revised by FCS, personal only, and shall be noted in the revision of the document..

Date of Test.....:

Date (s) of performance of tests. :	Apr 24, 2023 ~ May 5, 2023
Date of Issue.....:	May 5, 2023
Test Result..... :	Pass

Tested by : Scott Shen

(Scott Shen)

Reviewed by : Duke Qian

(Duke Qian)

Approved by : Jack Wang

(Jack Wang)

Table of Contents **Page**

1. SUMMARY OF TEST RESULTS 5
1.1 TEST FACTORY 6
1.2 MEASUREMENT UNCERTAINTY 6
2. GENERAL INFORMATION 7
2.1 GENERAL DESCRIPTION OF THE EUT 7
2.2 DESCRIPTION OF THE TEST MODES 9
2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS 10
2.4 EQUIPMENTS LIST 11
3 CONDUCTED EMISSION MEASUREMENT 12
3.1 LIMIT 12
3.2 TEST PROCEDURE 12
3.3 TEST SETUP 13
3.4 TEST RESULTS 14
4. RADIATED EMISSION MEASUREMENT 16
4.1 LIMIT 16
4.2 TEST PROCEDURE 17
4.3 TEST SETUP 18
4.4 (30MHZ-1000MHZ) 20
4.5 ABOVE 1GHZ 22
5. BAND EDGE TEST 23
5.1 LIMIT 23
5.2 TEST PROCEDURE 23
5.3 TEST SETUP 23
5.4 TEST RESULTS 24
6. 20 DB BANDWIDTH TEST 25
6.1 LIMIT 25
6.2 TEST PROCEDURE 25
6.3 TEST SETUP 25
6.4 TEST RESULTS 26
7. ANTENNA REQUIREMENT 28
7.1 STANDARD REQUIREMENT 28
7.2 EUT ANTENNA 28

Table of Contents **Page**

8.EUT PHOTOGRAPH 29

Revision History

Rev.	Issue Date	Effect Page	Contents
00	May 5, 2023	N/A	Initial Issue

1. SUMMARY OF TEST RESULTS

FCC Part 15.249,Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.205(a), 15.209(a), 15.249(a), 15.249(c)	Radiated Spurious Emission	PASS	--
15.209	Field strength of fundamental	PASS	--
15.249(d)	Band Edge Emission	PASS	--
15.215(c)	20dB Bandwidth	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

(2) All tests are according to ANSI C63.10-2013

1.1 TEST FACTORY

Company Name:	Flux Compliance Service Laboratory
Address:	Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan
Telephone:	+86-769-27280901
Fax:	+86-769-27280901
FCC Test Firm Registration Number: 514908 Designation number: CN0127 A2LA accreditation number：5545.01	

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement **y ±U**, where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95** %.

No.	Item	Uncertainty
1	RF output power, conducted	±0.71dB
2	Unwanted Emissions, conducted	±2.98 dB
3	Conducted Emission (9KHz-150KHz)	±4.13 dB
4	Conducted Emission (150KHz-30MHz)	±4.74 dB
5	All emissions,radiated(<1G) 30MHz-1000MHz	±3.2 dB
6	All emissions,radiated (1GHz -18GHz)	±3.66 dB
7	All emissions,radiated (18GHz -40GHz)	±4.31 dB

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	WIRELESS DESKTOP USB CONDENSER MICROPHONE
Trade Name	N/A
Model Name	IRON MINI-WL
Series Model	N/A
Model Difference	The above product with same circuit, PCB layout, electrical parts, materials and wiring structures, the materials of decorative accessories is same, For the product appearance difference, the size is the same, but the color of the product is different
Channel List	Please refer to the Note 2.
Specification	Frequency:902.8-926.8MHz Modulation: FM Channel number: 30CH
Power Supply	Input:DC 5V 1A
Battery	DC 3.7V
Hardware version number	V1.0
Software version number	V1.0
Connecting I/O Port(s)	Please refer to the User's Manual

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2. **Channel List**

A mode: Channel(A)	Frequency (MHz)	B mode :Channel(B)	Frequency (MHz)
1	902.80	16	915.60
2	903.60	17	916.40
3	904.40	18	917.20
4	905.20	19	918.00
5	906.00	20	918.80
6	906.80	21	919.60
7	907.60	22	920.40
8	908.40	23	921.20
9	909.20	24	922.00
10	910.00	25	922.80
11	910.80	26	923.60
12	911.60	27	924.40
13	912.40	28	925.20
14	913.20	29	926.00
15	914.00	30	926.80

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	Spring Antenna	N/A	-2.09 dBi	Antenna

2.2 DESCRIPTION OF THE TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test software:
Use the manual test control EUT to work in continuous TX mode, select the test channel; See table below for wireless mode

No.	Test model descrption
1	Low channel
2	Middle channel
3	High channel

Note:

1. All the test modes can be supply by battery, only the result of the worst case recorded in the report. mode is worst mode.
2. For radiated emission, 3 axis were chosen for testing for each applicable mode.
3. The EUT used fully charge battery when tested.
4. During the test, the dutycycle>98%, the test voltage was tuned from 85% to 115% of the Nominal rate supply votage, and found that the worst case was the nominal rated supply condition, So the report just shows that condition's data

Configuration and peripherals

Mode 1:



2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
1	adapter	XIAOMI	AD652G	N/A	Test use
2	laptop	Lenovo	E495	N/A	Test use

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
N/A	N/A	N/A	N/A	N/A	N/A

Note:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
(3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.4 EQUIPMENTS LIST

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESRP 3	FCS-E001	2022. 08.30	2023. 08.29
Signal Analyzer	R&S	FSV40-N	FCS-E012	2022. 08.30	2023. 08.29
Active loop Antenna	ZHINAN	ZN30900C	FCS-E013	2022. 08.30	2023. 08.29
Bilog Antenna	SCHWARZBECK	VULB 9168	FCS-E002	2022. 08.30	2023. 08.29
Horn Antenna	SCHWARZBECK	BBHA 9120D	FCS-E003	2022. 08.30	2023. 08.29
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	FCS-E018	2022. 08.30	2023. 08.29
Pre-Amplifier(0.1M-3G Hz)	EMCI	EM330N	FCS-E004	2022. 08.30	2023. 08.29
Pre-Amplifier (1G-18GHz)	N/A	TSAMP-0518SE	FCS-E014	2022. 08.30	2023. 08.29
Pre-Amplifier (18G-40GHz)	TERA-MW	TRLA-0400	FCS-E019	2022. 08.30	2023. 08.29
Temperature & Humidity	HTC-1	victor	FCS-E005	2022. 08.30	2023. 08.29

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESPI	FCS-E020	2022. 08.30	2023. 08.29
LISN	R&S	ENV216	FCS-E007	2022. 08.30	2023. 08.29
LISN	ETS	3810/2NM	FCS-E009	2022. 08.30	2023. 08.29
Temperature & Humidity	HTC-1	victor	FCS-E008	2022. 08.30	2023. 08.29

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
MXA SIGNAL Analyzer	Keysight	N9020A	FCS-E015	2022. 08.30	2023. 08.29
Spectrum Analyzer	Agilent	E4447A	MY50180039	2022. 08.30	2023. 08.29
Spectrum Analyzer	R&S	FSV-40	101499	2022. 08.30	2023. 08.29

Test Equipment Calibration

All of the test equipment is effective use and calibration certification institution, GRGT, the address is 163 tianhe district in huangpu road xiping cloud road .Guangzhou,China

3 CONDUCTED EMISSION MEASUREMENT

3.1 LIMIT

Operating frequency band. In case the emission fall within the restricted band specified on Part 207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Conducted Emissionlimit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:
(1) The tighter limit applies at the band edges.
(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

3.2 TEST PROCEDURE

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

a. The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.4 TEST RESULTS

Temperature:	25℃	Relative Humidity:	50%
Test Mode:	FM(worst mode)	Test Voltage:	DC 5V by adapter
Result:	L	Result:	Pass



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.2400	19.87	10.06	29.93	62. 10	32.17	QP
2	0.2400	16.58	10.06	26.64	52. 10	25.46	AVG
3	0.3885	18.73	10.02	28.75	58. 10	29.35	QP
4	0.3885	13.29	10.02	23.31	48. 10	24.79	AVG
5	1. 1265	20.73	10.00	30.73	56.00	25.27	QP
6	1. 1265	11.97	10.00	21.97	46.00	24.03	AVG
7	4.0200	10.67	9.91	20.58	56.00	35.42	QP
8	4.0200	-0.33	9.91	9.58	46.00	36.42	AVG
9	10.2524	12.28	9.80	22.08	60.00	37.92	QP
10	10.2524	1.91	9.80	11.71	50.00	38.29	AVG
11	29.0715	11.98	9.89	21.87	60.00	38. 13	QP
12	29.0715	0.99	9.89	10.88	50.00	39. 12	AVG

Temperature:	25℃	Relative Humidity:	50%
Test Mode:	FM(worst mode)	Test Voltage:	DC 5V by adapter
Result:	N	Result:	Pass



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0. 1860	21.94	10.06	32.00	64.21	32.21	QP
2	0. 1860	15.97	10.06	26.03	54.21	28.18	AVG
3	0.3345	19.32	10.03	29.35	59.34	29.99	QP
4	0.3345	15.72	10.03	25.75	49.34	23.59	AVG
5	0.6675	16.82	9.98	26.80	56.00	29.20	QP
6	0.6675	9.69	9.98	19.67	46.00	26.33	AVG
7	1. 1310	20.35	9.99	30.34	56.00	25.66	QP
8	1. 1310	13. 11	9.99	23. 10	46.00	22.90	AVG
9	3.7905	11.01	9.92	20.93	56.00	35.07	QP
10	3.7905	0. 11	9.92	10.03	46.00	35.97	AVG
11	8.8575	11.88	9.82	21.70	60.00	38.30	QP
12	8.8575	1.65	9.82	11.47	50.00	38.53	AVG

Remark:

1. All readings are Quasi-Peak and Average values

4. RADIATED EMISSION MEASUREMENT

4.1 LIMIT

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2013 below has to be followed

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009mhz - 1000mhz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1GHz-25 GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

LIMITS OF FIELD STRENGTH OF THE FUNDAMENTAL SIGNAL

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
2400-2483.5	114	94

Notes:
(1) The limit for radiated test was performed according to FCC PART 15C.
(2) The tighter limit applies at the band edges.
(3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	PK=1MHz / 1MHz, AV=1 MHz /10 Hz

a. The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz,and above 1GHz.
b. The EUT was placed on the top of a rotating table 0.8 meters (above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. horizontal and vertical polarizations of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then QuasiPeak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:
Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.3 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



Temperature:	23.7℃	Relative Humidity:	61%
Test Voltage:	DC 3.7V	Test Mode:	FM

For field strength of the fundamental signal

Frequency (MHz)	Emission (dBuV/m)	PK/AV	Ant. Pol.	Limrts PK/AV (dBuWm)	Margin (dB)
902.8	89.86	PK	H	114	-24.14
902.8	79.11	AV	H	94	-14.89
902.8	91.45	PK	V	114	-22.55
902.8	79.12	AV	V	94	-14.88

Frequency (MHz)	Emission (dBuV/m)	PK/AV	Ant. Pol.	Limrts PK/AV (dBuV/m)	Margin (dB)
914.0	93.89	PK	H	114	-20.11
914.0	79.78	AV	H	94	-14.22
914.0	93.01	PK	V	114	-20.99
914.0	80.81	AV	V	94	-13.19

Frequency (MHz)	Emission (dBuV/m)	PK/AV	Ant. Pol.	Limrts PK/AV (dBuV/m)	Margin (dB)
926.8	93.52	PK	H	114	-20.45
926.8	79.61	AV	H	94	-14.39
926.8	92.81	PK	V	114	-21.19
926.8	80.60	AV	V	94	-13.40

For spurious emission

(9KHz-30MHz)

Freq.	Reading	Limit	Margin	State	Test Result
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F	
--	--	--	--	--	PASS
--	--	--	--	--	PASS

Note:
The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
Distance extrapolation factor =40 log (specific distance/test distance)(dB);
Limit line = specific limits (dBuv) + distance extrapolation factor.

4.4 (30MHZ-1000MHZ)

Temperature:	23.7℃	Relative Humidity:	61%
Test Voltage:	DC 3.7V	Phase:	Horizontal
Test Mode:	FM		



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	35.2512	19.47	-10.77	8.70	40.00	-31.30	QP
2	66.2662	19.69	-20.22	-0.53	40.00	-40.53	QP
3	140.8351	37.35	-32.26	5.09	43.50	-38.41	QP
4	359.1860	40.24	-32.04	8.20	46.00	-37.80	QP
5	537.5891	45.00	-31.85	13.15	46.00	-32.85	QP
6	909.6667	62.37	-31.39	30.98	46.00	- 15.02	QP

Note: 1. level= Reading level+ Factor, Margin=Measurement-Limit

Temperature:	22.7℃	Relative Humidity:	61%
Test Voltage:	DC 3.7V	Phase:	Vertical
Test Mode:	FM		



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	38.3462	19.36	-12.79	6.57	40.00	-33.43	QP
2	79.2426	34.11	-32.26	1.85	40.00	-38.15	QP
3	146.8877	37.42	-32.25	5.17	43.50	-38.33	QP
4	270.3748	38.71	-32. 13	6.58	46.00	-39.42	QP
5	537.5891	45.00	-31.85	13.15	46.00	-32.85	QP
6	909.6667	62.37	-31.39	30.98	46.00	- 15.02	QP

Note: 1. level= Reading level+ Factor, Margin=Measurement-Limit

4.5 ABOVE 1GHZ

902.8MHz
PK

Frequency	Meter Reading	Detector	Amplifier	Loss	Antenna Factor	Orrected Factor	Corrected Amplitude	Limit	Margin	RX Antenna Polar
(MHz)	(dBμV/m)	(PK/QP/AV)	(Db)	(Db)	(Db/m)	(Db)	(dBμV/m)	(dBμV/m)	(Db)	(H/V)
1805.60	65.95	PK	45.10	4.91	25.00	-15.19	50.76	74	-23.24	H
1805.60	65.87	PK	45.10	4.91	25.00	-15.19	50.68	74	-23.32	V
2708.40	63.21	PK	44.10	5.03	25.80	-13.27	49.94	74	-24.06	H
2708.40	62.53	PK	44.10	5.03	25.80	-13.27	49.26	74	-24.74	V
3611.20	50.91	PK	43.80	6.72	33.40	-3.68	47.23	74	-26.77	H
3611.20	50.60	PK	43.80	6.72	33.40	-3.68	46.92	74	-27.08	V

914.0MHz
PK

Frequency	Meter Reading	Detector	Amplifier	Loss	Antenna Factor	Orrected Factor	Corrected Amplitude	Limit	Margin	RX Antenna Polar
(MHz)	(dBμV/m)	(PK/QP/AV)	(Db)	(Db)	(Db/m)	(Db)	(dBμV/m)	(dBμV/m)	(Db)	(H/V)
1828.00	62.32	PK	50.33	8.84	31.22	-10.27	52.05	74	-21.95	H
1828.00	62.53	PK	50.33	8.84	31.22	-10.27	52.26	74	-21.74	V
2742.00	60.38	PK	55.48	9.31	34.05	-12.12	48.26	74	-25.74	H
2742.00	59.81	PK	55.48	9.31	34.05	-12.12	47.69	74	-26.31	V
3656.00	55.41	PK	59.13	9.89	36.99	-12.25	43.16	74	-30.84	H
3656.00	55.14	PK	59.13	9.89	36.99	-12.25	42.89	74	-31.11	V

926.8MHz
PK

Frequency	Meter Reading	Detector	Amplifier	Loss	Antenna Factor	Orrected Factor	Corrected Amplitude	Limit	Margin	RX Antenna Polar
(MHz)	(dBμV/m)	(PK/QP/AV)	(Db)	(Db)	(Db/m)	(Db)	(dBμV/m)	(dBμV/m)	(Db)	(H/V)
1853.60	62.53	PK	50.33	8.84	31.22	-10.27	52.26	74	-21.74	H
1853.60	62.39	PK	50.33	8.84	31.22	-10.27	52.12	74	-21.88	V
2780.40	59.22	PK	55.48	9.31	34.05	-12.12	47.10	74	-26.90	H
2780.40	59.71	PK	55.48	9.31	34.05	-12.12	47.59	74	-26.41	V
3707.20	55.28	PK	59.13	9.89	36.99	-12.25	43.03	74	-30.97	H
3707.20	55.18	PK	59.13	9.89	36.99	-12.25	42.93	74	-31.07	V

Note:The emission levels of other frequencies are very lower than the limit and not show in test report.

5. BAND EDGE TEST

5.1 LIMIT

According to §15.249(d), Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 TEST PROCEDURE

a. The EUT is placed on a turntable, which is 1.5m above ground plane.

b. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.

c. Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured, RBW = 1 MHz, VBW ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold
Follow the guidelines in ANSI C63.4 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc.

d. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

e. Set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the duty cycle per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from 20log(duty cycle/100 ms), in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

5.3 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.4 TEST RESULTS

	Polar (H/V)	Frequenc y (MHz)	Meter Reading (dBuV)	Preamplifi er (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV /m)	Detec tor Type	Result
FM	Low Channe					902.8MHz				
	H	897.6	36.85	30.22	4.85	23.98	35.46	46.00	PK	PASS
	H	902	36.82	30.22	4.85	23.98	35.43	46.00	PK	PASS
	V	897.6	33.49	30.22	4.85	23.98	32.10	46.00	PK	PASS
	V	902	37.17	30.22	4.85	23.98	35.78	46.00	PK	PASS
	High Channe									
	H	928	36.87	30.22	4.85	23.98	35.52	46.00	PK	PASS
	H	932.9	37.29	30.22	4.85	23.98	35.90	46.00	PK	PASS
	V	928	35.55	30.22	4.85	23.98	34.16	46.00	PK	PASS
	V	932.9	35.67	30.22	4.85	23.98	34.28	46.00	PK	PASS

6. 20 DB BANDWIDTH TEST

6.1 LIMIT

According to 15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation

6.2 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator

b. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.

6.3 TEST SETUP



6.4 TEST RESULTS

Temperature:	25℃	Relative Humidity:	50%
Test Mode:	FM	Test Voltage:	DC 3.7V

Frequency	20dB Bandwidth (kHz)	99% Bandwidth (kHz)	Result
902.8 MHz	307.3	266.21	PASS
914.0 MHz	306.4	266.77	PASS
926.8 MHz	308.5	266.12	PASS




Keysight Spectrum Analyzer - Occupied BW
Center Freq 914.000000 MHz
Center Freq: 914.000000 MHz
Trig: Free Run
Avg|Hold:>10/10
#Atten: 10 dB
#IFGain:Low
Radio Std: None
Radio Device: BTS
10 dB/div
Ref 0.00 dBm
Center 914 MHz
#Res BW 30 kHz
#VBW 100 kHz
Span 1 MHz
Sweep 1.4 ms
Occupied Bandwidth
266.77 kHz
Total Power -20.2 dBm
Transmit Freq Error -2.369 kHz
% of OBW Power 99.00 %
x dB Bandwidth 306.4 kHz
x dB -20.00 dB
Frequency
Center Freq
914.000000 MHz
CF Step
100.000 kHz
Auto Man
Freq Offset
0 Hz


Keysight Spectrum Analyzer - Occupied BW
Center Freq 926.800000 MHz
Center Freq: 926.800000 MHz
Trig: Free Run
Avg|Hold:>10/10
#Atten: 10 dB
#IFGain:Low
Radio Std: None
Radio Device: BTS
10 dB/div
Ref 0.00 dBm
Center 926.8 MHz
#Res BW 30 kHz
#VBW 100 kHz
Span 1 MHz
Sweep 1.4 ms
Occupied Bandwidth
266.12 kHz
Total Power -20.9 dBm
Transmit Freq Error -2.340 kHz
% of OBW Power 99.00 %
x dB Bandwidth 308.5 kHz
x dB -20.00 dB
Frequency
Center Freq
926.800000 MHz
CF Step
100.000 kHz
Auto Man
Freq Offset
0 Hz

7. ANTENNA REQUIREMENT

7.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.2 EUT ANTENNA

The antennas used for this product are Spring Antenna antenna and other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is -2.09 dBi.

8.EUT PHOTOGRAPH

Photo 1	Photo 2
	
	Spring Antenna

※※※※※END OF THE REPORT※※※※※