



REPORT

For

Avari Wireless Inc.

1400 112th Ave SE, Ste 100
Bellevue, WA 98004, USA

Date: 2024-1-17
Report No.: 20.01.22063-1
Revision No.: 0
Project No.: 22063
Equipment: Tri-Band Medium Power Remote Unit
Model No.: RU37-3-PS-BFH-21-5N-D0-1
FCC ID: 2BA6ERU373PSBFH21A

TABLE OF CONTENTS

TEST REPORT_FCC Part 15 Subpart B, FCC Part 90..... 3

Revision History 4

Device Under Test Description..... 4

Program details 5

Description of Equipment Under Test (EUT) and Variant Models 6

Client Equipment Used During Test 7

Software and Firmware 7

Input/Output Ports 7

Power Interface 8

EUT Operation Modes..... 8

EUT Configuration Modes 8

Test Equipment Verified for function 8

Test Station Photo..... 9

Test Station Cables and Loads 9

Test Station Insertion Loss..... 9

Result Summary..... 10

Test Result..... 11

1 AGC Threshold..... 11

2 Occupied Bandwidth..... 13

3 Out of Band Rejection 25

4 Input-Versus-Output Signal Comparison 29

5 Input/Output Power and Amplifier/Booster Gain..... 50

6 Out-Of-Band / Out-Of-Block Intermodulation and Spurious Emissions..... 52

7 Noise Figure 71

8 Frequency Stability..... 73

9 Radiated Emissions – Enclosure 74

10 Conducted Emissions at AC Power Port 82

Annex 86

Annex 1 – Measurement Uncertainties 86


Annex 2 - ISO 17025 ACCREDITATION CERTIFICATE 86

Prepared by: LabTest Certification Inc.
Date Issued: 2024-03-18
Project No.: 22063

Client: Avari Wireless Inc.
Report No.: 20.01.22063-1
Revision No.: 0

TEST REPORT_FCC Part 15 Subpart B, FCC Part 90

Private Land Mobile Services

Report Reference No.:	20.01.22063-1	
Report Revision History.:	Rev. 0	
Compiled by (+ signature).....	Jack Qin	
Approved by (+ signature).....	Zara Vali	
Date of issue	2024-03-18	
Total number of pages	87	
FCC Site Registration No.:	721268	
IC Site Registration No.:	5970A-2	
Testing Laboratory.....:	LabTest Certification Inc.	
Address.....:	Unit 3128-20800 Westminster HWY, Richmond, B.C. V6V 2W3 Canada	
Applicant's name	Avari Wireless Inc.	
Address.....:	1400 112 th Ave SE, Ste 100, Bellevue, WA98004	
Manufacture's Name	Avari Wireless Inc.	
Address	1400 112th Ave SE, Ste 100 Bellevue, WA 98004	
Test specification:		
Standards.....:	➤ FCC Part 15 Radio Frequency Devices, Subpart B - Unintentional Radiators - Class B ➤ FCC Part 90 Private Land Mobile Radio Services	
Test procedure.....:	➤ KDB 935210 D05 Indus Booster Basic Meas v01r04 ➤ ANSI/TIA-603- E-2016 ➤ ANSI C63.4:2014 ➤ ANSI C63.26-2015	
Test item description :		
Trade Mark.....:	RU37™	
Model/Type reference	RU37-3-PS-BFH-21-5N-D0-1	
Serial Number	10911040E01BD3002	
FCC ID	2BA6ERU373PSBFH21A	
Possible test case verdicts:		

Prepared by: LabTest Certification Inc.
Date Issued: 2024-03-18
Project No.: 22063

Client: Avari Wireless Inc.
Report No.: 20.01.22063-1
Revision No.: 0

- test case does not apply to the test object	N/A
- test object does meet the requirement	P (Pass)
- test object does not meet the requirement.....	F (Fail)

Revision History

Revision	Date	Reason For Change	Author(s)
0	2024-03-18	Initial	Jack Qin

Device Under Test Description

Application for	PS 800/450/150 Remote Unit, Tri Band Medium Power DAS
Passing Transmit Frequency	851 MHz – 869 MHz 450 MHz – 480 MHz 152 MHz – 174 MHz
Operating Transmit Frequency FCC	851 MHz – 869 MHz 450 MHz – 454 MHz 456 MHz – 462.5375 MHz 462.7375 MHz – 467.5375 MHz 467.7375 MHz – 512 MHz 150.8 MHz – 156.2475 MHz 157.1875 MHz – 161.575 MHz 161.775 MHz – 161.9625 MHz 162. 0375 MHz – 173.4 MHz
Passing Receive Frequency	806 MHz – 824 MHz 450 MHz – 480 MHz 152 MHz – 174 MHz
Operating Receive Frequency FCC	806 MHz – 824 MHz 450 MHz – 454 MHz 456 MHz – 462.5375 MHz 462.7375 MHz – 467.5375 MHz 467.7375 MHz – 512 MHz 150.8 MHz – 156.2475 MHz 157.1875 MHz – 161.575 MHz 161.775 MHz – 161.9625 MHz 162. 0375 MHz – 173.4 MHz
Number of Channels	Up to 64 channels
Rated RF Output (e.i.r.p.).....	37 dBm

Prepared by: LabTest Certification Inc.
Date Issued: 2024-03-18
Project No.: 22063

Client: Avari Wireless Inc.
Report No.: 20.01.22063-1
Revision No.: 0

Modulation Type	P25 Phase I C4FM, CQPSK; P25 Phase II HDQPSK on full band of Band 800, Band 450 and Band 150 FM on Band 800 between 851 MHz – 869 MHz only;
Equipment mobility	Fixed
Operating condition	-40 to +50 °C
Mass of equipment (g)	< 27,700g
Dimensions (W X D X H)	410 mm X 230 mm X 696 mm
Supply Voltage:	<u>48V</u> DC <u>7.1</u> Amps
If DC Power:	☐ Internal Power Supply ☒ External Power Supply ☐ Battery ☐ Nickel Cadmium ☐ Alkaline ☐ Nickel-Metal Hydride ☐ Lithium-Ion ☐ Other

Program details

Testing Facility by procedure:		
☒	Radiated Measurement	LabTest Certification Inc.
Testing location/ address		Unit 3128-20800 Westminster HWY, Richmond, B.C. V6V 2W3 Canada
☒	Conducted Measurement:	LabTest Certification Inc.
Testing location/ address		Unit 3128-20800 Westminster HWY, Richmond, B.C. V6V 2W3 Canada

Summary of testing:	
Tests performed (name of test and test clause): Conducted Measurement Radiated Emissions on Enclosure	Testing location: Bench top, Richmond In SAC, Richmond
The tests indicated in Test Summary were performed on the product constructed as described below. The test sections are the verbatim text from the actual data sheets used during the investigation. These test sections include the test name, the specified test Method, a list of the actual Test Equipment Used, documentation Photos, Results and raw Data. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted. Based on the results of our investigation, we have concluded the product tested complies with the requirements of the standard(s) indicated. The results obtained in this test report pertain only to the item(s) tested. LabTest does not make any claims of compliance for samples or variants which were not tested.	

Description of Equipment Under Test (EUT) and Variant Models

Description:

The RU37 800PS/450PS/150 PS is a tri-band remote unit that provides at least 5 W of output power on each band. The tri-band unit supports up to 3 bands in a sealed type 2 chassis for Class A operation. On the downlink path the RU37 PS remote receives an aggregated stream of digitized RF signals from an DMU PS, which it then converts into analog RF signals. Depending on the frequency band, the signal is amplified in the RF module and then sent out through simplex RF ports to an external filter.

On the UL path the RU37 PS remote receives analog RF signals for the RF band, from an external filter. The RF signals are converted into a digital data stream and then delivered over optical fiber to an DMU PS. The RU37 PS remote also accommodates a 1 Gbps Ethernet backhaul for transporting the data from nearby IP devices such as security cameras and Wi-Fi access points.

The intentional transmitter only exists in the downlink path and hence the EMC tests in this report dedicated to the downlink emission.

In order to build up a complete signal booster system, the DMU PS was connected as the Auxiliary device. The DMU PS does not have an antenna port, where the signal was injected and ejected via coaxial cables.

EUT Picture



Variant Models:

The following variant models were not tested as part of this evaluation but have been identified by the manufacturer as being electrically identical models, depopulated models, or with reasonable similarity to the model(s) tested. LabTest does not make any claims of compliance for samples or variants which were not tested.

The variant models of RU37-3-PS-BFH-21-5N-D0-1 are listed as follows:

Tri Band

1. RU33-3-PS-BFH-21-5N-D0-1

Dual Band

1. RU37-2-PS-BF-21-3N-D0-1
2. RU33-2-PS-BF-21-3N-D0-1
3. RU37-2-PS-BH-21-3N-D0-1
4. RU33-2-PS-BH-21-3N-D0-1
5. RU37-2-PS-FH-21-4N-D0-1
6. RU33-2-PS-FH-21-4N-D0-1

Single Band

1. RU37-1-PS-B-21-1N-D0-1
2. RU33-1-PS-B-21-1N-D0-1
3. RU37-1-PS-F-21-2N-D0-1
4. RU33-1-PS-F-21-2N-D0-1
5. RU37-1-PS-H-21-2N-D0-1
6. RU33-1-PS-H-21-2N-D0-1

Client Equipment Used During Test

Use*	Product Type	Manufacturer	Model	Comments
EUT	<i>RU37, 800PS, 450PS, 150 PS</i>	Avari Wireless Inc.	VL-RU37-3-PS-BFH-21-5N-D0-1	EUT where the RF (I/O) antenna is attached via duplexers/multiplexer when necessary.
AE1	<i>DMU, 800PS, 450PS, 150PS</i>	Avari Wireless Inc.	VL-DMU-3-PS-BFH-1-6N-D-1F	Auxiliary equipment, which is the front end of system interfaced to Base Station.
AE2	Element Manager (DMC)	Avari Wireless Inc.	EM-1A	Auxiliary equipment provides the configuration and control interface to <i>DMU</i> and <i>RU37</i> .
AE3	Power Supply	MeanWell	HGL-480H-48	AC to DC Converter, I/P: 120VAC, 60Hz, 5.5A O/P: +48VDC, 480W
Abbreviations: EUT - Equipment Under Test, AE - Auxiliary/Associated Equipment, or SIM - Simulator (Not Subjected to Test)				

Software and Firmware

Use*	Description	Version
EUT	Software installed	5.6.2-0.5763
AE1	Software installed	5.6.2-0.5763
AE2	Software installed	5.6.2-1359
Abbreviations: EUT - Equipment Under Test, AE - Auxiliary/Associated Equipment, or SIM - Simulator (Not Subjected to Test)		

Input/Output Ports

Port #	Name	Type*	Cable Max. >3m	Cable Shielded	Comments
1	DC Power Port	DC	No	No	Dual feed 48 VDC Assembly
2	5 * RF Input/Output Ports	I/O	No	No	N-Type Coaxial
3	2 * Optical Fibre I/O Ports	I/O	No	No	LC/UPC Duplex
4	2 * TP	TP	No	No	RJ-45

*Note: AC = AC Power Port DC = DC Power Port N/E = Non-Electrical
I/O = Signal Input or Output Port (Not Involved in Process Control)
TP = Telecommunication Ports

Power Interface

Mode #	Voltage (V)	Current (A)	Power (W)	Frequency (DC/AC-Hz)	Phases (#)	Comments
1	48	7.1	340	DC	-	

EUT Operation Modes

Mode #	Description
1	UL and DL transmission and receiving ON

EUT Configuration Modes

Mode #	Description
1	DMU maximum input threshold set to -10 dBm, uplink attenuation set to 0dB; RU37 uplink and downlink attenuation set to 0dB.

Test Equipment Verified for function

Model #	Description	Checked Function	Results
KT-N9038A	Spectrum Analyzer	Frequency and Amplitude	Connected 50MHz and -20 dBm Ref_signal and checked OK
JB1	Antenna, 30 to 2000MHz	Checked structure	Normal – no damage
SAS-571	Antenna, 1 to 18GHz	Checked structure	Normal – no damage
AL-130	Antenna, 9kHz to 30MHz	Checked structure	Normal – no damage
KT-N5172B	Signal Generator	Frequency, Amplitude and Modulation	Within MFR Specs
KT-N9010A	Spectrum Analyzer	Frquency and Amplitude	Within MFR Specs

Test Station Photo



Test Station Cables and Loads

Model #	Manufacture	Description
3 x TM8-N1S1-60	MegaPhase	N male to SMA male coaxial cable in 60 inches
1 x 49-30-34	Aeroflex	30dB 25W attenuator

Test Station Insertion Loss

	Band 800	Band 450	Band 150
DL Transmitter	33.6 dB	31.8 dB	31.3 dB
UL Receiver	0.6 dB	0.5 dB	0.3 dB

Result Summary

The Compliance Status is a judgment based on the direct measurements and calculated highest emissions to appropriate standard limits. Measurement uncertainty values, provided on calibration certificates, were not be used in the judgment of the final status of compliance.


Test Item	Regulation	Measurement Method	Result
AGC Threshold	FCC KDB 935210 D05, v01r03, Section 4.2	ANSI TIA-603- E-2016	PASS
Out of Band Rejection	FCC KDB 935210 D05, v01r03, Section 4.3	ANSI TIA-603- E-2016	PASS
Input-versus-output Signal Comparison	FCC KDB 935210 D05, v01r03, Section 4.4	ANSI TIA-603- E-2016	PASS
Input/output Power and Amplifier/Booster Gain	FCC KDB 935210 D05, v01r03, Section 4.5	ANSI TIA-603- E-2016	PASS
Noise Figure	FCC KDB 935210 D05, v01r03, Section 4.6	ANSI TIA-603- E-2016	PASS
Measuring out-of-band/out-of-block (including intermodulation) and spurious emissions	FCC KDB 935210 D05, v01r03, Section 4.7	ANSI TIA-603- E-2016	PASS
Frequency stability	FCC KDB 935210 D05, v01r03, Section 4.8	ANSI TIA-603- E-2016	PASS
Spurious emissions radiated measurements	FCC KDB 935210 D05, v01r03, Section 4.9	ANSI C63.4:2014	PASS
Radiated Emissions	FCC Part 15/B	ANSI C63.4, CISPR 16-2-1	PASS
Conducted Emissions at AC Main	FCC Part 15/B	ANSI C63.4, CISPR 16-2-1	PASS

Test Result

1 AGC Threshold

Governing Doc	FCC Part 2 2.1046(a) FCC Part 90.219(d)	Room Temperature (°C)	20.5		
Test Procedure	ANSI/TIA-603- E-2016; FCC KDB 935210 D05, v01r03;	Relative Humidity (%)	38.6		
Test Location	Richmond	Barometric Pressure (kPa)	101.8		
Test Engineer	Jack Qin	Date	July 11, 2023		
EUT Voltage	☒ +48VDC ☐ 120VAC @ 60Hz				
Test Equipment Used	Manufacturer	Model	Serial Number	Calibration date	Calibration due
Signal Generator	Keysight	N5172B	MY53050270	Oct 9, 2021	Oct 9, 2023
Spectrum Analyzer	Keysight	N9010A	MY50520285	Oct 11, 2021	Oct 11, 2023
Frequency Range:	☒ 851 MHz – 869 MHz; ☒ 450 MHz – 480 MHz; ☒ 152 MHz – 174 MHz				
Detector:	☒ Peak				
Type of Facility:	☒ Test bench				
Distance:	☒ Direct				
Arrangement of EUT:	☒ Table-top only ☐ Floor-standing only ☐ Rack Mounted				
Output Power is less than or equal 36.98 dBm in band 800, less than or equal 37.04 dBm in band 450, and less than or equal 37.03 dBm in band 150.					
Compliant ☒ Non-Compliant ☐ Not Applicable ☐					

Test Setup

Description of test set-up:
Output power is measured by connecting a spectrum analyzer to RF output connector of EUT via 30dB Attenuator. With a nominal input power and the amplifier properly adjusted the RF output is measured. The EUT was set to Operation Mode #1 with configuration Mode #1 . The maximum output power is measured when the Automatic Level Control (ALC) starting to compress the power and hold to a constant level.


Prepared by: LabTest Certification Inc.
Date Issued: 2024-03-18
Project No.: 22063

Client: Avari Wireless Inc.
Report No.: 20.01.22063-1
Revision No.: 0

Test Data

Frequency Range (MHz)	Frequency (MHz)	Input Power Trip ALC (dBm)	Output Power (dBm)	Output Power (Watt)
800PS 851 - 869	851.025	-10.6	36.98	4.99
	860	-11.6	36.91	4.91
	868.975	-11.0	36.91	4.91
450PS 450 - 480	450.025	-10.2	36.91	4.91
	465	-12.2	37.04	5.06
	479.975	-12.0	37.00	5.01
150PS 152 - 174	152.025	-11.0	37.03	5.05
	163	-11.2	36.98	4.99
	173.975	-10.6	37.00	5.01

2 Occupied Bandwidth

Governing Doc	FCC Part 2 2.1049	Room Temperature (°C)	20.5
Test Procedure	ANSI/TIA-603- E-2016; FCC KDB 935210 D05, v01r03	Relative Humidity (%)	38.6
Test Location	Richmond	Barometric Pressure (kPa)	101.8
Test Engineer	Jack Qin	Date	July 11, 2023
EUT Voltage	☒ +48VDC ☐ 120VAC @ 60Hz		
Test Equipment Used	Manufacturer	Model	Serial Number
Signal Generator	Keysight	N5172B	MY53050270
Spectrum Analyzer	Keysight	N9010A	MY50520285
Calibration date	Oct 9, 2021		
Calibration due	Oct 9, 2023		
Frequency Range:	☒ 806 MHz – 824 MHz; ☒ 799 MHz – 805 MHz; ☒ 450 MHz – 470 MHz		
Detector:	☒ Peak		
Type of Facility:	☒ Test bench		
Distance:	☒ Direct		
Arrangement of EUT:	☒ Table-top only ☐ Floor-standing only ☐ Rack Mounted		
Output signal has an occupied channel bandwidth less than the designated channel bandwidth on any location on the operating band. - OBW C4FM < 12.5 kHz - OBW CQPSK < 6.25 kHz - OBW HDQPSK < 12.5 kHz - OBW 4 kHz FM with 1kHz deviation < 12.5 kHz			
Compliant ☒ Non-Compliant ☐ Not Applicable ☐			

Test Setup

Description of test set-up:

Occupied Bandwidth is measured by connecting a Spectrum Analyzer to the RF output connector via 30dB attenuator. The required measurement resolution bandwidth (RBW) is 1% of the emission bandwidth. 99% energy rule was applied to measure the occupied channel bandwidth. The emission bandwidth is measured as the width of the signal between two frequency points on the channel edge, outside of which the transmission power is attenuated at least 26dB below the transmitter output power

The EUT was set to **Operation Mode #1 with configuration Mode #1.**


The occupied bandwidth of UL output is measured under one input conditions:

- Nominal: with input 0.5dB below AGC threshold




Test Data


800PS CQPSK Signal at 868.975 MHz




800PS CQPSK Signal at 860 MHz




800PS CQPSK Signal at 851.025 MHz




800PS C4FM Signal at 868.975 MHz




800PS C4FM Signal at 860 MHz




800PS C4FM Signal at 851.025 MHz




800PS HDQPSK Signal at 868.975 MHz




800PS HDQPSK Signal at 860 MHz




800PS HDQPSK Signal at 851.025 MHz




800PS FM Signal at 868.975 MHz




800PS FM Signal at 860 MHz




800PS FM Signal at 851.025 MHz




800PS FM Signal at 868.975 MHz ALC




800PS FM Signal at 860 MHz ALC




800PS FM Signal at 851.025 MHz ALC




450PS CQPSK Signal at 479.975 MHz




450PS CQPSK Signal at 465 MHz




450PS CQPSK Signal at 450.025 MHz




450PS C4FM Signal at 479.975 MHz




450PS C4FM Signal at 465 MHz




450PS C4FM Signal at 450.025 MHz




450PS HDQPSK Signal at 479.975 MHz




450PS HDQPSK Signal at 465 MHz




450PS HDQPSK Signal at 450.025 MHz




150PS CQPSK Signal at 173.975 MHz




150PS CQPSK Signal at 163 MHz




150PS CQPSK Signal at 152.025 MHz




150PS C4FM Signal at 173.975 MHz




150PS C4FM Signal at 163 MHz




150PS C4FM Signal at 152.025 MHz




150PS HDQPSK Signal at 173.975 MH



150PS HDQPSK Signal at 163 MHz



150PS HDQPSK Signal at 152.025 MH



3 Out of Band Rejection

Governing Doc	FCC Part 2 2.1046(a) FCC Part 90.219(d)	Room Temperature (°C)	20.5		
Test Procedure	ANSI/TIA-603- E; FCC KDB 935210 D05, v01r03	Relative Humidity (%)	38.6		
Test Location	Richmond	Barometric Pressure (kPa)	101.8		
Test Engineer	Jack Qin	Date	July 11, 2023		
EUT Voltage	☒ +48VDC ☐ 120VAC @ 60Hz				
Test Equipment Used	Manufacturer	Model	Serial Number	Calibration date	Calibration due
Signal Generator	Keysight	N5172B	MY53050270	Oct 9, 2021	Oct 9, 2023
Spectrum Analyzer	Keysight	N9010A	MY50520285	Oct 11, 2021	Oct 11, 2023
Frequency Range:	☒ Product Passband $\pm$ 250%				
Detector:	☒ Peak				
RBW/VBW:	☒ 1 to 5% of the EUT passband / $\geq 3 \times$ RBW				
Type of Facility:	☒ Tabletop				
Distance:	☒ Direct				
Compliant ☒ Non-Compliant ☐ Not Applicable ☐					

Test Setup

Description of test set-up:


The procedure used was ANSI/TIA-603-E-2016 and FCC KDB 935210 D05 Indus Booster Basic Meas v01r03. The signal booster was set to maximum gain. A swept CW signal was set to the range of $\pm 250\%$ of the product pass band. The CW amplitude was set to 3 dB below the AGC threshold so that the ALC should not activate throughout the test. After the max-hold sweep trace was completed, a marker was set to the peak amplitude, and a 20dB bandwidth was measured between two additional markers fall 20 dB from the peak.

The EUT was set to **Operation Mode #1 with configuration Mode #1.**




Test Data


800PS at 868.975 MHz




800PS at 860 MHz




800PS at 851.025 MHz




450PS at 479.975 MHz




450PS at 465 MHz




450PS at 450.025 MHz




150PS at 173.975 MHz



150PS at 163 MHz



150PS at 152.025 MHz



4 Input-Versus-Output Signal Comparison

Governing Doc	FCC Part 90.210 (j) (h) (g) (c) (d) and (e)	Room Temperature (°C)	20.5
Test Procedure	ANSI/TIA-603- E; FCC KDB 935210 D05, v01r03	Relative Humidity (%)	38.6
Test Location	Richmond	Barometric Pressure (kPa)	101.8
Test Engineer	Jack Qin	Date	July 11, 2023
EUT Voltage	☒ +48VDC ☐ 120VAC @ 60Hz		
Test Equipment Used	Manufacturer	Model	Serial Number
Signal Generator	Keysight	N5172B	MY53050270
Spectrum Analyzer	Keysight	N9010A	MY50520285
Calibration date	Oct 9, 2021		
Calibration due	Oct 9, 2023		
Frequency Range:	☒ 851 MHz – 869 MHz; ☒ 450 MHz – 480 MHz; ☒ 152 MHz – 174 MHz		
Detector:	☒ Peak		
RBW/VBW:	☒ 100 Hz		
Type of Facility:	☒ Testbench		
Distance:	☒ direct connect		
Arrangement of EUT:	☒ Table-top only ☐ Floor-standing only ☐ Rack Mounted		
Signal of all types of modulation is contained within the emission mask.			
Compliant ☒ Non-Compliant ☐ Not Applicable ☐			

Test Setup

Description of test set-up:

Spectrum Emission Mask is measured by connecting a Spectrum Analyzer to the RF output connector. The input power was adjusted to produce maximum output power on the antenna port. The reference level was measured with integrated BW of the designated channel BW. The emission was measured with RBW 100 Hz.


The EUT was set to **Operation Mode #1 with configuration Mode #1.**

```


    graph LR
        VSG[Vector Signal Generator] --> AE1[AE1]
        AE1 -- Fiber --> EUT[EUT]
        EUT --> Att[30dB Attenuator]
        Att --> SA[Spectrum Analyzer]
    
```

Test Data

800PS CQPSK Signal at 868.975MHz




800PS CQPSK Signal at 860MHz




800PS CQPSK Signal at 851.025MHz




800PS C4FM Signal at 868.975MHz




800PS C4FM Signal at 860MHz




800PS C4FM Signal at 851.025MHz




800PS HDQPSK Signal at 868.975MHz




800PS HDQPSK Signal at 860MHz




800PS HDQPSK Signal at 851.025MHz




800PS FM Signal at 868.975MHz




800PS FM Signal at 860MHz




800PS FM Signal at 851.025MHz




800PS CQPSK Signal at 868.975MHz ALC




800PS CQPSK Signal at 860MHz ALC




800PS CQPSK Signal at 851.025MHz ALC




800PS C4FM Signal at 868.975MHz ALC




800PS C4FM Signal at 860MHz ALC




800PS C4FM Signal at 851.025MHz ALC




800PS HDQPSK Signal at 868.975MHz ALC




800PS HDQPSK Signal at 860MHz ALC




800PS HDQPSK Signal at 851.025MHz ALC




800PS FM Signal at 868.975MHz ALC




800PS FM Signal at 860MHz ALC




800PS FM Signal at 851.025MHz ALC




450PS CQPSK Signal at 479.975MHz




450PS CQPSK Signal at 465MHz




450PS CQPSK Signal at 450.025MHz




450PS C4FM Signal at 479.975MHz




450PS C4FM Signal at 465MHz




450PS C4FM Signal at 450.025MHz




450PS HDQPSK Signal at 479.975MHz




450PS HDQPSK Signal at 465MHz




450PS HDQPSK Signal at 450.025MHz




450PS CQPSK Signal at 479.975MHz ALC




450PS CQPSK Signal at 465MHz ALC




450PS CQPSK Signal at 450.025MHz ALC




450PS C4FM Signal at 479.975MHz ALC




450PS C4FM Signal at 465MHz ALC




450PS C4FM Signal at 450.025MHz ALC




450PS HDQPSK Signal at 479.975MHz ALC




450PS HDQPSK Signal at 465MHz ALC



450PS HDQPSK Signal at 450.025MHz ALC




150PS CQPSK Signal at 173.975MHz




150PS CQPSK Signal at 163MHz




150PS CQPSK Signal at 152.025MHz



150PS C4FM Signal at 173.975MHz



150PS C4FM Signal at 163MHz



150PS C4FM Signal at 152.025MHz

