

## FCC TEST REPORT FOR

Zaidtek Electronic Technology (Xiamen) Co., Ltd.


Ergonomic Wireless Mouse

Test Model: HM8190

|                                |   |                                                                                                                               |
|--------------------------------|---|-------------------------------------------------------------------------------------------------------------------------------|
| Prepared for                   | : | Zaidtek Electronic Technology (Xiamen) Co., Ltd.                                                                              |
| Address                        | : | No. 29-2 XinLe Road, Haicang District, Xiamen, China                                                                          |
| Prepared by                    | : | Shenzhen LCS Compliance Testing Laboratory Ltd                                                                                |
| Address                        | : | 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,<br>Shajing Street, Baoan District, Shenzhen, 518000, China |
| Tel                            | : | (+86)755-82591330                                                                                                             |
| Fax                            | : | (+86)755-82591332                                                                                                             |
| Web                            | : | www.LCS-cert.com                                                                                                              |
| Mail                           | : | webmaster@LCS-cert.com                                                                                                        |
| Date of receipt of test sample | : | February 11, 2025                                                                                                             |
| Number of tested samples       | : | 2                                                                                                                             |
| Sample No.                     | : | A250206023-1, A250206023-2                                                                                                    |
| Sample number                  | : | Prototype                                                                                                                     |
| Date of Test                   | : | February 11, 2025 ~ February 25, 2025                                                                                         |
| Date of Report                 | : | February 26, 2025                                                                                                             |



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen,  
518000, China  
Tel: (+86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity

**FCC TEST REPORT****FCC CFR 47 PART 15 C (15.249)****Report Reference No. .... : LCSA02075130EA**

Date of Issue..... : February 26, 2025

**Testing Laboratory Name..... : Shenzhen LCS Compliance Testing Laboratory Ltd.**

Address..... : 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Testing Location/ Procedure..... : Full application of Harmonised standards ■  
Partial application of Harmonised standards □  
Other standard testing method □**Applicant's Name..... : Zaidtek Electronic Technology (Xiamen) Co., Ltd.**

Address..... : No. 29-2 XinLe Road, Haicang District, Xiamen, China

**Test Specification**

Standard..... : FCC CFR 47 PART 15 C(15.249) / ANSI C63.10: 2013

Test Report Form No..... : TRF-4-E-189 A/0

TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

**Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test Item Description..... : Ergonomic Wireless Mouse**

Trade Mark..... : Amazon

Test Model..... : HM8190

Ratings..... : DC 3.0V by 2\*AAA Batteries

**Result ..... : Positive****Compiled by:**

Li Huan/ Administrator

**Supervised by:**

Jack Liu/ Technique principal

**Approved by:**

Gavin Liang/ Manager




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity

**FCC -- TEST REPORT**

|                                                |                                           |
|------------------------------------------------|-------------------------------------------|
| <b>Test Report No. :</b> <b>LCSA02075130EA</b> | <u>February 26, 2025</u><br>Date of issue |
|------------------------------------------------|-------------------------------------------|

|                          |                                                           |
|--------------------------|-----------------------------------------------------------|
| Test Model.....          | : HM8190                                                  |
| EUT.....                 | : Ergonomic Wireless Mouse                                |
| <b>Applicant.....</b>    | <b>: Zaidtek Electronic Technology (Xiamen) Co., Ltd.</b> |
| Address.....             | : No. 29-2 XinLe Road, Haicang District, Xiamen, China    |
| Telephone.....           | : /                                                       |
| Fax.....                 | : /                                                       |
| <b>Manufacturer.....</b> | <b>: Zaidtek Electronic Technology (Xiamen) Co., Ltd.</b> |
| Address.....             | : No. 29-2 XinLe Road, Haicang District, Xiamen, China    |
| Telephone.....           | : /                                                       |
| Fax.....                 | : /                                                       |
| <b>Factory.....</b>      | <b>: Zaidtek Electronic Technology (Xiamen) Co., Ltd.</b> |
| Address.....             | : No. 29-2 XinLe Road, Haicang District, Xiamen, China    |
| Telephone.....           | : /                                                       |
| Fax.....                 | : /                                                       |


|                    |                 |
|--------------------|-----------------|
| <b>Test Result</b> | <b>Positive</b> |
|--------------------|-----------------|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity




Revision History

| Report Version | Issue Date        | Revision Content | Revised By |
|----------------|-------------------|------------------|------------|
| 000            | February 26, 2025 | Initial Issue    | --         |
|                |                   |                  |            |
|                |                   |                  |            |




Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity



## TABLE OF CONTENTS

|                                               |           |
|-----------------------------------------------|-----------|
| <b>1. GENERAL INFORMATION</b>                 | <b>6</b>  |
| 1.1 Description of Device (EUT)               | 6         |
| 1.2. Support Equipment List                   | 7         |
| 1.3. External I/O                             | 7         |
| 1.4. Description of Test Facility             | 7         |
| 1.5. Statement of the measurement uncertainty | 7         |
| 1.6. Measurement Uncertainty                  | 8         |
| 1.7. Description of Test Modes                | 8         |
| <b>2. TEST METHODOLOGY</b>                    | <b>9</b>  |
| 2.1. EUT Configuration                        | 9         |
| 2.2. EUT Exercise                             | 9         |
| 2.3. General Test Procedures                  | 9         |
| <b>3. CONNECTION DIAGRAM OF TEST SYSTEM</b>   | <b>10</b> |
| 3.1. Justification                            | 10        |
| 3.2. EUT Exercise Software                    | 10        |
| 3.3. Special Accessories                      | 10        |
| 3.4. Block Diagram/Schematics                 | 10        |
| 3.5. Equipment Modifications                  | 10        |
| 3.6. Test Setup                               | 10        |
| <b>4. SUMMARY OF TEST RESULTS</b>             | <b>11</b> |
| <b>5. ANTENNA REQUIREMENT</b>                 | <b>12</b> |
| <b>6. POWER LINE CONDUCTED EMISSIONS</b>      | <b>13</b> |
| <b>7. RADIATED EMISSION MEASUREMENT</b>       | <b>14</b> |
| <b>8. RESULTS FOR BAND EDGE TESTING</b>       | <b>24</b> |
| <b>9. 20 DB BANDWIDTH MEASUREMENT</b>         | <b>30</b> |
| <b>10. LIST OF MEASURING EQUIPMENT</b>        | <b>32</b> |
| <b>11. TEST SETUP PHOTOGRAPHS OF THE EUT</b>  | <b>33</b> |
| <b>12. EXTERIOR PHOTOGRAPHS OF THE EUT</b>    | <b>33</b> |
| <b>13. INTERIOR PHOTOGRAPHS OF THE EUT</b>    | <b>33</b> |






## 1. GENERAL INFORMATION

### 1.1 Description of Device (EUT)

|                     |                              |
|---------------------|------------------------------|
| EUT                 | : Ergonomic Wireless Mouse   |
| Test Model          | : HM8190                     |
| Ratings             | : DC 3.0V by 2*AAA Batteries |
| Hardware Version    | : V1.0                       |
| Software Version    | : V7.C                       |
| 2.4G                | :                            |
| Frequency Range     | : 2403.65MHz-2479.65MHz      |
| Channel Number      | : 16 channels                |
| Modulation Type     | : GFSK                       |
| Antenna Description | : PCB Antenna, 1.16dBi(Max.) |





## 1.2. Support Equipment List

| Manufacturer | Description | Model | Serial Number | Certificate |
|--------------|-------------|-------|---------------|-------------|
| ---          | ---         | ---   | ---           | ---         |

## 1.3. External I/O

| I/O Port Description | Quantity | Cable |
|----------------------|----------|-------|
| ---                  | ---      | ---   |

## 1.4. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.


Test Firm Registration Number: 254912.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

## 1.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.





## 1.6. Measurement Uncertainty

| Test Item                    | Frequency Range | Uncertainty | Note |
|------------------------------|-----------------|-------------|------|
| Radiation Uncertainty :      | 9KHz~30MHz      | ±3.10dB     | (1)  |
|                              | 30MHz~200MHz    | ±2.96dB     | (1)  |
|                              | 200MHz~1000MHz  | ±3.10dB     | (1)  |
|                              | 1GHz~26.5GHz    | ±3.80dB     | (1)  |
|                              | 26.5GHz~40GHz   | ±3.90dB     | (1)  |
| Conduction Uncertainty :     | 150kHz~30MHz    | ±1.63dB     | (1)  |
| Power disturbance :          | 30MHz~300MHz    | ±1.60dB     | (1)  |
| Occupied Channel Bandwidth : | 1GHz-40GHz      | ±5%         | (1)  |

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 1.7. Description of Test Modes

Operates in the unlicensed ISM Band at 2.4GHz. With basic data rate feature, the data rates can be up to 1 Mb/s by modulating the RF carrier using GFSK techniques. The EUT works in the X-axis, Y-axis, Z-axis. The following operating modes were applied for the related test items. All test modes were tested, only the result of the worst case was recorded in the report.


| Mode of Operations    | Channel | Frequency Range (MHz) |
|-----------------------|---------|-----------------------|
| GFSK                  | 1       | 2403.65               |
|                       | 9       | 2441.65               |
|                       | 16      | 2479.65               |
| For Radiated Emission |         |                       |
| Test Mode             | TX Mode |                       |

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be TX.

Channel List:

| Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) |
|-------------|-----------------|-------------|-----------------|-------------|-----------------|-------------|-----------------|
| 1           | 2403.65         | 5           | 2422.65         | 9           | 2441.65         | 13          | 2463.65         |
| 2           | 2407.65         | 6           | 2426.65         | 10          | 2445.65         | 14          | 2466.65         |
| 3           | 2414.65         | 7           | 2436.65         | 11          | 2453.65         | 15          | 2473.65         |
| 4           | 2419.65         | 8           | 2439.65         | 12          | 2459.65         | 16          | 2479.65         |





## 2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10: 2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd.

### 2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.249 under the FCC Rules Part 15 Subpart C.

### 2.3. General Test Procedures


#### 2.3.1 Conducted Emissions(N/A)

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

#### 2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz and 1.5 m above ground plane above 1GHz. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013





### 3. CONNECTION DIAGRAM OF TEST SYSTEM

#### 3.1. Justification

The system was configured for testing in a continuous transmit condition. Continuous transmitting was pre-programmed. It'll keep transmitting with modulated signal at the lowest channel by installing the batter. When press the "up" button, it'll move to the next channel. Repeat press "up" button, it'll transmitting at each of the channel used.

#### 3.2. EUT Exercise Software

Press the corresponding button, and change the channel.

#### 3.3. Special Accessories

N/A

#### 3.4. Block Diagram/Schematics

Please refer to the related document


#### 3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

#### 3.6. Test Setup

Please refer to the test setup photo.





#### 4. SUMMARY OF TEST RESULTS


| Applied Standard: FCC Part 15 Subpart C §15.249 |                                |           |
|-------------------------------------------------|--------------------------------|-----------|
| FCC Rules                                       | Description Of Test            | Result    |
| §15.203                                         | Antenna Requirement            | Compliant |
| §15.207(a)                                      | Power Line Conducted Emissions | N/A       |
| §15.205(a), §15.209(a), §15.249(a), §15.249(c)  | Radiated Emissions Measurement | Compliant |
| §15.249 (d)                                     | Band Edges Measurement         | Compliant |
| §15.215(c)                                      | 20 dB Bandwidth                | Compliant |

Remark:

N/A\* - Not Applicable for this device!!!



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity



## 5. ANTENNA REQUIREMENT

### 5.1. Standard Applicable

According to § 15.203 and RSS-Gen, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 5.2. Antenna Connected Construction


The EUT use PCB Antenna and maximum antenna gain is 2.499dBi, antenna cannot replacement, meets FCC Part §15.203 antenna requirement. Please see EUT photo for details.

### 5.3. Results

Compliance



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: [webmaster@lcs-cert.com](mailto:webmaster@lcs-cert.com) | Web: [www.lcs-cert.com](http://www.lcs-cert.com)  
Scan code to check authenticity



## 6. POWER LINE CONDUCTED EMISSIONS


### 6.1. Standard Applicable

According to §15.207 (a) & RSS-Gen § 8.8: For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

| Frequency Range (MHz) | Limits (dBμV) |          |
|-----------------------|---------------|----------|
|                       | Quasi-peak    | Average  |
| 0.15 to 0.50          | 66 to 56      | 56 to 46 |
| 0.50 to 5             | 56            | 46       |
| 5 to 30               | 60            | 50       |

\* Decreasing linearly with the logarithm of the frequency

### 6.2. Block Diagram of Test Setup



### 6.3. Test Results

The AC mains conducted disturbance is calculated by adding the 10dB Pulse Limiter and Cable Factor and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$CD \text{ (dB}\mu\text{V)} = RA \text{ (dB}\mu\text{V)} + PL \text{ (dB)} + CL \text{ (dB)}$$


|                                  |                                            |
|----------------------------------|--------------------------------------------|
| Where CD = Conducted Disturbance | CL = Cable Attenuation Factor (Cable Loss) |
| RA = Reading Amplitude           | PL = 10 dB Pulse Limiter Factor            |

### 6.4. Test Results

Not applicable.

The product is battery powered.





## 7. RADIATED EMISSION MEASUREMENT

### 7.1. Standard Applicable

According to FCC § 15.249: Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) and 15.249 limit in the table below has to be followed.

| Fundamental Frequency | Field Strength of fundamental (millivolts/meter) | Field Strength of harmonics (microvolts/meter) |
|-----------------------|--------------------------------------------------|------------------------------------------------|
| 902-928MHz            | 50                                               | 500                                            |
| 2400-2483.5MHz        | 50                                               | 500                                            |
| 5725-5875MHz          | 50                                               | 500                                            |
| 24.0-24.25GHz         | 250                                              | 2500                                           |

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009~0.490       | 2400/F(KHz)                       | 300                           |
| 0.490~1.705       | 24000/F(KHz)                      | 30                            |
| 1.705~30.0        | 30                                | 30                            |
| 30~88             | 100                               | 3                             |
| 88~216            | 150                               | 3                             |
| 216~960           | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

According to RSS-210 B.10:

The field strength of fundamental and harmonic emissions, measured at 3 m, shall not exceed 50 mV/m and 0.5 mV/m respectively.

The field strength limits shall be measured using an average detector, except for the fundamental emission in the frequency band 902-928 MHz, which is based on measurements using an International Special Committee on Radio Interference (CISPR) quasi-peak detector.

Emissions radiated outside of the specified frequency bands, except for harmonic emissions, shall be attenuated by at least 50 dB below the level of the fundamental emissions or to the general field strength limits listed in RSS-Gen, whichever is less stringent.

### 7.2. Instruments Setting

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter                        | Setting                                           |
|-------------------------------------------|---------------------------------------------------|
| Attenuation                               | Auto                                              |
| Start Frequency                           | 1000 MHz                                          |
| Stop Frequency                            | 10 <sup>th</sup> carrier harmonic                 |
| RB / VB (Emission in restricted band)     | 1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average |
| RB / VB (Emission in non-restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average |




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



| Receiver Parameter     | Setting                                    |
|------------------------|--------------------------------------------|
| Attenuation            | Auto                                       |
| Start ~ Stop Frequency | 9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG  |
| Start ~ Stop Frequency | 150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB/VB 120kHz/1MHz for QP   |

### 7.3. Test Procedure

#### 1) Sequence of testing 9 kHz to 30 MHz

##### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.


##### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.0 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

##### Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.





## 2) Sequence of testing 30 MHz to 1 GHz

### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.


### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.





### 3) Sequence of testing 1 GHz to 18 GHz

#### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.


#### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

#### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.





#### 4) Sequence of testing above 18 GHz

##### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.

##### Premeasurement:

- The antenna is moved spherical over the EUT in different polarizations of the antenna.


##### Final measurement:

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.





#### 7.4. Block Diagram of Test Setup




Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

#### 7.5 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.





## 7.6. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS \text{ (dBuV/m)} = RA \text{ (dBuV)} + AF \text{ (dB/m)} + CL \text{ (dB)} - AG \text{ (dB)}$$

|                           |                                            |
|---------------------------|--------------------------------------------|
| Where FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| RA = Reading Amplitude    | AG = Amplifier Gain                        |
| AF = Antenna Factor       |                                            |

## 7.7. Test Results of Radiated Emissions (9 KHz~30 MHz)

|               |         |          |       |
|---------------|---------|----------|-------|
| Temperature   | 23.8°C  | Humidity | 52.1% |
| Test Engineer | Can Kun |          |       |

| Freq.<br>(MHz) | Level<br>(dBuV) | Over Limit<br>(dB) | Over Limit<br>(dBuV) | Remark   |
|----------------|-----------------|--------------------|----------------------|----------|
| -              | -               | -                  | -                    | See Note |

### Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance}) \text{ (dB)}$ ;

Limit line = specific limits (dBuV) + distance extrapolation factor.

## 7.8. Test Results of Radiated Emissions (30 MHz – 1000 MHz)


|               |         |          |       |
|---------------|---------|----------|-------|
| Temperature   | 23.8°C  | Humidity | 52.1% |
| Test Engineer | Can Kun |          |       |





Vertical

70.0 dBuV/m



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 38.4809         | 49.21          | -17.62        | 31.59          | 40.00          | -8.41       | QP       |
| 2   | 51.6616         | 41.72          | -17.35        | 24.37          | 40.00          | -15.63      | QP       |
| 3   | 99.5281         | 40.98          | -18.21        | 22.77          | 43.50          | -20.73      | QP       |
| 4   | 210.0482        | 43.07          | -17.14        | 25.93          | 43.50          | -17.57      | QP       |
| 5   | 381.2487        | 42.93          | -14.66        | 28.27          | 46.00          | -17.73      | QP       |
| 6   | 801.7863        | 43.11          | -9.89         | 33.22          | 46.00          | -12.78      | QP       |




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China


Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Horizontal

70.0 dBuV/m



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 38.4809         | 41.19          | -17.13        | 24.06          | 40.00          | -15.94      | QP       |
| 2   | 70.5836         | 37.79          | -19.12        | 18.67          | 40.00          | -21.33      | QP       |
| 3   | 119.0180        | 39.24          | -18.96        | 20.28          | 43.50          | -23.22      | QP       |
| 4   | 199.2855        | 47.08          | -18.58        | 28.50          | 43.50          | -15.00      | QP       |
| 5   | 345.5952        | 48.49          | -14.04        | 34.45          | 46.00          | -11.55      | QP       |
| 6   | 810.2654        | 39.33          | -9.14         | 30.19          | 46.00          | -15.81      | QP       |

Note:

1). Pre-scan all modes and recorded the worst case results in this report (GFSK-2410MHz).

2). Emission level (dBuV/m) = 20 log Emission level (uV/m).

3). Level = Reading + Factor, Margin = Level – Limit,

Factor = Antenna Factor + Cable Loss - Preamp Factor




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## 7.8. Results for Radiated Emissions (1 – 26 GHz)

| Field Strength of Fundamental (TX-2403.65 MHz) |      |                             |                     |                    |        |
|------------------------------------------------|------|-----------------------------|---------------------|--------------------|--------|
| Frequency (MHz)                                | Pol. | Measure Result (PK, dBuV/m) | Peak Limit (dBuV/m) | AVG Limit (dBuV/m) | Result |
| 2403.65                                        | H    | 86.29                       | 114                 | 94                 | Pass   |
| 2403.65                                        | V    | 85.29                       | 114                 | 94                 | Pass   |

## Channel 1 / 2403.65 MHz

| Freq. MHz | Reading Level dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4807.30   | 59.30              | 33.06          | 35.04        | 3.94         | 61.26           | 74.00        | -12.74    | Peak    | Horizontal |
| 4807.30   | 44.04              | 33.06          | 35.04        | 3.94         | 46.00           | 54.00        | -8.00     | Average | Horizontal |
| 4807.30   | 55.04              | 33.06          | 35.04        | 3.94         | 57.00           | 74.00        | -17.00    | Peak    | Vertical   |
| 4807.30   | 43.87              | 33.06          | 35.04        | 3.94         | 45.83           | 54.00        | -8.17     | Average | Vertical   |

## Field Strength of Fundamental (TX-2441.65 MHz)

| Frequency (MHz) | Pol. | Measure Result (PK, dBuV/m) | Peak Limit (dBuV/m) | AVG Limit (dBuV/m) | Result |
|-----------------|------|-----------------------------|---------------------|--------------------|--------|
| 2441.65         | H    | 84.98                       | 114                 | 94                 | Pass   |
| 2441.65         | V    | 85.09                       | 114                 | 94                 | Pass   |

## Channel 9/ 2441.65 MHz

| Freq. MHz | Reading Level dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4883.30   | 54.82              | 33.16          | 35.15        | 3.96         | 56.79           | 74.00        | -17.21    | Peak    | Horizontal |
| 4883.30   | 41.59              | 33.16          | 35.15        | 3.96         | 43.56           | 54.00        | -10.44    | Average | Horizontal |
| 4883.30   | 57.80              | 33.16          | 35.15        | 3.96         | 59.77           | 74.00        | -14.23    | Peak    | Vertical   |
| 4883.30   | 41.18              | 33.16          | 35.15        | 3.96         | 43.15           | 54.00        | -10.85    | Average | Vertical   |

## Field Strength of Fundamental (TX-2479.65 MHz)

| Frequency (MHz) | Pol. | Measure Result (PK, dBuV/m) | Peak Limit (dBuV/m) | AVG Limit (dBuV/m) | Result |
|-----------------|------|-----------------------------|---------------------|--------------------|--------|
| 2479.65         | H    | 87.52                       | 114                 | 94                 | Pass   |
| 2479.65         | V    | 88.76                       | 114                 | 94                 | Pass   |

## Channel 16/ 2479.65 MHz

| Freq. MHz | Reading Level dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4959.30   | 59.14              | 33.26          | 35.14        | 3.98         | 61.24           | 74.00        | -12.76    | Peak    | Horizontal |
| 4959.30   | 45.62              | 33.26          | 35.14        | 3.98         | 47.72           | 54.00        | -6.28     | Average | Horizontal |
| 4959.30   | 55.05              | 33.26          | 35.14        | 3.98         | 57.15           | 74.00        | -16.85    | Peak    | Vertical   |
| 4959.30   | 44.67              | 33.26          | 35.14        | 3.98         | 46.77           | 54.00        | -7.23     | Average | Vertical   |

## Notes:

- 1). Measuring frequencies from 9 KHz - 10<sup>th</sup> harmonic (ex. 26GHz), at least have 20dB margin found between lowest internal used/generated frequency to 30 MHz.
- 2). Radiated emissions measured in frequency range from 9 KHz - 10<sup>th</sup> harmonic (ex. 26GHz) were made with an instrument using Peak detector mode.
- 3). 18~25 GHz at least have 20dB margin. No recording in the test report.
- 4). Measured Level = Reading Level + Factor, Margin = Measured Level – Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor




## 8. RESULTS FOR BAND EDGE TESTING

### 8.1. Standard Applicable

According to FCC §15.249 (d): Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

According to RSS-210 B.10 (b): Emissions radiated outside of the specified frequency bands, except for harmonic emissions, shall be attenuated by at least 50 dB below the level of the fundamental emissions or to the general field strength limits listed in RSS-Gen, whichever is less stringent.

### 8.2. Test Setup Layout



### 8.3. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of Spectrum Analyzer.


### 8.4. Test Procedures

#### 3) Sequence of testing 1 GHz to 18 GHz

##### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.



**Premeasurement:**

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

**Final measurement:**

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.


**8.5. Measuring Instruments and Setting**

|               |         |          |       |
|---------------|---------|----------|-------|
| Temperature   | 23.5°C  | Humidity | 52.1% |
| Test Engineer | Can Kun |          |       |

**PASS****Remark:**


1. *The other emission levels were very low against the limit.*
2. *The average measurement was not performed when the peak measured data under the limit of average detection.*
3. *Detector AV is setting spectrum/receiver. RBW=1MHz/VBW=330Hz/Sweep time=Auto/Detector=Peak;*
4. *Please refer to following test plots;*





Channel 1 / 2403.65 MHz

Horizontal



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 2310.000        | 53.53          | -10.42        | 43.11          | 74.00          | -30.89      | peak     |
| 2   | 2322.560        | 59.20          | -10.49        | 48.71          | 74.00          | -25.29      | peak     |
| 3   | 2357.720        | 56.46          | -10.66        | 45.80          | 74.00          | -28.20      | peak     |
| 4   | 2390.000        | 58.91          | -10.89        | 48.02          | 74.00          | -25.98      | peak     |
| 5   | 2400.000        | 56.81          | -10.96        | 45.85          | 74.00          | -28.15      | peak     |
| 6   | 2403.440        | 97.23          | -10.94        | 86.29          | 114.00         | -27.71      | peak     |




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com


Scan code to check authenticity



Channel 1 / 2403.65 MHz

Vertical

130.0 dBuV/m



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 2310.000        | 54.85          | -12.02        | 42.83          | 74.00          | -31.17      | peak     |
| 2   | 2335.280        | 57.22          | -11.93        | 45.29          | 74.00          | -28.71      | peak     |
| 3   | 2358.920        | 56.81          | -11.84        | 44.97          | 74.00          | -29.03      | peak     |
| 4   | 2390.000        | 57.13          | -11.73        | 45.40          | 74.00          | -28.60      | peak     |
| 5   | 2400.000        | 58.89          | -11.70        | 47.19          | 74.00          | -26.81      | peak     |
| 6   | 2403.080        | 96.98          | -11.69        | 85.29          | 114.00         | -28.71      | peak     |




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China


Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Channel 16/ 2479.65 MHz

Horizontal



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 2479.690        | 98.45          | -10.93        | 87.52          | 114.00         | -26.48      | peak     |
| 2   | 2483.500        | 61.52          | -10.96        | 50.56          | 74.00          | -23.44      | peak     |
| 3   | 2488.150        | 55.85          | -11.02        | 44.83          | 74.00          | -29.17      | peak     |
| 4   | 2492.080        | 55.44          | -11.06        | 44.38          | 74.00          | -29.62      | peak     |
| 5   | 2496.370        | 56.84          | -11.11        | 45.73          | 74.00          | -28.27      | peak     |
| 6   | 2500.000        | 52.70          | -11.14        | 41.56          | 74.00          | -32.44      | peak     |




Shenzhen LCS Compliance Testing Laboratory Ltd.


Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Channel 16/ 2479.65 MHz



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 2479.990        | 100.18         | -11.42        | 88.76          | 114.00         | -25.24      | peak     |
| 2   | 2483.500        | 58.55          | -11.40        | 47.15          | 74.00          | -26.85      | peak     |
| 3   | 2487.250        | 57.30          | -11.39        | 45.91          | 74.00          | -28.09      | peak     |
| 4   | 2491.180        | 56.34          | -11.37        | 44.97          | 74.00          | -29.03      | peak     |
| 5   | 2495.110        | 55.70          | -11.36        | 44.34          | 74.00          | -29.66      | peak     |
| 6   | 2500.000        | 54.18          | -11.34        | 42.84          | 74.00          | -31.16      | peak     |

Note: Due to the measure PK emission level less than the AV limit value. No necessary to take down the AV emission level.




## 9. 20 DB BANDWIDTH MEASUREMENT

### 9.1. Standard Applicable

§15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. In the case of intentional radiators operating under the provisions of subpart E, the emission bandwidth may span across multiple contiguous frequency bands identified in that subpart. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

### 9.2. Block Diagram of Test Setup



### 9.3. Test Procedure

Use the following spectrum analyzer settings:

Span = 4MHz

RBW = 30 KHz

VBW = 100 KHz

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity




## 9.4. Test Results

|               |         |          |       |
|---------------|---------|----------|-------|
| Temperature   | 23.5°C  | Humidity | 52.1% |
| Test Engineer | Can Kun |          |       |

| Test Result of 20dB Bandwidth Measurement |                      |               |
|-------------------------------------------|----------------------|---------------|
| Test Frequency (MHz)                      | 20dB Bandwidth (MHz) | Limit (MHz)   |
| 2403.65                                   | 2.035                | Non-Specified |
| 2441.65                                   | 2.026                | Non-Specified |
| 2479.65                                   | 2.030                | Non-Specified |

Remark:

1. Test results including cable loss;
2. Please refer following test plots;




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity




## 10. LIST OF MEASURING EQUIPMENT

| Item | Equipment                      | Manufacturer   | Model No.       | Serial No.      | Cal Date   | Due Date   |
|------|--------------------------------|----------------|-----------------|-----------------|------------|------------|
| 1    | MXA Signal Analyzer            | Agilent        | N9020A          | MY49100060      | 2024-10-08 | 2025-10-07 |
| 2    | DC Power Supply                | Agilent        | E3642A          | N/A             | 2024-10-08 | 2025-10-07 |
| 3    | Temperature & Humidity Chamber | Baro           | /               | /               | 2024-06-12 | 2025-06-11 |
| 4    | EMI Test Software              | AUDIX          | E3              | /               | N/A        | N/A        |
| 5    | 3m Semi Anechoic Chamber       | SIDT FRANKONIA | SAC-3M          | 03CH03-HY       | 2024-06-06 | 2025-06-05 |
| 6    | Positioning Controller         | Max-Full       | MF7802BS        | MF780208586     | N/A        | N/A        |
| 7    | Active Loop Antenna            | SCHWARZBECK    | FMZB 1519B      | 00005           | 2024-07-13 | 2027-07-12 |
| 8    | By-log Antenna                 | SCHWARZBECK    | VULB9163        | 9163-470        | 2024-08-03 | 2027-08-02 |
| 9    | Horn Antenna                   | SCHWARZBECK    | BBHA 9120D      | 9120D-1925      | 2024-07-13 | 2027-07-12 |
| 10   | EMI Test Receiver              | R&S            | ESR 7           | 101181          | 2024-06-06 | 2025-06-05 |
| 11   | RS SPECTRUM ANALYZER           | R&S            | FSP40           | 100503          | 2024-06-06 | 2025-06-05 |
| 12   | Low-frequency amplifier        | SchwarzZBECK   | BBV9745         | 00253           | 2024-10-08 | 2025-10-07 |
| 13   | High-frequency amplifier       | JS Denki Pte   | PA0118-43       | JSPA21009       | 2024-10-08 | 2025-10-07 |
| 14   | EMI Test Receiver              | R&S            | ESPI            | 101940          | 2024-06-06 | 2025-06-05 |
| 15   | Artificial Mains               | R&S            | ENV216          | 101288          | 2024-06-06 | 2025-06-05 |
| 16   | 10dB Attenuator                | SCHWARZBECK    | MTS-IMP-13<br>6 | 261115-001-0032 | 2024-06-06 | 2025-06-05 |
| 17   | EMI Test Software              | Farad          | EZ              | /               | N/A        | N/A        |
| 18   | Antenna Mast                   | Max-Full       | MFA-515BS<br>N  | 1308572         | N/A        | N/A        |
| 19   | Pulse Limiter                  | R&S            | ESH3-Z2         | 102750-NB       | 2024-06-06 | 2025-06-05 |
| 20   | Broadband Horn Antenna         | SCHWARZBECK    | BBHA 9170       | 791             | 2024-07-13 | 2027-07-12 |
| 21   | Broadband Preamplifier         | SCHWARZBECK    | BBV9719         | 9719-025        | 2024-07-30 | 2025-07-29 |



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity



## 11. TEST SETUP PHOTOGRAPHS OF THE EUT

Please refer to separated files for Test Setup Photos of the EUT.

## 12. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

## 13. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: [webmaster@lcs-cert.com](mailto:webmaster@lcs-cert.com) | Web: [www.lcs-cert.com](http://www.lcs-cert.com)

Scan code to check authenticity