Test report no.: *Prüfbericht-Nr.:*	**CN23L252 002**	**Order No.:** *Auftragsnr.:*	168426958	**Page 1 of 24** *Seite 1 von 24*
Client reference no.: *Kunden-Referenz-Nr.:*	N/A	**Order date:** *Auftragsdatum:*	2023-05-16	
Client: *Auftraggeber:*	Guangzhou Lango Electronics Technology Co., Ltd. 15/F, Building B1, NO.11, Guangpu Road, Huangpu District, Guangzhou, Guangdong, P.R. China			
Test item: *Prüfgegenstand:*	OPS-8195A			
Identification / Type no.: *Bezeichnung / Typ-Nr.:*	OPS-8195A-4R64S, OPS-8195A-8R128S, OPS-8195A-16R256S			
Order content: *Auftrags-Inhalt*:	Test Report			
Test specification *Prüfgrundlage:*	CFR47 FCC Part 15: Subpart C Section 15.247 RSS-247 Issue 2 February 2017 RSS-Gen Issue 5 March 2019			
Date of sample receipt: *Wareneingangsdatum:*	2023-05-20	Please refer to Photo Document		
Test sample no: *Prüfmuster-Nr.:*	A003490153 001~003 A003473530-001,003 A003473530-006~007			
Testing period: *Prüfzeitraum:*	2023-05-21 to 2023-06-24			
Place of testing: *Ort der Prüfung:*	Refer to section 2.1			
Testing laboratory: *Prüflaboratorium:*	TÜV Rheinland (Shenzhen) Co., Ltd.			
Test result*: *Prüfergebnis*:*	Pass			
tested by: *geprüft von:*	x Bell Hu Signed by: Bell Hu	**authorized by:** *genehmigt von:*	X Lin Lin Signed by: Lin Lin	
Date: 2023-07-13 *Datum:*		**Issue date:** 2023-07-13 *Ausstellungsdatum:*		
Position / *Stellung*:	Expert/Sachverständige(r)	**Position** / *Stellung*:	Expert/Sachverständige(r)	
Other: *Sonstiges:*	FCC ID: 2BA840001 IC: 21669-0001 HVIN: OPS-8195A-4R64S, OPS-8195A-8R128S, OPS-8195A-16R256S This report is for 2.4GHz Wi-Fi only.			
Condition of the test item at delivery: *Zustand des Prüfgegenstandes bei Anlieferung:*	Test item complete and undamaged Prüfmuster vollständig und unbeschädigt			

* Legend:	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet

This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.
V05

Remarks
Anmerkungen

1	The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request. *Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.* *Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.*
2	As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. *Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben.*
3	Test clauses with remark of * are subcontracted to qualified subcontractors and descripted under the respective test clause in the report. Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report. *Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.*
4	The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the “Zero Guard Band Rule” and “Simple Acceptance” in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019. *Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnisen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezueglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.*

Test Summary

5.1.1 ANTENNA REQUIREMENT
RESULT: Pass

5.1.2 MAXIMUM CONDUCTED OUTPUT POWER
RESULT: Pass

5.1.3 CONDUCTED POWER SPECTRAL DENSITY
RESULT: Pass

5.1.4 99%DB BANDWIDTH
RESULT: Pass

5.1.5 6DB BANDWIDTH
RESULT: Pass

5.1.6 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHZ BANDWIDTH
RESULT: Pass

5.1.7 RADIATED SPURIOUS EMISSION
RESULT: Pass

5.1.8 CONDUCTED EMISSION ON AC MAINS
RESULT: Pass

Contents

1 GENERAL REMARKS 5
1.1 COMPLEMENTARY MATERIALS 5
1.2 TEST METHODOLOGY 5

2 TEST SITES 6
2.1 TEST FACILITIES 6
2.2 LIST OF TEST AND MEASUREMENT INSTRUMENTS 6
2.3 TRACEABILITY 7
2.4 CALIBRATION 7
2.5 MEASUREMENT UNCERTAINTY 7
2.6 LOCATION OF ORIGINAL DATA 7
2.7 STATUS OF FACILITY USED FOR TESTING 8

3 GENERAL PRODUCT INFORMATION 9
3.1 PRODUCT FUNCTION AND INTENDED USE 9
3.2 RATINGS AND SYSTEM DETAILS 9
3.3 INDEPENDENT OPERATION MODES 11
3.4 NOISE GENERATING AND NOISE SUPPRESSING PARTS 11
3.5 SUBMITTED DOCUMENTS 11

4 TEST SET-UP AND OPERATION MODES 12
4.1 PRINCIPLE OF CONFIGURATION SELECTION 12
4.2 TEST OPERATION AND TEST SOFTWARE 12
4.3 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT 12
4.4 COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE 12
4.5 TEST SETUP DIAGRAM 13

5 TEST RESULTS 15
5.1 TRANSMITTER REQUIREMENT & TEST SUITES 15
5.1.1 Antenna Requirement 15
5.1.2 Maximum Conducted Output Power 16
5.1.3 Conducted Power Spectral Density 18
5.1.4 99%dB Bandwidth 19
5.1.5 6dB Bandwidth 20
5.1.6 Conducted Spurious Emissions Measured in 100 kHz Bandwidth 21
5.1.7 Radiated Spurious Emission 22
5.1.8 Conducted Emission on AC Mains 23

6 PHOTOGRAPHS OF THE TEST SET-UP 24

7 LIST OF TABLES 24

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Test Results of 2.4GHz Wi-Fi.

Appendix B: Photographs of the Test Set-up

1.2 TEST METHODOLOGY

KDB 558074 D01 15.247 Meas Guidance.
662911 D01 Multiple Transmitter Output.
ANSI C63.10:2013 : American National Standard for Testing Unlicensed Wireless Devices

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.
No.362, Huanguan Middle Road, Songyuansha Community, Guanhu Subdistrict, Longhua District, Shenzhen 518110, Guangdong, China

FCC Registration No.: 694916

ISED wireless device testing laboratory: 25069

TÜV Rheinland (Guangdong) Ltd. EMC Laboratory
No.102, 1F of Southwest and No.205, 2F of West Warehouse Building, No.767 Tianyuan Road, Tianhe District, Guangzhou, Guangdong, P.R.China

FCC Registration No.: CN1207
ISED wireless device testing laboratory: 2932C

Note: Except for AC power-line conducted emissions, all test items performed in TÜV Rheinland (Shenzhen) Co., Ltd.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Radio Spectrum Testing (SRD-Tonscend)				
Equipment	**Manufacturer**	**Model**	**Serial No.**	**Cal. until**
EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY60241175	2023-10-10
MXG X-Series RF Vector Signal Generator	Keysight	N5182B	MY61250137	2023-10-10
EXG X-Series Microwave Analog Signal Generator	Keysight	N5173B	MY61250141	2023-10-10
DC power supply	Keysight	E3642A	MY61276100	2023-10-10
Power Control Unit	Tonscend	JS0806-4ADC	N/A	2023-10-10
Automation Control Unit	Tonscend	JS0806-2	21C8060396	2023-10-10
Test Software	Tonscend	JS1120-3	N/A	N/A
Control PC	Lenovo	TianYi510S-071MB	YLX23JMF	N/A
Shielding Room 8#	Albatross	SR8	APC17151-SR8	2024-06-22
Unwanted Emission Testing (TS9975)				
Equipment	**Manufacturer**	**Model**	**Serial No.**	**Cal. until**
EMI Test Receiver	R&S	ESR 7	102021	2023-08-02
Signal Analyzer	R&S	FSV 40	101439	2023-08-01
System Controller Interface	R&S	SCI-100	S10010038	N/A
Filterbank	R&S	Wlan	100759	2023-08-01
OSP	R&S	OSP 120	102040	N/A
Pre-amplifier	R&S	SCU08F1	08320031	2023-08-02
Amplifier	R&S	SCU-18F	180070	2023-08-02

Amplifier	R&S	SCU40A	100475	2023-08-02
Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	2024-08-06
Double-Ridged Antenna (1 -18 GHz)	ETS-LINDGREN	3117	00218717	2024-08-06
Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19067	2024-08-27
Active Loop Antenna	Schwarzbeck	FMZB 1513	302	2023-08-06
Test software	R&S	EMC32 (V10.60.10)	N/A	N/A
Control PC	Dell	OptiPlex 7050	36NV9P2	N/A
3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	2024-06-22

Conducted Emissions				
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Cal. Until**
EMI Test Receiver	R&S	ESU 26	100209	2024-03-01
Artificial Mains Network	R&S	ENV216	100195	2024-05-25
EMC32 test software	R&S	EMC32(Ver.10.50.00)	N/A	N/A

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basics using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Parameter	Uncertainty (k=2)
RF output power, conducted	± 0.99 dB
Occupied Channel Bandwidth	± 2.08 %
RF power density, conducted	± 0.99 dB
Unwanted Emissions, conducted	± 0.89 dB
All emissions, radiated	±4.17 dB
Conducted Emission, (9kHz to 150kHz)/(150kHz to 30MHz)	± 1.98 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at No.362, Huanguan Middle Road, Songyuansha Community, Guanhu Subdistrict, Longhua District, Shenzhen 518110, Guangdong, China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The Product is OPS-8195A, which supports Bluetooth(dual mode), 2.4GHz Wi-Fi 802.11 b/g/n/ax and 5GHz Wi-Fi 802.11a/n/ac/ax wireless technology.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 2: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment:	OPS-8195A
Type Designation:	OPS-8195A-4R64S, OPS-8195A-8R128S, OPS-8195A-16R256S
FCC ID:	2BA840001
IC ID:	21669-0001
PMN:	OPS-8195A
HVIN:	OPS-8195A-4R64S, OPS-8195A-8R128S, OPS-8195A-16R256S
Operating Voltage:	12V～19V DC input via panel JAE port
Testing Voltage:	AC 120V, 60Hz
Technical Specification of Bluetooth (dual mode)	
Operating Frequency:	2402 MHz to 2480 MHz
Type of Modulation:	GFSK, π/4-DQPSK, 8DPSK
Channel Number:	BDR & EDR mode:79 channels; Low Energy mode:40 channels
Channel Separation:	BDR & EDR mode: 1MHz, 2MHz; Low Energy mode: 2MHz
Data Rate:	BDR & EDR mode: 1Mbps, 2Mbps, 3Mbps Low Energy mode: 1Mbps, 2Mbps
Antenna Type:	External Antenna
Antenna Gain of Bluetooth:	5.0 dBi Max(As detailed in Antenna spec)
Technical Specification of Wi-Fi 802.11 b/g/n/ax	
Operating Frequency:	2412 - 2462 MHz for 802.11b/g/n(HT20)/ax(HE20) 2422 - 2452 MHz for 802.11n(HT40)/ax(HE40)
Type of Modulation:	802.11b: CCK, DQPSK, DBPSK 802.11g/n : BPSK, QPSK, 16QAM, 64QAM 802.11ax: BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM
Data Rate:	1/2/5.5/11 Mbps for 802.11b 6/9/12/18/24/36/48/54 Mbps for 802.11g MCS0~MCS 7 for 802.11n(HT20/40) MCS0~MCS11 for 802.11ax(HE20/40) (All data rates considered, only the Worst-cases reported)
Channel Number:	11 channels for 802.11b/g/n(HT20)/ax(HE20) 7 channels for 802.11n(HT40)/ax(HE40)
Channel Separation:	5 MHz
Antenna Type:	External Antenna

Number of Antenna:	2
Antenna Gain:	5.0 dBi Max(As detailed in Antenna spec)
Note: WLAN 2.4GHz 802.11n and 802.11ax support. For directional gain: Array Gain = 10 log(*NANT/NSS*) dB. So the Directional gain =GANT + 10 log(NANT) dBi (The worst case directional gain will occur when NSS = 1).	
Technical Specification of Wi-Fi 802.11 a/n/ac/ax	
Operating Frequency:	5180-5320MHz, 5500-5720MHz, 5745-5825MHz
Type of Modulation:	802.11n/a: BPSK, QPSK, 16QAM, 64QAM 802.11ac: BPSK, QPSK, 16QAM, 64QAM, 256QAM 802.11ax: BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM
Protocol:	802.11 a/n20/n40/ac20/ac40/ac80/ ax20/ax40/ax80
Data Rate:	6/9/12/18/24/36/48/54 Mbps for 802.11a MCS0~MCS7 for 802.11n MCS0~MCS9 for 802.11ac MCS0~MCS11 for 802.11ax (All data rates considered, only the Worst-cases reported)
Channel Separation	5 MHz
Antenna Type:	External Antenna
Number of Antenna:	2
Antenna Gain:	5.0 dBi Max (As detailed in Antenna spec)
Type of Device	Slave Device without Radar Detection
Note: WLAN 5GHz 802.11n/802.11ac/802.11ax. For directional gain: Array Gain = 10 log(*NANT/NSS*) dB. So the Directional gain =GANT + 10 log(NANT) dBi (The worst case directional gain will occur when NSS = 1).	

Note: all required modes tested for all items, and only the worst-case reported.

* All the models share the same circuit design and PCB layout, the different in RAM and ROM. RSE considered for all models, only the worst-case reported.

Model number	**RAM and ROM configuration**
OPS-8195A-4R64S	4GB/64GB
OPS-8195A-8R128S	8GB/128GB
OPS-8195A-16R256S	16GB/256GB

Table 3: RF Channel and Frequency of Wi-Fi 802.11 b/g/n/ax

RF Channel	802.11 b/g/n(HT20)/ax(HE20)	802.11 n(HT40)/ax(HE40)
	Frequency (MHz)	Frequency (MHz)
01	**2412**	**/**
02	2417	/
03	2422	**2422**
04	2427	2427
05	2432	2432
06	**2437**	**2437**
07	2442	2442
08	2447	2447
09	2452	**2452**
10	2457	/
11	**2462**	**/**

Test frequencies are lowest channel: 2412 MHz, middle channel: 2437 MHz and highest channel: 2462 MHz for 802.11b/g/n(HT20)/ax(HE20)

Test frequencies are lowest channel: 2422 MHz, middle channel: 2437 MHz and highest channel: 2452 MHz for 802.11n(HT40)/ax(HE40)

3.3 Independent Operation Modes

The basic operation modes are:

A. On, Wi-Fi transmitting mode
   1) Low Channel
   2) Middle Channel
   3) High Channel

B. On, Normal operation with Wi-Fi & Bluetooth connected.

C. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- Application Form
- ID Label and Location Info
- User Manual
- Operation Description

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10: 2013.

According to clause 3.1, all tests were performed on model OPS-8195A-4R64S in this report.

4.3 Special Accessories and Auxiliary Equipment

Table 4: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	Remark
Laptop	Lenovo	T480	PF-16A6N8
Laptop	Lenovo	T14	PF-35VTG1
Monitor	Lenovo	T24s-20	1S62A5MCR4CSULA20286
Router	HUAWEI	WS7200	L5KEQ20B02002259
Headset	Logitech	H110	/
Keyboard	DELL	KB212-B	DP/N ON291F
Mouse	A4TECH	OP-520NU	/
USB Disk	KingSton	8GB	/
Test Board	Lango	/	SN: 02K1150315A0
AC/DC Adapter	/	SWPP-12000-US	Input: 100-240V AC, 50/60Hz, 1.0A MAX Output: DC 12V/1A

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)



Diagram of Measurement Configuration for Radiation Test (Above 1GHz)



Diagram of Measurement Configuration for Mains Conduction Measurement



Diagram of Measurement Configuration for Conducted Transmitter Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT: **Pass**

Test Specification

Test standard	:	FCC Part 15.247(b)(4) and Part 15.203 RSS-Gen Clause 6.8

The EUT have External Antennas, the Maximum antenna gain of antenna is 5.0 dBi, and Non-standard connector (RP-SMA) designed, no consideration of replacement.

Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

5.1.2 Maximum Conducted Output Power

RESULT: **Pass**

Test Specification

Test standard	:	FCC Part 15.247(b)(3) RSS-247 Clause 5.4(d)
Basic standard	:	ANSI C63.10: 2013
Limits	:	< 1 W (Maximum Conducted Power) e.i.r.p. <4W
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	2023-06-03 to 2023-06-04
Input voltage	:	AC 120V, 60Hz
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	24.1 ℃
Relative humidity	:	61 %
Atmospheric pressure	:	101 kPa

For details refer to following test result.

Table 5: Test Result of Maximum Conducted Output Power

Worst case for SISO mode

Test Mode	Data Rate	Test Channel (MHz)	Measured conducted average Power		Limit (dBm)
			(dBm)	(W)	
802.11b	1 Mbps	2412	17.30	0.0537	30
		2437	17.25	0.0531	
		2462	17.29	0.0536	
802.11g	6 Mbps	2412	16.19	0.0416	
		2437	16.14	0.0411	
		2462	16.31	0.0428	
802.11n (HT20)	MCS0	2412	15.40	0.0347	
		2437	15.31	0.0340	
		2462	15.46	0.0352	
802.11n (HT40)	MCS0	2422	15.34	0.0342	
		2437	15.22	0.0333	
		2452	15.22	0.0333	
802.11ax (HE20)	MCS0	2412	15.36	0.0344	
		2437	15.43	0.0349	
		2462	15.47	0.0352	
802.11ax (HE40)	MCS0	2422	15.45	0.0351	
		2437	15.34	0.0342	
		2452	15.43	0.0349	
Max. e.i.r.p.=17.30dBm+5.0dBi=22.3dBm, which is less than 36dBm=4W.					

Both the Ant 1 and ant 2 tested, only worst-case reported.

Worst case for MIMO mode (Ant1+2)

Test Mode	Data Rate	Test Channel (MHz)	Measured conducted average Power		Limit (dBm)
			(dBm)	(W)	
802.11n (HT20)	MCS0	2412	18.04	0.0637	28
		2437	18.02	0.0634	
		2462	18.13	0.0650	
802.11n (HT40)	MCS0	2422	17.96	0.0625	
		2437	17.98	0.0628	
		2452	17.99	0.0630	
802.11ax (HE20)	MCS0	2412	18.08	0.0643	
		2437	18.11	0.0647	
		2462	**18.15**	0.0653	
802.11ax (HE40)	MCS0	2422	18.15	0.0653	
		2437	18.07	0.0641	
		2452	18.12	0.0649	
*: The directional gain for MIMO mode is 8dBi, which is 2dB higher than 6dBi, thus power limit should be reduced to 28dBm. Max. e.i.r.p.=18.15dBm+8.0dBi=26.15dBm, which is less than 36dBm=4W.					

Note:

1) The cable loss is taken into account in results.
2) Antenna gain(G): 5.0 dBi Max
3) Both SISO and MIMO tested, only the higher power mode MIMO reported.
4) e.i.r.p.=P(Average power)+ G(Directional Gain)

5.1.3 Conducted Power Spectral Density

RESULT: **Pass**

Test Specification

Test standard	:	FCC Part 15.247(e) RSS-247 Clause 5.2(b)
Basic standard	:	ANSI C63.10: 2013
Limits	:	8 dBm / 3kHz
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	2023-06-07 to 2023-06-09
Input voltage	:	AC 120V, 60Hz
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	24.1 ℃
Relative humidity	:	61 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix A.

5.1.4 99%dB Bandwidth

RESULT: **Pass**

Test Specification

Test standard	:	RSS-Gen clause 6.7
Basic standard	:	ANSI C63.10: 2013
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	2023-06-07 to 2023-06-09
Input voltage	:	AC 120V, 60Hz
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	24.1 ℃
Relative humidity	:	61 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix A.

5.1.5 6dB Bandwidth

RESULT: **Pass**

Test Specification

Test standard	:	FCC Part 15.247(a)(2) RSS-247 Clause 5.2(a)
Basic standard	:	ANSI C63.10: 2013
Limits	:	> 500 KHz
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	2023-06-07 to 2023-06-09
Input voltage	:	AC 120V, 60Hz
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	24.1 ℃
Relative humidity	:	61 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix A.

5.1.6 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

RESULT: **Pass**

Test Specification

Test standard	:	FCC Part 15.247(d) RSS-247 Clause 5.5
Basic standard	:	ANSI C63.10: 2013
Limits	:	20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	2023-06-07 to 2023-06-09
Input voltage	:	AC 120V, 60Hz
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	24.1 ℃
Relative humidity	:	61 %
Atmospheric pressure	:	101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to test plots, and compliance is achieved as well.

For the measurement records, refer to the appendix A.

5.1.7 Radiated Spurious Emission

RESULT: **Pass**

Test Specification

Test standard	:	FCC Part 15.247(d) & FCC Part 15.205 RSS-247 Clause 3.3 & 5.5
Basic standard	:	ANSI C63.10: 2013
Limits	:	Refer to 15.209(a) of FCC part 15.247(d) RSS-Gen Table 5
Kind of test site	:	3m Semi-anechoic Chamber

Test Setup

Date of testing	:	2023-06-09 to 2023-06-13
Input voltage	:	AC 120V, 60Hz
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	Refer to test result
Relative humidity	:	Refer to test result
Atmospheric pressure	:	101 kPa

Remark:
Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix A.

5.1.8 Conducted Emission on AC Mains

RESULT: **Pass**

Test Specification

Test standard	:	FCC Part 15.207(a) RSS-Gen Clause 8.8
Basic standard	:	ANSI C63.10: 2013
Frequency range	:	0.15 – 30MHz
Limits	:	FCC Part 15.207(a) RSS-Gen Table 4
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	2023-06-07
Input voltage	:	AC 120V, 60Hz
Operation mode	:	B
Earthing	:	Not connected
Ambient temperature	:	23.2 ℃
Relative humidity	:	50.6 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix A.

6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix B.

7 List of Tables

Table 1: List of Test and Measurement Equipment 6
Table 2: Technical Specification of EUT 9
Table 3: RF Channel and Frequency of Wi-Fi 802.11 b/g/n/ax 11
Table 4: List of Accessories and Auxiliary Equipment 12
Table 5: Test Result of Maximum Conducted Output Power 17