FCC TEST REPORT
FCC ID:2BA8I-GAS-501F

Report Number.....:	ZKT-230508L3293-02
Date of Test.....:	Mar 28, 2023 to May 8, 2023
Date of issue.....:	May 8, 2023
Total number of pages..... :	43
Test Result .....:	PASS
Testing Laboratory..... :	Shenzhen ZKT Technology Co., Ltd.
Address ..... :	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Applicant's name .....:	Guangdong Grasse Environmental Technology Co.,Ltd.
Address ..... :	No 670,GuangCong Five road, Zhongluotan Town,Baiyun District,Guangzhou
Manufacturer's name .....:	Guangdong Grasse Environmental Technology Co.,Ltd.
Address ..... :	No 670,GuangCong Five road, Zhongluotan Town,Baiyun District,Guangzhou
Test specification:	
Standard.....:	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Test procedure..... :	ANSI C63.10:2013 KDB558074 D0115.247 Meas Guidance v 05r02
Non-standard test method .....:	N/A
Test Report Form No..... :	TRF-EL-112_V0
Test Report Form(s) Originator..... :	ZKT Testing
Master TRF .....:	Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name :	Scent Machine
Trademark :	格迩斯

Model/Type reference	:	GAS-501F、GAS-100、GAS-100B、GAS-100F、GAS-100H、GAS-100HF、GAS-101、GAS-101B、GAS-101H、GAS-101F、GAS-101HF、HZ-1201、HZ-1202、HZ-1203、GAS-200、GAS-200B、GAS-200H、GAS-200F、GAS-200HF、GAS-201、GAS-201B、GAS-201H、GAS-201F、GAS-201HF、GAS-300、GAS-300B、GAS-300H、GAS-300F、GAS-300HF、GAS-301、GAS-301B、GAS-301H、GAS-301F、GAS-301HF、GAS-500、GAS-500B、GAS-500H、GAS-500F、GAS-500HF、GAS-501、GAS-501B、GAS-501H、GAS-501F、GAS-501HF、GAM-1000、GAM-1000H、GAM-1000F、GAM-1000HF、GAM-1001、GAM-1001H、GAM-1001F、GAM-1001HF、GAM-1500、GAM-1500H、GAM-1500F、GAM-1500HF、GAM-1501、GAM-1501H、GAM-1501F、GAM-1501HF、GAM-2000、GAM-2000H、GAM-2000HF、GAM-2001、GAM-2001H、GAM-2001F、GAM-2001HF、GAM-3000、GAM-3000H、GAM-3000HF
Ratings.....	:	DC 12V/1A from adapter

Testing procedure and testing location:

Testing Laboratory.....:	**Shenzhen ZKT Technology Co., Ltd.**
Address.....:	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Tested by (name + signature).....:	Alen He
Reviewer (name + signature).....:	Joe Liu
Approved (name + signature).....:	Lake Xie

Table of Contents

Page

1. VERSION 6
2. SUMMARY OF TEST RESULTS 7
   2.1 TEST FACILITY 8
   2.2 MEASUREMENT UNCERTAINTY 8
3. GENERAL INFORMATION 9
   3.1 GENERAL DESCRIPTION OF EUT 9
   3.2 DESCRIPTION OF TEST MODES 10
   3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 10
   3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) 11
   3.5EQUIPMENTS LIST FOR ALL TEST ITEMS 12
4. EMC EMISSION TEST 13
   4.1 CONDUCTED EMISSION MEASUREMENT 13
      4.1.1 POWER LINE CONDUCTED EMISSION Limits 13
      4.1.2 TEST PROCEDURE 13
      4.1.3 DEVIATION FROM TEST STANDARD 13
      4.1.4 TEST SETUP 14
      4.1.5 EUT OPERATING CONDITIONS 14
      4.1.6 TEST RESULT 15
   4.1.6 TEST RESULT 15
   4.2 RADIATED EMISSION MEASUREMENT 17
      4.2.1 RADIATED EMISSION LIMITS 17
      4.2.2 TEST PROCEDURE 17
      4.2.3 DEVIATION FROM TEST STANDARD 18
      4.2.4 TEST SETUP 18
      4.2.5 EUT OPERATING CONDITIONS 19
      4.2.6 TEST RESULTS 20
5.RADIATED BAND EMISSIONMEASUREMENT 24
   5.1 TEST REQUIREMENT: 24
   5.2 TEST PROCEDURE 24
   5.3 DEVIATION FROM TEST STANDARD 24
   5.4 TEST SETUP 25
   5.5 EUT OPERATING CONDITIONS 25
   5.6 TEST RESULT 26
6.POWER SPECTRAL DENSITY TEST 27
   6.1 APPLIED PROCEDURES / LIMIT 27
   6.2 TEST PROCEDURE 27
   6.3 DEVIATION FROM STANDARD 27
   6.4 TEST SETUP 27

6.5 EUT OPERATION CONDITIONS 27
6.6 TEST RESULT 27
7. CHANNEL BANDWIDTH 28
7.1 APPLIED PROCEDURES / LIMIT 28
7.2 TEST PROCEDURE 28
7.3 DEVIATION FROM STANDARD 28
7.4 TEST SETUP 28
7.5 EUT OPERATION CONDITIONS 28
7.6 TEST RESULT 28
8.PEAK OUTPUT POWER TEST 29
8.1 APPLIED PROCEDURES/LIMIT 29
8.2 TEST PROCEDURE 29
8.3 DEVIATION FROM STANDARD 29
8.4 TEST SETUP 29
8.5 EUT OPERATION CONDITIONS 29
8.6 TEST RESULT 29
9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION 30
9.1 APPLICABLE STANDARD 30
9.2 TEST PROCEDURE 30
9.3 DEVIATION FROM STANDARD 30
9.4 TEST SETUP 30
9.5 EUT OPERATION CONDITIONS 30
9.6 TEST RESULTS 30
10. ANTENNA REQUIREMENT 31
11.APPENDIX1 32
11.1. -6DB BANDWIDTH 32
11.2. BANDEDGE 34
11.3. PEAK OUTPUT POWER 36
11.4. POWER SPECTRAL DENSITY 38
11.5. SPURIOUS EMISSION 40
12. TEST SETUP PHOTO 43
13. EUT CONSTRUCTIONAL DETAILS 43

1. VERSION

Report No.	Version	Description	Approved
ZKT-230508L3293-02	Rev.01	Initial issue of report	May 8, 2023

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203/15.247 (c)	Antenna requirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	PASS	
FCC part 15.247 (b)(3)	Conducted Peak Output Power	PASS	
FCC part 15.247 (a)(2)	Channel Bandwidth	PASS	
FCC part 15.247 (e)	Power Spectral Density	PASS	
FCC part 15.247(d)	Band Edge	PASS	
FCC part 15.205/15.209	Spurious Emission	PASS	

NOTE:

(1)” N/A” denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.
Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225
Designation Number: CN1299
IC Registered No.: 27033

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ± U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %。

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power conducted	±0.16dB
3	Spurious emissions conducted	±0.21dB
4	All emissions radiated(<1G)	±4.68dB
5	All emissions radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Scent Machine
Model No.:	GAS-501F
Serial No.:	GAS-100、GAS-100B、GAS-100F、GAS-100H、GAS-100HF、GAS-101、GAS-101B、GAS-101H、GAS-101F、GAS-101HF、HZ-1201、HZ-1202、HZ-1203、GAS-200、GAS-200B、GAS-200H、GAS-200F、GAS-200HF、GAS-201、GAS-201B、GAS-201H、GAS-201F、GAS-201HF、GAS-300、GAS-300B、GAS-300H、GAS-300F、GAS-300HF、GAS-301、GAS-301B、GAS-301H、GAS-301F、GAS-301HF、GAS-500、GAS-500B、GAS-500H、GAS-500F、GAS-500HF、GAS-501、GAS-501B、GAS-501H、GAS-501F、GAS-501HF、GAM-1000、GAM-1000H、GAM-1000F、GAM-1000HF、GAM-1001、GAM-1001H、GAM-1001F、GAM-1001HF、GAM-1500、GAM-1500H、GAM-1500F、GAM-1500HF、GAM-1501、GAM-1501H、GAM-1501F、GAM-1501HF、GAM-2000、GAM-2000H、GAM-2000HF、GAM-2001、GAM-2001H、GAM-2001F、GAM-2001HF、GAM-3000、GAM-3000H、GAM-3000HF
Model difference:	The product has many models, only the model name is different, and the other parts such as the circuit principle, pcb and electrical structure are the same.
Hardware Version:	V1.0
Software Version:	V1.0
Sample(s) Status:	Engineer sample
Channel numbers:	40
Channel separation:	2402MHz~2480MHz
Date rate:	1Mbps
Modulation technology:	GFSK
Antenna Type:	PCB antenna
Antenna gain:	0dBi
Power supply:	DC 12V/1A from adapter
Power Adaptor:	AC/DC ADAPTER MODEL:KDP-AM120100N INPUT:100-240V~50/60Hz 0.5A Max OUTPUT:12V--1A 12W

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402	11	2422	21	2442	31	2462
2	2404	12	2424	22	2444	32	2464
3	2406	13	2426	23	2446	33	2466
4	2408	14	2428	24	2448	34	2468
5	2410	15	2430	25	2450	35	2470

6	2412	16	2432	26	2452	36	2472
7	2414	17	2434	27	2454	37	2474
8	2416	18	2436	28	2456	38	2476
9	2418	19	2438	29	2458	39	2478
10	2420	20	2440	30	2460	40	2480

Note:
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	**Frequency**
The lowest channel	2402MHz
The middle channel	2440MHz
The Highest channel	2480MHz

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission

adapter ——— EUT

Radiated Emission

adapter ——— EUT

Conducted Spurious

adapter ——— EUT

3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	AC Adapter	KINGDRIVE	KDP-AM120100N	N/A	N/A
2					

Item	Shielded Type	Ferrite Core	Length	Note

Note:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.

3.5EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY55370835	Oct. 18, 2022	Oct. 17, 2023
2	Spectrum Analyzer (1GHz-40GHz)	R&S	FSQ	100363	Oct. 17, 2022	Oct. 16, 2023
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESCI7	101169	Oct. 18, 2022	Oct. 17, 2023
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	N/A	Oct. 17, 2022	Oct. 16, 2023
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	Oct. 17, 2022	Oct. 16, 2023
6	Loop Antenna	TESEQ	HLA6121	58357	Oct. 17, 2022	Oct. 16, 2023
7	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	060747	Oct. 17, 2022	Oct. 16, 2023
8	Amplifier (1GHz-26.5GHz)	Agilent	8449B	3008A00315	Oct. 18, 2022	Oct. 17, 2023
9	RF cables1 (9kHz-30MHz)	N/A	9kHz-30MHz	N/A	Oct. 18, 2022	Oct. 17, 2023
10	RF cables2 (30MHz-1GHz)	N/A	30MHz-1GHz	N/A	Oct. 18, 2022	Oct. 17, 2023
11	RF cables3 (1GHz-40GHz)	N/A	1GHz-40GHz	N/A	Oct. 18, 2022	Oct. 17, 2023
12	ESG Signal Generator	Agilent	E4421B	N/A	Oct. 18, 2022	Oct. 17, 2023
13	Signal Generator	Agilent	N5182A	N/A	Oct. 22, 2022	Oct. 21, 2023
14	Magnetic Field Probe Tester	Narda	ELT-400	0-0344	Oct. 17, 2022	Oct. 16, 2023
15	MWRF Power Meter Test system	MW	MW100-RPCB	N/A	Oct. 22, 2022	Oct. 21, 2023
16	D.C. Power Supply	LongWei	TPR-6405D	N/A	\	\
17	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	\	\
18	RF Software	MW	MTS8310	V2.0.0.0	\	\
19	Turntable	MF	MF-7802BS	N/A	\	\
20	Antenna tower	MF	MF-7802BS	N/A	\	\

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	Oct. 22, 2022	Oct. 21, 2023
2	LISN	CYBERTEK	EM5040A	E1850400149	Oct. 22, 2022	Oct. 21, 2023
3	Test Cable	N/A	C01	N/A	Oct. 18, 2022	Oct. 17, 2023
4	Test Cable	N/A	C02	N/A	Oct. 18, 2022	Oct. 17, 2023
5	EMI Test Receiver	R&S	ESCI3	101393	Oct. 17, 2022	Oct. 16, 2023
6	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	\	\

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

4.1.6 TEST RESULT

4.1.6 Test Result

Temperature：	26℃	Relative Humidity：	54%
Pressure：	101kPa	Phase：	L
Test Voltage ：	AC 120V/60Hz	Test Mode	GFSK-lowest channel



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1500	40.86	10.05	50.91	65.99	-15.08	QP	
2		0.1500	15.82	10.05	25.87	55.99	-30.12	AVG	
3		0.6220	17.08	10.21	27.29	46.00	-18.71	AVG	
4		0.6260	33.01	10.21	43.22	56.00	-12.78	QP	
5	*	1.2460	35.33	10.14	45.47	56.00	-10.53	QP	
6		1.2460	22.17	10.14	32.31	46.00	-13.69	AVG	
7		2.4940	34.30	10.09	44.39	56.00	-11.61	QP	
8		2.4940	17.90	10.09	27.99	46.00	-18.01	AVG	
9		4.0700	31.43	9.82	41.25	56.00	-14.75	QP	
10		4.0700	19.35	9.82	29.17	46.00	-16.83	AVG	
11		28.4980	30.33	9.79	40.12	60.00	-19.88	QP	
12		28.4980	21.07	9.79	30.86	50.00	-19.14	AVG	

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode	GFSK-lowest channel



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1500	14.99	10.05	25.04	55.99	-30.95	AVG	
2		0.1580	40.08	10.06	50.14	65.56	-15.42	QP	
3		0.6260	34.59	10.21	44.80	56.00	-11.20	QP	
4		0.6260	19.69	10.21	29.90	46.00	-16.10	AVG	
5	*	1.2460	36.17	10.14	46.31	56.00	-9.69	QP	
6		1.2460	25.11	10.14	35.25	46.00	-10.75	AVG	
7		2.4940	21.14	10.09	31.23	46.00	-14.77	AVG	
8		2.5740	34.38	10.06	44.44	56.00	-11.56	QP	
9		4.0700	32.94	9.82	42.76	56.00	-13.24	QP	
10		4.0700	21.98	9.82	31.80	46.00	-14.20	AVG	
11		20.3580	27.82	9.79	37.61	60.00	-22.39	QP	
12		20.3580	17.19	9.79	26.98	50.00	-23.02	AVG	

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

4.2 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10:2013
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoiccamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of avariable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum valueof the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned toheights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could bestopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reportedin a data sheet.

Above 1GHz test procedure as below:

a. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber andchange form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
b. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation

4.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS

Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Test Mode	GFSK-lowest channel



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector	cm	degree	Comment
1	*	56.9911	43.32	-9.59	33.73	40.00	-6.27	QP	100	249	
2		130.3788	37.36	-4.20	33.16	43.50	-10.34	QP	100	248	
3		138.3873	37.60	-3.89	33.71	43.50	-9.79	QP	100	357	
4		173.2050	39.55	-4.42	35.13	43.50	-8.37	QP	100	29	
5		314.3765	36.45	-1.62	34.83	46.00	-11.17	QP	100	189	
6		352.9433	38.99	-0.76	38.23	46.00	-7.77	QP	100	69	

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz	Test Mode	GFSK-lowest channel



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector	cm	degree	Comment
1		48.8429	42.17	-8.91	33.26	40.00	-6.74	QP	100	24	
2		56.9911	42.79	-9.59	33.20	40.00	-6.80	QP	100	158	
3	*	65.1145	43.38	-9.36	34.02	40.00	-5.98	QP	100	249	
4		138.3873	39.90	-3.89	36.01	43.50	-7.49	QP	100	327	
5		162.6106	39.03	-3.97	35.06	43.50	-8.44	QP	100	98	
6		170.7925	40.31	-4.31	36.00	43.50	-7.50	QP	100	59	

Remarks:
1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2.The emission levels of other frequencies are very lower than the limit and not show in test report.
3.The test data shows only the worst case

1GHz~25GHz

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
BLE1M--Low Channel:2402MHz									
V	4804.00	56.54	30.55	5.77	24.66	56.42	74.00	-17.58	PK
V	4804.00	40.23	30.55	5.77	24.66	40.11	54.00	-13.89	AV
V	7206.00	53.10	30.33	6.32	24.55	53.64	74.00	-20.36	PK
V	7206.00	39.65	30.33	6.32	24.55	40.19	54.00	-13.81	AV
V	9608.00	52.15	30.85	7.45	24.69	53.44	74.00	-20.56	PK
V	9608.00	38.25	30.85	7.45	24.69	39.54	54.00	-14.46	AV
H	4804.00	55.68	30.55	5.77	24.66	55.56	74.00	-18.44	PK
H	4804.00	40.69	30.55	5.77	24.66	40.57	54.00	-13.43	AV
H	7206.00	53.63	30.33	6.32	24.55	54.17	74.00	-19.83	PK
H	7206.00	41.08	30.33	6.32	24.55	41.62	54.00	-12.38	AV
H	9608.00	51.73	30.85	7.45	24.69	53.02	74.00	-20.98	PK
H	9608.00	39.12	30.85	7.45	24.69	40.41	54.00	-13.59	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
BLE1M--Middle Channel:2440MHz									
V	4880.00	54.29	30.55	5.77	24.66	54.17	74.00	-19.83	PK
V	4880.00	39.60	30.55	5.77	24.66	39.48	54.00	-14.52	AV
V	7320.00	54.21	30.33	6.32	24.55	54.75	74.00	-19.25	PK
V	7320.00	39.39	30.33	6.32	24.55	39.93	54.00	-14.07	AV
V	9760.00	50.37	30.85	7.45	24.69	51.66	74.00	-22.34	PK
V	9760.00	37.53	30.85	7.45	24.69	38.82	54.00	-15.18	AV
H	4880.00	55.72	30.55	5.77	24.66	55.60	74.00	-18.40	PK
H	4880.00	39.68	30.55	5.77	24.66	39.56	54.00	-14.44	AV
H	7320.00	54.47	30.33	6.32	24.55	55.01	74.00	-18.99	PK
H	7320.00	40.45	30.33	6.32	24.55	40.99	54.00	-13.01	AV
H	9760.00	52.04	30.85	7.45	24.69	53.33	74.00	-20.67	PK
H	9760.00	36.86	30.85	7.45	24.69	38.15	54.00	-15.85	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
BLE1M--High Channel:2480MHz									
V	4960.00	54.38	30.55	5.77	24.66	54.26	74.00	-19.74	PK
V	4960.00	41.97	30.55	5.77	24.66	41.85	54.00	-12.15	AV
V	7440.00	53.98	30.33	6.32	24.55	54.52	74.00	-19.48	PK
V	7440.00	39.30	30.33	6.32	24.55	39.84	54.00	-14.16	AV
V	9920.00	52.72	30.85	7.45	24.69	54.01	74.00	-19.99	PK
V	9920.00	37.92	30.85	7.45	24.69	39.21	54.00	-14.79	AV
H	4960.00	55.25	30.55	5.77	24.66	55.13	74.00	-18.87	PK
H	4960.00	39.27	30.55	5.77	24.66	39.15	54.00	-14.85	AV
H	7440.00	53.02	30.33	6.32	24.55	53.56	74.00	-20.44	PK
H	7440.00	39.76	30.33	6.32	24.55	40.30	54.00	-13.70	AV
H	9920.00	51.93	30.85	7.45	24.69	53.22	74.00	-20.78	PK
H	9920.00	37.21	30.85	7.45	24.69	38.50	54.00	-15.50	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5.RADIATED BAND EMISSIONMEASUREMENT

5.1 TEST REQUIREMENT:

<table>
<tr><td>Test Requirement:</td><td>FCC Part15 C Section 15.209 and 15.205</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10: 2013</td></tr>
<tr><td>Test Frequency Range:</td><td>All of the restrict bands were tested, only the worst band’s (2310MHz to 2500MHz) data was showed.</td></tr>
<tr><td>Test site:</td><td>Measurement Distance: 3m</td></tr>
<tr><td>Receiver setup:</td><td>
<table>
<tr><td>Frequency</td><td>Detector</td><td>RBW</td><td>VBW</td><td>Value</td></tr>
<tr><td rowspan="2">Above 1GHz</td><td>Peak</td><td>1MHz</td><td>3MHz</td><td>Peak</td></tr>
<tr><td>Average</td><td>1MHz</td><td>3MHz</td><td>Average</td></tr>
</table>
</td></tr>
</table>

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could bestopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reportedin a data sheet.

g. Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin	Detector Type	Result
GFSK	Low Channel: 2402MHz										
	H	2390.00	54.91	30.22	4.85	23.98	53.52	74	-20.48	PK	PASS
	H	2390.00	35.84	30.22	4.85	23.98	34.45	54	-19.55	AV	PASS
	H	2400.00	54.00	30.22	4.85	23.98	52.61	74	-21.39	PK	PASS
	H	2400.00	38.43	30.22	4.85	23.98	37.04	54	-16.96	AV	PASS
	V	2390.00	50.94	30.22	4.85	23.98	49.55	74	-24.45	PK	PASS
	V	2390.00	42.36	30.22	4.85	23.98	40.97	54	-13.03	AV	PASS
	V	2400.00	50.96	30.22	4.85	23.98	49.57	74	-24.43	PK	PASS
	V	2400.00	39.42	30.22	4.85	23.98	38.03	54	-15.97	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	47.17	30.22	4.85	23.98	45.78	74	-28.22	PK	PASS
	H	2485.50	34.94	30.22	4.85	23.98	33.55	54	-20.45	AV	PASS
	H	2500.00	50.98	30.22	4.85	23.98	49.59	74	-24.41	PK	PASS
	H	2500.00	37.95	30.22	4.85	23.98	36.56	54	-17.44	AV	PASS
	V	2483.50	59.30	30.22	4.85	23.98	57.91	74	-16.09	PK	PASS
	V	2485.50	42.81	30.22	4.85	23.98	41.42	54	-12.58	AV	PASS
	V	2500.00	53.67	30.22	4.85	23.98	52.28	74	-21.72	PK	PASS
	V	2500.00	43.42	30.22	4.85	23.98	42.03	54	-11.97	AV	PASS

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

6.POWER SPECTRAL DENSITY TEST

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D0115.247 Meas Guidance v 05r02

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULT

PASS: PLEASE REFER TO APPENDIX: APPENDIX1 FOR DETAILS

7. CHANNEL BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 xRBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULT

PASS: PLEASE REFER TO APPENDIX: APPENDIX1 FOR DETAILS

8.PEAK OUTPUT POWER TEST

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

8.1 APPLIED PROCEDURES/LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

a. The EUT was directly connected to the Power meter

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP

8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULT

PASS: PLEASE REFER TO APPENDIX: APPENDIX1 FOR DETAILS

9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

9.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

9.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

A) Set the RBW = 100KHz.
B) Set the VBW = 300KHz.
C) Sweep time = auto couple.
D) Detector function = peak.
E) Trace mode = max hold.
F) Allow trace to fully stabilize.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP

9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.6 TEST RESULTS

PASS: PLEASE REFER TO APPENDIX: APPENDIX1 FOR DETAILS

10. ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203 /247(c)

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

EUT Antenna:

The antenna is PCB antenna, the best case gain of the antennas are 0dBi, reference to the below photo for details ANTforBLE.



11.APPENDIX1

11.1. -6DB BANDWIDTH

Condition	Antenna	Rate	Frequency (MHz)	-6dB BW(kHz)	limit(kHz)	Result
NVNT	ANT1	1Mbps	2402	701.55	500	Pass
NVNT	ANT1	1Mbps	2440.00	697.26	500	Pass
NVNT	ANT1	1Mbps	2480	698.38	500	Pass

-6dB_Bandwidth_NVNT_ANT1_1Mbps_2402



-6dB_Bandwidth_NVNT_ANT1_1Mbps_2440



-6dB_Bandwidth_NVNT_ANT1_1Mbps_2480



11.2. BANDEDGE

Condition	Antenna	Rate	TX_Frequency (MHz)	Max. Mark Frequency (MHz)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	1Mbps	2402	2399.01	-46.81	-23.43	Pass
NVNT	ANT1	1Mbps	2480	2483.75	-49.54	-24.00	Pass

1_Reference_Level_NVNT_ANT1_1Mbps_2402

2_Bandedge_NVNT_ANT1_1Mbps_2402



1_Reference_Level_NVNT_ANT1_1Mbps_2480

2_Bandedge_NVNT_ANT1_1Mbps_2480



11.3. PEAK OUTPUT POWER

Condition	Antenna	Rate	Frequency (MHz)	Max. Conducted Power(dBm)	Max. Conducted Power(mW)	Limit(mW)	Result
NVNT	ANT1	1Mbps	2402	-2.30	0.59	1000	Pass
NVNT	ANT1	1Mbps	2440.00	-2.81	0.52	1000	Pass
NVNT	ANT1	1Mbps	2480	-2.93	0.51	1000	Pass

Peak_Output_Power_NVNT_ANT1_1Mbps_2402



Peak_Output_Power_NVNT_ANT1_1Mbps_2440



Peak_Output_Power_NVNT_ANT1_1Mbps_2480



11.4. POWER SPECTRAL DENSITY

Condition	Antenna	Rate	Frequency (MHz)	Power Spectral Density(dBm)	Limit(dBm/3kHz)	Result
NVNT	ANT1	1Mbps	2402	-17.74	8	Pass
NVNT	ANT1	1Mbps	2440.00	-18.07	8	Pass
NVNT	ANT1	1Mbps	2480	-18.27	8	Pass

Power_Spectral_Density_NVNT_ANT1_1Mbps_2402



Power_Spectral_Density_NVNT_ANT1_1Mbps_2440



Power_Spectral_Density_NVNT_ANT1_1Mbps_2480



11.5. SPURIOUS EMISSION

Condition	Antenna	Rate	TX_Frequency(MHz)	Spurious MAX.Value(dBm)	Limit	Result
NVNT	ANT1	1Mbps	2402	-50.45	-23.43	Pass
NVNT	ANT1	1Mbps	2440.00	-51.29	-23.88	Pass
NVNT	ANT1	1Mbps	2480	-47.76	-24.00	Pass

1_Reference_Level_NVNT_ANT1_1Mbps_2402

2_Spurious_Emission_NVNT_ANT1_1Mbps_2402



1_Reference_Level_NVNT_ANT1_1Mbps_2440

2_Spurious_Emission_NVNT_ANT1_1Mbps_2440



1_Reference_Level_NVNT_ANT1_1Mbps_2480

2_Spurious_Emission_NVNT_ANT1_1Mbps_2480



12. TEST SETUP PHOTO

Reference to the Setup Photos for details.

13. EUT CONSTRUCTIONAL DETAILS

Please refer to external photos file and internal photos file

※※※※※ **END OF REPORT** ※※※※※