



Radio Test Report

Report No.: STS2512331W01

Issued for

Shenzhen Nito Power Source Technology Co., Ltd.

201-7, Building 2, Shihua Lixing Fengda Industrial Factory,
No. 49 Wuhe Avenue South, Wuhe Community, Bantian
Street, Longgang District, Shenzhen, China

Product Name: 5W Portable Wireless Watch Charger

Brand Name: JOYROOM

Model Name: JR-W19

Series Model(s): N/A

FCC ID: 2BA8X-JR-W19

Test Standards: FCC Part 15 Subpart C

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

**TEST REPORT**

Applicant's Name.....: Shenzhen Nito Power Source Technology Co., Ltd.
Address.....: 201-7, Building 2, Shihua Lixing Fengda Industrial Factory, No. 49
Wuhe Avenue South, Wuhe Community, Bantian Street, Longgang
District, Shenzhen, China
Manufacturer's Name.....: Shenzhen Nito Power Source Technology Co., Ltd.
Address.....: 201-7, Building 2, Shihua Lixing Fengda Industrial Factory, No. 49
Wuhe Avenue South, Wuhe Community, Bantian Street, Longgang
District, Shenzhen, China

Product Description

Product Name.....: 5W Portable Wireless Watch Charger
Brand.....: JOYROOM
Model Number.....: JR-W19
Series Model(s).....: N/A

Test Standards.....: FCC Part 15 Subpart C

Test Procedure.....: ANSI C63.10-2020

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

Date of Test.....:

Date of receipt of test item.....: 11 Dec. 2025
Date (s) of performance of tests.: 11 Dec. 2025 to 15 Dec. 2025
Date of Issue.....: 15 Dec. 2025
Test Result.....: **Pass**

Testing Engineer :

Aaron Bu

(Aaron Bu)

Technical Manager :

Skylar Li

(Skylar Li)

Authorized Signatory :

Bovey Yang

(Bovey Yang)





Table of Contents	Page
1. SUMMARY OF TEST RESULTS	5
1.1 TEST FACTORY	5
1.2 MEASUREMENT UNCERTAINTY	5
2. GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF THE EUT	6
2.2 DESCRIPTION OF THE TEST MODES	7
2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	8
2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	9
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
3. CONDUCTED EMISSION TEST RESULT (SECTION 15.207)	11
3.1 POWER LINE CONDUCTED EMISSION LIMITS	11
3.2 TEST PROCEDURE	12
3.3 TEST SETUP	12
3.4 EUT OPERATING CONDITIONS	12
3.5 TEST RESULTS	13
4. RADIATED& FIELD EMISSION TEST RESULT (SECTION 15.209)	15
4.1 LIMIT	15
4.2 TEST PROCEDURE	15
4.3 TEST SETUP	16
4.4 TEST RESULTS	17
5. 20 DB BANDWIDTH TEST	23
5.1 LIMIT	23
5.2 TEST SETUP	23
5.3 TEST RESULTS	24
APPENDIX-PHOTOS OF TEST SETUP	25



Revision History

Rev.	Issue Date	Report No.	Effect Page	Contents
00	15 Dec. 2025	STS2512331W01	ALL	Initial Issue



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.209(a)	Radiated emission, Spurious Emission	PASS	
2.1049	20 dB Bandwidth	PASS	

1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95** %.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.755\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.874\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 3.80\text{dB}$
4	All emissions, radiated 30M-1GHz	$\pm 4.18\text{dB}$
5	All emissions, radiated 1G-6GHz	$\pm 4.90\text{dB}$
6	All emissions, radiated >6G	$\pm 5.24\text{dB}$
7	Conducted Emission (9KHz-150KHz)	$\pm 2.19\text{dB}$
8	Conducted Emission (150KHz-30MHz)	$\pm 2.53\text{dB}$
9	Occupied Channel Bandwidth	$\pm 3.5\%$
10	Power Spectral Density, conducted	$\pm 1.245\text{dB}$
11	Duty Cycle	$\pm 3.2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	5W Portable Wireless Watch Charger
Brand	JOYROOM
Model Number	JR-W19
Series Model(s)	N/A
Model Difference	N/A
Equipemnt Category	Non-ISM frequency
Antenna Type	loop coil antenna
Operating frequency	300-350kHz, 1.778MHz
Modulation Type	ASK
Power Rating	Type-C/C1 Cable Input: DC 5V/3A, DC 9V/2A, DC 12V/1.5A Type-C/C1 Cable Output: DC 5V/2.4A, DC 9V/2.2A, DC 12V/1.67A Lighting Cable Output: DC 5V/2.4A, DC 9V/2.2A, DC 12V/1.67A Wireless Output: 5W (Max) Battery: DC 3.85V
Adapter	N/A
Battery	DC 3.85V
Wireless charging power	5W
Hardware version number	N/A
Software version number	N/A
Connecting I/O Port(s)	Please refer to the Note 1.

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	NOTE
1	N/A	N/A	Coil	N/A	Antenna



2.2 DESCRIPTION OF THE TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Charging+TX Mode(5W, 1.778MHz)
Mode 2	Charging+TX Mode(2.5W, 300-350kHz)
Mode 3	TX Mode(5W, 1.778MHz)
Mode 4	TX Mode(2.5W, 300-350kHz)

For Conducted Emission	
Final Test Mode	Description
Mode 1	Charging+TX Mode(5W, 1.778MHz)
Mode 2	Charging+TX Mode(2.5W, 300-350kHz)


For Radiated Emission	
Final Test Mode	Description
Mode 1	Charging+TX Mode(5W, 1.778MHz)
Mode 2	Charging+TX Mode(2.5W, 300-350kHz)
Mode 3	TX Mode(5W, 1.778MHz)
Mode 4	TX Mode(2.5W, 300-350kHz)




2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters

Radiated Emission Test Mode 1 and Mode 2




Mode 3 and Mode 4



Conducted Emission Test

Mode 1 and Mode 2





2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Note
E-1	Adapter	ZTC	NB-A515A	N/A
E-2	Load	N/A	N/A	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-1	N/A	N/A	0.8m	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2025.09.25	2026.09.24
Signal Analyzer	R&S	FSV 40-N	101823	2025.09.26	2026.09.25
Active loop Antenna	ZHINAN	ZN30900C	16035	2025.02.25	2026.02.24
Bilog Antenna	TESEQ	CBL6111D	34678	2025.09.27	2027.09.26
Pre-Amplifier (0.1M-3GHz)	EM	EM330	060665	2025.02.22	2026.02.21
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2025.09.25	2026.09.24
Limtter	CYBERTEK	EM5010	N/A	2025.09.25	2026.09.24
LISN	R&S	ENV216	101242	2025.09.25	2026.09.24
LISN	EMCO	3810/2NM	23625	2025.09.25	2026.09.24
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Signal Analyzer	Agilent	N9020A	MY51510623	2025.02.22	2026.02.21
Power detector group	Keysight	NW2021031	N/A	2025.09.23	2026.09.22
Switch control box	MW	MW100-RFCB	N/A	N/A	N/A
Temperature& Humidity test chamber	Safety test	AG80L	171200018	2025.02.22	2026.02.21
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23
Test SW	MW	MTS 8310 2.0.0.0			



3. CONDUCTED EMISSION TEST RESULT (SECTION 15.207)

3.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Class B (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of "*" marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.


3.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.5 TEST RESULTS

Temperature:	25.1°C	Relative Humidity:	59%
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode:	Mode 1(Worst case mode)		




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement = Reading Level + Correct Factor
4. Over = Measurement - Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz		dB	dBuV	dBuV	dB	Detector
1		0.3791	21.85	20.05	41.90	58.30	-16.40	QP
2		0.3791	6.62	20.05	26.67	48.30	-21.63	AVG
3		0.9087	24.29	20.27	44.56	56.00	-11.44	QP
4		0.9087	11.78	20.27	32.05	46.00	-13.95	AVG
5		1.8000	18.98	20.20	39.18	56.00	-16.82	QP
6		1.8000	17.17	20.20	37.37	46.00	-8.63	AVG
7		5.3900	17.77	20.76	38.53	60.00	-21.47	QP
8		5.3900	16.28	20.76	37.04	50.00	-12.96	AVG
9		8.9637	21.93	21.20	43.13	60.00	-16.87	QP
10	*	8.9637	20.76	21.20	41.96	50.00	-8.04	AVG
11		21.4860	19.16	23.77	42.93	60.00	-17.07	QP
12		21.4860	17.60	23.77	41.37	50.00	-8.63	AVG



Temperature:	25.1°C	Relative Humidity:	59%
Test Voltage:	AC 120V/60Hz	Phase:	N
Test Mode:	Mode 1(Worst case mode)		



Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement = Reading Level + Correct Factor
4. Over = Measurement - Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz		dB	dBuV	dBuV	dB	
1		0.2208	26.50	20.04	46.54	62.79	-16.25	QP
2		0.2208	16.24	20.04	36.28	52.79	-16.51	AVG
3		0.3338	25.91	20.05	45.96	59.36	-13.40	QP
4		0.3338	16.06	20.05	36.11	49.36	-13.25	AVG
5	*	0.9039	28.28	20.27	48.55	56.00	-7.45	QP
6		0.9039	9.41	20.27	29.68	46.00	-16.32	AVG
7		1.8000	16.32	20.20	36.52	56.00	-19.48	QP
8		1.8000	12.99	20.20	33.19	46.00	-12.81	AVG
9		5.3900	17.42	20.76	38.18	60.00	-21.82	QP
10		5.3900	15.68	20.76	36.44	50.00	-13.56	AVG
11		14.2665	21.49	22.31	43.80	60.00	-16.20	QP
12		14.2665	19.20	22.31	41.51	50.00	-8.49	AVG



4. RADIATED& FIELD EMISSION TEST RESULT (SECTION 15.209)

4.1 LIMIT

Frequency [MHz]	Field Strength [uV/m]	Measurement Distance [Meters]
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

§ 15.209(d) The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

4.2 TEST PROCEDURE


- a. The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz.
- b. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- d. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

4.3 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz





4.4 TEST RESULTS

Temperature :	23.4℃	Relative Humidity :	60%
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1
Polarization:	Coplanar (the worst mode)		


4.4.1 Spurious Radiated Emission Below 30 MHz
9KHz- 30MHz

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		0.0618	55.77	-7.53	48.24	111.7	-63.54	peak
2		0.0976	49.28	-7.51	41.77	107.8	-66.05	peak
3		0.1552	43.77	-7.60	36.17	103.7	-67.62	peak
4		0.3815	45.67	-7.65	38.02	95.97	-57.95	peak
5		0.7607	32.07	-7.36	24.71	69.99	-45.28	peak
6	*	1.7976	51.12	-7.33	43.79	69.54	-25.75	peak



Temperature :	23.4℃	Relative Humidity :	60%
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 2
Polarization:	Coplanar (the worst mode)		

9KHz- 30MHz




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		0.0618	54.64	-7.53	47.11	111.7	-64.67	peak
2		0.3220	55.51	-7.69	47.82	97.45	-49.63	peak
3		0.3815	45.17	-7.65	37.52	95.97	-58.45	peak
4	*	0.6468	39.43	-7.42	32.01	71.40	-39.39	peak
5		0.9704	33.38	-7.36	26.02	67.88	-41.86	peak
6		3.7000	27.76	-7.13	20.63	69.54	-48.91	peak



4.4.2 Spurious Radiated Emission below 1 GHz

Temperature :	23.4°C	Relative Humidity :	60%
Test Voltage :	AC 120V/60Hz	Test Mode :	Mode 1(Worst mode)

The following table shows the highest levels of radiated emissions on polarizations of horizontal



Remark:


1. Margin = Result (Result = Reading + Factor) - Limit
2. Factor = Antenna factor + Cable attenuation factor (cable loss) - Amplifier gain

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	42.0065	32.50	-11.79	20.71	40.00	-19.29	QP
2 *	69.8448	35.93	-14.14	21.79	40.00	-18.21	QP
3	141.8262	33.19	-11.20	21.99	43.50	-21.51	QP
4	234.1682	40.62	-12.85	27.77	46.00	-18.23	QP
5	264.7456	38.91	-11.65	27.26	46.00	-18.74	QP
6	432.5455	31.15	-7.18	23.97	46.00	-22.03	QP



Temperature :	23.4 °C	Relative Humidity :	60%
Test Voltage :	AC 120V/60Hz	Test Mode :	Mode 1(Worst mode)

The following table shows the highest levels of radiated emissions on polarizations of vertical



Remark:


1. Margin = Result (Result =Reading + Factor)-Limit
2. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	43.2014	37.71	-11.74	25.97	40.00	-14.03	QP
2 *	66.9668	42.43	-13.75	28.68	40.00	-11.32	QP
3	142.3240	36.10	-11.17	24.93	43.50	-18.57	QP
4	174.4240	35.82	-12.47	23.35	43.50	-20.15	QP
5	237.4755	36.06	-12.71	23.35	46.00	-22.65	QP
6	539.4773	33.85	-4.66	29.19	46.00	-16.81	QP



Temperature :	23.4°C	Relative Humidity :	60%
Test Voltage :	AC 120V/60Hz	Test Mode :	Mode 2(Worst mode)

The following table shows the highest levels of radiated emissions on polarizations of horizontal



Remark:

3. Margin = Result (Result =Reading + Factor)-Limit


4. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	41.1319	31.57	-11.82	19.75	40.00	-20.25	QP
2	114.5146	45.06	-13.37	31.69	43.50	-11.81	QP
3	164.9071	46.02	-11.77	34.25	43.50	-9.25	QP
4 *	257.4221	50.88	-11.90	38.98	46.00	-7.02	QP
5	357.9286	41.77	-8.95	32.82	46.00	-13.18	QP
6	501.1788	33.34	-5.73	27.61	46.00	-18.39	QP



Temperature :	23.4 °C	Relative Humidity :	60%
Test Voltage :	AC 120V/60Hz	Test Mode :	Mode 2(Worst mode)

The following table shows the highest levels of radiated emissions on polarizations of vertical



Remark:

3. Margin = Result (Result =Reading + Factor)-Limit

4. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	57.1914	34.32	-12.44	21.88	40.00	-18.12	QP
2	116.1320	41.32	-13.16	28.16	43.50	-15.34	QP
3	167.2366	40.11	-11.94	28.17	43.50	-15.33	QP
4	263.8190	35.79	-11.68	24.11	46.00	-21.89	QP
5	494.1983	37.73	-5.88	31.85	46.00	-14.15	QP
6 *	750.1082	32.56	-0.36	32.20	46.00	-13.80	QP



5. 20 DB BANDWIDTH TEST

5.1 Limit

FCC Part 2.1049, Only applicable to report.

5.2 TEST SETUP

1. Set RBW = 1%~5% OBW.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.







5.3 TEST RESULTS

Operating Frequency (kHz)	20 dB Bandwidth (Hz)
322.4	186
1798	1159

322.4kHz



1798kHz





APPENDIX-PHOTOS OF TEST SETUP

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

※※※※※END OF THE REPORT※※※※※