RF Exposure evaluation

According to 447498 D01 General RF Exposure Guidance v06
The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] ·[√f(GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where f(GHz) is the RF channel transmit frequency in GHz
Power and distance are rounded to the nearest mW and mm before calculation
The result is rounded to one decimal place for comparison

eirp = pt x gt = $(EXd)^2/30$
where:
pt = transmitter output power in watts,
gt = numeric gain of the transmitting antenna (unitless),
E = electric field strength in V/m, --- $10^{((dBuV/m)/20)}/10^6$
d = measurement distance in meters (m)---3m
So pt = $(EXd)^2/30$ x gt

For Worst case Mode: 915MHz

Field strength = 73.46 dBuV/m @3m
Ant gain 1.5dBi; so Ant numeric gain=1.41

So pt= $\{[10^{(73.46/20)}/10^6 \text{ x}3]^2/30\text{x}1\}$ x 1000 mW =0.0094 mW
So (0.0094mW/5mm) x √0.915 GHz = 0.0018<3

Then SAR evaluation is not required