TCT 通测检测 TESTING CENTRE TECHNOLOGY

TEST REPORT

FCC ID. ..... :	2BAA3-TC233	
Test Report No..... :	TCT230216E019	
Date of issue..... :	Aug. 11, 2023	
Testing laboratory ..... :	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name..... :	Shenzhen Zhimu Technology Co., Ltd.	
Address..... :	Room 1501, West block, Building 6, Phase 2, Tian'an Yungu industrial park, Bantian Street, Longgang District, Shenzhen, China	
Manufacturer's name ... :	Shenzhen Digital Dragon Electronics Co., LTD. (Dongguan) branch	
Address..... :	No.6, Jinshan 1st Street, Rome Village, Qingxi Town, Dongguan City, China	
Standard(s) ..... :	FCC CFR Title 47 Part 1.1307	
Product Name..... :	Dog camera T2	
Trade Mark ..... :	dokoo	
Model/Type reference..... :	ZS-TC233-US	
Rating(s)..... :	Refer to EUT description of page 3	
Date of receipt of test item ..... :	Feb. 16, 2023	
Date (s) of performance of test..... :	Feb. 16, 2023 - Aug. 11, 2023	
Tested by (+signature) ... :	Yannie ZHONG	Yannie Zhong
Check by (+signature).... :	Beryl ZHAO	Beryl Zhao
Approved by (+signature):	Tomsin	Tomsin

SHENZHEN TONGCE TESTING LAB TCT

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Table of Contents

1. General Product Information 3
1.1. EUT description 3
1.2. Model(s) list 3
2. General Information 4
2.1. Test environment and mode 4
2.2. Description of Support Units 4
3. Facilities and Accreditations 5
3.1. Facilities 5
3.2. Location 5
4. Test Results and Measurement Data 6

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

1. General Product Information

1.1. EUT description

Product Name.....:	Dog camera T2
Model/Type reference.....:	ZS-TC233-US
Sample Number.....:	TCT230216E018-0101
Operation Frequency.....:	2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20)) 2422MHz~2452MHz (802.11n(HT40))
Modulation Type.....:	DSSS(802.11b), OFDM (802.11g/802.11n)
Antenna Type.....:	FPC Antenna
Antenna Gain.....:	4.64dBi
Rating(s).....:	Adapter Information 1: Model: TPA-46050200UU Input: AC 100-240V, 50/60Hz, 0.3A Output: DC 5.0V, 2000mA Adapter Information 2: Model: KE012B-0500200M Input: AC 100-240V, 50/60Hz, 0.4A Max Output: DC 5.0V, 2.0A

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

None.

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

2. General Information

2.1. Test environment and mode

Item	Normal condition
Temperature	+25ºC
Voltage	AC 120V/60Hz
Humidity	56%
Atmospheric Pressure:	1008 mbar
Test Mode:	
Transmitting Mode:	Keep the EUT in continuous transmitting by select channel

2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.

2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

3. Facilities and Accreditations

3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

  SHENZHEN TONGCE TESTING LAB

  Designation Number: CN1205

  The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

  SHENZHEN TONGCE TESTING LAB

  CAB identifier: CN0031

  The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

4. Test Results and Measurement Data

According to §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Remark: 1) The maximum output power for antenna is 17.32dBm (53.95mW) at 2462MHz, 4.64dBi antenna gain (with 2.91 numeric antenna gain.)
2) For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20cm, even if the calculation indicate that the MPE distance would be lesser.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where E = *Field Strength in Volts / meter*
P = *Power in Watts*
G=*Numeric antenna gain*
d=*Distance in meters*
S=*Power Density in milliwatts / square centimeter*

Maximum Permissible Exposure
output power= 53.95mW
Numeric Antenna gain= 2.91
Substituting the MPE safe distance using d=20cm into above equation.
Yields:
*S=0.000199*P*G*
Where P=Power in mW
G=Numeric antenna gain
S=Power density in mW/cm^2
Power density= 0.031242mW/cm^2

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm^2 even if the calculation indicates that the power density would be larger.)

********END OF REPORT********

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com