

RF Exposure Evaluation Report

Report Reference No...... : **MTEB26010253-H**

FCC ID..... : **2BAA5-GI30PRO**

Compiled by

(position+printed name+signature)..: File administrators
Ekaterina Zhang

Ekaterina Zhang

Supervised by

(position+printed name+signature)..: Test Engineer Sunny Deng

Sunny Deng

Approved by

(position+printed name+signature)..: Manager Yvette Zhou

Yvette Zhou

Date of issue..... : **Jan.29,2026**

Representative Laboratory Name. : **Shenzhen Most Technology Service Co., Ltd.**

Address..... : No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park,
Nanshan, Shenzhen, Guangdong, China.

Applicant's name..... : **AcoustMax International Corporation**

Address..... : Room 501,Lingyun Building ,HongLang North 2 Road, Baoan
District, ShenZhen, China

Test specification/ Standard..... : **47 CFR Part 1.1307;47 CFR Part 1.1310**

KDB447498D01 General RF Exposure Guidance v06

TRF Originator..... : Shenzhen Most Technology Service Co., Ltd.

Shenzhen Most Technology Service Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description..... : Monster GI30 PRO

Trade Mark..... : Monster

Model/Type reference..... : MNGI30-2

Listed Models : GI30 PRO,MNGI30 PRO,MINGI30 PRO-S,MNGI30 PRO-X,
MINGI30 PRO PULS,MNGI30PRO-S-C,MNGI30PRO-Z,
MINGI30 PRO-WIFI

Modulation Type..... : GFSK
GFSK, $\pi/4$ DQPSK,8DPSK

Operation Frequency..... : From 2402MHz to 2480MHz

Hardware Version..... : V02

Software Version..... : V05

Rating..... : AC100-240V~50/60Hz,600W

Result..... : PASS

TEST REPORT

Equipment under Test : Monster GI30 PRO

Model /Type : MNGI30-2

Listed Models : GI30 PRO,MNGI30 PRO,MINGI30 PRO-S,MNGI30 PRO-X,
MINGI30 PRO PULS,MNGI30PRO-S-C,MNGI3OPRO-Z,
MINGI30 PRO-WIFI

Remark : Only the model “MNGI30-2” was tested, The electrical circuit design, layout, components used and internal wiring are identical, Only the model name and appearance color is different.

Applicant : AcoustMax International Corporation

Address : Room 501,Lingyun Building ,HongLang North 2 Road, Baoan District, ShenZhen, China

Manufacturer : Ningbo Polinata Electronics Co., Ltd

Address : NO. 9 XINRUI ROAD, LONGXING VILLAGE, WUXIANG TOWN, YINZHOU DISTRICT, NINGBO

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

1. Revision History

Revision	Issue Date	Revisions	Revised By
00	2026.01.29	Initial Issue	Ekaterina Zhang

2. SAR Evaluation

2.1 RF Exposure Compliance Requirement

2.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

2.1.2 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$ Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.1.3 EUT RF Exposure

BLE

GFSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	-0.81	-0.81 ± 1	0.19
Middle(2440MHz)	-1.38	-1.38 ± 1	-0.38
Highest(2480MHz)	-0.84	-0.84 ± 1	0.16

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Maximum Peak Conducted Output Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Lowest(2402MHz)	0.19	1.04	0	0.0002	1.0	Pass

Note: 1) Refer to report **MTEB26010253-R** for EUT test Max Conducted average Output Power value.

Note: 2) $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2) = (1.04 \cdot 1) / (4 \cdot 3.1416 \cdot 20^2) = 0.0002$

BT classic(EDR 1#)

GFSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	-0.89	-0.89 ± 1	0.11
Middle(2441MHz)	-1.34	-1.34 ± 1	-0.34
Highest(2480MHz)	-0.80	-0.80 ± 1	0.20

$\pi/4$ DQPSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	0.16	0.16 ± 1	0.84
Middle(2441MHz)	-0.53	-0.53 ± 1	0.47
Highest(2480MHz)	0.03	0.03 ± 1	1.03

8DPSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	0.49	0.49 ± 1	1.49
Middle(2441MHz)	0.02	0.02 ± 1	1.02
Highest(2480MHz)	0.50	0.50 ± 1	1.50

Worst case: 8DPSK						
Channel	Maximum tune-up Power (dBm)	Maximum tune-up Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Highest(2480MHz)	1.50	1.41	0	0.00028	1.0	Pass

Note: 1) Refer to report **MTEB26010253-R1** for EUT test Max Conducted average Output Power value.Note: 2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (1.41 * 1) / (4 * 3.1416 * 20^2) = 0.00028$

BT classic(EDR 2#)

GFSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	-0.95	-0.95 ± 1	0.05
Middle(2441MHz)	-3.49	-3.49 ± 1	-2.49
Highest(2480MHz)	-2.94	-2.94 ± 1	-1.49

π /4DQPSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	-2.54	-2.54 ± 1	-1.54
Middle(2441MHz)	-2.71	-2.71 ± 1	-1.71
Highest(2480MHz)	-2.12	-2.12 ± 1	-1.12

8DPSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	-2.13	-2.13 ± 1	-1.13
Middle(2441MHz)	-2.19	-2.19 ± 1	-1.19
Highest(2480MHz)	-1.62	-1.62 ± 1	-0.62

Worst case: GFSK						
Channel	Maximum tune-up Power (dBm)	Maximum tune-up Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Lowest(2402MHz)	0.05	1.01	0	0.0002	1.0	Pass

Note: 1) Refer to report **MTEB26010253-R2** for EUT test Max Conducted average Output Power value.

Note: 2) $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2) = (1.01 \cdot 1) / (4 \cdot 3.1416 \cdot 20^2) = 0.0002$