


LTE Band 13 (Part 27)



LTE band 13 - Low CH QPSK-5




LTE band 13 - Low CH 16QAM-5




LTE band 13 - Middle CH QPSK-5




LTE band 13 - Middle CH 16QAM-5



LTE band 13 - High CH QPSK-5



LTE band 13 - High CH 16QAM-5



LTE Band 14 (Part 27)




LTE band 14 - Low CH QPSK-5



LTE band 14 - Low CH 16QAM-5




LTE band 14 - Middle CH QPSK-5




LTE band 14 - Middle CH 16QAM-5




LTE band 14 - High CH QPSK-5



LTE band 14 - High CH 16QAM-5




LTE Band 66 (Part 27)
















LTE Band 71(Part 27)









10 SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Test Requirement:	FCC Part 2.1051, 22.917(a), 24.238(a), 27.53(h), 27.53(m)(4); 90.691
Test Method:	ANSI C63.26:2015 ANSI/TIA-603-E:2016
Test Mode:	TX transmitting


10.1 EUT Operation

Operating Environment :

Temperature:	23.5 °C
Humidity:	52.1 % RH
Atmospheric Pressure:	101.3kPa

10.2 Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonics.



10.3 Test Result

PASS

LTE Band

Please refer to the Annex C. LTE Transmitter Spurious Emissions for LTE Band 2/4/5/12/13/14/66/71.

11 SPURIOUS RADIATED EMISSIONS


Test Requirement:	FCC Part 2.1053, 22.917, 24.238, 27.53(h), 27.53(m)(4); 90.691
Test Method:	ANSI C63.26:2015 ANSI/TIA-603-E:2016
Test Mode:	TX transmitting

11.1 EUT Operation


Operating Environment :	
Temperature:	23.5 °C
Humidity:	52.1 % RH
Atmospheric Pressure:	101.2kPa

11.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site. The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



11.3 Spectrum Analyzer Setup

30MHz ~ 1GHz

Sweep Speed Auto
Detector PK
Resolution Bandwidth..... 100kHz
Video Bandwidth..... 300kHz

Above 1GHz

Sweep Speed Auto
Detector PK
Resolution Bandwidth..... 1MHz
Video Bandwidth..... 3MHz
Detector Ave.
Resolution Bandwidth..... 1MHz
Video Bandwidth..... 10Hz

11.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m for below 1GHz and 1.5m for above 1GHz above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from 30MHz up to the tenth harmonic of the highest fundamental frequency.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the Z position. So the data shown was the Z position only.
7. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg (\text{TXpwr in Watts}/0.001)$ – the absolute level
Spurious attenuation limit in dB = $43 + 10 \lg (\text{power out in Watts})$
8. Repeat above procedures until the measurements for all frequencies are completed.

11.5 Summary of Test Results

Remark: Test performed from 30MHz to 10th harmonics with low/middle/high channels, only the worst data were recorded.

LTE Band 2

Frequency	Receiver Reading	Turn table Angle	RX Antenna		Substituted			Absolute Level	Result	
			Height	Polar	SG Level	Cable	Antenna Gain		Limit	Margin
(MHz)	(dBμV)	Degree	(m)	(H/V)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dB)
LTE BAND 2 Channel 18607										
223.12	47.04	286	1.4	H	-63.47	0.15	0.00	-63.62	-13.00	-50.62
223.12	37.69	359	2.2	V	-69.90	0.15	0.00	-70.05	-13.00	-57.05
3701.40	65.95	2	1.8	H	-45.59	2.37	12.50	-35.46	-13.00	-22.46
3701.40	59.98	88	2.1	V	-49.83	2.37	12.50	-39.70	-13.00	-26.70
5552.10	53.58	152	1.4	H	-56.03	2.86	12.90	-45.99	-13.00	-32.99
5552.10	44.73	140	1.9	V	-64.15	2.86	12.90	-54.11	-13.00	-41.11
LTE BAND 2 Channel 18900										
223.12	48.01	62	1.1	H	-62.50	0.15	0.00	-62.65	-13.00	-49.65
223.12	38.49	190	2.2	V	-69.10	0.15	0.00	-69.25	-13.00	-56.25
3760.00	58.10	352	1.3	H	-53.44	2.37	12.50	-43.31	-13.00	-30.31
3760.00	52.61	140	1.4	V	-57.20	2.37	12.50	-47.07	-13.00	-34.07
5640.00	46.14	349	1.9	H	-63.47	2.86	12.90	-53.43	-13.00	-40.43
5640.00	37.46	137	2.1	V	-71.42	2.86	12.90	-61.38	-13.00	-48.38
LTE BAND 2 Channel 19193										
223.12	47.86	88	2.1	H	-62.65	0.15	0.00	-62.80	-13.00	-49.80
223.12	37.85	257	1.4	V	-69.74	0.15	0.00	-69.89	-13.00	-56.89
3818.60	50.94	216	1.3	H	-59.91	2.37	12.60	-49.68	-13.00	-36.68
3818.60	46.49	153	2.2	V	-62.82	2.37	12.60	-52.59	-13.00	-39.59
5727.90	38.24	173	1.0	H	-71.11	2.86	12.90	-61.07	-13.00	-48.07
5727.90	30.94	237	2.1	V	-77.56	2.86	12.90	-67.52	-13.00	-54.52

LTE Band 4

Frequency	Receiver Reading	Turn table Angle	RX Antenna		Substituted			Absolute Level	Result	
			Height	Polar	SG Level	Cable	Antenna Gain		Limit	Margin
(MHz)	(dBμV)	Degree	(m)	(H/V)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dB)
LTE BAND 4 Channel 19957										
223.12	38.99	15	2.1	H	-71.52	0.15	0.00	-71.67	-13.00	-58.67
223.12	30.22	217	1.8	V	-77.37	0.15	0.00	-77.52	-13.00	-64.52
3421.40	65.95	39	1.3	H	-47.10	2.34	12.40	-37.04	-13.00	-24.04
3421.40	59.98	143	1.1	V	-51.17	2.34	12.40	-41.11	-13.00	-28.11
5132.10	53.58	24	1.8	H	-55.83	2.79	12.70	-45.92	-13.00	-32.92
5132.10	44.73	161	1.6	V	-64.04	2.79	12.70	-54.13	-13.00	-41.13
LTE BAND 4 Channel 20175										
223.12	39.07	343	1.4	H	-71.44	0.15	0.00	-71.59	-13.00	-58.59
223.12	29.50	321	1.6	V	-78.09	0.15	0.00	-78.24	-13.00	-65.24
3465.00	58.63	332	1.7	H	-54.42	2.37	12.50	-44.29	-13.00	-31.29
3465.00	52.06	88	1.2	V	-59.09	2.37	12.50	-48.96	-13.00	-35.96
5197.50	45.64	159	1.7	H	-63.77	2.79	12.70	-53.86	-13.00	-40.86
5197.50	37.94	313	1.4	V	-70.83	2.79	12.70	-60.92	-13.00	-47.92
LTE BAND 4 Channel 20393										
223.12	38.48	115	1.9	H	-72.03	0.15	0.00	-72.18	-13.00	-59.18
223.12	29.40	353	1.2	V	-78.19	0.15	0.00	-78.34	-13.00	-65.34
3508.60	51.47	249	1.5	H	-61.17	2.37	12.50	-51.04	-13.00	-38.04
3508.60	45.38	279	1.5	V	-65.35	2.37	12.50	-55.22	-13.00	-42.22
5262.90	39.39	34	2.1	H	-70.19	2.81	12.80	-60.20	-13.00	-47.20
5262.90	30.76	298	2.0	V	-78.04	2.81	12.80	-68.05	-13.00	-55.05

LTE Band 5

Frequency	Receiver Reading	Turn table Angle	RX Antenna		Substituted			Absolute Level	Result	
			Height	Polar	SG Level	Cable	Antenna Gain		Limit	Margin
(MHz)	(dBμV)	Degree	(m)	(H/V)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dB)
LTE BAND 5 Channel 20407										
223.12	39.85	277	1.8	H	-70.66	0.15	0.00	-70.81	-13.00	-57.81
223.12	30.36	355	1.9	V	-77.23	0.15	0.00	-77.38	-13.00	-64.38
1649.40	65.95	51	2.1	H	-47.10	2.34	12.40	-37.04	-13.00	-24.04
1649.40	59.98	332	1.8	V	-51.17	2.34	12.40	-41.11	-13.00	-28.11
2474.10	53.58	103	1.5	H	-55.83	2.79	12.70	-45.92	-13.00	-32.92
2474.10	44.73	275	2.0	V	-64.04	2.79	12.70	-54.13	-13.00	-41.13
LTE BAND 5 Channel 20525										
223.12	39.44	141	1.5	H	-71.07	0.15	0.00	-71.22	-13.00	-58.22
223.12	30.21	122	1.6	V	-77.38	0.15	0.00	-77.53	-13.00	-64.53
1673.00	59.90	225	1.1	H	-53.15	2.37	12.50	-43.02	-13.00	-30.02
1673.00	52.38	165	1.6	V	-58.77	2.37	12.50	-48.64	-13.00	-35.64
2509.50	46.63	236	1.2	H	-62.78	2.79	12.70	-52.87	-13.00	-39.87
2509.50	37.07	311	1.7	V	-71.70	2.79	12.70	-61.79	-13.00	-48.79
LTE BAND 5 Channel 20643										
223.12	39.81	221	1.0	H	-70.70	0.15	0.00	-70.85	-13.00	-57.85
223.12	30.50	154	1.7	V	-77.09	0.15	0.00	-77.24	-13.00	-64.24
1696.60	52.21	244	1.2	H	-60.43	2.37	12.50	-50.30	-13.00	-37.30
1696.60	46.35	305	1.7	V	-64.38	2.37	12.50	-54.25	-13.00	-41.25
2544.90	40.42	224	1.1	H	-69.16	2.81	12.80	-59.17	-13.00	-46.17
2544.90	29.69	102	2.0	V	-79.11	2.81	12.80	-69.12	-13.00	-56.12

LTE Band 12

Frequency	Receiver Reading	Turn table Angle	RX Antenna		Substituted			Absolute Level	Result	
			Height	Polar	SG Level	Cable	Antenna Gain		Limit	Margin
(MHz)	(dBμV)	Degree	(m)	(H/V)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dB)
LTE BAND 12 Channel 23017										
223.12	53.56	30	1.1	H	-56.95	0.15	0.00	-57.10	-13.00	-44.10
223.12	44.06	10	2.1	V	-63.53	0.15	0.00	-63.68	-13.00	-50.68
1399.40	65.95	223	1.0	H	-47.10	2.34	12.40	-37.04	-13.00	-24.04
1399.40	59.98	195	1.9	V	-51.17	2.34	12.40	-41.11	-13.00	-28.11
2099.10	53.58	348	1.7	H	-55.83	2.79	12.70	-45.92	-13.00	-32.92
2099.10	44.73	59	1.9	V	-64.04	2.79	12.70	-54.13	-13.00	-41.13
LTE BAND 12 Channel 23095										
223.12	54.26	158	2.2	H	-56.25	0.15	0.00	-56.40	-13.00	-43.40
223.12	43.85	354	2.2	V	-63.74	0.15	0.00	-63.89	-13.00	-50.89
1415.00	58.68	118	2.2	H	-54.37	2.37	12.50	-44.24	-13.00	-31.24
1415.00	52.06	197	1.4	V	-59.09	2.37	12.50	-48.96	-13.00	-35.96
2122.50	47.09	214	2.1	H	-62.32	2.79	12.70	-52.41	-13.00	-39.41
2122.50	37.87	337	1.4	V	-70.90	2.79	12.70	-60.99	-13.00	-47.99
LTE BAND 12 Channel 23173										
223.12	53.56	105	1.5	H	-56.95	0.15	0.00	-57.10	-13.00	-44.10
223.12	43.88	90	1.8	V	-63.71	0.15	0.00	-63.86	-13.00	-50.86
1430.60	51.84	234	1.5	H	-60.80	2.37	12.50	-50.67	-13.00	-37.67
1430.60	45.30	307	1.2	V	-65.43	2.37	12.50	-55.30	-13.00	-42.30
2145.90	40.18	148	1.5	H	-69.40	2.81	12.80	-59.41	-13.00	-46.41
2145.90	30.82	93	1.6	V	-77.98	2.81	12.80	-67.99	-13.00	-54.99

LTE Band 13

Frequency	Receiver Reading	Turn table Angle	RX Antenna		Substituted			Absolute Level	Result	
			Height	Polar	SG Level	Cable	Antenna Gain		Limit	Margin
(MHz)	(dBμV)	Degree	(m)	(H/V)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dB)
LTE BAND 13 Channel 23205										
223.12	39.25	53	1.4	H	-71.26	0.15	0.00	-71.41	-13.00	-58.41
223.12	30.89	136	1.8	V	-76.70	0.15	0.00	-76.85	-13.00	-63.85
1559.00	65.95	123	1.3	H	-51.10	2.34	12.40	-41.04	-13.00	-28.04
1559.00	59.98	279	1.5	V	-51.17	2.34	12.40	-41.11	-13.00	-28.11
2338.50	53.58	61	1.4	H	-55.83	2.79	12.70	-45.92	-13.00	-32.92
2338.50	44.73	251	1.6	V	-64.04	2.79	12.70	-54.13	-13.00	-41.13
LTE BAND 13 Channel 23230										
223.12	38.92	6	2.0	H	-71.59	0.15	0.00	-71.74	-13.00	-58.74
223.12	31.70	305	2.1	V	-75.89	0.15	0.00	-76.04	-13.00	-63.04
1564.00	58.92	205	1.2	H	-54.13	2.37	12.50	-44.00	-13.00	-31.00
1564.00	52.08	322	1.8	V	-59.07	2.37	12.50	-48.94	-13.00	-35.94
2346.00	46.03	181	1.1	H	-63.38	2.79	12.70	-53.47	-13.00	-40.47
2346.00	36.86	46	1.9	V	-71.91	2.79	12.70	-62.00	-13.00	-49.00
LTE BAND 13 Channel 23255										
223.12	38.43	228	2.1	H	-72.08	0.15	0.00	-72.23	-13.00	-59.23
223.12	30.85	136	1.8	V	-76.74	0.15	0.00	-76.89	-13.00	-63.89
1569.00	51.76	163	1.3	H	-60.88	2.37	12.50	-50.75	-13.00	-37.75
1569.00	45.71	201	1.4	V	-65.02	2.37	12.50	-54.89	-13.00	-41.89
2353.50	39.27	113	1.1	H	-70.31	2.81	12.80	-60.32	-13.00	-47.32
2353.50	29.48	88	2.2	V	-79.32	2.81	12.80	-69.33	-13.00	-56.33

LTE Band 14

Frequency	Receiver Reading	Turn table Angle	RX Antenna		Substituted			Absolute Level	Result	
			Height	Polar	SG Level	Cable	Antenna Gain		Limit	Margin
(MHz)	(dBμV)	Degree	(m)	(H/V)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dB)
LTE BAND 14 Channel 23305										
223.12	39.56	41	1.8	H	-70.95	0.15	0.00	-71.10	-13.00	-58.10
223.12	32.29	225	1.7	V	-75.30	0.15	0.00	-75.45	-13.00	-62.45
1581.00	65.95	329	2.1	H	-44.29	2.79	12.70	-34.38	-13.00	-21.38
1581.00	59.98	274	1.3	V	-51.79	2.79	12.70	-41.88	-13.00	-28.88
2371.50	53.58	353	1.9	H	-58.96	3.12	11.50	-50.58	-13.00	-37.58
2371.50	44.73	183	1.3	V	-68.70	3.12	11.50	-60.32	-13.00	-47.32
LTE BAND 14 Channel 23330										
223.12	39.71	291	2.0	H	-70.80	0.15	0.00	-70.95	-13.00	-57.95
223.12	33.01	228	2.1	V	-74.58	0.15	0.00	-74.73	-13.00	-61.73
1587.00	59.24	264	1.7	H	-51.00	2.37	12.50	-40.87	-13.00	-27.87
1587.00	53.93	51	1.7	V	-57.84	2.37	12.50	-47.71	-13.00	-34.71
2380.50	47.48	168	1.4	H	-65.06	3.12	11.50	-56.68	-13.00	-43.68
2380.50	38.01	207	1.5	V	-75.42	3.12	11.50	-67.04	-13.00	-54.04
LTE BAND 14 Channel 23355										
223.12	40.21	258	1.6	H	-70.30	0.15	0.00	-70.45	-13.00	-57.45
223.12	32.89	108	1.1	V	-74.70	0.15	0.00	-74.85	-13.00	-61.85
1591.00	52.66	71	1.0	H	-57.58	2.37	12.50	-47.45	-13.00	-34.45
1591.00	46.11	350	1.5	V	-65.66	2.37	12.50	-55.53	-13.00	-42.53
2386.50	41.43	197	2.1	H	-71.11	3.12	11.50	-62.73	-13.00	-49.73
2386.50	31.34	334	1.1	V	-82.09	3.12	11.50	-73.71	-13.00	-60.71

LTE Band 66

Frequency	Receiver Reading	Turn table Angle	RX Antenna		Substituted			Absolute Level	Result	
			Height	Polar	SG Level	Cable	Antenna Gain		Limit	Margin
(MHz)	(dBμV)	Degree	(m)	(H/V)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dB)
LTE BAND 66 Channel 131979										
223.12	57.73	145	1.4	H	-52.78	0.15	0.00	-52.93	-13.00	-39.93
223.12	58.30	352	1.3	V	-49.29	0.15	0.00	-49.44	-13.00	-36.44
1413.00	65.95	165	1.1	H	-45.59	2.37	12.50	-35.46	-13.00	-22.46
1413.00	59.98	133	1.5	V	-49.83	2.37	12.50	-39.70	-13.00	-26.70
2119.50	53.58	13	1.3	H	-56.03	2.86	12.90	-45.99	-13.00	-32.99
2119.50	44.73	311	1.9	V	-64.15	2.86	12.90	-54.11	-13.00	-41.11
LTE BAND 66 Channel 132321										
223.12	58.20	185	1.2	H	-52.31	0.15	0.00	-52.46	-13.00	-39.46
223.12	57.98	94	2.2	V	-49.61	0.15	0.00	-49.76	-13.00	-36.76
1420.00	65.95	347	2.0	H	-45.59	2.37	12.50	-35.46	-13.00	-22.46
1420.00	59.98	190	1.7	V	-49.83	2.37	12.50	-39.70	-13.00	-26.70
2130.00	53.58	326	1.2	H	-56.03	2.86	12.90	-45.99	-13.00	-32.99
2130.00	44.73	228	1.5	V	-64.15	2.86	12.90	-54.11	-13.00	-41.11
LTE BAND 66 Channel 132664										
223.12	57.84	326	1.1	H	-52.67	0.15	0.00	-52.82	-13.00	-39.82
223.12	57.74	256	1.4	V	-49.85	0.15	0.00	-50.00	-13.00	-37.00
1427.00	65.95	231	1.2	H	-45.59	2.37	12.50	-35.46	-13.00	-22.46
1427.00	59.98	21	1.6	V	-49.83	2.37	12.50	-39.70	-13.00	-26.70
2140.50	53.58	8	1.6	H	-56.03	2.86	12.90	-45.99	-13.00	-32.99
2140.50	44.73	79	1.1	V	-64.15	2.86	12.90	-54.11	-13.00	-41.11

LTE Band 71

Frequency	Receiver Reading	Turn table Angle	RX Antenna		Substituted			Absolute Level	Result	
			Height	Polar	SG Level	Cable	Antenna Gain		Limit	Margin
(MHz)	(dBμV)	Degree	(m)	(H/V)	(dBm)	(dB)	(dB)	(dBm)	(dBm)	(dB)
LTE BAND 71 Channel 133147										
223.12	41.64	73	1.7	H	-68.87	0.15	0.00	-69.02	-13.00	-56.02
223.12	44.54	257	1.3	V	-63.05	0.15	0.00	-63.20	-13.00	-50.20
1331.00	66.43	93	1.0	H	-47.54	0.30	9.40	-38.44	-13.00	-25.44
1331.00	58.23	17	1.4	V	-55.30	0.30	9.40	-46.20	-13.00	-33.20
1996.50	58.83	190	1.9	H	-55.17	0.43	10.60	-45.00	-13.00	-32.00
1996.50	48.45	101	1.5	V	-61.83	0.43	10.60	-51.66	-13.00	-38.66
LTE BAND 71 Channel 133297										
223.12	41.43	130	1.5	H	-69.08	0.15	0.00	-69.23	-13.00	-56.23
223.12	45.65	107	1.7	V	-61.94	0.15	0.00	-62.09	-13.00	-49.09
1361.00	67.84	31	2.0	H	-46.13	0.30	9.40	-37.03	-13.00	-24.03
1361.00	58.32	205	1.7	V	-55.21	0.30	9.40	-46.11	-13.00	-33.11
2041.50	57.83	222	2.1	H	-56.17	0.43	10.60	-46.00	-13.00	-33.00
2041.50	48.14	178	1.6	V	-62.14	0.43	10.60	-51.97	-13.00	-38.97
LTE BAND 71 Channel 133447										
223.12	41.43	166	1.2	H	-69.08	0.15	0.00	-69.23	-13.00	-56.23
223.12	45.65	288	1.6	V	-61.94	0.15	0.00	-62.09	-13.00	-49.09
1391.00	67.84	307	2.1	H	-46.13	0.30	9.40	-37.03	-13.00	-24.03
1391.00	58.32	164	2.0	V	-55.21	0.30	9.40	-46.11	-13.00	-33.11
2086.50	57.83	243	1.3	H	-56.17	0.43	10.60	-46.00	-13.00	-33.00
2086.50	48.14	10	1.6	V	-62.14	0.43	10.60	-51.97	-13.00	-38.97

Note: 1) Absolute Level = SG Level - Cable loss + Antenna Gain

2) Margin = Absolute Level - Limit

12 Band Edge Measurement

Test Requirement:	FCC Part 2.1051, 22.917(a), 24.238(a), 27.53(h), 27.53(m)(4); 90.691
Test Method:	ANSI C63.26:2015 ANSI/TIA-603-E:2016
Test Mode:	TX transmitting

12.1 EUT Operation

Operating Environment :	
Temperature:	23.5 °C
Humidity:	52.3 % RH
Atmospheric Pressure:	101.3kPa

12.2 Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

According to FCC Part 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the TX transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


According to FCC Part 24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the TX transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to FCC Part 27.53(h), Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

According to FCC Part 27.53(m)(4), For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a

documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

The center of the spectrum analyzer was set to block edge frequency



12.3 Test Result

PASS

LTE Band

Please refer to the Annex E. LTE Band Edge for LTE Band 2/4/5/12/13/14/66/71.

13 FREQUENCY STABILITY

Test Requirement:	FCC Part 2.1055, 22.355, 24.235, 27.5(h),27.54; 90.691
Test Method:	ANSI C63.26:2015 ANSI/TIA-603-E:2016
Test Mode:	TX transmitting

13.1 EUT Operation


Operating Environment :	
Temperature:	22.9 °C
Humidity:	52.0 % RH
Atmospheric Pressure:	101.3kPa

13.2 Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



13.3 Test Result

LTE Band 2

Test Frequency:1880.0MHz QPSK 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	9	0.0048	2.5
40		7	0.0037	2.5
30		6	0.0032	2.5
20		1	0.0005	2.5
10		1	0.0005	2.5
0		-3	-0.0016	2.5
-10		3	0.0016	2.5
-20		2	0.0011	2.5
-30		-5	-0.0027	2.5
20	8.1	3	0.0016	2.5
20	9.9	-8	-0.0043	2.5

T Test Frequency:1880.0MHz 16QAM 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	3	0.0016	2.5
40		10	0.0053	2.5
30		16	0.0085	2.5
20		8	0.0043	2.5
10		5	0.0027	2.5
0		10	0.0053	2.5
-10		9	0.0048	2.5
-20		16	0.0085	2.5
-30		8	0.0043	2.5
20	8.1	14	0.0074	2.5
20	9.9	8	0.0043	2.5

LTE Band 2

Test Frequency:1880.0MHz QPSK 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	4	0.0021	2.5
40		12	0.0064	2.5
30		0	0.0000	2.5
20		6	0.0032	2.5
10		9	0.0048	2.5
0		8	0.0043	2.5
-10		-1	-0.0005	2.5
-20		8	0.0043	2.5
-30		11	0.0059	2.5
20	8.1	2	0.0011	2.5
20	9.9	14	0.0074	2.5

Test Frequency:1880.0MHz 16QAM 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	-1	-0.0005	2.5
40		2	0.0011	2.5
30		3	0.0016	2.5
20		5	0.0027	2.5
10		4	0.0021	2.5
0		12	0.0064	2.5
-10		-2	-0.0011	2.5
-20		13	0.0069	2.5
-30		4	0.0021	2.5
20	8.1	4	0.0021	2.5
20	9.9	1	0.0005	2.5

LTE Band 2

Test Frequency:1880.0MHz QPSK 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	-11	-0.0059	2.5
40		-11	-0.0059	2.5
30		-7	-0.0037	2.5
20		-2	-0.0011	2.5
10		-4	-0.0021	2.5
0		-5	-0.0027	2.5
-10		-5	-0.0027	2.5
-20		-6	-0.0032	2.5
-30		-3	-0.0016	2.5
20	8.1	-4	-0.0021	2.5
20	9.9	4	0.0021	2.5

Test Frequency:1880.0MHz 16QAM 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	-4	-0.0021	2.5
40		-3	-0.0016	2.5
30		-2	-0.0011	2.5
20		4	0.0021	2.5
10		8	0.0043	2.5
0		12	0.0064	2.5
-10		10	0.0053	2.5
-20		-3	-0.0016	2.5
-30		2	0.0011	2.5
20	8.1	13	0.0069	2.5
20	9.9	5	0.0027	2.5

LTE Band 2

Test Frequency:1880.0MHz QPSK 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	13	0.0069	2.5
40		-1	-0.0005	2.5
30		7	0.0037	2.5
20		5	0.0027	2.5
10		-2	-0.0011	2.5
0		10	0.0053	2.5
-10		3	0.0016	2.5
-20		9	0.0048	2.5
-30		5	0.0027	2.5
20	8.1	5	0.0027	2.5
20	9.9	3	0.0016	2.5

Test Frequency:1880.0MHz 16QAM 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	12	0.0064	2.5
40		1	0.0005	2.5
30		14	0.0074	2.5
20		6	0.0032	2.5
10		4	0.0021	2.5
0		4	0.0021	2.5
-10		0	0.0000	2.5
-20		4	0.0021	2.5
-30		8	0.0043	2.5
20	8.1	12	0.0064	2.5
20	9.9	11	0.0059	2.5

LTE Band 2

Test Frequency:1880.0MHz QPSK 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	18	0.0096	2.5
40		0	0.0000	2.5
30		17	0.0090	2.5
20		9	0.0048	2.5
10		6	0.0032	2.5
0		0	0.0000	2.5
-10		16	0.0085	2.5
-20		17	0.0090	2.5
-30		7	0.0037	2.5
20	8.1	7	0.0037	2.5
20	9.9	1	0.0005	2.5

Test Frequency:1880.0MHz 16QAM 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	14	0.0074	2.5
40		12	0.0064	2.5
30		9	0.0048	2.5
20		7	0.0037	2.5
10		-1	-0.0005	2.5
0		3	0.0016	2.5
-10		8	0.0043	2.5
-20		0	0.0000	2.5
-30		10	0.0053	2.5
20	8.1	13	0.0069	2.5
20	9.9	2	0.0011	2.5

LTE Band 2

Test Frequency:1880.0MHz QPSK 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	-7	-0.0037	2.5
40		-1	-0.0005	2.5
30		-8	-0.0043	2.5
20		-6	-0.0032	2.5
10		-14	-0.0074	2.5
0		1	0.0005	2.5
-10		-11	-0.0059	2.5
-20		-11	-0.0059	2.5
-30		-5	-0.0027	2.5
20	8.1	-9	-0.0048	2.5
20	9.9	-8	-0.0043	2.5

Test Frequency:1880.0MHz 16QAM 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	-12	-0.0064	2.5
40		0	0.0000	2.5
30		-8	-0.0043	2.5
20		-7	-0.0037	2.5
10		-8	-0.0043	2.5
0		-11	-0.0059	2.5
-10		-9	-0.0048	2.5
-20		1	0.0005	2.5
-30		-1	-0.0005	2.5
20	8.1	-6	-0.0032	2.5
20	9.9	-6	-0.0032	2.5

LTE Band 4

Test Frequency:1732.5MHz QPSK 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	17	0.0098	2.5
40		5	0.0029	2.5
30		16	0.0092	2.5
20		8	0.0046	2.5
10		0	0.0000	2.5
0		1	0.0006	2.5
-10		17	0.0098	2.5
-20		7	0.0040	2.5
-30		0	0.0000	2.5
20	8.1	9	0.0052	2.5
20	9.9	16	0.0092	2.5

Test Frequency:1732.5MHz 16QAM 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	11	0.0063	2.5
40		9	0.0052	2.5
30		10	0.0058	2.5
20		6	0.0035	2.5
10		-2	-0.0012	2.5
0		4	0.0023	2.5
-10		7	0.0040	2.5
-20		6	0.0035	2.5
-30		-3	-0.0017	2.5
20	8.1	-3	-0.0017	2.5
20	9.9	1	0.0006	2.5

LTE Band 4

Test Frequency:1732.5MHz QPSK 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	4	0.0023	2.5
40		10	0.0058	2.5
30		2	0.0012	2.5
20		2	0.0012	2.5
10		-5	-0.0029	2.5
0		6	0.0035	2.5
-10		3	0.0017	2.5
-20		5	0.0029	2.5
-30		7	0.0040	2.5
20	8.1	4	0.0023	2.5
20	9.9	-6	-0.0035	2.5

Test Frequency:1732.5MHz 16QAM 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	3	0.0017	2.5
40		13	0.0075	2.5
30		18	0.0104	2.5
20		9	0.0052	2.5
10		11	0.0063	2.5
0		12	0.0069	2.5
-10		1	0.0006	2.5
-20		10	0.0058	2.5
-30		7	0.0040	2.5
20	8.1	16	0.0092	2.5
20	9.9	4	0.0023	2.5

LTE Band 4

Test Frequency:1732.5MHz QPSK 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	-1	0.0041	2.5
40		0	0.0000	2.5
30		9	0.0052	2.5
20		-2	-0.0012	2.5
10		3	0.0017	2.5
0		6	0.0035	2.5
-10		7	0.0040	2.5
-20		2	0.0012	2.5
-30		10	0.0058	2.5
20	8.1	5	0.0029	2.5
20	9.9	0	0.0000	2.5

Test Frequency:1732.5MHz 16QAM 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	6	0.0035	2.5
40		12	0.0069	2.5
30		14	0.0081	2.5
20		8	0.0046	2.5
10		9	0.0052	2.5
0		16	0.0092	2.5
-10		11	0.0063	2.5
-20		7	0.0040	2.5
-30		7	0.0040	2.5
20	8.1	-1	-0.0006	2.5
20	9.9	8	0.0046	2.5

LTE Band 4

Test Frequency:1732.5MHz QPSK 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	-3	-0.0017	2.5
40		6	0.0035	2.5
30		-3	-0.0017	2.5
20		5	0.0029	2.5
10		1	0.0006	2.5
0		0	0.0000	2.5
-10		6	0.0035	2.5
-20		11	0.0063	2.5
-30		11	0.0063	2.5
20	8.1	11	0.0063	2.5
20	9.9	7	0.0040	2.5

Test Frequency:1732.5MHz 16QAM 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	5	0.0029	2.5
40		-5	-0.0029	2.5
30		7	0.0040	2.5
20		1	0.0006	2.5
10		0	0.0000	2.5
0		4	0.0023	2.5
-10		-7	-0.0040	2.5
-20		-3	-0.0017	2.5
-30		2	0.0012	2.5
20	8.1	8	0.0046	2.5
20	9.9	6	0.0035	2.5

LTE Band 4

Test Frequency:1732.5MHz QPSK 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	16	0.0092	2.5
40		0	0.0000	2.5
30		5	0.0029	2.5
20		8	0.0046	2.5
10		1	0.0006	2.5
0		5	0.0029	2.5
-10		7	0.0040	2.5
-20		12	0.0069	2.5
-30		14	0.0081	2.5
20	8.1	6	0.0035	2.5
20	9.9	10	0.0058	2.5

Test Frequency:1732.5MHz 16QAM 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	1	0.0006	2.5
40		-5	-0.0029	2.5
30		-9	-0.0052	2.5
20		-3	-0.0017	2.5
10		-5	-0.0029	2.5
0		-6	-0.0035	2.5
-10		-3	-0.0017	2.5
-20		-4	-0.0023	2.5
-30		4	0.0023	2.5
20	8.1	-6	-0.0035	2.5
20	9.9	-6	-0.0035	2.5

LTE Band 4

Test Frequency:1732.5MHz QPSK 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	-11	-0.0063	2.5
40		-13	-0.0075	2.5
30		-1	-0.0006	2.5
20		-4	-0.0023	2.5
10		-11	-0.0063	2.5
0		-4	-0.0023	2.5
-10		-12	-0.0069	2.5
-20		2	0.0012	2.5
-30		3	0.0017	2.5
20	8.1	3	0.0017	2.5
20	9.9	-7	-0.0040	2.5

Test Frequency:1732.5MHz 16QAM 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	-5	-0.0029	2.5
40		0	0.0000	2.5
30		-2	-0.0012	2.5
20		-5	-0.0029	2.5
10		-7	-0.0040	2.5
0		-9	-0.0052	2.5
-10		-4	-0.0023	2.5
-20		-13	-0.0075	2.5
-30		-2	-0.0012	2.5
20	8.1	-9	-0.0052	2.5
20	9.9	-10	-0.0058	2.5

LTE Band 5

Test Frequency:836.5MHz QPSK 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	-2	-0.0024	2.5
40		-4	-0.0048	2.5
30		8	0.0096	2.5
20		1	0.0012	2.5
10		-3	-0.0036	2.5
0		3	0.0036	2.5
-10		4	0.0048	2.5
-20		-2	-0.0024	2.5
-30		5	0.0060	2.5
20	8.1	3	0.0036	2.5
20	9.9	2	0.0024	2.5

Test Frequency:836.5MHz 16QAM 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	4	0.0048	2.5
40		4	0.0048	2.5
30		1	0.0012	2.5
20		6	0.0072	2.5
10		-2	-0.0024	2.5
0		9	0.0108	2.5
-10		15	0.0179	2.5
-20		6	0.0072	2.5
-30		10	0.0120	2.5
20	8.1	9	0.0108	2.5
20	9.9	6	0.0072	2.5

LTE Band 5

Test Frequency:836.5MHz QPSK 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	7	0.0084	2.5
40		-1	-0.0012	2.5
30		5	0.0060	2.5
20		4	0.0048	2.5
10		9	0.0108	2.5
0		-1	-0.0012	2.5
-10		13	0.0155	2.5
-20		-4	-0.0048	2.5
-30		-4	-0.0048	2.5
20	8.1	5	0.0060	2.5
20	9.9	-2	-0.0024	2.5

Test Frequency:836.5MHz 16QAM 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	-4	-0.0048	2.5
40		5	0.0060	2.5
30		-4	-0.0048	2.5
20		4	0.0048	2.5
10		10	0.0120	2.5
0		-3	-0.0036	2.5
-10		-4	-0.0048	2.5
-20		-5	-0.0060	2.5
-30		1	0.0012	2.5
20	8.1	3	0.0036	2.5
20	9.9	7	0.0084	2.5

LTE Band 5

Test Frequency:836.5MHz QPSK 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	7	0.0084	2.5
40		7	0.0084	2.5
30		12	0.0143	2.5
20		7	0.0084	2.5
10		11	0.0132	2.5
0		5	0.0060	2.5
-10		5	0.0060	2.5
-20		13	0.0155	2.5
-30		1	0.0012	2.5
20	8.1	12	0.0143	2.5
20	9.9	4	0.0048	2.5

Test Frequency:836.5MHz 16QAM 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	-2	-0.0024	2.5
40		11	0.0132	2.5
30		1	0.0012	2.5
20		6	0.0072	2.5
10		11	0.0132	2.5
0		2	0.0024	2.5
-10		0	0.0000	2.5
-20		-3	-0.0036	2.5
-30		1	0.0012	2.5
20	8.1	13	0.0155	2.5
20	9.9	3	0.0036	2.5

LTE Band 5

Test Frequency:836.5MHz QPSK 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	7	0.0084	2.5
40		11	0.0132	2.5
30		16	0.0191	2.5
20		7	0.0084	2.5
10		4	0.0048	2.5
0		0	0.0000	2.5
-10		9	0.0108	2.5
-20		11	0.0132	2.5
-30		0	0.0000	2.5
20	8.1	-2	-0.0024	2.5
20	9.9	16	0.0191	2.5

Test Frequency:836.5MHz 16QAM 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	3	0.0036	2.5
40		14	0.0167	2.5
30		12	0.0143	2.5
20		8	0.0096	2.5
10		12	0.0143	2.5
0		10	0.0120	2.5
-10		2	0.0024	2.5
-20		11	0.0132	2.5
-30		6	0.0072	2.5
20	8.1	7	0.0084	2.5
20	9.9	14	0.0167	2.5

LTE Band 12

Test Frequency:707.5MHz QPSK 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	1	0.0004	2.5
40		7	0.0028	2.5
30		10	0.0039	2.5
20		1	0.0004	2.5
10		7	0.0028	2.5
0		7	0.0028	2.5
-10		5	0.0020	2.5
-20		-8	-0.0032	2.5
-30		-4	-0.0016	2.5
20	8.1	7	0.0028	2.5
20	9.9	-4	-0.0016	2.5

Test Frequency:707.5MHz 16QAM 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	4	0.0016	2.5
40		0	0.0000	2.5
30		-5	-0.0020	2.5
20		3	0.0012	2.5
10		11	0.0043	2.5
0		-5	-0.0020	2.5
-10		4	0.0016	2.5
-20		-4	-0.0016	2.5
-30		11	0.0043	2.5
20	8.1	-5	-0.0020	2.5
20	9.9	9	0.0036	2.5

LTE Band 12

Test Frequency:707.5MHz QPSK 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	-6	-0.0072	2.5
40		-8	-0.0096	2.5
30		-6	-0.0072	2.5
20		-1	-0.0012	2.5
10		7	0.0084	2.5
0		0	0.0000	2.5
-10		-4	-0.0048	2.5
-20		4	0.0048	2.5
-30		-8	-0.0096	2.5
20	8.1	-7	-0.0084	2.5
20	9.9	5	0.0060	2.5

Test Frequency:707.5MHz 16QAM 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	7	0.0084	2.5
40		0	0.0000	2.5
30		-2	-0.0024	2.5
20		5	0.0060	2.5
10		-3	-0.0036	2.5
0		6	0.0072	2.5
-10		0	0.0000	2.5
-20		5	0.0060	2.5
-30		9	0.0108	2.5
20	8.1	0	0.0000	2.5
20	9.9	-3	-0.0036	2.5

LTE Band 12

Test Frequency:707.5MHz QPSK 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	10	0.0039	2.5
40		-6	-0.0024	2.5
30		11	0.0043	2.5
20		3	0.0012	2.5
10		6	0.0024	2.5
0		-2	-0.0008	2.5
-10		12	0.0047	2.5
-20		9	0.0036	2.5
-30		4	0.0016	2.5
20	8.1	-5	-0.0020	2.5
20	9.9	10	0.0039	2.5

Test Frequency:707.5MHz 16QAM 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	6	0.0024	2.5
40		-3	-0.0012	2.5
30		2	0.0008	2.5
20		3	0.0012	2.5
10		-2	-0.0008	2.5
0		11	0.0043	2.5
-10		-1	-0.0004	2.5
-20		4	0.0016	2.5
-30		11	0.0043	2.5
20	8.1	-4	-0.0016	2.5
20	9.9	-5	-0.0020	2.5

LTE Band 13

Test Frequency: 782.0MHz QPSK 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	1	0.0012	2.5
40		-7	-0.0084	2.5
30		-2	-0.0024	2.5
20		2	0.0024	2.5
10		3	0.0036	2.5
0		-5	-0.0060	2.5
-10		-2	-0.0024	2.5
-20		4	0.0048	2.5
-30		-1	-0.0012	2.5
20	8.1	3	0.0036	2.5
20	9.9	-3	-0.0036	2.5

Test Frequency: 782.0MHz 16QAM 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	1	0.0012	2.5
40		-8	-0.0096	2.5
30		6	0.0072	2.5
20		-2	-0.0024	2.5
10		5	0.0060	2.5
0		-1	-0.0012	2.5
-10		-4	-0.0048	2.5
-20		-10	-0.0120	2.5
-30		-6	-0.0072	2.5
20	8.1	-10	-0.0120	2.5
20	9.9	-1	-0.0012	2.5

LTE Band 13

Test Frequency: 782.0MHz QPSK 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	13	0.0155	2.5
40		14	0.0167	2.5
30		0	0.0000	2.5
20		5	0.0060	2.5
10		-1	-0.0012	2.5
0		7	0.0084	2.5
-10		5	0.0060	2.5
-20		9	0.0108	2.5
-30		11	0.0131	2.5
20	8.1	8	0.0096	2.5
20	9.9	-1	-0.0012	2.5

Test Frequency: 782.0MHz 16QAM 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	3	0.0012	2.5
40		4	0.0016	2.5
30		13	0.0051	2.5
20		8	0.0032	2.5
10		4	0.0016	2.5
0		17	0.0067	2.5
-10		3	0.0012	2.5
-20		0	0.0000	2.5
-30		10	0.0039	2.5
20	8.1	12	0.0047	2.5
20	9.9	7	0.0028	2.5

LTE Band 14

Test Frequency: 793.0MHz QPSK 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	11	0.0132	2.5
40		8	0.0096	2.5
30		11	0.0132	2.5
20		6	0.0072	2.5
10		4	0.0048	2.5
0		3	0.0036	2.5
-10		-1	-0.0012	2.5
-20		0	0.0000	2.5
-30		11	0.0132	2.5
20	8.1	0	0.0000	2.5
20	9.9	4	0.0048	2.5

Test Frequency: 793.0MHz 16QAM 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	5	0.0020	2.5
40		1	0.0004	2.5
30		0	0.0000	2.5
20		5	0.0020	2.5
10		5	0.0020	2.5
0		0	0.0000	2.5
-10		1	0.0004	2.5
-20		0	0.0000	2.5
-30		1	0.0004	2.5
20	8.1	13	0.0051	2.5
20	9.9	-1	-0.0004	2.5

LTE Band 14

Test Frequency: 793.0MHz QPSK 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	3	0.0012	2.5
40		10	0.0039	2.5
30		17	0.0067	2.5
20		8	0.0032	2.5
10		1	0.0004	2.5
0		1	0.0004	2.5
-10		15	0.0059	2.5
-20		14	0.0055	2.5
-30		7	0.0028	2.5
20	8.1	3	0.0012	2.5
20	9.9	1	0.0004	2.5

Test Frequency: 793.0MHz 16QAM 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	6	0.0072	2.5
40		1	0.0012	2.5
30		8	0.0096	2.5
20		8	0.0096	2.5
10		3	0.0036	2.5
0		10	0.0120	2.5
-10		14	0.0167	2.5
-20		12	0.0143	2.5
-30		14	0.0167	2.5
20	8.1	5	0.0060	2.5
20	9.9	11	0.0132	2.5

LTE Band 66

Test Frequency:1744.9MHz QPSK 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.8	14	0.0167	2.5
40		4	0.0048	2.5
30		13	0.0155	2.5
20		9	0.0108	2.5
10		17	0.0203	2.5
0		2	0.0024	2.5
-10		7	0.0084	2.5
-20		3	0.0036	2.5
-30		9	0.0108	2.5
20	3.3	5	0.0060	2.5
20	4.2	15	0.0179	2.5

T Test Frequency:1744.9MHz 16QAM 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.8	3	0.0016	2.5
40		11	0.0059	2.5
30		3	0.0016	2.5
20		7	0.0037	2.5
10		5	0.0027	2.5
0		8	0.0043	2.5
-10		3	0.0016	2.5
-20		11	0.0059	2.5
-30		14	0.0074	2.5
20	3.3	0	0.0000	2.5
20	4.2	0	0.0000	2.5

LTE Band 66

Test Frequency:1744.9MHz QPSK 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.8	14	0.0167	2.5
40		7	0.0084	2.5
30		2	0.0024	2.5
20		7	0.0084	2.5
10		10	0.0120	2.5
0		1	0.0012	2.5
-10		11	0.0132	2.5
-20		0	0.0000	2.5
-30		10	0.0120	2.5
20	3.3	9	0.0108	2.5
20	4.2	13	0.0155	2.5

Test Frequency:1744.9MHz 16QAM 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.8	10	0.0053	2.5
40		-4	-0.0021	2.5
30		5	0.0027	2.5
20		2	0.0011	2.5
10		4	0.0021	2.5
0		11	0.0059	2.5
-10		10	0.0053	2.5
-20		1	0.0005	2.5
-30		2	0.0011	2.5
20	3.3	9	0.0048	2.5
20	4.2	2	0.0011	2.5

LTE Band 66

Test Frequency:1744.9MHz QPSK 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.8	5	0.0027	2.5
40		9	0.0048	2.5
30		9	0.0048	2.5
20		8	0.0037	2.5
10		10	0.0053	2.5
0		1	0.0005	2.5
-10		-2	-0.0011	2.5
-20		2	0.0011	2.5
-30		14	0.0074	2.5
20	3.3	-1	-0.0005	2.5
20	4.2	1	0.0005	2.5

Test Frequency:1744.9MHz 16QAM 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.8	3	0.0016	2.5
40		-4	-0.0021	2.5
30		-1	-0.0005	2.5
20		-3	-0.0021	2.5
10		1	0.0005	2.5
0		-4	-0.0021	2.5
-10		-6	-0.0032	2.5
-20		4	0.0021	2.5
-30		1	0.0005	2.5
20	3.3	-12	-0.0064	2.5
20	4.2	5	0.0027	2.5

LTE Band 66

Test Frequency:1744.9MHz QPSK 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.8	4	0.0021	2.5
40		-6	-0.0032	2.5
30		0	0.0000	2.5
20		4	0.0011	2.5
10		10	0.0053	2.5
0		-4	-0.0021	2.5
-10		5	0.0027	2.5
-20		2	0.0011	2.5
-30		8	0.0043	2.5
20	3.3	-4	-0.0021	2.5
20	4.2	4	0.0021	2.5

Test Frequency:1744.9MHz 16QAM 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.8	15	0.0080	2.5
40		9	0.0048	2.5
30		3	0.0016	2.5
20		7	0.0037	2.5
10		-1	-0.0005	2.5
0		-2	-0.0011	2.5
-10		4	0.0021	2.5
-20		10	0.0053	2.5
-30		0	0.0000	2.5
20	3.3	0	0.0000	2.5
20	4.2	6	0.0032	2.5

LTE Band 66

Test Frequency:1744.9MHz QPSK 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.8	9	0.0048	2.5
40		-2	-0.0011	2.5
30		3	0.0016	2.5
20		2	0.0011	2.5
10		-3	-0.0016	2.5
0		10	0.0053	2.5
-10		2	0.0011	2.5
-20		4	0.0021	2.5
-30		5	0.0027	2.5
20	3.3	4	0.0021	2.5
20	4.2	-4	-0.0021	2.5

Test Frequency:1744.9MHz 16QAM 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.8	-7	-0.0037	2.5
40		-1	-0.0005	2.5
30		-4	-0.0021	2.5
20		1	0.0005	2.5
10		-3	-0.0016	2.5
0		3	0.0016	2.5
-10		0	0.0000	2.5
-20		-6	-0.0032	2.5
-30		-3	-0.0016	2.5
20	3.3	6	0.0032	2.5
20	4.2	-8	-0.0043	2.5

LTE Band 66

Test Frequency:1744.9MHz QPSK 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.8	9	0.0108	2.5
40		-3	-0.0036	2.5
30		13	0.0155	2.5
20		5	0.0060	2.5
10		7	0.0084	2.5
0		4	0.0048	2.5
-10		2	0.0024	2.5
-20		9	0.0108	2.5
-30		7	0.0084	2.5
20	3.3	1	0.0012	2.5
20	4.2	-4	-0.0048	2.5

Test Frequency:1744.9MHz 16QAM 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.8	7	0.0037	2.5
40		-3	-0.0016	2.5
30		7	0.0037	2.5
20		0	0.0000	2.5
10		5	0.0027	2.5
0		-4	-0.0021	2.5
-10		-3	-0.0016	2.5
-20		8	0.0043	2.5
-30		1	0.0005	2.5
20	3.3	8	0.0043	2.5
20	4.2	5	0.0027	2.5

LTE Band 71

Test Frequency:680.5MHz QPSK 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	10	0.0120	2.5
40		6	0.0072	2.5
30		14	0.0167	2.5
20		7	0.0084	2.5
10		1	0.0012	2.5
0		1	0.0012	2.5
-10		-1	-0.0012	2.5
-20		6	0.0072	2.5
-30		14	0.0167	2.5
20	8.1	7	0.0084	2.5
20	9.9	6	0.0072	2.5

Test Frequency:680.5MHz 16QAM 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	13	0.0051	2.5
40		13	0.0051	2.5
30		-1	-0.0004	2.5
20		6	0.0024	2.5
10		2	0.0008	2.5
0		7	0.0028	2.5
-10		14	0.0055	2.5
-20		3	0.0012	2.5
-30		13	0.0051	2.5
20	8.1	13	0.0051	2.5
20	9.9	6	0.0024	2.5

LTE Band 71

Test Frequency: 680.5MHz QPSK 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	1	0.0004	2.5
40		7	0.0028	2.5
30		10	0.0039	2.5
20		1	0.0004	2.5
10		7	0.0028	2.5
0		7	0.0028	2.5
-10		5	0.0020	2.5
-20		-8	-0.0032	2.5
-30		-4	-0.0016	2.5
20	8.1	7	0.0028	2.5
20	9.9	-4	-0.0016	2.5

Test Frequency: 680.5MHz 16QAM 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	1	0.0004	2.5
40		11	0.0043	2.5
30		4	0.0016	2.5
20		4	0.0016	2.5
10		7	0.0028	2.5
0		7	0.0028	2.5
-10		-1	-0.0004	2.5
-20		11	0.0043	2.5
-30		-4	-0.0016	2.5
20	8.1	5	0.0020	2.5
20	9.9	2	0.0008	2.5

LTE Band 71

Test Frequency:680.5MHz QPSK 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	4	0.0016	2.5
40		4	0.0016	2.5
30		0	0.0000	2.5
20		3	0.0012	2.5
10		4	0.0016	2.5
0		6	0.0024	2.5
-10		7	0.0028	2.5
-20		1	0.0004	2.5
-30		6	0.0024	2.5
20	8.1	-5	-0.0020	2.5
20	9.9	9	0.0036	2.5

Test Frequency:680.5MHz 16QAM 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	3	0.0012	2.5
40		8	0.0032	2.5
30		5	0.0020	2.5
20		6	0.0024	2.5
10		-1	-0.0004	2.5
0		13	0.0051	2.5
-10		6	0.0024	2.5
-20		-1	-0.0004	2.5
-30		12	0.0047	2.5
20	8.1	5	0.0020	2.5
20	9.9	14	0.0055	2.5

LTE Band 71

Test Frequency:680.5MHz QPSK 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	10	0.0039	2.5
40		-6	-0.0024	2.5
30		11	0.0043	2.5
20		3	0.0012	2.5
10		6	0.0024	2.5
0		-2	-0.0008	2.5
-10		12	0.0047	2.5
-20		9	0.0036	2.5
-30		4	0.0016	2.5
20	8.1	-5	-0.0020	2.5
20	9.9	10	0.0039	2.5

Test Frequency:680.5MHz 16QAM 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	9	9	0.0036	2.5
40		6	0.0024	2.5
30		15	0.0059	2.5
20		8	0.0032	2.5
10		2	0.0008	2.5
0		11	0.0043	2.5
-10		10	0.0039	2.5
-20		1	0.0004	2.5
-30		7	0.0028	2.5
20	8.1	10	0.0039	2.5
20	9.9	0	0.0000	2.5

14 RF Exposure

Remark: refer to MPE test report: WTD23D03064187W003.

15 Photographs of test setup and EUT.

Note: Please refer to appendix: Appendix- R4G-Photos.

===== End of Report =====