TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: **47 CFR FCC Part 15, Subpart C (Section 15.247)**

Report No.: RFBAYG-WTW-P23080102-2

FCC ID: 2BAGA010011

Product: Charging Case

Brand: OZLO

Model No.: 010011

Received Date: 2023/8/4

Test Date: 2023/9/23 ~ 2023/12/26

Issued Date: 2024/1/17

Applicant: Drowsy Digital Inc

Address: 850 New Burton Road Suite 201 19904 Dover Delaware United States 19904

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

FCC Registration / Designation Number: 198487 / TW2021

Approved by: Jeremy Lin , **Date:** 2024/1/17

Jeremy Lin / Project Engineer

This test report consists of 61 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Annie Chang / Senior Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record **4**

1 Certificate **5**

2 Summary of Test Results **6**

2.1 Measurement Uncertainty 6
2.2 Supplementary Information 6

3 General Information **7**

3.1 General Description 7
3.2 Antenna Description of EUT 7
3.3 Channel List 8
3.4 Test Mode Applicability and Tested Channel Detail 9
3.5 Duty Cycle of Test Signal 10
3.6 Test Program Used and Operation Descriptions 11
3.7 Connection Diagram of EUT and Peripheral Devices 11
3.8 Configuration of Peripheral Devices and Cable Connections 14

4 Test Instruments **15**

4.1 RF Output Power 15
4.2 Power Spectral Density 15
4.3 6 dB Bandwidth 15
4.4 Conducted Out of Band Emissions 15
4.5 AC Power Conducted Emissions 16
4.6 Unwanted Emissions below 1 GHz 17
4.7 Unwanted Emissions above 1 GHz 18

5 Limits of Test Items **19**

5.1 RF Output Power 19
5.2 Power Spectral Density 19
5.3 6 dB Bandwidth 19
5.4 Conducted Out of Band Emissions 19
5.5 AC Power Conducted Emissions 19
5.6 Unwanted Emissions below 1 GHz 19
5.7 Unwanted Emissions above 1 GHz 20

6 Test Arrangements **21**

6.1 RF Output Power 21
6.1.1 Test Setup 21
6.1.2 Test Procedure 21
6.2 Power Spectral Density 21
6.2.1 Test Setup 21
6.2.2 Test Procedure 21
6.3 6 dB Bandwidth 22
6.3.1 Test Setup 22
6.3.2 Test Procedure 22
6.4 Conducted Out of Band Emissions 22
6.4.1 Test Setup 22
6.4.2 Test Procedure 22
6.5 AC Power Conducted Emissions 23
6.5.1 Test Setup 23
6.5.2 Test Procedure 23
6.6 Unwanted Emissions below 1 GHz 24
6.6.1 Test Setup 24
6.6.2 Test Procedure 25
6.7 Unwanted Emissions above 1 GHz 26
6.7.1 Test Setup 26
6.7.2 Test Procedure 26

7 Test Results of Test Item **27**

7.1 RF Output Power 27
7.2 Power Spectral Density 28
7.3 6 dB Bandwidth 29
7.4 Conducted Out of Band Emissions 30
7.5 AC Power Conducted Emissions 32
7.6 Unwanted Emissions below 1 GHz 48
7.7 Unwanted Emissions above 1 GHz 50

8 Pictures of Test Arrangements 60

9 Information of the Testing Laboratories 61

Release Control Record

Issue No.	Description	Date Issued
RFBAYG-WTW-P23080102-2	Original release.	2024/1/17

1 Certificate

Product:	Charging Case
Brand:	OZLO
Test Model:	010011
Sample Status:	Engineering sample
Applicant:	Drowsy Digital Inc
Test Date:	2023/9/23 ~ 2023/12/26
Standard:	47 CFR FCC Part 15, Subpart C (Section 15.247)
Measurement procedure:	ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
Standard / Clause	Test Item	Result	Remark
15.247(b)	RF Output Power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement of limit.
15.247(d)	Conducted Out of Band Emissions	Pass	Meet the requirement of limit.
15.207	AC Power Conducted Emissions	Pass	Minimum passing margin is -7.44 dB at 0.56258 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -9.3 dB at 36.40 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -0.2 dB at 2483.50 MHz
15.203	Antenna Requirement	Pass	No antenna connector is used.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Specification	Uncertainty (±)
RF Output Power	-	1.1 dB
Power Spectral Density	-	1.2 dB
6 dB Bandwidth	-	960 Hz
Conducted Out of Band Emissions	9 kHz ~ 40 GHz	2.63 dB
AC Power Conducted Emissions	9 kHz ~ 30 MHz	2.88 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	2.38 dB
	30 MHz ~ 1 GHz	5.7 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 6 GHz	4.83 dB
	6 GHz ~ 18 GHz	5.37 dB
	18 GHz ~ 40 GHz	5.24 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description

Product	Charging Case
Brand	OZLO
Test Model	010011
Status of EUT	Engineering sample
Power Supply Rating	5Vdc form Type C port or 3.85Vdc from battery
Modulation Type	GFSK
Modulation Technology	DTS
Transfer Rate	Up to 2 Mbps
Operating Frequency	2.402 GHz ~ 2.48 GHz
Number of Channel	40
Output Power	16.331 mW (12.13 dBm)

Note:

1. The EUT uses following accessory.

Item	Specification
USB A to USB C cable	Shielded without core, 1.0m

2. The EUT has built-in two RF Chips as the following:

RF Chip	Model
1	QCC5141
2	NxH3675

3. Simultaneously transmission condition.

Condition	Technology	
1	BT-EDR (QCC5141)	BT-LE (NxH3675)
2	BT-LE (QCC5141)	BT-LE (NxH3675)

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 Antenna Description of EUT

The antenna information is listed as below.

Antenna No.	Gain (dBi)	Antenna Type	Connector Type
Antenna for NXH Chip (Ant 0)	0.5	LDS	N/A
Antenna for QCC Chip (Ant 1)	2	LDS	N/A
Note: The maximum gain was chosen for test.			

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

3.3 Channel List

40 channels are provided for BT-LE:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. EUT can be used in the following ways: XYZ 3-axis. Pre-scan in these ways and find the worst case as a representative test condition. 2. For Unwanted Emission below/above 1G has A~L mode. Pre-scan these modes and find the worst case as a representative test condition.
Worst Case:	1. X/ Y/ Z Worst Condition: X Axis for Unwanted Emission above 1GHz and Unwanted Emission below 1GHz. 2. For Unwanted Emission below/above 1G: Mode A is the worst test configuration.

Following channel(s) was (were) selected for the final test as listed below:

Test Item	EUT Configure Mode	Mode	Tested Channel	Modulation	Data Rate Parameter
RF Output Power / Power Spectral Density	A	BT-LE 1M	0, 19, 39	GFSK	1Mb/s
		BT-LE 2M	0, 19, 39	GFSK	2Mb/s
6 dB Bandwidth / Conducted Out of Band Emissions	A	BT-LE 1M	0, 19, 39	GFSK	1Mb/s
		BT-LE 2M	0, 19, 39	GFSK	2Mb/s
AC Power Conducted Emissions	A	BT-LE 1M	19	GFSK	1Mb/s
	B	BT-LE 1M	19	GFSK	1Mb/s
	C	BT-LE 1M	19	GFSK	1Mb/s
	D	BT-LE 1M	19	GFSK	1Mb/s
	E	BT-LE 1M	19	GFSK	1Mb/s
	F	BT-LE 1M	19	GFSK	1Mb/s
	G	BT-LE 1M	19	GFSK	1Mb/s
	H	BT-LE 1M	19	GFSK	1Mb/s
Unwanted Emissions below 1 GHz	A	BT-LE 1M	19	GFSK	1Mb/s
Unwanted Emissions above 1 GHz	A	BT-LE 1M	0, 19, 39	GFSK	1Mb/s
		BT-LE 2M	0, 19, 39	GFSK	2Mb/s
EUT Configure Mode:	A	Right+Left side earphone charging (Powered from Notebook)			
	B	Charger Case only (Powered from Notebook)			
	C	Left side earphone charging (Powered from Notebook)			
	D	Right side earphone charging (Powered from Notebook)			
	E	Right+Left side earphone charging (Powered from Adapter)			
	F	Charger Case only (Powered from Adapter)			
	G	Left side earphone charging (Powered from Adapter)			
	H	Right side earphone charging (Powered from Adapter)			
	I	Right+Left side earphone charging (Powered from internal Battery)			
	J	Right side earphone charging (Powered from internal Battery)			
	K	Left side earphone charging (Powered from internal Battery)			
	L	Charger Case only (Powered from internal Battery)			
Note : RF Chip_NxH3675					

3.5 Duty Cycle of Test Signal

BT-LE 1M: Duty cycle = 0.404 ms / 0.624 ms x 100% = 64.7%, duty factor = 10 * log (1/Duty cycle) = 1.89 dB
BT-LE 2M: Duty cycle = 1.092 ms / 1.874 ms x 100% = 58.3%, duty factor = 10 * log (1/Duty cycle) = 2.35 dB



BT-LE 1M



BT-LE 2M

3.6 Test Program Used and Operation Descriptions

Controlling software (cmd v10.0.19045.3803) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

3.7 Connection Diagram of EUT and Peripheral Devices

Mode A



Mode B



Mode C


(D) Left earphone
EUT
(A) NB
(1)
Type C
(2)
(B) NB Adapter

Mode D


(E) Right earphone
EUT
(A) NB
(1)
Type C
(2)
(B) NB Adapter

Mode E



Mode F



Mode G



Mode H



3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	NB	LENOVO	IdeaPad 5 15ITL05	N/A	N/A	Provided by Lab
B	NB Adapter	LENOVO	ADLX65CLGU2A	N/A	N/A	Provided by Lab
C	Adapter	APPLE	A1385	N/A	N/A	Provided by Lab
D	Left earphone	OZLO	010011L	N/A	2BAGA010011L	Supplied by applicant
E	Right earphone	OZLO	010011R	N/A	2BAGA010011R	Supplied by applicant

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	USB A to USB C cable	1	1	Y	0	Supplied by applicant
2	DC cable	1	1.8	N	0	Provided by Lab

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Power Meter Anritsu	ML2495A	0842014	2023/5/5	2024/5/4
Pulse Power Sensor Anritsu	MA2411B	0738404	2023/5/5	2024/5/4
USB Wideband Power Sensor Keysight	U2021XA	U2021XA_001	2023/6/6	2024/6/5

Notes:

1. The test was performed in LK - Oven
2. Tested Date: 2023/12/26

4.2 Power Spectral Density

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
PXA Signal Analyzer Keysight	N9030A	MY54490260	2023/7/13	2024/7/12
Signal Analyzer R&S	FSV40	101042	2023/9/5	2024/9/4
		101544	2023/5/9	2024/5/8
Software	ADT_RF Test Software V6.6.5.4	N/A	N/A	N/A

Notes:

1. The test was performed in LK - Oven
2. Tested Date: 2023/12/26

4.3 6 dB Bandwidth

Refer to section 4.2 to get information of the instruments.

4.4 Conducted Out of Band Emissions

Refer to section 4.2 to get information of the instruments.

4.5 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance LYNICS	0900510	E1-01-305	2023/2/13	2024/2/12
		E1-011285	2023/9/21	2024/9/20
		E1-011286	2023/9/21	2024/9/20
EMI Test Receiver R&S	ESCS 30	100276	2023/4/20	2024/4/19
	ESR3	102412	2022/12/21	2023/12/20
Fixed Attenuator STI	STI02-2200-10	NO.4	2023/9/1	2024/8/31
High Voltage Probe Schwarzbeck	TK9420	00982	2023/12/11	2024/12/10
LISN R&S	ENV216	101197	2023/7/12	2024/7/11
LISN Schwarzbeck	NNLK 8121	8121-731	2023/6/9	2024/6/8
		8121-808	2023/5/2	2024/5/1
	NNLK 8129	8129229	2023/6/27	2024/6/26
	NSLK 8128	8128-244	2023/11/10	2024/11/9
RF Coaxial Cable PEWC	5D-FB	Cable-CO5-01	2023/1/19	2024/1/18
Software BVADT	Cond_V7.3.7.4	N/A	N/A	N/A

Notes:

1. The test was performed in Linkou Conduction 5.
2. Tested Date: 2023/12/12

4.6 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Bi_Log Antenna Schwarzbeck	VULB 9168	137	2022/10/21	2023/10/20
Coupling / Decoupling Network Schwarzbeck	CDNE-M2	00097	2023/5/25	2024/5/24
	CDNE-M3	00091	2023/5/25	2024/5/24
Loop Antenna EMCI	LPA600	270	2023/9/4	2024/9/3
MXE EMI Receiver Agilent	N9038A	MY51210129	2023/3/24	2024/3/23
		MY51210137	2023/6/5	2024/6/4
Preamplifier EMCI	EMC001340	980269	2023/6/27	2024/6/26
Preamplifier HP	8447D	2432A03504	2023/2/16	2024/2/15
RF Coaxial Cable Pacific	8D-FB	Cable-CH6-02	2023/6/27	2024/6/26
Signal Analyzer R&S	FSV40	101544	2023/5/9	2024/5/8
Software BVADT	Radiated_V8.7.08	N/A	N/A	N/A
Tower ADT	AT100	0306	N/A	N/A
Turn Table ADT	TT100	0306	N/A	N/A

Notes:

1. The test was performed in Linkou 966 Chamber 6 (CH 6).
2. Tested Date: 2023/9/23

4.7 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Band Pass Filter Micro-Tronics	BRM17690	005	2023/5/25	2024/5/24
Boresight antenna tower fixture BV	BAF-02	6	N/A	N/A
High Pass Filter Wainwright	WHK 3.1/18G-10SS	SN 8	2023/5/25	2024/5/24
Horn Antenna EMCO	3115	00028257	2023/11/12	2024/11/11
Horn Antenna ETS-Lindgren	3117-PA	00215857	2023/11/12	2024/11/11
Horn Antenna Schwarzbeck	BBHA 9170	212	2023/10/16	2024/10/15
		BBHA9170241	2023/10/16	2024/10/15
MXE EMI Receiver Agilent	N9038A	MY51210129	2023/3/24	2024/3/23
		MY51210137	2023/6/5	2024/6/4
Notch Filter Micro-Tronics	BRC50703-01	010	2023/5/25	2024/5/24
Preamplifier EMCI	EMC0126545	980076	2023/2/16	2024/2/15
	EMC184045B	980175	2023/9/2	2024/9/1
		980235	2023/2/16	2024/2/15
Preamplifier HP	8449B	3008A01201	2023/2/16	2024/2/15
RF Coaxial Cable EMCI	EMC102-KM-KM-1000	200310	2023/3/12	2024/3/11
	EMC104	190801	2023/9/13	2024/9/12
		190804	2023/9/13	2024/9/12
RF Coaxial Cable HUBER+SUHNER	SF-104	Cable-CH6-01	2023/9/13	2024/9/12
Signal Analyzer R&S	FSV40	101042	2023/9/5	2024/9/4
		101544	2023/5/9	2024/5/8
Software BVADT	Radiated_V7.7.1.1.1	N/A	N/A	N/A
Tower ADT	AT100	0306	N/A	N/A
Turn Table ADT	TT100	0306	N/A	N/A

Notes:

1. The test was performed in Linkou 966 Chamber 6 (CH 6).
2. Tested Date: 2023/12/5 ~ 2023/12/6

5 Limits of Test Items

5.1 RF Output Power

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

5.2 Power Spectral Density

The Maximum of Power Spectral Density Measurement is 8 dBm in any 3 kHz.

5.3 6 dB Bandwidth

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

5.4 Conducted Out of Band Emissions

Below 20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

5.5 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.6 Unwanted Emissions below 1 GHz

Radiated emissions up to 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.7 Unwanted Emissions above 1 GHz

Radiated emissions above 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

6 Test Arrangements

6.1 RF Output Power

6.1.1 Test Setup



6.1.2 Test Procedure

Peak Power:
A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average Power:
Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

6.2 Power Spectral Density

6.2.1 Test Setup



6.2.2 Test Procedure

a. Set analyzer center frequency to DTS channel center frequency.
b. Set the span to 1.5 times the DTS bandwidth.
c. Set the RBW to: 3 kHz.
d. Set the VBW ≥ 3 × RBW.
e. Detector = peak.
f. Sweep time = auto couple.
g. Trace mode = max hold.
h. Allow trace to fully stabilize.
i. Use the peak marker function to determine the maximum amplitude level within the RBW.

6.3 6 dB Bandwidth

6.3.1 Test Setup



6.3.2 Test Procedure

a. Set resolution bandwidth (RBW) = 100 kHz.
b. Set the video bandwidth (VBW) ≥ 3 x RBW, Detector = Peak.
c. Trace mode = max hold.
d. Sweep = auto couple.
e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.4 Conducted Out of Band Emissions

6.4.1 Test Setup



6.4.2 Test Procedure

MEASUREMENT PROCEDURE REF

a. Set the RBW = 100 kHz.
b. Set the VBW ≥ 300 kHz.
c. Detector = peak.
d. Sweep time = auto couple.
e. Trace mode = max hold.
f. Allow trace to fully stabilize.
g. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

a. Set RBW = 100 kHz.
b. Set VBW ≥ 300 kHz.
c. Detector = peak.
d. Sweep = auto couple.
e. Trace Mode = max hold.
f. Allow trace to fully stabilize.
g. Use the peak marker function to determine the maximum amplitude level.

6.5 AC Power Conducted Emissions

6.5.1 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.5.2 Test Procedure

a. The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.

6.6 Unwanted Emissions below 1 GHz

6.6.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.6.2 Test Procedure

For Radiated emission below 30 MHz

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

6.7 Unwanted Emissions above 1 GHz

6.7.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.2 Test Procedure

a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver/spectrum analyzer was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

1. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
2. For harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98%) or 10 Hz (Duty cycle ≥ 98%) for Average detection (AV) at frequency above 1 GHz.
3. All modes of operation were investigated and the worst-case emissions are reported.

7 Test Results of Test Item

7.1 RF Output Power

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 76% RH	Tested By:	Dalen Dai

For Peak Power

BT-LE 1M

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
0	2402	14.388	11.58	30	Pass
19	2440	16.331	12.13	30	Pass
39	2480	15.704	11.96	30	Pass

Note: The antenna gain is 2 dBi < 6 dBi, so the output power limit shall not be reduced.

BT-LE 2M

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
0	2402	13.709	11.37	30	Pass
19	2440	15.631	11.94	30	Pass
39	2480	15.136	11.80	30	Pass

Note: The antenna gain is 2 dBi < 6 dBi, so the output power limit shall not be reduced.

For Average Power

BT-LE 1M

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	4.406	6.44
19	2440	4.808	6.82
39	2480	4.786	6.80

BT-LE 2M

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	4.256	6.29
19	2440	4.645	6.67
39	2480	4.56	6.59

7.2 Power Spectral Density

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 76% RH	Tested By:	Dalen Dai

BT-LE 1M

Channel	Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
0	2402	-6.72	8	Pass
19	2440	-6.07	8	Pass
39	2480	-7.05	8	Pass

Note: The antenna gain is 2 dBi < 6 dBi, so the power density limit shall not be reduced.

BT-LE 2M

Channel	Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
0	2402	-7.05	8	Pass
19	2440	-7.98	8	Pass
39	2480	-8.32	8	Pass

Note: The antenna gain is 2 dBi < 6 dBi, so the power density limit shall not be reduced.

Spectrum Plot of Maximum Value



BT-LE 1M : CH 19



BT-LE 2M : CH 0

7.3 6 dB Bandwidth

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 76% RH	Tested By:	Dalen Dai

BT-LE 1M

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
0	2402	0.73	0.5	Pass
19	2440	0.75	0.5	Pass
39	2480	0.72	0.5	Pass

BT-LE 2M

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
0	2402	1.27	0.5	Pass
19	2440	1.29	0.5	Pass
39	2480	1.31	0.5	Pass

Spectrum Plot of Minimum Value



BT-LE 1M : CH 39



BT-LE 2M : CH 0

7.4 Conducted Out of Band Emissions

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 76% RH	Tested By:	Dalen Dai

BT-LE 1M



CH 0



CH 0



CH 19



CH 19



CH 39



CH 39



CH 0 Band edge



CH 39 Band edge

BT-LE 2M



CH 0



CH 0



CH 19



CH 19



CH 39



CH 39



CH 0 Band edge



CH 39 Band edge

7.5 AC Power Conducted Emissions

Mode A

RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15719	10.01	37.32	20.47	47.33	30.48	65.61	55.61	-18.28	-25.13
2	0.21565	10.07	30.31	10.86	40.38	20.93	62.98	52.98	-22.60	-32.05
3	0.53911	10.09	31.28	24.40	41.37	34.49	56.00	46.00	-14.63	-11.51
4	1.33304	10.11	16.70	8.56	26.81	18.67	56.00	46.00	-29.19	-27.33
5	3.58396	10.18	22.99	11.49	33.17	21.67	56.00	46.00	-22.83	-24.33
6	12.26664	10.41	14.12	8.97	24.53	19.38	60.00	50.00	-35.47	-30.62

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.00	39.94	11.26	49.94	21.26	66.00	56.00	-16.06	-34.74
2	0.22431	10.07	33.39	12.34	43.46	22.41	62.66	52.66	-19.20	-30.25
3	**0.56258**	**10.09**	**34.02**	**28.47**	**44.11**	**38.56**	**56.00**	**46.00**	**-11.89**	**-7.44**
4	1.13358	10.11	25.67	16.95	35.78	27.06	56.00	46.00	-20.22	-18.94
5	3.81079	10.19	26.56	15.84	36.75	26.03	56.00	46.00	-19.25	-19.97
6	10.05692	10.36	19.68	13.57	30.04	23.93	60.00	50.00	-29.96	-26.07

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



Mode B

RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15719	10.01	38.27	16.58	48.28	26.59	65.61	55.61	-17.33	-29.02
2	0.22024	10.07	29.21	9.85	39.28	19.92	62.81	52.81	-23.53	-32.89
3	0.53805	10.09	31.30	25.47	41.39	35.56	56.00	46.00	-14.61	-10.44
4	1.24698	10.11	17.29	10.34	27.40	20.45	56.00	46.00	-28.60	-25.55
5	3.79906	10.19	26.92	14.91	37.11	25.10	56.00	46.00	-18.89	-20.90
6	14.90656	10.46	14.71	10.14	25.17	20.60	60.00	50.00	-34.83	-29.40

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18122	10.05	35.58	16.26	45.63	26.31	64.43	54.43	-18.80	-28.12
2	0.56258	10.09	30.01	22.87	40.10	32.96	56.00	46.00	-15.90	-13.04
3	0.87546	10.10	24.44	18.02	34.54	28.12	56.00	46.00	-21.46	-17.88
4	1.24309	10.11	22.27	16.06	32.38	26.17	56.00	46.00	-23.62	-19.83
5	3.77559	10.19	23.32	12.23	33.51	22.42	56.00	46.00	-22.49	-23.58
6	9.59151	10.35	16.00	10.16	26.35	20.51	60.00	50.00	-33.65	-29.49

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value

Mode C

RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16173	10.02	38.61	21.21	48.63	31.23	65.37	55.37	-16.74	-24.14
2	0.35337	10.08	21.20	8.66	31.28	18.74	58.88	48.88	-27.60	-30.14
3	0.53805	10.09	31.68	23.89	41.77	33.98	56.00	46.00	-14.23	-12.02
4	1.82192	10.10	15.49	8.23	25.59	18.33	56.00	46.00	-30.41	-27.67
5	3.84599	10.19	25.89	14.33	36.08	24.52	56.00	46.00	-19.92	-21.48
6	12.43872	10.42	14.87	9.73	25.29	20.15	60.00	50.00	-34.71	-29.85

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17283	10.03	35.83	20.08	45.86	30.11	64.82	54.82	-18.96	-24.71
2	0.33382	10.08	25.30	16.21	35.38	26.29	59.36	49.36	-23.98	-23.07
3	0.53663	10.09	30.72	22.41	40.81	32.50	56.00	46.00	-15.19	-13.50
4	1.00452	10.11	20.30	12.41	30.41	22.52	56.00	46.00	-25.59	-23.48
5	3.69346	10.18	22.33	11.84	32.51	22.02	56.00	46.00	-23.49	-23.98
6	9.77533	10.35	13.23	8.42	23.58	18.77	60.00	50.00	-36.42	-31.23

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value

Mode D

RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16173	10.02	37.32	19.86	47.34	29.88	65.37	55.37	-18.03	-25.49
2	0.26733	10.07	25.76	17.56	35.83	27.63	61.20	51.20	-25.37	-23.57
3	0.54302	10.09	31.03	23.80	41.12	33.89	56.00	46.00	-14.88	-12.11
4	1.32913	10.11	15.13	8.13	25.24	18.24	56.00	46.00	-30.76	-27.76
5	3.85772	10.19	22.89	11.28	33.08	21.47	56.00	46.00	-22.92	-24.53
6	15.15687	10.47	11.31	6.96	21.78	17.43	60.00	50.00	-38.22	-32.57

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value

RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16173	10.02	37.18	21.39	47.20	31.41	65.37	55.37	-18.17	-23.96
2	0.30644	10.08	26.11	16.48	36.19	26.56	60.07	50.07	-23.88	-23.51
3	0.53805	10.09	30.55	22.24	40.64	32.33	56.00	46.00	-15.36	-13.67
4	1.20789	10.11	22.33	15.57	32.44	25.68	56.00	46.00	-23.56	-20.32
5	3.75604	10.19	24.54	13.83	34.73	24.02	56.00	46.00	-21.27	-21.98
6	7.71423	10.30	14.50	8.48	24.80	18.78	60.00	50.00	-35.20	-31.22

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



Mode E

RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16181	10.02	26.40	6.08	36.42	16.10	65.37	55.37	-28.95	-39.27
2	0.26276	10.07	23.99	13.33	34.06	23.40	61.34	51.34	-27.28	-27.94
3	0.64533	10.09	21.43	12.77	31.52	22.86	56.00	46.00	-24.48	-23.14
4	0.80097	10.10	24.35	14.26	34.45	24.36	56.00	46.00	-21.55	-21.64
5	1.45037	10.11	11.97	6.35	22.08	16.46	56.00	46.00	-33.92	-29.54
6	5.51625	10.24	13.48	6.71	23.72	16.95	60.00	50.00	-36.28	-33.05

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16526	10.02	26.71	8.45	36.73	18.47	65.20	55.20	-28.47	-36.73
2	0.28689	10.07	22.78	12.10	32.85	22.17	60.61	50.61	-27.76	-28.44
3	0.64862	10.09	22.81	13.80	32.90	23.89	56.00	46.00	-23.10	-22.11
4	0.80506	10.10	22.97	16.73	33.07	26.83	56.00	46.00	-22.93	-19.17
5	1.45037	10.11	11.64	5.76	21.75	15.87	56.00	46.00	-34.25	-30.13
6	4.59299	10.22	13.00	4.94	23.22	15.16	56.00	46.00	-32.78	-30.84

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



Mode F

RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16526	10.02	26.53	5.69	36.55	15.71	65.20	55.20	-28.65	-39.49
2	0.26342	10.07	24.39	13.52	34.46	23.59	61.32	51.32	-26.86	-27.73
3	0.64703	10.09	22.25	13.43	32.34	23.52	56.00	46.00	-23.66	-22.48
4	0.78550	10.10	22.52	16.22	32.62	26.32	56.00	46.00	-23.38	-19.68
5	1.44255	10.11	12.52	7.07	22.63	17.18	56.00	46.00	-33.37	-28.82
6	6.49791	10.27	15.78	9.82	26.05	20.09	60.00	50.00	-33.95	-29.91

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16139	10.02	27.08	7.79	37.10	17.81	65.39	55.39	-28.29	-37.58
2	0.25933	10.07	25.09	15.59	35.16	25.66	61.45	51.45	-26.29	-25.79
3	0.64862	10.09	23.27	15.43	33.36	25.52	56.00	46.00	-22.64	-20.48
4	0.75387	10.10	23.69	16.86	33.79	26.96	56.00	46.00	-22.21	-19.04
5	1.48166	10.11	13.72	7.21	23.83	17.32	56.00	46.00	-32.17	-28.68
6	6.51747	10.27	14.99	9.02	25.26	19.29	60.00	50.00	-34.74	-30.71

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



Mode G

RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16096	10.02	26.38	7.19	36.40	17.21	65.41	55.41	-29.01	-38.20
2	0.26733	10.07	25.21	16.94	35.28	27.01	61.20	51.20	-25.92	-24.19
3	0.67134	10.09	21.83	13.92	31.92	24.01	56.00	46.00	-24.08	-21.99
4	0.79675	10.10	21.73	14.44	31.83	24.54	56.00	46.00	-24.17	-21.46
5	1.49339	10.11	11.07	6.66	21.18	16.77	56.00	46.00	-34.82	-29.23
6	6.40796	10.27	15.24	7.29	25.51	17.56	60.00	50.00	-34.49	-32.44

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16526	10.02	25.60	6.69	35.62	16.71	65.20	55.20	-29.58	-38.49
2	0.25864	10.07	24.63	15.67	34.70	25.74	61.47	51.47	-26.77	-25.73
3	0.64862	10.09	22.34	13.36	32.43	23.45	56.00	46.00	-23.57	-22.55
4	0.79332	10.10	21.16	14.44	31.26	24.54	56.00	46.00	-24.74	-21.46
5	1.45671	10.11	11.65	5.83	21.76	15.94	56.00	46.00	-34.24	-30.06
6	7.53433	10.29	13.42	7.01	23.71	17.30	60.00	50.00	-36.29	-32.70

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



Mode H

RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16956	10.03	25.29	8.29	35.32	18.32	64.98	54.98	-29.66	-36.66
2	0.25796	10.07	25.58	15.76	35.65	25.83	61.50	51.50	-25.85	-25.67
3	0.67208	10.09	22.70	14.25	32.79	24.34	56.00	46.00	-23.21	-21.66
4	0.80506	10.10	21.89	14.85	31.99	24.95	56.00	46.00	-24.01	-21.05
5	1.48166	10.11	11.10	6.34	21.21	16.45	56.00	46.00	-34.79	-29.55
6	5.46932	10.24	14.44	8.66	24.68	18.90	60.00	50.00	-35.32	-31.10

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16956	10.03	26.04	10.49	36.07	20.52	64.98	54.98	-28.91	-34.46
2	0.26342	10.07	25.52	16.00	35.59	26.07	61.32	51.32	-25.73	-25.25
3	0.62906	10.09	22.31	14.01	32.40	24.10	56.00	46.00	-23.60	-21.90
4	0.78159	10.10	22.64	17.01	32.74	27.11	56.00	46.00	-23.26	-18.89
5	1.48383	10.11	11.88	6.74	21.99	16.85	56.00	46.00	-34.01	-29.15
6	6.46662	10.27	14.16	8.65	24.43	18.92	60.00	50.00	-35.57	-31.08

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



7.6 Unwanted Emissions below 1 GHz

RF Mode	BT-LE 1M	**Channel**	CH 19：2440 MHz
Frequency Range	30 MHz ~ 1 GHz	**Detector Function & Bandwidth**	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	**Environmental Conditions**	23°C, 69% RH
Tested By	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	36.89	23.4 QP	40.0	-16.6	1.58 H	38	33.5	-10.1
2	66.57	25.4 QP	40.0	-14.6	1.76 H	336	35.7	-10.3
3	208.67	25.9 QP	43.5	-17.6	1.49 H	69	36.8	-10.9
4	246.46	26.2 QP	46.0	-19.8	1.32 H	353	34.9	-8.7
5	376.87	22.3 QP	46.0	-23.7	1.05 H	93	27.0	-4.7
6	437.06	25.1 QP	46.0	-20.9	1.53 H	271	28.2	-3.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 69% RH
Tested By	Jed Wu		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	**36.40**	**30.7 QP**	**40.0**	**-9.3**	**1.43 V**	**360**	**40.8**	**-10.1**
2	141.31	19.8 QP	43.5	-23.7	1.52 V	1	28.8	-9.0
3	277.59	20.3 QP	46.0	-25.7	1.69 V	192	27.3	-7.0
4	354.71	22.2 QP	46.0	-23.8	1.38 V	58	27.6	-5.4
5	434.10	24.4 QP	46.0	-21.6	1.20 V	359	27.6	-3.2
6	510.54	26.9 QP	46.0	-19.1	1.17 V	213	28.6	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



7.7 Unwanted Emissions above 1 GHz

RF Mode	BT-LE 1M	**Channel**	CH 0：2402 MHz
Frequency Range	1 GHz ~ 25 GHz	**Detector Function & Bandwidth**	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	**Environmental Conditions**	25°C, 75% RH
Tested By	William Su		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	2390.00	58.0 PK	74.0	-16.0	1.29 H	292	59.2	-1.2
2	2390.00	51.2 AV	54.0	-2.8	1.29 H	292	52.4	-1.2
3	*2402.00	114.7 PK			1.29 H	292	115.9	-1.2
4	*2402.00	108.1 AV			1.29 H	292	109.3	-1.2
5	4804.00	48.6 PK	74.0	-25.4	1.68 H	251	40.6	8.0
6	4804.00	38.5 AV	54.0	-15.5	1.68 H	251	30.5	8.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	2390.00	53.9 PK	74.0	-20.1	1.19 V	46	55.1	-1.2
2	2390.00	45.4 AV	54.0	-8.6	1.19 V	46	46.6	-1.2
3	*2402.00	107.0 PK			1.19 V	46	108.2	-1.2
4	*2402.00	100.2 AV			1.19 V	46	101.4	-1.2
5	4804.00	47.6 PK	74.0	-26.4	2.57 V	184	39.6	8.0
6	4804.00	37.5 AV	54.0	-16.5	2.57 V	184	29.5	8.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	113.7 PK			1.12 H	288	114.7	-1.0
2	*2440.00	106.6 AV			1.12 H	288	107.6	-1.0
3	4880.00	48.5 PK	74.0	-25.5	1.72 H	253	40.6	7.9
4	4880.00	38.4 AV	54.0	-15.6	1.72 H	253	30.5	7.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	101.9 PK			1.50 V	227	102.9	-1.0
2	*2440.00	95.1 AV			1.50 V	227	96.1	-1.0
3	4880.00	47.0 PK	74.0	-27.0	2.52 V	184	39.1	7.9
4	4880.00	37.0 AV	54.0	-17.0	2.52 V	184	29.1	7.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 1M	Channel	CH 39：2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	112.5 PK			1.26 H	84	113.5	-1.0
2	*2480.00	105.6 AV			1.26 H	84	106.6	-1.0
3	2483.50	67.9 PK	74.0	-6.1	1.26 H	84	68.9	-1.0
4	**2483.50**	**53.8 AV**	**54.0**	**-0.2**	**1.26 H**	**84**	**54.8**	**-1.0**
5	4960.00	48.4 PK	74.0	-25.6	1.66 H	248	40.5	7.9
6	4960.00	38.3 AV	54.0	-15.7	1.66 H	248	30.4	7.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	98.4 PK			4.00 V	236	99.4	-1.0
2	*2480.00	91.6 AV			4.00 V	236	92.6	-1.0
3	2483.50	55.4 PK	74.0	-18.6	1.95 V	236	56.4	-1.0
4	2483.50	43.4 AV	54.0	-10.6	1.95 V	236	44.4	-1.0
5	4960.00	47.3 PK	74.0	-26.7	2.55 V	162	39.4	7.9
6	4960.00	37.2 AV	54.0	-16.8	2.55 V	162	29.3	7.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 2M	Channel	CH 0：2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.3 PK	74.0	-16.7	1.50 H	207	58.5	-1.2
2	2390.00	49.1 AV	54.0	-4.9	1.50 H	207	50.3	-1.2
3	*2402.00	114.6 PK			1.50 H	207	115.8	-1.2
4	*2402.00	106.2 AV			1.50 H	207	107.4	-1.2
5	4804.00	50.2 PK	74.0	-23.8	1.82 H	255	42.2	8.0
6	4804.00	39.6 AV	54.0	-14.4	1.82 H	255	31.6	8.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	53.4 PK	74.0	-20.6	1.50 V	39	54.6	-1.2
2	2390.00	44.6 AV	54.0	-9.4	1.50 V	39	45.8	-1.2
3	*2402.00	106.4 PK			1.50 V	39	107.6	-1.2
4	*2402.00	97.9 AV			1.50 V	39	99.1	-1.2
5	4804.00	49.2 PK	74.0	-24.8	2.55 V	175	41.2	8.0
6	4804.00	38.4 AV	54.0	-15.6	2.55 V	175	30.4	8.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 2M	**Channel**	CH 19：2440 MHz
Frequency Range	1 GHz ~ 25 GHz	**Detector Function & Bandwidth**	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	**Environmental Conditions**	25°C, 75% RH
Tested By	William Su		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	*2440.00	114.6 PK			1.15 H	289	115.6	-1.0
2	*2440.00	106.8 AV			1.15 H	289	107.8	-1.0
3	4880.00	50.4 PK	74.0	-23.6	1.85 H	251	42.5	7.9
4	4880.00	39.5 AV	54.0	-14.5	1.85 H	251	31.6	7.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	*2440.00	103.6 PK			4.00 V	45	104.6	-1.0
2	*2440.00	97.1 AV			4.00 V	45	98.1	-1.0
3	4880.00	48.7 PK	74.0	-25.3	2.55 V	169	40.8	7.9
4	4880.00	38.0 AV	54.0	-16.0	2.55 V	169	30.1	7.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 2M	Channel	CH 39：2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	25°C, 75% RH
Tested By	William Su		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	111.7 PK			1.25 H	89	112.7	-1.0
2	*2480.00	102.9 AV			1.25 H	89	103.9	-1.0
3	2483.50	67.9 PK	74.0	-6.1	1.25 H	89	68.9	-1.0
4	2483.50	51.2 AV	54.0	-2.8	1.25 H	89	52.2	-1.0
5	4960.00	50.0 PK	74.0	-24.0	1.66 H	245	42.1	7.9
6	4960.00	39.1 AV	54.0	-14.9	1.66 H	245	31.2	7.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	100.5 PK			3.81 V	152	101.5	-1.0
2	*2480.00	92.2 AV			3.81 V	152	93.2	-1.0
3	2483.50	56.7 PK	74.0	-17.3	3.81 V	152	57.7	-1.0
4	2483.50	43.8 AV	54.0	-10.2	3.81 V	152	44.8	-1.0
5	4960.00	49.1 PK	74.0	-24.9	2.61 V	184	41.2	7.9
6	4960.00	38.4 AV	54.0	-15.6	2.61 V	184	30.5	7.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

Plot of Band Edge

Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 kHz, DET=Peak

BT-LE 1M Channel 0



Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)

BT-LE 1M Channel 39



Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)

Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak

BT-LE 2M Channel 0



Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)

BT-LE 2M Channel 39



Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)

8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab
Tel: 886-3-6668565
Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@bureauveritas.com
Web Site: http://ee.bureauveritas.com.tw

The address and road map of all our labs can be found in our web site also.

--- END ---