

RF Exposure Evaluation Report

APPLICANT : Procon Analytics LLC
EQUIPMENT : Arrow-QI
BRAND NAME : Procon Analytics
MODEL NAME : 4-6360-20, 4-6360-17, 4-6361-20, 4-6361-17
FCC ID : 2BAH7AQI01
STANDARD : 47 CFR Part 2.1091
FCC KDB 447498 D01 v06

The product evaluation date was started from Aug. 27, 2025 and completed on Aug. 27, 2025. We, Sporton International Inc. (Kunshan), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang

Sporton International Inc. (Kunshan)

***No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China***



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	7
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	8
5.1. Standalone Power Density Calculation	8
5.2. Collocated Power Density Calculation.....	8



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA570110	Rev. 01	Initial issue of report.	Sep. 16, 2025



1. Administration Data

1.1. Testing Laboratory

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory			
Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-KS	CN1257	314309

Applicant	
Company Name	Procon Analytics LLC
Address	17361 Armstrong Avenue Irvine, CA 92614

Manufacturer	
Company Name	Procon Analytics LLC
Address	17361 Armstrong Avenue Irvine, CA 92614

2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Arrow-QI
Brand Name	Procon Analytics
Model Name	4-6360-20, 4-6360-17, 4-6361-20, 4-6361-17
FCC ID	2BAH7AQI01
Wireless Technology and Frequency Range	LTE Cat-M1: LTE Band 2 : 1850 MHz ~ 1910 MHz LTE Band 4 : 1710 MHz ~ 1755 MHz LTE Band 5 : 824 MHz ~ 849 MHz LTE Band 12 : 699 MHz ~ 716 MHz LTE Band 13 : 777 MHz ~ 787 MHz LTE Band 25 : 1850 MHz ~ 1915 MHz LTE Band 26 : 814 MHz ~ 849 MHz LTE Band 66 : 1710 MHz ~ 1780 MHz LTE Band 85: 698 MHz ~ 716 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	LTE: QPSK, 16QAM Bluetooth LE
Antenna Gain	LTE Band 2 : 3.64 dBi LTE Band 4 : 2.41 dBi LTE Band 5 : -0.35 dBi LTE Band 12 : 2.65 dBi LTE Band 13 : 1.74 dBi LTE Band 25 : 3.64 dBi LTE Band 26 : -0.35 dBi LTE Band 66: 2.50 dBi LTE Band 85: 2.65 dBi Bluetooth: 3.80 dBi
Antenna Type	WWAN: FPC Antenna Bluetooth: Chip Antenna
HW Version	V1.2
SW Version	BG95M1LAR05A01_01
EUT Stage	Production Unit

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT, the differences could be referred to the 4-6360-20, 4-6360-17, 4-6361-20, 4-6361-17_ Class II Permissive Change letter which is exhibit separately, and the differences do not affect the MPE analysis results.

Comments and Explanations:

1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.

3. Maximum RF average output tune up power among production units

<LTE>

Mode		Maximum Average power(dBm)
LTE Cat-M1	Band 2	23.00
	Band 4	23.00
	Band 5	23.00
	Band 12	23.00
	Band 13	23.00
	Band 25	23.00
	Band 26	23.00
	Band 66	23.00
	Band 85	23.00

<Bluetooth>

Mode		Maximum Average power(dBm)
Bluetooth	LE	4.79

4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna

5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power(dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit
CAT M1 Band 2	1850.7	3.64	23.00	26.640	0.461	461.318	0.092	1.000	0.092
CAT M1 Band 4	1710.7	2.41	23.00	25.410	0.348	347.536	0.069	1.000	0.069
CAT M1 Band 5	824.7	-0.35	23.00	22.650	0.184	184.077	0.037	0.550	0.067
CAT M1 Band 12	699.7	2.65	23.00	25.650	0.367	367.282	0.073	0.466	0.157
CAT M1 Band 13	779.5	1.74	23.00	24.740	0.298	297.852	0.059	0.520	0.114
CAT M1 Band 25	1850.7	3.64	23.00	26.640	0.461	461.318	0.092	1.000	0.092
CAT M1 Band 26	814.7	-0.35	23.00	22.650	0.184	184.077	0.037	0.543	0.067
CAT M1 Band 66	1710.7	2.50	23.00	25.500	0.355	354.813	0.071	1.000	0.071
CAT M1 Band 85	700.5	2.65	23.00	25.650	0.367	367.282	0.073	0.467	0.157
Bluetooth	2402.0	3.80	4.79	8.590	0.007	7.228	0.001	1.000	0.001

Note:

- For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
- Chose the maximum power to do MPE analysis.

5.2. Collocated Power Density Calculation

WWAN Power Density / Limit	Bluetooth Power Density / Limit	Σ (Power Density / Limit) of WWAN + Bluetooth
0.157	0.001	0.158

Note:

- For colocation analysis, LTE Band 85 is chosen for summation due to the highest (power density/limit) among all WWAN wireless modes.
- Σ (Power Density / Limit): This is a summation of [(power density for each transmitter/antenna included in the simultaneous transmission)/ (corresponding MPE limit)], for WWAN + Bluetooth.
- Considering all transmitter of the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1, and MPE of 2 collocated transmitters is compliant.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----